



PYTHON API Reference

Table of contents

| | |
|---|-----------|
| 1. Introduction | 1 |
| 2. Using the Yocto-Demo with Python | 3 |
| 2.1. Source files | 3 |
| 2.2. Dynamic library | 3 |
| 2.3. Control of the Led function | 3 |
| 2.4. Control of the module part | 5 |
| 2.5. Error handling | 7 |
| Blueprint | 10 |
| 3. Reference | 10 |
| 3.1. General functions | 11 |
| 3.2. Accelerometer function interface | 36 |
| 3.3. AnButton function interface | 82 |
| 3.4. CarbonDioxide function interface | 124 |
| 3.5. ColorLed function interface | 167 |
| 3.6. Compass function interface | 200 |
| 3.7. Current function interface | 244 |
| 3.8. DataLogger function interface | 287 |
| 3.9. Formatted data sequence | 322 |
| 3.10. Recorded data sequence | 332 |
| 3.11. Unformatted data sequence | 345 |
| 3.12. Digital IO function interface | 360 |
| 3.13. Display function interface | 408 |
| 3.14. DisplayLayer object interface | 459 |
| 3.15. External power supply control interface | 491 |
| 3.16. Files function interface | 520 |
| 3.17. GenericSensor function interface | 553 |
| 3.18. Gyroscope function interface | 603 |
| 3.19. Yocto-hub port interface | 658 |
| 3.20. Humidity function interface | 687 |
| 3.21. Led function interface | 730 |
| 3.22. LightSensor function interface | 761 |
| 3.23. Magnetometer function interface | 805 |
| 3.24. Measured value | 851 |

| | |
|--|-------------|
| 3.25. Module control interface | 857 |
| 3.26. Network function interface | 903 |
| 3.27. OS control | 964 |
| 3.28. Power function interface | 991 |
| 3.29. Pressure function interface | 1038 |
| 3.30. Pwm function interface | 1081 |
| 3.31. PwmPowerSource function interface | 1123 |
| 3.32. Quaternion interface | 1150 |
| 3.33. Real Time Clock function interface | 1193 |
| 3.34. Reference frame configuration | 1224 |
| 3.35. Relay function interface | 1264 |
| 3.36. Sensor function interface | 1304 |
| 3.37. Servo function interface | 1347 |
| 3.38. Temperature function interface | 1386 |
| 3.39. Tilt function interface | 1431 |
| 3.40. Voc function interface | 1474 |
| 3.41. Voltage function interface | 1517 |
| 3.42. Voltage source function interface | 1560 |
| 3.43. WakeUpMonitor function interface | 1596 |
| 3.44. WakeUpSchedule function interface | 1635 |
| 3.45. Watchdog function interface | 1676 |
| 3.46. Wireless function interface | 1725 |
| Index | 1759 |

1. Introduction

This manual is intended to be used as a reference for Yoctopuce Python library, in order to interface your code with USB sensors and controllers.

The next chapter is taken from the free USB device Yocto-Demo, in order to provide a concrete examples of how the library is used within a program.

The remaining part of the manual is a function-by-function, class-by-class documentation of the API. The first section describes all general-purpose global function, while the forthcoming sections describe the various classes that you may have to use depending on the Yoctopuce device being used. For more informations regarding the purpose and the usage of a given device attribute, please refer to the extended discussion provided in the device-specific user manual.

2. Using the Yocto-Demo with Python

Python is an interpreted object oriented language developed by Guido van Rossum. Among its advantages is the fact that it is free, and the fact that it is available for most platforms, Windows as well as UNIX. It is an ideal language to write small scripts on a napkin. The Yoctopuce library is compatible with Python 2.6+ and 3+. It works under Windows, Mac OS X, and Linux, Intel as well as ARM. The library was tested with Python 2.6 and Python 3.2. Python interpreters are available on the Python web site¹.

2.1. Source files

The Yoctopuce library classes² for Python that you will use are provided as source files. Copy all the content of the *Sources* directory in the directory of your choice and add this directory to the *PYTHONPATH* environment variable. If you use an IDE to program in Python, refer to its documentation to configure it so that it automatically finds the API source files.

2.2. Dynamic library

A section of the low-level library is written in C, but you should not need to interact directly with it: it is provided as a DLL under Windows, as a .so files under UNIX, and as a .dylib file under Mac OS X. Everything was done to ensure the simplest possible interaction from Python: the distinct versions of the dynamic library corresponding to the distinct operating systems and architectures are stored in the *cdll* directory. The API automatically loads the correct file during its initialization. You should not have to worry about it.

If you ever need to recompile the dynamic library, its complete source code is located in the Yoctopuce C++ library.

In order to keep them simple, all the examples provided in this documentation are console applications. Naturally, the libraries function in a strictly identical manner if you integrate them in an application with a graphical interface.

2.3. Control of the Led function

A few lines of code are enough to use a Yocto-Demo. Here is the skeleton of a Python code snippet to use the Led function.

¹ <http://www.python.org/download/>

² www.yoctopuce.com/EN/libraries.php

```
[...]
errmsg=YRefParam()
#Get access to your device, connected locally on USB for instance
YAPI.RegisterHub("usb",errmsg)
led = YLed.FindLed("YCTOPOC1-123456.led")

# Hot-plug is easy: just check that the device is online
if led.isOnline():
    #Use led.set_power()
    ...
[...]
```

Let's look at these lines in more details.

YAPI.RegisterHub

The `yAPI.RegisterHub` function initializes the Yoctopuce API and indicates where the modules should be looked for. When used with the parameter "`usb`", it will use the modules locally connected to the computer running the library. If the initialization does not succeed, this function returns a value different from `YAPI.SUCCESS` and `errmsg` contains the error message.

YLed.FindLed

The `YLed.FindLed` function allows you to find a led from the serial number of the module on which it resides and from its function name. You can use logical names as well, as long as you have initialized them. Let us imagine a Yocto-Demo module with serial number `YCTOPOC1-123456` which you have named "`MyModule`", and for which you have given the `led` function the name "`MyFunction`". The following five calls are strictly equivalent, as long as "`MyFunction`" is defined only once.

```
led = YLed.FindLed("YCTOPOC1-123456.led")
led = YLed.FindLed("YCTOPOC1-123456.MyFunction")
led = YLed.FindLed("MyModule.led")
led = YLed.FindLed("MyModule.MyFunction")
led = YLed.FindLed("MyFunction")
```

`YLed.FindLed` returns an object which you can then use at will to control the led.

isOnline

The `isOnline()` method of the object returned by `YLed.FindLed` allows you to know if the corresponding module is present and in working order.

set_power

The `set_power()` function of the objet returned by `YLed.FindLed` allows you to turn on and off the led. The argument is `YLed.POWER_ON` or `YLed.POWER_OFF`. In the reference on the programming interface, you will find more methods to precisely control the luminosity and make the led blink automatically.

A real example

Launch Python and open the corresponding sample script provided in the directory **Examples/Doc-GettingStarted-Yocto-Demo** of the Yoctopuce library.

In this example, you will recognize the functions explained above, but this time used with all side materials needed to make it work nicely as a small demo.

```
#!/usr/bin/python
# -*- coding: utf-8 -*-
import os,sys
from yocto_api import *
from yocto_led import *

def usage():
    scriptname = os.path.basename(sys.argv[0])
    print("Usage:")
```

```

print(scriptname+' <serial_number>')
print(scriptname+' <logical_name>')
print(scriptname+' any ')
sys.exit()

def die(msg):
    sys.exit(msg+' (check USB cable)')

def setLedState(led,state):
    if led.isOnline():
        if state :
            led.set_power(YLed.POWER_ON)
        else:
            led.set_power(YLed.POWER_OFF)
    else:
        print('Module not connected (check identification and USB cable)')

errmsg=YRefParam()

if len(sys.argv)<2 : usage()

target=sys.argv[1]

# Setup the API to use local USB devices
if YAPI.RegisterHub("usb", errmsg)!= YAPI.SUCCESS:
    sys.exit("init error"+errmsg.value)

if target=='any':
    # retreive any RGB led
    led = YLed.FirstLed()
    if led is None :
        die('No module connected')
else:
    led= YLed.FindLed(target + '.led')

if not(led.isOnline()):die('device not connected')

print('0: turn test led OFF')
print('1: turn test led ON')
print('x: exit')

try: input = raw_input # python 2.x fix
except: pass

c= input("command:")

while c!='x':
    if c=='0' : setLedState(led,False);
    elif c=='1' :setLedState(led,True);
    c= input("command:")

```

2.4. Control of the module part

Each module can be controlled in a similar manner, you can find below a simple sample program displaying the main parameters of the module and enabling you to activate the localization beacon.

```

#!/usr/bin/python
# -*- coding: utf-8 -*-
import os,sys
from yocto_api import *

def usage():
    sys.exit("usage: demo <serial or logical name> [ON/OFF]")

errmsg =YRefParam()
if YAPI.RegisterHub("usb", errmsg) != YAPI.SUCCESS:
    sys.exit("RegisterHub error: " + str(errmsg))

if len(sys.argv)<2 : usage()

m = YModule.FindModule(sys.argv[1]) ## use serial or logical name

```

```

if m.isOnline():
    if len(sys.argv) > 2:
        if sys.argv[2].upper() == "ON" : m.set_beacon(YModule.BEACON_ON)
        if sys.argv[2].upper() == "OFF" : m.set_beacon(YModule.BEACON_OFF)

    print("serial:      " + m.get_serialNumber())
    print("logical name: " + m.get_logicalName())
    print("luminosity:   " + str(m.get_luminosity()))
    if m.get_beacon() == YModule.BEACON_ON:
        print("beacon:      ON")
    else:
        print("beacon:      OFF")
    print("upTime:       " + str(m.get_upTime()/1000)+" sec")
    print("USB current:  " + str(m.get_usbCurrent())+" mA")
    print("logs:\n" + m.get_lastLogs())
else:
    print(sys.argv[1] + " not connected (check identification and USB cable)")

```

Each property `xxx` of the module can be read thanks to a method of type `YModule.get_xxxx()`, and properties which are not read-only can be modified with the help of the `YModule.set_xxx()` method. For more details regarding the used functions, refer to the API chapters.

Changing the module settings

When you want to modify the settings of a module, you only need to call the corresponding `YModule.set_xxx()` function. However, this modification is performed only in the random access memory (RAM) of the module: if the module is restarted, the modifications are lost. To memorize them persistently, it is necessary to ask the module to save its current configuration in its permanent memory. To do so, use the `YModule.saveToFlash()` method. Inversely, it is possible to force the module to forget its current settings by using the `YModule.revertFromFlash()` method. The short example below allows you to modify the logical name of a module.

```

#!/usr/bin/python
# -*- coding: utf-8 -*-
import os,sys
from yocto_api import *

def usage():
    sys.exit("usage: demo <serial or logical name> <new logical name>")

if len(sys.argv) != 3 : usage()

errormsg =YRefParam()
if YAPI.RegisterHub("usb", errormsg) != YAPI.SUCCESS:
    sys.exit("RegisterHub error: " + str(errormsg))

m = YModule.FindModule(sys.argv[1]) # use serial or logical name

if m.isOnline():
    newname = sys.argv[2]
    if not YAPI.CheckLogicalName(newname):
        sys.exit("Invalid name (" + newname + ")")
    m.set_logicalName(newname)
    m.saveToFlash() # do not forget this
    print ("Module: serial= " + m.get_serialNumber() + " / name= " + m.get_logicalName())
else:
    sys.exit("not connected (check identification and USB cable)")

```

Warning: the number of write cycles of the nonvolatile memory of the module is limited. When this limit is reached, nothing guarantees that the saving process is performed correctly. This limit, linked to the technology employed by the module micro-processor, is located at about 100000 cycles. In short, you can use the `YModule.saveToFlash()` function only 100000 times in the life of the module. Make sure you do not call this function within a loop.

List the modules

Obtaining the list of the connected modules is performed with the `YModule.yFirstModule()` function which returns the first module found. Then, you only need to call the `nextModule()` function of this object to find the following modules, and this as long as the returned value is not null. Below a short example listing the connected modules.

```
#!/usr/bin/python
# -*- coding: utf-8 -*-
import os,sys

from yocto_api import *

errmsg=YRefParam()

# Setup the API to use local USB devices
if YAPI.RegisterHub("usb", errmsg)!= YAPI.SUCCESS:
    sys.exit("init error"+str(errmsg))

print('Device list')

module = YModule.FirstModule()
while module is not None:
    print(module.get_serialNumber()+' ('+module.get_productName()+')')
    module = module.nextModule()
```

2.5. Error handling

When you implement a program which must interact with USB modules, you cannot disregard error handling. Inevitably, there will be a time when a user will have unplugged the device, either before running the software, or even while the software is running. The Yoctopuce library is designed to help you support this kind of behavior, but your code must nevertheless be conceived to interpret in the best possible way the errors indicated by the library.

The simplest way to work around the problem is the one used in the short examples provided in this chapter: before accessing a module, check that it is online with the `isOnline` function, and then hope that it will stay so during the fraction of a second necessary for the following code lines to run. This method is not perfect, but it can be sufficient in some cases. You must however be aware that you cannot completely exclude an error which would occur after the call to `isOnline` and which could crash the software. The only way to prevent this is to implement one of the two error handling techniques described below.

The method recommended by most programming languages for unpredictable error handling is the use of exceptions. By default, it is the behavior of the Yoctopuce library. If an error happens while you try to access a module, the library throws an exception. In this case, there are three possibilities:

- If your code catches the exception and handles it, everything goes well.
- If your program is running in debug mode, you can relatively easily determine where the problem happened and view the explanatory message linked to the exception.
- Otherwise... the exception makes your program crash, bang!

As this latest situation is not the most desirable, the Yoctopuce library offers another possibility for error handling, allowing you to create a robust program without needing to catch exceptions at every line of code. You simply need to call the `yDisableExceptions()` function to commute the library to a mode where exceptions for all the functions are systematically replaced by specific return values, which can be tested by the caller when necessary. For each function, the name of each return value in case of error is systematically documented in the library reference. The name always follows the same logic: a `get_state()` method returns a `Y_STATE_INVALID` value, a `get_currentValue` method returns a `Y_CURRENTVALUE_INVALID` value, and so on. In any case, the returned value is of the expected type and is not a null pointer which would risk crashing your program. At worst, if you display the value without testing it, it will be outside the expected bounds for the returned value. In the case of functions which do not normally return information, the return value is `YAPI_SUCCESS` if everything went well, and a different error code in case of failure.

When you work without exceptions, you can obtain an error code and an error message explaining the source of the error. You can request them from the object which returned the error, calling the `errType()` and `errMessage()` methods. Their returned values contain the same information as in the exceptions when they are active.

3. Reference

3.1. General functions

These general functions should be used to initialize and configure the Yoctopuce library. In most cases, a simple call to function `yRegisterHub()` should be enough. The module-specific functions `yFind...()` or `yFirst...()` should then be used to retrieve an object that provides interaction with the module.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_api.js'></script>
node.js var yoctolib = require('yoctolib');
var YAPI = yoctolib.YAPI;
var YModule = yoctolib.YModule;
php require_once('yocto_api.php');
cpp #include "yocto_api.h"
m #import "yocto_api.h"
pas uses yocto_api;
vb yocto_api.vb
cs yocto_api.cs
java import com.yoctopuce.YoctoAPI.YModule;
py from yocto_api import *

```

Global functions

`yCheckLogicalName(name)`

Checks if a given string is valid as logical name for a module or a function.

`yDisableExceptions()`

Disables the use of exceptions to report runtime errors.

`yEnableExceptions()`

Re-enables the use of exceptions for runtime error handling.

`yEnableUSBHost(osContext)`

This function is used only on Android.

`yFreeAPI()`

Frees dynamically allocated memory blocks used by the Yoctopuce library.

`yGetAPIVersion()`

Returns the version identifier for the Yoctopuce library in use.

`yGetTickCount()`

Returns the current value of a monotone millisecond-based time counter.

`yHandleEvents(errmsg)`

Maintains the device-to-library communication channel.

`yInitAPI(mode, errmsg)`

Initializes the Yoctopuce programming library explicitly.

`yPreregisterHub(url, errmsg)`

Fault-tolerant alternative to RegisterHub().

`yRegisterDeviceArrivalCallback(arrivalCallback)`

Register a callback function, to be called each time a device is plugged.

`yRegisterDeviceRemovalCallback(removalCallback)`

Register a callback function, to be called each time a device is unplugged.

`yRegisterHub(url, errmsg)`

Setup the Yoctopuce library to use modules connected on a given machine.

`yRegisterHubDiscoveryCallback(hubDiscoveryCallback)`

3. Reference

Register a callback function, to be called each time an Network Hub send an SSDP message.

yRegisterLogFunction(logfun)

Registers a log callback function.

ySelectArchitecture(arch)

Select the architecture or the library to be loaded to access to USB.

ySetDelegate(object)

(Objective-C only) Register an object that must follow the protocol YDeviceHotPlug.

ySetTimeout(callback, ms_timeout, arguments)

Invoke the specified callback function after a given timeout.

ySleep(ms_duration, errmsg)

Pauses the execution flow for a specified duration.

yTriggerHubDiscovery(errmsg)

Force a hub discovery, if a callback as been registered with yRegisterDeviceRemovalCallback it will be called for each net work hub that will respond to the discovery.

yUnregisterHub(url)

Setup the Yoctopuce library to no more use modules connected on a previously registered machine with RegisterHub.

yUpdateDeviceList(errmsg)

Triggers a (re)detection of connected Yoctopuce modules.

yUpdateDeviceList_async(callback, context)

Triggers a (re)detection of connected Yoctopuce modules.

YAPI.CheckLogicalName()**YAPI****yCheckLogicalName()YAPI.CheckLogicalName()**

Checks if a given string is valid as logical name for a module or a function.

| | |
|---------|---|
| js | function yCheckLogicalName(name) |
| node.js | function CheckLogicalName(name) |
| php | function yCheckLogicalName(\$name) |
| cpp | bool yCheckLogicalName(const string& name) |
| m | BOOL yCheckLogicalName(NSString * name) |
| pas | function yCheckLogicalName(name: string): boolean |
| vb | function yCheckLogicalName(ByVal name As String) As Boolean |
| cs | bool CheckLogicalName(string name) |
| java | boolean CheckLogicalName(String name) |
| py | def CheckLogicalName(name) |

A valid logical name has a maximum of 19 characters, all among A..Z, a..z, 0..9, _, and -. If you try to configure a logical name with an incorrect string, the invalid characters are ignored.

Parameters :

name a string containing the name to check.

Returns :

true if the name is valid, false otherwise.

YAPI.DisableExceptions()**YAPI****yDisableExceptions()YAPI.DisableExceptions()**

Disables the use of exceptions to report runtime errors.

| | |
|---------|--|
| js | function yDisableExceptions() |
| node.js | function DisableExceptions() |
| php | function yDisableExceptions() |
| cpp | void yDisableExceptions() |
| m | void yDisableExceptions() |
| pas | procedure yDisableExceptions() |
| vb | procedure yDisableExceptions() |
| cs | void DisableExceptions() |
| py | def DisableExceptions() |

When exceptions are disabled, every function returns a specific error value which depends on its type and which is documented in this reference manual.

YAPI.EnableExceptions()**YAPI****yEnableExceptions()YAPI.EnableExceptions()**

Re-enables the use of exceptions for runtime error handling.

```
js function yEnableExceptions( )
nodejs function EnableExceptions( )
php function yEnableExceptions( )
cpp void yEnableExceptions( )
m void yEnableExceptions( )
pas procedure yEnableExceptions( )
vb procedure yEnableExceptions( )
cs void EnableExceptions( )
py def EnableExceptions( )
```

Be aware than when exceptions are enabled, every function that fails triggers an exception. If the exception is not caught by the user code, it either fires the debugger or aborts (i.e. crash) the program. On failure, throws an exception or returns a negative error code.

YAPI.EnableUSBHost() yEnableUSBHost()

YAPI

This function is used only on Android.

```
java void EnableUSBHost( Object osContext)
```

Before calling `yRegisterHub("usb")` you need to activate the USB host port of the system. This function takes as argument, an object of class `android.content.Context` (or any subclass). It is not necessary to call this function to reach modules through the network.

Parameters :

osContext an object of class `android.content.Context` (or any subclass).

YAPI.FreeAPI() yFreeAPI()YAPI.FreeAPI()

YAPI

Frees dynamically allocated memory blocks used by the Yoctopuce library.

```
js function yFreeAPI( )
nodejs function FreeAPI( )
php function yFreeAPI( )
cpp void yFreeAPI( )
m void yFreeAPI( )
pas procedure yFreeAPI( )
vb procedure yFreeAPI( )
cs void FreeAPI( )
java void FreeAPI( )
py def FreeAPI( )
```

It is generally not required to call this function, unless you want to free all dynamically allocated memory blocks in order to track a memory leak for instance. You should not call any other library function after calling `yFreeAPI()`, or your program will crash.

YAPI.GetAPIVersion() yGetAPIVersion()YAPI.GetAPIVersion()

YAPI

Returns the version identifier for the Yoctopuce library in use.

| | |
|---------|---|
| js | function yGetAPIVersion() |
| node.js | function GetAPIVersion() |
| php | function yGetAPIVersion() |
| cpp | string yGetAPIVersion() |
| m | NSString* yGetAPIVersion() |
| pas | function yGetAPIVersion(): string |
| vb | function yGetAPIVersion() As String |
| cs | String GetAPIVersion() |
| java | String GetAPIVersion() |
| py | def GetAPIVersion() |

The version is a string in the form "Major.Minor.Build", for instance "1.01.5535". For languages using an external DLL (for instance C#, VisualBasic or Delphi), the character string includes as well the DLL version, for instance "1.01.5535 (1.01.5439)".

If you want to verify in your code that the library version is compatible with the version that you have used during development, verify that the major number is strictly equal and that the minor number is greater or equal. The build number is not relevant with respect to the library compatibility.

Returns :

a character string describing the library version.

YAPI.GetTickCount() yGetTickCount()YAPI.GetTickCount()

YAPI

Returns the current value of a monotone millisecond-based time counter.

```
js function yGetTickCount( )
nodejs function GetTickCount()
php function yGetTickCount( )
cpp u64 yGetTickCount( )
m u64 yGetTickCount( )
pas function yGetTickCount( ): u64
vb function yGetTickCount( ) As Long
cs ulong GetTickCount( )
java long GetTickCount( )
py def GetTickCount( )
```

This counter can be used to compute delays in relation with Yoctopuce devices, which also uses the millisecond as timebase.

Returns :
a long integer corresponding to the millisecond counter.

YAPI.HandleEvents() yHandleEvents()YAPI.HandleEvents()

YAPI

Maintains the device-to-library communication channel.

```
js function yHandleEvents( errmsg)
node.js function HandleEvents( errmsg)
php function yHandleEvents( &$errmsg)
cpp YRETCODE yHandleEvents( string& errmsg)
m YRETCODE yHandleEvents( NSError** errmsg)
pas function yHandleEvents( var errmsg: string): integer
vb function yHandleEvents( ByRef errmsg As String) As YRETCODE
cs YRETCODE HandleEvents( ref string errmsg)
java int HandleEvents( )
py def HandleEvents( errmsg=None)
```

If your program includes significant loops, you may want to include a call to this function to make sure that the library takes care of the information pushed by the modules on the communication channels. This is not strictly necessary, but it may improve the reactivity of the library for the following commands.

This function may signal an error in case there is a communication problem while contacting a module.

Parameters :

errmsg a string passed by reference to receive any error message.

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

YAPI.InitAPI() yInitAPI()YAPI.InitAPI()

YAPI

Initializes the Yoctopuce programming library explicitly.

| | |
|--------|---|
| js | function yInitAPI(mode, errmsg) |
| nodejs | function InitAPI(mode, errmsg) |
| php | function yInitAPI(\$mode, &\$errmsg) |
| cpp | YRETCODE yInitAPI(int mode, string& errmsg) |
| m | YRETCODE yInitAPI(int mode, NSError** errmsg) |
| pas | function yInitAPI(mode: integer, var errmsg: string): integer |
| vb | function yInitAPI(ByVal mode As Integer, ByRef errmsg As String) As Integer |
| cs | int InitAPI(int mode, ref string errmsg) |
| java | int InitAPI(int mode) |
| py | def InitAPI(mode, errmsg=None) |

It is not strictly needed to call `yInitAPI()`, as the library is automatically initialized when calling `yRegisterHub()` for the first time.

When `Y_DETECT_NONE` is used as detection mode, you must explicitly use `yRegisterHub()` to point the API to the VirtualHub on which your devices are connected before trying to access them.

Parameters :

mode an integer corresponding to the type of automatic device detection to use. Possible values are `Y_DETECT_NONE`, `Y_DETECT_USB`, `Y_DETECT_NET`, and `Y_DETECT_ALL`.
errmsg a string passed by reference to receive any error message.

Returns :

`YAPI_SUCCESS` when the call succeeds. On failure, throws an exception or returns a negative error code.

YAPI.PreregisterHub() yPreregisterHub()YAPI.PreregisterHub()

YAPI

Fault-tolerant alternative to RegisterHub().

```
js function yPreregisterHub( url, errmsg)
node.js function PreregisterHub( url, errmsg)
php function yPreregisterHub( $url, &$errmsg)
cpp YRETCODE yPreregisterHub( const string& url, string& errmsg)
m YRETCODE yPreregisterHub( NSString * url, NSError** errmsg)
pas function yPreregisterHub( url: string, var errmsg: string): integer
vb function yPreregisterHub( ByVal url As String,
                           ByRef errmsg As String) As Integer
cs int PreregisterHub( string url, ref string errmsg)
java int PreregisterHub( String url)
py def PreregisterHub( url, errmsg=None)
```

This function has the same purpose and same arguments as RegisterHub(), but does not trigger an error when the selected hub is not available at the time of the function call. This makes it possible to register a network hub independently of the current connectivity, and to try to contact it only when a device is actively needed.

Parameters :

url a string containing either "usb", "callback" or the root URL of the hub to monitor
errmsg a string passed by reference to receive any error message.

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

YAPI.RegisterDeviceArrivalCallback()**YAPI****yRegisterDeviceArrivalCallback()****YAPI.RegisterDeviceArrivalCallback()**

Register a callback function, to be called each time a device is plugged.

```
js   function yRegisterDeviceArrivalCallback( arrivalCallback)
node.js function RegisterDeviceArrivalCallback( arrivalCallback)
php  function yRegisterDeviceArrivalCallback( $arrivalCallback)
cpp   void yRegisterDeviceArrivalCallback( yDeviceUpdateCallback arrivalCallback)
m    void yRegisterDeviceArrivalCallback( yDeviceUpdateCallback arrivalCallback)
pas   procedure yRegisterDeviceArrivalCallback( arrivalCallback: yDeviceUpdateFunc)
vb    procedure yRegisterDeviceArrivalCallback( ByVal arrivalCallback As yDeviceUpdateFunc)
cs    void RegisterDeviceArrivalCallback( yDeviceUpdateFunc arrivalCallback)
java  void RegisterDeviceArrivalCallback( DeviceArrivalCallback arrivalCallback)
py    def RegisterDeviceArrivalCallback( arrivalCallback)
```

This callback will be invoked while `yUpdateDeviceList` is running. You will have to call this function on a regular basis.

Parameters :

`arrivalCallback` a procedure taking a `YModule` parameter, or `null`

YAPI.RegisterDeviceRemovalCallback() yRegisterDeviceRemovalCallback() YAPI.RegisterDeviceRemovalCallback()

YAPI

Register a callback function, to be called each time a device is unplugged.

```
js function yRegisterDeviceRemovalCallback( removalCallback )
nodejs function RegisterDeviceRemovalCallback( removalCallback )
php function yRegisterDeviceRemovalCallback( $removalCallback )
cpp void yRegisterDeviceRemovalCallback( yDeviceUpdateCallback removalCallback )
m void yRegisterDeviceRemovalCallback( yDeviceUpdateCallback removalCallback )
pas procedure yRegisterDeviceRemovalCallback( removalCallback: yDeviceUpdateFunc )
vb procedure yRegisterDeviceRemovalCallback( ByVal removalCallback As yDeviceUpdateFunc )
cs void RegisterDeviceRemovalCallback( yDeviceUpdateFunc removalCallback )
java void RegisterDeviceRemovalCallback( DeviceRemovalCallback removalCallback )
py def RegisterDeviceRemovalCallback( removalCallback )
```

This callback will be invoked while `yUpdateDeviceList` is running. You will have to call this function on a regular basis.

Parameters :

`removalCallback` a procedure taking a `YModule` parameter, or `null`

YAPI.RegisterHub() yRegisterHub()YAPI.RegisterHub()

YAPI

Setup the Yoctopuce library to use modules connected on a given machine.

```

js   function yRegisterHub( url, errmsg)
nodejs function RegisterHub( url, errmsg)
php  function yRegisterHub( $url, &$errmsg)
cpp   YRETCODE yRegisterHub( const string& url, string& errmsg)
m     YRETCODE yRegisterHub( NSString * url, NSError** errmsg)
pas   function yRegisterHub( url: string, var errmsg: string): integer
vb    function yRegisterHub( ByVal url As String,
                           ByRef errmsg As String) As Integer
cs    int RegisterHub( string url, ref string errmsg)
java  int RegisterHub( String url)
py   def RegisterHub( url, errmsg=None)

```

The parameter will determine how the API will work. Use the following values:

usb: When the **usb** keyword is used, the API will work with devices connected directly to the USB bus. Some programming languages such as Javascript, PHP, and Java don't provide direct access to USB hardware, so **usb** will not work with these. In this case, use a VirtualHub or a networked YoctoHub (see below).

x.x.x.x or **hostname**: The API will use the devices connected to the host with the given IP address or hostname. That host can be a regular computer running a VirtualHub, or a networked YoctoHub such as YoctoHub-Ethernet or YoctoHub-Wireless. If you want to use the VirtualHub running on your local computer, use the IP address 127.0.0.1.

callback: that keyword makes the API run in "*HTTP Callback*" mode. This is a special mode allowing to take control of Yoctopuce devices through a NAT filter when using a VirtualHub or a networked YoctoHub. You only need to configure your hub to call your server script on a regular basis. This mode is currently available for PHP and Node.JS only.

Be aware that only one application can use direct USB access at a given time on a machine. Multiple access would cause conflicts while trying to access the USB modules. In particular, this means that you must stop the VirtualHub software before starting an application that uses direct USB access. The workaround for this limitation is to setup the library to use the VirtualHub rather than direct USB access.

If access control has been activated on the hub, virtual or not, you want to reach, the URL parameter should look like:

```
http://username:password@adresse:port
```

You can call *RegisterHub* several times to connect to several machines.

Parameters :

- url** a string containing either "**usb**", "**callback**" or the root URL of the hub to monitor
- errmsg** a string passed by reference to receive any error message.

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

YAPI.RegisterHubDiscoveryCallback()
yRegisterHubDiscoveryCallback()
YAPI.RegisterHubDiscoveryCallback()

YAPI

Register a callback function, to be called each time an Network Hub send an SSDP message.

| | |
|------|--|
| cpp | void yRegisterHubDiscoveryCallback(YHubDiscoveryCallback hubDiscoveryCallback) |
| m | + (void) yRegisterHubDiscoveryCallback : (YHubDiscoveryCallback) hubDiscoveryCallback |
| pas | procedure yRegisterHubDiscoveryCallback(hubDiscoveryCallback: YHubDiscoveryCallback) |
| vb | procedure yRegisterHubDiscoveryCallback(ByVal hubDiscoveryCallback As YHubDiscoveryCallback) |
| cs | void RegisterHubDiscoveryCallback(YHubDiscoveryCallback hubDiscoveryCallback) |
| java | void RegisterHubDiscoveryCallback(HubDiscoveryCallback hubDiscoveryCallback) |
| py | def RegisterHubDiscoveryCallback(hubDiscoveryCallback) |

The callback has two string parameter, the first one contain the serial number of the hub and the second contain the URL of the network hub (this URL can be passed to RegisterHub). This callback will be invoked while yUpdateDeviceList is running. You will have to call this function on a regular basis.

Parameters :

hubDiscoveryCallback a procedure taking two string parameter, or null

YAPI.RegisterLogFunction()**YAPI****yRegisterLogFunction()YAPI.RegisterLogFunction()**

Registers a log callback function.

| | |
|------|--|
| cpp | void yRegisterLogFunction(yLogFunction logfun) |
| m | void yRegisterLogFunction(yLogCallback logfun) |
| pas | procedure yRegisterLogFunction(logfun: yLogFunc) |
| vb | procedure yRegisterLogFunction(ByVal logfun As yLogFunc) |
| cs | void RegisterLogFunction(yLogFunc logfun) |
| java | void RegisterLogFunction(LogCallback logfun) |
| py | def RegisterLogFunction(logfun) |

This callback will be called each time the API have something to say. Quite useful to debug the API.

Parameters :

logfun a procedure taking a string parameter, or null

YAPI.SelectArchitecture()**YAPI****ySelectArchitecture()YAPI.SelectArchitecture()**

Select the architecture or the library to be loaded to access to USB.

py def **SelectArchitecture(arch)**

By default, the Python library automatically detects the appropriate library to use. However, for Linux ARM, it is not possible to reliably distinguish between a Hard Float (armhf) and a Soft Float (armel) install. For this case, it is therefore recommended to manually select the proper architecture by calling SelectArchitecture() before any other call to the library.

Parameters :

arch A string containing the architecture to use. Possible values are: "armhf", "armel", "i386", "x86_64", "32bit", "64bit"

Returns :

nothing.

On failure, throws an exception.

YAPI.SetDelegate() ySetDelegate()

YAPI

(Objective-C only) Register an object that must follow the protocol YDeviceHotPlug.

```
m void ySetDelegate( id object)
```

The methods `yDeviceArrival` and `yDeviceRemoval` will be invoked while `yUpdateDeviceList` is running. You will have to call this function on a regular basis.

Parameters :

object an object that must follow the protocol YAPIDelegate, or nil

YAPI.SetTimeout() ySetTimeout()

YAPI

Invoke the specified callback function after a given timeout.

```
js  function ySetTimeout( callback, ms_timeout, arguments )
node.js function SetTimeout( callback, ms_timeout, arguments )
```

This function behaves more or less like Javascript `setTimeout`, but during the waiting time, it will call `yHandleEvents` and `yUpdateDeviceList` periodically, in order to keep the API up-to-date with current devices.

Parameters :

- callback** the function to call after the timeout occurs. On Microsoft Internet Explorer, the callback must be provided as a string to be evaluated.
- ms_timeout** an integer corresponding to the duration of the timeout, in milliseconds.
- arguments** additional arguments to be passed to the callback function can be provided, if needed (not supported on Microsoft Internet Explorer).

Returns :

`YAPI_SUCCESS` when the call succeeds. On failure, throws an exception or returns a negative error code.

YAPI.Sleep() ySleep()YAPI.Sleep()

YAPI

Pauses the execution flow for a specified duration.

| | |
|--------|--|
| js | function ySleep(ms_duration, errmsg) |
| nodejs | function Sleep(ms_duration, errmsg) |
| php | function ySleep(\$ms_duration, &\$errmsg) |
| cpp | YRETCODE ySleep(unsigned ms_duration, string& errmsg) |
| m | YRETCODE ySleep(unsigned ms_duration, NSError ** errmsg) |
| pas | function ySleep(ms_duration: integer, var errmsg: string): integer |
| vb | function ySleep(ByVal ms_duration As Integer, ByRef errmsg As String) As Integer |
| cs | int Sleep(int ms_duration, ref string errmsg) |
| java | int Sleep(long ms_duration) |
| py | def Sleep(ms_duration, errmsg=None) |

This function implements a passive waiting loop, meaning that it does not consume CPU cycles significantly. The processor is left available for other threads and processes. During the pause, the library nevertheless reads from time to time information from the Yoctopuce modules by calling `yHandleEvents()`, in order to stay up-to-date.

This function may signal an error in case there is a communication problem while contacting a module.

Parameters :

ms_duration an integer corresponding to the duration of the pause, in milliseconds.

errmsg a string passed by reference to receive any error message.

Returns :

`YAPI_SUCCESS` when the call succeeds. On failure, throws an exception or returns a negative error code.

YAPI.TriggerHubDiscovery()**YAPI****yTriggerHubDiscovery()YAPI.TriggerHubDiscovery()**

Force a hub discovery, if a callback has been registered with yRegisterDeviceRemovalCallback it will be called for each net work hub that will respond to the discovery.

| | |
|------|---|
| cpp | YRETCODE yTriggerHubDiscovery(string& errmsg) |
| m | + (YRETCODE) yTriggerHubDiscovery : (NSError**) errmsg |
| pas | function yTriggerHubDiscovery(var errmsg: string): integer |
| vb | function yTriggerHubDiscovery(ByRef errmsg As String) As Integer |
| cs | int TriggerHubDiscovery(ref string errmsg) |
| java | int TriggerHubDiscovery() |
| py | def TriggerHubDiscovery(errmsg=None) |

Parameters :

errmsg a string passed by reference to receive any error message.

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

YAPI.UnregisterHub()**YAPI****yUnregisterHub()YAPI.UnregisterHub()**

Setup the Yoctopuce library to no more use modules connected on a previously registered machine with RegisterHub.

| | |
|--------|---|
| js | function yUnregisterHub(url) |
| nodejs | function UnregisterHub(url) |
| php | function yUnregisterHub(\$url) |
| cpp | void yUnregisterHub(const string& url) |
| m | void yUnregisterHub(NSString * url) |
| pas | procedure yUnregisterHub(url: string) |
| vb | procedure yUnregisterHub(ByVal url As String) |
| cs | void UnregisterHub(string url) |
| java | void UnregisterHub(String url) |
| py | def UnregisterHub(url) |

Parameters :

url a string containing either "usb" or the

YAPI.UpdateDeviceList()

YAPI

yUpdateDeviceList()YAPI.UpdateDeviceList()

Triggers a (re)detection of connected Yoctopuce modules.

```
js function yUpdateDeviceList( errmsg)
node.js function UpdateDeviceList( errmsg)
php function yUpdateDeviceList( &$errmsg)
cpp YRETCODE yUpdateDeviceList( string& errmsg)
m YRETCODE yUpdateDeviceList( NSError** errmsg)
pas function yUpdateDeviceList( var errmsg: string): integer
vb function yUpdateDeviceList( ByRef errmsg As String) As YRETCODE
cs YRETCODE UpdateDeviceList( ref string errmsg)
java int UpdateDeviceList( )
py def UpdateDeviceList( errmsg=None)
```

The library searches the machines or USB ports previously registered using `yRegisterHub()`, and invokes any user-defined callback function in case a change in the list of connected devices is detected.

This function can be called as frequently as desired to refresh the device list and to make the application aware of hot-plug events.

Parameters :

errmsg a string passed by reference to receive any error message.

Returns :

`YAPI_SUCCESS` when the call succeeds. On failure, throws an exception or returns a negative error code.

YAPI.UpdateDeviceList_async() yUpdateDeviceList_async()

YAPI

Triggers a (re)detection of connected Yoctopuce modules.

```
js   function yUpdateDeviceList_async( callback, context )
nodejs function UpdateDeviceList_async( callback, context )
```

The library searches the machines or USB ports previously registered using `yRegisterHub()`, and invokes any user-defined callback function in case a change in the list of connected devices is detected.

This function can be called as frequently as desired to refresh the device list and to make the application aware of hot-plug events.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox Javascript VM that does not implement context switching during blocking I/O calls.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the result code (`YAPI_SUCCESS` if the operation completes successfully) and the error message.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

3.2. Accelerometer function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_accelerometer.js'></script>
nodejs var yoctolib = require('yoctolib');
var YAccelerometer = yoctolib.YAccelerometer;
php require_once('yocto_accelerometer.php');
cpp #include "yocto_accelerometer.h"
m #import "yocto_accelerometer.h"
pas uses yocto_accelerometer;
vb yocto_accelerometer.vb
cs yocto_accelerometer.cs
java import com.yoctopuce.YoctoAPI.YAccelerometer;
py from yocto_accelerometer import *

```

Global functions

yFindAccelerometer(func)

Retrieves an accelerometer for a given identifier.

yFirstAccelerometer()

Starts the enumeration of accelerometers currently accessible.

YAccelerometer methods

accelerometer→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

accelerometer→describe()

Returns a short text that describes unambiguously the instance of the accelerometer in the form TYPE (NAME) = SERIAL . FUNCTIONID.

accelerometer→get_advertisedValue()

Returns the current value of the accelerometer (no more than 6 characters).

accelerometer→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor.

accelerometer→get_currentValue()

Returns the current value of the acceleration.

accelerometer→get_errorMessage()

Returns the error message of the latest error with the accelerometer.

accelerometer→get_errorType()

Returns the numerical error code of the latest error with the accelerometer.

accelerometer→get_friendlyName()

Returns a global identifier of the accelerometer in the format MODULE_NAME . FUNCTION_NAME.

accelerometer→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

accelerometer→get_functionId()

Returns the hardware identifier of the accelerometer, without reference to the module.

accelerometer→get_hardwareId()

Returns the unique hardware identifier of the accelerometer in the form SERIAL . FUNCTIONID.

| | |
|--|--|
| accelerometer→get_highestValue() | Returns the maximal value observed for the acceleration since the device was started. |
| accelerometer→get_logFrequency() | Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory. |
| accelerometer→get_logicalName() | Returns the logical name of the accelerometer. |
| accelerometer→get_lowestValue() | Returns the minimal value observed for the acceleration since the device was started. |
| accelerometer→get_module() | Gets the YModule object for the device on which the function is located. |
| accelerometer→get_module_async(callback, context) | Gets the YModule object for the device on which the function is located (asynchronous version). |
| accelerometer→get_recordedData(startTime, endTime) | Retrieves a DataSet object holding historical data for this sensor, for a specified time interval. |
| accelerometer→get_reportFrequency() | Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function. |
| accelerometer→get_resolution() | Returns the resolution of the measured values. |
| accelerometer→get_unit() | Returns the measuring unit for the acceleration. |
| accelerometer→get(userData) | Returns the value of the userData attribute, as previously stored using method set(userData). |
| accelerometer→get_xValue() | Returns the X component of the acceleration, as a floating point number. |
| accelerometer→get_yValue() | Returns the Y component of the acceleration, as a floating point number. |
| accelerometer→get_zValue() | Returns the Z component of the acceleration, as a floating point number. |
| accelerometer→isOnline() | Checks if the accelerometer is currently reachable, without raising any error. |
| accelerometer→isOnline_async(callback, context) | Checks if the accelerometer is currently reachable, without raising any error (asynchronous version). |
| accelerometer→load(msValidity) | Preloads the accelerometer cache with a specified validity duration. |
| accelerometer→loadCalibrationPoints(rawValues, refValues) | Retrieves error correction data points previously entered using the method calibrateFromPoints. |
| accelerometer→load_async(msValidity, callback, context) | Preloads the accelerometer cache with a specified validity duration (asynchronous version). |
| accelerometer→nextAccelerometer() | Continues the enumeration of accelerometers started using yFirstAccelerometer(). |
| accelerometer→registerTimedReportCallback(callback) | Registers the callback function that is invoked on every periodic timed notification. |
| accelerometer→registerValueCallback(callback) | Registers the callback function that is invoked on every change of advertised value. |

3. Reference

accelerometer→set_highestValue(newval)

Changes the recorded maximal value observed.

accelerometer→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

accelerometer→set_logicalName(newval)

Changes the logical name of the accelerometer.

accelerometer→set_lowestValue(newval)

Changes the recorded minimal value observed.

accelerometer→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

accelerometer→set_resolution(newval)

Changes the resolution of the measured physical values.

accelerometer→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

accelerometer→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YAccelerometer.FindAccelerometer() yFindAccelerometer() YAccelerometer.FindAccelerometer()

YAccelerometer

Retrieves an accelerometer for a given identifier.

| | |
|---------|---|
| js | function yFindAccelerometer(func) |
| node.js | function FindAccelerometer(func) |
| php | function yFindAccelerometer(\$func) |
| cpp | YAccelerometer* yFindAccelerometer(const string& func) |
| m | YAccelerometer* yFindAccelerometer(NSString* func) |
| pas | function yFindAccelerometer(func: string): TYAccelerometer |
| vb | function yFindAccelerometer(ByVal func As String) As YAccelerometer |
| cs | YAccelerometer FindAccelerometer(string func) |
| java | YAccelerometer FindAccelerometer(String func) |
| py | def FindAccelerometer(func) |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the accelerometer is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YAccelerometer.isOnline()` to test if the accelerometer is indeed online at a given time. In case of ambiguity when looking for an accelerometer by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the accelerometer

Returns :

a `YAccelerometer` object allowing you to drive the accelerometer.

YAccelerometer.FirstAccelerometer()**YAccelerometer****yFirstAccelerometer()****YAccelerometer.FirstAccelerometer()**

Starts the enumeration of accelerometers currently accessible.

```
js function yFirstAccelerometer( )  
nodejs function FirstAccelerometer( )  
php function yFirstAccelerometer( )  
cpp YAccelerometer* yFirstAccelerometer( )  
m YAccelerometer* yFirstAccelerometer( )  
pas function yFirstAccelerometer( ): TYAccelerometer  
vb function yFirstAccelerometer( ) As YAccelerometer  
cs YAccelerometer FirstAccelerometer( )  
java YAccelerometer FirstAccelerometer( )  
py def FirstAccelerometer( )
```

Use the method `YAccelerometer.nextAccelerometer()` to iterate on next accelerometers.

Returns :

a pointer to a `YAccelerometer` object, corresponding to the first accelerometer currently online, or a null pointer if there are none.

accelerometer→calibrateFromPoints() accelerometer.calibrateFromPoints()

YAccelerometer

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```

js   function calibrateFromPoints( rawValues, refValues)
node.js function calibrateFromPoints( rawValues, refValues)
php  function calibrateFromPoints( $rawValues, $refValues)
cpp   int calibrateFromPoints( vector<double> rawValues,
                           vector<double> refValues)

m    -(int) calibrateFromPoints : (NSMutableArray*) rawValues
      : (NSMutableArray*) refValues

pas  function calibrateFromPoints( rawValues: TDoubleArray,
                                  refValues: TDoubleArray): LongInt

vb   procedure calibrateFromPoints( )
cs    int calibrateFromPoints( List<double> rawValues,
                           List<double> refValues)

java int calibrateFromPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def calibrateFromPoints( rawValues, refValues)
cmd  YAccelerometer target calibrateFromPoints rawValues refValues

```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.
refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

accelerometer→describe()accelerometer.describe()**YAccelerometer**

Returns a short text that describes unambiguously the instance of the accelerometer in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the accelerometer (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

accelerometer→get_advertisedValue()
accelerometer→advertisedValue()
accelerometer.get_advertisedValue()

YAccelerometer

Returns the current value of the accelerometer (no more than 6 characters).

| | |
|---------------|--|
| js | function get_advertisedValue() |
| nodejs | function get_advertisedValue() |
| php | function get_advertisedValue() |
| cpp | string get_advertisedValue() |
| m | -(NSString*) advertisedValue |
| pas | function get_advertisedValue() : string |
| vb | function get_advertisedValue() As String |
| cs | string get_advertisedValue() |
| java | String get_advertisedValue() |
| py | def get_advertisedValue() |
| cmd | YAccelerometer target get_advertisedValue |

Returns :

a string corresponding to the current value of the accelerometer (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

accelerometer→get_currentRawValue()
accelerometer→currentRawValue()
accelerometer.get_currentRawValue()

YAccelerometer

Returns the uncalibrated, unrounded raw value returned by the sensor.

```
js function get_currentRawValue( )
nodejs function get_currentRawValue( )
php function get_currentRawValue( )
cpp double get_currentRawValue( )
m -(double) currentRawValue
pas function get_currentRawValue( ): double
vb function get_currentRawValue( ) As Double
cs double get_currentRawValue( )
java double get_currentRawValue( )
py def get_currentRawValue( )
cmd YAccelerometer target get_currentRawValue
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

accelerometer→get_currentValue()
accelerometer→currentValue()
accelerometer.get_currentValue()

YAccelerometer

Returns the current value of the acceleration.

| | |
|---------------|---|
| js | function get_currentValue() |
| nodejs | function get_currentValue() |
| php | function get_currentValue() |
| cpp | double get_currentValue() |
| m | -(double) currentValue |
| pas | function get_currentValue() : double |
| vb | function get_currentValue() As Double |
| cs | double get_currentValue() |
| java | double get_currentValue() |
| py | def get_currentValue() |
| cmd | YAccelerometer target get_currentValue |

Returns :

a floating point number corresponding to the current value of the acceleration

On failure, throws an exception or returns **Y_CURRENTVALUE_INVALID**.

accelerometer→get_errorMessage()
accelerometer→errorMessage()
accelerometer.get_errorMessage()**YAccelerometer**

Returns the error message of the latest error with the accelerometer.

| | |
|--------|--|
| js | function get_errorMessage() |
| nodejs | function get_errorMessage() |
| php | function get_errorMessage() |
| cpp | string get_errorMessage() |
| m | -(NSString*) errorMessage |
| pas | function get_errorMessage(): string |
| vb | function get_errorMessage() As String |
| cs | string get_errorMessage() |
| java | String get_errorMessage() |
| py | def get_errorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the accelerometer object

accelerometer→get_errorType()
accelerometer→errorType()
accelerometer.get_errorType()

YAccelerometer

Returns the numerical error code of the latest error with the accelerometer.

| | |
|----------------------|--|
| <code>js</code> | <code>function get_errorType()</code> |
| <code>node.js</code> | <code>function get_errorType()</code> |
| <code>php</code> | <code>function get_errorType()</code> |
| <code>cpp</code> | <code>YRETCODE get_errorType()</code> |
| <code>pas</code> | <code>function get_errorType(): YRETCODE</code> |
| <code>vb</code> | <code>function get_errorType() As YRETCODE</code> |
| <code>cs</code> | <code>YRETCODE get_errorType()</code> |
| <code>java</code> | <code>int get_errorType()</code> |
| <code>py</code> | <code>def get_errorType()</code> |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the accelerometer object

accelerometer→get_friendlyName()
accelerometer→friendlyName()
accelerometer.get_friendlyName()

YAccelerometer

Returns a global identifier of the accelerometer in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the accelerometer if they are defined, otherwise the serial number of the module and the hardware identifier of the accelerometer (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the accelerometer using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

accelerometer→get_functionDescriptor()
accelerometer→functionDescriptor()
accelerometer.get_functionDescriptor()

YAccelerometer

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

accelerometer→get_functionId()
accelerometer→functionId()
accelerometer.get_functionId()

YAccelerometer

Returns the hardware identifier of the accelerometer, without reference to the module.

| | |
|--------|---|
| js | function get_functionId() |
| nodejs | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the accelerometer (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

accelerometer→get.hardwareId()
accelerometer→hardwareId()
accelerometer.get.hardwareId()

YAccelerometer

Returns the unique hardware identifier of the accelerometer in the form SERIAL.FUNCTIONID.

| | |
|----------------|---|
| js | function get.hardwareId() |
| node.js | function get.hardwareId() |
| php | function get.hardwareId() |
| cpp | string get.hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get.hardwareId() As String |
| cs | string get.hardwareId() |
| java | String get.hardwareId() |
| py | def get.hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the accelerometer. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the accelerometer (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

accelerometer→get_highestValue()
accelerometer→highestValue()
accelerometer.get_highestValue()**YAccelerometer**

Returns the maximal value observed for the acceleration since the device was started.

js function **get_highestValue()**
nodejs function **get_highestValue()**
php function **get_highestValue()**
cpp double **get_highestValue()**
m -(double) highestValue
pas function **get_highestValue(): double**
vb function **get_highestValue() As Double**
cs double **get_highestValue()**
java double **get_highestValue()**
py def **get_highestValue()**
cmd YAccelerometer **target get_highestValue**

Returns :

a floating point number corresponding to the maximal value observed for the acceleration since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

accelerometer→get_logFrequency()
accelerometer→logFrequency()
accelerometer.get_logFrequency()

YAccelerometer

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
js   function get_logFrequency( )  
nodejs function get_logFrequency( )  
php  function get_logFrequency( )  
cpp   string get_logFrequency( )  
m    -(NSString*) logFrequency  
pas   function get_logFrequency( ): string  
vb    function get_logFrequency( ) As String  
cs   string get_logFrequency( )  
java  String get_logFrequency( )  
py    def get_logFrequency()  
cmd   YAccelerometer target get_logFrequency
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns `Y_LOGFREQUENCY_INVALID`.

accelerometer→get_logicalName()
accelerometer→logicalName()
accelerometer.get_logicalName()

YAccelerometer

Returns the logical name of the accelerometer.

```
js function get_logicalName( )  
nodejs function get_logicalName( )  
php function get_logicalName( )  
cpp string get_logicalName( )  
m -(NSString*) logicalName  
pas function get_logicalName( ): string  
vb function get_logicalName( ) As String  
cs string get_logicalName( )  
java String get_logicalName( )  
py def get_logicalName( )  
cmd YAccelerometer target get_logicalName
```

Returns :

a string corresponding to the logical name of the accelerometer. On failure, throws an exception or returns `Y_LOGICALNAME_INVALID`.

accelerometer→get_lowestValue()
accelerometer→lowestValue()
accelerometer.get_lowestValue()

YAccelerometer

Returns the minimal value observed for the acceleration since the device was started.

```
js   function get_lowestValue( )  
node.js function get_lowestValue( )  
php  function get_lowestValue( )  
cpp   double get_lowestValue( )  
m    -(double) lowestValue  
pas   function get_lowestValue( ): double  
vb    function get_lowestValue( ) As Double  
cs    double get_lowestValue( )  
java  double get_lowestValue( )  
py    def get_lowestValue( )  
cmd   YAccelerometer target get_lowestValue
```

Returns :

a floating point number corresponding to the minimal value observed for the acceleration since the device was started

On failure, throws an exception or returns **Y_LOWESTVALUE_INVALID**.

accelerometer→get_module()**YAccelerometer****accelerometer→module()accelerometer.get_module()**

Gets the `YModule` object for the device on which the function is located.

| | |
|---------|---|
| js | function get_module() |
| node.js | function get_module() |
| php | function get_module() |
| cpp | <code>YModule * get_module()</code> |
| m | <code>-(YModule*) module</code> |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | <code>YModule get_module()</code> |
| java | <code>YModule get_module()</code> |
| py | <code>def get_module()</code> |

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

accelerometer→get_module_async()
accelerometer→module_async()**YAccelerometer**

Gets the **YModule** object for the device on which the function is located (asynchronous version).

```
js   function get_module_async( callback, context )
nodejs function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned **YModule** object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested **YModule** object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

accelerometer → `get_recordedData()`
accelerometer → `recordedData()`
accelerometer.`get_recordedData()`

YAccelerometer

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the `DataSet` class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measurement, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of `YDataSet`, providing access to historical data. Past measures can be loaded progressively using methods from the `YDataSet` object.

accelerometer→get_reportFrequency()
accelerometer→reportFrequency()
accelerometer.get_reportFrequency()

YAccelerometer

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
js    function get_reportFrequency( )  
nodejs function get_reportFrequency( )  
php   function get_reportFrequency( )  
cpp   string get_reportFrequency( )  
m     -(NSString*) reportFrequency  
pas   function get_reportFrequency( ): string  
vb    function get_reportFrequency( ) As String  
cs    string get_reportFrequency( )  
java  String get_reportFrequency( )  
py    def get_reportFrequency( )  
cmd   YAccelerometer target get_reportFrequency
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns `Y_REPORTFREQUENCY_INVALID`.

accelerometer→get_resolution()
accelerometer→resolution()
accelerometer.get_resolution()

YAccelerometer

Returns the resolution of the measured values.

```
js function get_resolution( )
nodejs function get_resolution( )
php function get_resolution( )
cpp double get_resolution( )
m -(double) resolution
pas function get_resolution( ): double
vb function get_resolution( ) As Double
cs double get_resolution( )
java double get_resolution( )
py def get_resolution( )
cmd YAccelerometer target get_resolution
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

accelerometer→get_unit()**YAccelerometer****accelerometer→unit()accelerometer.get_unit()**

Returns the measuring unit for the acceleration.

| | |
|--------|---------------------------------------|
| js | function get_unit() |
| nodejs | function get_unit() |
| php | function get_unit() |
| cpp | string get_unit() |
| m | -(NSString*) unit |
| pas | function get_unit() : string |
| vb | function get_unit() As String |
| cs | string get_unit() |
| java | String get_unit() |
| py | def get_unit() |
| cmd | YAccelerometer target get_unit |

Returns :

a string corresponding to the measuring unit for the acceleration

On failure, throws an exception or returns **Y_UNIT_INVALID**.

accelerometer→get(userData)
accelerometer→userData()
accelerometer.get(userData)

YAccelerometer

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
js function get(userData) {  
nodejs function get(userData) {  
php function get(userData) {  
cpp void * get(userData) {  
m -(void*) userData  
pas function get(userData): Tobject  
vb function get(userData) As Object  
cs object get(userData)  
java Object get(userData)  
py def get(userData)
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

accelerometer→get_xValue()**YAccelerometer****accelerometer→xValue()accelerometer.get_xValue()**

Returns the X component of the acceleration, as a floating point number.

| | |
|---------|---|
| js | function get_xValue() |
| node.js | function get_xValue() |
| php | function get_xValue() |
| cpp | double get_xValue() |
| m | -(double) xValue |
| pas | function get_xValue(): double |
| vb | function get_xValue() As Double |
| cs | double get_xValue() |
| java | double get_xValue() |
| py | def get_xValue() |
| cmd | YAccelerometer target get_xValue |

Returns :

a floating point number corresponding to the X component of the acceleration, as a floating point number

On failure, throws an exception or returns **Y_XVALUE_INVALID**.

accelerometer→get_yValue()**YAccelerometer****accelerometer→yValue()accelerometer.get_yValue()**

Returns the Y component of the acceleration, as a floating point number.

```
js function get_yValue( )
node.js function get_yValue( )
php function get_yValue( )
cpp double get_yValue( )
m -(double) yValue
pas function get_yValue( ): double
vb function get_yValue( ) As Double
cs double get_yValue( )
java double get_yValue( )
py def get_yValue( )
cmd YAccelerometer target get_yValue
```

Returns :

a floating point number corresponding to the Y component of the acceleration, as a floating point number

On failure, throws an exception or returns Y_YVALUE_INVALID.

accelerometer→get_zValue()**YAccelerometer****accelerometer→zValue()accelerometer.get_zValue()**

Returns the Z component of the acceleration, as a floating point number.

| | |
|--------|---|
| js | function get_zValue() |
| nodejs | function get_zValue() |
| php | function get_zValue() |
| cpp | double get_zValue() |
| m | -(double) zValue |
| pas | function get_zValue(): double |
| vb | function get_zValue() As Double |
| cs | double get_zValue() |
| java | double get_zValue() |
| py | def get_zValue() |
| cmd | YAccelerometer target get_zValue |

Returns :

a floating point number corresponding to the Z component of the acceleration, as a floating point number

On failure, throws an exception or returns **Y_ZVALUE_INVALID**.

accelerometer→isOnline()accelerometer.isOnline()**YAccelerometer**

Checks if the accelerometer is currently reachable, without raising any error.

| | |
|--------|--|
| js | function isOnline() |
| nodejs | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the accelerometer in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the accelerometer.

Returns :

true if the accelerometer can be reached, and false otherwise

accelerometer→isOnline_async()**YAccelerometer**

Checks if the accelerometer is currently reachable, without raising any error (asynchronous version).

| | |
|---------|--|
| js | function isOnline_async(callback, context) |
| node.js | function isOnline_async(callback, context) |

If there is a cached value for the accelerometer in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

accelerometer→load()accelerometer.load()**YAccelerometer**

Preloads the accelerometer cache with a specified validity duration.

| | |
|--------|--|
| js | function load(msValidity) |
| nodejs | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | - (YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

accelerometer→loadCalibrationPoints() accelerometer.loadCalibrationPoints()

YAccelerometer

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```

js   function loadCalibrationPoints( rawValues, refValues)
nodejs function loadCalibrationPoints( rawValues, refValues)
php  function loadCalibrationPoints( &$rawValues, &$refValues)
cpp   int loadCalibrationPoints( vector<double>& rawValues,
                                vector<double>& refValues)

m    -(int) loadCalibrationPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues

pas  function loadCalibrationPoints( var rawValues: TDoubleArray,
                           var refValues: TDoubleArray): LongInt

vb   procedure loadCalibrationPoints( )
cs   int loadCalibrationPoints( List<double> rawValues,
                           List<double> refValues)

java int loadCalibrationPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def loadCalibrationPoints( rawValues, refValues)
cmd  YAccelerometer target loadCalibrationPoints rawValues refValues

```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

accelerometer→load_async()

YAccelerometer

Preloads the accelerometer cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

accelerometer→nextAccelerometer()**YAccelerometer**

Continues the enumeration of accelerometers started using `yFirstAccelerometer()`.

| | |
|---------------------|--|
| <code>js</code> | <code>function nextAccelerometer()</code> |
| <code>nodejs</code> | <code>function nextAccelerometer()</code> |
| <code>php</code> | <code>function nextAccelerometer()</code> |
| <code>cpp</code> | <code>YAccelerometer * nextAccelerometer()</code> |
| <code>m</code> | <code>-(YAccelerometer*) nextAccelerometer</code> |
| <code>pas</code> | <code>function nextAccelerometer(): TYAccelerometer</code> |
| <code>vb</code> | <code>function nextAccelerometer() As YAccelerometer</code> |
| <code>cs</code> | <code>YAccelerometer nextAccelerometer()</code> |
| <code>java</code> | <code>YAccelerometer nextAccelerometer()</code> |
| <code>py</code> | <code>def nextAccelerometer()</code> |

Returns :

a pointer to a `YAccelerometer` object, corresponding to an accelerometer currently online, or a null pointer if there are no more accelerometers to enumerate.

**accelerometer→registerTimedReportCallback()
accelerometer.registerTimedReportCallback()****YAccelerometer**

Registers the callback function that is invoked on every periodic timed notification.

```
js   function registerTimedReportCallback( callback )
node.js function registerTimedReportCallback( callback )
php  function registerTimedReportCallback( $callback )
cpp   int registerTimedReportCallback( YAccelerometerTimedReportCallback callback )
m    -(int) registerTimedReportCallback : (YAccelerometerTimedReportCallback) callback
pas   function registerTimedReportCallback( callback: TYAccelerometerTimedReportCallback): LongInt
vb    function registerTimedReportCallback( ) As Integer
cs    int registerTimedReportCallback( TimedReportCallback callback )
java  int registerTimedReportCallback( TimedReportCallback callback )
py    def registerTimedReportCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

accelerometer→registerValueCallback() accelerometer.registerValueCallback()

YAccelerometer

Registers the callback function that is invoked on every change of advertised value.

| | |
|---------|--|
| js | function registerValueCallback(callback) |
| node.js | function registerValueCallback(callback) |
| php | function registerValueCallback(\$callback) |
| cpp | int registerValueCallback(YAccelerometerValueCallback callback) |
| m | -(int) registerValueCallback : (YAccelerometerValueCallback) callback |
| pas | function registerValueCallback(callback : TYAccelerometerValueCallback): LongInt |
| vb | function registerValueCallback() As Integer |
| cs | int registerValueCallback(ValueCallback callback) |
| java | int registerValueCallback(UpdateCallback callback) |
| py | def registerValueCallback(callback) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

accelerometer→set_highestValue()
accelerometer→setHighestValue()
accelerometer.set_highestValue()

YAccelerometer

Changes the recorded maximal value observed.

```
js function set_highestValue( newval)
nodejs function set_highestValue( newval)
php function set_highestValue( $newval)
cpp int set_highestValue( double newval)
m -(int) setHighestValue : (double) newval
pas function set_highestValue( newval: double): integer
vb function set_highestValue( ByVal newval As Double) As Integer
cs int set_highestValue( double newval)
java int set_highestValue( double newval)
py def set_highestValue( newval)
cmd YAccelerometer target set_highestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

accelerometer→set_logFrequency()
accelerometer→setLogFrequency()
accelerometer.set_logFrequency()

YAccelerometer

Changes the datalogger recording frequency for this function.

| | |
|---------|--|
| js | function set_logFrequency(newval) |
| node.js | function set_logFrequency(newval) |
| php | function set_logFrequency(\$newval) |
| cpp | int set_logFrequency(const string& newval) |
| m | -(int) setLogFrequency : (NSString*) newval |
| pas | function set_logFrequency(newval: string): integer |
| vb | function set_logFrequency(ByVal newval As String) As Integer |
| cs | int set_logFrequency(string newval) |
| java | int set_logFrequency(String newval) |
| py | def set_logFrequency(newval) |
| cmd | YAccelerometer target set_logFrequency newval |

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

accelerometer→set_logicalName()
accelerometer→setLogicalName()
accelerometer.set_logicalName()

YAccelerometer

Changes the logical name of the accelerometer.

```
js function set_logicalName( newval)
nodejs function set_logicalName( newval)
php function set_logicalName( $newval)
cpp int set_logicalName( const string& newval)
m -(int) setLogicalName : (NSString*) newval
pas function set_logicalName( newval: string): integer
vb function set_logicalName( ByVal newval As String) As Integer
cs int set_logicalName( string newval)
java int set_logicalName( String newval)
py def set_logicalName( newval)
cmd YAccelerometer target set_logicalName newval
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the accelerometer.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

accelerometer→set_lowestValue()
accelerometer→setLowestValue()
accelerometer.set_lowestValue()

YAccelerometer

Changes the recorded minimal value observed.

```
js function set_lowestValue( newval)
nodejs function set_lowestValue( newval)
php function set_lowestValue( $newval)
cpp int set_lowestValue( double newval)
m -(int) setLowestValue : (double) newval
pas function set_lowestValue( newval: double): integer
vb function set_lowestValue( ByVal newval As Double) As Integer
cs int set_lowestValue( double newval)
java int set_lowestValue( double newval)
py def set_lowestValue( newval)
cmd YAccelerometer target set_lowestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

accelerometer→set_reportFrequency()
accelerometer→setReportFrequency()
accelerometer.set_reportFrequency()

YAccelerometer

Changes the timed value notification frequency for this function.

```
js    function set_reportFrequency( newval)
nodejs function set_reportFrequency( newval)
php   function set_reportFrequency( $newval)
cpp   int set_reportFrequency( const string& newval)
m     -(int) setReportFrequency : (NSString*) newval
pas   function set_reportFrequency( newval: string): integer
vb    function set_reportFrequency( ByVal newval As String) As Integer
cs    int set_reportFrequency( string newval)
java  int set_reportFrequency( String newval)
py    def set_reportFrequency( newval)
cmd   YAccelerometer target set_reportFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

accelerometer→set_resolution()
accelerometer→setResolution()
accelerometer.set_resolution()

YAccelerometer

Changes the resolution of the measured physical values.

| | |
|---------------|--|
| js | function set_resolution(newval) |
| nodejs | function set_resolution(newval) |
| php | function set_resolution(\$newval) |
| cpp | int set_resolution(double newval) |
| m | -(int) setResolution : (double) newval |
| pas | function set_resolution(newval: double): integer |
| vb | function set_resolution(ByVal newval As Double) As Integer |
| cs | int set_resolution(double newval) |
| java | int set_resolution(double newval) |
| py | def set_resolution(newval) |
| cmd | YAccelerometer target set_resolution newval |

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

accelerometer→**set(userData)**
accelerometer→**setUserData()**
accelerometer.set(userData)

YAccelerometer

Stores a user context provided as argument in the userData attribute of the function.

```
js  function setUserData( data)
nodejs function setUserData( data)
php  function setUserData( $data)
cpp  void setUserData( void* data)
m    -(void) setUserData : (void*) data
pas   procedure setUserData( data: Tobject)
vb    procedure setUserData( ByVal data As Object)
cs    void setUserData( object data)
java  void setUserData( Object data)
py    def setUserData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

accelerometer→wait_async()**YAccelerometer**

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.3. AnButton function interface

Yoctopuce application programming interface allows you to measure the state of a simple button as well as to read an analog potentiometer (variable resistance). This can be used for instance with a continuous rotating knob, a throttle grip or a joystick. The module is capable to calibrate itself on min and max values, in order to compute a calibrated value that varies proportionally with the potentiometer position, regardless of its total resistance.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_anbutton.js'></script>
nodejs var yoctolib = require('yoctolib');
var YAnButton = yoctolib.YAnButton;
php require_once('yocto_anbutton.php');
cpp #include "yocto_anbutton.h"
m #import "yocto_anbutton.h"
pas uses yocto_anbutton;
vb yocto_anbutton.vb
cs yocto_anbutton.cs
java import com.yoctopuce.YoctoAPI.YAnButton;
py from yocto_anbutton import *

```

Global functions

yFindAnButton(func)

Retrieves an analog input for a given identifier.

yFirstAnButton()

Starts the enumeration of analog inputs currently accessible.

YAnButton methods

anbutton→describe()

Returns a short text that describes unambiguously the instance of the analog input in the form TYPE (NAME)=SERIAL.FUNCTIONID.

anbutton→get_advertisedValue()

Returns the current value of the analog input (no more than 6 characters).

anbutton→get_analogCalibration()

Tells if a calibration process is currently ongoing.

anbutton→get_calibratedValue()

Returns the current calibrated input value (between 0 and 1000, included).

anbutton→get_calibrationMax()

Returns the maximal value measured during the calibration (between 0 and 4095, included).

anbutton→get_calibrationMin()

Returns the minimal value measured during the calibration (between 0 and 4095, included).

anbutton→get_errorMessage()

Returns the error message of the latest error with the analog input.

anbutton→get_errorType()

Returns the numerical error code of the latest error with the analog input.

anbutton→get_friendlyName()

Returns a global identifier of the analog input in the format MODULE_NAME . FUNCTION_NAME.

anbutton→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

anbutton→get_functionId()

Returns the hardware identifier of the analog input, without reference to the module.

anbutton→get_hardwareId()

Returns the unique hardware identifier of the analog input in the form SERIAL.FUNCTIONID.

anbutton→get_isPressed()

Returns true if the input (considered as binary) is active (closed contact), and false otherwise.

anbutton→get_lastTimePressed()

Returns the number of elapsed milliseconds between the module power on and the last time the input button was pressed (the input contact transitionned from open to closed).

anbutton→get_lastTimeReleased()

Returns the number of elapsed milliseconds between the module power on and the last time the input button was released (the input contact transitionned from closed to open).

anbutton→get_logicalName()

Returns the logical name of the analog input.

anbutton→get_module()

Gets the YModule object for the device on which the function is located.

anbutton→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

anbutton→get_pulseCounter()

Returns the pulse counter value

anbutton→get_pulseTimer()

Returns the timer of the pulses counter (ms)

anbutton→get_rawValue()

Returns the current measured input value as-is (between 0 and 4095, included).

anbutton→get_sensitivity()

Returns the sensibility for the input (between 1 and 1000) for triggering user callbacks.

anbutton→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

anbutton→isOnline()

Checks if the analog input is currently reachable, without raising any error.

anbutton→isOnline_async(callback, context)

Checks if the analog input is currently reachable, without raising any error (asynchronous version).

anbutton→load(msValidity)

Preloads the analog input cache with a specified validity duration.

anbutton→load_async(msValidity, callback, context)

Preloads the analog input cache with a specified validity duration (asynchronous version).

anbutton→nextAnButton()

Continues the enumeration of analog inputs started using yFirstAnButton().

anbutton→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

anbutton→resetCounter()

Returns the pulse counter value as well as his timer

anbutton→set_analogCalibration(newval)

Starts or stops the calibration process.

anbutton→set_calibrationMax(newval)

3. Reference

Changes the maximal calibration value for the input (between 0 and 4095, included), without actually starting the automated calibration.

anbutton→set_calibrationMin(newval)

Changes the minimal calibration value for the input (between 0 and 4095, included), without actually starting the automated calibration.

anbutton→set_logicalName(newval)

Changes the logical name of the analog input.

anbutton→set_sensitivity(newval)

Changes the sensibility for the input (between 1 and 1000) for triggering user callbacks.

anbutton→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

anbutton→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YAnButton.FindAnButton()**YAnButton****yFindAnButton()YAnButton.FindAnButton()**

Retrieves an analog input for a given identifier.

| | |
|----------------------|---|
| <code>js</code> | <code>function yFindAnButton(func)</code> |
| <code>node.js</code> | <code>function FindAnButton(func)</code> |
| <code>php</code> | <code>function yFindAnButton(\$func)</code> |
| <code>cpp</code> | <code>YAnButton* yFindAnButton(const string& func)</code> |
| <code>m</code> | <code>YAnButton* yFindAnButton(NSString* func)</code> |
| <code>pas</code> | <code>function yFindAnButton(func: string): TYAnButton</code> |
| <code>vb</code> | <code>function yFindAnButton(ByVal func As String) As YAnButton</code> |
| <code>cs</code> | <code>YAnButton FindAnButton(string func)</code> |
| <code>java</code> | <code>YAnButton FindAnButton(String func)</code> |
| <code>py</code> | <code>def FindAnButton(func)</code> |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the analog input is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YAnButton.isOnline()` to test if the analog input is indeed online at a given time. In case of ambiguity when looking for an analog input by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the analog input

Returns :

a `YAnButton` object allowing you to drive the analog input.

YAnButton.FirstAnButton()**YAnButton****yFirstAnButton()YAnButton.FirstAnButton()**

Starts the enumeration of analog inputs currently accessible.

```
js function yFirstAnButton( )  
node.js function FirstAnButton( )  
php function yFirstAnButton( )  
cpp YAnButton* yFirstAnButton( )  
m YAnButton* yFirstAnButton( )  
pas function yFirstAnButton( ): TYAnButton  
vb function yFirstAnButton( ) As YAnButton  
cs YAnButton FirstAnButton( )  
java YAnButton FirstAnButton( )  
py def FirstAnButton( )
```

Use the method `YAnButton.nextAnButton()` to iterate on next analog inputs.

Returns :

a pointer to a `YAnButton` object, corresponding to the first analog input currently online, or a null pointer if there are none.

anbutton→describe()anbutton.describe()**YAnButton**

Returns a short text that describes unambiguously the instance of the analog input in the form
TYPE (**NAME**)=**SERIAL**.**FUNCTIONID**.

| | |
|--------|--|
| js | function describe () |
| nodejs | function describe () |
| php | function describe () |
| cpp | string describe () |
| m | -(NSString*) describe |
| pas | function describe (): string |
| vb | function describe () As String |
| cs | string describe () |
| java | String describe () |
| py | def describe () |

More precisely, **TYPE** is the type of the function, **NAME** is the name used for the first access to the function, **SERIAL** is the serial number of the module if the module is connected or "unresolved", and **FUNCTIONID** is the hardware identifier of the function if the module is connected. For example, this method returns `Relay(MyCustomName.relay1)=RELAYL01-123456.relay1` if the module is already connected or `Relay(BadCustomName.relay1)=unresolved` if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the analog input (ex: `Relay(MyCustomName.relay1)=RELAYL01-123456.relay1`)

anbutton→get_advertisedValue()
anbutton→advertisedValue()
anbutton.get_advertisedValue()

YAnButton

Returns the current value of the analog input (no more than 6 characters).

js function **get_advertisedValue()**
nodejs function **get_advertisedValue()**
php function **get_advertisedValue()**
cpp string **get_advertisedValue()**
m -(NSString*) advertisedValue
pas function **get_advertisedValue(): string**
vb function **get_advertisedValue() As String**
cs string **get_advertisedValue()**
java String **get_advertisedValue()**
py def **get_advertisedValue()**
cmd YAnButton target **get_advertisedValue**

Returns :

a string corresponding to the current value of the analog input (no more than 6 characters). On failure, throws an exception or returns **Y_ADVERTISEDVALUE_INVALID**.

anbutton→get_analogCalibration()
anbutton→analogCalibration()
anbutton.get_analogCalibration()

YAnButton

Tells if a calibration process is currently ongoing.

```
js    function get_analogCalibration( )  
node.js function get_analogCalibration( )  
php   function get_analogCalibration( )  
cpp   Y_ANALOGCALIBRATION_enum get_analogCalibration( )  
m     -(Y_ANALOGCALIBRATION_enum) analogCalibration  
pas   function get_analogCalibration( ): Integer  
vb    function get_analogCalibration( ) As Integer  
cs    int get_analogCalibration( )  
java  int get_analogCalibration( )  
py    def get_analogCalibration( )  
cmd   YAnButton target get_analogCalibration
```

Returns :

either Y_ANALOGCALIBRATION_OFF or Y_ANALOGCALIBRATION_ON

On failure, throws an exception or returns Y_ANALOGCALIBRATION_INVALID.

anbutton→get_calibratedValue()
anbutton→calibratedValue()
anbutton.get_calibratedValue()

YAnButton

Returns the current calibrated input value (between 0 and 1000, included).

js function **get_calibratedValue()**
nodejs function **get_calibratedValue()**
php function **get_calibratedValue()**
cpp int **get_calibratedValue()**
m -(int) calibratedValue
pas function **get_calibratedValue()**: LongInt
vb function **get_calibratedValue()** As Integer
cs int **get_calibratedValue()**
java int **get_calibratedValue()**
py def **get_calibratedValue()**
cmd YAnButton target **get_calibratedValue**

Returns :

an integer corresponding to the current calibrated input value (between 0 and 1000, included)

On failure, throws an exception or returns **Y_CALIBRATEDVALUE_INVALID**.

anbutton→get_calibrationMax()
anbutton→calibrationMax()
anbutton.get_calibrationMax()**YAnButton**

Returns the maximal value measured during the calibration (between 0 and 4095, included).

| | |
|---------|--|
| js | function get_calibrationMax() |
| node.js | function get_calibrationMax() |
| php | function get_calibrationMax() |
| cpp | int get_calibrationMax() |
| m | -(int) calibrationMax |
| pas | function get_calibrationMax() : LongInt |
| vb | function get_calibrationMax() As Integer |
| cs | int get_calibrationMax() |
| java | int get_calibrationMax() |
| py | def get_calibrationMax() |
| cmd | YAnButton target get_calibrationMax |

Returns :

an integer corresponding to the maximal value measured during the calibration (between 0 and 4095, included)

On failure, throws an exception or returns Y_CALIBRATIONMAX_INVALID.

anbutton→get_calibrationMin()
anbutton→calibrationMin()
anbutton.get_calibrationMin()**YAnButton**

Returns the minimal value measured during the calibration (between 0 and 4095, included).

```
js function get_calibrationMin( )
nodejs function get_calibrationMin( )
php function get_calibrationMin( )
cpp int get_calibrationMin( )
m -(int) calibrationMin
pas function get_calibrationMin( ): LongInt
vb function get_calibrationMin( ) As Integer
cs int get_calibrationMin( )
java int get_calibrationMin( )
py def get_calibrationMin( )
cmd YAnButton target get_calibrationMin
```

Returns :

an integer corresponding to the minimal value measured during the calibration (between 0 and 4095, included)

On failure, throws an exception or returns Y_CALIBRATIONMIN_INVALID.

anbutton→get_errorMessage()
anbutton→errorMessage()
anbutton.get_errorMessage()**YAnButton**

Returns the error message of the latest error with the analog input.

| | |
|----------------------|---|
| <code>js</code> | <code>function get_errorMessage()</code> |
| <code>node.js</code> | <code>function get_errorMessage()</code> |
| <code>php</code> | <code>function get_errorMessage()</code> |
| <code>cpp</code> | <code>string get_errorMessage()</code> |
| <code>m</code> | <code>-(NSString*) errorMessage</code> |
| <code>pas</code> | <code>function get_errorMessage(): string</code> |
| <code>vb</code> | <code>function get_errorMessage() As String</code> |
| <code>cs</code> | <code>string get_errorMessage()</code> |
| <code>java</code> | <code>String get_errorMessage()</code> |
| <code>py</code> | <code>def get_errorMessage()</code> |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the analog input object

anbutton→get_errorType()**YAnButton****anbutton→errorType()anbutton.get_errorType()**

Returns the numerical error code of the latest error with the analog input.

| | |
|---------|--|
| js | function get_errorType() |
| node.js | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType() : YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the analog input object

anbutton→get_friendlyName()
anbutton→friendlyName()
anbutton.get_friendlyName()

YAnButton

Returns a global identifier of the analog input in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|-------------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the analog input if they are defined, otherwise the serial number of the module and the hardware identifier of the analog input (for exemple: MyCustomName . relay1)

Returns :

a string that uniquely identifies the analog input using logical names (ex: MyCustomName . relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

**anbutton→get_functionDescriptor()
anbutton→functionDescriptor()
anbutton.get_functionDescriptor()****YAnButton**

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|---|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

anbutton→get_functionId()**YAnButton****anbutton→functionId()anbutton.get_functionId()**

Returns the hardware identifier of the analog input, without reference to the module.

| | |
|--------|---|
| js | function get_functionId() |
| nodejs | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the analog input (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

anbutton→get_hardwareId()**YAnButton****anbutton→hardwareId()anbutton.get_hardwareId()**

Returns the unique hardware identifier of the analog input in the form SERIAL.FUNCTIONID.

| | |
|---------|---|
| js | function get_hardwareId() |
| node.js | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the analog input. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the analog input (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

anbutton→get_isPressed()**YAnButton****anbutton→isPressed()anbutton.get_isPressed()**

Returns true if the input (considered as binary) is active (closed contact), and false otherwise.

| | |
|--------|---|
| js | function get_isPressed() |
| nodejs | function get_isPressed() |
| php | function get_isPressed() |
| cpp | Y_ISPRESSED_enum get_isPressed() |
| m | -(Y_ISPRESSED_enum) isPressed |
| pas | function get_isPressed(): Integer |
| vb | function get_isPressed() As Integer |
| cs | int get_isPressed() |
| java | int get_isPressed() |
| py | def get_isPressed() |
| cmd | YAnButton target get_isPressed |

Returns :

either Y_ISPRESSED_FALSE or Y_ISPRESSED_TRUE, according to true if the input (considered as binary) is active (closed contact), and false otherwise

On failure, throws an exception or returns Y_ISPRESSED_INVALID.

anbutton→get_lastTimePressed()
anbutton→lastTimePressed()
anbutton.get_lastTimePressed()

YAnButton

Returns the number of elapsed milliseconds between the module power on and the last time the input button was pressed (the input contact transitionned from open to closed).

```
js function get_lastTimePressed( )
nodejs function get_lastTimePressed( )
php function get_lastTimePressed( )
cpp s64 get_lastTimePressed( )
m -(s64) lastTimePressed
pas function get_lastTimePressed( ): int64
vb function get_lastTimePressed( ) As Long
cs long get_lastTimePressed( )
java long get_lastTimePressed( )
py def get_lastTimePressed( )
cmd YAnButton target get_lastTimePressed
```

Returns :

an integer corresponding to the number of elapsed milliseconds between the module power on and the last time the input button was pressed (the input contact transitionned from open to closed)

On failure, throws an exception or returns `Y_LASTTIMEPRESSED_INVALID`.

anbutton→get_lastTimeReleased()
anbutton→lastTimeReleased()
anbutton.get_lastTimeReleased()

YAnButton

Returns the number of elapsed milliseconds between the module power on and the last time the input button was released (the input contact transitionned from closed to open).

```
js function get_lastTimeReleased( )
nodejs function get_lastTimeReleased( )
php function get_lastTimeReleased( )
cpp s64 get_lastTimeReleased( )
m -(s64) lastTimeReleased
pas function get_lastTimeReleased( ): int64
vb function get_lastTimeReleased( ) As Long
cs long get_lastTimeReleased( )
java long get_lastTimeReleased( )
py def get_lastTimeReleased( )
cmd YAnButton target get_lastTimeReleased
```

Returns :

an integer corresponding to the number of elapsed milliseconds between the module power on and the last time the input button was released (the input contact transitionned from closed to open)

On failure, throws an exception or returns `Y_LASTTIMERELEASED_INVALID`.

anbutton→get_logicalName()**YAnButton****anbutton→logicalName()anbutton.get_logicalName()**

Returns the logical name of the analog input.

| | |
|---------|--|
| js | function get_logicalName() |
| node.js | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | - (NSString*) logicalName |
| pas | function get_logicalName(): string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YAnButton target get_logicalName |

Returns :

a string corresponding to the logical name of the analog input. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

anbutton→get_module()**YAnButton****anbutton→module()anbutton.get_module()**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

anbutton→get_module_async()
anbutton→module_async()**YAnButton**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

anbutton→get_pulseCounter()
anbutton→pulseCounter()
anbutton.get_pulseCounter()

YAnButton

Returns the pulse counter value

| | |
|---------------|---|
| js | function get_pulseCounter() |
| nodejs | function get_pulseCounter() |
| php | function get_pulseCounter() |
| cpp | s64 get_pulseCounter() |
| m | -(s64) pulseCounter |
| pas | function get_pulseCounter() : int64 |
| vb | function get_pulseCounter() As Long |
| cs | long get_pulseCounter() |
| java | long get_pulseCounter() |
| py | def get_pulseCounter() |

Returns :

an integer corresponding to the pulse counter value

On failure, throws an exception or returns **Y_PULSECOUNTER_INVALID**.

anbutton→get_pulseTimer()**YAnButton****anbutton→pulseTimer()&anbutton.get_pulseTimer()**

Returns the timer of the pulses counter (ms)

js function **get_pulseTimer()****node.js** function **get_pulseTimer()****php** function **get_pulseTimer()****cpp** s64 **get_pulseTimer()****m** -(s64) pulseTimer**pas** function **get_pulseTimer(): int64****vb** function **get_pulseTimer() As Long****cs** long **get_pulseTimer()****java** long **get_pulseTimer()****py** def **get_pulseTimer()****Returns :**

an integer corresponding to the timer of the pulses counter (ms)

On failure, throws an exception or returns **Y_PULSE_TIMER_INVALID**.

anbutton→get_rawValue()**YAnButton****anbutton→rawValue()anbutton.get_rawValue()**

Returns the current measured input value as-is (between 0 and 4095, included).

| | |
|--------|--|
| js | function get_rawValue() |
| nodejs | function get_rawValue() |
| php | function get_rawValue() |
| cpp | int get_rawValue() |
| m | -(int) rawValue |
| pas | function get_rawValue(): LongInt |
| vb | function get_rawValue() As Integer |
| cs | int get_rawValue() |
| java | int get_rawValue() |
| py | def get_rawValue() |
| cmd | YAnButton target get_rawValue |

Returns :

an integer corresponding to the current measured input value as-is (between 0 and 4095, included)

On failure, throws an exception or returns Y_RAWVALUE_INVALID.

anbutton→get_sensitivity()**YAnButton****anbutton→sensitivity()|anbutton.get_sensitivity()**

Returns the sensibility for the input (between 1 and 1000) for triggering user callbacks.

| | |
|---------|--|
| js | function get_sensitivity() |
| node.js | function get_sensitivity() |
| php | function get_sensitivity() |
| cpp | int get_sensitivity() |
| m | -(int) sensitivity |
| pas | function get_sensitivity() : LongInt |
| vb | function get_sensitivity() As Integer |
| cs | int get_sensitivity() |
| java | int get_sensitivity() |
| py | def get_sensitivity() |
| cmd | YAnButton target get_sensitivity |

Returns :

an integer corresponding to the sensibility for the input (between 1 and 1000) for triggering user callbacks

On failure, throws an exception or returns Y_SENSITIVITY_INVALID.

anbutton→get(userData)**YAnButton****anbutton→userData()anbutton.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|---|
| js | <code>function get(userData) </code> |
| nodejs | <code>function get(userData) </code> |
| php | <code>function get(userData) </code> |
| cpp | <code>void * get(userData) </code> |
| m | <code>-(void*) userData</code> |
| pas | <code>function get(userData): Tobject</code> |
| vb | <code>function get(userData) As Object</code> |
| cs | <code>object get(userData) </code> |
| java | <code>Object get(userData) </code> |
| py | <code>def get(userData) </code> |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

anbutton→isOnline()anbutton.isOnline()**YAnButton**

Checks if the analog input is currently reachable, without raising any error.

| | |
|--------|--|
| js | function isOnline() |
| nodejs | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the analog input in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the analog input.

Returns :

true if the analog input can be reached, and false otherwise

anbutton→isOnline_async()**YAnButton**

Checks if the analog input is currently reachable, without raising any error (asynchronous version).

| | |
|---------|---|
| js | function isOnline_async(callback, context) |
| node.js | function isOnline_async(callback, context) |

If there is a cached value for the analog input in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

anbutton→load()**YAnButton**

Preloads the analog input cache with a specified validity duration.

| | |
|--------|--|
| js | function load(msValidity) |
| nodejs | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | -(YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

anbutton→load_async()

YAnButton

Preloads the analog input cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

anbutton→nextAnButton()anbutton.nextAnButton()**YAnButton**

Continues the enumeration of analog inputs started using `yFirstAnButton()`.

| | |
|--------|--|
| js | <code>function nextAnButton()</code> |
| nodejs | <code>function nextAnButton()</code> |
| php | <code>function nextAnButton()</code> |
| cpp | <code>YAnButton * nextAnButton()</code> |
| m | <code>-(YAnButton*) nextAnButton</code> |
| pas | <code>function nextAnButton(): TYAnButton</code> |
| vb | <code>function nextAnButton() As YAnButton</code> |
| cs | <code>YAnButton nextAnButton()</code> |
| java | <code>YAnButton nextAnButton()</code> |
| py | <code>def nextAnButton()</code> |

Returns :

a pointer to a `YAnButton` object, corresponding to an analog input currently online, or a `null` pointer if there are no more analog inputs to enumerate.

anbutton→registerValueCallback() anbutton.registerValueCallback()

YAnButton

Registers the callback function that is invoked on every change of advertised value.

| | |
|---------|---|
| js | function registerValueCallback(callback) |
| node.js | function registerValueCallback(callback) |
| php | function registerValueCallback(\$callback) |
| cpp | int registerValueCallback(YAnButtonValueCallback callback) |
| m | -(int) registerValueCallback : (YAnButtonValueCallback) callback |
| pas | function registerValueCallback(callback : TYAnButtonValueCallback): LongInt |
| vb | function registerValueCallback() As Integer |
| cs | int registerValueCallback(ValueCallback callback) |
| java | int registerValueCallback(UpdateCallback callback) |
| py | def registerValueCallback(callback) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

anbutton→resetCounter()|anbutton.resetCounter()**YAnButton**

Returns the pulse counter value as well as his timer

| | |
|--------|---|
| js | function resetCounter() |
| nodejs | function resetCounter() |
| php | function resetCounter() |
| cpp | int resetCounter() |
| m | - (int) resetCounter |
| pas | function resetCounter() : LongInt |
| vb | function resetCounter() As Integer |
| cs | int resetCounter() |
| java | int resetCounter() |
| py | def resetCounter() |

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

anbutton→set_analogCalibration()
anbutton→setAnalogCalibration()
anbutton.set_analogCalibration()

YAnButton

Starts or stops the calibration process.

| | |
|---------------|--|
| js | function set_analogCalibration(newval) |
| nodejs | function set_analogCalibration(newval) |
| php | function set_analogCalibration(\$newval) |
| cpp | int set_analogCalibration(Y_ANALOGCALIBRATION_enum newval) |
| m | -(int) setAnalogCalibration : (Y_ANALOGCALIBRATION_enum) newval |
| pas | function set_analogCalibration(newval: Integer): integer |
| vb | function set_analogCalibration(ByVal newval As Integer) As Integer |
| cs | int set_analogCalibration(int newval) |
| java | int set_analogCalibration(int newval) |
| py | def set_analogCalibration(newval) |
| cmd | YAnButton target set_analogCalibration newval |

Remember to call the `saveToFlash()` method of the module at the end of the calibration if the modification must be kept.

Parameters :

newval either `Y_ANALOGCALIBRATION_OFF` or `Y_ANALOGCALIBRATION_ON`

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

anbutton→set_calibrationMax()
anbutton→setCalibrationMax()
anbutton.set_calibrationMax()

YAnButton

Changes the maximal calibration value for the input (between 0 and 4095, included), without actually starting the automated calibration.

| | |
|--------|---|
| js | function set_calibrationMax(newval) |
| nodejs | function set_calibrationMax(newval) |
| php | function set_calibrationMax(\$newval) |
| cpp | int set_calibrationMax(int newval) |
| m | - (int) setCalibrationMax : (int) newval |
| pas | function set_calibrationMax(newval: LongInt): integer |
| vb | function set_calibrationMax(ByVal newval As Integer) As Integer |
| cs | int set_calibrationMax(int newval) |
| java | int set_calibrationMax(int newval) |
| py | def set_calibrationMax(newval) |
| cmd | YAnButton target set_calibrationMax newval |

Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval an integer corresponding to the maximal calibration value for the input (between 0 and 4095, included), without actually starting the automated calibration

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

anbutton→set_calibrationMin()
anbutton→setCalibrationMin()
anbutton.set_calibrationMin()

YAnButton

Changes the minimal calibration value for the input (between 0 and 4095, included), without actually starting the automated calibration.

| | |
|--------|---|
| js | function set_calibrationMin(newval) |
| nodejs | function set_calibrationMin(newval) |
| php | function set_calibrationMin(\$newval) |
| cpp | int set_calibrationMin(int newval) |
| m | -(int) setCalibrationMin : (int) newval |
| pas | function set_calibrationMin(newval: LongInt): integer |
| vb | function set_calibrationMin(ByVal newval As Integer) As Integer |
| cs | int set_calibrationMin(int newval) |
| java | int set_calibrationMin(int newval) |
| py | def set_calibrationMin(newval) |
| cmd | YAnButton target set_calibrationMin newval |

Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval an integer corresponding to the minimal calibration value for the input (between 0 and 4095, included), without actually starting the automated calibration

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

anbutton→set_logicalName()
anbutton→setLogicalName()
anbutton.set_logicalName()

YAnButton

Changes the logical name of the analog input.

```
js function set_logicalName( newval)
nodejs function set_logicalName( newval)
php function set_logicalName( $newval)
cpp int set_logicalName( const string& newval)
m -(int) setLogicalName : (NSString*) newval
pas function set_logicalName( newval: string): integer
vb function set_logicalName( ByVal newval As String) As Integer
cs int set_logicalName( string newval)
java int set_logicalName( String newval)
py def set_logicalName( newval)
cmd YAnButton target set_logicalName newval
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the analog input.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

anbutton→set_sensitivity()**YAnButton****anbutton→setSensitivity()|anbutton.set_sensitivity()**

Changes the sensibility for the input (between 1 and 1000) for triggering user callbacks.

| | |
|----------------|--|
| js | <code>function set_sensitivity(newval)</code> |
| node.js | <code>function set_sensitivity(newval)</code> |
| php | <code>function set_sensitivity(\$newval)</code> |
| cpp | <code>int set_sensitivity(int newval)</code> |
| m | <code>-(int) setSensitivity : (int) newval</code> |
| pas | <code>function set_sensitivity(newval: LongInt): integer</code> |
| vb | <code>function set_sensitivity(ByVal newval As Integer) As Integer</code> |
| cs | <code>int set_sensitivity(int newval)</code> |
| java | <code>int set_sensitivity(int newval)</code> |
| py | <code>def set_sensitivity(newval)</code> |
| cmd | <code>YAnButton target set_sensitivity newval</code> |

The sensibility is used to filter variations around a fixed value, but does not preclude the transmission of events when the input value evolves constantly in the same direction. Special case: when the value 1000 is used, the callback will only be thrown when the logical state of the input switches from pressed to released and back. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval an integer corresponding to the sensibility for the input (between 1 and 1000) for triggering user callbacks

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

anbutton→set(userData)**YAnButton****anbutton→setUserData()anbutton.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

```
js   function setUserData( data)
node.js function setUserData( data)
php  function setUserData( $data)
cpp   void setUserData( void* data)
m    -(void) setUserData : (void*) data
pas   procedure setUserData( data: Tobject)
vb    procedure setUserData( ByVal data As Object)
cs    void setUserData( object data)
java  void setUserData( Object data)
py    def setUserData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

anbutton→wait_async()

YAnButton

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context )
nodejs function wait_async( callback, context )
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.4. CarbonDioxide function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_carbondioxide.js'></script>
nodejs var yoctolib = require('yoctolib');
var YCarbonDioxide = yoctolib.YCarbonDioxide;
php require_once('yocto_carbondioxide.php');
cpp #include "yocto_carbondioxide.h"
m #import "yocto_carbondioxide.h"
pas uses yocto_carbondioxide;
vb yocto_carbondioxide.vb
cs yocto_carbondioxide.cs
java import com.yoctopuce.YoctoAPI.YCarbonDioxide;
py from yocto_carbondioxide import *

```

Global functions

yFindCarbonDioxide(func)

Retrieves a CO2 sensor for a given identifier.

yFirstCarbonDioxide()

Starts the enumeration of CO2 sensors currently accessible.

YCarbonDioxide methods

carbondioxide→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

carbondioxide→describe()

Returns a short text that describes unambiguously the instance of the CO2 sensor in the form TYPE (NAME) = SERIAL . FUNCTIONID.

carbondioxide→get_advertisedValue()

Returns the current value of the CO2 sensor (no more than 6 characters).

carbondioxide→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor.

carbondioxide→get_currentValue()

Returns the current value of the CO2 concentration.

carbondioxide→get_errorMessage()

Returns the error message of the latest error with the CO2 sensor.

carbondioxide→get_errorType()

Returns the numerical error code of the latest error with the CO2 sensor.

carbondioxide→get_friendlyName()

Returns a global identifier of the CO2 sensor in the format MODULE_NAME . FUNCTION_NAME.

carbondioxide→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

carbondioxide→get_functionId()

Returns the hardware identifier of the CO2 sensor, without reference to the module.

carbondioxide→get_hardwareId()

Returns the unique hardware identifier of the CO2 sensor in the form SERIAL . FUNCTIONID.

carbondioxide→get_highestValue()

Returns the maximal value observed for the CO2 concentration since the device was started.

carbondioxide→get_logFrequency()

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

carbondioxide→get_logicalName()

Returns the logical name of the CO2 sensor.

carbondioxide→get_lowestValue()

Returns the minimal value observed for the CO2 concentration since the device was started.

carbondioxide→get_module()

Gets the YModule object for the device on which the function is located.

carbondioxide→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

carbondioxide→get_recordedData(startTime, endTime)

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

carbondioxide→get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

carbondioxide→get_resolution()

Returns the resolution of the measured values.

carbondioxide→get_unit()

Returns the measuring unit for the CO2 concentration.

carbondioxide→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

carbondioxide→isOnline()

Checks if the CO2 sensor is currently reachable, without raising any error.

carbondioxide→isOnline_async(callback, context)

Checks if the CO2 sensor is currently reachable, without raising any error (asynchronous version).

carbondioxide→load(msValidity)

Preloads the CO2 sensor cache with a specified validity duration.

carbondioxide→loadCalibrationPoints(rawValues, refValues)

Retrieves error correction data points previously entered using the method calibrateFromPoints.

carbondioxide→load_async(msValidity, callback, context)

Preloads the CO2 sensor cache with a specified validity duration (asynchronous version).

carbondioxide→nextCarbonDioxide()

Continues the enumeration of CO2 sensors started using yFirstCarbonDioxide().

carbondioxide→registerTimedReportCallback(callback)

Registers the callback function that is invoked on every periodic timed notification.

carbondioxide→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

carbondioxide→set_highestValue(newval)

Changes the recorded maximal value observed.

carbondioxide→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

carbondioxide→set_logicalName(newval)

Changes the logical name of the CO2 sensor.

3. Reference

carbondioxide→set_lowestValue(newval)

Changes the recorded minimal value observed.

carbondioxide→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

carbondioxide→set_resolution(newval)

Changes the resolution of the measured physical values.

carbondioxide→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

carbondioxide→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YCarbonDioxide.FindCarbonDioxide() yFindCarbonDioxide() YCarbonDioxide.FindCarbonDioxide()

YCarbonDioxide

Retrieves a CO2 sensor for a given identifier.

| | |
|----------------------|---|
| <code>js</code> | <code>function yFindCarbonDioxide(func)</code> |
| <code>node.js</code> | <code>function FindCarbonDioxide(func)</code> |
| <code>php</code> | <code>function yFindCarbonDioxide(\$func)</code> |
| <code>cpp</code> | <code>YCarbonDioxide* yFindCarbonDioxide(const string& func)</code> |
| <code>m</code> | <code>YCarbonDioxide* yFindCarbonDioxide(NSString* func)</code> |
| <code>pas</code> | <code>function yFindCarbonDioxide(func: string): TYCarbonDioxide</code> |
| <code>vb</code> | <code>function yFindCarbonDioxide(ByVal func As String) As YCarbonDioxide</code> |
| <code>cs</code> | <code>YCarbonDioxide FindCarbonDioxide(string func)</code> |
| <code>java</code> | <code>YCarbonDioxide FindCarbonDioxide(String func)</code> |
| <code>py</code> | <code>def FindCarbonDioxide(func)</code> |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the CO2 sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YCarbonDioxide.isOnline()` to test if the CO2 sensor is indeed online at a given time. In case of ambiguity when looking for a CO2 sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the CO2 sensor

Returns :

a `YCarbonDioxide` object allowing you to drive the CO2 sensor.

YCarbonDioxide.FirstCarbonDioxide() yFirstCarbonDioxide() YCarbonDioxide.FirstCarbonDioxide()

YCarbonDioxide

Starts the enumeration of CO2 sensors currently accessible.

```
js function yFirstCarbonDioxide( )  
nodejs function FirstCarbonDioxide( )  
php function yFirstCarbonDioxide( )  
cpp YCarbonDioxide* yFirstCarbonDioxide( )  
m YCarbonDioxide* yFirstCarbonDioxide( )  
pas function yFirstCarbonDioxide( ): TYCarbonDioxide  
vb function yFirstCarbonDioxide( ) As YCarbonDioxide  
cs YCarbonDioxide FirstCarbonDioxide( )  
java YCarbonDioxide FirstCarbonDioxide( )  
py def FirstCarbonDioxide( )
```

Use the method `YCarbonDioxide.nextCarbonDioxide()` to iterate on next CO2 sensors.

Returns :

a pointer to a `YCarbonDioxide` object, corresponding to the first CO2 sensor currently online, or a null pointer if there are none.

carbondioxide→calibrateFromPoints() carbondioxide.calibrateFromPoints()

YCarbonDioxide

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```

js   function calibrateFromPoints( rawValues, refValues)
nodejs function calibrateFromPoints( rawValues, refValues)
php  function calibrateFromPoints( $rawValues, $refValues)
cpp   int calibrateFromPoints( vector<double> rawValues,
                             vector<double> refValues)

m    -(int) calibrateFromPoints : (NSMutableArray*) rawValues
                  : (NSMutableArray*) refValues

pas  function calibrateFromPoints( rawValues: TDoubleArray,
                                 refValues: TDoubleArray): LongInt

vb   procedure calibrateFromPoints( )
cs    int calibrateFromPoints( List<double> rawValues,
                           List<double> refValues)

java int calibrateFromPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def calibrateFromPoints( rawValues, refValues)
cmd  YCarbonDioxide target calibrateFromPoints rawValues refValues

```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.
refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

carbondioxide→describe()carbon dioxide.describe()**YCarbonDioxide**

Returns a short text that describes unambiguously the instance of the CO2 sensor in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the CO2 sensor (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

carbondioxide→get_advertisedValue()
carbondioxide→advertisedValue()
carbondioxide.get_advertisedValue()

YCarbonDioxide

Returns the current value of the CO2 sensor (no more than 6 characters).

| | |
|---------|--|
| js | function get_advertisedValue() |
| node.js | function get_advertisedValue() |
| php | function get_advertisedValue() |
| cpp | string get_advertisedValue() |
| m | -(NSString*) advertisedValue |
| pas | function get_advertisedValue() : string |
| vb | function get_advertisedValue() As String |
| cs | string get_advertisedValue() |
| java | String get_advertisedValue() |
| py | def get_advertisedValue() |
| cmd | YCarbonDioxide target get_advertisedValue |

Returns :

a string corresponding to the current value of the CO2 sensor (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

carbon dioxide → get_currentRawValue()
carbon dioxide → currentRawValue()
carbon dioxide.get_currentRawValue()**YCarbonDioxide**

Returns the uncalibrated, unrounded raw value returned by the sensor.

js function **get_currentRawValue()**
nodejs function **get_currentRawValue()**
php function **get_currentRawValue()**
cpp double **get_currentRawValue()**
m -(double) currentRawValue
pas function **get_currentRawValue()**: double
vb function **get_currentRawValue()** As Double
cs double **get_currentRawValue()**
java double **get_currentRawValue()**
py def **get_currentRawValue()**
cmd YCarbonDioxide **target get_currentRawValue**

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor

On failure, throws an exception or returns **Y_CURRENTRAWVALUE_INVALID**.

carbondioxide→get_currentValue()
carbondioxide→currentValue()
carbondioxide.get_currentValue()

YCarbonDioxide

Returns the current value of the CO2 concentration.

| | |
|---------|---|
| js | function get_currentValue() |
| node.js | function get_currentValue() |
| php | function get_currentValue() |
| cpp | double get_currentValue() |
| m | -(double) currentValue |
| pas | function get_currentValue() : double |
| vb | function get_currentValue() As Double |
| cs | double get_currentValue() |
| java | double get_currentValue() |
| py | def get_currentValue() |
| cmd | YCarbonDioxide target get_currentValue |

Returns :

a floating point number corresponding to the current value of the CO2 concentration

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

**carbon dioxide → getErrorMessage()
carbon dioxide → errorMessage()
carbon dioxide.getErrorMessage()****YCarbonDioxide**

Returns the error message of the latest error with the CO2 sensor.

| | |
|--------|--|
| js | function getErrorMessage() |
| nodejs | function getErrorMessage() |
| php | function getErrorMessage() |
| cpp | string getErrorMessage() |
| m | -(NSString*) errorMessage |
| pas | function getErrorMessage() : string |
| vb | function getErrorMessage() As String |
| cs | string getErrorMessage() |
| java | String getErrorMessage() |
| py | def getErrorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the CO2 sensor object

carbondioxide→get_errorType()
carbondioxide→errorType()
carbondioxide.get_errorType()**YCarbonDioxide**

Returns the numerical error code of the latest error with the CO2 sensor.

| | |
|---------|--|
| js | function get_errorType() |
| node.js | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType(): YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the CO2 sensor object

carbon dioxide → get_friendlyName()
carbon dioxide → friendlyName()
carbon dioxide.get_friendlyName()**YCarbonDioxide**

Returns a global identifier of the CO2 sensor in the format MODULE_NAME . FUNCTION_NAME.

| | |
|---------|------------------------------------|
| js | function get_friendlyName() |
| node.js | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | - (NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the CO2 sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the CO2 sensor (for exemple: MyCustomName . relay1)

Returns :

a string that uniquely identifies the CO2 sensor using logical names (ex: MyCustomName . relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

carbondioxide→get_functionDescriptor()
carbondioxide→functionDescriptor()
carbondioxide.get_functionDescriptor()

YCarbonDioxide

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

carbon dioxide → get_functionId()
carbon dioxide → functionId()
carbon dioxide.get_functionId()

YCarbonDioxide

Returns the hardware identifier of the CO2 sensor, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the CO2 sensor (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

carbondioxide→get.hardwareId()
carbondioxide→hardwareId()
carbondioxide.get.hardwareId()**YCarbonDioxide**

Returns the unique hardware identifier of the CO2 sensor in the form SERIAL.FUNCTIONID.

| | |
|---------|---|
| js | function get.hardwareId() |
| node.js | function get.hardwareId() |
| php | function get.hardwareId() |
| cpp | string get.hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get.hardwareId() As String |
| cs | string get.hardwareId() |
| java | String get.hardwareId() |
| py | def get.hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the CO2 sensor. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the CO2 sensor (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

carbon dioxide → get_highestValue()
carbon dioxide → highestValue()
carbon dioxide.get_highestValue()**YCarbonDioxide**

Returns the maximal value observed for the CO2 concentration since the device was started.

| | |
|--------|---|
| js | function get_highestValue() |
| nodejs | function get_highestValue() |
| php | function get_highestValue() |
| cpp | double get_highestValue() |
| m | -(double) highestValue |
| pas | function get_highestValue() : double |
| vb | function get_highestValue() As Double |
| cs | double get_highestValue() |
| java | double get_highestValue() |
| py | def get_highestValue() |
| cmd | YCarbonDioxide target get_highestValue |

Returns :

a floating point number corresponding to the maximal value observed for the CO2 concentration since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

carbondioxide→get_logFrequency()
carbondioxide→logFrequency()
carbondioxide.get_logFrequency()

YCarbonDioxide

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
js   function get_logFrequency( )  
nodejs function get_logFrequency( )  
php  function get_logFrequency( )  
cpp   string get_logFrequency( )  
m    -(NSString*) logFrequency  
pas   function get_logFrequency( ): string  
vb    function get_logFrequency( ) As String  
cs   string get_logFrequency( )  
java  String get_logFrequency( )  
py    def get_logFrequency()  
cmd   YCarbonDioxide target get_logFrequency
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns `Y_LOGFREQUENCY_INVALID`.

carbon dioxide → get_logicalName()
carbon dioxide → logicalName()
carbon dioxide.get_logicalName()**YCarbonDioxide**

Returns the logical name of the CO2 sensor.

```
js function get_logicalName( )
nodejs function get_logicalName( )
php function get_logicalName( )
cpp string get_logicalName( )
m -(NSString*) logicalName
pas function get_logicalName( ): string
vb function get_logicalName( ) As String
cs string get_logicalName( )
java String get_logicalName( )
py def get_logicalName( )
cmd YCarbonDioxide target get_logicalName
```

Returns :

a string corresponding to the logical name of the CO2 sensor. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

carbondioxide→get_lowestValue()
carbondioxide→lowestValue()
carbondioxide.get_lowestValue()

YCarbonDioxide

Returns the minimal value observed for the CO2 concentration since the device was started.

| | |
|---------|--|
| js | function get_lowestValue() |
| node.js | function get_lowestValue() |
| php | function get_lowestValue() |
| cpp | double get_lowestValue() |
| m | -(double) lowestValue |
| pas | function get_lowestValue(): double |
| vb | function get_lowestValue() As Double |
| cs | double get_lowestValue() |
| java | double get_lowestValue() |
| py | def get_lowestValue() |
| cmd | YCarbonDioxide target get_lowestValue |

Returns :

a floating point number corresponding to the minimal value observed for the CO2 concentration since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

**carbon dioxide → get_module()
carbon dioxide → module()
carbon dioxide.get_module()****YCarbonDioxide**

Gets the `YModule` object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

carbondioxide→get_module_async()
carbondioxide→module_async()**YCarbonDioxide**

Gets the YModule object for the device on which the function is located (asynchronous version).

```
js   function get_module_async( callback, context )
nodejs function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned YModule object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested YModule object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

carbondioxide→`get_recordedData()`
carbondioxide→`recordedData()`
carbondioxide.`get_recordedData()`

YCarbonDioxide

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the `DataSet` class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measurement, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of `YDataSet`, providing access to historical data. Past measures can be loaded progressively using methods from the `YDataSet` object.

carbondioxide→get_reportFrequency()
carbondioxide→reportFrequency()
carbondioxide.get_reportFrequency()**YCarbonDioxide**

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
js   function get_reportFrequency( )
nodejs function get_reportFrequency( )
php  function get_reportFrequency( )
cpp   string get_reportFrequency( )
m    -(NSString*) reportFrequency
pas   function get_reportFrequency( ): string
vb    function get_reportFrequency( ) As String
cs   string get_reportFrequency( )
java  String get_reportFrequency( )
py    def get_reportFrequency( )
cmd   YCarbonDioxide target get_reportFrequency
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns `Y_REPORTFREQUENCY_INVALID`.

carbondioxide→get_resolution()
carbondioxide→resolution()
carbondioxide.get_resolution()

YCarbonDioxide

Returns the resolution of the measured values.

```
js function get_resolution( )
nodejs function get_resolution( )
php function get_resolution( )
cpp double get_resolution( )
m -(double) resolution
pas function get_resolution( ): double
vb function get_resolution( ) As Double
cs double get_resolution( )
java double get_resolution( )
py def get_resolution( )
cmd YCarbonDioxide target get_resolution
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

carbondioxide→get_unit()**YCarbonDioxide****carbondioxide→unit()carbondioxide.get_unit()**

Returns the measuring unit for the CO2 concentration.

| | |
|--------|---------------------------------------|
| js | function get_unit() |
| nodejs | function get_unit() |
| php | function get_unit() |
| cpp | string get_unit() |
| m | -(NSString*) unit |
| pas | function get_unit() : string |
| vb | function get_unit() As String |
| cs | string get_unit() |
| java | String get_unit() |
| py | def get_unit() |
| cmd | YCarbonDioxide target get_unit |

Returns :

a string corresponding to the measuring unit for the CO2 concentration

On failure, throws an exception or returns **Y_UNIT_INVALID**.

carbon dioxide → get(userData)
carbon dioxide → userData()
carbon dioxide.get(userData)**YCarbonDioxide**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
js function get(userData) {  
nodejs function get(userData) {  
php function get(userData) {  
cpp void * get(userData) {  
m -(void*) userData  
pas function get(userData): Tobject  
vb function get(userData) As Object  
cs object get(userData)  
java Object get(userData)  
py def get(userData)
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

carbondioxide→isOnline()**YCarbonDioxide**

Checks if the CO2 sensor is currently reachable, without raising any error.

| | |
|---------|--|
| js | function isOnline() |
| node.js | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the CO2 sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the CO2 sensor.

Returns :

`true` if the CO2 sensor can be reached, and `false` otherwise

carbondioxide→isOnline_async()**YCarbonDioxide**

Checks if the CO2 sensor is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context )
nodejs function isOnline_async( callback, context )
```

If there is a cached value for the CO2 sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

carbondioxide→load()carbon dioxide.load()**YCarbonDioxide**

Preloads the CO2 sensor cache with a specified validity duration.

| | |
|----------------------|--|
| <code>js</code> | <code>function load(msValidity)</code> |
| <code>node.js</code> | <code>function load(msValidity)</code> |
| <code>php</code> | <code>function load(\$msValidity)</code> |
| <code>cpp</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>m</code> | <code>-(YRETCODE) load : (int) msValidity</code> |
| <code>pas</code> | <code>function load(msValidity: integer): YRETCODE</code> |
| <code>vb</code> | <code>function load(ByVal msValidity As Integer) As YRETCODE</code> |
| <code>cs</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>java</code> | <code>int load(long msValidity)</code> |
| <code>py</code> | <code>def load(msValidity)</code> |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

carbondioxide→loadCalibrationPoints() carbondioxide.loadCalibrationPoints()

YCarbonDioxide

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```

js   function loadCalibrationPoints( rawValues, refValues)
nodejs function loadCalibrationPoints( rawValues, refValues)
php  function loadCalibrationPoints( &$rawValues, &$refValues)
cpp   int loadCalibrationPoints( vector<double>& rawValues,
                                vector<double>& refValues)

m    -(int) loadCalibrationPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues

pas  function loadCalibrationPoints( var rawValues: TDoubleArray,
                           var refValues: TDoubleArray): LongInt

vb   procedure loadCalibrationPoints( )
cs   int loadCalibrationPoints( List<double> rawValues,
                           List<double> refValues)

java int loadCalibrationPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def loadCalibrationPoints( rawValues, refValues)
cmd  YCarbonDioxide target loadCalibrationPoints rawValues refValues

```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

carbondioxide→load_async()

YCarbonDioxide

Preloads the CO2 sensor cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

carbon dioxide → nextCarbonDioxide()
carbon dioxide.nextCarbonDioxide()**YCarbonDioxide**

Continues the enumeration of CO2 sensors started using `yFirstCarbonDioxide()`.

| | |
|----------------------|--|
| <code>js</code> | function nextCarbonDioxide() |
| <code>node.js</code> | function nextCarbonDioxide() |
| <code>php</code> | function nextCarbonDioxide() |
| <code>cpp</code> | YCarbonDioxide * nextCarbonDioxide() |
| <code>m</code> | -(YCarbonDioxide*) nextCarbonDioxide |
| <code>pas</code> | function nextCarbonDioxide(): TYCarbonDioxide |
| <code>vb</code> | function nextCarbonDioxide() As YCarbonDioxide |
| <code>cs</code> | YCarbonDioxide nextCarbonDioxide() |
| <code>java</code> | YCarbonDioxide nextCarbonDioxide() |
| <code>py</code> | def nextCarbonDioxide() |

Returns :

a pointer to a `YCarbonDioxide` object, corresponding to a CO2 sensor currently online, or a null pointer if there are no more CO2 sensors to enumerate.

carbondioxide→registerTimedReportCallback() carbondioxide.registerTimedReportCallback()

YCarbonDioxide

Registers the callback function that is invoked on every periodic timed notification.

| | |
|---------|--|
| js | function registerTimedReportCallback(callback) |
| node.js | function registerTimedReportCallback(callback) |
| php | function registerTimedReportCallback(\$callback) |
| cpp | int registerTimedReportCallback(YCarbonDioxideTimedReportCallback callback) |
| m | -(int) registerTimedReportCallback : (YCarbonDioxideTimedReportCallback) callback |
| pas | function registerTimedReportCallback(callback : TYCarbonDioxideTimedReportCallback): LongInt |
| vb | function registerTimedReportCallback() As Integer |
| cs | int registerTimedReportCallback(TimedReportCallback callback) |
| java | int registerTimedReportCallback(TimedReportCallback callback) |
| py | def registerTimedReportCallback(callback) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

carbon dioxide → registerValueCallback() carbon dioxide.registerValueCallback()

YCarbonDioxide

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YCarbonDioxideValueCallback callback )
m    -(int) registerValueCallback : (YCarbonDioxideValueCallback) callback
pas   function registerValueCallback( callback: TYCarbonDioxideValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

carbondioxide→set_highestValue()
carbondioxide→setHighestValue()
carbondioxide.set_highestValue()

YCarbonDioxide

Changes the recorded maximal value observed.

```
js function set_highestValue( newval)
nodejs function set_highestValue( newval)
php function set_highestValue( $newval)
cpp int set_highestValue( double newval)
m -(int) setHighestValue : (double) newval
pas function set_highestValue( newval: double): integer
vb function set_highestValue( ByVal newval As Double) As Integer
cs int set_highestValue( double newval)
java int set_highestValue( double newval)
py def set_highestValue( newval)
cmd YCarbonDioxide target set_highestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

carbon dioxide → set_logFrequency()
carbon dioxide → setLogFrequency()
carbon dioxide.set_logFrequency()

YCarbonDioxide

Changes the datalogger recording frequency for this function.

```
js   function set_logFrequency( newval)
nodejs function set_logFrequency( newval)
php  function set_logFrequency( $newval)
cpp   int set_logFrequency( const string& newval)
m    -(int) setLogFrequency : (NSString*) newval
pas   function set_logFrequency( newval: string): integer
vb    function set_logFrequency( ByVal newval As String) As Integer
cs    int set_logFrequency( string newval)
java  int set_logFrequency( String newval)
py    def set_logFrequency( newval)
cmd   YCarbonDioxide target set_logFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

carbondioxide→set_logicalName()
carbondioxide→setLogicalName()
carbondioxide.set_logicalName()

YCarbonDioxide

Changes the logical name of the CO2 sensor.

| | |
|---------------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YCarbonDioxide target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the CO2 sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

carbon dioxide → set_lowestValue()
carbon dioxide → setLowestValue()
carbon dioxide.set_lowestValue()

YCarbonDioxide

Changes the recorded minimal value observed.

```
js function set_lowestValue( newval)
nodejs function set_lowestValue( newval)
php function set_lowestValue( $newval)
cpp int set_lowestValue( double newval)
m -(int) setLowestValue : (double) newval
pas function set_lowestValue( newval: double): integer
vb function set_lowestValue( ByVal newval As Double) As Integer
cs int set_lowestValue( double newval)
java int set_lowestValue( double newval)
py def set_lowestValue( newval)
cmd YCarbonDioxide target set_lowestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

carbondioxide→set_reportFrequency()
carbondioxide→setReportFrequency()
carbondioxide.set_reportFrequency()

YCarbonDioxide

Changes the timed value notification frequency for this function.

| | |
|---------|---|
| js | function set_reportFrequency(newval) |
| node.js | function set_reportFrequency(newval) |
| php | function set_reportFrequency(\$newval) |
| cpp | int set_reportFrequency(const string& newval) |
| m | -(int) setReportFrequency : (NSString*) newval |
| pas | function set_reportFrequency(newval: string): integer |
| vb | function set_reportFrequency(ByVal newval As String) As Integer |
| cs | int set_reportFrequency(string newval) |
| java | int set_reportFrequency(String newval) |
| py | def set_reportFrequency(newval) |
| cmd | YCarbonDioxide target set_reportFrequency newval |

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

carbondioxide→set_resolution()
carbondioxide→setResolution()
carbondioxide.set_resolution()

YCarbonDioxide

Changes the resolution of the measured physical values.

```
js function set_resolution( newval)
nodejs function set_resolution( newval)
php function set_resolution( $newval)
cpp int set_resolution( double newval)
m -(int) setResolution : (double) newval
pas function set_resolution( newval: double): integer
vb function set_resolution( ByVal newval As Double) As Integer
cs int set_resolution( double newval)
java int set_resolution( double newval)
py def set_resolution( newval)
cmd YCarbonDioxide target set_resolution newval
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

carbondioxide→set(userData)
carbondioxide→setUserData()
carbondioxide.set(userData)

YCarbonDioxide

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|---|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData \$data) |
| cpp | void set(userData void* data) |
| m | -(void) setUserData : (void*) data |
| pas | procedure set(userData data: Tobject) |
| vb | procedure set(userData ByVal data As Object) |
| cs | void set(userData object data) |
| java | void set(userData Object data) |
| py | def set(userData data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

carbondioxide→wait_async()

YCarbonDioxide

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.5. ColorLed function interface

Yoctopuce application programming interface allows you to drive a color led using RGB coordinates as well as HSL coordinates. The module performs all conversions from RGB to HSL automatically. It is then self-evident to turn on a led with a given hue and to progressively vary its saturation or lightness. If needed, you can find more information on the difference between RGB and HSL in the section following this one.

In order to use the functions described here, you should include:

| | |
|---------|--|
| js | <script type='text/javascript' src='yocto_colorled.js'></script> |
| node.js | var yoctolib = require('yoctolib'); |
| php | var YColorLed = yoctolib.YColorLed; |
| cpp | require_once('yocto_colorled.php'); |
| m | #include "yocto_colorled.h" |
| pas | #import "yocto_colorled.h" |
| vb | uses yocto_colorled; |
| cs | yocto_colorled.vb |
| java | yocto_colorled.cs |
| py | import com.yoctopuce.YoctoAPI.YColorLed; |
| | from yocto_colorled import * |

Global functions

yFindColorLed(func)

Retrieves an RGB led for a given identifier.

yFirstColorLed()

Starts the enumeration of RGB leds currently accessible.

YColorLed methods

colorled→describe()

Returns a short text that describes unambiguously the instance of the RGB led in the form TYPE (NAME) = SERIAL . FUNCTIONID.

colorled→get_advertisedValue()

Returns the current value of the RGB led (no more than 6 characters).

colorled→get_errorMessage()

Returns the error message of the latest error with the RGB led.

colorled→get_errorType()

Returns the numerical error code of the latest error with the RGB led.

colorled→get_friendlyName()

Returns a global identifier of the RGB led in the format MODULE_NAME . FUNCTION_NAME.

colorled→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

colorled→get_functionId()

Returns the hardware identifier of the RGB led, without reference to the module.

colorled→get_hardwareId()

Returns the unique hardware identifier of the RGB led in the form SERIAL . FUNCTIONID.

colorled→get_hslColor()

Returns the current HSL color of the led.

colorled→get_logicalName()

Returns the logical name of the RGB led.

3. Reference

| | |
|---|--|
| colorled→get_module() | Gets the YModule object for the device on which the function is located. |
| colorled→get_module_async(callback, context) | Gets the YModule object for the device on which the function is located (asynchronous version). |
| colorled→get_rgbColor() | Returns the current RGB color of the led. |
| colorled→get_rgbColorAtPowerOn() | Returns the configured color to be displayed when the module is turned on. |
| colorled→get_userData() | Returns the value of the userData attribute, as previously stored using method set(userData). |
| colorled→hslMove(hsl_target, ms_duration) | Performs a smooth transition in the HSL color space between the current color and a target color. |
| colorled→isOnline() | Checks if the RGB led is currently reachable, without raising any error. |
| colorled→isOnline_async(callback, context) | Checks if the RGB led is currently reachable, without raising any error (asynchronous version). |
| colorled→load(msValidity) | Preloads the RGB led cache with a specified validity duration. |
| colorled→load_async(msValidity, callback, context) | Preloads the RGB led cache with a specified validity duration (asynchronous version). |
| colorled→nextColorLed() | Continues the enumeration of RGB leds started using yFirstColorLed(). |
| colorled→registerValueCallback(callback) | Registers the callback function that is invoked on every change of advertised value. |
| colorled→rgbMove(rgb_target, ms_duration) | Performs a smooth transition in the RGB color space between the current color and a target color. |
| colorled→set_hslColor(newval) | Changes the current color of the led, using a color HSL. |
| colorled→set_logicalName(newval) | Changes the logical name of the RGB led. |
| colorled→set_rgbColor(newval) | Changes the current color of the led, using a RGB color. |
| colorled→set_rgbColorAtPowerOn(newval) | Changes the color that the led will display by default when the module is turned on. |
| colorled→set_userData(data) | Stores a user context provided as argument in the userData attribute of the function. |
| colorled→wait_async(callback, context) | Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function. |

YColorLed.FindColorLed() yFindColorLed()YColorLed.FindColorLed()

YColorLed

Retrieves an RGB led for a given identifier.

| | |
|--------|---|
| js | function yFindColorLed(func) |
| nodejs | function FindColorLed(func) |
| php | function yFindColorLed(\$func) |
| cpp | YColorLed* yFindColorLed(const string& func) |
| m | YColorLed* yFindColorLed(NSString* func) |
| pas | function yFindColorLed(func: string): TYColorLed |
| vb | function yFindColorLed(ByVal func As String) As YColorLed |
| cs | YColorLed FindColorLed(string func) |
| java | YColorLed FindColorLed(String func) |
| py | def FindColorLed(func) |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the RGB led is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YColorLed.isOnline()` to test if the RGB led is indeed online at a given time. In case of ambiguity when looking for an RGB led by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the RGB led

Returns :

a `YColorLed` object allowing you to drive the RGB led.

YColorLed.FirstColorLed()**YColorLed****yFirstColorLed() YColorLed.FirstColorLed()**

Starts the enumeration of RGB leds currently accessible.

```
js function yFirstColorLed( )
node.js function FirstColorLed( )
php function yFirstColorLed( )
cpp YColorLed* yFirstColorLed( )
m YColorLed* yFirstColorLed( )
pas function yFirstColorLed( ): TYColorLed
vb function yFirstColorLed( ) As YColorLed
cs YColorLed FirstColorLed( )
java YColorLed FirstColorLed( )
py def FirstColorLed( )
```

Use the method `YColorLed.nextColorLed()` to iterate on next RGB leds.

Returns :

a pointer to a `YColorLed` object, corresponding to the first RGB led currently online, or a `null` pointer if there are none.

colorled→describe()colorled.describe()**YColorLed**

Returns a short text that describes unambiguously the instance of the RGB led in the form TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--|
| js | function describe () |
| nodejs | function describe () |
| php | function describe () |
| cpp | string describe () |
| m | -(NSString*) describe |
| pas | function describe (): string |
| vb | function describe () As String |
| cs | string describe () |
| java | String describe () |
| py | def describe () |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the RGB led (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

colorled→get_advertisedValue()
colorled→advertisedValue()
colorled.get_advertisedValue()**YColorLed**

Returns the current value of the RGB led (no more than 6 characters).

| | |
|--------|---|
| js | function get_advertisedValue() |
| nodejs | function get_advertisedValue() |
| php | function get_advertisedValue() |
| cpp | string get_advertisedValue() |
| m | -(NSString*) advertisedValue |
| pas | function get_advertisedValue(): string |
| vb | function get_advertisedValue() As String |
| cs | string get_advertisedValue() |
| java | String get_advertisedValue() |
| py | def get_advertisedValue() |
| cmd | YColorLed target get_advertisedValue |

Returns :

a string corresponding to the current value of the RGB led (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

**colorled→getErrorMessage()
colorled→errorMessage()
colorled.getErrorMessage()****YColorLed**

Returns the error message of the latest error with the RGB led.

| | |
|---------|---------------------------------------|
| js | function getErrorMessage() |
| node.js | function getErrorMessage() |
| php | function getErrorMessage() |
| cpp | string getErrorMessage() |
| m | -(NSString*) errorMessage |
| pas | function getErrorMessage(): string |
| vb | function getErrorMessage() As String |
| cs | string getErrorMessage() |
| java | String getErrorMessage() |
| py | def getErrorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the RGB led object

colorled→get_errorType()**YColorLed****colorled→errorType()colorled.get_errorType()**

Returns the numerical error code of the latest error with the RGB led.

| | |
|---------|--|
| js | function get_errorType() |
| node.js | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType() : YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the RGB led object

colorled→get_friendlyName()**YColorLed****colorled→friendlyName()colorled.get_friendlyName()**

Returns a global identifier of the RGB led in the format MODULE_NAME . FUNCTION_NAME.

```
js function get_friendlyName( )  
nodejs function get_friendlyName( )  
php function get_friendlyName( )  
cpp string get_friendlyName( )  
m -(NSString*) friendlyName  
cs string get_friendlyName( )  
java String get_friendlyName( )  
py def get_friendlyName( )
```

The returned string uses the logical names of the module and of the RGB led if they are defined, otherwise the serial number of the module and the hardware identifier of the RGB led (for exemple: MyCustomName . relay1)

Returns :

a string that uniquely identifies the RGB led using logical names (ex: MyCustomName . relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

**colorled→get_functionDescriptor()
colorled→functionDescriptor()
colorled.get_functionDescriptor()****YColorLed**

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|--------|---|
| js | function get_functionDescriptor() |
| nodejs | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

colorled→get_functionId()**YColorLed****colorled→functionId()colorled.get_functionId()**

Returns the hardware identifier of the RGB led, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the RGB led (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

colorled→get_hardwareId()**YColorLed****colorled→hardwareId()colorled.get_hardwareId()**

Returns the unique hardware identifier of the RGB led in the form SERIAL.FUNCTIONID.

| | |
|---------|--------------------------------------|
| js | function get_hardwareId() |
| node.js | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the RGB led. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the RGB led (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

colorled→get_hslColor()**colorled→hslColor()colorled.get_hslColor()****YColorLed**

Returns the current HSL color of the led.

```
js   function get_hslColor( )  
nodejs function get_hslColor( )  
php  function get_hslColor( )  
cpp   int get_hslColor( )  
m    -(int) hslColor  
pas   function get_hslColor( ): LongInt  
vb    function get_hslColor( ) As Integer  
cs    int get_hslColor( )  
java  int get_hslColor( )  
py    def get_hslColor( )  
cmd   YColorLed target get_hslColor
```

Returns :

an integer corresponding to the current HSL color of the led

On failure, throws an exception or returns Y_HSLCOLOR_INVALID.

colorled→get_logicalName()**YColorLed****colorled→logicalName()colorled.get_logicalName()**

Returns the logical name of the RGB led.

```
js function get_logicalName( )
node.js function get_logicalName( )
php function get_logicalName( )
cpp string get_logicalName( )
m -(NSString*) logicalName
pas function get_logicalName( ): string
vb function get_logicalName( ) As String
cs string get_logicalName( )
java String get_logicalName( )
py def get_logicalName( )
cmd YColorLed target get_logicalName
```

Returns :

a string corresponding to the logical name of the RGB led. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

colorled→get_module()**YColorLed****colorled→module()colorled.get_module()**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

colorled→get_module_async()
colorled→module_async()**YColorLed**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

colorled→get_rgbColor()**colorled→rgbColor()colorled.get_rgbColor()****YColorLed**

Returns the current RGB color of the led.

| | |
|--------|--|
| js | function get_rgbColor() |
| nodejs | function get_rgbColor() |
| php | function get_rgbColor() |
| cpp | int get_rgbColor() |
| m | -(int) rgbColor |
| pas | function get_rgbColor(): LongInt |
| vb | function get_rgbColor() As Integer |
| cs | int get_rgbColor() |
| java | int get_rgbColor() |
| py | def get_rgbColor() |
| cmd | YColorLed target get_rgbColor |

Returns :

an integer corresponding to the current RGB color of the led

On failure, throws an exception or returns **Y_RGBCOLOR_INVALID**.

colorled→get_rgbColorAtPowerOn()
colorled→rgbColorAtPowerOn()
colorled.get_rgbColorAtPowerOn()**YColorLed**

Returns the configured color to be displayed when the module is turned on.

js function **get_rgbColorAtPowerOn()**
nodejs function **get_rgbColorAtPowerOn()**
php function **get_rgbColorAtPowerOn()**
cpp int **get_rgbColorAtPowerOn()**
m -(int) **rgbColorAtPowerOn**
pas function **get_rgbColorAtPowerOn(): LongInt**
vb function **get_rgbColorAtPowerOn() As Integer**
cs int **get_rgbColorAtPowerOn()**
java int **get_rgbColorAtPowerOn()**
py def **get_rgbColorAtPowerOn()**
cmd YColorLed target **get_rgbColorAtPowerOn**

Returns :

an integer corresponding to the configured color to be displayed when the module is turned on

On failure, throws an exception or returns **Y_RGBCOLORATPOWERON_INVALID**.

colorled→get(userData)**YColorLed****colorled→userData()colorled.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|---|
| js | <code>function get(userData) </code> |
| nodejs | <code>function get(userData) </code> |
| php | <code>function get(userData) </code> |
| cpp | <code>void * get(userData) </code> |
| m | <code>-(void*) userData</code> |
| pas | <code>function get(userData): Tobject</code> |
| vb | <code>function get(userData) As Object</code> |
| cs | <code>object get(userData) </code> |
| java | <code>Object get(userData) </code> |
| py | <code>def get(userData) </code> |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

colorled→hslMove()colorled.hslMove()

YColorLed

Performs a smooth transition in the HSL color space between the current color and a target color.

```
js function hslMove( hsl_target, ms_duration)
nodejs function hslMove( hsl_target, ms_duration)
php function hslMove( $hsl_target, $ms_duration)
cpp int hslMove( int hsl_target, int ms_duration)
m -(int) hslMove : (int) hsl_target : (int) ms_duration
pas function hslMove( hsl_target: LongInt, ms_duration: LongInt): integer
vb function hslMove( ByVal hsl_target As Integer,
                     ByVal ms_duration As Integer) As Integer
cs int hslMove( int hsl_target, int ms_duration)
java int hslMove( int hsl_target, int ms_duration)
py def hslMove( hsl_target, ms_duration)
cmd YColorLed target hslMove hsl_target ms_duration
```

Parameters :

hsl_target desired HSL color at the end of the transition

ms_duration duration of the transition, in millisecond

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

colorled→isOnline()colorled.isOnline()**YColorLed**

Checks if the RGB led is currently reachable, without raising any error.

| | |
|---------|--|
| js | function isOnline() |
| node.js | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the RGB led in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the RGB led.

Returns :

true if the RGB led can be reached, and false otherwise

colorled→isOnline_async()

YColorLed

Checks if the RGB led is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the RGB led in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

colorled→load()colorled.load()**YColorLed**

Preloads the RGB led cache with a specified validity duration.

| | |
|----------------|--|
| js | <code>function load(msValidity)</code> |
| node.js | <code>function load(msValidity)</code> |
| php | <code>function load(\$msValidity)</code> |
| cpp | <code>YRETCODE load(int msValidity)</code> |
| m | <code>-(YRETCODE) load : (int) msValidity</code> |
| pas | <code>function load(msValidity: integer): YRETCODE</code> |
| vb | <code>function load(ByVal msValidity As Integer) As YRETCODE</code> |
| cs | <code>YRETCODE load(int msValidity)</code> |
| java | <code>int load(long msValidity)</code> |
| py | <code>def load(msValidity)</code> |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

colorled→load_async()

YColorLed

Preloads the RGB led cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

colorled→nextColorLed()colorled.nextColorLed()**YColorLed**

Continues the enumeration of RGB leds started using `yFirstColorLed()`.

| | |
|--------|---|
| js | function nextColorLed() |
| nodejs | function nextColorLed() |
| php | function nextColorLed() |
| cpp | YColorLed * nextColorLed() |
| m | -(YColorLed*) nextColorLed |
| pas | function nextColorLed() : TYColorLed |
| vb | function nextColorLed() As YColorLed |
| cs | YColorLed nextColorLed() |
| java | YColorLed nextColorLed() |
| py | def nextColorLed() |

Returns :

a pointer to a `YColorLed` object, corresponding to an RGB led currently online, or a `null` pointer if there are no more RGB leds to enumerate.

colorled→registerValueCallback() colorled.registerValueCallback()

YColorLed

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YColorLedValueCallback callback )
m    -(int) registerValueCallback : (YColorLedValueCallback) callback
pas   function registerValueCallback( callback: TYColorLedValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

colorled→rgbMove()colorled.rgbMove()**YColorLed**

Performs a smooth transition in the RGB color space between the current color and a target color.

| | |
|---------------|---|
| js | function rgbMove(rgb_target , ms_duration) |
| nodejs | function rgbMove(rgb_target , ms_duration) |
| php | function rgbMove(\$ rgb_target , \$ ms_duration) |
| cpp | int rgbMove(int rgb_target , int ms_duration) |
| m | -(int) rgbMove : (int) rgb_target : (int) ms_duration |
| pas | function rgbMove(rgb_target : LongInt, ms_duration : LongInt): integer |
| vb | function rgbMove(ByVal rgb_target As Integer, ByVal ms_duration As Integer) As Integer |
| cs | int rgbMove(int rgb_target , int ms_duration) |
| java | int rgbMove(int rgb_target , int ms_duration) |
| py | def rgbMove(rgb_target , ms_duration) |
| cmd | YColorLed target rgbMove rgb_target ms_duration |

Parameters :

rgb_target desired RGB color at the end of the transition

ms_duration duration of the transition, in millisecond

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

colorled→set_hslColor()**YColorLed****colorled→setHslColor()colorled.set_hslColor()**

Changes the current color of the led, using a color HSL.

```
js function set_hslColor( newval)
node.js function set_hslColor( newval)
php function set_hslColor( $newval)
cpp int set_hslColor( int newval)
m -(int) setHslColor : (int) newval
pas function set_hslColor( newval: LongInt): integer
vb function set_hslColor( ByVal newval As Integer) As Integer
cs int set_hslColor( int newval)
java int set_hslColor( int newval)
py def set_hslColor( newval)
cmd YColorLed target set_hslColor newval
```

Encoding is done as follows: 0xHHSSL.

Parameters :

newval an integer corresponding to the current color of the led, using a color HSL

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

colorled→set_logicalName()
colorled→setLogicalName()
colorled.set_logicalName()

YColorLed

Changes the logical name of the RGB led.

| | |
|---------------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YColorLed target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the RGB led.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

colorled→set_rgbColor()**YColorLed****colorled→setRgbColor()colorled.set_rgbColor()**

Changes the current color of the led, using a RGB color.

| | |
|---------|---|
| js | function set_rgbColor(newval) |
| node.js | function set_rgbColor(newval) |
| php | function set_rgbColor(\$newval) |
| cpp | int set_rgbColor(int newval) |
| m | -{int) setRgbColor : (int) newval |
| pas | function set_rgbColor(newval: LongInt): integer |
| vb | function set_rgbColor(ByVal newval As Integer) As Integer |
| cs | int set_rgbColor(int newval) |
| java | int set_rgbColor(int newval) |
| py | def set_rgbColor(newval) |
| cmd | YColorLed target set_rgbColor newval |

Encoding is done as follows: 0xRRGGBB.

Parameters :

newval an integer corresponding to the current color of the led, using a RGB color

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

colorled→set_rgbColorAtPowerOn()
colorled→setRgbColorAtPowerOn()
colorled.set_rgbColorAtPowerOn()

YColorLed

Changes the color that the led will display by default when the module is turned on.

| | |
|---------|--|
| js | function set_rgbColorAtPowerOn(newval) |
| node.js | function set_rgbColorAtPowerOn(newval) |
| php | function set_rgbColorAtPowerOn(\$newval) |
| cpp | int set_rgbColorAtPowerOn(int newval) |
| m | -(int) setRgbColorAtPowerOn : (int) newval |
| pas | function set_rgbColorAtPowerOn(newval: LongInt): integer |
| vb | function set_rgbColorAtPowerOn(ByVal newval As Integer) As Integer |
| cs | int set_rgbColorAtPowerOn(int newval) |
| java | int set_rgbColorAtPowerOn(int newval) |
| py | def set_rgbColorAtPowerOn(newval) |
| cmd | YColorLed target set_rgbColorAtPowerOn newval |

This color will be displayed as soon as the module is powered on. Remember to call the `saveToFlash()` method of the module if the change should be kept.

Parameters :

newval an integer corresponding to the color that the led will display by default when the module is turned on

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

colorled→set(userData)**YColorLed****colorled→setUserData()colorled.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

```
js   function setUserData( data)
node.js function setUserData( data)
php  function setUserData( $data)
cpp   void setUserData( void* data)
m    -(void) setUserData : (void*) data
pas   procedure setUserData( data: Tobject)
vb    procedure setUserData( ByVal data As Object)
cs    void setUserData( object data)
java  void setUserData( Object data)
py    def setUserData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

colorled→wait_async()

YColorLed

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context )
nodejs function wait_async( callback, context )
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.6. Compass function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_compass.js'></script>
nodejs var yoctolib = require('yoctolib');
var YCompass = yoctolib.YCompass;
php require_once('yocto_compass.php');
cpp #include "yocto_compass.h"
m #import "yocto_compass.h"
pas uses yocto_compass;
vb yocto_compass.vb
cs yocto_compass.cs
java import com.yoctopuce.YoctoAPI.YCompass;
py from yocto_compass import *

```

Global functions

yFindCompass(func)

Retrieves a compass for a given identifier.

yFirstCompass()

Starts the enumeration of compasses currently accessible.

YCompass methods

compass→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

compass→describe()

Returns a short text that describes unambiguously the instance of the compass in the form TYPE(NAME)=SERIAL.FUNCTIONID.

compass→get_advertisedValue()

Returns the current value of the compass (no more than 6 characters).

compass→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor.

compass→get_currentValue()

Returns the current value of the relative bearing.

compass→get_errorMessage()

Returns the error message of the latest error with the compass.

compass→get_errorType()

Returns the numerical error code of the latest error with the compass.

compass→get_friendlyName()

Returns a global identifier of the compass in the format MODULE_NAME.FUNCTION_NAME.

compass→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

compass→get_functionId()

Returns the hardware identifier of the compass, without reference to the module.

compass→get_hardwareId()

Returns the unique hardware identifier of the compass in the form SERIAL.FUNCTIONID.

compass→get_highestValue()

Returns the maximal value observed for the relative bearing since the device was started.

compass→get_logFrequency()

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

compass→get_logicalName()

Returns the logical name of the compass.

compass→get_lowestValue()

Returns the minimal value observed for the relative bearing since the device was started.

compass→get_magneticHeading()

Returns the magnetic heading, regardless of the configured bearing.

compass→get_module()

Gets the YModule object for the device on which the function is located.

compass→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

compass→get_recordedData(startTime, endTime)

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

compass→get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

compass→get_resolution()

Returns the resolution of the measured values.

compass→get_unit()

Returns the measuring unit for the relative bearing.

compass→get(userData)

Returns the value of the userData attribute, as previously stored using method set(userData).

compass→isOnline()

Checks if the compass is currently reachable, without raising any error.

compass→isOnline_async(callback, context)

Checks if the compass is currently reachable, without raising any error (asynchronous version).

compass→load(msValidity)

Preloads the compass cache with a specified validity duration.

compass→loadCalibrationPoints(rawValues, refValues)

Retrieves error correction data points previously entered using the method calibrateFromPoints.

compass→load_async(msValidity, callback, context)

Preloads the compass cache with a specified validity duration (asynchronous version).

compass→nextCompass()

Continues the enumeration of compasses started using yFirstCompass().

compass→registerTimedReportCallback(callback)

Registers the callback function that is invoked on every periodic timed notification.

compass→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

compass→set_highestValue(newval)

Changes the recorded maximal value observed.

compass→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

3. Reference

compass→set_logicalName(newval)

Changes the logical name of the compass.

compass→set_lowestValue(newval)

Changes the recorded minimal value observed.

compass→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

compass→set_resolution(newval)

Changes the resolution of the measured physical values.

compass→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

compass→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YCompass.FindCompass() yFindCompass()YCompass.FindCompass()

YCompass

Retrieves a compass for a given identifier.

| | |
|---------------------|---|
| <code>js</code> | <code>function yFindCompass(func)</code> |
| <code>nodejs</code> | <code>function FindCompass(func)</code> |
| <code>php</code> | <code>function yFindCompass(\$func)</code> |
| <code>cpp</code> | <code>YCompass* yFindCompass(const string& func)</code> |
| <code>m</code> | <code>YCompass* yFindCompass(NSString* func)</code> |
| <code>pas</code> | <code>function yFindCompass(func: string): TYCompass</code> |
| <code>vb</code> | <code>function yFindCompass(ByVal func As String) As YCompass</code> |
| <code>cs</code> | <code>YCompass FindCompass(string func)</code> |
| <code>java</code> | <code>YCompass FindCompass(String func)</code> |
| <code>py</code> | <code>def FindCompass(func)</code> |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the compass is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YCompass.isOnline()` to test if the compass is indeed online at a given time. In case of ambiguity when looking for a compass by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the compass

Returns :

a `YCompass` object allowing you to drive the compass.

YCompass.FirstCompass()**YCompass****yFirstCompass() YCompass.FirstCompass()**

Starts the enumeration of compasses currently accessible.

| | |
|---------|--|
| js | function yFirstCompass() |
| node.js | function FirstCompass() |
| php | function yFirstCompass() |
| cpp | YCompass* yFirstCompass() |
| m | YCompass* yFirstCompass() |
| pas | function yFirstCompass() : TYCompass |
| vb | function yFirstCompass() As YCompass |
| cs | YCompass FirstCompass() |
| java | YCompass FirstCompass() |
| py | def FirstCompass() |

Use the method `YCompass.nextCompass()` to iterate on next compasses.

Returns :

a pointer to a `YCompass` object, corresponding to the first compass currently online, or a `null` pointer if there are none.

compass→calibrateFromPoints() compass.calibrateFromPoints()

YCompass

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```

js   function calibrateFromPoints( rawValues, refValues)
nodejs function calibrateFromPoints( rawValues, refValues)
php  function calibrateFromPoints( $rawValues, $refValues)
cpp   int calibrateFromPoints( vector<double> rawValues,
                           vector<double> refValues)

m    -(int) calibrateFromPoints : (NSMutableArray*) rawValues
      : (NSMutableArray*) refValues

pas  function calibrateFromPoints( rawValues: TDoubleArray,
                                  refValues: TDoubleArray): LongInt

vb   procedure calibrateFromPoints( )

cs   int calibrateFromPoints( List<double> rawValues,
                           List<double> refValues)

java int calibrateFromPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def calibrateFromPoints( rawValues, refValues)
cmd  YCompass target calibrateFromPoints rawValues refValues

```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.
refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

compass→describe()compass.describe()**YCompass**

Returns a short text that describes unambiguously the instance of the compass in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the compass (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

compass→get_advertisedValue()
compass→advertisedValue()
compass.get_advertisedValue()

YCompass

Returns the current value of the compass (no more than 6 characters).

| | |
|----------------------|--|
| <code>js</code> | function get_advertisedValue() |
| <code>node.js</code> | function get_advertisedValue() |
| <code>php</code> | function get_advertisedValue() |
| <code>cpp</code> | string get_advertisedValue() |
| <code>m</code> | -(NSString*) advertisedValue |
| <code>pas</code> | function get_advertisedValue() : string |
| <code>vb</code> | function get_advertisedValue() As String |
| <code>cs</code> | string get_advertisedValue() |
| <code>java</code> | String get_advertisedValue() |
| <code>py</code> | def get_advertisedValue() |
| <code>cmd</code> | YCompass target get_advertisedValue |

Returns :

a string corresponding to the current value of the compass (no more than 6 characters). On failure, throws an exception or returns `Y_ADVERTISEDVALUE_INVALID`.

compass→get_currentRawValue()
compass→currentRawValue()
compass.get_currentRawValue()

YCompass

Returns the uncalibrated, unrounded raw value returned by the sensor.

js function **get_currentRawValue()**
nodejs function **get_currentRawValue()**
php function **get_currentRawValue()**
cpp double **get_currentRawValue()**
m -(double) currentRawValue
pas function **get_currentRawValue(): double**
vb function **get_currentRawValue() As Double**
cs double **get_currentRawValue()**
java double **get_currentRawValue()**
py def **get_currentRawValue()**
cmd YCompass **target get_currentRawValue**

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor

On failure, throws an exception or returns **Y_CURRENTRAWVALUE_INVALID**.

compass→get_currentValue()
compass→currentValue()
compass.get_currentValue()

YCompass

Returns the current value of the relative bearing.

```
js    function get_currentValue( )  
nodejs function get_currentValue( )  
php   function get_currentValue( )  
cpp   double get_currentValue( )  
m     -(double) currentValue  
pas   function get_currentValue( ): double  
vb    function get_currentValue( ) As Double  
cs    double get_currentValue( )  
java  double get_currentValue( )  
py    def get_currentValue( )  
cmd   YCompass target get_currentValue
```

Returns :

a floating point number corresponding to the current value of the relative bearing

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

compass→get_errorMessage()
compass→errorMessage()
compass.get_errorMessage()**YCompass**

Returns the error message of the latest error with the compass.

| | |
|--------|--|
| js | function get_errorMessage() |
| nodejs | function get_errorMessage() |
| php | function get_errorMessage() |
| cpp | string get_errorMessage() |
| m | -(NSString*) errorMessage |
| pas | function get_errorMessage(): string |
| vb | function get_errorMessage() As String |
| cs | string get_errorMessage() |
| java | String get_errorMessage() |
| py | def get_errorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the compass object

compass→get_errorType()**YCompass****compass→errorType()compass.get_errorType()**

Returns the numerical error code of the latest error with the compass.

| | |
|--------|--|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType(): YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the compass object

compass→get_friendlyName()
compass→friendlyName()
compass.get_friendlyName()

YCompass

Returns a global identifier of the compass in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the compass if they are defined, otherwise the serial number of the module and the hardware identifier of the compass (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the compass using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

compass→get_functionDescriptor()
compass→functionDescriptor()
compass.get_functionDescriptor()

YCompass

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

compass→get_functionId()**YCompass****compass→functionId()compass.get_functionId()**

Returns the hardware identifier of the compass, without reference to the module.

| | |
|---------|--|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the compass (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

compass→get_hardwareId()**YCompass****compass→hardwareId()compass.get_hardwareId()**

Returns the unique hardware identifier of the compass in the form SERIAL.FUNCTIONID.

| | |
|--------|---|
| js | function get_hardwareId() |
| nodejs | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the compass. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the compass (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

compass→get_highestValue()
compass→highestValue()
compass.get_highestValue()

YCompass

Returns the maximal value observed for the relative bearing since the device was started.

js function **get_highestValue()**
nodejs function **get_highestValue()**
php function **get_highestValue()**
cpp double **get_highestValue()**
m -(double) highestValue
pas function **get_highestValue(): double**
vb function **get_highestValue() As Double**
cs double **get_highestValue()**
java double **get_highestValue()**
py def **get_highestValue()**
cmd YCompass **target get_highestValue**

Returns :

a floating point number corresponding to the maximal value observed for the relative bearing since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

compass→get_logFrequency()
compass→logFrequency()
compass.get_logFrequency()

YCompass

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
js   function get_logFrequency( )  
nodejs function get_logFrequency( )  
php  function get_logFrequency( )  
cpp   string get_logFrequency( )  
m    -(NSString*) logFrequency  
pas   function get_logFrequency( ): string  
vb    function get_logFrequency( ) As String  
cs    string get_logFrequency( )  
java  String get_logFrequency( )  
py    def get_logFrequency()  
cmd   YCompass target get_logFrequency
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns `Y_LOGFREQUENCY_INVALID`.

compass→get_logicalName()**YCompass****compass→logicalName()compass.get_logicalName()**

Returns the logical name of the compass.

```
js function get_logicalName( )  
node.js function get_logicalName( )  
php function get_logicalName( )  
cpp string get_logicalName( )  
m -(NSString*) logicalName  
pas function get_logicalName( ): string  
vb function get_logicalName( ) As String  
cs string get_logicalName( )  
java String get_logicalName( )  
py def get_logicalName( )  
cmd YCompass target get_logicalName
```

Returns :

a string corresponding to the logical name of the compass. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

compass→get_lowestValue()**YCompass****compass→lowestValue()compass.get_lowestValue()**

Returns the minimal value observed for the relative bearing since the device was started.

| | |
|---------|--|
| js | function get_lowestValue() |
| node.js | function get_lowestValue() |
| php | function get_lowestValue() |
| cpp | double get_lowestValue() |
| m | -(double) lowestValue |
| pas | function get_lowestValue(): double |
| vb | function get_lowestValue() As Double |
| cs | double get_lowestValue() |
| java | double get_lowestValue() |
| py | def get_lowestValue() |
| cmd | YCompass target get_lowestValue |

Returns :

a floating point number corresponding to the minimal value observed for the relative bearing since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

compass→get_magneticHeading()
compass→magneticHeading()
compass.get_magneticHeading()

YCompass

Returns the magnetic heading, regardless of the configured bearing.

```
js function get_magneticHeading( )  
nodejs function get_magneticHeading( )  
php function get_magneticHeading( )  
cpp double get_magneticHeading( )  
m -(double) magneticHeading  
pas function get_magneticHeading( ): double  
vb function get_magneticHeading( ) As Double  
cs double get_magneticHeading( )  
java double get_magneticHeading( )  
py def get_magneticHeading( )  
cmd YCompass target get_magneticHeading
```

Returns :

a floating point number corresponding to the magnetic heading, regardless of the configured bearing

On failure, throws an exception or returns Y_MAGNETICHEADING_INVALID.

compass→get_module()**YCompass****compass→module()compass.get_module()**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

compass→get_module_async()
compass→module_async()**YCompass**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

compass→get_recordedData()
compass→recordedData()
compass.get_recordedData()

YCompass

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

| | |
|---------|--|
| js | function get_recordedData(startTime, endTime) |
| node.js | function get_recordedData(startTime, endTime) |
| php | function get_recordedData(\$startTime, \$endTime) |
| cpp | YDataSet get_recordedData(s64 startTime, s64 endTime) |
| m | - (YDataSet*) recordedData : (s64) startTime : (s64) endTime |
| pas | function get_recordedData(startTime: int64, endTime: int64): TYDataSet |
| vb | function get_recordedData() As YDataSet |
| cs | YDataSet get_recordedData(long startTime, long endTime) |
| java | YDataSet get_recordedData(long startTime, long endTime) |
| py | def get_recordedData(startTime, endTime) |
| cmd | YCompass target get_recordedData startTime endTime |

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

compass→get_reportFrequency()
compass→reportFrequency()
compass.get_reportFrequency()

YCompass

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
js   function get_reportFrequency( )  
nodejs function get_reportFrequency( )  
php  function get_reportFrequency( )  
cpp   string get_reportFrequency( )  
m    -(NSString*) reportFrequency  
pas   function get_reportFrequency( ): string  
vb    function get_reportFrequency( ) As String  
cs    string get_reportFrequency( )  
java  String get_reportFrequency( )  
py    def get_reportFrequency( )  
cmd   YCompass target get_reportFrequency
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

compass→get_resolution()**YCompass****compass→resolution()compass.get_resolution()**

Returns the resolution of the measured values.

| | |
|--------|---|
| js | function get_resolution() |
| nodejs | function get_resolution() |
| php | function get_resolution() |
| cpp | double get_resolution() |
| m | -(double) resolution |
| pas | function get_resolution(): double |
| vb | function get_resolution() As Double |
| cs | double get_resolution() |
| java | double get_resolution() |
| py | def get_resolution() |
| cmd | YCompass target get_resolution |

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

compass→get_unit()**YCompass****compass→unit()compass.get_unit()**

Returns the measuring unit for the relative bearing.

| | |
|---------|---------------------------------------|
| js | function get_unit() |
| node.js | function get_unit() |
| php | function get_unit() |
| cpp | string get_unit() |
| m | -(NSString*) unit |
| pas | function get_unit() : string |
| vb | function get_unit() As String |
| cs | string get_unit() |
| java | String get_unit() |
| py | def get_unit() |
| cmd | YCompass target get_unit |

Returns :

a string corresponding to the measuring unit for the relative bearing

On failure, throws an exception or returns Y_UNIT_INVALID.

compass→get(userData)**YCompass****compass→userData()compass.get(userData())**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|--|
| js | <code>function get(userData) </code> |
| nodejs | <code>function get(userData) </code> |
| php | <code>function get(userData) </code> |
| cpp | <code>void * get(userData) </code> |
| m | <code>-(void*) userData </code> |
| pas | <code>function get(userData): Tobject </code> |
| vb | <code>function get(userData) As Object </code> |
| cs | <code>object get(userData) </code> |
| java | <code>Object get(userData) </code> |
| py | <code>def get(userData) </code> |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

compass→isOnline()compass.isOnline()**YCompass**

Checks if the compass is currently reachable, without raising any error.

| | |
|--------|--|
| js | function isOnline() |
| nodejs | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the compass in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the compass.

Returns :

true if the compass can be reached, and false otherwise

compass→isOnline_async()

YCompass

Checks if the compass is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context)
node.js function isOnline_async( callback, context)
```

If there is a cached value for the compass in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

compass→load()compass.load()**YCompass**

Preloads the compass cache with a specified validity duration.

| | |
|--------|--|
| js | function load(msValidity) |
| nodejs | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | - (YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

compass→loadCalibrationPoints() compass.loadCalibrationPoints()

YCompass

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```

js   function loadCalibrationPoints( rawValues, refValues)
nodejs function loadCalibrationPoints( rawValues, refValues)
php  function loadCalibrationPoints( &$rawValues, &$refValues)
cpp   int loadCalibrationPoints( vector<double>& rawValues,
                                vector<double>& refValues)

m    -(int) loadCalibrationPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues

pas  function loadCalibrationPoints( var rawValues: TDoubleArray,
                           var refValues: TDoubleArray): LongInt

vb   procedure loadCalibrationPoints( )
cs   int loadCalibrationPoints( List<double> rawValues,
                           List<double> refValues)

java int loadCalibrationPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def loadCalibrationPoints( rawValues, refValues)
cmd  YCompass target loadCalibrationPoints rawValues refValues

```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

compass→load_async()

YCompass

Preloads the compass cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

compass→nextCompass()|compass.nextCompass()**YCompass**

Continues the enumeration of compasses started using `yFirstCompass()`.

| | |
|--------|---|
| js | function nextCompass() |
| nodejs | function nextCompass() |
| php | function nextCompass() |
| cpp | YCompass * nextCompass() |
| m | -(YCompass*) nextCompass |
| pas | function nextCompass() : TYCompass |
| vb | function nextCompass() As YCompass |
| cs | YCompass nextCompass() |
| java | YCompass nextCompass() |
| py | def nextCompass() |

Returns :

a pointer to a `YCompass` object, corresponding to a compass currently online, or a `null` pointer if there are no more compasses to enumerate.

compass→registerTimedReportCallback() compass.registerTimedReportCallback()

YCompass

Registers the callback function that is invoked on every periodic timed notification.

```
js   function registerTimedReportCallback( callback)
node.js function registerTimedReportCallback( callback)
php  function registerTimedReportCallback( $callback)
cpp   int registerTimedReportCallback( YCompassTimedReportCallback callback)
m    -(int) registerTimedReportCallback : (YCompassTimedReportCallback) callback
pas   function registerTimedReportCallback( callback: TYCompassTimedReportCallback): LongInt
vb    function registerTimedReportCallback( ) As Integer
cs    int registerTimedReportCallback( TimedReportCallback callback)
java  int registerTimedReportCallback( TimedReportCallback callback)
py    def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

compass→registerValueCallback() compass.registerValueCallback()

YCompass

Registers the callback function that is invoked on every change of advertised value.

| | |
|---------|--|
| js | function registerValueCallback(callback) |
| node.js | function registerValueCallback(callback) |
| php | function registerValueCallback(\$callback) |
| cpp | int registerValueCallback(YCompassValueCallback callback) |
| m | -(int) registerValueCallback : (YCompassValueCallback) callback |
| pas | function registerValueCallback(callback : TYCompassValueCallback): LongInt |
| vb | function registerValueCallback() As Integer |
| cs | int registerValueCallback(ValueCallback callback) |
| java | int registerValueCallback(UpdateCallback callback) |
| py | def registerValueCallback(callback) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

compass→set_highestValue()
compass→setHighestValue()
compass.set_highestValue()**YCompass**

Changes the recorded maximal value observed.

```
js function set_highestValue( newval)
nodejs function set_highestValue( newval)
php function set_highestValue( $newval)
cpp int set_highestValue( double newval)
m -(int) setHighestValue : (double) newval
pas function set_highestValue( newval: double): integer
vb function set_highestValue( ByVal newval As Double) As Integer
cs int set_highestValue( double newval)
java int set_highestValue( double newval)
py def set_highestValue( newval)
cmd YCompass target set_highestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

compass→set_logFrequency()
compass→setLogFrequency()
compass.set_logFrequency()

YCompass

Changes the datalogger recording frequency for this function.

| | |
|---------|--|
| js | function set_logFrequency(newval) |
| node.js | function set_logFrequency(newval) |
| php | function set_logFrequency(\$newval) |
| cpp | int set_logFrequency(const string& newval) |
| m | -(int) setLogFrequency : (NSString*) newval |
| pas | function set_logFrequency(newval: string): integer |
| vb | function set_logFrequency(ByVal newval As String) As Integer |
| cs | int set_logFrequency(string newval) |
| java | int set_logFrequency(String newval) |
| py | def set_logFrequency(newval) |
| cmd | YCompass target set_logFrequency newval |

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

compass→set_logicalName()
compass→setLogicalName()
compass.set_logicalName()

YCompass

Changes the logical name of the compass.

```
js function set_logicalName( newval)
nodejs function set_logicalName( newval)
php function set_logicalName( $newval)
cpp int set_logicalName( const string& newval)
m -(int) setLogicalName : (NSString*) newval
pas function set_logicalName( newval: string): integer
vb function set_logicalName( ByVal newval As String) As Integer
cs int set_logicalName( string newval)
java int set_logicalName( String newval)
py def set_logicalName( newval)
cmd YCompass target set_logicalName newval
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the compass.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

compass→set_lowestValue()
compass→setLowestValue()
compass.set_lowestValue()

YCompass

Changes the recorded minimal value observed.

```
js function set_lowestValue( newval)
nodejs function set_lowestValue( newval)
php function set_lowestValue( $newval)
cpp int set_lowestValue( double newval)
m -(int) setLowestValue : (double) newval
pas function set_lowestValue( newval: double): integer
vb function set_lowestValue( ByVal newval As Double) As Integer
cs int set_lowestValue( double newval)
java int set_lowestValue( double newval)
py def set_lowestValue( newval)
cmd YCompass target set_lowestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

compass→set_reportFrequency()
compass→setReportFrequency()
compass.set_reportFrequency()**YCompass**

Changes the timed value notification frequency for this function.

```
js   function set_reportFrequency( newval)
nodejs function set_reportFrequency( newval)
php  function set_reportFrequency( $newval)
cpp   int set_reportFrequency( const string& newval)
m    -(int) setReportFrequency : (NSString*) newval
pas   function set_reportFrequency( newval: string): integer
vb    function set_reportFrequency( ByVal newval As String) As Integer
cs    int set_reportFrequency( string newval)
java  int set_reportFrequency( String newval)
py    def set_reportFrequency( newval)
cmd   YCompass target set_reportFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

compass→set_resolution()**YCompass****compass→setResolution()compass.set_resolution()**

Changes the resolution of the measured physical values.

| | |
|--------|--|
| js | function set_resolution(newval) |
| nodejs | function set_resolution(newval) |
| php | function set_resolution(\$newval) |
| cpp | int set_resolution(double newval) |
| m | -(int) setResolution : (double) newval |
| pas | function set_resolution(newval: double): integer |
| vb | function set_resolution(ByVal newval As Double) As Integer |
| cs | int set_resolution(double newval) |
| java | int set_resolution(double newval) |
| py | def set_resolution(newval) |
| cmd | YCompass target set_resolution newval |

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

compass→set(userData)**YCompass****compass→setUserData()compass.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

```
js   function setUserData( data)
node.js function setUserData( data)
php  function setUserData( $data)
cpp   void setUserData( void* data)
m    -(void) setUserData : (void*) data
pas   procedure setUserData( data: Tobject)
vb    procedure setUserData( ByVal data As Object)
cs    void setUserData( object data)
java  void setUserData( Object data)
py    def setUserData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

compass→wait_async()

YCompass

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context )
nodejs function wait_async( callback, context )
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.7. Current function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

| | |
|--------|---|
| js | <script type='text/javascript' src='yocto_current.js'></script> |
| nodejs | var yoctolib = require('yoctolib'); |
| | var YCurrent = yoctolib.YCurrent; |
| php | require_once('yocto_current.php'); |
| cpp | #include "yocto_current.h" |
| m | #import "yocto_current.h" |
| pas | uses yocto_current; |
| vb | yocto_current.vb |
| cs | yocto_current.cs |
| java | import com.yoctopuce.YoctoAPI.YCurrent; |
| py | from yocto_current import * |

Global functions

yFindCurrent(func)

Retrieves a current sensor for a given identifier.

yFirstCurrent()

Starts the enumeration of current sensors currently accessible.

YCurrent methods

current→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

current→describe()

Returns a short text that describes unambiguously the instance of the current sensor in the form TYPE (NAME) = SERIAL . FUNCTIONID.

current→get_advertisedValue()

Returns the current value of the current sensor (no more than 6 characters).

current→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor.

current→get_currentValue()

Returns the current measure for the current.

current→get_errorMessage()

Returns the error message of the latest error with the current sensor.

current→get_errorType()

Returns the numerical error code of the latest error with the current sensor.

current→get_friendlyName()

Returns a global identifier of the current sensor in the format MODULE_NAME . FUNCTION_NAME.

current→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

current→get_functionId()

Returns the hardware identifier of the current sensor, without reference to the module.

current→get_hardwareId()

Returns the unique hardware identifier of the current sensor in the form SERIAL . FUNCTIONID.

| | |
|--|--|
| current→get_highestValue() | Returns the maximal value observed for the current. |
| current→get_logFrequency() | Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory. |
| current→get_logicalName() | Returns the logical name of the current sensor. |
| current→get_lowestValue() | Returns the minimal value observed for the current. |
| current→get_module() | Gets the YModule object for the device on which the function is located. |
| current→get_module_async(callback, context) | Gets the YModule object for the device on which the function is located (asynchronous version). |
| current→get_recordedData(startTime, endTime) | Retrieves a DataSet object holding historical data for this sensor, for a specified time interval. |
| current→get_reportFrequency() | Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function. |
| current→get_resolution() | Returns the resolution of the measured values. |
| current→get_unit() | Returns the measuring unit for the current. |
| current→get(userData) | Returns the value of the userData attribute, as previously stored using method set(userData). |
| current→isOnline() | Checks if the current sensor is currently reachable, without raising any error. |
| current→isOnline_async(callback, context) | Checks if the current sensor is currently reachable, without raising any error (asynchronous version). |
| current→load(msValidity) | Preloads the current sensor cache with a specified validity duration. |
| current→loadCalibrationPoints(rawValues, refValues) | Retrieves error correction data points previously entered using the method calibrateFromPoints. |
| current→load_async(msValidity, callback, context) | Preloads the current sensor cache with a specified validity duration (asynchronous version). |
| current→nextCurrent() | Continues the enumeration of current sensors started using yFirstCurrent(). |
| current→registerTimedReportCallback(callback) | Registers the callback function that is invoked on every periodic timed notification. |
| current→registerValueCallback(callback) | Registers the callback function that is invoked on every change of advertised value. |
| current→set_highestValue(newval) | Changes the recorded maximal value observed pour the current. |
| current→set_logFrequency(newval) | Changes the datalogger recording frequency for this function. |
| current→set_logicalName(newval) | Changes the logical name of the current sensor. |

3. Reference

current→set_lowestValue(newval)

Changes the recorded minimal value observed pour the current.

current→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

current→set_resolution(newval)

Changes the resolution of the measured values.

current→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

current→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YCurrent.FindCurrent()**YCurrent****yFindCurrent() YCurrent.FindCurrent()**

Retrieves a current sensor for a given identifier.

| | |
|---------------|---|
| js | function yFindCurrent(func) |
| nodejs | function FindCurrent(func) |
| php | function yFindCurrent(\$func) |
| cpp | YCurrent* yFindCurrent(const string& func) |
| m | YCurrent* yFindCurrent(NSString* func) |
| pas | function yFindCurrent(func: string): TYCurrent |
| vb | function yFindCurrent(ByVal func As String) As YCurrent |
| cs | YCurrent FindCurrent(string func) |
| java | YCurrent FindCurrent(String func) |
| py | def FindCurrent(func) |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the current sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YCurrent.isOnline()` to test if the current sensor is indeed online at a given time. In case of ambiguity when looking for a current sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the current sensor

Returns :

a `YCurrent` object allowing you to drive the current sensor.

YCurrent.FirstCurrent() yFirstCurrent() YCurrent.FirstCurrent()

YCurrent

Starts the enumeration of current sensors currently accessible.

```
js function yFirstCurrent( )
node.js function FirstCurrent( )
php function yFirstCurrent( )
cpp YCurrent* yFirstCurrent( )
m YCurrent* yFirstCurrent( )
pas function yFirstCurrent( ): TYCurrent
vb function yFirstCurrent( ) As YCurrent
cs YCurrent FirstCurrent( )
java YCurrent FirstCurrent( )
py def FirstCurrent( )
```

Use the method `YCurrent.nextCurrent()` to iterate on next current sensors.

Returns :

a pointer to a `YCurrent` object, corresponding to the first current sensor currently online, or a null pointer if there are none.

current→calibrateFromPoints() current.calibrateFromPoints()

YCurrent

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```

js   function calibrateFromPoints( rawValues, refValues)
nodejs function calibrateFromPoints( rawValues, refValues)
php  function calibrateFromPoints( $rawValues, $refValues)
cpp   int calibrateFromPoints( vector<double> rawValues,
                             vector<double> refValues)

m    -(int) calibrateFromPoints : (NSMutableArray*) rawValues
                  : (NSMutableArray*) refValues

pas  function calibrateFromPoints( rawValues: TDoubleArray,
                                 refValues: TDoubleArray): LongInt

vb   procedure calibrateFromPoints( )

cs   int calibrateFromPoints( List<double> rawValues,
                           List<double> refValues)

java int calibrateFromPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def calibrateFromPoints( rawValues, refValues)
cmd  YCurrent target calibrateFromPoints rawValues refValues

```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.
refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

current→describe()current.describe()**YCurrent**

Returns a short text that describes unambiguously the instance of the current sensor in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the current sensor (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

current→get_advertisedValue()
current→advertisedValue()
current.get_advertisedValue()**YCurrent**

Returns the current value of the current sensor (no more than 6 characters).

| | |
|----------------------|--|
| <code>js</code> | <code>function get_advertisedValue()</code> |
| <code>node.js</code> | <code>function get_advertisedValue()</code> |
| <code>php</code> | <code>function get_advertisedValue()</code> |
| <code>cpp</code> | <code>string get_advertisedValue()</code> |
| <code>m</code> | <code>-(NSString*) advertisedValue</code> |
| <code>pas</code> | <code>function get_advertisedValue(): string</code> |
| <code>vb</code> | <code>function get_advertisedValue() As String</code> |
| <code>cs</code> | <code>string get_advertisedValue()</code> |
| <code>java</code> | <code>String get_advertisedValue()</code> |
| <code>py</code> | <code>def get_advertisedValue()</code> |
| <code>cmd</code> | <code>YCurrent target get_advertisedValue</code> |

Returns :

a string corresponding to the current value of the current sensor (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

current→get_currentRawValue()
current→currentRawValue()
current.get_currentRawValue()

YCurrent

Returns the uncalibrated, unrounded raw value returned by the sensor.

```
js function get_currentRawValue( )  
nodejs function get_currentRawValue( )  
php function get_currentRawValue( )  
cpp double get_currentRawValue( )  
m -(double) currentRawValue  
pas function get_currentRawValue( ): double  
vb function get_currentRawValue( ) As Double  
cs double get_currentRawValue( )  
java double get_currentRawValue( )  
py def get_currentRawValue( )  
cmd YCurrent target get_currentRawValue
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

current→get_currentValue()**YCurrent****current→currentValue()current.get_currentValue()**

Returns the current measure for the current.

| | |
|---------|---|
| js | function get_currentValue() |
| node.js | function get_currentValue() |
| php | function get_currentValue() |
| cpp | double get_currentValue() |
| m | -(double) currentValue |
| pas | function get_currentValue() : double |
| vb | function get_currentValue() As Double |
| cs | double get_currentValue() |
| java | double get_currentValue() |
| py | def get_currentValue() |
| cmd | YCurrent target get_currentValue |

Returns :

a floating point number corresponding to the current measure for the current

On failure, throws an exception or returns **Y_CURRENTVALUE_INVALID**.

current→get_errorMessage()**YCurrent****current→errorMessage()current.getErrorMessage()**

Returns the error message of the latest error with the current sensor.

| | |
|---------|--|
| js | function getErrorMessage() |
| node.js | function getErrorMessage() |
| php | function getErrorMessage() |
| cpp | string getErrorMessage() |
| m | -(NSString*) errorMessage |
| pas | function getErrorMessage() : string |
| vb | function getErrorMessage() As String |
| cs | string getErrorMessage() |
| java | String getErrorMessage() |
| py | def getErrorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the current sensor object

current→get_errorType()**YCurrent****current→errorType()current.get_errorType()**

Returns the numerical error code of the latest error with the current sensor.

| | |
|--------|--|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType(): YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the current sensor object

current→get_friendlyName()**YCurrent****current→friendlyName()current.get_friendlyName()**

Returns a global identifier of the current sensor in the format MODULE_NAME . FUNCTION_NAME.

| | |
|---------|------------------------------|
| js | function get_friendlyName() |
| node.js | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the current sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the current sensor (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the current sensor using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

current→get_functionDescriptor()
current→functionDescriptor()
current.get_functionDescriptor()

YCurrent

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

current→get_functionId() YCurrent
current→functionId()current.get_functionId()

Returns the hardware identifier of the current sensor, without reference to the module.

| | |
|---------|--|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the current sensor (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

current→get_hardwareId()**YCurrent****current→hardwareId()current.get_hardwareId()**

Returns the unique hardware identifier of the current sensor in the form SERIAL.FUNCTIONID.

| | |
|--------|---|
| js | function get_hardwareId() |
| nodejs | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the current sensor. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the current sensor (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

current→get_highestValue()**YCurrent****current→highestValue()current.get_highestValue()**

Returns the maximal value observed for the current.

js function **get_highestValue()****node.js** function **get_highestValue()****php** function **get_highestValue()****cpp** double **get_highestValue()****m** -(double) highestValue**pas** function **get_highestValue(): double****vb** function **get_highestValue() As Double****cs** double **get_highestValue()****java** double **get_highestValue()****py** def **get_highestValue()****cmd** YCurrent target **get_highestValue****Returns :**

a floating point number corresponding to the maximal value observed for the current

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

current→get_logFrequency()**YCurrent****current→logFrequency()current.get_logFrequency()**

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

| | |
|--------|--|
| js | function get_logFrequency() |
| nodejs | function get_logFrequency() |
| php | function get_logFrequency() |
| cpp | string get_logFrequency() |
| m | -(NSString*) logFrequency |
| pas | function get_logFrequency() : string |
| vb | function get_logFrequency() As String |
| cs | string get_logFrequency() |
| java | String get_logFrequency() |
| py | def get_logFrequency() |
| cmd | YCurrent target get_logFrequency |

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

current→get_logicalName()**YCurrent****current→logicalName()current.get_logicalName()**

Returns the logical name of the current sensor.

| | |
|---------|--|
| js | function get_logicalName() |
| node.js | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | - (NSString*) logicalName |
| pas | function get_logicalName(): string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YCurrent target get_logicalName |

Returns :

a string corresponding to the logical name of the current sensor. On failure, throws an exception or returns **Y_LOGICALNAME_INVALID**.

current→get_lowestValue()
current→lowestValue()current.get_lowestValue()**YCurrent**

Returns the minimal value observed for the current.

| | |
|--------|--|
| js | function get_lowestValue() |
| nodejs | function get_lowestValue() |
| php | function get_lowestValue() |
| cpp | double get_lowestValue() |
| m | -(double) lowestValue |
| pas | function get_lowestValue(): double |
| vb | function get_lowestValue() As Double |
| cs | double get_lowestValue() |
| java | double get_lowestValue() |
| py | def get_lowestValue() |
| cmd | YCurrent target get_lowestValue |

Returns :

a floating point number corresponding to the minimal value observed for the current

On failure, throws an exception or returns **Y_LOWESTVALUE_INVALID**.

current→get_module()
current→module()current.get_module()**YCurrent**

Gets the `YModule` object for the device on which the function is located.

| | |
|---------|---|
| js | function get_module() |
| node.js | function get_module() |
| php | function get_module() |
| cpp | <code>YModule * get_module()</code> |
| m | <code>-(YModule*) module</code> |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | <code>YModule get_module()</code> |
| java | <code>YModule get_module()</code> |
| py | <code>def get_module()</code> |

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

current→get_module_async()
current→module_async()**YCurrent**

Gets the YModule object for the device on which the function is located (asynchronous version).

```
js   function get_module_async( callback, context )
nodejs function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned YModule object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested YModule object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

current→get recordedData()

YCurrent

`current→recordedData()current.get_recordedData()`

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
js function get_recordedData( startTime, endTime)
nodejs function get_recordedData( startTime, endTime)
php function get_recordedData( $startTime, $endTime)
cpp YDataSet get_recordedData( s64 startTime, s64 endTime)
m -(YDataSet*) recordedData : (s64) startTime
                           : (s64) endTime
pas function get_recordedData( startTime: int64, endTime: int64): TYDataSet
vb function get_recordedData( ) As YDataSet
cs YDataSet get_recordedData( long startTime, long endTime)
java YDataSet get_recordedData( long startTime, long endTime)
py def get_recordedData( startTime, endTime)
cmd YCurrent target get_recordedData startTime endTime
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the `DataSet` class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of `YDataSet`, providing access to historical data. Past measures can be loaded progressively using methods from the `YDataSet` object.

current→get_reportFrequency()
current→reportFrequency()
current.get_reportFrequency()**YCurrent**

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

| | |
|---------|---|
| js | function get_reportFrequency() |
| node.js | function get_reportFrequency() |
| php | function get_reportFrequency() |
| cpp | string get_reportFrequency() |
| m | -(NSString*) reportFrequency |
| pas | function get_reportFrequency() : string |
| vb | function get_reportFrequency() As String |
| cs | string get_reportFrequency() |
| java | String get_reportFrequency() |
| py | def get_reportFrequency() |
| cmd | YCurrent target get_reportFrequency |

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns **Y_REPORTFREQUENCY_INVALID**.

current→get_resolution() YCurrent
current→resolution()current.get_resolution()

Returns the resolution of the measured values.

```
js function get_resolution( )
node.js function get_resolution( )
php function get_resolution( )
cpp double get_resolution( )
m -(double) resolution
pas function get_resolution( ): double
vb function get_resolution( ) As Double
cs double get_resolution( )
java double get_resolution( )
py def get_resolution( )
cmd YCurrent target get_resolution
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

current→get_unit()**YCurrent****current→unit()current.get_unit()**

Returns the measuring unit for the current.

| | |
|--------|---------------------------------------|
| js | function get_unit() |
| nodejs | function get_unit() |
| php | function get_unit() |
| cpp | string get_unit() |
| m | -(NSString*) unit |
| pas | function get_unit() : string |
| vb | function get_unit() As String |
| cs | string get_unit() |
| java | String get_unit() |
| py | def get_unit() |
| cmd | YCurrent target get_unit |

Returns :

a string corresponding to the measuring unit for the current

On failure, throws an exception or returns Y_UNIT_INVALID.

current→get(userData)**YCurrent****current→userData()current.get(userData)**

Returns the value of the userData attribute, as previously stored using method set(userData).

```
js function get(userData) 
node.js function get(userData) 
php function get(userData) 
cpp void * get(userData) 
m -(void*) userData 
pas function get(userData): Tobject 
vb function get(userData) As Object 
cs object get(userData) 
java Object get(userData) 
py def get(userData)
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

current→isOnline()current.isOnline()**YCurrent**

Checks if the current sensor is currently reachable, without raising any error.

| | |
|---------|--|
| js | function isOnline() |
| node.js | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | -(BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the current sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the current sensor.

Returns :

true if the current sensor can be reached, and false otherwise

current→isOnline_async()**YCurrent**

Checks if the current sensor is currently reachable, without raising any error (asynchronous version).

```
js  function isOnline_async( callback, context )
nodejs function isOnline_async( callback, context )
```

If there is a cached value for the current sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

current→load()current.load()**YCurrent**

Preloads the current sensor cache with a specified validity duration.

| | |
|----------------------|--|
| <code>js</code> | <code>function load(msValidity)</code> |
| <code>node.js</code> | <code>function load(msValidity)</code> |
| <code>php</code> | <code>function load(\$msValidity)</code> |
| <code>cpp</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>m</code> | <code>-(YRETCODE) load : (int) msValidity</code> |
| <code>pas</code> | <code>function load(msValidity: integer): YRETCODE</code> |
| <code>vb</code> | <code>function load(ByVal msValidity As Integer) As YRETCODE</code> |
| <code>cs</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>java</code> | <code>int load(long msValidity)</code> |
| <code>py</code> | <code>def load(msValidity)</code> |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

current→loadCalibrationPoints() current.loadCalibrationPoints()

YCurrent

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```

js   function loadCalibrationPoints( rawValues, refValues)
nodejs function loadCalibrationPoints( rawValues, refValues)
php   function loadCalibrationPoints( &$rawValues, &$refValues)
cpp   int loadCalibrationPoints( vector<double>& rawValues,
                               vector<double>& refValues)

m    -(int) loadCalibrationPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues

pas  function loadCalibrationPoints( var rawValues: TDoubleArray,
                           var refValues: TDoubleArray): LongInt

vb   procedure loadCalibrationPoints( )
cs   int loadCalibrationPoints( List<double> rawValues,
                           List<double> refValues)

java int loadCalibrationPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def loadCalibrationPoints( rawValues, refValues)
cmd  YCurrent target loadCalibrationPoints rawValues refValues

```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

current→load_async()

YCurrent

Preloads the current sensor cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

current→nextCurrent()current.nextCurrent()**YCurrent**

Continues the enumeration of current sensors started using `yFirstCurrent()`.

js `function nextCurrent()`
nodejs `function nextCurrent()`
php `function nextCurrent()`
cpp `YCurrent * nextCurrent()`
m `-(YCurrent*) nextCurrent`
pas `function nextCurrent(): TYCurrent`
vb `function nextCurrent() As YCurrent`
cs `YCurrent nextCurrent()`
java `YCurrent nextCurrent()`
py `def nextCurrent()`

Returns :

a pointer to a `YCurrent` object, corresponding to a current sensor currently online, or a `null` pointer if there are no more current sensors to enumerate.

current→registerTimedReportCallback() current.registerTimedReportCallback()

YCurrent

Registers the callback function that is invoked on every periodic timed notification.

| | |
|---------|--|
| js | function registerTimedReportCallback(callback) |
| node.js | function registerTimedReportCallback(callback) |
| php | function registerTimedReportCallback(\$callback) |
| cpp | int registerTimedReportCallback(YCurrentTimedReportCallback callback) |
| m | -(int) registerTimedReportCallback : (YCurrentTimedReportCallback) callback |
| pas | function registerTimedReportCallback(callback : TYCurrentTimedReportCallback): LongInt |
| vb | function registerTimedReportCallback() As Integer |
| cs | int registerTimedReportCallback(TimedReportCallback callback) |
| java | int registerTimedReportCallback(TimedReportCallback callback) |
| py | def registerTimedReportCallback(callback) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

**current→registerValueCallback()
current.registerValueCallback()****YCurrent**

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YCurrentValueCallback callback )
m    -(int) registerValueCallback : (YCurrentValueCallback) callback
pas   function registerValueCallback( callback: TYCurrentValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

current→set_highestValue()
current→setHighestValue()
current.set_highestValue()

YCurrent

Changes the recorded maximal value observed pour the current.

| | |
|---------------|--|
| js | function set_highestValue(newval) |
| nodejs | function set_highestValue(newval) |
| php | function set_highestValue(\$newval) |
| cpp | int set_highestValue(double newval) |
| m | -(int) setHighestValue : (double) newval |
| pas | function set_highestValue(newval: double): integer |
| vb | function set_highestValue(ByVal newval As Double) As Integer |
| cs | int set_highestValue(double newval) |
| java | int set_highestValue(double newval) |
| py | def set_highestValue(newval) |
| cmd | YCurrent target set_highestValue newval |

Parameters :

newval a floating point number corresponding to the recorded maximal value observed pour the current

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

current→set_logFrequency()
current→setLogFrequency()
current.set_logFrequency()

YCurrent

Changes the datalogger recording frequency for this function.

```
js   function set_logFrequency( newval)
nodejs function set_logFrequency( newval)
php  function set_logFrequency( $newval)
cpp   int set_logFrequency( const string& newval)
m    -(int) setLogFrequency : (NSString*) newval
pas   function set_logFrequency( newval: string): integer
vb    function set_logFrequency( ByVal newval As String) As Integer
cs    int set_logFrequency( string newval)
java  int set_logFrequency( String newval)
py    def set_logFrequency( newval)
cmd   YCurrent target set_logFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

**current→set_logicalName()
current→setLogicalName()current.set_logicalName()****YCurrent**

Changes the logical name of the current sensor.

| | |
|--------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YCurrent target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the current sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

current→set_lowestValue() YCurrent**current→setLowestValue()current.set_lowestValue()**

Changes the recorded minimal value observed pour the current.

```
js function set_lowestValue( newval)
node.js function set_lowestValue( newval)
php function set_lowestValue( $newval)
cpp int set_lowestValue( double newval)
m -(int) setLowestValue : (double) newval
pas function set_lowestValue( newval: double): integer
vb function set_lowestValue( ByVal newval As Double) As Integer
cs int set_lowestValue( double newval)
java int set_lowestValue( double newval)
py def set_lowestValue( newval)
cmd YCurrent target set_lowestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed pour the current

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

current→set_reportFrequency()
current→setReportFrequency()
current.set_reportFrequency()

YCurrent

Changes the timed value notification frequency for this function.

| | |
|---------------|---|
| js | function set_reportFrequency(newval) |
| nodejs | function set_reportFrequency(newval) |
| php | function set_reportFrequency(\$newval) |
| cpp | int set_reportFrequency(const string& newval) |
| m | -(int) setReportFrequency : (NSString*) newval |
| pas | function set_reportFrequency(newval: string): integer |
| vb | function set_reportFrequency(ByVal newval As String) As Integer |
| cs | int set_reportFrequency(string newval) |
| java | int set_reportFrequency(String newval) |
| py | def set_reportFrequency(newval) |
| cmd | YCurrent target set_reportFrequency newval |

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

**current→set_resolution()
current→setResolution()current.set_resolution()****YCurrent**

Changes the resolution of the measured values.

```
js function set_resolution( newval)
node.js function set_resolution( newval)
php function set_resolution( $newval)
cpp int set_resolution( double newval)
m -(int) setResolution : (double) newval
pas function set_resolution( newval: double): integer
vb function set_resolution( ByVal newval As Double) As Integer
cs int set_resolution( double newval)
java int set_resolution( double newval)
py def set_resolution( newval)
cmd YCurrent target set_resolution newval
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

current→set(userData)**YCurrent****current→setUserData()current.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|---|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData \$data) |
| cpp | void set(userData void* data) |
| m | -(void) setUserData : (void*) data |
| pas | procedure set(userData Tobject) |
| vb | procedure set(userData ByVal data As Object) |
| cs | void set(userData object data) |
| java | void set(userData Object data) |
| py | def set(userData data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

current→wait_async()

YCurrent

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.8. DataLogger function interface

Yoctopuce sensors include a non-volatile memory capable of storing ongoing measured data automatically, without requiring a permanent connection to a computer. The DataLogger function controls the global parameters of the internal data logger.

In order to use the functions described here, you should include:

| | |
|---------------------------------------|--|
| js | <script type='text/javascript' src='yocto_datalogger.js'></script> |
| node.js | var yoctolib = require('yoctolib'); |
| php | var YDataLogger = yoctolib.YDataLogger; |
| require_once('yocto_datalogger.php'); | |
| cpp | #include "yocto_datalogger.h" |
| m | #import "yocto_datalogger.h" |
| pas | uses yocto_datalogger; |
| vb | yocto_datalogger.vb |
| cs | yocto_datalogger.cs |
| java | import com.yoctopuce.YoctoAPI.YDataLogger; |
| py | from yocto_datalogger import * |

Global functions

yFindDataLogger(func)

Retrieves a data logger for a given identifier.

yFirstDataLogger()

Starts the enumeration of data loggers currently accessible.

YDataLogger methods

datalogger→describe()

Returns a short text that describes unambiguously the instance of the data logger in the form TYPE (NAME)=SERIAL.FUNCTIONID.

datalogger→forgetAllDataStreams()

Clears the data logger memory and discards all recorded data streams.

datalogger→get_advertisedValue()

Returns the current value of the data logger (no more than 6 characters).

datalogger→get_autoStart()

Returns the default activation state of the data logger on power up.

datalogger→get_currentRunIndex()

Returns the current run number, corresponding to the number of times the module was powered on with the dataLogger enabled at some point.

datalogger→get_dataSets()

Returns a list of YDataSet objects that can be used to retrieve all measures stored by the data logger.

datalogger→get_dataStreams(v)

Builds a list of all data streams held by the data logger (legacy method).

datalogger→get_errorMessage()

Returns the error message of the latest error with the data logger.

datalogger→get_errorType()

Returns the numerical error code of the latest error with the data logger.

datalogger→get_friendlyName()

Returns a global identifier of the data logger in the format MODULE_NAME . FUNCTION_NAME.

datalogger→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

datalogger→get_functionId()

Returns the hardware identifier of the data logger, without reference to the module.

datalogger→get_hardwareId()

Returns the unique hardware identifier of the data logger in the form SERIAL . FUNCTIONID.

datalogger→get_logicalName()

Returns the logical name of the data logger.

datalogger→get_module()

Gets the YModule object for the device on which the function is located.

datalogger→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

datalogger→get_recording()

Returns the current activation state of the data logger.

datalogger→get_timeUTC()

Returns the Unix timestamp for current UTC time, if known.

datalogger→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

datalogger→isOnline()

Checks if the data logger is currently reachable, without raising any error.

datalogger→isOnline_async(callback, context)

Checks if the data logger is currently reachable, without raising any error (asynchronous version).

datalogger→load(msValidity)

Preloads the data logger cache with a specified validity duration.

datalogger→load_async(msValidity, callback, context)

Preloads the data logger cache with a specified validity duration (asynchronous version).

datalogger→nextDataLogger()

Continues the enumeration of data loggers started using yFirstDataLogger().

datalogger→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

datalogger→set_autoStart(newval)

Changes the default activation state of the data logger on power up.

datalogger→set_logicalName(newval)

Changes the logical name of the data logger.

datalogger→set_recording(newval)

Changes the activation state of the data logger to start/stop recording data.

datalogger→set_timeUTC(newval)

Changes the current UTC time reference used for recorded data.

datalogger→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

datalogger→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YDataLogger.FindDataLogger()**yFindDataLogger()YDataLogger.FindDataLogger()****YDataLogger**

Retrieves a data logger for a given identifier.

| | |
|---------------------|---|
| <code>js</code> | <code>function yFindDataLogger(func)</code> |
| <code>nodejs</code> | <code>function FindDataLogger(func)</code> |
| <code>php</code> | <code>function yFindDataLogger(\$func)</code> |
| <code>cpp</code> | <code>YDataLogger* yFindDataLogger(string func)</code> |
| <code>m</code> | <code>+ (YDataLogger*) yFindDataLogger : (NSString*) func</code> |
| <code>pas</code> | <code>function yFindDataLogger(func: string): TYDataLogger</code> |
| <code>vb</code> | <code>function yFindDataLogger(ByVal func As String) As YDataLogger</code> |
| <code>cs</code> | <code>YDataLogger FindDataLogger(string func)</code> |
| <code>java</code> | <code>YDataLogger FindDataLogger(String func)</code> |
| <code>py</code> | <code>def FindDataLogger(func)</code> |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the data logger is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YDataLogger.isOnline()` to test if the data logger is indeed online at a given time. In case of ambiguity when looking for a data logger by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the data logger

Returns :

a `YDataLogger` object allowing you to drive the data logger.

YDataLogger.FirstDataLogger()**YDataLogger****yFirstDataLogger()YDataLogger.FirstDataLogger()**

Starts the enumeration of data loggers currently accessible.

| | |
|---------|--|
| js | function yFirstDataLogger() |
| node.js | function FirstDataLogger() |
| php | function yFirstDataLogger() |
| cpp | YDataLogger* yFirstDataLogger() |
| m | YDataLogger* yFirstDataLogger() |
| pas | function yFirstDataLogger(): TYDataLogger |
| vb | function yFirstDataLogger() As YDataLogger |
| cs | YDataLogger FirstDataLogger() |
| java | YDataLogger FirstDataLogger() |
| py | def FirstDataLogger() |

Use the method `YDataLogger.nextDataLogger()` to iterate on next data loggers.

Returns :

a pointer to a `YDataLogger` object, corresponding to the first data logger currently online, or a null pointer if there are none.

datalogger→describe()datalogger.describe()**YDataLogger**

Returns a short text that describes unambiguously the instance of the data logger in the form TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--|
| js | function describe () |
| nodejs | function describe () |
| php | function describe () |
| cpp | string describe () |
| m | -(NSString*) describe |
| pas | function describe (): string |
| vb | function describe () As String |
| cs | string describe () |
| java | String describe () |
| py | def describe () |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the data logger (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

datalogger→forgetAllDataStreams()
datalogger.forgetAllDataStreams()**YDataLogger**

Clears the data logger memory and discards all recorded data streams.

| | |
|---------|--|
| js | function forgetAllDataStreams() |
| node.js | function forgetAllDataStreams() |
| php | function forgetAllDataStreams() |
| cpp | int forgetAllDataStreams() |
| m | - (int) forgetAllDataStreams |
| pas | function forgetAllDataStreams() : LongInt |
| vb | function forgetAllDataStreams() As Integer |
| cs | int forgetAllDataStreams() |
| java | int forgetAllDataStreams() |
| py | def forgetAllDataStreams() |
| cmd | YDataLogger target forgetAllDataStreams |

This method also resets the current run index to zero.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

datalogger→get_advertisedValue()
datalogger→advertisedValue()
datalogger.get_advertisedValue()

YDataLogger

Returns the current value of the data logger (no more than 6 characters).

| | |
|----------------------|--|
| <code>js</code> | <code>function get_advertisedValue()</code> |
| <code>node.js</code> | <code>function get_advertisedValue()</code> |
| <code>php</code> | <code>function get_advertisedValue()</code> |
| <code>cpp</code> | <code>string get_advertisedValue()</code> |
| <code>m</code> | <code>-(NSString*) advertisedValue</code> |
| <code>pas</code> | <code>function get_advertisedValue(): string</code> |
| <code>vb</code> | <code>function get_advertisedValue() As String</code> |
| <code>cs</code> | <code>string get_advertisedValue()</code> |
| <code>java</code> | <code>String get_advertisedValue()</code> |
| <code>py</code> | <code>def get_advertisedValue()</code> |
| <code>cmd</code> | <code>YDataLogger target get_advertisedValue</code> |

Returns :

a string corresponding to the current value of the data logger (no more than 6 characters). On failure, throws an exception or returns `Y_ADVERTISEDVALUE_INVALID`.

datalogger→get_autoStart()**YDataLogger****datalogger→autoStart()datalogger.get_autoStart()**

Returns the default activation state of the data logger on power up.

```
js function get_autoStart( )
node.js function get_autoStart( )
php function get_autoStart( )
cpp Y_AUTOSTART_enum get_autoStart( )
m -(Y_AUTOSTART_enum) autoStart
pas function get_autoStart( ): Integer
vb function get_autoStart( ) As Integer
cs int get_autoStart( )
java int get_autoStart( )
py def get_autoStart( )
cmd YDataLogger target get_autoStart
```

Returns :

either Y_AUTOSTART_OFF or Y_AUTOSTART_ON, according to the default activation state of the data logger on power up

On failure, throws an exception or returns Y_AUTOSTART_INVALID.

datalogger→get_currentRunIndex()
datalogger→currentRunIndex()
datalogger.get_currentRunIndex()**YDataLogger**

Returns the current run number, corresponding to the number of times the module was powered on with the dataLogger enabled at some point.

```
js function get_currentRunIndex( )
nodejs function get_currentRunIndex( )
php function get_currentRunIndex( )
cpp int get_currentRunIndex( )
m -(int) currentRunIndex
pas function get_currentRunIndex( ): LongInt
vb function get_currentRunIndex( ) As Integer
cs int get_currentRunIndex( )
java int get_currentRunIndex( )
py def get_currentRunIndex( )
cmd YDataLogger target get_currentRunIndex
```

Returns :

an integer corresponding to the current run number, corresponding to the number of times the module was powered on with the dataLogger enabled at some point

On failure, throws an exception or returns `Y_CURRENTRUNINDEX_INVALID`.

datalogger→get_dataSets()**YDataLogger****datalogger→dataSets()datalogger.get_dataSets()**

Returns a list of YDataSet objects that can be used to retrieve all measures stored by the data logger.

```
js function get_dataSets( )  
nodejs function get_dataSets( )  
php function get_dataSets( )  
cpp vector<YDataSet> get_dataSets( )  
m -(NSMutableArray*) dataSets  
pas function get_dataSets( ): TYDataSetArray  
vb function get_dataSets( ) As List  
cs List<YDataSet> get_dataSets( )  
java ArrayList<YDataSet> get_dataSets( )  
py def get_dataSets( )  
cmd YDataLogger target get_dataSets
```

This function only works if the device uses a recent firmware, as YDataSet objects are not supported by firmwares older than version 13000.

Returns :

a list of YDataSet object.

On failure, throws an exception or returns an empty list.

datalogger→get_dataStreams()
datalogger→dataStreams()
datalogger.get_dataStreams()

YDataLogger

Builds a list of all data streams hold by the data logger (legacy method).

| | |
|---------|---|
| js | function get_dataStreams(v) |
| node.js | function get_dataStreams(v) |
| php | function get_dataStreams(&\$v) |
| cpp | int get_dataStreams() |
| m | -(int) dataStreams : (NSArray**) v |
| pas | function get_dataStreams(v: Tlist): integer |
| vb | procedure get_dataStreams(ByVal v As List) |
| cs | int get_dataStreams(List<YDataStream> v) |
| java | int get_dataStreams(ArrayList<YDataStream> v) |
| py | def get_dataStreams(v) |

The caller must pass by reference an empty array to hold YDataStream objects, and the function fills it with objects describing available data sequences.

This is the old way to retrieve data from the DataLogger. For new applications, you should rather use `get_dataSets()` method, or call directly `get_recordedData()` on the sensor object.

Parameters :

v an array of YDataStream objects to be filled in

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

datalogger→get_errorMessage()
datalogger→errorMessage()
datalogger.get_errorMessage()

YDataLogger

Returns the error message of the latest error with the data logger.

```
js function get_errorMessage( )  
nodejs function get_errorMessage( )  
php function get_errorMessage( )  
cpp string get_errorMessage( )  
m -(NSString*) errorMessage  
pas function get_errorMessage( ): string  
vb function get_errorMessage( ) As String  
cs string get_errorMessage( )  
java String get_errorMessage( )  
py def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the data logger object

datalogger→get_errorType()**YDataLogger****datalogger→errorType()datalogger.get_errorType()**

Returns the numerical error code of the latest error with the data logger.

| | |
|--------|--|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType(): YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the data logger object

datalogger→get_friendlyName()
datalogger→friendlyName()
datalogger.get_friendlyName()

YDataLogger

Returns a global identifier of the data logger in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the data logger if they are defined, otherwise the serial number of the module and the hardware identifier of the data logger (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the data logger using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

datalogger→get_functionDescriptor()
datalogger→functionDescriptor()
datalogger.get_functionDescriptor()

YDataLogger

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

datalogger→get_functionId()**YDataLogger****datalogger→functionId()datalogger.get_functionId()**

Returns the hardware identifier of the data logger, without reference to the module.

| | |
|---------|--|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the data logger (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

datalogger→get_hardwareId()
datalogger→hardwareId()
datalogger.get_hardwareId()

YDataLogger

Returns the unique hardware identifier of the data logger in the form SERIAL.FUNCTIONID.

| | |
|---------|--|
| js | function get_hardwareId() |
| node.js | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the data logger. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the data logger (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

datalogger→get_logicalName()
datalogger→logicalName()
datalogger.get_logicalName()

YDataLogger

Returns the logical name of the data logger.

```
js function get_logicalName( )  
nodejs function get_logicalName( )  
php function get_logicalName( )  
cpp string get_logicalName( )  
m -(NSString*) logicalName  
pas function get_logicalName( ): string  
vb function get_logicalName( ) As String  
cs string get_logicalName( )  
java String get_logicalName( )  
py def get_logicalName( )  
cmd YDataLogger target get_logicalName
```

Returns :

a string corresponding to the logical name of the data logger. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

**datalogger→get_module()
datalogger→module()datalogger.get_module()****YDataLogger**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

**datalogger→get_module_async()
datalogger→module_async()****YDataLogger**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

datalogger→get_recording()**YDataLogger****datalogger→recording()datalogger.get_recording()**

Returns the current activation state of the data logger.

| | |
|--------|--|
| js | function get_recording() |
| nodejs | function get_recording() |
| php | function get_recording() |
| cpp | Y_RECORDING_enum get_recording() |
| m | -(Y_RECORDING_enum) recording |
| pas | function get_recording() : Integer |
| vb | function get_recording() As Integer |
| cs | int get_recording() |
| java | int get_recording() |
| py | def get_recording() |
| cmd | YDataLogger target get_recording |

Returns :

either Y_RECORDING_OFF or Y_RECORDING_ON, according to the current activation state of the data logger

On failure, throws an exception or returns Y_RECORDING_INVALID.

datalogger→get_timeUTC()**YDataLogger****datalogger→timeUTC()datalogger.get_timeUTC()**

Returns the Unix timestamp for current UTC time, if known.

```
js function get_timeUTC( )  
node.js function get_timeUTC( )  
php function get_timeUTC( )  
cpp s64 get_timeUTC( )  
m -(s64) timeUTC  
pas function get_timeUTC( ): int64  
vb function get_timeUTC( ) As Long  
cs long get_timeUTC( )  
java long get_timeUTC( )  
py def get_timeUTC( )  
cmd YDataLogger target get_timeUTC
```

Returns :

an integer corresponding to the Unix timestamp for current UTC time, if known

On failure, throws an exception or returns Y_TIMEUTC_INVALID.

datalogger→get(userData)**YDataLogger****datalogger→userData()datalogger.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|---|
| js | <code>function get(userData) </code> |
| nodejs | <code>function get(userData) </code> |
| php | <code>function get(userData) </code> |
| cpp | <code>void * get(userData) </code> |
| m | <code>-(void*) userData</code> |
| pas | <code>function get(userData): Tobject</code> |
| vb | <code>function get(userData) As Object</code> |
| cs | <code>object get(userData) </code> |
| java | <code>Object get(userData) </code> |
| py | <code>def get(userData) </code> |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

datalogger→isOnline()datalogger.isOnline()**YDataLogger**

Checks if the data logger is currently reachable, without raising any error.

| | |
|--------|---------------------------------------|
| js | function isOnline() |
| nodejs | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the data logger in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the data logger.

Returns :

true if the data logger can be reached, and false otherwise

datalogger→isOnline_async()

YDataLogger

Checks if the data logger is currently reachable, without raising any error (asynchronous version).

```
js   function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the data logger in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

datalogger→load()datalogger.load()**YDataLogger**

Preloads the data logger cache with a specified validity duration.

```
js function load( msValidity)
nodejs function load( msValidity)
php function load( $msValidity)
cpp YRETCODE load( int msValidity)
m -(YRETCODE) load : (int) msValidity
pas function load( msValidity: integer): YRETCODE
vb function load( ByVal msValidity As Integer) As YRETCODE
cs YRETCODE load( int msValidity)
java int load( long msValidity)
py def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

datalogger→load_async()

YDataLogger

Preloads the data logger cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

datalogger→nextDataLogger()
datalogger.nextDataLogger()**YDataLogger**

Continues the enumeration of data loggers started using `yFirstDataLogger()`.

| | |
|----------------------|--|
| <code>js</code> | <code>function nextDataLogger()</code> |
| <code>node.js</code> | <code>function nextDataLogger()</code> |
| <code>php</code> | <code>function nextDataLogger()</code> |
| <code>cpp</code> | <code>YDataLogger * nextDataLogger()</code> |
| <code>m</code> | <code>-(YDataLogger*) nextDataLogger</code> |
| <code>pas</code> | <code>function nextDataLogger(): TYDataLogger</code> |
| <code>vb</code> | <code>function nextDataLogger() As YDataLogger</code> |
| <code>cs</code> | <code>YDataLogger nextDataLogger()</code> |
| <code>java</code> | <code>YDataLogger nextDataLogger()</code> |
| <code>py</code> | <code>def nextDataLogger()</code> |

Returns :

a pointer to a `YDataLogger` object, corresponding to a data logger currently online, or a `null` pointer if there are no more data loggers to enumerate.

datalogger→registerValueCallback() datalogger.registerValueCallback()

YDataLogger

Registers the callback function that is invoked on every change of advertised value.

| | |
|----------------------|--|
| <code>js</code> | <code>function registerValueCallback(callback)</code> |
| <code>node.js</code> | <code>function registerValueCallback(callback)</code> |
| <code>php</code> | <code>function registerValueCallback(\$callback)</code> |
| <code>cpp</code> | <code>int registerValueCallback(YDataLoggerValueCallback callback)</code> |
| <code>m</code> | <code>-(int) registerValueCallback : (YDataLoggerValueCallback) callback</code> |
| <code>pas</code> | <code>function registerValueCallback(callback: TYDataLoggerValueCallback): LongInt</code> |
| <code>vb</code> | <code>function registerValueCallback() As Integer</code> |
| <code>cs</code> | <code>int registerValueCallback(ValueCallback callback)</code> |
| <code>java</code> | <code>int registerValueCallback(UpdateCallback callback)</code> |
| <code>py</code> | <code>def registerValueCallback(callback)</code> |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

datalogger→set_autoStart()**YDataLogger****datalogger→setAutoStart()datalogger.set_autoStart()**

Changes the default activation state of the data logger on power up.

| | |
|---------|--|
| js | function set_autoStart(newval) |
| node.js | function set_autoStart(newval) |
| php | function set_autoStart(\$newval) |
| cpp | int set_autoStart(Y_AUTOSTART_enum newval) |
| m | -(int) setAutoStart : (Y_AUTOSTART_enum) newval |
| pas | function set_autoStart(newval: Integer): integer |
| vb | function set_autoStart(ByVal newval As Integer) As Integer |
| cs | int set_autoStart(int newval) |
| java | int set_autoStart(int newval) |
| py | def set_autoStart(newval) |
| cmd | YDataLogger target set_autoStart newval |

Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval either `Y_AUTOSTART_OFF` or `Y_AUTOSTART_ON`, according to the default activation state of the data logger on power up

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

datalogger→set_logicalName()
datalogger→setLogicalName()
datalogger.set_logicalName()

YDataLogger

Changes the logical name of the data logger.

| | |
|---------------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YDataLogger target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the data logger.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

datalogger→set_recording()
datalogger→setRecording()
datalogger.set_recording()

YDataLogger

Changes the activation state of the data logger to start/stop recording data.

```
js function set_recording( newval)
nodejs function set_recording( newval)
php function set_recording( $newval)
cpp int set_recording( Y_RECORDING_enum newval)
m -(int) setRecording : (Y_RECORDING_enum) newval
pas function set_recording( newval: Integer): integer
vb function set_recording( ByVal newval As Integer) As Integer
cs int set_recording( int newval)
java int set_recording( int newval)
py def set_recording( newval)
cmd YDataLogger target set_recording newval
```

Parameters :

newval either Y_RECORDING_OFF or Y_RECORDING_ON, according to the activation state of the data logger to start/stop recording data

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

datalogger→set_timeUTC()**datalogger→setTimeUTC()datalogger.set_timeUTC()****YDataLogger**

Changes the current UTC time reference used for recorded data.

| | |
|--------|---|
| js | function set_timeUTC(newval) |
| nodejs | function set_timeUTC(newval) |
| php | function set_timeUTC(\$newval) |
| cpp | int set_timeUTC(s64 newval) |
| m | -(int) setTimeUTC : (s64) newval |
| pas | function set_timeUTC(newval: int64): integer |
| vb | function set_timeUTC(ByVal newval As Long) As Integer |
| cs | int set_timeUTC(long newval) |
| java | int set_timeUTC(long newval) |
| py | def set_timeUTC(newval) |
| cmd | YDataLogger target set_timeUTC newval |

Parameters :

newval an integer corresponding to the current UTC time reference used for recorded data

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

datalogger→set(userData)**YDataLogger****datalogger→setUserData()datalogger.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

```
js   function set(userData) {  
node.js function set(userData) {  
php  function set(userData) {  
cpp   void set(userData) {  
m    -(void) setUserData : (void*) userData  
pas  procedure set(userData: Tobject);  
vb   procedure set(userData: ByVal data As Object);  
cs   void set(userData: object data);  
java void set(userData: Object data);  
py   def set(userData: data);
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

datalogger→wait_async()

YDataLogger

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
```

```
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.9. Formatted data sequence

A run is a continuous interval of time during which a module was powered on. A data run provides easy access to all data collected during a given run, providing on-the-fly resampling at the desired reporting rate.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_datalogger.js'></script>
nodejs var yoctolib = require('yoctolib');
var YDataLogger = yoctolib.YDataLogger;
php require_once('yocto_datalogger.php');
cpp #include "yocto_datalogger.h"
m #import "yocto_datalogger.h"
pas uses yocto_datalogger;
vb yocto_datalogger.vb
cs yocto_datalogger.cs
java import com.yoctopuce.YoctoAPI.YDataLogger;
py from yocto_datalogger import *

```

YDataRun methods

datarun→get_averageValue(measureName, pos)

Returns the average value of the measure observed at the specified time period.

datarun→get_duration()

Returns the duration (in seconds) of the data run.

datarun→get_maxValue(measureName, pos)

Returns the maximal value of the measure observed at the specified time period.

datarun→get_measureNames()

Returns the names of the measures recorded by the data logger.

datarun→get_minValue(measureName, pos)

Returns the minimal value of the measure observed at the specified time period.

datarun→get_startTimeUTC()

Returns the start time of the data run, relative to the Jan 1, 1970.

datarun→get_valueCount()

Returns the number of values accessible in this run, given the selected data samples interval.

datarun→get_valueInterval()

Returns the number of seconds covered by each value in this run.

datarun→set_valueInterval(valueInterval)

Changes the number of seconds covered by each value in this run.

datarun→get_averageValue()**YDataRun****datarun→averageValue()datarun.get_averageValue()**

Returns the average value of the measure observed at the specified time period.

```
js function get_averageValue( measureName, pos)
nodejs function get_averageValue( measureName, pos)
php function get_averageValue( $measureName, $pos)
java double get_averageValue( String measureName, int pos)
py def get_averageValue( measureName, pos)
```

Parameters :

measureName the name of the desired measure (one of the names returned by `get_measureNames`)

pos the position index, between 0 and the value returned by `get_valueCount`

Returns :

a floating point number (the average value)

On failure, throws an exception or returns `Y_AVERAGEVALUE_INVALID`.

datarun→get_duration()**YDataRun****datarun→duration()datarun.get_duration()**

Returns the duration (in seconds) of the data run.

```
js function get_duration( )  
nodejs function get_duration( )  
php function get_duration( )  
java long get_duration( )  
py def get_duration( )
```

When the datalogger is actively recording and the specified run is the current run, calling this method reloads last sequence(s) from device to make sure it includes the latest recorded data.

Returns :

an unsigned number corresponding to the number of seconds between the beginning of the run (when the module was powered up) and the last recorded measure.

datarun→get_maxValue()**YDataRun****datarun→maxValue()datarun.get_maxValue()**

Returns the maximal value of the measure observed at the specified time period.

```
js function get_maxValue( measureName, pos)
nodejs function get_maxValue( measureName, pos)
php function get_maxValue( $measureName, $pos)
java double get_maxValue( String measureName, int pos)
py def get_maxValue( measureName, pos)
```

Parameters :

measureName the name of the desired measure (one of the names returned by `get_measureNames`)

pos the position index, between 0 and the value returned by `get_valueCount`

Returns :

a floating point number (the maximal value)

On failure, throws an exception or returns `Y_MAXVALUE_INVALID`.

`datarun→get_measureNames()`
`datarun→measureNames()`
`datarun.get_measureNames()`

YDataRun

Returns the names of the measures recorded by the data logger.

```
js function get_measureNames( )  
nodejs function get_measureNames( )  
php function get_measureNames( )  
java ArrayList<String> get_measureNames( )  
py def get_measureNames( )
```

In most case, the measure names match the hardware identifier of the sensor that produced the data.

Returns :

a list of strings (the measure names) On failure, throws an exception or returns an empty array.

datarun→get_minValue()**YDataRun****datarun→minValue()datarun.get_minValue()**

Returns the minimal value of the measure observed at the specified time period.

```
js function get_minValue( measureName, pos)
nodejs function get_minValue( measureName, pos)
php function get_minValue( $measureName, $pos)
java double get_minValue( String measureName, int pos)
py def get_minValue( measureName, pos)
```

Parameters :

measureName the name of the desired measure (one of the names returned by `get_measureNames`)

pos the position index, between 0 and the value returned by `get_valueCount`

Returns :

a floating point number (the minimal value)

On failure, throws an exception or returns `Y_MINVALUE_INVALID`.

datarun→get_startTimeUTC()
datarun→startTimeUTC()

YDataRun

Returns the start time of the data run, relative to the Jan 1, 1970.

If the UTC time was not set in the datalogger at any time during the recording of this data run, and if this is not the current run, this method returns 0.

Returns :

an unsigned number corresponding to the number of seconds between the Jan 1, 1970 and the beginning of this data run (i.e. Unix time representation of the absolute time).

datarun→get_valueCount()**YDataRun****datarun→valueCount()datarun.get_valueCount()**

Returns the number of values accessible in this run, given the selected data samples interval.

```
js function get_valueCount( )  
nodejs function get_valueCount( )  
php function get_valueCount( )  
java int get_valueCount( )  
py def get_valueCount( )
```

When the datalogger is actively recording and the specified run is the current run, calling this method reloads last sequence(s) from device to make sure it includes the latest recorded data.

Returns :

an unsigned number corresponding to the run duration divided by the samples interval.

datarun→get_valueInterval()**YDataRun****datarun→valueInterval()datarun.get_valueInterval()**

Returns the number of seconds covered by each value in this run.

```
js function get_valueInterval( )
nodejs function get_valueInterval( )
php function get_valueInterval( )
java int get_valueInterval( )
py def get_valueInterval( )
```

By default, the value interval is set to the coarsest data rate archived in the data logger flash for this run. The value interval can however be configured at will to a different rate when desired.

Returns :

an unsigned number corresponding to a number of seconds covered by each data sample in the Run.

datarun→set_valueInterval()
datarun→setValueInterval()
datarun.set_valueInterval()

YDataRun

Changes the number of seconds covered by each value in this run.

```
js function set_valueInterval( valueInterval)
nodejs function set_valueInterval( valueInterval)
php function set_valueInterval( $valueInterval)
java void set_valueInterval( int valueInterval)
py def set_valueInterval( valueInterval)
```

By default, the value interval is set to the coarsest data rate archived in the data logger flash for this run. The value interval can however be configured at will to a different rate when desired.

Parameters :

valueInterval an integer number of seconds.

Returns :

nothing

3.10. Recorded data sequence

YDataSet objects make it possible to retrieve a set of recorded measures for a given sensor and a specified time interval. They can be used to load data points with a progress report. When the YDataSet object is instanciated by the `get_recordedData()` function, no data is yet loaded from the module. It is only when the `loadMore()` method is called over and over than data will be effectively loaded from the dataLogger.

A preview of available measures is available using the function `get_preview()` as soon as `loadMore()` has been called once. Measures themselves are available using function `get_measures()` when loaded by subsequent calls to `loadMore()`.

This class can only be used on devices that use a recent firmware, as YDataSet objects are not supported by firmwares older than version 13000.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_api.js'></script>
nodejs var yoctolib = require('yoctolib');
var YAPI = yoctolib.YAPI;
var YModule = yoctolib.YModule;
php require_once('yocto_api.php');
cpp #include "yocto_api.h"
m #import "yocto_api.h"
pas uses yocto_api;
vb yocto_api.vb
cs yocto_api.cs
java import com.yoctopuce.YoctoAPI.YModule;
py from yocto_api import *

```

YDataSet methods

`dataset→get_endTimeUTC()`

Returns the end time of the dataset, relative to the Jan 1, 1970.

`dataset→get_functionId()`

Returns the hardware identifier of the function that performed the measure, without reference to the module.

`dataset→get_hardwareId()`

Returns the unique hardware identifier of the function who performed the measures, in the form SERIAL.FUNCTIONID.

`dataset→get_measures()`

Returns all measured values currently available for this DataSet, as a list of YMeasure objects.

`dataset→get_preview()`

Returns a condensed version of the measures that can retrieved in this YDataSet, as a list of YMeasure objects.

`dataset→get_progress()`

Returns the progress of the downloads of the measures from the data logger, on a scale from 0 to 100.

`dataset→get_startTimeUTC()`

Returns the start time of the dataset, relative to the Jan 1, 1970.

`dataset→get_summary()`

Returns an YMeasure object which summarizes the whole DataSet.

`dataset→get_unit()`

Returns the measuring unit for the measured value.

dataset→loadMore()

Loads the the next block of measures from the dataLogger, and updates the progress indicator.

dataset→loadMore_async(callback, context)

Loads the the next block of measures from the dataLogger asynchronously.

dataset→get_endTimeUTC()**YDataSet****dataset→endTimeUTC()dataset.get_endTimeUTC()**

Returns the end time of the dataset, relative to the Jan 1, 1970.

```
js function get_endTimeUTC( )  
node.js function get_endTimeUTC( )  
php function get_endTimeUTC( )  
cpp s64 get_endTimeUTC( )  
m -(s64) endTimeUTC  
pas function get_endTimeUTC( ): int64  
vb function get_endTimeUTC( ) As Long  
cs long get_endTimeUTC( )  
java long get_endTimeUTC( )  
py def get_endTimeUTC( )
```

When the YDataSet is created, the end time is the value passed in parameter to the `get_dataSet()` function. After the very first call to `loadMore()`, the end time is updated to reflect the timestamp of the last measure actually found in the dataLogger within the specified range.

Returns :

an unsigned number corresponding to the number of seconds between the Jan 1, 1970 and the end of this data set (i.e. Unix time representation of the absolute time).

dataset→get_functionId()**YDataSet****dataset→functionId()dataset.get_functionId()**

Returns the hardware identifier of the function that performed the measure, without reference to the module.

| | |
|--------|--|
| js | function get_functionId() |
| nodejs | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| pas | function get_functionId() : string |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `temperature1`.

Returns :

a string that identifies the function (ex: `temperature1`)

dataset→get_hardwareId()**YDataSet****dataset→hardwareId()dataset.get_hardwareId()**

Returns the unique hardware identifier of the function who performed the measures, in the form SERIAL.FUNCTIONID.

| | |
|--------|---|
| js | function get_hardwareId() |
| nodejs | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| pas | function get_hardwareId() : string |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the function (for example THRMCPL1-123456.temperature1)

Returns :

a string that uniquely identifies the function (ex: THRMCPL1-123456.temperature1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

dataset→get_measures()**YDataSet****dataset→measures()dataset.get_measures()**

Returns all measured values currently available for this DataSet, as a list of YMeasure objects.

| | |
|---------|---|
| js | function get_measures() |
| node.js | function get_measures() |
| php | function get_measures() |
| cpp | vector<YMeasure> get_measures() |
| m | -(NSMutableArray*) get_measures() |
| pas | function get_measures(): TYMeasureArray |
| vb | function get_measures() As List |
| cs | List<YMeasure> get_measures() |
| java | ArrayList<YMeasure> get_measures() |
| py | def get_measures() |

Each item includes: - the start of the measure time interval - the end of the measure time interval - the minimal value observed during the time interval - the average value observed during the time interval - the maximal value observed during the time interval

Before calling this method, you should call `loadMore()` to load data from the device. You may have to call `loadMore()` several time until all rows are loaded, but you can start looking at available data rows before the load is complete.

The oldest measures are always loaded first, and the most recent measures will be loaded last. As a result, timestamps are normally sorted in ascending order within the measure table, unless there was an unexpected adjustment of the datalogger UTC clock.

Returns :

a table of records, where each record depicts the measured value for a given time interval

On failure, throws an exception or returns an empty array.

dataset→get_preview()**YDataSet****dataset→preview()dataset.get_preview()**

Returns a condensed version of the measures that can retrieved in this YDataSet, as a list of YMeasure objects.

```
js function get_preview( )
nodejs function get_preview( )
php function get_preview( )
cpp vector<YMeasure> get_preview( )
m -(NSMutableArray*) preview
pas function get_preview( ): TYMeasureArray
vb function get_preview( ) As List
cs List<YMeasure> get_preview( )
java ArrayList<YMeasure> get_preview( )
py def get_preview( )
```

Each item includes: - the start of a time interval - the end of a time interval - the minimal value observed during the time interval - the average value observed during the time interval - the maximal value observed during the time interval

This preview is available as soon as `loadMore()` has been called for the first time.

Returns :

a table of records, where each record depicts the measured values during a time interval

On failure, throws an exception or returns an empty array.

dataset→get_progress()**YDataSet****dataset→progress()dataset.get_progress()**

Returns the progress of the downloads of the measures from the data logger, on a scale from 0 to 100.

| | |
|--------|--|
| js | function get_progress() |
| nodejs | function get_progress() |
| php | function get_progress() |
| cpp | int get_progress() |
| m | -(int) progress |
| pas | function get_progress(): LongInt |
| vb | function get_progress() As Integer |
| cs | int get_progress() |
| java | int get_progress() |
| py | def get_progress() |

When the object is instanciated by `get_dataSet`, the progress is zero. Each time `loadMore()` is invoked, the progress is updated, to reach the value 100 only once all measures have been loaded.

Returns :

an integer in the range 0 to 100 (percentage of completion).

dataset→get_startTimeUTC()**YDataSet****dataset→startTimeUTC()dataset.get_startTimeUTC()**

Returns the start time of the dataset, relative to the Jan 1, 1970.

```
js function getStartTimeUTC( )
node.js function getStartTimeUTC( )
php function getStartTimeUTC( )
cpp s64 getStartTimeUTC( )
m -(s64) startTimeUTC
pas function getStartTimeUTC( ): int64
vb function getStartTimeUTC( ) As Long
cs long getStartTimeUTC( )
java long getStartTimeUTC( )
py def getStartTimeUTC( )
```

When the YDataSet is created, the start time is the value passed in parameter to the `get_dataSet()` function. After the very first call to `loadMore()`, the start time is updated to reflect the timestamp of the first measure actually found in the dataLogger within the specified range.

Returns :

an unsigned number corresponding to the number of seconds between the Jan 1, 1970 and the beginning of this data set (i.e. Unix time representation of the absolute time).

dataset→get_summary()**YDataSet****dataset→summary()dataset.get_summary()**

Returns an YMeasure object which summarizes the whole DataSet.

| | |
|---------|---|
| js | function get_summary() |
| node.js | function get_summary() |
| php | function get_summary() |
| cpp | YMeasure get_summary() |
| m | -(YMeasure*) summary |
| pas | function get_summary() : TYMeasure |
| vb | function get_summary() As YMeasure |
| cs | YMeasure get_summary() |
| java | YMeasure get_summary() |
| py | def get_summary() |

In includes the following information: - the start of a time interval - the end of a time interval - the minimal value observed during the time interval - the average value observed during the time interval - the maximal value observed during the time interval

This summary is available as soon as `loadMore()` has been called for the first time.

Returns :

an YMeasure object

dataset→get_unit()**dataset→unit()dataset.get_unit()****YDataSet**

Returns the measuring unit for the measured value.

js function **get_unit()****node.js** function **get_unit()****php** function **get_unit()****cpp** string **get_unit()****m** -(NSString*) **unit****pas** function **get_unit()**: string**vb** function **get_unit()** As String**cs** string **get_unit()****java** String **get_unit()****py** def **get_unit()****Returns :**

a string that represents a physical unit.

On failure, throws an exception or returns Y_UNIT_INVALID.

dataset→loadMore()dataset.loadMore()**YDataSet**

Loads the the next block of measures from the dataLogger, and updates the progress indicator.

| | |
|--------|--|
| js | function loadMore() |
| nodejs | function loadMore() |
| php | function loadMore() |
| cpp | int loadMore() |
| m | - (int) loadMore |
| pas | function loadMore() : LongInt |
| vb | function loadMore() As Integer |
| cs | int loadMore() |
| java | int loadMore() |
| py | def loadMore() |

Returns :

an integer in the range 0 to 100 (percentage of completion), or a negative error code in case of failure.

On failure, throws an exception or returns a negative error code.

dataset→loadMore_async()**YDataSet**

Loads the the next block of measures from the dataLogger asynchronously.

```
js function loadMore_async( callback, context)
nodejs function loadMore_async( callback, context)
```

Parameters :

callback callback function that is invoked when the w The callback function receives three arguments: - the user-specific context object - the YDataSet object whose loadMore_async was invoked - the load result: either the progress indicator (0...100), or a negative error code in case of failure.

context user-specific object that is passed as-is to the callback function

Returns :

nothing.

3.11. Unformatted data sequence

YDataStream objects represent bare recorded measure sequences, exactly as found within the data logger present on Yoctopuce sensors.

In most cases, it is not necessary to use YDataStream objects directly, as the YDataSet objects (returned by the `get_recordedData()` method from sensors and the `get_dataSets()` method from the data logger) provide a more convenient interface.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_api.js'></script>
nodejs var yoctolib = require('yoctolib');
var YAPI = yoctolib.YAPI;
var YModule = yoctolib.YModule;
php require_once('yocto_api.php');
cpp #include "yocto_api.h"
m #import "yocto_api.h"
pas uses yocto_api;
vb yocto_api.vb
cs yocto_api.cs
java import com.yoctopuce.YoctoAPI.YModule;
py from yocto_api import *

```

YDataStream methods

`datastream→get_averageValue()`

Returns the average of all measures observed within this stream.

`datastream→get_columnCount()`

Returns the number of data columns present in this stream.

`datastream→get_columnNames()`

Returns the title (or meaning) of each data column present in this stream.

`datastream→get_data(row, col)`

Returns a single measure from the data stream, specified by its row and column index.

`datastream→get_dataRows()`

Returns the whole data set contained in the stream, as a bidimensional table of numbers.

`datastream→get_dataSamplesIntervalMs()`

Returns the number of milliseconds between two consecutive rows of this data stream.

`datastream→get_duration()`

Returns the approximate duration of this stream, in seconds.

`datastream→get_maxValue()`

Returns the largest measure observed within this stream.

`datastream→get_minValue()`

Returns the smallest measure observed within this stream.

`datastream→getRowCount()`

Returns the number of data rows present in this stream.

`datastream→get_runIndex()`

Returns the run index of the data stream.

`datastream→get_startTime()`

Returns the relative start time of the data stream, measured in seconds.

`datastream→get_startTimeUTC()`

3. Reference

Returns the start time of the data stream, relative to the Jan 1, 1970.

datastream→get_averageValue()
datastream→averageValue()
datastream.get_averageValue()

YDataStream

Returns the average of all measures observed within this stream.

| | |
|---------|---|
| js | function get_averageValue() |
| node.js | function get_averageValue() |
| php | function get_averageValue() |
| cpp | double get_averageValue() |
| m | -(double) averageValue |
| pas | function get_averageValue() : double |
| vb | function get_averageValue() As Double |
| cs | double get_averageValue() |
| java | double get_averageValue() |
| py | def get_averageValue() |

If the device uses a firmware older than version 13000, this method will always return Y_DATA_INVALID.

Returns :

a floating-point number corresponding to the average value, or Y_DATA_INVALID if the stream is not yet complete (still recording).

On failure, throws an exception or returns Y_DATA_INVALID.

datastream→get_columnCount()
datastream→columnCount()
datastream.get_columnCount()

YDataStream

Returns the number of data columns present in this stream.

| | |
|--------|---|
| js | function get_columnCount() |
| nodejs | function get_columnCount() |
| php | function get_columnCount() |
| cpp | int get_columnCount() |
| m | -(int) columnCount |
| pas | function get_columnCount() : LongInt |
| vb | function get_columnCount() As Integer |
| cs | int get_columnCount() |
| java | int get_columnCount() |
| py | def get_columnCount() |

The meaning of the values present in each column can be obtained using the method `get_columnNames()`.

If the device uses a firmware older than version 13000, this method fetches the whole data stream from the device if not yet done, which can cause a little delay.

Returns :

an unsigned number corresponding to the number of columns.

On failure, throws an exception or returns zero.

datastream→get_columnNames()
datastream→columnNames()
datastream.get_columnNames()

YDataStream

Returns the title (or meaning) of each data column present in this stream.

| | |
|---------|---|
| js | function get_columnNames() |
| node.js | function get_columnNames() |
| php | function get_columnNames() |
| cpp | vector<string> get_columnNames() |
| m | -(NSMutableArray*) columnNames |
| pas | function get_columnNames() : TStringArray |
| vb | function get_columnNames() As List |
| cs | List<string> get_columnNames() |
| java | ArrayList<String> get_columnNames() |
| py | def get_columnNames() |

In most case, the title of the data column is the hardware identifier of the sensor that produced the data. For streams recorded at a lower recording rate, the dataLogger stores the min, average and max value during each measure interval into three columns with suffixes _min, _avg and _max respectively.

If the device uses a firmware older than version 13000, this method fetches the whole data stream from the device if not yet done, which can cause a little delay.

Returns :

a list containing as many strings as there are columns in the data stream.

On failure, throws an exception or returns an empty array.

`datastream->get_data()`
`datastream->data()datastream.get_data()`

YDataStream

Returns a single measure from the data stream, specified by its row and column index.

The meaning of the values present in each column can be obtained using the method `get_columnNames()`.

This method fetches the whole data stream from the device, if not yet done.

Parameters :

row row index

col column index

Returns :

a floating-point number

On failure, throws an exception or returns Y_DATA_INVALID.

datastream→get_dataRows()**YDataStream****datastream→dataRows()datastream.get_dataRows()**

Returns the whole data set contained in the stream, as a bidimensional table of numbers.

| | |
|---------|---|
| js | function get_dataRows() |
| node.js | function get_dataRows() |
| php | function get_dataRows() |
| cpp | vector< vector<double> > get_dataRows() |
| m | -(NSMutableArray*) dataRows |
| pas | function get_dataRows(): TDoubleArrayList |
| vb | function get_dataRows() As List |
| cs | List<List<double>> get_dataRows() |
| java | ArrayList<ArrayList<Double>> get_dataRows() |
| py | def get_dataRows() |

The meaning of the values present in each column can be obtained using the method `get_columnNames()`.

This method fetches the whole data stream from the device, if not yet done.

Returns :

a list containing as many elements as there are rows in the data stream. Each row itself is a list of floating-point numbers.

On failure, throws an exception or returns an empty array.

`datastream→get_dataSamplesIntervalMs()`
`datastream→dataSamplesIntervalMs()`
`datastream.get_dataSamplesIntervalMs()`

YDataStream

Returns the number of milliseconds between two consecutive rows of this data stream.

| | |
|---------------------|---|
| <code>js</code> | <code>function get_dataSamplesIntervalMs()</code> |
| <code>nodejs</code> | <code>function get_dataSamplesIntervalMs()</code> |
| <code>php</code> | <code>function get_dataSamplesIntervalMs()</code> |
| <code>cpp</code> | <code>int get_dataSamplesIntervalMs()</code> |
| <code>m</code> | <code>-(int) dataSamplesIntervalMs</code> |
| <code>pas</code> | <code>function get_dataSamplesIntervalMs(): LongInt</code> |
| <code>vb</code> | <code>function get_dataSamplesIntervalMs() As Integer</code> |
| <code>cs</code> | <code>int get_dataSamplesIntervalMs()</code> |
| <code>java</code> | <code>int get_dataSamplesIntervalMs()</code> |
| <code>py</code> | <code>def get_dataSamplesIntervalMs()</code> |

By default, the data logger records one row per second, but the recording frequency can be changed for each device function

Returns :

an unsigned number corresponding to a number of milliseconds.

datastream→get_duration()**YDataStream****datastream→duration()datastream.get_duration()**

Returns the approximate duration of this stream, in seconds.

| | |
|--------|--|
| js | function get_duration() |
| nodejs | function get_duration() |
| php | function get_duration() |
| cpp | int get_duration() |
| m | -(int) duration |
| pas | function get_duration() : LongInt |
| vb | function get_duration() As Integer |
| cs | int get_duration() |
| java | int get_duration() |
| py | def get_duration() |

Returns :

the number of seconds covered by this stream.

On failure, throws an exception or returns Y_DURATION_INVALID.

datastream→get_maxValue()**YDataStream****datastream→maxValue()datastream.get_maxValue()**

Returns the largest measure observed within this stream.

```
js function get_maxValue( )
node.js function get_maxValue( )
php function get_maxValue( )
cpp double get_maxValue( )
m -(double) maxValue
pas function get_maxValue( ): double
vb function get_maxValue( ) As Double
cs double get_maxValue( )
java double get_maxValue( )
py def get_maxValue( )
```

If the device uses a firmware older than version 13000, this method will always return Y_DATA_INVALID.

Returns :

a floating-point number corresponding to the largest value, or Y_DATA_INVALID if the stream is not yet complete (still recording).

On failure, throws an exception or returns Y_DATA_INVALID.

datastream→get_minValue()**YDataStream****datastream→minValue()datastream.get_minValue()**

Returns the smallest measure observed within this stream.

| | |
|---------|---|
| js | function get_minValue() |
| node.js | function get_minValue() |
| php | function get_minValue() |
| cpp | double get_minValue() |
| m | -(double) minValue |
| pas | function get_minValue(): double |
| vb | function get_minValue() As Double |
| cs | double get_minValue() |
| java | double get_minValue() |
| py | def get_minValue() |

If the device uses a firmware older than version 13000, this method will always return Y_DATA_INVALID.

Returns :

a floating-point number corresponding to the smallest value, or Y_DATA_INVALID if the stream is not yet complete (still recording).

On failure, throws an exception or returns Y_DATA_INVALID.

datastream→getRowCount()**YDataStream****datastream→rowCount()datastream.getRowCount()**

Returns the number of data rows present in this stream.

| | |
|---------|---|
| js | function getRowCount() |
| node.js | function getRowCount() |
| php | function getRowCount() |
| cpp | int getRowCount() |
| m | -(int) rowCount |
| pas | function getRowCount() : LongInt |
| vb | function getRowCount() As Integer |
| cs | int getRowCount() |
| java | int getRowCount() |
| py | def getRowCount() |

If the device uses a firmware older than version 13000, this method fetches the whole data stream from the device if not yet done, which can cause a little delay.

Returns :

an unsigned number corresponding to the number of rows.

On failure, throws an exception or returns zero.

datastream→get_runIndex()**YDataStream****datastream→runIndex()datastream.get_runIndex()**

Returns the run index of the data stream.

| | |
|---------|--|
| js | function get_runIndex() |
| node.js | function get_runIndex() |
| php | function get_runIndex() |
| cpp | int get_runIndex() |
| m | -(int) runIndex |
| pas | function get_runIndex(): LongInt |
| vb | function get_runIndex() As Integer |
| cs | int get_runIndex() |
| java | int get_runIndex() |
| py | def get_runIndex() |

A run can be made of multiple datastreams, for different time intervals.

Returns :

an unsigned number corresponding to the run index.

datastream→getStartTime()**YDataStream****datastream→startTime()datastream.getStartTime()**

Returns the relative start time of the data stream, measured in seconds.

| | |
|---------|--|
| js | function getStartTime() |
| node.js | function getStartTime() |
| php | function getStartTime() |
| cpp | int getStartTime() |
| m | -(int) startTime |
| pas | function getStartTime(): LongInt |
| vb | function getStartTime() As Integer |
| cs | int getStartTime() |
| java | int getStartTime() |
| py | def getStartTime() |

For recent firmwares, the value is relative to the present time, which means the value is always negative. If the device uses a firmware older than version 13000, value is relative to the start of the time the device was powered on, and is always positive. If you need an absolute UTC timestamp, use `getStartTimeUTC()`.

Returns :

an unsigned number corresponding to the number of seconds between the start of the run and the beginning of this data stream.

datastream→getStartTimeUTC()
datastream→startTimeUTC()
datastream.getStartTimeUTC()**YDataStream**

Returns the start time of the data stream, relative to the Jan 1, 1970.

| | |
|---------|--|
| js | function getStartTimeUTC() |
| node.js | function getStartTimeUTC() |
| php | function getStartTimeUTC() |
| cpp | s64 getStartTimeUTC() |
| m | -(s64) startTimeUTC |
| pas | function getStartTimeUTC() : int64 |
| vb | function getStartTimeUTC() As Long |
| cs | long getStartTimeUTC() |
| java | long getStartTimeUTC() |
| py | def getStartTimeUTC() |

If the UTC time was not set in the datalogger at the time of the recording of this data stream, this method returns 0.

Returns :

an unsigned number corresponding to the number of seconds between the Jan 1, 1970 and the beginning of this data stream (i.e. Unix time representation of the absolute time).

3.12. Digital IO function interface

The Yoctopuce application programming interface allows you to switch the state of each bit of the I/O port. You can switch all bits at once, or one by one. The library can also automatically generate short pulses of a determined duration. Electrical behavior of each I/O can be modified (open drain and reverse polarity).

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_digitalio.js'></script>
nodejs var yoctolib = require('yoctolib');
var YDigitalIO = yoctolib.YDigitalIO;
php require_once('yocto_digitalio.php');
cpp #include "yocto_digitalio.h"
m #import "yocto_digitalio.h"
pas uses yocto_digitalio;
vb yocto_digitalio.vb
cs yocto_digitalio.cs
java import com.yoctopuce.YoctoAPI.YDigitalIO;
py from yocto_digitalio import *

```

Global functions

yFindDigitalIO(func)

Retrieves a digital IO port for a given identifier.

yFirstDigitalIO()

Starts the enumeration of digital IO ports currently accessible.

YDigitalIO methods

digitalio->delayedPulse(bitno, ms_delay, ms_duration)

Schedules a pulse on a single bit for a specified duration.

digitalio->describe()

Returns a short text that describes unambiguously the instance of the digital IO port in the form TYPE(NAME)=SERIAL.FUNCTIONID.

digitalio->get_advertisedValue()

Returns the current value of the digital IO port (no more than 6 characters).

digitalio->get_bitDirection(bitno)

Returns the direction of a single bit from the I/O port (0 means the bit is an input, 1 an output).

digitalio->get_bitOpenDrain(bitno)

Returns the type of electrical interface of a single bit from the I/O port.

digitalio->get_bitPolarity(bitno)

Returns the polarity of a single bit from the I/O port (0 means the I/O works in regular mode, 1 means the I/O works in reverse mode).

digitalio->get_bitState(bitno)

Returns the state of a single bit of the I/O port.

digitalio->get_errorMessage()

Returns the error message of the latest error with the digital IO port.

digitalio->get_errorType()

Returns the numerical error code of the latest error with the digital IO port.

digitalio->get_friendlyName()

Returns a global identifier of the digital IO port in the format MODULE_NAME . FUNCTION_NAME.

digitalio→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

digitalio→get_functionId()

Returns the hardware identifier of the digital IO port, without reference to the module.

digitalio→get_hardwareId()

Returns the unique hardware identifier of the digital IO port in the form SERIAL.FUNCTIONID.

digitalio→get_logicalName()

Returns the logical name of the digital IO port.

digitalio→get_module()

Gets the YModule object for the device on which the function is located.

digitalio→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

digitalio→get_outputVoltage()

Returns the voltage source used to drive output bits.

digitalio→get_portDirection()

Returns the IO direction of all bits of the port: 0 makes a bit an input, 1 makes it an output.

digitalio→get_portOpenDrain()

Returns the electrical interface for each bit of the port.

digitalio→get_portPolarity()

Returns the polarity of all the bits of the port.

digitalio→get_portSize()

Returns the number of bits implemented in the I/O port.

digitalio→get_portState()

Returns the digital IO port state: bit 0 represents input 0, and so on.

digitalio→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

digitalio→isOnline()

Checks if the digital IO port is currently reachable, without raising any error.

digitalio→isOnline_async(callback, context)

Checks if the digital IO port is currently reachable, without raising any error (asynchronous version).

digitalio→load(msValidity)

Preloads the digital IO port cache with a specified validity duration.

digitalio→load_async(msValidity, callback, context)

Preloads the digital IO port cache with a specified validity duration (asynchronous version).

digitalio→nextDigitalIO()

Continues the enumeration of digital IO ports started using yFirstDigitalIO().

digitalio→pulse(bitno, ms_duration)

Triggers a pulse on a single bit for a specified duration.

digitalio→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

digitalio→set_bitDirection(bitno, bitdirection)

Changes the direction of a single bit from the I/O port.

digitalio→set_bitOpenDrain(bitno, opendrain)

Changes the electrical interface of a single bit from the I/O port.

digitalio→set_bitPolarity(bitno, bitpolarity)

Changes the polarity of a single bit from the I/O port.

digitalio→set_bitState(bitno, bitstate)

Sets a single bit of the I/O port.

digitalio→set_logicalName(newval)

Changes the logical name of the digital IO port.

digitalio→set_outputVoltage(newval)

Changes the voltage source used to drive output bits.

digitalio→set_portDirection(newval)

Changes the IO direction of all bits of the port: 0 makes a bit an input, 1 makes it an output.

digitalio→set_portOpenDrain(newval)

Changes the electrical interface for each bit of the port.

digitalio→set_portPolarity(newval)

Changes the polarity of all the bits of the port: 0 makes a bit an input, 1 makes it an output.

digitalio→set_portState(newval)

Changes the digital IO port state: bit 0 represents input 0, and so on.

digitalio→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

digitalio→toggle_bitState(bitno)

Reverts a single bit of the I/O port.

digitalio→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YDigitalIO.FindDigitalIO()**yFindDigitalIO()YDigitalIO.FindDigitalIO()****YDigitalIO**

Retrieves a digital IO port for a given identifier.

| | |
|----------------------|---|
| <code>js</code> | <code>function yFindDigitalIO(func)</code> |
| <code>node.js</code> | <code>function FindDigitalIO(func)</code> |
| <code>php</code> | <code>function yFindDigitalIO(\$func)</code> |
| <code>cpp</code> | <code>YDigitalIO* yFindDigitalIO(const string& func)</code> |
| <code>m</code> | <code>YDigitalIO* yFindDigitalIO(NSString* func)</code> |
| <code>pas</code> | <code>function yFindDigitalIO(func: string): TYDigitalIO</code> |
| <code>vb</code> | <code>function yFindDigitalIO(ByVal func As String) As YDigitalIO</code> |
| <code>cs</code> | <code>YDigitalIO FindDigitalIO(string func)</code> |
| <code>java</code> | <code>YDigitalIO FindDigitalIO(String func)</code> |
| <code>py</code> | <code>def FindDigitalIO(func)</code> |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the digital IO port is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YDigitalIO.isOnline()` to test if the digital IO port is indeed online at a given time. In case of ambiguity when looking for a digital IO port by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the digital IO port

Returns :

a `YDigitalIO` object allowing you to drive the digital IO port.

YDigitalIO.FirstDigitalIO()**YDigitalIO****yFirstDigitalIO()YDigitalIO.FirstDigitalIO()**

Starts the enumeration of digital IO ports currently accessible.

| | |
|---------|--|
| js | function yFirstDigitalIO() |
| node.js | function FirstDigitalIO() |
| php | function yFirstDigitalIO() |
| cpp | YDigitalIO* yFirstDigitalIO() |
| m | YDigitalIO* yFirstDigitalIO() |
| pas | function yFirstDigitalIO() : TYDigitalIO |
| vb | function yFirstDigitalIO() As YDigitalIO |
| cs | YDigitalIO FirstDigitalIO() |
| java | YDigitalIO FirstDigitalIO() |
| py | def FirstDigitalIO() |

Use the method `YDigitalIO.nextDigitalIO()` to iterate on next digital IO ports.

Returns :

a pointer to a `YDigitalIO` object, corresponding to the first digital IO port currently online, or a null pointer if there are none.

digitalio→delayedPulse()digitalio.delayedPulse()

YDigitalIO

Schedules a pulse on a single bit for a specified duration.

| | |
|---------------|--|
| js | function delayedPulse (bitno , ms_delay , ms_duration) |
| nodejs | function delayedPulse (bitno , ms_delay , ms_duration) |
| php | function delayedPulse (\$ bitno , \$ ms_delay , \$ ms_duration) |
| cpp | int delayedPulse (int bitno , int ms_delay , int ms_duration) |
| m | -(int) delayedPulse : (int) bitno : (int) ms_delay : (int) ms_duration |
| pas | function delayedPulse (bitno : LongInt, ms_delay : LongInt, ms_duration : LongInt): LongInt |
| vb | function delayedPulse () As Integer |
| cs | int delayedPulse (int bitno , int ms_delay , int ms_duration) |
| java | int delayedPulse (int bitno , int ms_delay , int ms_duration) |
| py | def delayedPulse (bitno , ms_delay , ms_duration) |
| cmd | YDigitalIO target delayedPulse bitno ms_delay ms_duration |

The specified bit will be turned to 1, and then back to 0 after the given duration.

Parameters :

bitno the bit number; lowest bit has index 0
ms_delay waiting time before the pulse, in milliseconds
ms_duration desired pulse duration in milliseconds. Be aware that the device time resolution is not guaranteed up to the millisecond.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→describe()digitalio.describe()**YDigitalIO**

Returns a short text that describes unambiguously the instance of the digital IO port in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | - (NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the digital IO port (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

digitalio→get_advertisedValue()
digitalio→advertisedValue()
digitalio.get_advertisedValue()**YDigitalIO**

Returns the current value of the digital IO port (no more than 6 characters).

| | |
|---------|--|
| js | function get_advertisedValue() |
| node.js | function get_advertisedValue() |
| php | function get_advertisedValue() |
| cpp | string get_advertisedValue() |
| m | -(NSString*) advertisedValue |
| pas | function get_advertisedValue() : string |
| vb | function get_advertisedValue() As String |
| cs | string get_advertisedValue() |
| java | String get_advertisedValue() |
| py | def get_advertisedValue() |
| cmd | YDigitalIO target get_advertisedValue |

Returns :

a string corresponding to the current value of the digital IO port (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

digitalio→get_bitDirection() digitalio→bitDirection()digitalio.get_bitDirection()

YDigitalIO

Returns the direction of a single bit from the I/O port (0 means the bit is an input, 1 an output).

| | |
|---------|---|
| js | function get_bitDirection(bitno) |
| node.js | function get_bitDirection(bitno) |
| php | function get_bitDirection(\$bitno) |
| cpp | int get_bitDirection(int bitno) |
| m | -(int) bitDirection : (int) bitno |
| pas | function get_bitDirection(bitno : LongInt): LongInt |
| vb | function get_bitDirection() As Integer |
| cs | int get_bitDirection(int bitno) |
| java | int get_bitDirection(int bitno) |
| py | def get_bitDirection(bitno) |
| cmd | YDigitalIO target get_bitDirection bitno |

Parameters :

bitno the bit number; lowest bit has index 0

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→get_bitOpenDrain()

digitalio→bitOpenDrain()digitalio.get_bitOpenDrain()

YDigitalIO

Returns the type of electrical interface of a single bit from the I/O port.

```
js function get_bitOpenDrain( bitno)
nodejs function get_bitOpenDrain( bitno)
php function get_bitOpenDrain( $bitno)
cpp int get_bitOpenDrain( int bitno)
m -(int) bitOpenDrain : (int) bitno
pas function get_bitOpenDrain( bitno: LongInt): LongInt
vb function get_bitOpenDrain( ) As Integer
cs int get_bitOpenDrain( int bitno)
java int get_bitOpenDrain( int bitno)
py def get_bitOpenDrain( bitno)
cmd YDigitalIO target get_bitOpenDrain bitno
```

(0 means the bit is an input, 1 an output).

Parameters :

bitno the bit number; lowest bit has index 0

Returns :

0 means the a bit is a regular input/output, 1 means the bit is an open-drain (open-collector) input/output.

On failure, throws an exception or returns a negative error code.

digitalio→get_bitPolarity()**YDigitalIO****digitalio→bitPolarity()digitalio.get_bitPolarity()**

Returns the polarity of a single bit from the I/O port (0 means the I/O works in regular mode, 1 means the I/O works in reverse mode).

```
js function get_bitPolarity( bitno)
nodejs function get_bitPolarity( bitno)
php function get_bitPolarity( $bitno)
cpp int get_bitPolarity( int bitno)
m -(int) bitPolarity : (int) bitno
pas function get_bitPolarity( bitno: LongInt): LongInt
vb function get_bitPolarity( ) As Integer
cs int get_bitPolarity( int bitno)
java int get_bitPolarity( int bitno)
py def get_bitPolarity( bitno)
cmd YDigitalIO target get_bitPolarity bitno
```

Parameters :

bitno the bit number; lowest bit has index 0

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→get_bitState()**YDigitalIO****digitalio→bitState()digitalio.get_bitState()**

Returns the state of a single bit of the I/O port.

| | |
|---------|--|
| js | function get_bitState(bitno) |
| node.js | function get_bitState(bitno) |
| php | function get_bitState(\$bitno) |
| cpp | int get_bitState(int bitno) |
| m | -(int) bitState : (int) bitno |
| pas | function get_bitState(bitno: LongInt): LongInt |
| vb | function get_bitState() As Integer |
| cs | int get_bitState(int bitno) |
| java | int get_bitState(int bitno) |
| py | def get_bitState(bitno) |
| cmd | YDigitalIO target get_bitState bitno |

Parameters :

bitno the bit number; lowest bit has index 0

Returns :

the bit state (0 or 1)

On failure, throws an exception or returns a negative error code.

digitalio→get_errorMessage()
digitalio→errorMessage()
digitalio.get_errorMessage()**YDigitalIO**

Returns the error message of the latest error with the digital IO port.

| | |
|--------|--|
| js | function get_errorMessage() |
| nodejs | function get_errorMessage() |
| php | function get_errorMessage() |
| cpp | string get_errorMessage() |
| m | -(NSString*) errorMessage |
| pas | function get_errorMessage(): string |
| vb | function get_errorMessage() As String |
| cs | string get_errorMessage() |
| java | String get_errorMessage() |
| py | def get_errorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the digital IO port object

digitalio→get_errorType()**YDigitalIO****digitalio→errorType()digitalio.get_errorType()**

Returns the numerical error code of the latest error with the digital IO port.

| | |
|--------|--|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType() : YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the digital IO port object

digitalio→get_friendlyName()**YDigitalIO****digitalio→friendlyName()digitalio.get_friendlyName()**

Returns a global identifier of the digital IO port in the format MODULE_NAME . FUNCTION_NAME.

| | |
|---------|-------------------------------------|
| js | function get_friendlyName() |
| node.js | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the digital IO port if they are defined, otherwise the serial number of the module and the hardware identifier of the digital IO port (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the digital IO port using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

digitalio→get_functionDescriptor()
digitalio→functionDescriptor()
digitalio.get_functionDescriptor()**YDigitalIO**

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

digitalio→get_functionId()**YDigitalIO****digitalio→functionId()digitalio.get_functionId()**

Returns the hardware identifier of the digital IO port, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the digital IO port (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

digitalio→get_hardwareId()**YDigitalIO****digitalio→hardwareId()digitalio.get_hardwareId()**

Returns the unique hardware identifier of the digital IO port in the form SERIAL.FUNCTIONID.

| | |
|--------|---|
| js | function get_hardwareId() |
| nodejs | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the digital IO port. (for example RELAY01-123456.relay1)

Returns :

a string that uniquely identifies the digital IO port (ex: RELAY01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

digitalio→get_logicalName()**YDigitalIO****digitalio→logicalName()digitalio.get_logicalName()**

Returns the logical name of the digital IO port.

| | |
|---------|--|
| js | function get_logicalName() |
| node.js | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | - (NSString*) logicalName |
| pas | function get_logicalName(): string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YDigitalIO target get_logicalName |

Returns :

a string corresponding to the logical name of the digital IO port. On failure, throws an exception or returns **Y_LOGICALNAME_INVALID**.

digitalio→get_module()**YDigitalIO****digitalio→module()digitalio.get_module()**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

digitalio→get_module_async() digitalio→module_async()

YDigitalIO

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

digitalio→get_outputVoltage()
digitalio→outputVoltage()
digitalio.get_outputVoltage()**YDigitalIO**

Returns the voltage source used to drive output bits.

| | |
|---------|--|
| js | function get_outputVoltage() |
| node.js | function get_outputVoltage() |
| php | function get_outputVoltage() |
| cpp | Y_OUTPUTVOLTAGE_enum get_outputVoltage() |
| m | -(Y_OUTPUTVOLTAGE_enum) outputVoltage |
| pas | function get_outputVoltage() : Integer |
| vb | function get_outputVoltage() As Integer |
| cs | int get_outputVoltage() |
| java | int get_outputVoltage() |
| py | def get_outputVoltage() |
| cmd | YDigitalIO target get_outputVoltage |

Returns :

a value among Y_OUTPUTVOLTAGE_USB_5V, Y_OUTPUTVOLTAGE_USB_3V and Y_OUTPUTVOLTAGE_EXT_V corresponding to the voltage source used to drive output bits

On failure, throws an exception or returns Y_OUTPUTVOLTAGE_INVALID.

digitalio→get_portDirection()**YDigitalIO****digitalio→portDirection()digitalio.get_portDirection()**

Returns the IO direction of all bits of the port: 0 makes a bit an input, 1 makes it an output.

js function **get_portDirection()****node.js** function **get_portDirection()****php** function **get_portDirection()****cpp** int **get_portDirection()****m** -(int) **portDirection****pas** function **get_portDirection(): LongInt****vb** function **get_portDirection() As Integer****cs** int **get_portDirection()****java** int **get_portDirection()****py** def **get_portDirection()****cmd** YDigitalIO target **get_portDirection****Returns :**

an integer corresponding to the IO direction of all bits of the port: 0 makes a bit an input, 1 makes it an output

On failure, throws an exception or returns **Y_PORTDIRECTION_INVALID**.

digitalio→get_portOpenDrain()
digitalio→portOpenDrain()
digitalio.get_portOpenDrain()**YDigitalIO**

Returns the electrical interface for each bit of the port.

| | |
|---------|---|
| js | function get_portOpenDrain() |
| node.js | function get_portOpenDrain() |
| php | function get_portOpenDrain() |
| cpp | int get_portOpenDrain() |
| m | -(int) portOpenDrain |
| pas | function get_portOpenDrain() : LongInt |
| vb | function get_portOpenDrain() As Integer |
| cs | int get_portOpenDrain() |
| java | int get_portOpenDrain() |
| py | def get_portOpenDrain() |
| cmd | YDigitalIO target get_portOpenDrain |

For each bit set to 0 the matching I/O works in the regular, intuitive way, for each bit set to 1, the I/O works in reverse mode.

Returns :

an integer corresponding to the electrical interface for each bit of the port

On failure, throws an exception or returns **Y_PORTOPENRAIN_INVALID**.

digitalio→get_portPolarity()**YDigitalIO****digitalio→portPolarity()digitalio.get_portPolarity()**

Returns the polarity of all the bits of the port.

```
js function get_portPolarity( )
node.js function get_portPolarity( )
php function get_portPolarity( )
cpp int get_portPolarity( )
m -(int) portPolarity
pas function get_portPolarity( ): LongInt
vb function get_portPolarity( ) As Integer
cs int get_portPolarity( )
java int get_portPolarity( )
py def get_portPolarity( )
cmd YDigitalIO target get_portPolarity
```

For each bit set to 0, the matching I/O works the regular, intuitive way; for each bit set to 1, the I/O works in reverse mode.

Returns :

an integer corresponding to the polarity of all the bits of the port

On failure, throws an exception or returns Y_PORTPOLARITY_INVALID.

digitalio→get_portSize()**YDigitalIO****digitalio→portSize()digitalio.get_portSize()**

Returns the number of bits implemented in the I/O port.

| | |
|--------|--|
| js | function get_portSize() |
| nodejs | function get_portSize() |
| php | function get_portSize() |
| cpp | int get_portSize() |
| m | -(int) portSize |
| pas | function get_portSize() : LongInt |
| vb | function get_portSize() As Integer |
| cs | int get_portSize() |
| java | int get_portSize() |
| py | def get_portSize() |
| cmd | YDigitalIO target get_portSize |

Returns :

an integer corresponding to the number of bits implemented in the I/O port

On failure, throws an exception or returns **Y_PORTSIZE_INVALID**.

digitalio→get_portState()
digitalio→portState()digitalio.get_portState()**YDigitalIO**

Returns the digital IO port state: bit 0 represents input 0, and so on.

| | |
|---------|---|
| js | function get_portState() |
| node.js | function get_portState() |
| php | function get_portState() |
| cpp | int get_portState() |
| m | -(int) portState |
| pas | function get_portState(): LongInt |
| vb | function get_portState() As Integer |
| cs | int get_portState() |
| java | int get_portState() |
| py | def get_portState() |
| cmd | YDigitalIO target get_portState |

Returns :

an integer corresponding to the digital IO port state: bit 0 represents input 0, and so on

On failure, throws an exception or returns **Y_PORTSTATE_INVALID**.

digitalio→get(userData)**YDigitalIO****digitalio→userData()digitalio.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|---|
| js | <code>function get(userData) </code> |
| nodejs | <code>function get(userData) </code> |
| php | <code>function get(userData) </code> |
| cpp | <code>void * get(userData) </code> |
| m | <code>-(void*) userData</code> |
| pas | <code>function get(userData): Tobject</code> |
| vb | <code>function get(userData) As Object</code> |
| cs | <code>object get(userData) </code> |
| java | <code>Object get(userData) </code> |
| py | <code>def get(userData) </code> |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

digitalio→isOnline()digitalio.isOnline()

YDigitalIO

Checks if the digital IO port is currently reachable, without raising any error.

| | |
|--------|---|
| js | function isOnline () |
| nodejs | function isOnline () |
| php | function isOnline () |
| cpp | bool isOnline () |
| m | - (BOOL) isOnline |
| pas | function isOnline (): boolean |
| vb | function isOnline () As Boolean |
| cs | bool isOnline () |
| java | boolean isOnline () |
| py | def isOnline () |

If there is a cached value for the digital IO port in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the digital IO port.

Returns :

true if the digital IO port can be reached, and false otherwise

digitalio→isOnline_async()

YDigitalIO

Checks if the digital IO port is currently reachable, without raising any error (asynchronous version).

```
js   function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the digital IO port in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

digitalio→load()**digitalio.load()**

YDigitalIO

Preloads the digital IO port cache with a specified validity duration.

```
js function load( msValidity)
nodejs function load( msValidity)
php function load( $msValidity)
cpp YRETCODE load( int msValidity)
m -(YRETCODE) load : (int) msValidity
pas function load( msValidity: integer): YRETCODE
vb function load( ByVal msValidity As Integer) As YRETCODE
cs YRETCODE load( int msValidity)
java int load( long msValidity)
py def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

digitalio→load_async()

YDigitalIO

Preloads the digital IO port cache with a specified validity duration (asynchronous version).

```
js   function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

digitalio→nextDigitalIO()digitalio.nextDigitalIO()**YDigitalIO**

Continues the enumeration of digital IO ports started using `yFirstDigitalIO()`.

| | |
|---------------------|--|
| <code>js</code> | <code>function nextDigitalIO()</code> |
| <code>nodejs</code> | <code>function nextDigitalIO()</code> |
| <code>php</code> | <code>function nextDigitalIO()</code> |
| <code>cpp</code> | <code>YDigitalIO * nextDigitalIO()</code> |
| <code>m</code> | <code>-(YDigitalIO*) nextDigitalIO</code> |
| <code>pas</code> | <code>function nextDigitalIO(): TYDigitalIO</code> |
| <code>vb</code> | <code>function nextDigitalIO() As YDigitalIO</code> |
| <code>cs</code> | <code>YDigitalIO nextDigitalIO()</code> |
| <code>java</code> | <code>YDigitalIO nextDigitalIO()</code> |
| <code>py</code> | <code>def nextDigitalIO()</code> |

Returns :

a pointer to a `YDigitalIO` object, corresponding to a digital IO port currently online, or a `null` pointer if there are no more digital IO ports to enumerate.

digitalio→pulse()

YDigitalIO

Triggers a pulse on a single bit for a specified duration.

| | |
|--------|---|
| js | function pulse(bitno, ms_duration) |
| nodejs | function pulse(bitno, ms_duration) |
| php | function pulse(\$bitno, \$ms_duration) |
| cpp | int pulse(int bitno, int ms_duration) |
| m | - (int) pulse : (int) bitno : (int) ms_duration |
| pas | function pulse(bitno: LongInt, ms_duration: LongInt): LongInt |
| vb | function pulse() As Integer |
| cs | int pulse(int bitno, int ms_duration) |
| java | int pulse(int bitno, int ms_duration) |
| py | def pulse(bitno, ms_duration) |
| cmd | YDigitalIO target pulse bitno ms_duration |

The specified bit will be turned to 1, and then back to 0 after the given duration.

Parameters :

bitno the bit number; lowest bit has index 0

ms_duration desired pulse duration in milliseconds. Be aware that the device time resolution is not guaranteed up to the millisecond.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→registerValueCallback() digitalio.registerValueCallback()

YDigitalIO

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YDigitalIOValueCallback callback )
m    -(int) registerValueCallback : (YDigitalIOValueCallback) callback
pas   function registerValueCallback( callback: TYDigitalIOValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

digitalio→set_bitDirection()**YDigitalIO****digitalio→setBitDirection()digitalio.set_bitDirection()**

Changes the direction of a single bit from the I/O port.

| | |
|---------------|---|
| js | <code>function set_bitDirection(bitno, bitdirection)</code> |
| nodejs | <code>function set_bitDirection(bitno, bitdirection)</code> |
| php | <code>function set_bitDirection(\$bitno, \$bitdirection)</code> |
| cpp | <code>int set_bitDirection(int bitno, int bitdirection)</code> |
| m | <code>-(int) setBitDirection : (int) bitno : (int) bitdirection</code> |
| pas | <code>function set_bitDirection(bitno: LongInt, bitdirection: LongInt): LongInt</code> |
| vb | <code>function set_bitDirection() As Integer</code> |
| cs | <code>int set_bitDirection(int bitno, int bitdirection)</code> |
| java | <code>int set_bitDirection(int bitno, int bitdirection)</code> |
| py | <code>def set_bitDirection(bitno, bitdirection)</code> |
| cmd | <code>YDigitalIO target set_bitDirection bitno bitdirection</code> |

Parameters :

bitno the bit number; lowest bit has index 0

bitdirection direction to set, 0 makes the bit an input, 1 makes it an output. Remember to call the `saveToFlash()` method to make sure the setting is kept after a reboot.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→set_bitOpenDrain()
digitalio→setBitOpenDrain()
digitalio.set_bitOpenDrain()

YDigitalIO

Changes the electrical interface of a single bit from the I/O port.

```
js function set_bitOpenDrain( bitno, opendrain)
nodejs function set_bitOpenDrain( bitno, opendrain)
php function set_bitOpenDrain( $bitno, $opendrain)
cpp int set_bitOpenDrain( int bitno, int opendrain)
m -(int) setBitOpenDrain : (int) bitno : (int) opendrain
pas function set_bitOpenDrain( bitno: LongInt, opendrain: LongInt): LongInt
vb function set_bitOpenDrain( ) As Integer
cs int set_bitOpenDrain( int bitno, int opendrain)
java int set_bitOpenDrain( int bitno, int opendrain)
py def set_bitOpenDrain( bitno, opendrain)
cmd YDigitalIO target set_bitOpenDrain bitno opendrain
```

Parameters :

bitno the bit number; lowest bit has index 0

opendrain 0 makes a bit a regular input/output, 1 makes it an open-drain (open-collector) input/output.
Remember to call the `saveToFlash()` method to make sure the setting is kept after a reboot.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→set_bitPolarity()**YDigitalIO****digitalio→setBitPolarity()digitalio.set_bitPolarity()**

Changes the polarity of a single bit from the I/O port.

| | |
|---------------|---|
| js | <code>function set_bitPolarity(bitno, bitpolarity)</code> |
| nodejs | <code>function set_bitPolarity(bitno, bitpolarity)</code> |
| php | <code>function set_bitPolarity(\$bitno, \$bitpolarity)</code> |
| cpp | <code>int set_bitPolarity(int bitno, int bitpolarity)</code> |
| m | <code>-(int) setBitPolarity : (int) bitno : (int) bitpolarity</code> |
| pas | <code>function set_bitPolarity(bitno: LongInt, bitpolarity: LongInt): LongInt</code> |
| vb | <code>function set_bitPolarity() As Integer</code> |
| cs | <code>int set_bitPolarity(int bitno, int bitpolarity)</code> |
| java | <code>int set_bitPolarity(int bitno, int bitpolarity)</code> |
| py | <code>def set_bitPolarity(bitno, bitpolarity)</code> |
| cmd | <code>YDigitalIO target set_bitPolarity bitno bitpolarity</code> |

Parameters :

bitno the bit number; lowest bit has index 0.

bitpolarity polarity to set, 0 makes the I/O work in regular mode, 1 makes the I/O works in reverse mode.

Remember to call the `saveToFlash()` method to make sure the setting is kept after a reboot.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→set_bitState() digitalio→setBitState()digitalio.set_bitState()

YDigitalIO

Sets a single bit of the I/O port.

```
js function set_bitState( bitno, bitstate)
node.js function set_bitState( bitno, bitstate)
php function set_bitState( $bitno, $bitstate)
cpp int set_bitState( int bitno, int bitstate)
m -(int) setBitState : (int) bitno : (int) bitstate
pas function set_bitState( bitno: LongInt, bitstate: LongInt): LongInt
vb function set_bitState( ) As Integer
cs int set_bitState( int bitno, int bitstate)
java int set_bitState( int bitno, int bitstate)
py def set_bitState( bitno, bitstate)
cmd YDigitalIO target set_bitState bitno bitstate
```

Parameters :

bitno the bit number; lowest bit has index 0

bitstate the state of the bit (1 or 0)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→set_logicalName()

digitalio→setLogicalName()

digitalio.set_logicalName()

YDigitalIO

Changes the logical name of the digital IO port.

| | |
|---------------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YDigitalIO target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the digital IO port.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

digitalio→set_outputVoltage()
digitalio→setOutputVoltage()
digitalio.set_outputVoltage()

YDigitalIO

Changes the voltage source used to drive output bits.

| | |
|--------|--|
| js | function set_outputVoltage(newval) |
| nodejs | function set_outputVoltage(newval) |
| php | function set_outputVoltage(\$newval) |
| cpp | int set_outputVoltage(Y_OUTPUTVOLTAGE_enum newval) |
| m | - (int) setOutputVoltage : (Y_OUTPUTVOLTAGE_enum) newval |
| pas | function set_outputVoltage(newval: Integer): integer |
| vb | function set_outputVoltage(ByVal newval As Integer) As Integer |
| cs | int set_outputVoltage(int newval) |
| java | int set_outputVoltage(int newval) |
| py | def set_outputVoltage(newval) |
| cmd | YDigitalIO target set_outputVoltage newval |

Remember to call the `saveToFlash()` method to make sure the setting is kept after a reboot.

Parameters :

newval a value among `Y_OUTPUTVOLTAGE_USB_5V`, `Y_OUTPUTVOLTAGE_USB_3V` and `Y_OUTPUTVOLTAGE_EXT_V` corresponding to the voltage source used to drive output bits

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→set_portDirection()

digitalio→setPortDirection()

digitalio.set_portDirection()

YDigitalIO

Changes the IO direction of all bits of the port: 0 makes a bit an input, 1 makes it an output.

| | |
|---------|--|
| js | function set_portDirection(newval) |
| node.js | function set_portDirection(newval) |
| php | function set_portDirection(\$newval) |
| cpp | int set_portDirection(int newval) |
| m | -(int) setPortDirection : (int) newval |
| pas | function set_portDirection(newval: LongInt): integer |
| vb | function set_portDirection(ByVal newval As Integer) As Integer |
| cs | int set_portDirection(int newval) |
| java | int set_portDirection(int newval) |
| py | def set_portDirection(newval) |
| cmd | YDigitalIO target set_portDirection newval |

Remember to call the `saveToFlash()` method to make sure the setting is kept after a reboot.

Parameters :

newval an integer corresponding to the IO direction of all bits of the port: 0 makes a bit an input, 1 makes it an output

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→set_portOpenDrain()
digitalio→setPortOpenDrain()
digitalio.set_portOpenDrain()

YDigitalIO

Changes the electrical interface for each bit of the port.

```
js function set_portOpenDrain( newval)
nodejs function set_portOpenDrain( newval)
php function set_portOpenDrain( $newval)
cpp int set_portOpenDrain( int newval)
m -(int) setPortOpenDrain : (int) newval
pas function set_portOpenDrain( newval: LongInt): integer
vb function set_portOpenDrain( ByVal newval As Integer) As Integer
cs int set_portOpenDrain( int newval)
java int set_portOpenDrain( int newval)
py def set_portOpenDrain( newval)
cmd YDigitalIO target set_portOpenDrain newval
```

0 makes a bit a regular input/output, 1 makes it an open-drain (open-collector) input/output. Remember to call the `saveToFlash()` method to make sure the setting is kept after a reboot.

Parameters :

newval an integer corresponding to the electrical interface for each bit of the port

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→set_portPolarity()**YDigitalIO****digitalio→setPortPolarity()digitalio.set_portPolarity()**

Changes the polarity of all the bits of the port: 0 makes a bit an input, 1 makes it an output.

| | |
|---------------|---|
| js | function set_portPolarity(newval) |
| nodejs | function set_portPolarity(newval) |
| php | function set_portPolarity(\$newval) |
| cpp | int set_portPolarity(int newval) |
| m | -(int) setPortPolarity : (int) newval |
| pas | function set_portPolarity(newval: LongInt): integer |
| vb | function set_portPolarity(ByVal newval As Integer) As Integer |
| cs | int set_portPolarity(int newval) |
| java | int set_portPolarity(int newval) |
| py | def set_portPolarity(newval) |
| cmd | YDigitalIO target set_portPolarity newval |

Remember to call the `saveToFlash()` method to make sure the setting will be kept after a reboot.

Parameters :

newval an integer corresponding to the polarity of all the bits of the port: 0 makes a bit an input, 1 makes it an output

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→set_portState()**YDigitalIO****digitalio→setPortState()digitalio.set_portState()**

Changes the digital IO port state: bit 0 represents input 0, and so on.

| | |
|---------|--|
| js | function set_portState(newval) |
| node.js | function set_portState(newval) |
| php | function set_portState(\$newval) |
| cpp | int set_portState(int newval) |
| m | -(int) setPortState : (int) newval |
| pas | function set_portState(newval: LongInt): integer |
| vb | function set_portState(ByVal newval As Integer) As Integer |
| cs | int set_portState(int newval) |
| java | int set_portState(int newval) |
| py | def set_portState(newval) |
| cmd | YDigitalIO target set_portState newval |

This function has no effect on bits configured as input in `portDirection`.

Parameters :

newval an integer corresponding to the digital IO port state: bit 0 represents input 0, and so on

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→set(userData)**YDigitalIO****digitalio→setUserData()digitalio.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|---|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData) |
| cpp | void set(userData) (void* data) |
| m | -(void) set(userData : (void*) data |
| pas | procedure set(userData : Tobject) |
| vb | procedure set(userData : ByVal data As Object) |
| cs | void set(userData : object data) |
| java | void set(userData : Object data) |
| py | def set(userData : data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

digitalio→toggle_bitState()|digitalio.toggle_bitState()**YDigitalIO**

Reverts a single bit of the I/O port.

```
js function toggle_bitState( bitno)
nodejs function toggle_bitState( bitno)
php function toggle_bitState( $bitno)
cpp int toggle_bitState( int bitno)
m -(int) toggle_bitState : (int) bitno
pas function toggle_bitState( bitno: LongInt): LongInt
vb function toggle_bitState( ) As Integer
cs int toggle_bitState( int bitno)
java int toggle_bitState( int bitno)
py def toggle_bitState( bitno)
cmd YDigitalIO target toggle_bitState bitno
```

Parameters :

bitno the bit number; lowest bit has index 0

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→wait_async()

YDigitalIO

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.13. Display function interface

Yoctopuce display interface has been designed to easily show information and images. The device provides built-in multi-layer rendering. Layers can be drawn offline, individually, and freely moved on the display. It can also replay recorded sequences (animations).

In order to use the functions described here, you should include:

| | |
|--------|---|
| js | <script type='text/javascript' src='yocto_display.js'></script> |
| nodejs | var yoctolib = require('yoctolib'); |
| | var YDisplay = yoctolib.YDisplay; |
| php | require_once('yocto_display.php'); |
| cpp | #include "yocto_display.h" |
| m | #import "yocto_display.h" |
| pas | uses yocto_display; |
| vb | yocto_display.vb |
| cs | yocto_display.cs |
| java | import com.yoctopuce.YoctoAPI.YDisplay; |
| py | from yocto_display import * |

Global functions

yFindDisplay(func)

Retrieves a display for a given identifier.

yFirstDisplay()

Starts the enumeration of displays currently accessible.

YDisplay methods

display→copyLayerContent(srcLayerId, dstLayerId)

Copies the whole content of a layer to another layer.

display→describe()

Returns a short text that describes unambiguously the instance of the display in the form TYPE (NAME)=SERIAL.FUNCTIONID.

display→fade(brightness, duration)

Smoothly changes the brightness of the screen to produce a fade-in or fade-out effect.

display→get_advertisedValue()

Returns the current value of the display (no more than 6 characters).

display→get_brightness()

Returns the luminosity of the module informative leds (from 0 to 100).

display→get_displayHeight()

Returns the display height, in pixels.

display→get_displayLayer(layerId)

Returns a YDisplayLayer object that can be used to draw on the specified layer.

display→get_displayType()

Returns the display type: monochrome, gray levels or full color.

display→get_displayWidth()

Returns the display width, in pixels.

display→get_enabled()

Returns true if the screen is powered, false otherwise.

display→get_errorMessage()

Returns the error message of the latest error with the display.

display→get_errorType()

Returns the numerical error code of the latest error with the display.

display→get_friendlyName()

Returns a global identifier of the display in the format MODULE_NAME . FUNCTION_NAME.

display→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

display→get_functionId()

Returns the hardware identifier of the display, without reference to the module.

display→get_hardwareId()

Returns the unique hardware identifier of the display in the form SERIAL . FUNCTIONID.

display→get_layerCount()

Returns the number of available layers to draw on.

display→get_layerHeight()

Returns the height of the layers to draw on, in pixels.

display→get_layerWidth()

Returns the width of the layers to draw on, in pixels.

display→get_logicalName()

Returns the logical name of the display.

display→get_module()

Gets the YModule object for the device on which the function is located.

display→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

display→get_orientation()

Returns the currently selected display orientation.

display→get_startupSeq()

Returns the name of the sequence to play when the displayed is powered on.

display→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

display→isOnline()

Checks if the display is currently reachable, without raising any error.

display→isOnline_async(callback, context)

Checks if the display is currently reachable, without raising any error (asynchronous version).

display→load(msValidity)

Preloads the display cache with a specified validity duration.

display→load_async(msValidity, callback, context)

Preloads the display cache with a specified validity duration (asynchronous version).

display→newSequence()

Starts to record all display commands into a sequence, for later replay.

display→nextDisplay()

Continues the enumeration of displays started using yFirstDisplay().

display→pauseSequence(delay_ms)

Waits for a specified delay (in milliseconds) before playing next commands in current sequence.

display→playSequence(sequenceName)

Replays a display sequence previously recorded using newSequence() and saveSequence().

display→registerValueCallback(callback)

3. Reference

Registers the callback function that is invoked on every change of advertised value.

display→resetAll()

Clears the display screen and resets all display layers to their default state.

display→saveSequence(sequenceName)

Stops recording display commands and saves the sequence into the specified file on the display internal memory.

display→set_brightness(newval)

Changes the brightness of the display.

display→set_enabled(newval)

Changes the power state of the display.

display→set_logicalName(newval)

Changes the logical name of the display.

display→set_orientation(newval)

Changes the display orientation.

display→set_startupSeq(newval)

Changes the name of the sequence to play when the displayed is powered on.

display→set(userData)

Stores a user context provided as argument in the userData attribute of the function.

display→stopSequence()

Stops immediately any ongoing sequence replay.

display→swapLayerContent(layerIdA, layerIdB)

Swaps the whole content of two layers.

display→upload(pathname, content)

Uploads an arbitrary file (for instance a GIF file) to the display, to the specified full path name.

display→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YDisplay.FindDisplay() yFindDisplay()YDisplay.FindDisplay()

YDisplay

Retrieves a display for a given identifier.

| | |
|--------|---|
| js | function yFindDisplay(func) |
| nodejs | function FindDisplay(func) |
| php | function yFindDisplay(\$func) |
| cpp | YDisplay* yFindDisplay(string func) |
| m | + (YDisplay*) yFindDisplay : (NSString*) func |
| pas | function yFindDisplay(func: string): TYDisplay |
| vb | function yFindDisplay(ByVal func As String) As YDisplay |
| cs | YDisplay FindDisplay(string func) |
| java | YDisplay FindDisplay(String func) |
| py | def FindDisplay(func) |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the display is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YDisplay.isOnline()` to test if the display is indeed online at a given time. In case of ambiguity when looking for a display by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the display

Returns :

a `YDisplay` object allowing you to drive the display.

YDisplay.FirstDisplay() yFirstDisplay()YDisplay.FirstDisplay()

YDisplay

Starts the enumeration of displays currently accessible.

```
js function yFirstDisplay( )
node.js function FirstDisplay( )
php function yFirstDisplay( )
cpp YDisplay* yFirstDisplay( )
m YDisplay* yFirstDisplay( )
pas function yFirstDisplay( ): TYDisplay
vb function yFirstDisplay( ) As YDisplay
cs YDisplay FirstDisplay( )
java YDisplay FirstDisplay( )
py def FirstDisplay( )
```

Use the method `YDisplay.nextDisplay()` to iterate on next displays.

Returns :

a pointer to a `YDisplay` object, corresponding to the first display currently online, or a `null` pointer if there are none.

display→copyLayerContent() display.copyLayerContent()

YDisplay

Copies the whole content of a layer to another layer.

```

js   function copyLayerContent( srcLayerId, dstLayerId)
nodejs function copyLayerContent( srcLayerId, dstLayerId)
php  function copyLayerContent( $srcLayerId, $dstLayerId)
cpp   int copyLayerContent( int srcLayerId, int dstLayerId)
m     -(int) copyLayerContent : (int) srcLayerId
                  : (int) dstLayerId

pas  function copyLayerContent( srcLayerId: LongInt,
                               dstLayerId: LongInt): LongInt

vb   function copyLayerContent( ) As Integer
cs    int copyLayerContent( int srcLayerId, int dstLayerId)
java  int copyLayerContent( int srcLayerId, int dstLayerId)
py    def copyLayerContent( srcLayerId, dstLayerId)
cmd   YDisplay target copyLayerContent srcLayerId dstLayerId

```

The color and transparency of all the pixels from the destination layer are set to match the source pixels. This method only affects the displayed content, but does not change any property of the layer object. Note that layer 0 has no transparency support (it is always completely opaque).

Parameters :

srcLayerId the identifier of the source layer (a number in range 0..layerCount-1)
dstLayerId the identifier of the destination layer (a number in range 0..layerCount-1)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→describe()display.describe()**YDisplay**

Returns a short text that describes unambiguously the instance of the display in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the display (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

display→fade()`display.fade()`

YDisplay

Smoothly changes the brightness of the screen to produce a fade-in or fade-out effect.

```
js function fade( brightness, duration)
nodejs function fade( brightness, duration)
php function fade( $brightness, $duration)
cpp int fade( int brightness, int duration)
m -(int) fade : (int) brightness : (int) duration
pas function fade( brightness: LongInt, duration: LongInt): LongInt
vb function fade( ) As Integer
cs int fade( int brightness, int duration)
java int fade( int brightness, int duration)
py def fade( brightness, duration)
cmd YDisplay target fade brightness duration
```

Parameters :

brightness the new screen brightness

duration duration of the brightness transition, in milliseconds.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→get_advertisedValue()
display→advertisedValue()
display.get_advertisedValue()**YDisplay**

Returns the current value of the display (no more than 6 characters).

```
js function get_advertisedValue( )  
nodejs function get_advertisedValue( )  
php function get_advertisedValue( )  
cpp string get_advertisedValue( )  
m -(NSString*) advertisedValue  
pas function get_advertisedValue( ): string  
vb function get_advertisedValue( ) As String  
cs string get_advertisedValue( )  
java String get_advertisedValue( )  
py def get_advertisedValue( )  
cmd YDisplay target get_advertisedValue
```

Returns :

a string corresponding to the current value of the display (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

display→get_brightness() display→brightness()display.get_brightness()

YDisplay

Returns the luminosity of the module informative leds (from 0 to 100).

| | |
|--------|--|
| js | function get_brightness() |
| nodejs | function get_brightness() |
| php | function get_brightness() |
| cpp | int get_brightness() |
| m | -(int) brightness |
| pas | function get_brightness() : LongInt |
| vb | function get_brightness() As Integer |
| cs | int get_brightness() |
| java | int get_brightness() |
| py | def get_brightness() |
| cmd | YDisplay target get_brightness |

Returns :

an integer corresponding to the luminosity of the module informative leds (from 0 to 100)

On failure, throws an exception or returns Y_BRIGHTNESS_INVALID.

display→get_displayHeight() YDisplay
display→displayHeight()display.get_displayHeight()

Returns the display height, in pixels.

```
js function get_displayHeight( )  
node.js function get_displayHeight( )  
php function get_displayHeight( )  
cpp int get_displayHeight( )  
m -(int) displayHeight  
pas function get_displayHeight( ): LongInt  
vb function get_displayHeight( ) As Integer  
cs int get_displayHeight( )  
java int get_displayHeight( )  
py def get_displayHeight( )  
cmd YDisplay target get_displayHeight
```

Returns :

an integer corresponding to the display height, in pixels

On failure, throws an exception or returns Y_DISPLAYHEIGHT_INVALID.

display→get_displayLayer() display→displayLayer()display.get_displayLayer()

YDisplay

Returns a YDisplayLayer object that can be used to draw on the specified layer.

```
js function get_displayLayer( layerId)
nodejs function get_displayLayer( layerId)
php function get_displayLayer( $layerId)
cpp YDisplayLayer* get_displayLayer( unsigned layerId)
m -(YDisplayLayer*) displayLayer : (unsigned) layerId
vb function get_displayLayer( ) As YDisplayLayer
cs YDisplayLayer get_displayLayer( int layerId)
java synchronized YDisplayLayer get_displayLayer( int layerId)
py def get_displayLayer( layerId)
```

The content is displayed only when the layer is active on the screen (and not masked by other overlapping layers).

Parameters :

layerId the identifier of the layer (a number in range 0..layerCount-1)

Returns :

an YDisplayLayer object

On failure, throws an exception or returns null.

display→get_displayType()**YDisplay****display→displayType()display.get_displayType()**

Returns the display type: monochrome, gray levels or full color.

| | |
|---------|---|
| js | function get_displayType() |
| node.js | function get_displayType() |
| php | function get_displayType() |
| cpp | Y_DISPLAYTYPE_enum get_displayType() |
| m | -(Y_DISPLAYTYPE_enum) displayType |
| pas | function get_displayType() : Integer |
| vb | function get_displayType() As Integer |
| cs | int get_displayType() |
| java | int get_displayType() |
| py | def get_displayType() |
| cmd | YDisplay target get_displayType |

Returns :

a value among Y_DISPLAYTYPE_MONO, Y_DISPLAYTYPE_GRAY and Y_DISPLAYTYPE_RGB corresponding to the display type: monochrome, gray levels or full color

On failure, throws an exception or returns Y_DISPLAYTYPE_INVALID.

display→get_displayWidth()**YDisplay****display→displayWidth()display.get_displayWidth()**

Returns the display width, in pixels.

| | |
|--------|--|
| js | function get_displayWidth() |
| nodejs | function get_displayWidth() |
| php | function get_displayWidth() |
| cpp | int get_displayWidth() |
| m | -(int) displayWidth |
| pas | function get_displayWidth() : LongInt |
| vb | function get_displayWidth() As Integer |
| cs | int get_displayWidth() |
| java | int get_displayWidth() |
| py | def get_displayWidth() |
| cmd | YDisplay target get_displayWidth |

Returns :

an integer corresponding to the display width, in pixels

On failure, throws an exception or returns **Y_DISPLAYWIDTH_INVALID**.

display→get_enabled()
display→enabled()display.get_enabled()**YDisplay**

Returns true if the screen is powered, false otherwise.

```
js function get_enabled( )
node.js function get_enabled( )
php function get_enabled( )
cpp Y_ENABLED_enum get_enabled( )
m -(Y_ENABLED_enum) enabled
pas function get_enabled( ): Integer
vb function get_enabled( ) As Integer
cs int get_enabled( )
java int get_enabled( )
py def get_enabled( )
cmd YDisplay target get_enabled
```

Returns :

either Y_ENABLED_FALSE or Y_ENABLED_TRUE, according to true if the screen is powered, false otherwise

On failure, throws an exception or returns Y_ENABLED_INVALID.

display→getErrorMessage()**YDisplay****display→errorMessage()display.getErrorMessage()**

Returns the error message of the latest error with the display.

| | |
|--------|--|
| js | function getErrorMessage() |
| nodejs | function getErrorMessage() |
| php | function getErrorMessage() |
| cpp | string getErrorMessage() |
| m | -(NSString*) errorMessage |
| pas | function getErrorMessage() : string |
| vb | function getErrorMessage() As String |
| cs | string getErrorMessage() |
| java | String getErrorMessage() |
| py | def getErrorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the display object

**display→get_errorType()
display→errorType()display.get_errorType()****YDisplay**

Returns the numerical error code of the latest error with the display.

| | |
|---------|--|
| js | function get_errorType() |
| node.js | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType() : YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the display object

display→get_friendlyName()**YDisplay****display→friendlyName()display.get_friendlyName()**

Returns a global identifier of the display in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|-------------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the display if they are defined, otherwise the serial number of the module and the hardware identifier of the display (for exemple: MyCustomName . relay1)

Returns :

a string that uniquely identifies the display using logical names (ex: MyCustomName . relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

**display→get_functionDescriptor()
display→functionDescriptor()
display.get_functionDescriptor()****YDisplay**

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|--------|---|
| js | function get_functionDescriptor() |
| nodejs | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

display→get_functionId()**YDisplay****display→functionId()display.get_functionId()**

Returns the hardware identifier of the display, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the display (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

display→get_hardwareId()**YDisplay****display→hardwareId()display.get_hardwareId()**

Returns the unique hardware identifier of the display in the form SERIAL.FUNCTIONID.

| | |
|---------|--------------------------------------|
| js | function get_hardwareId() |
| node.js | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the display. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the display (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

display→get_layerCount() display→layerCount()display.get_layerCount()

YDisplay

Returns the number of available layers to draw on.

```
js function get_layerCount( )
nodejs function get_layerCount( )
php function get_layerCount( )
cpp int get_layerCount( )
m -(int) layerCount
pas function get_layerCount( ): LongInt
vb function get_layerCount( ) As Integer
cs int get_layerCount( )
java int get_layerCount( )
py def get_layerCount( )
cmd YDisplay target get_layerCount
```

Returns :

an integer corresponding to the number of available layers to draw on

On failure, throws an exception or returns Y_LAYERCOUNT_INVALID.

display→get_layerHeight()**YDisplay****display→layerHeight()display.get_layerHeight()**

Returns the height of the layers to draw on, in pixels.

js function **get_layerHeight()****node.js** function **get_layerHeight()****php** function **get_layerHeight()****cpp** int **get_layerHeight()****m** -(int) **layerHeight****pas** function **get_layerHeight(): LongInt****vb** function **get_layerHeight() As Integer****cs** int **get_layerHeight()****java** int **get_layerHeight()****py** def **get_layerHeight()****cmd** YDisplay **target get_layerHeight****Returns :**

an integer corresponding to the height of the layers to draw on, in pixels

On failure, throws an exception or returns **Y_LAYERHEIGHT_INVALID**.

display→get_layerWidth() display→layerWidth()display.get_layerWidth()

YDisplay

Returns the width of the layers to draw on, in pixels.

```
js function get_layerWidth( )
nodejs function get_layerWidth( )
php function get_layerWidth( )
cpp int get_layerWidth( )
m -(int) layerWidth
pas function get_layerWidth( ): LongInt
vb function get_layerWidth( ) As Integer
cs int get_layerWidth( )
java int get_layerWidth( )
py def get_layerWidth( )
cmd YDisplay target get_layerWidth
```

Returns :

an integer corresponding to the width of the layers to draw on, in pixels

On failure, throws an exception or returns Y_LAYERWIDTH_INVALID.

display→get_logicalName()**YDisplay****display→logicalName()display.get_logicalName()**

Returns the logical name of the display.

```
js function get_logicalName( )  
node.js function get_logicalName( )  
php function get_logicalName( )  
cpp string get_logicalName( )  
m -(NSString*) logicalName  
pas function get_logicalName( ): string  
vb function get_logicalName( ) As String  
cs string get_logicalName( )  
java String get_logicalName( )  
py def get_logicalName( )  
cmd YDisplay target get_logicalName
```

Returns :

a string corresponding to the logical name of the display. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

**display→get_module()
display→module()display.get_module()****YDisplay**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

display→get_module_async()
display→module_async()**YDisplay**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

display→get_orientation() display→orientation()display.get_orientation()

YDisplay

Returns the currently selected display orientation.

```
js function get_orientation( )
nodejs function get_orientation( )
php function get_orientation( )
cpp Y_ORIENTATION_enum get_orientation( )
m -(Y_ORIENTATION_enum) orientation
pas function get_orientation( ): Integer
vb function get_orientation( ) As Integer
cs int get_orientation( )
java int get_orientation( )
py def get_orientation( )
cmd YDisplay target get_orientation
```

Returns :

a value among Y_ORIENTATION_LEFT, Y_ORIENTATION_UP, Y_ORIENTATION_RIGHT and Y_ORIENTATION_DOWN corresponding to the currently selected display orientation

On failure, throws an exception or returns Y_ORIENTATION_INVALID.

display→get_startupSeq() YDisplay
display→startupSeq()display.get_startupSeq()

Returns the name of the sequence to play when the displayed is powered on.

```
js function get_startupSeq( )  
node.js function get_startupSeq( )  
php function get_startupSeq( )  
cpp string get_startupSeq( )  
m -(NSString*) startupSeq  
pas function get_startupSeq( ): string  
vb function get_startupSeq( ) As String  
cs string get_startupSeq( )  
java String get_startupSeq( )  
py def get_startupSeq( )  
cmd YDisplay target get_startupSeq
```

Returns :

a string corresponding to the name of the sequence to play when the displayed is powered on

On failure, throws an exception or returns Y_STARTUPSEQ_INVALID.

display→get(userData) display→userData()display.get(userData)

YDisplay

Returns the value of the userData attribute, as previously stored using method set(userData).

```
js function get(userData) 
nodejs function get(userData) 
php function get(userData) 
cpp void * get(userData) 
m -(void*) userData 
pas function get(userData): Tobject 
vb function get(userData) As Object 
cs object get(userData) 
java Object get(userData) 
py def get(userData)
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

display→isOnline()display.isOnline()**YDisplay**

Checks if the display is currently reachable, without raising any error.

| | |
|--------|---|
| js | function isOnline () |
| nodejs | function isOnline () |
| php | function isOnline () |
| cpp | bool isOnline () |
| m | - (BOOL) isOnline |
| pas | function isOnline (): boolean |
| vb | function isOnline () As Boolean |
| cs | bool isOnline () |
| java | boolean isOnline () |
| py | def isOnline () |

If there is a cached value for the display in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the display.

Returns :

true if the display can be reached, and false otherwise

display→isOnline_async()

YDisplay

Checks if the display is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context)
node.js function isOnline_async( callback, context)
```

If there is a cached value for the display in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

display→load()display.load()

YDisplay

Preloads the display cache with a specified validity duration.

```
js function load( msValidity)
nodejs function load( msValidity)
php function load( $msValidity)
cpp YRETCODE load( int msValidity)
m -(YRETCODE) load : (int) msValidity
pas function load( msValidity: integer): YRETCODE
vb function load( ByVal msValidity As Integer) As YRETCODE
cs YRETCODE load( int msValidity)
java int load( long msValidity)
py def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

display→load_async()

YDisplay

Preloads the display cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

display→newSequence()display.newSequence()**YDisplay**

Starts to record all display commands into a sequence, for later replay.

```
js function newSequence( )  
nodejs function newSequence( )  
php function newSequence( )  
cpp int newSequence( )  
m -(int) newSequence  
pas function newSequence( ): LongInt  
vb function newSequence( ) As Integer  
cs int newSequence( )  
java int newSequence( )  
py def newSequence( )  
cmd YDisplay target newSequence
```

The name used to store the sequence is specified when calling `saveSequence()`, once the recording is complete.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→nextDisplay()display.nextDisplay()**YDisplay**

Continues the enumeration of displays started using `yFirstDisplay()`.

| | |
|--------|--|
| js | function nextDisplay() |
| nodejs | function nextDisplay() |
| php | function nextDisplay() |
| cpp | YDisplay * nextDisplay() |
| m | -(YDisplay *) nextDisplay |
| pas | function nextDisplay() : TYDisplay |
| vb | function nextDisplay() As YDisplay |
| cs | YDisplay nextDisplay() |
| java | YDisplay nextDisplay() |
| py | def nextDisplay() |

Returns :

a pointer to a `YDisplay` object, corresponding to a display currently online, or a `null` pointer if there are no more displays to enumerate.

display→pauseSequence()`display.pauseSequence()`

YDisplay

Waits for a specified delay (in milliseconds) before playing next commands in current sequence.

```
js function pauseSequence( delay_ms)
nodejs function pauseSequence( delay_ms)
php function pauseSequence( $delay_ms)
cpp int pauseSequence( int delay_ms)
m -(int) pauseSequence : (int) delay_ms
pas function pauseSequence( delay_ms: LongInt): LongInt
vb function pauseSequence( ) As Integer
cs int pauseSequence( int delay_ms)
java int pauseSequence( int delay_ms)
py def pauseSequence( delay_ms)
cmd YDisplay target pauseSequence delay_ms
```

This method can be used while recording a display sequence, to insert a timed wait in the sequence (without any immediate effect). It can also be used dynamically while playing a pre-recorded sequence, to suspend or resume the execution of the sequence. To cancel a delay, call the same method with a zero delay.

Parameters :

delay_ms the duration to wait, in milliseconds

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→playSequence()`display.playSequence()`

YDisplay

Replays a display sequence previously recorded using `newSequence()` and `saveSequence()`.

```
js function playSequence( sequenceName)
nodejs function playSequence( sequenceName)
php function playSequence( $sequenceName)
cpp int playSequence( string sequenceName)
m -(int) playSequence : (NSString*) sequenceName
pas function playSequence( sequenceName: string): LongInt
vb function playSequence( ) As Integer
cs int playSequence( string sequenceName)
java int playSequence( String sequenceName)
py def playSequence( sequenceName)
cmd YDisplay target playSequence sequenceName
```

Parameters :

`sequenceName` the name of the newly created sequence

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→registerValueCallback() display.registerValueCallback()

YDisplay

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YDisplayValueCallback callback )
m    -(int) registerValueCallback : (YDisplayValueCallback) callback
pas   function registerValueCallback( callback: TYDisplayValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

display→resetAll()display.resetAll()**YDisplay**

Clears the display screen and resets all display layers to their default state.

| | |
|--------|--|
| js | function resetAll() |
| nodejs | function resetAll() |
| php | function resetAll() |
| cpp | int resetAll() |
| m | - (int) resetAll |
| pas | function resetAll(): LongInt |
| vb | function resetAll() As Integer |
| cs | int resetAll() |
| java | int resetAll() |
| py | def resetAll() |
| cmd | YDisplay target resetAll |

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→saveSequence()display.saveSequence()**YDisplay**

Stops recording display commands and saves the sequence into the specified file on the display internal memory.

```
js function saveSequence( sequenceName)
nodejs function saveSequence( sequenceName)
php function saveSequence( $sequenceName)
cpp int saveSequence( string sequenceName)
m -(int) saveSequence : (NSString*) sequenceName
pas function saveSequence( sequenceName: string): LongInt
vb function saveSequence( ) As Integer
cs int saveSequence( string sequenceName)
java int saveSequence( String sequenceName)
py def saveSequence( sequenceName)
cmd YDisplay target saveSequence sequenceName
```

The sequence can be later replayed using `playSequence()`.

Parameters :

sequenceName the name of the newly created sequence

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→set_brightness()**display→setBrightness()display.set_brightness()****YDisplay**

Changes the brightness of the display.

| | |
|---------------|---|
| js | <code>function set_brightness(newval)</code> |
| nodejs | <code>function set_brightness(newval)</code> |
| php | <code>function set_brightness(\$newval)</code> |
| cpp | <code>int set_brightness(int newval)</code> |
| m | <code>-(int) setBrightness : (int) newval</code> |
| pas | <code>function set_brightness(newval: LongInt): integer</code> |
| vb | <code>function set_brightness(ByVal newval As Integer) As Integer</code> |
| cs | <code>int set_brightness(int newval)</code> |
| java | <code>int set_brightness(int newval)</code> |
| py | <code>def set_brightness(newval)</code> |
| cmd | <code>YDisplay target set_brightness newval</code> |

The parameter is a value between 0 and 100. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval an integer corresponding to the brightness of the display

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

**display→set_enabled()
display→setEnabled()
display.set_enabled()****YDisplay**

Changes the power state of the display.

```
js function set_enabled( newval)
node.js function set_enabled( newval)
php function set_enabled( $newval)
cpp int set_enabled( Y_ENABLED_enum newval)
m -(int) setEnabled : (Y_ENABLED_enum) newval
pas function set_enabled( newval: Integer): integer
vb function set_enabled( ByVal newval As Integer) As Integer
cs int set_enabled( int newval)
java int set_enabled( int newval)
py def set_enabled( newval)
cmd YDisplay target set_enabled newval
```

Parameters :

newval either Y_ENABLED_FALSE or Y_ENABLED_TRUE, according to the power state of the display

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→set_logicalName() display→setLogicalName()display.set_logicalName()

YDisplay

Changes the logical name of the display.

| | |
|--------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YDisplay target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the display.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

display→set_orientation() display→setOrientation()display.set_orientation()

YDisplay

Changes the display orientation.

```
js function set_orientation( newval)
node.js function set_orientation( newval)
php function set_orientation( $newval)
cpp int set_orientation( Y_ORIENTATION_enum newval)
m -(int) setOrientation : (Y_ORIENTATION_enum) newval
pas function set_orientation( newval: Integer): integer
vb function set_orientation( ByVal newval As Integer) As Integer
cs int set_orientation( int newval)
java int set_orientation( int newval)
py def set_orientation( newval)
cmd YDisplay target set_orientation newval
```

Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a value among `Y_ORIENTATION_LEFT`, `Y_ORIENTATION_UP`, `Y_ORIENTATION_RIGHT` and `Y_ORIENTATION_DOWN` corresponding to the display orientation

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→set_startupSeq() display→setStartupSeq()display.set_startupSeq()

YDisplay

Changes the name of the sequence to play when the displayed is powered on.

| | |
|--------|--|
| js | function set_startupSeq(newval) |
| nodejs | function set_startupSeq(newval) |
| php | function set_startupSeq(\$newval) |
| cpp | int set_startupSeq(const string& newval) |
| m | -(int) setStartupSeq : (NSString*) newval |
| pas | function set_startupSeq(newval: string): integer |
| vb | function set_startupSeq(ByVal newval As String) As Integer |
| cs | int set_startupSeq(string newval) |
| java | int set_startupSeq(String newval) |
| py | def set_startupSeq(newval) |
| cmd | YDisplay target set_startupSeq newval |

Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the name of the sequence to play when the displayed is powered on

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→set(userData) display→setUserData()display.set(userData)

YDisplay

Stores a user context provided as argument in the userData attribute of the function.

```
js   function set(userData) data
node.js function set(userData) data
php  function set(userData) $data
cpp   void set(userData void* data)
m    -(void) setUserData : (void*) data
pas   procedure set(userData data: Tobject)
vb    procedure set(userData ByVal data As Object)
cs    void set(userData object data)
java  void set(userData Object data)
py    def set(userData data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

display→stopSequence()display.stopSequence()**YDisplay**

Stops immediately any ongoing sequence replay.

| | |
|---------|-------------------------------------|
| js | function stopSequence() |
| node.js | function stopSequence() |
| php | function stopSequence() |
| cpp | int stopSequence() |
| m | -(int) stopSequence |
| pas | function stopSequence(): LongInt |
| vb | function stopSequence() As Integer |
| cs | int stopSequence() |
| java | int stopSequence() |
| py | def stopSequence() |
| cmd | YDisplay target stopSequence |

The display is left as is.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→swapLayerContent() display.swapLayerContent()

YDisplay

Swaps the whole content of two layers.

```

js   function swapLayerContent( layerIdA, layerIdB)
node.js function swapLayerContent( layerIdA, layerIdB)
php  function swapLayerContent( $layerIdA, $layerIdB)
cpp   int swapLayerContent( int layerIdA, int layerIdB)
m    -(int) swapLayerContent : (int) layerIdA
                 : (int) layerIdB

pas  function swapLayerContent( layerIdA: LongInt, layerIdB: LongInt): LongInt
vb   function swapLayerContent( ) As Integer
cs   int swapLayerContent( int layerIdA, int layerIdB)
java  int swapLayerContent( int layerIdA, int layerIdB)
py    def swapLayerContent( layerIdA, layerIdB)
cmd   YDisplay target swapLayerContent layerIdA layerIdB

```

The color and transparency of all the pixels from the two layers are swapped. This method only affects the displayed content, but does not change any property of the layer objects. In particular, the visibility of each layer stays unchanged. When used between one hidden layer and a visible layer, this method makes it possible to easily implement double-buffering. Note that layer 0 has no transparency support (it is always completely opaque).

Parameters :

layerIdA the first layer (a number in range 0..layerCount-1)
layerIdB the second layer (a number in range 0..layerCount-1)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→upload()display.upload()**YDisplay**

Uploads an arbitrary file (for instance a GIF file) to the display, to the specified full path name.

| | |
|--------|--|
| js | function upload (pathname , content) |
| nodejs | function upload (pathname , content) |
| php | function upload (\$pathname , \$content) |
| cpp | int upload (string pathname , string content) |
| m | - (int upload : (NSString*) pathname : (NSData*) content |
| pas | function upload (pathname : string, content : TByteArray): LongInt |
| vb | procedure upload () |
| cs | int upload (string pathname) |
| java | int upload (String pathname) |
| py | def upload (pathname , content) |
| cmd | YDisplay target upload pathname content |

If a file already exists with the same path name, its content is overwritten.

Parameters :

pathname path and name of the new file to create
content binary buffer with the content to set

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→wait_async()

YDisplay

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.14. DisplayLayer object interface

A DisplayLayer is an image layer containing objects to display (bitmaps, text, etc.). The content is displayed only when the layer is active on the screen (and not masked by other overlapping layers).

In order to use the functions described here, you should include:

| | |
|--------|---|
| js | <script type='text/javascript' src='yocto_display.js'></script> |
| nodejs | var yoctolib = require('yoctolib'); |
| | var YDisplay = yoctolib.YDisplay; |
| php | require_once('yocto_display.php'); |
| cpp | #include "yocto_display.h" |
| m | #import "yocto_display.h" |
| pas | uses yocto_display; |
| vb | yocto_display.vb |
| cs | yocto_display.cs |
| java | import com.yoctopuce.YoctoAPI.YDisplay; |
| py | from yocto_display import * |

YDisplayLayer methods

displaylayer→clear()

Erases the whole content of the layer (makes it fully transparent).

displaylayer→clearConsole()

Blanks the console area within console margins, and resets the console pointer to the upper left corner of the console.

displaylayer→consoleOut(text)

Outputs a message in the console area, and advances the console pointer accordingly.

displaylayer→drawBar(x1, y1, x2, y2)

Draws a filled rectangular bar at a specified position.

displaylayer→drawBitmap(x, y, w, bitmap, bgcol)

Draws a bitmap at the specified position.

displaylayer→drawCircle(x, y, r)

Draws an empty circle at a specified position.

displaylayer→drawDisc(x, y, r)

Draws a filled disc at a given position.

displaylayer→drawImage(x, y, imagename)

Draws a GIF image at the specified position.

displaylayer→drawPixel(x, y)

Draws a single pixel at the specified position.

displaylayer→drawRect(x1, y1, x2, y2)

Draws an empty rectangle at a specified position.

displaylayer→drawText(x, y, anchor, text)

Draws a text string at the specified position.

displaylayer→get_display()

Gets parent YDisplay.

displaylayer→get_displayHeight()

Returns the display height, in pixels.

displaylayer→get_displayWidth()

Returns the display width, in pixels.

3. Reference

displaylayer→get_layerHeight()

Returns the height of the layers to draw on, in pixels.

displaylayer→get_layerWidth()

Returns the width of the layers to draw on, in pixels.

displaylayer→hide()

Hides the layer.

displaylayer→lineTo(x, y)

Draws a line from current drawing pointer position to the specified position.

displaylayer→moveTo(x, y)

Moves the drawing pointer of this layer to the specified position.

displaylayer→reset()

Reverts the layer to its initial state (fully transparent, default settings).

displaylayer→selectColorPen(color)

Selects the pen color for all subsequent drawing functions, including text drawing.

displaylayer→selectEraser()

Selects an eraser instead of a pen for all subsequent drawing functions, except for text drawing and bitmap copy functions.

displaylayer→selectFont(fontname)

Selects a font to use for the next text drawing functions, by providing the name of the font file.

displaylayer→selectGrayPen(graylevel)

Selects the pen gray level for all subsequent drawing functions, including text drawing.

displaylayer→setAntialiasingMode(mode)

Enables or disables anti-aliasing for drawing oblique lines and circles.

displaylayer→setConsoleBackground(bgcol)

Sets up the background color used by the `clearConsole` function and by the console scrolling feature.

displaylayer→setConsoleMargins(x1, y1, x2, y2)

Sets up display margins for the `consoleOut` function.

displaylayer→setConsoleWordWrap(wordwrap)

Sets up the wrapping behaviour used by the `consoleOut` function.

displaylayer→setLayerPosition(x, y, scrollTime)

Sets the position of the layer relative to the display upper left corner.

displaylayer→unhide()

Shows the layer.

displaylayer→clear()**displaylayer.clear()**

YDisplayLayer

Erases the whole content of the layer (makes it fully transparent).

```
js function clear( )
nodejs function clear( )
php function clear( )
cpp int clear( )
m -(int) clear
pas function clear( ): LongInt
vb function clear( ) As Integer
cs int clear( )
java int clear( )
py def clear( )
cmd YDisplay target [-layer layerId] clear
```

This method does not change any other attribute of the layer. To reinitialize the layer attributes to defaults settings, use the method `reset()` instead.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→clearConsole()
displaylayer.clearConsole()**YDisplayLayer**

Blanks the console area within console margins, and resets the console pointer to the upper left corner of the console.

| | |
|--------|--|
| js | function clearConsole() |
| nodejs | function clearConsole() |
| php | function clearConsole() |
| cpp | int clearConsole() |
| m | - (int) clearConsole |
| pas | function clearConsole(): LongInt |
| vb | function clearConsole() As Integer |
| cs | int clearConsole() |
| java | int clearConsole() |
| py | def clearConsole() |
| cmd | YDisplay target [-layer layerId] clearConsole |

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→consoleOut()displaylayer.consoleOut()**YDisplayLayer**

Outputs a message in the console area, and advances the console pointer accordingly.

| | |
|---------|---|
| js | function consoleOut(text) |
| node.js | function consoleOut(text) |
| php | function consoleOut(\$text) |
| cpp | int consoleOut(string text) |
| m | - (int) consoleOut : (NSString*) text |
| pas | function consoleOut(text: string): LongInt |
| vb | function consoleOut() As Integer |
| cs | int consoleOut(string text) |
| java | int consoleOut(String text) |
| py | def consoleOut(text) |
| cmd | YDisplay target [-layer layerId] consoleOut text |

The console pointer position is automatically moved to the beginning of the next line when a newline character is met, or when the right margin is hit. When the new text to display extends below the lower margin, the console area is automatically scrolled up.

Parameters :

text the message to display

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→drawBar()displaylayer.drawBar()**YDisplayLayer**

Draws a filled rectangular bar at a specified position.

```

js function drawBar( x1, y1, x2, y2)
nodejs function drawBar( x1, y1, x2, y2)
php function drawBar( $x1, $y1, $x2, $y2)
cpp int drawBar( int x1, int y1, int x2, int y2)
m -(int) drawBar : (int) x1
           : (int) y1
           : (int) x2
           : (int) y2
pas function drawBar( x1: LongInt,
                      y1: LongInt,
                      x2: LongInt,
                      y2: LongInt): LongInt
vb function drawBar( ) As Integer
cs int drawBar( int x1, int y1, int x2, int y2)
java int drawBar( int x1, int y1, int x2, int y2)
py def drawBar( x1, y1, x2, y2)
cmd YDisplay target [-layer layerId] drawBar x1 y1 x2 y2

```

Parameters :

x1 the distance from left of layer to the left border of the rectangle, in pixels
y1 the distance from top of layer to the top border of the rectangle, in pixels
x2 the distance from left of layer to the right border of the rectangle, in pixels
y2 the distance from top of layer to the bottom border of the rectangle, in pixels

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→drawBitmap() displaylayer.drawBitmap()

YDisplayLayer

Draws a bitmap at the specified position.

```

js   function drawBitmap( x, y, w, bitmap, bgcol)
nodejs function drawBitmap( x, y, w, bitmap, bgcol)
php  function drawBitmap( $x, $y, $w, $bitmap, $bgcol)
cpp   int drawBitmap( int x, int y, int w, string bitmap, int bgcol)
m    -(int) drawBitmap : (int) x
      : (int) y
      : (int) w
      : (NSData*) bitmap
      : (int) bgcol

pas  function drawBitmap( x: LongInt,
                        y: LongInt,
                        w: LongInt,
                        bitmap: TByteArray,
                        bgcol: LongInt): LongInt

vb   procedure drawBitmap( )
cs    int drawBitmap( int x, int y, int w, int bgcol)
java  int drawBitmap( int x, int y, int w, int bgcol)
py    def drawBitmap( x, y, w, bitmap, bgcol)
cmd   YDisplay target [-layer layerId] drawBitmap x y w bitmap bgcol

```

The bitmap is provided as a binary object, where each pixel maps to a bit, from left to right and from top to bottom. The most significant bit of each byte maps to the leftmost pixel, and the least significant bit maps to the rightmost pixel. Bits set to 1 are drawn using the layer selected pen color. Bits set to 0 are drawn using the specified background gray level, unless -1 is specified, in which case they are not drawn at all (as if transparent).

Parameters :

- x** the distance from left of layer to the left of the bitmap, in pixels
- y** the distance from top of layer to the top of the bitmap, in pixels
- w** the width of the bitmap, in pixels
- bitmap** a binary object
- bgcol** the background gray level to use for zero bits (0 = black, 255 = white), or -1 to leave the pixels unchanged

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→drawCircle()displaylayer.drawCircle()**YDisplayLayer**

Draws an empty circle at a specified position.

```
js function drawCircle( x, y, r)
nodejs function drawCircle( x, y, r)
php function drawCircle( $x, $y, $r)
cpp int drawCircle( int x, int y, int r)
m -(int) drawCircle : (int) x
               : (int) y
               : (int) r

pas function drawCircle( x: LongInt, y: LongInt, r: LongInt): LongInt
vb function drawCircle( ) As Integer
cs int drawCircle( int x, int y, int r)
java int drawCircle( int x, int y, int r)
py def drawCircle( x, y, r)
cmd YDisplay target [-layer layerId] drawCircle x y r
```

Parameters :

- x** the distance from left of layer to the center of the circle, in pixels
- y** the distance from top of layer to the center of the circle, in pixels
- r** the radius of the circle, in pixels

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→drawDisc()displaylayer.drawDisc()**YDisplayLayer**

Draws a filled disc at a given position.

| | |
|---------------|---|
| js | function drawDisc(x, y, r) |
| nodejs | function drawDisc(x, y, r) |
| php | function drawDisc(\$x, \$y, \$r) |
| cpp | int drawDisc(int x, int y, int r) |
| m | - (int) drawDisc : (int) x : (int) y : (int) r |
| pas | function drawDisc(x: LongInt, y: LongInt, r: LongInt): LongInt |
| vb | function drawDisc() As Integer |
| cs | int drawDisc(int x, int y, int r) |
| java | int drawDisc(int x, int y, int r) |
| py | def drawDisc(x, y, r) |
| cmd | YDisplay target [-layer layerId] drawDisc x y r |

Parameters :

- x** the distance from left of layer to the center of the disc, in pixels
- y** the distance from top of layer to the center of the disc, in pixels
- r** the radius of the disc, in pixels

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→drawImage()displaylayer.drawImage()**YDisplayLayer**

Draws a GIF image at the specified position.

```

js function drawImage( x, y, imagename)
nodejs function drawImage( x, y, imagename)
php function drawImage( $x, $y, $imagename)
cpp int drawImage( int x, int y, string imagename)
m -(int) drawImage : (int) x
: (int) y
: (NSString*) imagename

pas function drawImage( x: LongInt, y: LongInt, imagename: string): LongInt
vb function drawImage( ) As Integer
cs int drawImage( int x, int y, string imagename)
java int drawImage( int x, int y, String imagename)
py def drawImage( x, y, imagename)
cmd YDisplay target [-layer layerId] drawImage x y imagename

```

The GIF image must have been previously uploaded to the device built-in memory. If you experience problems using an image file, check the device logs for any error message such as missing image file or bad image file format.

Parameters :

x the distance from left of layer to the left of the image, in pixels
y the distance from top of layer to the top of the image, in pixels
imagename the GIF file name

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

**displaylayer→drawPixel()
displaylayer.drawPixel()****YDisplayLayer**

Draws a single pixel at the specified position.

```
js function drawPixel( x, y)
nodejs function drawPixel( x, y)
php function drawPixel( $x, $y)
cpp int drawPixel( int x, int y)
m -(int) drawPixel : (int) x
                  : (int) y
pas function drawPixel( x: LongInt, y: LongInt): LongInt
vb function drawPixel( ) As Integer
cs int drawPixel( int x, int y)
java int drawPixel( int x, int y)
py def drawPixel( x, y)
cmd YDisplay target [-layer layerId] drawPixel x y
```

Parameters :

x the distance from left of layer, in pixels
y the distance from top of layer, in pixels

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→drawRect()displaylayer.drawRect()**YDisplayLayer**

Draws an empty rectangle at a specified position.

```

js function drawRect( x1, y1, x2, y2)
nodejs function drawRect( x1, y1, x2, y2)
php function drawRect( $x1, $y1, $x2, $y2)
cpp int drawRect( int x1, int y1, int x2, int y2)
m -(int) drawRect : (int) x1
           : (int) y1
           : (int) x2
           : (int) y2
pas function drawRect( x1: LongInt,
                      y1: LongInt,
                      x2: LongInt,
                      y2: LongInt): LongInt
vb function drawRect( ) As Integer
cs int drawRect( int x1, int y1, int x2, int y2)
java int drawRect( int x1, int y1, int x2, int y2)
py def drawRect( x1, y1, x2, y2)
cmd YDisplay target [-layer layerId] drawRect x1 y1 x2 y2

```

Parameters :

x1 the distance from left of layer to the left border of the rectangle, in pixels
y1 the distance from top of layer to the top border of the rectangle, in pixels
x2 the distance from left of layer to the right border of the rectangle, in pixels
y2 the distance from top of layer to the bottom border of the rectangle, in pixels

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→drawText()displaylayer.drawText()**YDisplayLayer**

Draws a text string at the specified position.

```

js   function drawText( x, y, anchor, text)
node.js function drawText( x, y, anchor, text)
php  function drawText( $x, $y, $anchor, $text)
cpp   int drawText( int x, int y, Y_ALIGN anchor, string text)
m     -(int) drawText : (int) x
          : (int) y
          : (Y_ALIGN) anchor
          : (NSString*) text

pas  function drawText( x: LongInt,
                      y: LongInt,
                      anchor: TYALIGN,
                      text: string): LongInt

vb   function drawText( ) As Integer
cs    int drawText( int x, int y, ALIGN anchor, string text)
java   int drawText( int x, int y, ALIGN anchor, String text)
py     def drawText( x, y, anchor, text)
cmd   YDisplay target [-layer layerId] drawText x y anchor text

```

The point of the text that is aligned to the specified pixel position is called the anchor point, and can be chosen among several options. Text is rendered from left to right, without implicit wrapping.

Parameters :

- x** the distance from left of layer to the text anchor point, in pixels
- y** the distance from top of layer to the text anchor point, in pixels
- anchor** the text anchor point, chosen among the `Y_ALIGN` enumeration: `Y_ALIGN_TOP_LEFT`, `Y_ALIGN_CENTER_LEFT`, `Y_ALIGN_BASELINE_LEFT`, `Y_ALIGN_BOTTOM_LEFT`, `Y_ALIGN_TOP_CENTER`, `Y_ALIGN_CENTER`, `Y_ALIGN_BASELINE_CENTER`, `Y_ALIGN_BOTTOM_CENTER`, `Y_ALIGN_TOP_DECIMAL`, `Y_ALIGN_CENTER_DECIMAL`, `Y_ALIGN_BASELINE_DECIMAL`, `Y_ALIGN_BOTTOM_DECIMAL`, `Y_ALIGN_TOP_RIGHT`, `Y_ALIGN_CENTER_RIGHT`, `Y_ALIGN_BASELINE_RIGHT`, `Y_ALIGN_BOTTOM_RIGHT`.
- text** the text string to draw

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→get_display()**YDisplayLayer****displaylayer→display()displaylayer.get_display()**

Gets parent YDisplay.

```
js function get_display( )
node.js function get_display( )
php function get_display( )
cpp YDisplay* get_display( )
m -(YDisplay*) display
pas function get_display( ): TYDisplay
vb function get_display( ) As YDisplay
cs YDisplay get_display( )
java YDisplay get_display( )
py def get_display( )
```

Returns the parent YDisplay object of the current YDisplayLayer.

Returns :

an YDisplay object

displaylayer→get_displayHeight()
displaylayer→displayHeight()
displaylayer.get_displayHeight()

YDisplayLayer

Returns the display height, in pixels.

| | |
|----------------|---|
| js | function get_displayHeight() |
| node.js | function get_displayHeight() |
| php | function get_displayHeight() |
| cpp | int get_displayHeight() |
| m | -(int) displayHeight |
| pas | function get_displayHeight() : LongInt |
| vb | function get_displayHeight() As Integer |
| cs | int get_displayHeight() |
| java | int get_displayHeight() |
| py | def get_displayHeight() |
| cmd | YDisplay target [-layer layerId] get_displayHeight |

Returns :

an integer corresponding to the display height, in pixels On failure, throws an exception or returns Y_DISPLAYHEIGHT_INVALID.

**displaylayer→get_displayWidth()
displaylayer→displayWidth()
displaylayer.get_displayWidth()****YDisplayLayer**

Returns the display width, in pixels.

| | |
|--------|--|
| js | function get_displayWidth() |
| nodejs | function get_displayWidth() |
| php | function get_displayWidth() |
| cpp | int get_displayWidth() |
| m | -(int) displayWidth |
| pas | function get_displayWidth() : LongInt |
| vb | function get_displayWidth() As Integer |
| cs | int get_displayWidth() |
| java | int get_displayWidth() |
| py | def get_displayWidth() |
| cmd | YDisplay target [-layer layerId] get_displayWidth |

Returns :

an integer corresponding to the display width, in pixels On failure, throws an exception or returns Y_DISPLAYWIDTH_INVALID.

displaylayer→get_layerHeight()
displaylayer→layerHeight()
displaylayer.get_layerHeight()**YDisplayLayer**

Returns the height of the layers to draw on, in pixels.

| | |
|---------|---|
| js | function get_layerHeight() |
| node.js | function get_layerHeight() |
| php | function get_layerHeight() |
| cpp | int get_layerHeight() |
| m | -(int) layerHeight |
| pas | function get_layerHeight() : LongInt |
| vb | function get_layerHeight() As Integer |
| cs | int get_layerHeight() |
| java | int get_layerHeight() |
| py | def get_layerHeight() |
| cmd | YDisplay target [-layer layerId] get_layerHeight |

Returns :

an integer corresponding to the height of the layers to draw on, in pixels

On failure, throws an exception or returns Y_LAYERHEIGHT_INVALID.

**displaylayer→get_layerWidth()
displaylayer→layerWidth()
displaylayer.get_layerWidth()****YDisplayLayer**

Returns the width of the layers to draw on, in pixels.

```
js function get_layerWidth( )  
nodejs function get_layerWidth( )  
php function get_layerWidth( )  
cpp int get_layerWidth( )  
m -(int) layerWidth  
pas function get_layerWidth( ): LongInt  
vb function get_layerWidth( ) As Integer  
cs int get_layerWidth( )  
java int get_layerWidth( )  
py def get_layerWidth( )  
cmd YDisplay target [-layer layerId] get_layerWidth
```

Returns :

an integer corresponding to the width of the layers to draw on, in pixels

On failure, throws an exception or returns Y_LAYERWIDTH_INVALID.

displaylayer→hide()displaylayer.hide()**YDisplayLayer**

Hides the layer.

```
js function hide( )
node.js function hide( )
php function hide( )
cpp int hide( )
m -(int) hide
pas function hide( ): LongInt
vb function hide( ) As Integer
cs int hide( )
java int hide( )
py def hide( )
cmd YDisplay target [-layer layerId] hide
```

The state of the layer is preserved but the layer is not displayed on the screen until the next call to `unhide()`. Hiding the layer can positively affect the drawing speed, since it postpones the rendering until all operations are completed (double-buffering).

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→lineTo()displaylayer.lineTo()

YDisplayLayer

Draws a line from current drawing pointer position to the specified position.

```
js function lineTo( x, y)
nodejs function lineTo( x, y)
php function lineTo( $x, $y)
cpp int lineTo( int x, int y)
m -(int) lineTo : (int) x
: (int) y
pas function lineTo( x: LongInt, y: LongInt): LongInt
vb function lineTo( ) As Integer
cs int lineTo( int x, int y)
java int lineTo( int x, int y)
py def lineTo( x, y)
cmd YDisplay target [-layer layerId] lineTo x y
```

The specified destination pixel is included in the line. The pointer position is then moved to the end point of the line.

Parameters :

x the distance from left of layer to the end point of the line, in pixels
y the distance from top of layer to the end point of the line, in pixels

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→moveTo()displaylayer.moveTo()**YDisplayLayer**

Moves the drawing pointer of this layer to the specified position.

| | |
|---------|--|
| js | function moveTo(x, y) |
| node.js | function moveTo(x, y) |
| php | function moveTo(\$x, \$y) |
| cpp | int moveTo(int x, int y) |
| m | - (int) moveTo : (int) x : (int) y |
| pas | function moveTo(x: LongInt, y: LongInt): LongInt |
| vb | function moveTo() As Integer |
| cs | int moveTo(int x, int y) |
| java | int moveTo(int x, int y) |
| py | def moveTo(x, y) |
| cmd | YDisplay target [-layer layerId] moveTo x y |

Parameters :

x the distance from left of layer, in pixels
y the distance from top of layer, in pixels

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→reset()displaylayer.reset()**YDisplayLayer**

Reverts the layer to its initial state (fully transparent, default settings).

```
js function reset( )  
nodejs function reset( )  
php function reset( )  
cpp int reset( )  
m -(int) reset  
pas function reset( ): LongInt  
vb function reset( ) As Integer  
cs int reset( )  
java int reset( )  
py def reset( )  
cmd YDisplay target [-layer layerId] reset
```

Reinitializes the drawing pointer to the upper left position, and selects the most visible pen color. If you only want to erase the layer content, use the method `clear()` instead.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→selectColorPen()
displaylayer.selectColorPen()**YDisplayLayer**

Selects the pen color for all subsequent drawing functions, including text drawing.

| | |
|---------|--|
| js | function selectColorPen(color) |
| node.js | function selectColorPen(color) |
| php | function selectColorPen(\$color) |
| cpp | int selectColorPen(int color) |
| m | - (int) selectColorPen : (int) color |
| pas | function selectColorPen(color: LongInt): LongInt |
| vb | function selectColorPen() As Integer |
| cs | int selectColorPen(int color) |
| java | int selectColorPen(int color) |
| py | def selectColorPen(color) |
| cmd | YDisplay target [-layer layerId] selectColorPen color |

The pen color is provided as an RGB value. For grayscale or monochrome displays, the value is automatically converted to the proper range.

Parameters :

color the desired pen color, as a 24-bit RGB value

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→selectEraser()
displaylayer.selectEraser()**YDisplayLayer**

Selects an eraser instead of a pen for all subsequent drawing functions, except for text drawing and bitmap copy functions.

```
js function selectEraser( )  
nodejs function selectEraser( )  
php function selectEraser( )  
cpp int selectEraser( )  
m -(int) selectEraser  
pas function selectEraser( ): LongInt  
vb function selectEraser( ) As Integer  
cs int selectEraser( )  
java int selectEraser( )  
py def selectEraser( )  
cmd YDisplay target [-layer layerId] selectEraser
```

Any point drawn using the eraser becomes transparent (as when the layer is empty), showing the other layers beneath it.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→selectFont()displaylayer.selectFont()**YDisplayLayer**

Selects a font to use for the next text drawing functions, by providing the name of the font file.

```
js function selectFont( fontname)
nodejs function selectFont( fontname)
php function selectFont( $fontname)
cpp int selectFont( string fontname)
m -(int) selectFont : (NSString*) fontname
pas function selectFont( fontname: string): LongInt
vb function selectFont( ) As Integer
cs int selectFont( string fontname)
java int selectFont( String fontname)
py def selectFont( fontname)
cmd YDisplay target [-layer layerId] selectFont fontname
```

You can use a built-in font as well as a font file that you have previously uploaded to the device built-in memory. If you experience problems selecting a font file, check the device logs for any error message such as missing font file or bad font file format.

Parameters :

fontname the font file name

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→selectGrayPen()
displaylayer.selectGrayPen()**YDisplayLayer**

Selects the pen gray level for all subsequent drawing functions, including text drawing.

```
js function selectGrayPen( graylevel)
node.js function selectGrayPen( graylevel)
php function selectGrayPen( $graylevel)
cpp int selectGrayPen( int graylevel)
m -(int) selectGrayPen : (int) graylevel
pas function selectGrayPen( graylevel: LongInt): LongInt
vb function selectGrayPen( ) As Integer
cs int selectGrayPen( int graylevel)
java int selectGrayPen( int graylevel)
py def selectGrayPen( graylevel)
cmd YDisplay target [-layer layerId] selectGrayPen graylevel
```

The gray level is provided as a number between 0 (black) and 255 (white, or whichever the highest color is). For monochrome displays (without gray levels), any value lower than 128 is rendered as black, and any value equal or above to 128 is non-black.

Parameters :

graylevel the desired gray level, from 0 to 255

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→setAntialiasingMode() displaylayer.setAntialiasingMode()

YDisplayLayer

Enables or disables anti-aliasing for drawing oblique lines and circles.

| | |
|---------|--|
| js | function setAntialiasingMode(mode) |
| node.js | function setAntialiasingMode(mode) |
| php | function setAntialiasingMode(\$mode) |
| cpp | int setAntialiasingMode(bool mode) |
| m | -(int) setAntialiasingMode : (bool) mode |
| pas | function setAntialiasingMode(mode: boolean): LongInt |
| vb | function setAntialiasingMode() As Integer |
| cs | int setAntialiasingMode(bool mode) |
| java | int setAntialiasingMode(boolean mode) |
| py | def setAntialiasingMode(mode) |
| cmd | YDisplay target [-layer layerId] setAntialiasingMode mode |

Anti-aliasing provides a smoother aspect when looked from far enough, but it can add fuzziness when the display is looked from very close. At the end of the day, it is your personal choice. Anti-aliasing is enabled by default on grayscale and color displays, but you can disable it if you prefer. This setting has no effect on monochrome displays.

Parameters :

mode true to enable antialiasing, false to disable it.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→setConsoleBackground()
displaylayer.setConsoleBackground()**YDisplayLayer**

Sets up the background color used by the `clearConsole` function and by the console scrolling feature.

```
js   function setConsoleBackground( bgcol)
nodejs function setConsoleBackground( bgcol)
php  function setConsoleBackground( $bgcol)
cpp   int setConsoleBackground( int bgcol)
m    -(int) setConsoleBackground : (int) bgcol
pas   function setConsoleBackground( bgcol: LongInt): LongInt
vb    function setConsoleBackground( ) As Integer
cs    int setConsoleBackground( int bgcol)
java  int setConsoleBackground( int bgcol)
py    def setConsoleBackground( bgcol)
cmd   YDisplay target [-layer layerId] setConsoleBackground bgcol
```

Parameters :

bgcol the background gray level to use when scrolling (0 = black, 255 = white), or -1 for transparent

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→setConsoleMargins() displaylayer.setConsoleMargins()

YDisplayLayer

Sets up display margins for the `consoleOut` function.

```

js   function setConsoleMargins( x1, y1, x2, y2)
nodejs function setConsoleMargins( x1, y1, x2, y2)
php  function setConsoleMargins( $x1, $y1, $x2, $y2)
cpp   int setConsoleMargins( int x1, int y1, int x2, int y2)
m    -(int) setConsoleMargins : (int) x1
           : (int) y1
           : (int) x2
           : (int) y2
pas   function setConsoleMargins( x1: LongInt,
                                  y1: LongInt,
                                  x2: LongInt,
                                  y2: LongInt): LongInt
vb    function setConsoleMargins( ) As Integer
cs    int setConsoleMargins( int x1, int y1, int x2, int y2)
java  int setConsoleMargins( int x1, int y1, int x2, int y2)
py    def setConsoleMargins( x1, y1, x2, y2)
cmd   YDisplay target [-layer layerId] setConsoleMargins x1 y1 x2 y2

```

Parameters :

x1 the distance from left of layer to the left margin, in pixels
y1 the distance from top of layer to the top margin, in pixels
x2 the distance from left of layer to the right margin, in pixels
y2 the distance from top of layer to the bottom margin, in pixels

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→setConsoleWordWrap()
displaylayer.setConsoleWordWrap()**YDisplayLayer**

Sets up the wrapping behaviour used by the `consoleOut` function.

```
js   function setConsoleWordWrap( wordwrap)
node.js function setConsoleWordWrap( wordwrap)
php  function setConsoleWordWrap( $wordwrap)
cpp   int setConsoleWordWrap( bool wordwrap)
m    -(int) setConsoleWordWrap : (bool) wordwrap
pas   function setConsoleWordWrap( wordwrap: boolean): LongInt
vb    function setConsoleWordWrap( ) As Integer
cs    int setConsoleWordWrap( bool wordwrap)
java  int setConsoleWordWrap( boolean wordwrap)
py    def setConsoleWordWrap( wordwrap)
cmd   YDisplay target [-layer layerId] setConsoleWordWrap wordwrap
```

Parameters :

wordwrap true to wrap only between words, false to wrap on the last column anyway.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→setLayerPosition() displaylayer.setLayerPosition()

YDisplayLayer

Sets the position of the layer relative to the display upper left corner.

```

js   function setLayerPosition( x, y, scrollTime)
nodejs function setLayerPosition( x, y, scrollTime)
php  function setLayerPosition( $x, $y, $scrollTime)
cpp   int setLayerPosition( int x, int y, int scrollTime)
m     -(int) setLayerPosition : (int) x
          : (int) y
          : (int) scrollTime
pas   function setLayerPosition( x: LongInt,
                                y: LongInt,
                                scrollTime: LongInt): LongInt
vb    function setLayerPosition( ) As Integer
cs    int setLayerPosition( int x, int y, int scrollTime)
java  int setLayerPosition( int x, int y, int scrollTime)
py    def setLayerPosition( x, y, scrollTime)
cmd   YDisplay target [-layer layerId] setLayerPosition x y scrollTime

```

When smooth scrolling is used, the display offset of the layer is automatically updated during the next milliseconds to animate the move of the layer.

Parameters :

x the distance from left of display to the upper left corner of the layer
y the distance from top of display to the upper left corner of the layer
scrollTime number of milliseconds to use for smooth scrolling, or 0 if the scrolling should be immediate.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→unhide()displaylayer.unhide()**YDisplayLayer**

Shows the layer.

```
js function unhide( )
nodejs function unhide( )
php function unhide( )
cpp int unhide( )
m -(int) unhide
pas function unhide( ): LongInt
vb function unhide( ) As Integer
cs int unhide( )
java int unhide( )
py def unhide( )
cmd YDisplay target [-layer layerId] unhide
```

Shows the layer again after a hide command.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

3.15. External power supply control interface

Yoctopuce application programming interface allows you to control the power source to use for module functions that require high current. The module can also automatically disconnect the external power when a voltage drop is observed on the external power source (external battery running out of power).

In order to use the functions described here, you should include:

| | |
|--------------------------------------|---|
| js | <script type='text/javascript' src='yocto_dualpower.js'></script> |
| node.js | var yoctolib = require('yoctolib'); |
| php | var YDualPower = yoctolib.YDualPower; |
| require_once('yocto_dualpower.php'); | |
| cpp | #include "yocto_dualpower.h" |
| m | #import "yocto_dualpower.h" |
| pas | uses yocto_dualpower; |
| vb | yocto_dualpower.vb |
| cs | yocto_dualpower.cs |
| java | import com.yoctopuce.YoctoAPI.YDualPower; |
| py | from yocto_dualpower import * |

Global functions

yFindDualPower(func)

Retrieves a dual power control for a given identifier.

yFirstDualPower()

Starts the enumeration of dual power controls currently accessible.

YDualPower methods

dualpower→describe()

Returns a short text that describes unambiguously the instance of the power control in the form TYPE (NAME)=SERIAL.FUNCTIONID.

dualpower→get_advertisedValue()

Returns the current value of the power control (no more than 6 characters).

dualpower→get_errorMessage()

Returns the error message of the latest error with the power control.

dualpower→get_errorType()

Returns the numerical error code of the latest error with the power control.

dualpower→get_extVoltage()

Returns the measured voltage on the external power source, in millivolts.

dualpower→get_friendlyName()

Returns a global identifier of the power control in the format MODULE_NAME . FUNCTION_NAME.

dualpower→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

dualpower→get_functionId()

Returns the hardware identifier of the power control, without reference to the module.

dualpower→get_hardwareId()

Returns the unique hardware identifier of the power control in the form SERIAL.FUNCTIONID.

dualpower→get_logicalName()

Returns the logical name of the power control.

dualpower→get_module()

Gets the YModule object for the device on which the function is located.

dualpower→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

dualpower→get_powerControl()

Returns the selected power source for module functions that require lots of current.

dualpower→get_powerState()

Returns the current power source for module functions that require lots of current.

dualpower→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

dualpower→isOnline()

Checks if the power control is currently reachable, without raising any error.

dualpower→isOnline_async(callback, context)

Checks if the power control is currently reachable, without raising any error (asynchronous version).

dualpower→load(msValidity)

Preloads the power control cache with a specified validity duration.

dualpower→load_async(msValidity, callback, context)

Preloads the power control cache with a specified validity duration (asynchronous version).

dualpower→nextDualPower()

Continues the enumeration of dual power controls started using yFirstDualPower().

dualpower→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

dualpower→set_logicalName(newval)

Changes the logical name of the power control.

dualpower→set_powerControl(newval)

Changes the selected power source for module functions that require lots of current.

dualpower→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

dualpower→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YDualPower.FindDualPower()**YDualPower****yFindDualPower()YDualPower.FindDualPower()**

Retrieves a dual power control for a given identifier.

| | |
|----------------------|---|
| <code>js</code> | <code>function yFindDualPower(func)</code> |
| <code>node.js</code> | <code>function FindDualPower(func)</code> |
| <code>php</code> | <code>function yFindDualPower(\$func)</code> |
| <code>cpp</code> | <code>YDualPower* yFindDualPower(const string& func)</code> |
| <code>m</code> | <code>YDualPower* yFindDualPower(NSString* func)</code> |
| <code>pas</code> | <code>function yFindDualPower(func: string): TYDualPower</code> |
| <code>vb</code> | <code>function yFindDualPower(ByVal func As String) As YDualPower</code> |
| <code>cs</code> | <code>YDualPower FindDualPower(string func)</code> |
| <code>java</code> | <code>YDualPower FindDualPower(String func)</code> |
| <code>py</code> | <code>def FindDualPower(func)</code> |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the power control is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YDualPower.isOnline()` to test if the power control is indeed online at a given time. In case of ambiguity when looking for a dual power control by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the power control

Returns :

a `YDualPower` object allowing you to drive the power control.

YDualPower.FirstDualPower()**YDualPower****yFirstDualPower() YDualPower.FirstDualPower()**

Starts the enumeration of dual power controls currently accessible.

| | |
|---------|--|
| js | function yFirstDualPower() |
| node.js | function FirstDualPower() |
| php | function yFirstDualPower() |
| cpp | YDualPower* yFirstDualPower() |
| m | YDualPower* yFirstDualPower() |
| pas | function yFirstDualPower() : TYDualPower |
| vb | function yFirstDualPower() As YDualPower |
| cs | YDualPower FirstDualPower() |
| java | YDualPower FirstDualPower() |
| py | def FirstDualPower() |

Use the method `YDualPower.nextDualPower()` to iterate on next dual power controls.

Returns :

a pointer to a `YDualPower` object, corresponding to the first dual power control currently online, or a null pointer if there are none.

dualpower→describe()dualpower.describe()**YDualPower**

Returns a short text that describes unambiguously the instance of the power control in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--|
| js | function describe () |
| nodejs | function describe () |
| php | function describe () |
| cpp | string describe () |
| m | -(NSString*) describe |
| pas | function describe (): string |
| vb | function describe () As String |
| cs | string describe () |
| java | String describe () |
| py | def describe () |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the power control (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

dualpower→get_advertisedValue()
dualpower→advertisedValue()
dualpower.get_advertisedValue()

YDualPower

Returns the current value of the power control (no more than 6 characters).

```
js function get_advertisedValue( )  
nodejs function get_advertisedValue( )  
php function get_advertisedValue( )  
cpp string get_advertisedValue( )  
m -(NSString*) advertisedValue  
pas function get_advertisedValue( ): string  
vb function get_advertisedValue( ) As String  
cs string get_advertisedValue( )  
java String get_advertisedValue( )  
py def get_advertisedValue( )  
cmd YDualPower target get_advertisedValue
```

Returns :

a string corresponding to the current value of the power control (no more than 6 characters). On failure, throws an exception or returns **Y_ADVERTISEDVALUE_INVALID**.

dualpower→getErrorMessage()
dualpower→errorMessage()
dualpower.getErrorMessage()**YDualPower**

Returns the error message of the latest error with the power control.

| | |
|---------|--|
| js | function getErrorMessage() |
| node.js | function getErrorMessage() |
| php | function getErrorMessage() |
| cpp | string getErrorMessage() |
| m | -(NSString*) errorMessage |
| pas | function getErrorMessage() : string |
| vb | function getErrorMessage() As String |
| cs | string getErrorMessage() |
| java | String getErrorMessage() |
| py | def getErrorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the power control object

dualpower→get_errorType()**YDualPower****dualpower→errorType()dualpower.get_errorType()**

Returns the numerical error code of the latest error with the power control.

| | |
|---------|--|
| js | function get_errorType() |
| node.js | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType() : YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the power control object

dualpower→get_extVoltage()**YDualPower****dualpower→extVoltage()dualpower.get_extVoltage()**

Returns the measured voltage on the external power source, in millivolts.

| | |
|--------|--|
| js | function get_extVoltage() |
| nodejs | function get_extVoltage() |
| php | function get_extVoltage() |
| cpp | int get_extVoltage() |
| m | -(int) extVoltage |
| pas | function get_extVoltage() : LongInt |
| vb | function get_extVoltage() As Integer |
| cs | int get_extVoltage() |
| java | int get_extVoltage() |
| py | def get_extVoltage() |
| cmd | YDualPower target get_extVoltage |

Returns :

an integer corresponding to the measured voltage on the external power source, in millivolts

On failure, throws an exception or returns Y_EXTVOLTAGE_INVALID.

dualpower→get_friendlyName()
dualpower→friendlyName()
dualpower.get_friendlyName()**YDualPower**

Returns a global identifier of the power control in the format MODULE_NAME.FUNCTION_NAME.

| | |
|--------|------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the power control if they are defined, otherwise the serial number of the module and the hardware identifier of the power control (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the power control using logical names (ex: MyCustomName.relay1)
On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

dualpower→get_functionDescriptor()
dualpower→functionDescriptor()
dualpower.get_functionDescriptor()

YDualPower

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

dualpower→get_functionId()**YDualPower****dualpower→functionId()dualpower.get_functionId()**

Returns the hardware identifier of the power control, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the power control (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

dualpower→get_hardwareId()**YDualPower****dualpower→hardwareId()dualpower.get_hardwareId()**

Returns the unique hardware identifier of the power control in the form SERIAL.FUNCTIONID.

| | |
|--------|---|
| js | function get_hardwareId() |
| nodejs | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the power control. (for example RELAY01-123456.relay1)

Returns :

a string that uniquely identifies the power control (ex: RELAY01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

dualpower→get_logicalName()
dualpower→logicalName()
dualpower.get_logicalName()

YDualPower

Returns the logical name of the power control.

```
js function get_logicalName( )  
nodejs function get_logicalName( )  
php function get_logicalName( )  
cpp string get_logicalName( )  
m -(NSString*) logicalName  
pas function get_logicalName( ): string  
vb function get_logicalName( ) As String  
cs string get_logicalName( )  
java String get_logicalName( )  
py def get_logicalName( )  
cmd YDualPower target get_logicalName
```

Returns :

a string corresponding to the logical name of the power control. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

dualpower→get_module()**YDualPower****dualpower→module()dualpower.get_module()**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

dualpower→get_module_async()
dualpower→module_async()**YDualPower**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

`js` `function get_module_async(callback, context)`
`node.js` `function get_module_async(callback, context)`

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

dualpower→get_powerControl()
dualpower→powerControl()
dualpower.get_powerControl()**YDualPower**

Returns the selected power source for module functions that require lots of current.

| | |
|--------|--|
| js | function get_powerControl() |
| nodejs | function get_powerControl() |
| php | function get_powerControl() |
| cpp | Y_POWERCONTROL_enum get_powerControl() |
| m | -(Y_POWERCONTROL_enum) powerControl |
| pas | function get_powerControl(): Integer |
| vb | function get_powerControl() As Integer |
| cs | int get_powerControl() |
| java | int get_powerControl() |
| py | def get_powerControl() |
| cmd | YDualPower target get_powerControl |

Returns :

a value among Y_POWERCONTROL_AUTO, Y_POWERCONTROL_FROM_USB, Y_POWERCONTROL_FROM_EXT and Y_POWERCONTROL_OFF corresponding to the selected power source for module functions that require lots of current

On failure, throws an exception or returns Y_POWERCONTROL_INVALID.

dualpower→get_powerState()
dualpower→powerState()
dualpower.get_powerState()**YDualPower**

Returns the current power source for module functions that require lots of current.

| | |
|--------|--|
| js | function get_powerState() |
| nodejs | function get_powerState() |
| php | function get_powerState() |
| cpp | Y_POWERSTATE_enum get_powerState() |
| m | -(Y_POWERSTATE_enum) powerState |
| pas | function get_powerState() : Integer |
| vb | function get_powerState() As Integer |
| cs | int get_powerState() |
| java | int get_powerState() |
| py | def get_powerState() |
| cmd | YDualPower target get_powerState |

Returns :

a value among Y_POWERSTATE_OFF, Y_POWERSTATE_FROM_USB and Y_POWERSTATE_FROM_EXT corresponding to the current power source for module functions that require lots of current

On failure, throws an exception or returns Y_POWERSTATE_INVALID.

dualpower→get(userData)**dualpower→userData()dualpower.get(userData())****YDualPower**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|--|
| js | <code>function get(userData) </code> |
| nodejs | <code>function get(userData) </code> |
| php | <code>function get(userData) </code> |
| cpp | <code>void * get(userData) </code> |
| m | <code>-(void*) userData </code> |
| pas | <code>function get(userData): Tobject </code> |
| vb | <code>function get(userData) As Object </code> |
| cs | <code>object get(userData) </code> |
| java | <code>Object get(userData) </code> |
| py | <code>def get(userData) </code> |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

dualpower→isOnline()dualpower.isOnline()**YDualPower**

Checks if the power control is currently reachable, without raising any error.

| | |
|--------|---|
| js | function isOnline () |
| nodejs | function isOnline () |
| php | function isOnline () |
| cpp | bool isOnline () |
| m | - (BOOL) isOnline |
| pas | function isOnline (): boolean |
| vb | function isOnline () As Boolean |
| cs | bool isOnline () |
| java | boolean isOnline () |
| py | def isOnline () |

If there is a cached value for the power control in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the power control.

Returns :

true if the power control can be reached, and false otherwise

dualpower→isOnline_async()**YDualPower**

Checks if the power control is currently reachable, without raising any error (asynchronous version).

```
js   function isOnline_async( callback, context )
nodejs function isOnline_async( callback, context )
```

If there is a cached value for the power control in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

dualpower→load()dualpower.load()**YDualPower**

Preloads the power control cache with a specified validity duration.

| | |
|--------|--|
| js | function load(msValidity) |
| nodejs | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | - (YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

dualpower→load_async()

YDualPower

Preloads the power control cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

dualpower→nextDualPower()
dualpower.nextDualPower()**YDualPower**

Continues the enumeration of dual power controls started using `yFirstDualPower()`.

| | |
|----------------------|--|
| <code>js</code> | <code>function nextDualPower()</code> |
| <code>node.js</code> | <code>function nextDualPower()</code> |
| <code>php</code> | <code>function nextDualPower()</code> |
| <code>cpp</code> | <code>YDualPower * nextDualPower()</code> |
| <code>m</code> | <code>-(YDualPower*) nextDualPower</code> |
| <code>pas</code> | <code>function nextDualPower(): TYDualPower</code> |
| <code>vb</code> | <code>function nextDualPower() As YDualPower</code> |
| <code>cs</code> | <code>YDualPower nextDualPower()</code> |
| <code>java</code> | <code>YDualPower nextDualPower()</code> |
| <code>py</code> | <code>def nextDualPower()</code> |

Returns :

a pointer to a `YDualPower` object, corresponding to a dual power control currently online, or a null pointer if there are no more dual power controls to enumerate.

dualpower→registerValueCallback() dualpower.registerValueCallback()

YDualPower

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback)
nodejs function registerValueCallback( callback)
php  function registerValueCallback( $callback)
cpp   int registerValueCallback( YDualPowerValueCallback callback)
m     -(int) registerValueCallback : (YDualPowerValueCallback) callback
pas   function registerValueCallback( callback: TYDualPowerValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback)
java  int registerValueCallback( UpdateCallback callback)
py    def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

dualpower→set_logicalName()
dualpower→setLogicalName()
dualpower.set_logicalName()

YDualPower

Changes the logical name of the power control.

```
js function set_logicalName( newval)
nodejs function set_logicalName( newval)
php function set_logicalName( $newval)
cpp int set_logicalName( const string& newval)
m -(int) setLogicalName : (NSString*) newval
pas function set_logicalName( newval: string): integer
vb function set_logicalName( ByVal newval As String) As Integer
cs int set_logicalName( string newval)
java int set_logicalName( String newval)
py def set_logicalName( newval)
cmd YDualPower target set_logicalName newval
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the power control.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

dualpower→set_powerControl()
dualpower→setPowerControl()
dualpower.set_powerControl()

YDualPower

Changes the selected power source for module functions that require lots of current.

| | |
|---------|---|
| js | function set_powerControl(newval) |
| node.js | function set_powerControl(newval) |
| php | function set_powerControl(\$newval) |
| cpp | int set_powerControl(Y_POWERCONTROL_enum newval) |
| m | -(int) setPowerControl : (Y_POWERCONTROL_enum) newval |
| pas | function set_powerControl(newval: Integer): integer |
| vb | function set_powerControl(ByVal newval As Integer) As Integer |
| cs | int set_powerControl(int newval) |
| java | int set_powerControl(int newval) |
| py | def set_powerControl(newval) |
| cmd | YDualPower target set_powerControl newval |

Parameters :

newval a value among `Y_POWERCONTROL_AUTO`, `Y_POWERCONTROL_FROM_USB`, `Y_POWERCONTROL_FROM_EXT` and `Y_POWERCONTROL_OFF` corresponding to the selected power source for module functions that require lots of current

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

dualpower→set(userData)**YDualPower****dualpower→setUserData()dualpower.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|--|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData) |
| cpp | void set(userData) |
| m | - (void) set(userData : (void*) data |
| pas | procedure set(userData) data: Tobject |
| vb | procedure set(userData) ByVal data As Object |
| cs | void set(userData) object data |
| java | void set(userData) Object data |
| py | def set(userData) data |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

dualpower→wait_async()

YDualPower

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context )
nodejs function wait_async( callback, context )
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.16. Files function interface

The filesystem interface makes it possible to store files on some devices, for instance to design a custom web UI (for networked devices) or to add fonts (on display devices).

In order to use the functions described here, you should include:

| | |
|--------|---|
| js | <script type='text/javascript' src='yocto_files.js'></script> |
| nodejs | var yoctolib = require('yoctolib'); |
| | var YFiles = yoctolib.YFiles; |
| php | require_once('yocto_files.php'); |
| cpp | #include "yocto_files.h" |
| m | #import "yocto_files.h" |
| pas | uses yocto_files; |
| vb | yocto_files.vb |
| cs | yocto_files.cs |
| java | import com.yoctopuce.YoctoAPI.YFiles; |
| py | from yocto_files import * |

Global functions

yFindFiles(func)

Retrieves a filesystem for a given identifier.

yFirstFiles()

Starts the enumeration of filesystems currently accessible.

YFiles methods

files→describe()

Returns a short text that describes unambiguously the instance of the filesystem in the form TYPE (NAME)=SERIAL .FUNCTIONID.

files→download(pathname)

Downloads the requested file and returns a binary buffer with its content.

files→download_async(pathname, callback, context)

Downloads the requested file and returns a binary buffer with its content.

files→format_fs()

Reinitializes the filesystem to its clean, unfragmented, empty state.

files→get_advertisedValue()

Returns the current value of the filesystem (no more than 6 characters).

files→get_errorMessage()

Returns the error message of the latest error with the filesystem.

files→get_errorType()

Returns the numerical error code of the latest error with the filesystem.

files→get_filesCount()

Returns the number of files currently loaded in the filesystem.

files→get_freeSpace()

Returns the free space for uploading new files to the filesystem, in bytes.

files→get_friendlyName()

Returns a global identifier of the filesystem in the format MODULE_NAME .FUNCTION_NAME.

files→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

files→get_functionId()

Returns the hardware identifier of the filesystem, without reference to the module.

files→get_hardwareId()

Returns the unique hardware identifier of the filesystem in the form SERIAL.FUNCTIONID.

files→get_list(pattern)

Returns a list of YFileRecord objects that describe files currently loaded in the filesystem.

files→get_logicalName()

Returns the logical name of the filesystem.

files→get_module()

Gets the YModule object for the device on which the function is located.

files→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

files→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

files→isOnline()

Checks if the filesystem is currently reachable, without raising any error.

files→isOnline_async(callback, context)

Checks if the filesystem is currently reachable, without raising any error (asynchronous version).

files→load(msValidity)

Preloads the filesystem cache with a specified validity duration.

files→load_async(msValidity, callback, context)

Preloads the filesystem cache with a specified validity duration (asynchronous version).

files→nextFiles()

Continues the enumeration of filesystems started using yFirstFiles().

files→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

files→remove(pathname)

Deletes a file, given by its full path name, from the filesystem.

files→set_logicalName(newval)

Changes the logical name of the filesystem.

files→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

files→upload(pathname, content)

Uploads a file to the filesystem, to the specified full path name.

files→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YFiles.FindFiles() yFindFiles()YFiles.FindFiles()

YFiles

Retrieves a filesystem for a given identifier.

| | |
|---------|---|
| js | function yFindFiles(func) |
| node.js | function FindFiles(func) |
| php | function yFindFiles(\$func) |
| cpp | YFiles* yFindFiles(string func) |
| m | +(YFiles*) yFindFiles : (NSString*) func |
| pas | function yFindFiles(func: string): TYFiles |
| vb | function yFindFiles(ByVal func As String) As YFiles |
| cs | YFiles FindFiles(string func) |
| java | YFiles FindFiles(String func) |
| py | def FindFiles(func) |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the filesystem is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YFiles.isOnline()` to test if the filesystem is indeed online at a given time. In case of ambiguity when looking for a filesystem by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the filesystem

Returns :

a `Yfiles` object allowing you to drive the filesystem.

YFiles.FirstFiles()

YFiles

yFirstFiles() YFiles.FirstFiles()

Starts the enumeration of filesystems currently accessible.

| | |
|---------|--|
| js | function yFirstFiles() |
| node.js | function FirstFiles() |
| php | function yFirstFiles() |
| cpp | YFiles* yFirstFiles() |
| m | YFiles* yFirstFiles() |
| pas | function yFirstFiles() : TYFiles |
| vb | function yFirstFiles() As YFiles |
| cs | YFiles FirstFiles() |
| java | YFiles FirstFiles() |
| py | def FirstFiles() |

Use the method `Yfiles.nextFiles()` to iterate on next filesystems.

Returns :

a pointer to a `Yfiles` object, corresponding to the first filesystem currently online, or a `null` pointer if there are none.

files→describe(files.describe())**YFiles**

Returns a short text that describes unambiguously the instance of the filesystem in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the filesystem (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

files→download()files.download()

YFiles

Downloads the requested file and returns a binary buffer with its content.

| | |
|---------|---|
| js | function download(pathname) |
| node.js | function download(pathname) |
| php | function download(\$pathname) |
| cpp | string download(string pathname) |
| m | -NSData* download : (NSString*) pathname |
| pas | function download(pathname: string): TByteArray |
| vb | function download() As Byte |
| py | def download(pathname) |
| cmd | YFiles target download pathname |

Parameters :

pathname path and name of the file to download

Returns :

a binary buffer with the file content

On failure, throws an exception or returns an empty content.

files→download_async()**YFiles**

Downloads the requested file and returns a binary buffer with its content.

```
js function download_async( pathname, callback, context)
nodejs function download_async( pathname, callback, context)
```

This is the asynchronous version that uses a callback to pass the result when the download is completed.

Parameters :

pathname path and name of the new file to load

callback callback function that is invoked when the download is completed. The callback function receives three arguments: - the user-specific context object - the YFiles object whose download_async was invoked - a binary buffer with the file content

context user-specific object that is passed as-is to the callback function

Returns :

nothing.

files→format_fs()files.format_fs()

YFiles

Reinitializes the filesystem to its clean, unfragmented, empty state.

| | |
|---------|---|
| js | function format_fs() |
| node.js | function format_fs() |
| php | function format_fs() |
| cpp | int format_fs() |
| m | - (int) format_fs |
| pas | function format_fs(): LongInt |
| vb | function format_fs() As Integer |
| cs | int format_fs() |
| java | int format_fs() |
| py | def format_fs() |
| cmd | YFiles target format_fs |

All files previously uploaded are permanently lost.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

files→get_advertisedValue() YFiles
files→advertisedValue()files.get_advertisedValue()

Returns the current value of the filesystem (no more than 6 characters).

```
js function get_advertisedValue( )  
node.js function get_advertisedValue( )  
php function get_advertisedValue( )  
cpp string get_advertisedValue( )  
m -(NSString*) advertisedValue  
pas function get_advertisedValue( ): string  
vb function get_advertisedValue( ) As String  
cs string get_advertisedValue( )  
java String get_advertisedValue( )  
py def get_advertisedValue( )  
cmd YFiles target get_advertisedValue
```

Returns :

a string corresponding to the current value of the filesystem (no more than 6 characters). On failure, throws an exception or returns `Y_ADVERTISEDVALUE_INVALID`.

files→get_errorMessage()
files→errorMessage()files.get_errorMessage()**YFiles**

Returns the error message of the latest error with the filesystem.

| | |
|--------|---|
| js | function get_errorMessage() |
| nodejs | function get_errorMessage() |
| php | function get_errorMessage() |
| cpp | string get_errorMessage() |
| m | -(NSString*) errorMessage |
| pas | function get_errorMessage() : string |
| vb | function get_errorMessage() As String |
| cs | string get_errorMessage() |
| java | String get_errorMessage() |
| py | def get_errorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the filesystem object

files→get_errorType()
files→errorType()files.get_errorType()**YFiles**

Returns the numerical error code of the latest error with the filesystem.

| | |
|---------|--|
| js | function get_errorType() |
| node.js | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType() : YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the filesystem object

files→get_filesCount()**YFiles****files→filesCount()files.get_filesCount()**

Returns the number of files currently loaded in the filesystem.

| | |
|--------|--|
| js | function get_filesCount() |
| nodejs | function get_filesCount() |
| php | function get_filesCount() |
| cpp | int get_filesCount() |
| m | -(int) filesCount |
| pas | function get_filesCount(): LongInt |
| vb | function get_filesCount() As Integer |
| cs | int get_filesCount() |
| java | int get_filesCount() |
| py | def get_filesCount() |
| cmd | YFiles target get_filesCount |

Returns :

an integer corresponding to the number of files currently loaded in the filesystem

On failure, throws an exception or returns **Y_FILESCOUNT_INVALID**.

files→get_freeSpace() YFiles
files→freeSpace()files.get_freeSpace()

Returns the free space for uploading new files to the filesystem, in bytes.

```
js function get_freeSpace( )
node.js function get_freeSpace( )
php function get_freeSpace( )
cpp int get_freeSpace( )
m -(int) freeSpace
pas function get_freeSpace( ): LongInt
vb function get_freeSpace( ) As Integer
cs int get_freeSpace( )
java int get_freeSpace( )
py def get_freeSpace( )
cmd YFiles target get_freeSpace
```

Returns :

an integer corresponding to the free space for uploading new files to the filesystem, in bytes

On failure, throws an exception or returns Y_FREESPACE_INVALID.

files→get_friendlyName()**YFiles****files→friendlyName()files.get_friendlyName()**

Returns a global identifier of the filesystem in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|-------------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the filesystem if they are defined, otherwise the serial number of the module and the hardware identifier of the filesystem (for exemple: MyCustomName . relay1)

Returns :

a string that uniquely identifies the filesystem using logical names (ex: MyCustomName . relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

files→get_functionDescriptor()
files→functionDescriptor()
files.get_functionDescriptor()

YFiles

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|---|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

files→get_functionId()**YFiles****files→functionId()files.get_functionId()**

Returns the hardware identifier of the filesystem, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the filesystem (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

files→get_hardwareId()
files→hardwareId(files.get_hardwareId())**YFiles**

Returns the unique hardware identifier of the filesystem in the form SERIAL.FUNCTIONID.

| | |
|---------|--------------------------------------|
| js | function get_hardwareId() |
| node.js | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the filesystem. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the filesystem (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

files→get_list()**YFiles****files→list()files.get_list()**

Returns a list of YFileRecord objects that describe files currently loaded in the filesystem.

| | |
|----------------|---|
| js | <code>function get_list(pattern)</code> |
| node.js | <code>function get_list(pattern)</code> |
| php | <code>function get_list(\$pattern)</code> |
| cpp | <code>vector<YFileRecord> get_list(string pattern)</code> |
| m | <code>-(NSMutableArray*) list : (NSString*) pattern</code> |
| pas | <code>function get_list(pattern: string): TYFileRecordArray</code> |
| vb | <code>function get_list() As List</code> |
| cs | <code>List<YFileRecord> get_list(string pattern)</code> |
| java | <code>ArrayList<YFileRecord> get_list(String pattern)</code> |
| py | <code>def get_list(pattern)</code> |
| cmd | <code>YFiles target get_list pattern</code> |

Parameters :

pattern an optional filter pattern, using star and question marks as wildcards. When an empty pattern is provided, all file records are returned.

Returns :

a list of YFileRecord objects, containing the file path and name, byte size and 32-bit CRC of the file content.

On failure, throws an exception or returns an empty list.

files→get_logicalName()
files→logicalName()files.get_logicalName()**YFiles**

Returns the logical name of the filesystem.

| | |
|---------|--|
| js | function get_logicalName() |
| node.js | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | - (NSString*) logicalName |
| pas | function get_logicalName(): string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YFiles target get_logicalName |

Returns :

a string corresponding to the logical name of the filesystem. On failure, throws an exception or returns **Y_LOGICALNAME_INVALID**.

files→get_module()**YFiles****files→module()files.get_module()**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

files→get_module_async()
files→module_async()**YFiles**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

`js` `function get_module_async(callback, context)`
`node.js` `function get_module_async(callback, context)`

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

files→get(userData)**YFiles****files→userData(files.get(userData))**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|---|
| js | <code>function get(userData) </code> |
| nodejs | <code>function get(userData) </code> |
| php | <code>function get(userData) </code> |
| cpp | <code>void * get(userData) </code> |
| m | <code>-(void*) userData</code> |
| pas | <code>function get(userData): Tobject</code> |
| vb | <code>function get(userData) As Object</code> |
| cs | <code>object get(userData) </code> |
| java | <code>Object get(userData) </code> |
| py | <code>def get(userData) </code> |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

files→isOnline(files.isOnline())**YFiles**

Checks if the filesystem is currently reachable, without raising any error.

| | |
|--------|---------------------------------------|
| js | function isOnline() |
| nodejs | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the filesystem in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the filesystem.

Returns :

true if the filesystem can be reached, and false otherwise

files→isOnline_async()**YFiles**

Checks if the filesystem is currently reachable, without raising any error (asynchronous version).

```
js   function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the filesystem in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

files→load()files.load()**YFiles**

Preloads the filesystem cache with a specified validity duration.

| | |
|--------|--|
| js | function load(msValidity) |
| nodejs | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | -(YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

files→load_async()

YFiles

Preloads the filesystem cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

files→nextFiles()files.nextFiles()**YFiles**

Continues the enumeration of filesystems started using `yFirstFiles()`.

| | |
|--------|---------------------------------------|
| js | function nextFiles() |
| nodejs | function nextFiles() |
| php | function nextFiles() |
| cpp | YFiles * nextFiles() |
| m | -(YFiles*) nextFiles |
| pas | function nextFiles() : TYFiles |
| vb | function nextFiles() As YFiles |
| cs | YFiles nextFiles() |
| java | YFiles nextFiles() |
| py | def nextFiles() |

Returns :

a pointer to a `YFiles` object, corresponding to a filesystem currently online, or a `null` pointer if there are no more filesystems to enumerate.

files→registerValueCallback() files.registerValueCallback()

YFiles

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback)
nodejs function registerValueCallback( callback)
php  function registerValueCallback( $callback)
cpp   int registerValueCallback( YFilesValueCallback callback)
m    -(int) registerValueCallback : (YFilesValueCallback) callback
pas   function registerValueCallback( callback: TYFilesValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs   int registerValueCallback( ValueCallback callback)
java  int registerValueCallback( UpdateCallback callback)
py    def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

files→remove()files.remove()**YFiles**

Deletes a file, given by its full path name, from the filesystem.

```
js function remove( pathname)
nodejs function remove( pathname)
php function remove( $pathname)
cpp int remove( string pathname)
m -(int) remove : (NSString*) pathname
pas function remove( pathname: string): LongInt
vb function remove( ) As Integer
cs int remove( string pathname)
java int remove( String pathname)
py def remove( pathname)
cmd YFiles target remove pathname
```

Because of filesystem fragmentation, deleting a file may not always free up the whole space used by the file. However, rewriting a file with the same path name will always reuse any space not freed previously. If you need to ensure that no space is taken by previously deleted files, you can use `format_fs` to fully reinitialize the filesystem.

Parameters :

pathname path and name of the file to remove.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

files→set_logicalName() files→setLogicalName()files.set_logicalName()

YFiles

Changes the logical name of the filesystem.

| | |
|--------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YFiles target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the filesystem.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

files→set(userData)**YFiles****files→setUserData(files.set(userData))**

Stores a user context provided as argument in the userData attribute of the function.

```
js   function set(userData) {  
node.js function set(userData) {  
php  function set(userData) {  
cpp   void set(userData) {  
m    -(void) setUserData : (void*) userData  
pas  procedure set(userData: Tobject);  
vb   procedure set(userData: ByVal data As Object);  
cs   void set(userData: object data);  
java void set(userData: Object data);  
py   def set(userData: data);
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

files→upload()files.upload()**YFiles**

Uploads a file to the filesystem, to the specified full path name.

| | |
|----------------|--|
| js | function upload(pathname, content) |
| node.js | function upload(pathname, content) |
| php | function upload(\$pathname, \$content) |
| cpp | int upload(string pathname, string content) |
| m | - (int) upload : (NSString*) pathname : (NSData*) content |
| pas | function upload(pathname: string, content: TByteArray): LongInt |
| vb | procedure upload() |
| cs | int upload(string pathname) |
| java | int upload(String pathname) |
| py | def upload(pathname, content) |
| cmd | YFiles target upload pathname content |

If a file already exists with the same path name, its content is overwritten.

Parameters :

pathname path and name of the new file to create
content binary buffer with the content to set

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

files→wait_async()**YFiles**

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.17. GenericSensor function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

| | |
|--------|---|
| js | <script type='text/javascript' src='yocto_geneticsensor.js'></script> |
| nodejs | var yoctolib = require('yoctolib'); |
| | var YGenericSensor = yoctolib.YGenericSensor; |
| php | require_once('yocto_geneticsensor.php'); |
| cpp | #include "yocto_geneticsensor.h" |
| m | #import "yocto_geneticsensor.h" |
| pas | uses yocto_geneticsensor; |
| vb | yocto_geneticsensor.vb |
| cs | yocto_geneticsensor.cs |
| java | import com.yoctopuce.YoctoAPI.YGenericSensor; |
| py | from yocto_geneticsensor import * |

Global functions

yFindGenericSensor(func)

Retrieves a generic sensor for a given identifier.

yFirstGenericSensor()

Starts the enumeration of generic sensors currently accessible.

YGenericSensor methods

geneticsensor→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

geneticsensor→describe()

Returns a short text that describes unambiguously the instance of the generic sensor in the form TYPE (NAME)=SERIAL . FUNCTIONID.

geneticsensor→get_advertisedValue()

Returns the current value of the generic sensor (no more than 6 characters).

geneticsensor→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor.

geneticsensor→get_currentValue()

Returns the current measured value.

geneticsensor→get_errorMessage()

Returns the error message of the latest error with the generic sensor.

geneticsensor→get_errorType()

Returns the numerical error code of the latest error with the generic sensor.

geneticsensor→get_friendlyName()

Returns a global identifier of the generic sensor in the format MODULE_NAME . FUNCTION_NAME.

geneticsensor→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

geneticsensor→get_functionId()

Returns the hardware identifier of the generic sensor, without reference to the module.

geneticsensor→get_hardwareId()

Returns the unique hardware identifier of the generic sensor in the form SERIAL . FUNCTIONID.

| | |
|--|--|
| genericsensor→get_highestValue() | Returns the maximal value observed for the measure since the device was started. |
| genericsensor→get_logFrequency() | Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory. |
| genericsensor→get_logicalName() | Returns the logical name of the generic sensor. |
| genericsensor→get_lowestValue() | Returns the minimal value observed for the measure since the device was started. |
| genericsensor→get_module() | Gets the YModule object for the device on which the function is located. |
| genericsensor→get_module_async(callback, context) | Gets the YModule object for the device on which the function is located (asynchronous version). |
| genericsensor→get_recordedData(startTime, endTime) | Retrieves a DataSet object holding historical data for this sensor, for a specified time interval. |
| genericsensor→get_reportFrequency() | Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function. |
| genericsensor→get_resolution() | Returns the resolution of the measured values. |
| genericsensor→get_signalRange() | Returns the electric signal range used by the sensor. |
| genericsensor→get_signalUnit() | Returns the measuring unit of the electrical signal used by the sensor. |
| genericsensor→get_signalValue() | Returns the measured value of the electrical signal used by the sensor. |
| genericsensor→get_unit() | Returns the measuring unit for the measure. |
| genericsensor→get(userData) | Returns the value of the userData attribute, as previously stored using method set(userData). |
| genericsensor→get_valueRange() | Returns the physical value range measured by the sensor. |
| genericsensor→isOnline() | Checks if the generic sensor is currently reachable, without raising any error. |
| genericsensor→isOnline_async(callback, context) | Checks if the generic sensor is currently reachable, without raising any error (asynchronous version). |
| genericsensor→load(msValidity) | Preloads the generic sensor cache with a specified validity duration. |
| genericsensor→loadCalibrationPoints(rawValues, refValues) | Retrieves error correction data points previously entered using the method calibrateFromPoints. |
| genericsensor→load_async(msValidity, callback, context) | Preloads the generic sensor cache with a specified validity duration (asynchronous version). |
| genericsensor→nextGenericSensor() | Continues the enumeration of generic sensors started using yFirstGenericSensor(). |
| genericsensor→registerTimedReportCallback(callback) | Registers the callback function that is invoked on every periodic timed notification. |

genericsensor→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

genericsensor→set_highestValue(newval)

Changes the recorded maximal value observed.

genericsensor→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

genericsensor→set_logicalName(newval)

Changes the logical name of the generic sensor.

genericsensor→set_lowestValue(newval)

Changes the recorded minimal value observed.

genericsensor→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

genericsensor→set_resolution(newval)

Changes the resolution of the measured physical values.

genericsensor→set_signalRange(newval)

Changes the electric signal range used by the sensor.

genericsensor→set_unit(newval)

Changes the measuring unit for the measured value.

genericsensor→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

genericsensor→set_valueRange(newval)

Changes the physical value range measured by the sensor.

genericsensor→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YGenericSensor.FindGenericSensor() yFindGenericSensor() YGenericSensor.FindGenericSensor()

YGenericSensor

Retrieves a generic sensor for a given identifier.

```
js function yFindGenericSensor( func)
nodejs function FindGenericSensor( func)
php function yFindGenericSensor( $func)
cpp YGenericSensor* yFindGenericSensor( const string& func)
m YGenericSensor* yFindGenericSensor( NSString* func)
pas function yFindGenericSensor( func: string): TYGenericSensor
vb function yFindGenericSensor( ByVal func As String) As YGenericSensor
cs YGenericSensor FindGenericSensor( string func)
java YGenericSensor FindGenericSensor( String func)
py def FindGenericSensor( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the generic sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YGenericSensor.isOnline()` to test if the generic sensor is indeed online at a given time. In case of ambiguity when looking for a generic sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the generic sensor

Returns :

a `YGenericSensor` object allowing you to drive the generic sensor.

YGenericSensor.FirstGenericSensor() yFirstGenericSensor() YGenericSensor.FirstGenericSensor()

YGenericSensor

Starts the enumeration of generic sensors currently accessible.

| | |
|---------|---|
| js | function yFirstGenericSensor() |
| node.js | function FirstGenericSensor() |
| php | function yFirstGenericSensor() |
| cpp | YGenericSensor* yFirstGenericSensor() |
| m | YGenericSensor* yFirstGenericSensor() |
| pas | function yFirstGenericSensor(): TYGenericSensor |
| vb | function yFirstGenericSensor() As YGenericSensor |
| cs | YGenericSensor FirstGenericSensor() |
| java | YGenericSensor FirstGenericSensor() |
| py | def FirstGenericSensor() |

Use the method `YGenericSensor.nextGenericSensor()` to iterate on next generic sensors.

Returns :

a pointer to a `YGenericSensor` object, corresponding to the first generic sensor currently online, or a null pointer if there are none.

genericsensor→calibrateFromPoints() genericsensor.calibrateFromPoints()

YGenericSensor

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```

js   function calibrateFromPoints( rawValues, refValues)
nodejs function calibrateFromPoints( rawValues, refValues)
php   function calibrateFromPoints( $rawValues, $refValues)
cpp   int calibrateFromPoints( vector<double> rawValues,
                           vector<double> refValues)
m    -(int) calibrateFromPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues
pas  function calibrateFromPoints( rawValues: TDoubleArray,
                           refValues: TDoubleArray): LongInt
vb   procedure calibrateFromPoints( )
cs   int calibrateFromPoints( List<double> rawValues,
                           List<double> refValues)
java int calibrateFromPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)
py   def calibrateFromPoints( rawValues, refValues)
cmd  YGenericSensor target calibrateFromPoints rawValues refValues

```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→describe()genericsensor.describe()**YGenericSensor**

Returns a short text that describes unambiguously the instance of the generic sensor in the form TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--|
| js | function describe () |
| nodejs | function describe () |
| php | function describe () |
| cpp | string describe () |
| m | -(NSString*) describe |
| pas | function describe (): string |
| vb | function describe () As String |
| cs | string describe () |
| java | String describe () |
| py | def describe () |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the generic sensor (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

genericsensor→get_advertisedValue()
genericsensor→advertisedValue()
genericsensor.get_advertisedValue()

YGenericSensor

Returns the current value of the generic sensor (no more than 6 characters).

```
js function get_advertisedValue( )  
nodejs function get_advertisedValue( )  
php function get_advertisedValue( )  
cpp string get_advertisedValue( )  
m -(NSString*) advertisedValue  
pas function get_advertisedValue( ): string  
vb function get_advertisedValue( ) As String  
cs string get_advertisedValue( )  
java String get_advertisedValue( )  
py def get_advertisedValue( )  
cmd YGenericSensor target get_advertisedValue
```

Returns :

a string corresponding to the current value of the generic sensor (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

genericsensor→get_currentRawValue()
genericsensor→currentRawValue()
genericsensor.get_currentRawValue()

YGenericSensor

Returns the uncalibrated, unrounded raw value returned by the sensor.

| | |
|---------|--|
| js | function get_currentRawValue() |
| node.js | function get_currentRawValue() |
| php | function get_currentRawValue() |
| cpp | double get_currentRawValue() |
| m | -(double) currentRawValue |
| pas | function get_currentRawValue(): double |
| vb | function get_currentRawValue() As Double |
| cs | double get_currentRawValue() |
| java | double get_currentRawValue() |
| py | def get_currentRawValue() |
| cmd | YGenericSensor target get_currentRawValue |

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

genericsensor→get_currentValue()
genericsensor→currentValue()
genericsensor.get_currentValue()

YGenericSensor

Returns the current measured value.

| | |
|--------|---|
| js | function get_currentValue() |
| nodejs | function get_currentValue() |
| php | function get_currentValue() |
| cpp | double get_currentValue() |
| m | -(double) currentValue |
| pas | function get_currentValue() : double |
| vb | function get_currentValue() As Double |
| cs | double get_currentValue() |
| java | double get_currentValue() |
| py | def get_currentValue() |
| cmd | YGenericSensor target get_currentValue |

Returns :

a floating point number corresponding to the current measured value

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

genericsensor→getErrorMessage()
genericsensor→errorMessage()
genericsensor.getErrorMessage()

YGenericSensor

Returns the error message of the latest error with the generic sensor.

| | |
|---------|---------------------------------------|
| js | function getErrorMessage() |
| node.js | function getErrorMessage() |
| php | function getErrorMessage() |
| cpp | string getErrorMessage() |
| m | -(NSString*) errorMessage |
| pas | function getErrorMessage(): string |
| vb | function getErrorMessage() As String |
| cs | string getErrorMessage() |
| java | String getErrorMessage() |
| py | def getErrorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the generic sensor object

genericsensor→get_errorType()
genericsensor→errorType()
genericsensor.get_errorType()

YGenericSensor

Returns the numerical error code of the latest error with the generic sensor.

| | |
|--------|---------------------------------------|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType(): YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the generic sensor object

genericsensor→get_friendlyName()
genericsensor→friendlyName()
genericsensor.get_friendlyName()

YGenericSensor

Returns a global identifier of the generic sensor in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|-------------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the generic sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the generic sensor (for exemple: MyCustomName . relay1)

Returns :

a string that uniquely identifies the generic sensor using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

genericsensor→get_functionDescriptor()
genericsensor→functionDescriptor()
genericsensor.get_functionDescriptor()

YGenericSensor

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|--------|---|
| js | function get_functionDescriptor() |
| nodejs | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

genericsensor→get_functionId()
genericsensor→functionId()
genericsensor.get_functionId()

YGenericSensor

Returns the hardware identifier of the generic sensor, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the generic sensor (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

genericsensor→get_hardwareId()
genericsensor→hardwareId()
genericsensor.get_hardwareId()

YGenericSensor

Returns the unique hardware identifier of the generic sensor in the form SERIAL.FUNCTIONID.

| | |
|---------|--------------------------------------|
| js | function get_hardwareId() |
| node.js | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the generic sensor. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the generic sensor (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

genericsensor→get_highestValue()
genericsensor→highestValue()
genericsensor.get_highestValue()

YGenericSensor

Returns the maximal value observed for the measure since the device was started.

| | |
|---------|---|
| js | function get_highestValue() |
| node.js | function get_highestValue() |
| php | function get_highestValue() |
| cpp | double get_highestValue() |
| m | -(double) highestValue |
| pas | function get_highestValue() : double |
| vb | function get_highestValue() As Double |
| cs | double get_highestValue() |
| java | double get_highestValue() |
| py | def get_highestValue() |
| cmd | YGenericSensor target get_highestValue |

Returns :

a floating point number corresponding to the maximal value observed for the measure since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

genericsensor→get_logFrequency()
genericsensor→logFrequency()
genericsensor.get_logFrequency()

YGenericSensor

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
js   function get_logFrequency( )  
nodejs function get_logFrequency( )  
php  function get_logFrequency( )  
cpp   string get_logFrequency( )  
m    -(NSString*) logFrequency  
pas   function get_logFrequency( ): string  
vb    function get_logFrequency( ) As String  
cs    string get_logFrequency( )  
java  String get_logFrequency( )  
py    def get_logFrequency( )  
cmd   YGenericSensor target get_logFrequency
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns `Y_LOGFREQUENCY_INVALID`.

genericsensor→get_logicalName()
genericsensor→logicalName()
genericsensor.get_logicalName()

YGenericSensor

Returns the logical name of the generic sensor.

| | |
|---------------|--|
| js | function get_logicalName() |
| nodejs | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | -(NSString*) logicalName |
| pas | function get_logicalName() : string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YGenericSensor target get_logicalName |

Returns :

a string corresponding to the logical name of the generic sensor. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

genericsensor→get_lowestValue()
genericsensor→lowestValue()
genericsensor.get_lowestValue()

YGenericSensor

Returns the minimal value observed for the measure since the device was started.

js function **get_lowestValue()**
nodejs function **get_lowestValue()**
php function **get_lowestValue()**
cpp double **get_lowestValue()**
m -(double) lowestValue
pas function **get_lowestValue()**: double
vb function **get_lowestValue()** As Double
cs double **get_lowestValue()**
java double **get_lowestValue()**
py def **get_lowestValue()**
cmd YGenericSensor **target get_lowestValue**

Returns :

a floating point number corresponding to the minimal value observed for the measure since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

genericsensor→get_module()
genericsensor→module()
genericsensor.get_module()

YGenericSensor

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as on-line.

Returns :

an instance of YModule

genericsensor→get_module_async()
genericsensor→module_async()**YGenericSensor**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

genericsensor→get_recordedData()
genericsensor→recordedData()
genericsensor.get_recordedData()

YGenericSensor

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

| | |
|----------------|--|
| js | function get_recordedData(startTime, endTime) |
| node.js | function get_recordedData(startTime, endTime) |
| php | function get_recordedData(\$startTime, \$endTime) |
| cpp | YDataSet get_recordedData(s64 startTime, s64 endTime) |
| m | - (YDataSet*) recordedData : (s64) startTime : (s64) endTime |
| pas | function get_recordedData(startTime: int64, endTime: int64): TYDataSet |
| vb | function get_recordedData() As YDataSet |
| cs | YDataSet get_recordedData(long startTime, long endTime) |
| java | YDataSet get_recordedData(long startTime, long endTime) |
| py | def get_recordedData(startTime, endTime) |
| cmd | YGenericSensor target get_recordedData startTime endTime |

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

genericsensor→get_reportFrequency()
genericsensor→reportFrequency()
genericsensor.get_reportFrequency()

YGenericSensor

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
js   function get_reportFrequency( )  
nodejs function get_reportFrequency( )  
php  function get_reportFrequency( )  
cpp   string get_reportFrequency( )  
m    -(NSString*) reportFrequency  
pas   function get_reportFrequency( ): string  
vb    function get_reportFrequency( ) As String  
cs    string get_reportFrequency( )  
java  String get_reportFrequency( )  
py    def get_reportFrequency( )  
cmd   YGenericSensor target get_reportFrequency
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

genericsensor→get_resolution()
genericsensor→resolution()
genericsensor.get_resolution()

YGenericSensor

Returns the resolution of the measured values.

| | |
|--------|---|
| js | function get_resolution() |
| nodejs | function get_resolution() |
| php | function get_resolution() |
| cpp | double get_resolution() |
| m | -(double) resolution |
| pas | function get_resolution(): double |
| vb | function get_resolution() As Double |
| cs | double get_resolution() |
| java | double get_resolution() |
| py | def get_resolution() |
| cmd | YGenericSensor target get_resolution |

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

genericsensor→get_signalRange()
genericsensor→signalRange()
genericsensor.get_signalRange()

YGenericSensor

Returns the electric signal range used by the sensor.

| | |
|--------|--|
| js | function get_signalRange() |
| nodejs | function get_signalRange() |
| php | function get_signalRange() |
| cpp | string get_signalRange() |
| m | -(NSString*) signalRange |
| pas | function get_signalRange() : string |
| vb | function get_signalRange() As String |
| cs | string get_signalRange() |
| java | String get_signalRange() |
| py | def get_signalRange() |
| cmd | YGenericSensor target get_signalRange |

Returns :

a string corresponding to the electric signal range used by the sensor

On failure, throws an exception or returns Y_SIGNALRANGE_INVALID.

genericSensor→get_signalUnit()
genericSensor→signalUnit()
genericSensor.get_signalUnit()

YGenericSensor

Returns the measuring unit of the electrical signal used by the sensor.

| | |
|---------------|---|
| js | function get_signalUnit() |
| nodejs | function get_signalUnit() |
| php | function get_signalUnit() |
| cpp | string get_signalUnit() |
| m | -(NSString*) signalUnit |
| pas | function get_signalUnit() : string |
| vb | function get_signalUnit() As String |
| cs | string get_signalUnit() |
| java | String get_signalUnit() |
| py | def get_signalUnit() |
| cmd | YGenericSensor target get_signalUnit |

Returns :

a string corresponding to the measuring unit of the electrical signal used by the sensor

On failure, throws an exception or returns **Y_SIGNALUNIT_INVALID**.

genericsensor→get_signalValue()
genericsensor→signalValue()
genericsensor.get_signalValue()

YGenericSensor

Returns the measured value of the electrical signal used by the sensor.

| | |
|--------|--|
| js | function get_signalValue() |
| nodejs | function get_signalValue() |
| php | function get_signalValue() |
| cpp | double get_signalValue() |
| m | -(double) signalValue |
| pas | function get_signalValue() : double |
| vb | function get_signalValue() As Double |
| cs | double get_signalValue() |
| java | double get_signalValue() |
| py | def get_signalValue() |
| cmd | YGenericSensor target get_signalValue |

Returns :

a floating point number corresponding to the measured value of the electrical signal used by the sensor

On failure, throws an exception or returns Y_SIGNALVALUE_INVALID.

genericsensor→get_unit()**YGenericSensor****genericsensor→unit()genericsensor.get_unit()**

Returns the measuring unit for the measure.

| | |
|--------|---------------------------------------|
| js | function get_unit() |
| nodejs | function get_unit() |
| php | function get_unit() |
| cpp | string get_unit() |
| m | -(NSString*) unit |
| pas | function get_unit() : string |
| vb | function get_unit() As String |
| cs | string get_unit() |
| java | String get_unit() |
| py | def get_unit() |
| cmd | YGenericSensor target get_unit |

Returns :

a string corresponding to the measuring unit for the measure

On failure, throws an exception or returns Y_UNIT_INVALID.

genericsensor→get(userData)
genericsensor→userData()
genericsensor.get(userData)

YGenericSensor

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|---|
| js | function get(userData) { } |
| nodejs | function get(userData) { } |
| php | function get(userData) { } |
| cpp | void * get(userData) { } |
| m | - (void*) userData |
| pas | function get(userData) : Tobject { } |
| vb | function get(userData) As Object { } |
| cs | object get(userData) { } |
| java | Object get(userData) { } |
| py | def get(userData) { } |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

genericsensor→get_valueRange()
genericsensor→valueRange()
genericsensor.get_valueRange()

YGenericSensor

Returns the physical value range measured by the sensor.

| | |
|--------|---|
| js | function get_valueRange() |
| nodejs | function get_valueRange() |
| php | function get_valueRange() |
| cpp | string get_valueRange() |
| m | -(NSString*) valueRange |
| pas | function get_valueRange() : string |
| vb | function get_valueRange() As String |
| cs | string get_valueRange() |
| java | String get_valueRange() |
| py | def get_valueRange() |
| cmd | YGenericSensor target get_valueRange |

Returns :

a string corresponding to the physical value range measured by the sensor

On failure, throws an exception or returns Y_VALUERANGE_INVALID.

genericsensor→isOnline()genericsensor.isOnline()**YGenericSensor**

Checks if the generic sensor is currently reachable, without raising any error.

| | |
|--------|--|
| js | function isOnline() |
| nodejs | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the generic sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the generic sensor.

Returns :

true if the generic sensor can be reached, and false otherwise

genericsensor→isOnline_async()**YGenericSensor**

Checks if the generic sensor is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the generic sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

genericsensor→load()genericsensor.load()**YGenericSensor**

Preloads the generic sensor cache with a specified validity duration.

| | |
|--------|--|
| js | function load(msValidity) |
| nodejs | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | - (YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

genericsensor→loadCalibrationPoints() genericsensor.loadCalibrationPoints()

YGenericSensor

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```

js   function loadCalibrationPoints( rawValues, refValues)
nodejs function loadCalibrationPoints( rawValues, refValues)
php  function loadCalibrationPoints( &$rawValues, &$refValues)
cpp   int loadCalibrationPoints( vector<double>& rawValues,
                                vector<double>& refValues)

m    -(int) loadCalibrationPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues

pas  function loadCalibrationPoints( var rawValues: TDoubleArray,
                           var refValues: TDoubleArray): LongInt

vb   procedure loadCalibrationPoints( )
cs   int loadCalibrationPoints( List<double> rawValues,
                           List<double> refValues)

java int loadCalibrationPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def loadCalibrationPoints( rawValues, refValues)
cmd  YGenericSensor target loadCalibrationPoints rawValues refValues

```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→load_async()**YGenericSensor**

Preloads the generic sensor cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

genericsensor→nextGenericSensor()
genericsensor.nextGenericSensor()**YGenericSensor**

Continues the enumeration of generic sensors started using `yFirstGenericSensor()`.

| | |
|---------------------|--|
| <code>js</code> | <code>function nextGenericSensor()</code> |
| <code>nodejs</code> | <code>function nextGenericSensor()</code> |
| <code>php</code> | <code>function nextGenericSensor()</code> |
| <code>cpp</code> | <code>YGenericSensor * nextGenericSensor()</code> |
| <code>m</code> | <code>-(YGenericSensor*) nextGenericSensor</code> |
| <code>pas</code> | <code>function nextGenericSensor(): TYGenericSensor</code> |
| <code>vb</code> | <code>function nextGenericSensor() As YGenericSensor</code> |
| <code>cs</code> | <code>YGenericSensor nextGenericSensor()</code> |
| <code>java</code> | <code>YGenericSensor nextGenericSensor()</code> |
| <code>py</code> | <code>def nextGenericSensor()</code> |

Returns :

a pointer to a `YGenericSensor` object, corresponding to a generic sensor currently online, or a null pointer if there are no more generic sensors to enumerate.

genericsensor→registerTimedReportCallback()
genericsensor.registerTimedReportCallback()**YGenericSensor**

Registers the callback function that is invoked on every periodic timed notification.

```
js   function registerTimedReportCallback( callback)
node.js function registerTimedReportCallback( callback)
php  function registerTimedReportCallback( $callback)
cpp   int registerTimedReportCallback( YGenericSensorTimedReportCallback callback)
m     -(int) registerTimedReportCallback : (YGenericSensorTimedReportCallback) callback
pas   function registerTimedReportCallback( callback: TYGenericSensorTimedReportCallback): LongInt
vb    function registerTimedReportCallback( ) As Integer
cs    int registerTimedReportCallback( TimedReportCallback callback)
java  int registerTimedReportCallback( TimedReportCallback callback)
py    def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

genericsensor→registerValueCallback() genericsensor.registerValueCallback()

YGenericSensor

Registers the callback function that is invoked on every change of advertised value.

| | |
|---------|---|
| js | <code>function registerValueCallback(callback)</code> |
| node.js | <code>function registerValueCallback(callback)</code> |
| php | <code>function registerValueCallback(\$callback)</code> |
| cpp | <code>int registerValueCallback(YGenericSensorValueCallback callback)</code> |
| m | <code>-(int) registerValueCallback : (YGenericSensorValueCallback) callback</code> |
| pas | <code>function registerValueCallback(callback: TYGenericSensorValueCallback): LongInt</code> |
| vb | <code>function registerValueCallback() As Integer</code> |
| cs | <code>int registerValueCallback(ValueCallback callback)</code> |
| java | <code>int registerValueCallback(UpdateCallback callback)</code> |
| py | <code>def registerValueCallback(callback)</code> |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

genericsensor→set_highestValue()
genericsensor→setHighestValue()
genericsensor.set_highestValue()

YGenericSensor

Changes the recorded maximal value observed.

```
js function set_highestValue( newval)
nodejs function set_highestValue( newval)
php function set_highestValue( $newval)
cpp int set_highestValue( double newval)
m -(int) setHighestValue : (double) newval
pas function set_highestValue( newval: double): integer
vb function set_highestValue( ByVal newval As Double) As Integer
cs int set_highestValue( double newval)
java int set_highestValue( double newval)
py def set_highestValue( newval)
cmd YGenericSensor target set_highestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→set_logFrequency()
genericsensor→setLogFrequency()
genericsensor.set_logFrequency()

YGenericSensor

Changes the datalogger recording frequency for this function.

| | |
|--------|--|
| js | function set_logFrequency(newval) |
| nodejs | function set_logFrequency(newval) |
| php | function set_logFrequency(\$newval) |
| cpp | int set_logFrequency(const string& newval) |
| m | -(int) setLogFrequency : (NSString*) newval |
| pas | function set_logFrequency(newval: string): integer |
| vb | function set_logFrequency(ByVal newval As String) As Integer |
| cs | int set_logFrequency(string newval) |
| java | int set_logFrequency(String newval) |
| py | def set_logFrequency(newval) |
| cmd | YGenericSensor target set_logFrequency newval |

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→set_logicalName()
genericsensor→setLogicalName()
genericsensor.set_logicalName()

YGenericSensor

Changes the logical name of the generic sensor.

| | |
|--------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YGenericSensor target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the generic sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

genericsensor→set_lowestValue()
genericsensor→setLowestValue()
genericsensor.set_lowestValue()

YGenericSensor

Changes the recorded minimal value observed.

```
js function set_lowestValue( newval)
nodejs function set_lowestValue( newval)
php function set_lowestValue( $newval)
cpp int set_lowestValue( double newval)
m -(int) setLowestValue : (double) newval
pas function set_lowestValue( newval: double): integer
vb function set_lowestValue( ByVal newval As Double) As Integer
cs int set_lowestValue( double newval)
java int set_lowestValue( double newval)
py def set_lowestValue( newval)
cmd YGenericSensor target set_lowestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→set_reportFrequency()
genericsensor→setReportFrequency()
genericsensor.set_reportFrequency()

YGenericSensor

Changes the timed value notification frequency for this function.

| | |
|--------|---|
| js | function set_reportFrequency(newval) |
| nodejs | function set_reportFrequency(newval) |
| php | function set_reportFrequency(\$newval) |
| cpp | int set_reportFrequency(const string& newval) |
| m | -(int) setReportFrequency : (NSString*) newval |
| pas | function set_reportFrequency(newval: string): integer |
| vb | function set_reportFrequency(ByVal newval As String) As Integer |
| cs | int set_reportFrequency(string newval) |
| java | int set_reportFrequency(String newval) |
| py | def set_reportFrequency(newval) |
| cmd | YGenericSensor target set_reportFrequency newval |

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→set_resolution()
genericsensor→setResolution()
genericsensor.set_resolution()

YGenericSensor

Changes the resolution of the measured physical values.

| | |
|---------------|--|
| js | function set_resolution(newval) |
| nodejs | function set_resolution(newval) |
| php | function set_resolution(\$newval) |
| cpp | int set_resolution(double newval) |
| m | -(int) setResolution : (double) newval |
| pas | function set_resolution(newval: double): integer |
| vb | function set_resolution(ByVal newval As Double) As Integer |
| cs | int set_resolution(double newval) |
| java | int set_resolution(double newval) |
| py | def set_resolution(newval) |
| cmd | YGenericSensor target set_resolution newval |

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→set_signalRange()
genericsensor→setSignalRange()
genericsensor.set_signalRange()

YGenericSensor

Changes the electric signal range used by the sensor.

```
js function set_signalRange( newval)
nodejs function set_signalRange( newval)
php function set_signalRange( $newval)
cpp int set_signalRange( const string& newval)
m -(int) setSignalRange : (NSString*) newval
pas function set_signalRange( newval: string): integer
vb function set_signalRange( ByVal newval As String) As Integer
cs int set_signalRange( string newval)
java int set_signalRange( String newval)
py def set_signalRange( newval)
cmd YGenericSensor target set_signalRange newval
```

Parameters :

newval a string corresponding to the electric signal range used by the sensor

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→set_unit() genericsensor→setUnit()genericsensor.set_unit()

YGenericSensor

Changes the measuring unit for the measured value.

| | |
|--------|--|
| js | function set_unit(newval) |
| nodejs | function set_unit(newval) |
| php | function set_unit(\$newval) |
| cpp | int set_unit(const string& newval) |
| m | -(int) setUnit : (NSString*) newval |
| pas | function set_unit(newval: string): integer |
| vb | function set_unit(ByVal newval As String) As Integer |
| cs | int set_unit(string newval) |
| java | int set_unit(String newval) |
| py | def set_unit(newval) |
| cmd | YGenericSensor target set_unit newval |

Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the measuring unit for the measured value

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→set(userData)
genericsensor→setUserData()
genericsensor.set(userData)

YGenericSensor

Stores a user context provided as argument in the userData attribute of the function.

| | |
|--------|--|
| js | function set(userData) |
| nodejs | function set(userData) |
| php | function set(userData) |
| cpp | void set(userData) void* data |
| m | -(void) set(userData : (void*) data |
| pas | procedure set(userData) data : Tobject |
| vb | procedure set(userData) ByVal data As Object |
| cs | void set(userData) object data |
| java | void set(userData) Object data |
| py | def set(userData) data |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

genericsensor→set_valueRange()
genericsensor→setValueRange()
genericsensor.set_valueRange()

YGenericSensor

Changes the physical value range measured by the sensor.

| | |
|---------------|--|
| js | function set_valueRange(newval) |
| nodejs | function set_valueRange(newval) |
| php | function set_valueRange(\$newval) |
| cpp | int set_valueRange(const string& newval) |
| m | -(int) setValueRange : (NSString*) newval |
| pas | function set_valueRange(newval: string): integer |
| vb | function set_valueRange(ByVal newval As String) As Integer |
| cs | int set_valueRange(string newval) |
| java | int set_valueRange(String newval) |
| py | def set_valueRange(newval) |
| cmd | YGenericSensor target set_valueRange newval |

The range change may have a side effect on the display resolution, as it may be adapted automatically.

Parameters :

newval a string corresponding to the physical value range measured by the sensor

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→wait_async()

YGenericSensor

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.18. Gyroscope function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

| | |
|--------|--|
| js | <script type='text/javascript' src='yocto_gyro.js'></script> |
| nodejs | var yoctolib = require('yoctolib'); |
| | var YGyro = yoctolib.YGyro; |
| php | require_once('yocto_gyro.php'); |
| cpp | #include "yocto_gyro.h" |
| m | #import "yocto_gyro.h" |
| pas | uses yocto_gyro; |
| vb | yocto_gyro.vb |
| cs | yocto_gyro.cs |
| java | import com.yoctopuce.YoctoAPI.YGyro; |
| py | from yocto_gyro import * |

Global functions

yocto_gyro(func)

Retrieves a gyroscope for a given identifier.

yFirstGyro()

Starts the enumeration of gyroscopes currently accessible.

YGyro methods

gyro->calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

gyro->describe()

Returns a short text that describes unambiguously the instance of the gyroscope in the form TYPE (NAME)=SERIAL . FUNCTIONID.

gyro->get_advertisedValue()

Returns the current value of the gyroscope (no more than 6 characters).

gyro->get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor.

gyro->get_currentValue()

Returns the current value of the angular velocity.

gyro->get_errorMessage()

Returns the error message of the latest error with the gyroscope.

gyro->get_errorType()

Returns the numerical error code of the latest error with the gyroscope.

gyro->get_friendlyName()

Returns a global identifier of the gyroscope in the format MODULE_NAME . FUNCTION_NAME.

gyro->get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

gyro->get_functionId()

Returns the hardware identifier of the gyroscope, without reference to the module.

gyro->get_hardwareId()

Returns the unique hardware identifier of the gyroscope in the form SERIAL . FUNCTIONID.

| | |
|--|--|
| gyro→get_heading() | Returns the estimated heading angle, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements. |
| gyro→get_highestValue() | Returns the maximal value observed for the angular velocity since the device was started. |
| gyro→get_logFrequency() | Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory. |
| gyro→get_logicalName() | Returns the logical name of the gyroscope. |
| gyro→get_lowestValue() | Returns the minimal value observed for the angular velocity since the device was started. |
| gyro→get_module() | Gets the YModule object for the device on which the function is located. |
| gyro→get_module_async(callback, context) | Gets the YModule object for the device on which the function is located (asynchronous version). |
| gyro→get_pitch() | Returns the estimated pitch angle, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements. |
| gyro→get_quaternionW() | Returns the w component (real part) of the quaternion describing the device estimated orientation, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements. |
| gyro→get_quaternionX() | Returns the x component of the quaternion describing the device estimated orientation, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements. |
| gyro→get_quaternionY() | Returns the y component of the quaternion describing the device estimated orientation, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements. |
| gyro→get_quaternionZ() | Returns the z component of the quaternion describing the device estimated orientation, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements. |
| gyro→get_recordedData(startTime, endTime) | Retrieves a DataSet object holding historical data for this sensor, for a specified time interval. |
| gyro→get_reportFrequency() | Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function. |
| gyro→get_resolution() | Returns the resolution of the measured values. |
| gyro→get_roll() | Returns the estimated roll angle, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements. |
| gyro→get_unit() | Returns the measuring unit for the angular velocity. |
| gyro→get_userData() | Returns the value of the userData attribute, as previously stored using method set(userData). |
| gyro→get_xValue() | Returns the angular velocity around the X axis of the device, as a floating point number. |
| gyro→get_yValue() | |

Returns the angular velocity around the Y axis of the device, as a floating point number.

gyro→get_zValue()

Returns the angular velocity around the Z axis of the device, as a floating point number.

gyro→isOnline()

Checks if the gyroscope is currently reachable, without raising any error.

gyro→isOnline_async(callback, context)

Checks if the gyroscope is currently reachable, without raising any error (asynchronous version).

gyro→load(msValidity)

Preloads the gyroscope cache with a specified validity duration.

gyro→loadCalibrationPoints(rawValues, refValues)

Retrieves error correction data points previously entered using the method calibrateFromPoints.

gyro→load_async(msValidity, callback, context)

Preloads the gyroscope cache with a specified validity duration (asynchronous version).

gyro→nextGyro()

Continues the enumeration of gyroscopes started using yFirstGyro().

gyro→registerAnglesCallback(callback)

Registers a callback function that will be invoked each time that the estimated device orientation has changed.

gyro→registerQuaternionCallback(callback)

Registers a callback function that will be invoked each time that the estimated device orientation has changed.

gyro→registerTimedReportCallback(callback)

Registers the callback function that is invoked on every periodic timed notification.

gyro→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

gyro→set_highestValue(newval)

Changes the recorded maximal value observed.

gyro→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

gyro→set_logicalName(newval)

Changes the logical name of the gyroscope.

gyro→set_lowestValue(newval)

Changes the recorded minimal value observed.

gyro→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

gyro→set_resolution(newval)

Changes the resolution of the measured physical values.

gyro→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

gyro→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YGyro.FindGyro() yFindGyro()YGyro.FindGyro()

YGyro

Retrieves a gyroscope for a given identifier.

```
js function yFindGyro( func)
node.js function FindGyro( func)
php function yFindGyro( $func)
cpp YGyro* yFindGyro( string func)
m +(YGyro*) yFindGyro : (NSString*) func
pas function yFindGyro( func: string): TYGyro
vb function yFindGyro( ByVal func As String) As YGyro
cs YGyro FindGyro( string func)
java YGyro FindGyro( String func)
def FindGyro( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the gyroscope is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YGyro.isOnline()` to test if the gyroscope is indeed online at a given time. In case of ambiguity when looking for a gyroscope by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the gyroscope

Returns :

a `YGyro` object allowing you to drive the gyroscope.

YGyro.FirstGyro()

YGyro

yFirstGyro()YGyro.FirstGyro()

Starts the enumeration of gyroscopes currently accessible.

```
js function yFirstGyro( )  
nodejs function FirstGyro( )  
php function yFirstGyro( )  
cpp YGyro* yFirstGyro( )  
m YGyro* yFirstGyro( )  
pas function yFirstGyro( ): TYGyro  
vb function yFirstGyro( ) As YGyro  
cs YGyro FirstGyro( )  
java YGyro FirstGyro( )  
py def FirstGyro( )
```

Use the method `YGyro.nextGyro()` to iterate on next gyroscopes.

Returns :

a pointer to a `YGyro` object, corresponding to the first gyro currently online, or a `null` pointer if there are none.

gyro→calibrateFromPoints() gyro.calibrateFromPoints()

YGyro

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```

js   function calibrateFromPoints( rawValues, refValues)
nodejs function calibrateFromPoints( rawValues, refValues)
php   function calibrateFromPoints( $rawValues, $refValues)
cpp    int calibrateFromPoints( vector<double> rawValues,
                               vector<double> refValues)

m    -(int) calibrateFromPoints : (NSMutableArray*) rawValues
                : (NSMutableArray*) refValues

pas   function calibrateFromPoints( rawValues: TDoubleArray,
                                   refValues: TDoubleArray): LongInt

vb    procedure calibrateFromPoints( )

cs    int calibrateFromPoints( List<double> rawValues,
                           List<double> refValues)

java   int calibrateFromPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py    def calibrateFromPoints( rawValues, refValues)
cmd   YGyro target calibrateFromPoints rawValues refValues

```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

gyro→describe()gyro.describe()**YGyro**

Returns a short text that describes unambiguously the instance of the gyroscope in the form TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--|
| js | function describe () |
| nodejs | function describe () |
| php | function describe () |
| cpp | string describe () |
| m | -(NSString*) describe |
| pas | function describe (): string |
| vb | function describe () As String |
| cs | string describe () |
| java | String describe () |
| py | def describe () |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the gyroscope (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

gyro→get_advertisedValue() YGyro
gyro→advertisedValue()gyro.get_advertisedValue()

Returns the current value of the gyroscope (no more than 6 characters).

```
js function get_advertisedValue( )  
node.js function get_advertisedValue( )  
php function get_advertisedValue( )  
cpp string get_advertisedValue( )  
m -(NSString*) advertisedValue  
pas function get_advertisedValue( ): string  
vb function get_advertisedValue( ) As String  
cs string get_advertisedValue( )  
java String get_advertisedValue( )  
py def get_advertisedValue( )  
cmd YGyro target get_advertisedValue
```

Returns :

a string corresponding to the current value of the gyroscope (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

gyro→get_currentRawValue()**YGyro****gyro→currentRawValue()gyro.get_currentRawValue()**

Returns the uncalibrated, unrounded raw value returned by the sensor.

```
js function get_currentRawValue( )
nodejs function get_currentRawValue( )
php function get_currentRawValue( )
cpp double get_currentRawValue( )
m -(double) currentRawValue
pas function get_currentRawValue( ): double
vb function get_currentRawValue( ) As Double
cs double get_currentRawValue( )
java double get_currentRawValue( )
py def get_currentRawValue( )
cmd YGyro target get_currentRawValue
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

gyro→get_currentValue()
gyro→currentValue()gyro.get_currentValue()**YGyro**

Returns the current value of the angular velocity.

```
js function get_currentValue( )
node.js function get_currentValue( )
php function get_currentValue( )
cpp double get_currentValue( )
m -(double) currentValue
pas function get_currentValue( ): double
vb function get_currentValue( ) As Double
cs double get_currentValue( )
java double get_currentValue( )
py def get_currentValue( )
cmd YGyro target get_currentValue
```

Returns :

a floating point number corresponding to the current value of the angular velocity

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

gyro→get_errorMessage() gyro→errorMessage()gyro.get_errorMessage()

YGyro

Returns the error message of the latest error with the gyroscope.

```
js   function get_errorMessage( )  
nodejs function get_errorMessage( )  
php  function get_errorMessage( )  
cpp   string get_errorMessage( )  
m    -(NSString*) errorMessage  
pas   function get_errorMessage( ): string  
vb    function get_errorMessage( ) As String  
cs    string get_errorMessage( )  
java  String get_errorMessage( )  
py    def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the gyroscope object

gyro→get_errorType()
gyro→errorType()gyro.get_errorType()**YGyro**

Returns the numerical error code of the latest error with the gyroscope.

| | |
|---------|--|
| js | function get_errorType() |
| node.js | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType() : YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the gyroscope object

gyro→get_friendlyName()**YGyro****gyro→friendlyName()gyro.get_friendlyName()**

Returns a global identifier of the gyroscope in the format MODULE_NAME . FUNCTION_NAME.

```
js function get_friendlyName( )  
nodejs function get_friendlyName( )  
php function get_friendlyName( )  
cpp string get_friendlyName( )  
m -(NSString*) friendlyName  
cs string get_friendlyName( )  
java String get_friendlyName( )  
py def get_friendlyName( )
```

The returned string uses the logical names of the module and of the gyroscope if they are defined, otherwise the serial number of the module and the hardware identifier of the gyroscope (for exemple: MyCustomName . relay1)

Returns :

a string that uniquely identifies the gyroscope using logical names (ex: MyCustomName . relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

gyro→get_functionDescriptor()
gyro→functionDescriptor()
gyro.get_functionDescriptor()

YGyro

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|---|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

gyro→get_functionId() gyro→functionId()gyro.get_functionId()

YGyro

Returns the hardware identifier of the gyroscope, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the gyroscope (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

gyro→get_hardwareId()
gyro→hardwareId()gyro.get_hardwareId()**YGyro**

Returns the unique hardware identifier of the gyroscope in the form SERIAL.FUNCTIONID.

| | |
|---------|--------------------------------------|
| js | function get_hardwareId() |
| node.js | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the gyroscope. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the gyroscope (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

gyro→get_heading()**YGyro****gyro→heading()gyro.get_heading()**

Returns the estimated heading angle, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.

```
js function get_heading( )
nodejs function get_heading( )
php function get_heading( )
cpp double get_heading( )
m -(double) heading
pas function get_heading( ): double
vb function get_heading( ) As Double
cs double get_heading( )
java double get_heading( )
py def get_heading( )
```

The axis corresponding to the heading can be mapped to any of the device X, Y or Z physical directions using methods of the class `YRefFrame`.

Returns :

a floating-point number corresponding to heading in degrees, between 0 and 360.

gyro→get_highestValue() YGyro
gyro→highestValue()gyro.get_highestValue()

Returns the maximal value observed for the angular velocity since the device was started.

```
js function get_highestValue( )
node.js function get_highestValue( )
php function get_highestValue( )
cpp double get_highestValue( )
m -(double) highestValue
pas function get_highestValue( ): double
vb function get_highestValue( ) As Double
cs double get_highestValue( )
java double get_highestValue( )
py def get_highestValue( )
cmd YGyro target get_highestValue
```

Returns :

a floating point number corresponding to the maximal value observed for the angular velocity since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

gyro→get_logFrequency()**YGyro****gyro→logFrequency()gyro.get_logFrequency()**

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

| | |
|--------|--|
| js | function get_logFrequency() |
| nodejs | function get_logFrequency() |
| php | function get_logFrequency() |
| cpp | string get_logFrequency() |
| m | -(NSString*) logFrequency |
| pas | function get_logFrequency() : string |
| vb | function get_logFrequency() As String |
| cs | string get_logFrequency() |
| java | String get_logFrequency() |
| py | def get_logFrequency() |
| cmd | YGyro target get_logFrequency |

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

gyro→get_logicalName()
gyro→logicalName()gyro.get_logicalName()**YGyro**

Returns the logical name of the gyroscope.

| | |
|---------|--|
| js | function get_logicalName() |
| node.js | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | -(NSString*) logicalName |
| pas | function get_logicalName(): string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YGyro target get_logicalName |

Returns :

a string corresponding to the logical name of the gyroscope. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

gyro→get_lowestValue()**YGyro****gyro→lowestValue()gyro.get_lowestValue()**

Returns the minimal value observed for the angular velocity since the device was started.

```
js   function get_lowestValue( )  
nodejs function get_lowestValue( )  
php  function get_lowestValue( )  
cpp   double get_lowestValue( )  
m    -(double) lowestValue  
pas   function get_lowestValue( ): double  
vb    function get_lowestValue( ) As Double  
cs    double get_lowestValue( )  
java  double get_lowestValue( )  
py    def get_lowestValue( )  
cmd   YGyro target get_lowestValue
```

Returns :

a floating point number corresponding to the minimal value observed for the angular velocity since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

gyro→get_module()
gyro→module()gyro.get_module()**YGyro**

Gets the `YModule` object for the device on which the function is located.

| | |
|---------|---|
| js | function get_module() |
| node.js | function get_module() |
| php | function get_module() |
| cpp | <code>YModule * get_module()</code> |
| m | <code>-(YModule*) module</code> |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | <code>YModule get_module()</code> |
| java | <code>YModule get_module()</code> |
| py | <code>def get_module()</code> |

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

gyro→get_module_async() gyro→module_async()

YGyro

Gets the YModule object for the device on which the function is located (asynchronous version).

```
js   function get_module_async( callback, context )
nodejs function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned YModule object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested YModule object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

gyro→get_pitch()
gyro→pitch()gyro.get_pitch()**YGyro**

Returns the estimated pitch angle, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.

| | |
|--------|---------------------------------------|
| js | function get_pitch() |
| nodejs | function get_pitch() |
| php | function get_pitch() |
| cpp | double get_pitch() |
| m | -(double) pitch |
| pas | function get_pitch() : double |
| vb | function get_pitch() As Double |
| cs | double get_pitch() |
| java | double get_pitch() |
| py | def get_pitch() |

The axis corresponding to the pitch angle can be mapped to any of the device X, Y or Z physical directions using methods of the class **YRefFrame**.

Returns :

a floating-point number corresponding to pitch angle in degrees, between -90 and +90.

gyro→get_quaternionW()**YGyro****gyro→quaternionW()gyro.get_quaternionW()**

Returns the w component (real part) of the quaternion describing the device estimated orientation, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.

| | |
|--------|--|
| js | function get_quaternionW() |
| nodejs | function get_quaternionW() |
| php | function get_quaternionW() |
| cpp | double get_quaternionW() |
| m | -(double) quaternionW |
| pas | function get_quaternionW(): double |
| vb | function get_quaternionW() As Double |
| cs | double get_quaternionW() |
| java | double get_quaternionW() |
| py | def get_quaternionW() |

Returns :

a floating-point number corresponding to the w component of the quaternion.

gyro→get_quaternionX()
gyro→quaternionX()gyro.get_quaternionX()**YGyro**

Returns the x component of the quaternion describing the device estimated orientation, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.

| | |
|--------|--|
| js | function get_quaternionX() |
| nodejs | function get_quaternionX() |
| php | function get_quaternionX() |
| cpp | double get_quaternionX() |
| m | -(double) quaternionX |
| pas | function get_quaternionX(): double |
| vb | function get_quaternionX() As Double |
| cs | double get_quaternionX() |
| java | double get_quaternionX() |
| py | def get_quaternionX() |

The x component is mostly correlated with rotations on the roll axis.

Returns :

a floating-point number corresponding to the x component of the quaternion.

gyro→get_quaternionY()**YGyro****gyro→quaternionY()gyro.get_quaternionY()**

Returns the `y` component of the quaternion describing the device estimated orientation, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.

```
js function get_quaternionY( )
nodejs function get_quaternionY( )
php function get_quaternionY( )
cpp double get_quaternionY( )
m -(double) quaternionY
pas function get_quaternionY( ): double
vb function get_quaternionY( ) As Double
cs double get_quaternionY( )
java double get_quaternionY( )
py def get_quaternionY( )
```

The `y` component is mostly correlated with rotations on the pitch axis.

Returns :

a floating-point number corresponding to the `y` component of the quaternion.

gyro→get_quaternionZ()
gyro→quaternionZ()gyro.get_quaternionZ()**YGyro**

Returns the x component of the quaternion describing the device estimated orientation, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.

```
js function get_quaternionZ( )
nodejs function get_quaternionZ( )
php function get_quaternionZ( )
cpp double get_quaternionZ( )
m -(double) quaternionZ
pas function get_quaternionZ( ): double
vb function get_quaternionZ( ) As Double
cs double get_quaternionZ( )
java double get_quaternionZ( )
py def get_quaternionZ( )
```

The x component is mostly correlated with changes of heading.

Returns :

a floating-point number corresponding to the z component of the quaternion.

gyro→get_recordedData() gyro→recordedData()gyro.get_recordedData()

YGyro

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```

js   function get_recordedData( startTime, endTime)
nodejs function get_recordedData( startTime, endTime)
php  function get_recordedData( $startTime, $endTime)
cpp   YDataSet get_recordedData( s64 startTime, s64 endTime)
m     -(YDataSet*) recordedData : (s64) startTime
          : (s64) endTime

pas   function get_recordedData( startTime: int64, endTime: int64): TYDataSet
vb    function get_recordedData( ) As YDataSet
cs    YDataSet get_recordedData( long startTime, long endTime)
java   YDataSet get_recordedData( long startTime, long endTime)
py    def get_recordedData( startTime, endTime)
cmd   YGyro target get_recordedData startTime endTime

```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

gyro→get_reportFrequency() gyro→reportFrequency()gyro.get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
js  function get_reportFrequency( )  
nodejs function get_reportFrequency( )  
php  function get_reportFrequency( )  
cpp   string get_reportFrequency( )  
m    -(NSString*) reportFrequency  
pas   function get_reportFrequency( ): string  
vb    function get_reportFrequency( ) As String  
cs    string get_reportFrequency( )  
java   String get_reportFrequency( )  
py    def get_reportFrequency( )  
cmd  YGyro target get_reportFrequency
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

gyro→get_resolution() gyro→resolution()gyro.get_resolution()

YGYro

Returns the resolution of the measured values.

```
js function get_resolution( )
nodejs function get_resolution( )
php function get_resolution( )
cpp double get_resolution( )
m -(double) resolution
pas function get_resolution( ): double
vb function get_resolution( ) As Double
cs double get_resolution( )
java double get_resolution( )
py def get_resolution( )
cmd YGYro target get_resolution
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

gyro→get_roll()**YGyro****gyro→roll()gyro.get_roll()**

Returns the estimated roll angle, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.

```
js function get_roll( )
nodejs function get_roll( )
php function get_roll( )
cpp double get_roll( )
m -(double) roll
pas function get_roll( ): double
vb function get_roll( ) As Double
cs double get_roll( )
java double get_roll( )
py def get_roll( )
```

The axis corresponding to the roll angle can be mapped to any of the device X, Y or Z physical directions using methods of the class `YRefFrame`.

Returns :

a floating-point number corresponding to roll angle in degrees, between -180 and +180.

gyro→get_unit()**YGyro****gyro→unit()gyro.get_unit()**

Returns the measuring unit for the angular velocity.

| | |
|---------|---------------------------------------|
| js | function get_unit() |
| node.js | function get_unit() |
| php | function get_unit() |
| cpp | string get_unit() |
| m | -(NSString*) unit |
| pas | function get_unit() : string |
| vb | function get_unit() As String |
| cs | string get_unit() |
| java | String get_unit() |
| py | def get_unit() |
| cmd | YGyro target get_unit |

Returns :

a string corresponding to the measuring unit for the angular velocity

On failure, throws an exception or returns Y_UNIT_INVALID.

gyro→get(userData)
gyro→userData()gyro.get(userData)**YGyro**

Returns the value of the userData attribute, as previously stored using method set(userData).

```
js function get(userData) 
node.js function get(userData) 
php function get(userData) 
cpp void * get(userData) 
m -(void*) userData 
pas function get(userData): Tobject 
vb function get(userData) As Object 
cs object get(userData) 
java Object get(userData) 
py def get(userData)
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

gyro→get_xValue() gyro→xValue()gyro.get_xValue()

YGyro

Returns the angular velocity around the X axis of the device, as a floating point number.

| | |
|---------|---|
| js | function get_xValue() |
| node.js | function get_xValue() |
| php | function get_xValue() |
| cpp | double get_xValue() |
| m | -(double) xValue |
| pas | function get_xValue() : double |
| vb | function get_xValue() As Double |
| cs | double get_xValue() |
| java | double get_xValue() |
| py | def get_xValue() |

Returns :

a floating point number corresponding to the angular velocity around the X axis of the device, as a floating point number

On failure, throws an exception or returns Y_XVALUE_INVALID.

gyro→get_yValue()**YGyro****gyro→yValue()gyro.get_yValue()**

Returns the angular velocity around the Y axis of the device, as a floating point number.

| | |
|---------|---|
| js | function get_yValue() |
| node.js | function get_yValue() |
| php | function get_yValue() |
| cpp | double get_yValue() |
| m | -{double} yValue |
| pas | function get_yValue() : double |
| vb | function get_yValue() As Double |
| cs | double get_yValue() |
| java | double get_yValue() |
| py | def get_yValue() |

Returns :

a floating point number corresponding to the angular velocity around the Y axis of the device, as a floating point number

On failure, throws an exception or returns Y_YVALUE_INVALID.

gyro→get_zValue()**YGyro****gyro→zValue()gyro.get_zValue()**

Returns the angular velocity around the Z axis of the device, as a floating point number.

js function **get_zValue()****nodejs** function **get_zValue()****php** function **get_zValue()****cpp** double **get_zValue()****m** -(double) zValue**pas** function **get_zValue(): double****vb** function **get_zValue() As Double****cs** double **get_zValue()****java** double **get_zValue()****py** def **get_zValue()****Returns :**

a floating point number corresponding to the angular velocity around the Z axis of the device, as a floating point number

On failure, throws an exception or returns **Y_ZVALUE_INVALID**.

gyro→isOnline()gyro.isOnline()**YGyro**

Checks if the gyroscope is currently reachable, without raising any error.

| | |
|--------|---------------------------------------|
| js | function isOnline() |
| nodejs | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the gyroscope in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the gyroscope.

Returns :

true if the gyroscope can be reached, and false otherwise

gyro→isOnline_async()

YGyro

Checks if the gyroscope is currently reachable, without raising any error (asynchronous version).

```
js   function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the gyroscope in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

gyro→load()gyro.load()**YGyro**

Preloads the gyroscope cache with a specified validity duration.

| | |
|--------|--|
| js | function load(msValidity) |
| nodejs | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | - (YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

gyro→loadCalibrationPoints() gyro.loadCalibrationPoints()

YGyro

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```

js   function loadCalibrationPoints( rawValues, refValues)
nodejs function loadCalibrationPoints( rawValues, refValues)
php  function loadCalibrationPoints( &$rawValues, &$refValues)
cpp   int loadCalibrationPoints( vector<double>& rawValues,
                                vector<double>& refValues)

m    -(int) loadCalibrationPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues

pas  function loadCalibrationPoints( var rawValues: TDoubleArray,
                           var refValues: TDoubleArray): LongInt

vb   procedure loadCalibrationPoints( )
cs   int loadCalibrationPoints( List<double> rawValues,
                           List<double> refValues)

java int loadCalibrationPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def loadCalibrationPoints( rawValues, refValues)
cmd  YGyro target loadCalibrationPoints rawValues refValues

```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

gyro→load_async()**YGyro**

Preloads the gyroscope cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

gyro→nextGyro()gyro.nextGyro()**YGYro**

Continues the enumeration of gyroscopes started using `yFirstGyro()`.

| | |
|---------------------|--|
| <code>js</code> | <code>function nextGyro()</code> |
| <code>nodejs</code> | <code>function nextGyro()</code> |
| <code>php</code> | <code>function nextGyro()</code> |
| <code>cpp</code> | <code>YGYro * nextGyro()</code> |
| <code>m</code> | <code>-(YGYro*) nextGyro</code> |
| <code>pas</code> | <code>function nextGyro(): TGYro</code> |
| <code>vb</code> | <code>function nextGyro() As YGYro</code> |
| <code>cs</code> | <code>YGYro nextGyro()</code> |
| <code>java</code> | <code>YGYro nextGyro()</code> |
| <code>py</code> | <code>def nextGyro()</code> |

Returns :

a pointer to a `YGYro` object, corresponding to a gyroscope currently online, or a `null` pointer if there are no more gyroscopes to enumerate.

**gyro→registerAnglesCallback()
gyro.registerAnglesCallback()****YGyro**

Registers a callback function that will be invoked each time that the estimated device orientation has changed.

```
js  function registerAnglesCallback( callback)
nodejs function registerAnglesCallback( callback)
php  function registerAnglesCallback( $callback)
cpp   int registerAnglesCallback( YAnglesCallback callback)
m    -(int) registerAnglesCallback : (YAnglesCallback) callback
pas   function registerAnglesCallback( callback: TYAnglesCallback): LongInt
vb    function registerAnglesCallback( ) As Integer
cs   int registerAnglesCallback( YAnglesCallback callback)
java  int registerAnglesCallback( YAnglesCallback callback)
py   def registerAnglesCallback( callback)
```

The call frequency is typically around 95Hz during a move. The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to invoke, or a null pointer. The callback function should take four arguments: the YGyro object of the turning device, and the floating point values of the three angles roll, pitch and heading in degrees (as floating-point numbers).

gyro→registerQuaternionCallback() gyro.registerQuaternionCallback()

YGyro

Registers a callback function that will be invoked each time that the estimated device orientation has changed.

| | |
|---------|---|
| js | function registerQuaternionCallback(callback) |
| node.js | function registerQuaternionCallback(callback) |
| php | function registerQuaternionCallback(\$callback) |
| cpp | int registerQuaternionCallback(YQuatCallback callback) |
| m | -(int) registerQuaternionCallback : (YQuatCallback) callback |
| pas | function registerQuaternionCallback(callback : TYQuatCallback): LongInt |
| vb | function registerQuaternionCallback() As Integer |
| cs | int registerQuaternionCallback(YQuatCallback callback) |
| java | int registerQuaternionCallback(YQuatCallback callback) |
| py | def registerQuaternionCallback(callback) |

The call frequency is typically around 95Hz during a move. The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to invoke, or a null pointer. The callback function should take five arguments: the YGyro object of the turning device, and the floating point values of the four components w, x, y and z (as floating-point numbers).

gyro→registerTimedReportCallback() gyro.registerTimedReportCallback()

YGyro

Registers the callback function that is invoked on every periodic timed notification.

```
js   function registerTimedReportCallback( callback )
node.js function registerTimedReportCallback( callback )
php  function registerTimedReportCallback( $callback )
cpp   int registerTimedReportCallback( YGyroTimedReportCallback callback )
m    -(int) registerTimedReportCallback : (YGyroTimedReportCallback) callback
pas   function registerTimedReportCallback( callback: TYGyroTimedReportCallback): LongInt
vb    function registerTimedReportCallback( ) As Integer
cs    int registerTimedReportCallback( TimedReportCallback callback )
java  int registerTimedReportCallback( TimedReportCallback callback )
py    def registerTimedReportCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

gyro→registerValueCallback() gyro.registerValueCallback()

YGYro

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback)
nodejs function registerValueCallback( callback)
php  function registerValueCallback( $callback)
cpp   int registerValueCallback( YGyroValueCallback callback)
m    -(int) registerValueCallback : (YGyroValueCallback) callback
pas   function registerValueCallback( callback: TYGYroValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs   int registerValueCallback( ValueCallback callback)
java  int registerValueCallback( UpdateCallback callback)
py    def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

gyro→set_highestValue() gyro→setHighestValue()gyro.set_highestValue()

YGYro

Changes the recorded maximal value observed.

```
js function set_highestValue( newval)
node.js function set_highestValue( newval)
php function set_highestValue( $newval)
cpp int set_highestValue( double newval)
m -(int) setHighestValue : (double) newval
pas function set_highestValue( newval: double): integer
vb function set_highestValue( ByVal newval As Double) As Integer
cs int set_highestValue( double newval)
java int set_highestValue( double newval)
py def set_highestValue( newval)
cmd YGYro target set_highestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

gyro→set_logFrequency()**YGyro****gyro→setLogFrequency()gyro.set_logFrequency()**

Changes the datalogger recording frequency for this function.

```
js   function set_logFrequency( newval)
nodejs function set_logFrequency( newval)
php  function set_logFrequency( $newval)
cpp   int set_logFrequency( const string& newval)
m    -(int) setLogFrequency : (NSString*) newval
pas   function set_logFrequency( newval: string): integer
vb    function set_logFrequency( ByVal newval As String) As Integer
cs    int set_logFrequency( string newval)
java  int set_logFrequency( String newval)
py    def set_logFrequency( newval)
cmd   YGyro target set_logFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

gyro→set_logicalName()YGyro

Changes the logical name of the gyroscope.

```
js function set_logicalName( newval)
node.js function set_logicalName( newval)
php function set_logicalName( $newval)
cpp int set_logicalName( const string& newval)
m -(int) setLogicalName : (NSString*) newval
pas function set_logicalName( newval: string): integer
vb function set_logicalName( ByVal newval As String) As Integer
cs int set_logicalName( string newval)
java int set_logicalName( String newval)
py def set_logicalName( newval)
cmd YGyro target set_logicalName newval
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the gyroscope.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

gyro→set_lowestValue() gyro→setLowestValue()gyro.set_lowestValue()

YGYro

Changes the recorded minimal value observed.

```
js function set_lowestValue( newval)
nodejs function set_lowestValue( newval)
php function set_lowestValue( $newval)
cpp int set_lowestValue( double newval)
m -(int) setLowestValue : (double) newval
pas function set_lowestValue( newval: double): integer
vb function set_lowestValue( ByVal newval As Double) As Integer
cs int set_lowestValue( double newval)
java int set_lowestValue( double newval)
py def set_lowestValue( newval)
cmd YGYro target set_lowestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

| | |
|-----------------------------------|--------------|
| gyro→set_reportFrequency() | YGyro |
| gyro→setReportFrequency() | |
| gyro.set_reportFrequency() | |

Changes the timed value notification frequency for this function.

```
js    function set_reportFrequency( newval)
nodejs function set_reportFrequency( newval)
php   function set_reportFrequency( $newval)
cpp   int set_reportFrequency( const string& newval)
m     -(int) setReportFrequency : (NSString*) newval
pas   function set_reportFrequency( newval: string): integer
vb    function set_reportFrequency( ByVal newval As String) As Integer
cs    int set_reportFrequency( string newval)
java  int set_reportFrequency( String newval)
py    def set_reportFrequency( newval)
cmd   YGyro target set_reportFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

gyro→set_resolution()**YGyro****gyro→setResolution()gyro.set_resolution()**

Changes the resolution of the measured physical values.

| | |
|---------------|--|
| js | <code>function set_resolution(newval)</code> |
| nodejs | <code>function set_resolution(newval)</code> |
| php | <code>function set_resolution(\$newval)</code> |
| cpp | <code>int set_resolution(double newval)</code> |
| m | <code>-(int) setResolution : (double) newval</code> |
| pas | <code>function set_resolution(newval: double): integer</code> |
| vb | <code>function set_resolution(ByVal newval As Double) As Integer</code> |
| cs | <code>int set_resolution(double newval)</code> |
| java | <code>int set_resolution(double newval)</code> |
| py | <code>def set_resolution(newval)</code> |
| cmd | <code>YGyro target set_resolution newval</code> |

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

gyro→set(userData)
gyro→setUserData()gyro.set(userData)**YGyro**

Stores a user context provided as argument in the userData attribute of the function.

```
js   function set(userData) data
node.js function set(userData) data
php  function set(userData) $data
cpp   void set(userData void* data)
m    -(void) setUserData : (void*) data
pas   procedure set(userData data: Tobject)
vb    procedure set(userData ByVal data As Object)
cs    void set(userData object data)
java  void set(userData Object data)
py    def set(userData data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

gyro→wait_async()

YGyro

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context )
nodejs function wait_async( callback, context )
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.19. Yocto-hub port interface

YHubPort objects provide control over the power supply for every YoctoHub port and provide information about the device connected to it. The logical name of a YHubPort is always automatically set to the unique serial number of the Yoctopuce device connected to it.

In order to use the functions described here, you should include:

| | |
|--------|---|
| js | <script type='text/javascript' src='yocto_hubport.js'></script> |
| nodejs | var yoctolib = require('yoctolib'); |
| | var YHubPort = yoctolib.YHubPort; |
| php | require_once('yocto_hubport.php'); |
| cpp | #include "yocto_hubport.h" |
| m | #import "yocto_hubport.h" |
| pas | uses yocto_hubport; |
| vb | yocto_hubport.vb |
| cs | yocto_hubport.cs |
| java | import com.yoctopuce.YoctoAPI.YHubPort; |
| py | from yocto_hubport import * |

Global functions

yFindHubPort(func)

Retrieves a Yocto-hub port for a given identifier.

yFirstHubPort()

Starts the enumeration of Yocto-hub ports currently accessible.

YHubPort methods

hubport→describe()

Returns a short text that describes unambiguously the instance of the Yocto-hub port in the form TYPE (NAME)=SERIAL . FUNCTIONID.

hubport→get_advertisedValue()

Returns the current value of the Yocto-hub port (no more than 6 characters).

hubport→get_baudRate()

Returns the current baud rate used by this Yocto-hub port, in kbps.

hubport→get_enabled()

Returns true if the Yocto-hub port is powered, false otherwise.

hubport→get_errorMessage()

Returns the error message of the latest error with the Yocto-hub port.

hubport→get_errorType()

Returns the numerical error code of the latest error with the Yocto-hub port.

hubport→get_friendlyName()

Returns a global identifier of the Yocto-hub port in the format MODULE_NAME . FUNCTION_NAME.

hubport→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

hubport→get_functionId()

Returns the hardware identifier of the Yocto-hub port, without reference to the module.

hubport→get_hardwareId()

Returns the unique hardware identifier of the Yocto-hub port in the form SERIAL . FUNCTIONID.

hubport→get_logicalName()

Returns the logical name of the Yocto-hub port.

| | |
|--|--|
| hubport→get_module() | Gets the YModule object for the device on which the function is located. |
| hubport→get_module_async(callback, context) | Gets the YModule object for the device on which the function is located (asynchronous version). |
| hubport→get_portState() | Returns the current state of the Yocto-hub port. |
| hubport→get_userData() | Returns the value of the userData attribute, as previously stored using method set(userData). |
| hubport→isOnline() | Checks if the Yocto-hub port is currently reachable, without raising any error. |
| hubport→isOnline_async(callback, context) | Checks if the Yocto-hub port is currently reachable, without raising any error (asynchronous version). |
| hubport→load(msValidity) | Preloads the Yocto-hub port cache with a specified validity duration. |
| hubport→load_async(msValidity, callback, context) | Preloads the Yocto-hub port cache with a specified validity duration (asynchronous version). |
| hubport→nextHubPort() | Continues the enumeration of Yocto-hub ports started using yFirstHubPort(). |
| hubport→registerValueCallback(callback) | Registers the callback function that is invoked on every change of advertised value. |
| hubport→set_enabled(newval) | Changes the activation of the Yocto-hub port. |
| hubport→set_logicalName(newval) | Changes the logical name of the Yocto-hub port. |
| hubport→set_userData(data) | Stores a user context provided as argument in the userData attribute of the function. |
| hubport→wait_async(callback, context) | Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function. |

YHubPort.FindHubPort() yFindHubPort()YHubPort.FindHubPort()

YHubPort

Retrieves a Yocto-hub port for a given identifier.

```
js function yFindHubPort( func)
node.js function FindHubPort( func)
php function yFindHubPort( $func)
cpp YHubPort* yFindHubPort( const string& func)
m YHubPort* yFindHubPort( NSString* func)
pas function yFindHubPort( func: string): TYHubPort
vb function yFindHubPort( ByVal func As String) As YHubPort
cs YHubPort FindHubPort( string func)
java YHubPort FindHubPort( String func)
py def FindHubPort( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the Yocto-hub port is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YHubPort.isOnline()` to test if the Yocto-hub port is indeed online at a given time. In case of ambiguity when looking for a Yocto-hub port by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the Yocto-hub port

Returns :

a `YHubPort` object allowing you to drive the Yocto-hub port.

YHubPort.FirstHubPort()**YHubPort****yFirstHubPort()YHubPort.FirstHubPort()**

Starts the enumeration of Yocto-hub ports currently accessible.

| | |
|--------|--|
| js | function yFirstHubPort() |
| nodejs | function FirstHubPort() |
| php | function yFirstHubPort() |
| cpp | YHubPort* yFirstHubPort() |
| m | YHubPort* yFirstHubPort() |
| pas | function yFirstHubPort(): TYHubPort |
| vb | function yFirstHubPort() As YHubPort |
| cs | YHubPort FirstHubPort() |
| java | YHubPort FirstHubPort() |
| py | def FirstHubPort() |

Use the method `YHubPort.nextHubPort()` to iterate on next Yocto-hub ports.

Returns :

a pointer to a `YHubPort` object, corresponding to the first Yocto-hub port currently online, or a `null` pointer if there are none.

hubport→describe()hubport.describe()**YHubPort**

Returns a short text that describes unambiguously the instance of the Yocto-hub port in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the Yocto-hub port (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

hubport→get_advertisedValue()
hubport→advertisedValue()
hubport.get_advertisedValue()

YHubPort

Returns the current value of the Yocto-hub port (no more than 6 characters).

| | |
|----------------|--|
| js | function get_advertisedValue() |
| node.js | function get_advertisedValue() |
| php | function get_advertisedValue() |
| cpp | string get_advertisedValue() |
| m | -(NSString*) advertisedValue |
| pas | function get_advertisedValue() : string |
| vb | function get_advertisedValue() As String |
| cs | string get_advertisedValue() |
| java | String get_advertisedValue() |
| py | def get_advertisedValue() |
| cmd | YHubPort target get_advertisedValue |

Returns :

a string corresponding to the current value of the Yocto-hub port (no more than 6 characters). On failure, throws an exception or returns **Y_ADVERTISEDVALUE_INVALID**.

hubport→get_baudRate() hubport→baudRate()hubport.get_baudRate()

Returns the current baud rate used by this Yocto-hub port, in kbps.

| | |
|---------|--|
| js | function get_baudRate() |
| node.js | function get_baudRate() |
| php | function get_baudRate() |
| cpp | int get_baudRate() |
| m | -(int) baudRate |
| pas | function get_baudRate() : LongInt |
| vb | function get_baudRate() As Integer |
| cs | int get_baudRate() |
| java | int get_baudRate() |
| py | def get_baudRate() |
| cmd | YHubPort target get_baudRate |

The default value is 1000 kbps, but a slower rate may be used if communication problems are encountered.

Returns :

an integer corresponding to the current baud rate used by this Yocto-hub port, in kbps

On failure, throws an exception or returns Y_BAUDRATE_INVALID.

hubport→get_enabled()**YHubPort****hubport→enabled()hubport.get_enabled()**

Returns true if the Yocto-hub port is powered, false otherwise.

| | |
|--------|---|
| js | function get_enabled() |
| nodejs | function get_enabled() |
| php | function get_enabled() |
| cpp | Y_ENABLED_enum get_enabled() |
| m | -(Y_ENABLED_enum) enabled |
| pas | function get_enabled() : Integer |
| vb | function get_enabled() As Integer |
| cs | int get_enabled() |
| java | int get_enabled() |
| py | def get_enabled() |
| cmd | YHubPort target get_enabled |

Returns :

either Y_ENABLED_FALSE or Y_ENABLED_TRUE, according to true if the Yocto-hub port is powered, false otherwise

On failure, throws an exception or returns Y_ENABLED_INVALID.

hubport→get_errorMessage()**YHubPort****hubport→errorMessage()hubport.get_errorMessage()**

Returns the error message of the latest error with the Yocto-hub port.

| | |
|---------|---|
| js | function get_errorMessage() |
| node.js | function get_errorMessage() |
| php | function get_errorMessage() |
| cpp | string get_errorMessage() |
| m | - (NSString*) errorMessage |
| pas | function get_errorMessage(): string |
| vb | function get_errorMessage() As String |
| cs | string get_errorMessage() |
| java | String get_errorMessage() |
| py | def get_errorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the Yocto-hub port object

hubport→get_errorType() hubport→errorType()hubport.get_errorType()

YHubPort

Returns the numerical error code of the latest error with the Yocto-hub port.

| | |
|--------|---------------------------------------|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType(): YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the Yocto-hub port object

hubport→get_friendlyName()**YHubPort****hubport→friendlyName()hubport.get_friendlyName()**

Returns a global identifier of the Yocto-hub port in the format MODULE_NAME . FUNCTION_NAME.

| | |
|---------|------------------------------|
| js | function get_friendlyName() |
| node.js | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the Yocto-hub port if they are defined, otherwise the serial number of the module and the hardware identifier of the Yocto-hub port (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the Yocto-hub port using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

hubport→get_functionDescriptor()
hubport→functionDescriptor()
hubport.get_functionDescriptor()

YHubPort

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

hubport→get_functionId()**YHubPort****hubport→functionId()hubport.get_functionId()**

Returns the hardware identifier of the Yocto-hub port, without reference to the module.

| | |
|---------|--|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the Yocto-hub port (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

hubport→get_hardwareId()**YHubPort****hubport→hardwareId()hubport.get_hardwareId()**

Returns the unique hardware identifier of the Yocto-hub port in the form SERIAL.FUNCTIONID.

| | |
|--------|---|
| js | function get_hardwareId() |
| nodejs | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the Yocto-hub port. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the Yocto-hub port (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

hubport→get_logicalName()**YHubPort****hubport→logicalName()hubport.get_logicalName()**

Returns the logical name of the Yocto-hub port.

| | |
|---------|--|
| js | function get_logicalName() |
| node.js | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | - (NSString*) logicalName |
| pas | function get_logicalName(): string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YHubPort target get_logicalName |

Returns :

a string corresponding to the logical name of the Yocto-hub port. On failure, throws an exception or returns **Y_LOGICALNAME_INVALID**.

hubport→get_module()**YHubPort****hubport→module()hubport.get_module()**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

hubport→get_module_async()
hubport→module_async()**YHubPort**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

`js` `function get_module_async(callback, context)`
`node.js` `function get_module_async(callback, context)`

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

hubport→get_portState()**YHubPort****hubport→portState()hubport.get_portState()**

Returns the current state of the Yocto-hub port.

| | |
|--------|--|
| js | function get_portState() |
| nodejs | function get_portState() |
| php | function get_portState() |
| cpp | Y_PORTSTATE_enum get_portState() |
| m | -(Y_PORTSTATE_enum) portState |
| pas | function get_portState() : Integer |
| vb | function get_portState() As Integer |
| cs | int get_portState() |
| java | int get_portState() |
| py | def get_portState() |
| cmd | YHubPort target get_portState |

Returns :

a value among Y_PORTSTATE_OFF, Y_PORTSTATE_OVRLD, Y_PORTSTATE_ON, Y_PORTSTATE_RUN and Y_PORTSTATE_PROG corresponding to the current state of the Yocto-hub port

On failure, throws an exception or returns Y_PORTSTATE_INVALID.

hubport→get(userData)**YHubPort****hubport→userData()hubport.get(userData)**

Returns the value of the userData attribute, as previously stored using method set(userData).

```
js function get(userData) 
node.js function get(userData) 
php function get(userData) 
cpp void * get(userData) 
m -(void*) userData 
pas function get(userData): Tobject 
vb function get(userData) As Object 
cs object get(userData) 
java Object get(userData) 
py def get(userData)
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

hubport→isOnline()hubport.isOnline()**YHubPort**

Checks if the Yocto-hub port is currently reachable, without raising any error.

| | |
|---------|---|
| js | function isOnline () |
| node.js | function isOnline () |
| php | function isOnline () |
| cpp | bool isOnline () |
| m | -(BOOL) isOnline |
| pas | function isOnline (): boolean |
| vb | function isOnline () As Boolean |
| cs | bool isOnline () |
| java | boolean isOnline () |
| py | def isOnline () |

If there is a cached value for the Yocto-hub port in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the Yocto-hub port.

Returns :

true if the Yocto-hub port can be reached, and false otherwise

hubport→isOnline_async()

YHubPort

Checks if the Yocto-hub port is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the Yocto-hub port in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

hubport→load()hubport.load()**YHubPort**

Preloads the Yocto-hub port cache with a specified validity duration.

| | |
|----------------------|--|
| <code>js</code> | <code>function load(msValidity)</code> |
| <code>node.js</code> | <code>function load(msValidity)</code> |
| <code>php</code> | <code>function load(\$msValidity)</code> |
| <code>cpp</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>m</code> | <code>-(YRETCODE) load : (int) msValidity</code> |
| <code>pas</code> | <code>function load(msValidity: integer): YRETCODE</code> |
| <code>vb</code> | <code>function load(ByVal msValidity As Integer) As YRETCODE</code> |
| <code>cs</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>java</code> | <code>int load(long msValidity)</code> |
| <code>py</code> | <code>def load(msValidity)</code> |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

hubport→load_async()

YHubPort

Preloads the Yocto-hub port cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

hubport→nextHubPort()hubport.nextHubPort()**YHubPort**

Continues the enumeration of Yocto-hub ports started using `yFirstHubPort()`.

| | |
|---------------------|--|
| <code>js</code> | <code>function nextHubPort()</code> |
| <code>nodejs</code> | <code>function nextHubPort()</code> |
| <code>php</code> | <code>function nextHubPort()</code> |
| <code>cpp</code> | <code>YHubPort * nextHubPort()</code> |
| <code>m</code> | <code>-(YHubPort*) nextHubPort</code> |
| <code>pas</code> | <code>function nextHubPort(): TYHubPort</code> |
| <code>vb</code> | <code>function nextHubPort() As YHubPort</code> |
| <code>cs</code> | <code>YHubPort nextHubPort()</code> |
| <code>java</code> | <code>YHubPort nextHubPort()</code> |
| <code>py</code> | <code>def nextHubPort()</code> |

Returns :

a pointer to a `YHubPort` object, corresponding to a Yocto-hub port currently online, or a `null` pointer if there are no more Yocto-hub ports to enumerate.

hubport→registerValueCallback() hubport.registerValueCallback()

YHubPort

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YHubPortValueCallback callback )
m    -(int) registerValueCallback : (YHubPortValueCallback) callback
pas   function registerValueCallback( callback: TYHubPortValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

hubport→set_enabled()

YHubPort

Changes the activation of the Yocto-hub port.

| | |
|---------------------|--|
| <code>js</code> | <code>function set_enabled(newval)</code> |
| <code>nodejs</code> | <code>function set_enabled(newval)</code> |
| <code>php</code> | <code>function set_enabled(\$newval)</code> |
| <code>cpp</code> | <code>int set_enabled(Y_ENABLED_enum newval)</code> |
| <code>m</code> | <code>-(int) setEnabled : (Y_ENABLED_enum) newval</code> |
| <code>pas</code> | <code>function set_enabled(newval: Integer): integer</code> |
| <code>vb</code> | <code>function set_enabled(ByVal newval As Integer) As Integer</code> |
| <code>cs</code> | <code>int set_enabled(int newval)</code> |
| <code>java</code> | <code>int set_enabled(int newval)</code> |
| <code>py</code> | <code>def set_enabled(newval)</code> |
| <code>cmd</code> | <code>YHubPort target set_enabled newval</code> |

If the port is enabled, the connected module is powered. Otherwise, port power is shut down.

Parameters :

newval either `Y_ENABLED_FALSE` or `Y_ENABLED_TRUE`, according to the activation of the Yocto-hub port

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

hubport→set_logicalName()
hubport→setLogicalName()
hubport.set_logicalName()

YHubPort

Changes the logical name of the Yocto-hub port.

```
js function set_logicalName( newval)
nodejs function set_logicalName( newval)
php function set_logicalName( $newval)
cpp int set_logicalName( const string& newval)
m -(int) setLogicalName : (NSString*) newval
pas function set_logicalName( newval: string): integer
vb function set_logicalName( ByVal newval As String) As Integer
cs int set_logicalName( string newval)
java int set_logicalName( String newval)
py def set_logicalName( newval)
cmd YHubPort target set_logicalName newval
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the Yocto-hub port.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

hubport→set(userData)**YHubPort****hubport→setUserData()hubport.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|---|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData) |
| cpp | void set(userData) (void* data) |
| m | -(void) set(userData : (void*) data |
| pas | procedure set(userData : Tobject) |
| vb | procedure set(userData : ByVal data As Object) |
| cs | void set(userData : object data) |
| java | void set(userData : Object data) |
| py | def set(userData : data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

hubport→wait_async()

YHubPort

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.20. Humidity function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

| | |
|--------|--|
| js | <script type='text/javascript' src='yocto_humidity.js'></script> |
| nodejs | var yoctolib = require('yoctolib'); |
| | var YHumidity = yoctolib.YHumidity; |
| php | require_once('yocto_humidity.php'); |
| cpp | #include "yocto_humidity.h" |
| m | #import "yocto_humidity.h" |
| pas | uses yocto_humidity; |
| vb | yocto_humidity.vb |
| cs | yocto_humidity.cs |
| java | import com.yoctopuce.YoctoAPI.YHumidity; |
| py | from yocto_humidity import * |

Global functions

yFindHumidity(func)

Retrieves a humidity sensor for a given identifier.

yFirstHumidity()

Starts the enumeration of humidity sensors currently accessible.

YHumidity methods

humidity→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

humidity→describe()

Returns a short text that describes unambiguously the instance of the humidity sensor in the form TYPE (NAME)=SERIAL . FUNCTIONID.

humidity→get_advertisedValue()

Returns the current value of the humidity sensor (no more than 6 characters).

humidity→get_currentRawValue()

Returns the unrounded and uncalibrated raw value returned by the sensor.

humidity→get_currentValue()

Returns the current measure for the humidity.

humidity→get_errorMessage()

Returns the error message of the latest error with the humidity sensor.

humidity→get_errorType()

Returns the numerical error code of the latest error with the humidity sensor.

humidity→get_friendlyName()

Returns a global identifier of the humidity sensor in the format MODULE_NAME . FUNCTION_NAME.

humidity→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

humidity→get_functionId()

Returns the hardware identifier of the humidity sensor, without reference to the module.

humidity→get_hardwareId()

Returns the unique hardware identifier of the humidity sensor in the form SERIAL . FUNCTIONID.

3. Reference

| |
|--|
| humidity→get_highestValue() |
| Returns the maximal value observed for the humidity. |
| humidity→get_logFrequency() |
| Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory. |
| humidity→get_logicalName() |
| Returns the logical name of the humidity sensor. |
| humidity→get_lowestValue() |
| Returns the minimal value observed for the humidity. |
| humidity→get_module() |
| Gets the YModule object for the device on which the function is located. |
| humidity→get_module_async(callback, context) |
| Gets the YModule object for the device on which the function is located (asynchronous version). |
| humidity→get_recordedData(startTime, endTime) |
| Retrieves a DataSet object holding historical data for this sensor, for a specified time interval. |
| humidity→get_reportFrequency() |
| Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function. |
| humidity→get_resolution() |
| Returns the resolution of the measured values. |
| humidity→get_unit() |
| Returns the measuring unit for the humidity. |
| humidity→get(userData) |
| Returns the value of the userData attribute, as previously stored using method set(userData). |
| humidity→isOnline() |
| Checks if the humidity sensor is currently reachable, without raising any error. |
| humidity→isOnline_async(callback, context) |
| Checks if the humidity sensor is currently reachable, without raising any error (asynchronous version). |
| humidity→load(msValidity) |
| Preloads the humidity sensor cache with a specified validity duration. |
| humidity→loadCalibrationPoints(rawValues, refValues) |
| Retrieves error correction data points previously entered using the method calibrateFromPoints. |
| humidity→load_async(msValidity, callback, context) |
| Preloads the humidity sensor cache with a specified validity duration (asynchronous version). |
| humidity→nextHumidity() |
| Continues the enumeration of humidity sensors started using yFirstHumidity(). |
| humidity→registerTimedReportCallback(callback) |
| Registers the callback function that is invoked on every periodic timed notification. |
| humidity→registerValueCallback(callback) |
| Registers the callback function that is invoked on every change of advertised value. |
| humidity→set_highestValue(newval) |
| Changes the recorded maximal value observed for the humidity. |
| humidity→set_logFrequency(newval) |
| Changes the datalogger recording frequency for this function. |
| humidity→set_logicalName(newval) |
| Changes the logical name of the humidity sensor. |

humidity→set_lowestValue(newval)

Changes the recorded minimal value observed for the humidity.

humidity→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

humidity→set_resolution(newval)

Changes the resolution of the measured physical values.

humidity→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

humidity→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YHumidity.FindHumidity()**YHumidity****yFindHumidity()YHumidity.FindHumidity()**

Retrieves a humidity sensor for a given identifier.

```
js function yFindHumidity( func)
node.js function FindHumidity( func)
php function yFindHumidity( $func)
cpp YHumidity* yFindHumidity( const string& func)
m YHumidity* yFindHumidity( NSString* func)
pas function yFindHumidity( func: string): TYHumidity
vb function yFindHumidity( ByVal func As String) As YHumidity
cs YHumidity FindHumidity( string func)
java YHumidity FindHumidity( String func)
def FindHumidity( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the humidity sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YHumidity.isOnline()` to test if the humidity sensor is indeed online at a given time. In case of ambiguity when looking for a humidity sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the humidity sensor

Returns :

a `YHumidity` object allowing you to drive the humidity sensor.

YHumidity.FirstHumidity()

yFirstHumidity() YHumidity.FirstHumidity()

YHumidity

Starts the enumeration of humidity sensors currently accessible.

| | |
|--------|--|
| js | function yFirstHumidity() |
| nodejs | function FirstHumidity() |
| php | function yFirstHumidity() |
| cpp | YHumidity* yFirstHumidity() |
| m | YHumidity* yFirstHumidity() |
| pas | function yFirstHumidity() : TYHumidity |
| vb | function yFirstHumidity() As YHumidity |
| cs | YHumidity FirstHumidity() |
| java | YHumidity FirstHumidity() |
| py | def FirstHumidity() |

Use the method `YHumidity.nextHumidity()` to iterate on next humidity sensors.

Returns :

a pointer to a `YHumidity` object, corresponding to the first humidity sensor currently online, or a `null` pointer if there are none.

humidity→calibrateFromPoints() humidity.calibrateFromPoints()

YHumidity

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```

js   function calibrateFromPoints( rawValues, refValues)
nodejs function calibrateFromPoints( rawValues, refValues)
php   function calibrateFromPoints( $rawValues, $refValues)
cpp    int calibrateFromPoints( vector<double> rawValues,
                               vector<double> refValues)
m     -(int) calibrateFromPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues
pas   function calibrateFromPoints( rawValues: TDoubleArray,
                                   refValues: TDoubleArray): LongInt
vb    procedure calibrateFromPoints( )
cs    int calibrateFromPoints( List<double> rawValues,
                           List<double> refValues)
java  int calibrateFromPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)
py    def calibrateFromPoints( rawValues, refValues)
cmd   YHumidity target calibrateFromPoints rawValues refValues

```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

humidity→describe()humidity.describe()**YHumidity**

Returns a short text that describes unambiguously the instance of the humidity sensor in the form TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--|
| js | function describe () |
| nodejs | function describe () |
| php | function describe () |
| cpp | string describe () |
| m | -(NSString*) describe |
| pas | function describe (): string |
| vb | function describe () As String |
| cs | string describe () |
| java | String describe () |
| py | def describe () |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the humidity sensor (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

humidity→get_advertisedValue()**YHumidity****humidity→advertisedValue()****humidity.get_advertisedValue()**

Returns the current value of the humidity sensor (no more than 6 characters).

```
js function get_advertisedValue( )  
nodejs function get_advertisedValue( )  
php function get_advertisedValue( )  
cpp string get_advertisedValue( )  
m -(NSString*) advertisedValue  
pas function get_advertisedValue( ): string  
vb function get_advertisedValue( ) As String  
cs string get_advertisedValue( )  
java String get_advertisedValue( )  
py def get_advertisedValue( )  
cmd YHumidity target get_advertisedValue
```

Returns :

a string corresponding to the current value of the humidity sensor (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

humidity→get_currentRawValue()
humidity→currentRawValue()
humidity.get_currentRawValue()**YHumidity**

Returns the unrounded and uncalibrated raw value returned by the sensor.

| | |
|---------|--|
| js | function get_currentRawValue() |
| node.js | function get_currentRawValue() |
| php | function get_currentRawValue() |
| cpp | double get_currentRawValue() |
| m | -(double) currentRawValue |
| pas | function get_currentRawValue(): double |
| vb | function get_currentRawValue() As Double |
| cs | double get_currentRawValue() |
| java | double get_currentRawValue() |
| py | def get_currentRawValue() |
| cmd | YHumidity target get_currentRawValue |

Returns :

a floating point number corresponding to the unrounded and uncalibrated raw value returned by the sensor

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

humidity→get_currentValue()**YHumidity****humidity→currentValue()humidity.get_currentValue()**

Returns the current measure for the humidity.

```
js function get_currentValue( )
node.js function get_currentValue( )
php function get_currentValue( )
cpp double get_currentValue( )
m -(double) currentValue
pas function get_currentValue( ): double
vb function get_currentValue( ) As Double
cs double get_currentValue( )
java double get_currentValue( )
py def get_currentValue( )
cmd YHumidity target get_currentValue
```

Returns :

a floating point number corresponding to the current measure for the humidity

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

humidity→getErrorMessage()
humidity→errorMessage()
humidity.getErrorMessage()**YHumidity**

Returns the error message of the latest error with the humidity sensor.

| | |
|---------|---------------------------------------|
| js | function getErrorMessage() |
| node.js | function getErrorMessage() |
| php | function getErrorMessage() |
| cpp | string getErrorMessage() |
| m | -(NSString*) errorMessage |
| pas | function getErrorMessage(): string |
| vb | function getErrorMessage() As String |
| cs | string getErrorMessage() |
| java | String getErrorMessage() |
| py | def getErrorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the humidity sensor object

humidity→get_errorType()**YHumidity****humidity→errorType()humidity.get_errorType()**

Returns the numerical error code of the latest error with the humidity sensor.

```
js   function get_errorType( )  
node.js function get_errorType( )  
php  function get_errorType( )  
cpp   YRETCODE get_errorType( )  
pas   function get_errorType( ): YRETCODE  
vb    function get_errorType( ) As YRETCODE  
cs    YRETCODE get_errorType( )  
java  int get_errorType( )  
py    def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the humidity sensor object

humidity→get_friendlyName()
humidity→friendlyName()
humidity.get_friendlyName()**YHumidity**

Returns a global identifier of the humidity sensor in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the humidity sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the humidity sensor (for exemple: MyCustomName . relay1)

Returns :

a string that uniquely identifies the humidity sensor using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

**humidity→get_functionDescriptor()
humidity→functionDescriptor()
humidity.get_functionDescriptor()****YHumidity**

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|---|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

humidity→get_functionId()**YHumidity****humidity→functionId()humidity.get_functionId()**

Returns the hardware identifier of the humidity sensor, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the humidity sensor (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

humidity→get.hardwareId()**YHumidity****humidity→hardwareId()humidity.get.hardwareId()**

Returns the unique hardware identifier of the humidity sensor in the form SERIAL.FUNCTIONID.

| | |
|---------|--------------------------------------|
| js | function get.hardwareId() |
| node.js | function get.hardwareId() |
| php | function get.hardwareId() |
| cpp | string get.hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get.hardwareId() As String |
| cs | string get.hardwareId() |
| java | String get.hardwareId() |
| py | def get.hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the humidity sensor. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the humidity sensor (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

humidity→get_highestValue()
humidity→highestValue()
humidity.get_highestValue()

YHumidity

Returns the maximal value observed for the humidity.

| | |
|----------------------|---|
| <code>js</code> | <code>function get_highestValue()</code> |
| <code>node.js</code> | <code>function get_highestValue()</code> |
| <code>php</code> | <code>function get_highestValue()</code> |
| <code>cpp</code> | <code>double get_highestValue()</code> |
| <code>m</code> | <code>-(double) highestValue</code> |
| <code>pas</code> | <code>function get_highestValue(): double</code> |
| <code>vb</code> | <code>function get_highestValue() As Double</code> |
| <code>cs</code> | <code>double get_highestValue()</code> |
| <code>java</code> | <code>double get_highestValue()</code> |
| <code>py</code> | <code>def get_highestValue()</code> |
| <code>cmd</code> | <code>YHumidity target get_highestValue</code> |

Returns :

a floating point number corresponding to the maximal value observed for the humidity

On failure, throws an exception or returns `Y_HIGHESTVALUE_INVALID`.

humidity→get_logFrequency()
humidity→logFrequency()
humidity.get_logFrequency()**YHumidity**

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

| | |
|--------|--|
| js | function get_logFrequency() |
| nodejs | function get_logFrequency() |
| php | function get_logFrequency() |
| cpp | string get_logFrequency() |
| m | -(NSString*) logFrequency |
| pas | function get_logFrequency(): string |
| vb | function get_logFrequency() As String |
| cs | string get_logFrequency() |
| java | String get_logFrequency() |
| py | def get_logFrequency() |
| cmd | YHumidity target get_logFrequency |

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

humidity→get_logicalName()**YHumidity****humidity→logicalName()humidity.get_logicalName()**

Returns the logical name of the humidity sensor.

```
js   function get_logicalName( )  
nodejs function get_logicalName( )  
php  function get_logicalName( )  
cpp   string get_logicalName( )  
m    -(NSString*) logicalName  
pas   function get_logicalName( ): string  
vb    function get_logicalName( ) As String  
cs    string get_logicalName( )  
java  String get_logicalName( )  
py    def get_logicalName( )  
cmd   YHumidity target get_logicalName
```

Returns :

a string corresponding to the logical name of the humidity sensor. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

humidity→get_lowestValue()**YHumidity****humidity→lowestValue()humidity.get_lowestValue()**

Returns the minimal value observed for the humidity.

```
js function get_lowestValue( )  
node.js function get_lowestValue( )  
php function get_lowestValue( )  
cpp double get_lowestValue( )  
m -(double) lowestValue  
pas function get_lowestValue( ): double  
vb function get_lowestValue( ) As Double  
cs double get_lowestValue( )  
java double get_lowestValue( )  
py def get_lowestValue( )  
cmd YHumidity target get_lowestValue
```

Returns :

a floating point number corresponding to the minimal value observed for the humidity

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

humidity→get_module()**YHumidity****humidity→module()humidity.get_module()**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

humidity→get_module_async()**YHumidity****humidity→module_async()**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

humidity→`get_recordedData()`
humidity→`recordedData()`
humidity.get_recordedData()

YHumidity

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the `DataSet` class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measurement, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of `YDataSet`, providing access to historical data. Past measures can be loaded progressively using methods from the `YDataSet` object.

humidity→get_reportFrequency()
humidity→reportFrequency()
humidity.get_reportFrequency()**YHumidity**

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

| | |
|--------|---|
| js | function get_reportFrequency() |
| nodejs | function get_reportFrequency() |
| php | function get_reportFrequency() |
| cpp | string get_reportFrequency() |
| m | -(NSString*) reportFrequency |
| pas | function get_reportFrequency(): string |
| vb | function get_reportFrequency() As String |
| cs | string get_reportFrequency() |
| java | String get_reportFrequency() |
| py | def get_reportFrequency() |
| cmd | YHumidity target get_reportFrequency |

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

humidity→get_resolution()**YHumidity****humidity→resolution()humidity.get_resolution()**

Returns the resolution of the measured values.

| | |
|--------|---|
| js | function get_resolution() |
| nodejs | function get_resolution() |
| php | function get_resolution() |
| cpp | double get_resolution() |
| m | -(double) resolution |
| pas | function get_resolution(): double |
| vb | function get_resolution() As Double |
| cs | double get_resolution() |
| java | double get_resolution() |
| py | def get_resolution() |
| cmd | YHumidity target get_resolution |

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns **Y_RESOLUTION_INVALID**.

humidity→get_unit()**YHumidity****humidity→unit()humidity.get_unit()**

Returns the measuring unit for the humidity.

| | |
|---------|---------------------------------------|
| js | function get_unit() |
| node.js | function get_unit() |
| php | function get_unit() |
| cpp | string get_unit() |
| m | -(NSString*) unit |
| pas | function get_unit(): string |
| vb | function get_unit() As String |
| cs | string get_unit() |
| java | String get_unit() |
| py | def get_unit() |
| cmd | YHumidity target get_unit |

Returns :

a string corresponding to the measuring unit for the humidity

On failure, throws an exception or returns Y_UNIT_INVALID.

humidity→get(userData)**YHumidity****humidity→userData()humidity.get(userData())**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|---|
| js | <code>function get(userData) </code> |
| nodejs | <code>function get(userData) </code> |
| php | <code>function get(userData) </code> |
| cpp | <code>void * get(userData) </code> |
| m | <code>-(void*) userData</code> |
| pas | <code>function get(userData): Tobject</code> |
| vb | <code>function get(userData) As Object</code> |
| cs | <code>object get(userData) </code> |
| java | <code>Object get(userData) </code> |
| py | <code>def get(userData) </code> |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

humidity→isOnline()humidity.isOnline()****

YHumidity

Checks if the humidity sensor is currently reachable, without raising any error.

| | |
|--------|---------------------------------------|
| js | function isOnline() |
| nodejs | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the humidity sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the humidity sensor.

Returns :

true if the humidity sensor can be reached, and false otherwise

humidity→isOnline_async()

YHumidity

Checks if the humidity sensor is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the humidity sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

humidity→load()**humidity.load()**

YHumidity

Preloads the humidity sensor cache with a specified validity duration.

```
js   function load( msValidity)
nodejs function load( msValidity)
php  function load( $msValidity)
cpp   YRETCODE load( int msValidity)
m    -(YRETCODE) load : (int) msValidity
pas   function load( msValidity: integer): YRETCODE
vb    function load( ByVal msValidity As Integer) As YRETCODE
cs    YRETCODE load( int msValidity)
java  int load( long msValidity)
py    def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

humidity→loadCalibrationPoints() humidity.loadCalibrationPoints()

YHumidity

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```

js   function loadCalibrationPoints( rawValues, refValues)
nodejs function loadCalibrationPoints( rawValues, refValues)
php  function loadCalibrationPoints( &$rawValues, &$refValues)
cpp   int loadCalibrationPoints( vector<double>& rawValues,
                                vector<double>& refValues)

m    -(int) loadCalibrationPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues

pas  function loadCalibrationPoints( var rawValues: TDoubleArray,
                           var refValues: TDoubleArray): LongInt

vb   procedure loadCalibrationPoints( )
cs   int loadCalibrationPoints( List<double> rawValues,
                           List<double> refValues)

java int loadCalibrationPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def loadCalibrationPoints( rawValues, refValues)
cmd  YHumidity target loadCalibrationPoints rawValues refValues

```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

humidity→load_async()

YHumidity

Preloads the humidity sensor cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

humidity→nextHumidity()humidity.nextHumidity()**YHumidity**

Continues the enumeration of humidity sensors started using `yFirstHumidity()`.

| | |
|---------------------|--|
| <code>js</code> | <code>function nextHumidity()</code> |
| <code>nodejs</code> | <code>function nextHumidity()</code> |
| <code>php</code> | <code>function nextHumidity()</code> |
| <code>cpp</code> | <code>YHumidity * nextHumidity()</code> |
| <code>m</code> | <code>-(YHumidity*) nextHumidity</code> |
| <code>pas</code> | <code>function nextHumidity(): TYHumidity</code> |
| <code>vb</code> | <code>function nextHumidity() As YHumidity</code> |
| <code>cs</code> | <code>YHumidity nextHumidity()</code> |
| <code>java</code> | <code>YHumidity nextHumidity()</code> |
| <code>py</code> | <code>def nextHumidity()</code> |

Returns :

a pointer to a `YHumidity` object, corresponding to a humidity sensor currently online, or a `null` pointer if there are no more humidity sensors to enumerate.

humidity→registerTimedReportCallback() humidity.registerTimedReportCallback()

YHumidity

Registers the callback function that is invoked on every periodic timed notification.

```
js   function registerTimedReportCallback( callback)
node.js function registerTimedReportCallback( callback)
php  function registerTimedReportCallback( $callback)
cpp   int registerTimedReportCallback( YHumidityTimedReportCallback callback)
m    -(int) registerTimedReportCallback : (YHumidityTimedReportCallback) callback
pas   function registerTimedReportCallback( callback: TYHumidityTimedReportCallback): LongInt
vb    function registerTimedReportCallback( ) As Integer
cs    int registerTimedReportCallback( TimedReportCallback callback)
java  int registerTimedReportCallback( TimedReportCallback callback)
py    def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

humidity→registerValueCallback() humidity.registerValueCallback()

YHumidity

Registers the callback function that is invoked on every change of advertised value.

| | |
|---------|---|
| js | function registerValueCallback(callback) |
| node.js | function registerValueCallback(callback) |
| php | function registerValueCallback(\$callback) |
| cpp | int registerValueCallback(YHumidityValueCallback callback) |
| m | -(int) registerValueCallback : (YHumidityValueCallback) callback |
| pas | function registerValueCallback(callback : TYHumidityValueCallback): LongInt |
| vb | function registerValueCallback() As Integer |
| cs | int registerValueCallback(ValueCallback callback) |
| java | int registerValueCallback(UpdateCallback callback) |
| py | def registerValueCallback(callback) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

humidity→set_highestValue()
humidity→setHighestValue()
humidity.set_highestValue()**YHumidity**

Changes the recorded maximal value observed for the humidity.

```
js function set_highestValue( newval)
nodejs function set_highestValue( newval)
php function set_highestValue( $newval)
cpp int set_highestValue( double newval)
m -(int) setHighestValue : (double) newval
pas function set_highestValue( newval: double): integer
vb function set_highestValue( ByVal newval As Double) As Integer
cs int set_highestValue( double newval)
java int set_highestValue( double newval)
py def set_highestValue( newval)
cmd YHumidity target set_highestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed for the humidity

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

humidity→set_logFrequency()
humidity→setLogFrequency()
humidity.set_logFrequency()

YHumidity

Changes the datalogger recording frequency for this function.

| | |
|---------|--|
| js | function set_logFrequency(newval) |
| node.js | function set_logFrequency(newval) |
| php | function set_logFrequency(\$newval) |
| cpp | int set_logFrequency(const string& newval) |
| m | -(int) setLogFrequency : (NSString*) newval |
| pas | function set_logFrequency(newval: string): integer |
| vb | function set_logFrequency(ByVal newval As String) As Integer |
| cs | int set_logFrequency(string newval) |
| java | int set_logFrequency(String newval) |
| py | def set_logFrequency(newval) |
| cmd | YHumidity target set_logFrequency newval |

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

humidity→set_logicalName()
humidity→setLogicalName()
humidity.set_logicalName()**YHumidity**

Changes the logical name of the humidity sensor.

```
js function set_logicalName( newval)
nodejs function set_logicalName( newval)
php function set_logicalName( $newval)
cpp int set_logicalName( const string& newval)
m -(int) setLogicalName : (NSString*) newval
pas function set_logicalName( newval: string): integer
vb function set_logicalName( ByVal newval As String) As Integer
cs int set_logicalName( string newval)
java int set_logicalName( String newval)
py def set_logicalName( newval)
cmd YHumidity target set_logicalName newval
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the humidity sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

humidity→set_lowestValue()
humidity→setLowestValue()
humidity.set_lowestValue()

YHumidity

Changes the recorded minimal value observed for the humidity.

| | |
|---------------------|---|
| <code>js</code> | function set_lowestValue(newval) |
| <code>nodejs</code> | function set_lowestValue(newval) |
| <code>php</code> | function set_lowestValue(\$newval) |
| <code>cpp</code> | int set_lowestValue(double newval) |
| <code>m</code> | - (int) setLowestValue : (double) newval |
| <code>pas</code> | function set_lowestValue(newval: double): integer |
| <code>vb</code> | function set_lowestValue(ByVal newval As Double) As Integer |
| <code>cs</code> | int set_lowestValue(double newval) |
| <code>java</code> | int set_lowestValue(double newval) |
| <code>py</code> | def set_lowestValue(newval) |
| <code>cmd</code> | YHumidity target set_lowestValue newval |

Parameters :

newval a floating point number corresponding to the recorded minimal value observed for the humidity

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

| | |
|---------------------------------------|------------------|
| humidity→set_reportFrequency() | YHumidity |
| humidity→setReportFrequency() | |
| humidity.set_reportFrequency() | |

Changes the timed value notification frequency for this function.

```
js    function set_reportFrequency( newval)
nodejs function set_reportFrequency( newval)
php   function set_reportFrequency( $newval)
cpp   int set_reportFrequency( const string& newval)
m     -(int) setReportFrequency : (NSString*) newval
pas   function set_reportFrequency( newval: string): integer
vb    function set_reportFrequency( ByVal newval As String) As Integer
cs    int set_reportFrequency( string newval)
java  int set_reportFrequency( String newval)
py    def set_reportFrequency( newval)
cmd   YHumidity target set_reportFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

humidity→set_resolution()**YHumidity****humidity→setResolution()humidity.set_resolution()**

Changes the resolution of the measured physical values.

| | |
|--------|--|
| js | function set_resolution(newval) |
| nodejs | function set_resolution(newval) |
| php | function set_resolution(\$newval) |
| cpp | int set_resolution(double newval) |
| m | -(int) setResolution : (double) newval |
| pas | function set_resolution(newval: double): integer |
| vb | function set_resolution(ByVal newval As Double) As Integer |
| cs | int set_resolution(double newval) |
| java | int set_resolution(double newval) |
| py | def set_resolution(newval) |
| cmd | YHumidity target set_resolution newval |

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

humidity→set(userData)**YHumidity****humidity→setUserData()humidity.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

```
js   function setUserData( data)
node.js function setUserData( data)
php  function setUserData( $data)
cpp   void setUserData( void* data)
m    -(void) setUserData : (void*) data
pas   procedure setUserData( data: Tobject)
vb    procedure setUserData( ByVal data As Object)
cs    void setUserData( object data)
java  void setUserData( Object data)
py    def setUserData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

humidity→wait_async()

YHumidity

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context )
nodejs function wait_async( callback, context )
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.21. Led function interface

Yoctopuce application programming interface allows you not only to drive the intensity of the led, but also to have it blink at various preset frequencies.

In order to use the functions described here, you should include:

| | |
|--------|---|
| js | <script type='text/javascript' src='yocto_led.js'></script> |
| nodejs | var yoctolib = require('yoctolib'); |
| | var YLed = yoctolib.YLed; |
| php | require_once('yocto_led.php'); |
| cpp | #include "yocto_led.h" |
| m | #import "yocto_led.h" |
| pas | uses yocto_led; |
| vb | yocto_led.vb |
| cs | yocto_led.cs |
| java | import com.yoctopuce.YoctoAPI.YLed; |
| py | from yocto_led import * |

Global functions

yFindLed(func)

Retrieves a led for a given identifier.

yFirstLed()

Starts the enumeration of leds currently accessible.

YLed methods

led->describe()

Returns a short text that describes unambiguously the instance of the led in the form TYPE (NAME)=SERIAL .FUNCTIONID.

led->get_advertisedValue()

Returns the current value of the led (no more than 6 characters).

led->get_blinking()

Returns the current led signaling mode.

led->get_errorMessage()

Returns the error message of the latest error with the led.

led->get_errorType()

Returns the numerical error code of the latest error with the led.

led->get_friendlyName()

Returns a global identifier of the led in the format MODULE _ NAME . FUNCTION _ NAME.

led->get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

led->get_functionId()

Returns the hardware identifier of the led, without reference to the module.

led->get_hardwareId()

Returns the unique hardware identifier of the led in the form SERIAL .FUNCTIONID.

led->get_logicalName()

Returns the logical name of the led.

led->get_luminosity()

Returns the current led intensity (in per cent).

led->get_module()

Gets the YModule object for the device on which the function is located.

led->get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

led->get_power()

Returns the current led state.

led->get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

led->isOnline()

Checks if the led is currently reachable, without raising any error.

led->isOnline_async(callback, context)

Checks if the led is currently reachable, without raising any error (asynchronous version).

led->load(msValidity)

Preloads the led cache with a specified validity duration.

led->load_async(msValidity, callback, context)

Preloads the led cache with a specified validity duration (asynchronous version).

led->nextLed()

Continues the enumeration of leds started using yFirstLed().

led->registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

led->set_blinking(newval)

Changes the current led signaling mode.

led->set_logicalName(newval)

Changes the logical name of the led.

led->set_luminosity(newval)

Changes the current led intensity (in per cent).

led->set_power(newval)

Changes the state of the led.

led->set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

led->wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YLed.FindLed() yFindLed() YLed.FindLed()

YLed

Retrieves a led for a given identifier.

```
js function yFindLed( func)
node.js function FindLed( func)
php function yFindLed( $func)
cpp YLed* yFindLed( const string& func)
m YLed* yFindLed( NSString* func)
pas function yFindLed( func: string): TYLed
vb function yFindLed( ByVal func As String) As YLed
cs YLed FindLed( string func)
java YLed FindLed( String func)
py def FindLed( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the led is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YLed.isOnline()` to test if the led is indeed online at a given time. In case of ambiguity when looking for a led by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the led

Returns :

a `YLed` object allowing you to drive the led.

YLed.FirstLed()

YLed

yFirstLed()YLed.FirstLed()

Starts the enumeration of leds currently accessible.

```
js function yFirstLed( )
nodejs function FirstLed( )
php function yFirstLed( )
cpp YLed* yFirstLed( )
m YLed* yFirstLed( )
pas function yFirstLed( ): TYLed
vb function yFirstLed( ) As YLed
cs YLed FirstLed( )
java YLed FirstLed( )
py def FirstLed( )
```

Use the method `YLed.nextLed()` to iterate on next leds.

Returns :

a pointer to a `YLed` object, corresponding to the first led currently online, or a `null` pointer if there are none.

led→describe()led.describe()

YLed

Returns a short text that describes unambiguously the instance of the led in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the led (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

led→get_advertisedValue()**YLed****led→advertisedValue()led.get_advertisedValue()**

Returns the current value of the led (no more than 6 characters).

| | |
|--------|--|
| js | function get_advertisedValue() |
| nodejs | function get_advertisedValue() |
| php | function get_advertisedValue() |
| cpp | string get_advertisedValue() |
| m | -(NSString*) advertisedValue |
| pas | function get_advertisedValue() : string |
| vb | function get_advertisedValue() As String |
| cs | string get_advertisedValue() |
| java | String get_advertisedValue() |
| py | def get_advertisedValue() |
| cmd | YLed target get_advertisedValue |

Returns :

a string corresponding to the current value of the led (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

led->get_blinking()
led->blinking()led.get_blinking()

YLed

Returns the current led signaling mode.

| | |
|---------|--|
| js | function get_blinking() |
| node.js | function get_blinking() |
| php | function get_blinking() |
| cpp | Y_BLINKING_enum get_blinking() |
| m | -(Y_BLINKING_enum) blinking |
| pas | function get_blinking() : Integer |
| vb | function get_blinking() As Integer |
| cs | int get_blinking() |
| java | int get_blinking() |
| py | def get_blinking() |
| cmd | YLed target get_blinking |

Returns :

a value among Y_BLINKING_STILL, Y_BLINKING_RELAX, Y_BLINKING_AWARE, Y_BLINKING_RUN, Y_BLINKING_CALL and Y_BLINKING_PANIC corresponding to the current led signaling mode

On failure, throws an exception or returns Y_BLINKING_INVALID.

led→get_errorMessage()

YLed

led→errorMessage()led.get_errorMessage()

Returns the error message of the latest error with the led.

| | |
|--------|---|
| js | function get_errorMessage() |
| nodejs | function get_errorMessage() |
| php | function get_errorMessage() |
| cpp | string get_errorMessage() |
| m | -(NSString*) errorMessage |
| pas | function get_errorMessage(): string |
| vb | function get_errorMessage() As String |
| cs | string get_errorMessage() |
| java | String get_errorMessage() |
| py | def get_errorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the led object

led->get_errorType()

YLed

led->errorType()led.get_errorType()

Returns the numerical error code of the latest error with the led.

```
js   function get_errorType( )  
node.js function get_errorType( )  
php  function get_errorType( )  
cpp   YRETCODE get_errorType( )  
pas   function get_errorType( ): YRETCODE  
vb    function get_errorType( ) As YRETCODE  
cs    YRETCODE get_errorType( )  
java  int get_errorType( )  
py    def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the led object

led→get_friendlyName()**YLed****led→friendlyName()led.get_friendlyName()**

Returns a global identifier of the led in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|-------------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the led if they are defined, otherwise the serial number of the module and the hardware identifier of the led (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the led using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

led->get_functionDescriptor()
led->functionDescriptor()
led.get_functionDescriptor()

YLed

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|---|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

led→get_functionId()**YLed****led→functionId()led.get_functionId()**

Returns the hardware identifier of the led, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the led (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

led→get_hardwareId()

YLed

led→hardwareId()led.get_hardwareId()

Returns the unique hardware identifier of the led in the form SERIAL.FUNCTIONID.

```
js function get_hardwareId( )  
node.js function get_hardwareId( )  
php function get_hardwareId( )  
cpp string get_hardwareId( )  
m -(NSString*) hardwareId  
vb function get_hardwareId( ) As String  
cs string get_hardwareId( )  
java String get_hardwareId( )  
py def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the led. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the led (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

led→get_logicalName()**YLed****led→logicalName()led.get_logicalName()**

Returns the logical name of the led.

```
js function get_logicalName( )  
nodejs function get_logicalName( )  
php function get_logicalName( )  
cpp string get_logicalName( )  
m -(NSString*) logicalName  
pas function get_logicalName( ): string  
vb function get_logicalName( ) As String  
cs string get_logicalName( )  
java String get_logicalName( )  
py def get_logicalName( )  
cmd YLed target get_logicalName
```

Returns :

a string corresponding to the logical name of the led. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

led→get_luminosity() led→luminosity()led.get_luminosity()

YLed

Returns the current led intensity (in per cent).

```
js function get_luminosity( )
node.js function get_luminosity( )
php function get_luminosity( )
cpp int get_luminosity( )
m -(int) luminosity
pas function get_luminosity( ): LongInt
vb function get_luminosity( ) As Integer
cs int get_luminosity( )
java int get_luminosity( )
py def get_luminosity( )
cmd YLed target get_luminosity
```

Returns :

an integer corresponding to the current led intensity (in per cent)

On failure, throws an exception or returns Y_LUMINOSITY_INVALID.

led->get_module()**YLed****led->module()led.get_module()**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

led→get_module_async() led→module_async()

YLed

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js   function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

led->get_power()**YLed****led->power()led.get_power()**

Returns the current led state.

| | |
|--------|---|
| js | function get_power() |
| nodejs | function get_power() |
| php | function get_power() |
| cpp | Y_POWER_enum get_power() |
| m | -(Y_POWER_enum) power |
| pas | function get_power() : Integer |
| vb | function get_power() As Integer |
| cs | int get_power() |
| java | int get_power() |
| py | def get_power() |
| cmd | YLed target get_power |

Returns :

either Y_POWER_OFF or Y_POWER_ON, according to the current led state

On failure, throws an exception or returns Y_POWER_INVALID.

led→get(userData)

YLed

led→userData()led.get(userData())

Returns the value of the userData attribute, as previously stored using method set(userData).

```
js function get(userData) 
node.js function get(userData) 
php function get(userData) 
cpp void * get(userData) 
m -(void*) userData 
pas function get(userData): Tobject 
vb function get(userData) As Object 
cs object get(userData) 
java Object get(userData) 
py def get(userData)
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

led→isOnline()|led.isOnline()**YLed**

Checks if the led is currently reachable, without raising any error.

| | |
|---------|---|
| js | function isOnline () |
| node.js | function isOnline () |
| php | function isOnline () |
| cpp | bool isOnline () |
| m | -(BOOL) isOnline |
| pas | function isOnline (): boolean |
| vb | function isOnline () As Boolean |
| cs | bool isOnline () |
| java | boolean isOnline () |
| py | def isOnline () |

If there is a cached value for the led in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the led.

Returns :

`true` if the led can be reached, and `false` otherwise

led→isOnline_async()

YLed

Checks if the led is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context )
nodejs function isOnline_async( callback, context )
```

If there is a cached value for the led in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

led→load()led.load()

YLed

Preloads the led cache with a specified validity duration.

```
js function load( msValidity)
nodejs function load( msValidity)
php function load( $msValidity)
cpp YRETCODE load( int msValidity)
m -(YRETCODE) load : (int) msValidity
pas function load( msValidity: integer): YRETCODE
vb function load( ByVal msValidity As Integer) As YRETCODE
cs YRETCODE load( int msValidity)
java int load( long msValidity)
py def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

led→load_async()

YLed

Preloads the led cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

led->nextLed()|led.nextLed()**YLed**

Continues the enumeration of leds started using `yFirstLed()`.

| | |
|---------------------|--|
| <code>js</code> | <code>function nextLed()</code> |
| <code>nodejs</code> | <code>function nextLed()</code> |
| <code>php</code> | <code>function nextLed()</code> |
| <code>cpp</code> | <code>YLed * nextLed()</code> |
| <code>m</code> | <code>-(YLed*) nextLed</code> |
| <code>pas</code> | <code>function nextLed(): TYLed</code> |
| <code>vb</code> | <code>function nextLed() As YLed</code> |
| <code>cs</code> | <code>YLed nextLed()</code> |
| <code>java</code> | <code>YLed nextLed()</code> |
| <code>py</code> | <code>def nextLed()</code> |

Returns :

a pointer to a `YLed` object, corresponding to a led currently online, or a `null` pointer if there are no more leds to enumerate.

led→registerValueCallback() led.registerValueCallback()

YLed

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YLedValueCallback callback )
m    -(int) registerValueCallback : (YLedValueCallback) callback
pas   function registerValueCallback( callback: TYLedValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

led->set_blinking() led->setBlinking()led.set_blinking()

YLed

Changes the current led signaling mode.

| | |
|---------------------|---|
| <code>js</code> | <code>function set_blinking(newval)</code> |
| <code>nodejs</code> | <code>function set_blinking(newval)</code> |
| <code>php</code> | <code>function set_blinking(\$newval)</code> |
| <code>cpp</code> | <code>int set_blinking(Y_BLINKING_enum newval)</code> |
| <code>m</code> | <code>-(int) setBlinking : (Y_BLINKING_enum) newval</code> |
| <code>pas</code> | <code>function set_blinking(newval: Integer): integer</code> |
| <code>vb</code> | <code>function set_blinking(ByVal newval As Integer) As Integer</code> |
| <code>cs</code> | <code>int set_blinking(int newval)</code> |
| <code>java</code> | <code>int set_blinking(int newval)</code> |
| <code>py</code> | <code>def set_blinking(newval)</code> |
| <code>cmd</code> | <code>YLed target set_blinking newval</code> |

Parameters :

newval a value among Y_BLINKING_STILL, Y_BLINKING_RELAX, Y_BLINKING_AWARE, Y_BLINKING_RUN, Y_BLINKING_CALL and Y_BLINKING_PANIC corresponding to the current led signaling mode

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

led->set_logicalName()
led->setLogicalName()led.set_logicalName()

YLed

Changes the logical name of the led.

```
js function set_logicalName( newval)
node.js function set_logicalName( newval)
php function set_logicalName( $newval)
cpp int set_logicalName( const string& newval)
m -(int) setLogicalName : (NSString*) newval
pas function set_logicalName( newval: string): integer
vb function set_logicalName( ByVal newval As String) As Integer
cs int set_logicalName( string newval)
java int set_logicalName( String newval)
py def set_logicalName( newval)
cmd YLed target set_logicalName newval
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the led.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

led->set_luminosity()

YLed

led->setLuminosity()|led.set_luminosity()

Changes the current led intensity (in per cent).

| | |
|--------|---|
| js | function set_luminosity(newval) |
| nodejs | function set_luminosity(newval) |
| php | function set_luminosity(\$newval) |
| cpp | int set_luminosity(int newval) |
| m | -(int) setLuminosity : (int) newval |
| pas | function set_luminosity(newval: LongInt): integer |
| vb | function set_luminosity(ByVal newval As Integer) As Integer |
| cs | int set_luminosity(int newval) |
| java | int set_luminosity(int newval) |
| py | def set_luminosity(newval) |
| cmd | YLed target set_luminosity newval |

Parameters :

newval an integer corresponding to the current led intensity (in per cent)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

led->set_power()
led->setPower()led.set_power()

YLed

Changes the state of the led.

```
js function set_power( newval)
node.js function set_power( newval)
php function set_power( $newval)
cpp int set_power( Y_POWER_enum newval)
m -(int) setPower : (Y_POWER_enum) newval
pas function set_power( newval: Integer): integer
vb function set_power( ByVal newval As Integer) As Integer
cs int set_power( int newval)
java int set_power( int newval)
py def set_power( newval)
cmd YLed target set_power newval
```

Parameters :

newval either Y_POWER_OFF or Y_POWER_ON, according to the state of the led

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

led→set(userData)**YLed****led→setUserData()|led.set(userData())**

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|---|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData \$data) |
| cpp | void set(userData void* data) |
| m | -(void) setUserData : (void*) data |
| pas | procedure set(userData data: Tobject) |
| vb | procedure set(userData ByVal data As Object) |
| cs | void set(userData object data) |
| java | void set(userData Object data) |
| py | def set(userData data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

led→wait_async()

YLed

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.22. LightSensor function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

| | |
|---------|---|
| js | <script type='text/javascript' src='yocto_lightsensor.js'></script> |
| node.js | var yoctolib = require('yoctolib'); |
| php | var YLightSensor = yoctolib.YLightSensor; |
| cpp | require_once('yocto_lightsensor.php'); |
| m | #include "yocto_lightsensor.h" |
| pas | #import "yocto_lightsensor.h" |
| vb | uses yocto_lightsensor; |
| cs | yocto_lightsensor.vb |
| java | yocto_lightsensor.cs |
| py | import com.yoctopuce.YoctoAPI.YLightSensor; |
| | from yocto_lightsensor import * |

Global functions

yFindLightSensor(func)

Retrieves a light sensor for a given identifier.

yFirstLightSensor()

Starts the enumeration of light sensors currently accessible.

YLightSensor methods

lightsensor→calibrate(calibratedVal)

Changes the sensor-specific calibration parameter so that the current value matches a desired target (linear scaling).

lightsensor→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

lightsensor→describe()

Returns a short text that describes unambiguously the instance of the light sensor in the form TYPE (NAME) = SERIAL.FUNCTIONID.

lightsensor→get_advertisedValue()

Returns the current value of the light sensor (no more than 6 characters).

lightsensor→get_currentRawValue()

Returns the unrounded and uncalibrated raw value returned by the sensor.

lightsensor→get_currentValue()

Returns the current measure for the ambient light.

lightsensor→get_errorMessage()

Returns the error message of the latest error with the light sensor.

lightsensor→get_errorType()

Returns the numerical error code of the latest error with the light sensor.

lightsensor→get_friendlyName()

Returns a global identifier of the light sensor in the format MODULE_NAME . FUNCTION_NAME.

lightsensor→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

lightsensor→get_functionId()

| |
|--|
| Returns the hardware identifier of the light sensor, without reference to the module. |
| lightsensor→get_hardwareId() |
| Returns the unique hardware identifier of the light sensor in the form SERIAL.FUNCTIONID. |
| lightsensor→get_highestValue() |
| Returns the maximal value observed for the ambient light. |
| lightsensor→get_logFrequency() |
| Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory. |
| lightsensor→get_logicalName() |
| Returns the logical name of the light sensor. |
| lightsensor→get_lowestValue() |
| Returns the minimal value observed for the ambient light. |
| lightsensor→get_module() |
| Gets the YModule object for the device on which the function is located. |
| lightsensor→get_module_async(callback, context) |
| Gets the YModule object for the device on which the function is located (asynchronous version). |
| lightsensor→get_recordedData(startTime, endTime) |
| Retrieves a DataSet object holding historical data for this sensor, for a specified time interval. |
| lightsensor→get_reportFrequency() |
| Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function. |
| lightsensor→get_resolution() |
| Returns the resolution of the measured values. |
| lightsensor→get_unit() |
| Returns the measuring unit for the ambient light. |
| lightsensor→get(userData) |
| Returns the value of the userData attribute, as previously stored using method set(userData). |
| lightsensor→isOnline() |
| Checks if the light sensor is currently reachable, without raising any error. |
| lightsensor→isOnline_async(callback, context) |
| Checks if the light sensor is currently reachable, without raising any error (asynchronous version). |
| lightsensor→load(msValidity) |
| Preloads the light sensor cache with a specified validity duration. |
| lightsensor→loadCalibrationPoints(rawValues, refValues) |
| Retrieves error correction data points previously entered using the method calibrateFromPoints. |
| lightsensor→load_async(msValidity, callback, context) |
| Preloads the light sensor cache with a specified validity duration (asynchronous version). |
| lightsensor→nextLightSensor() |
| Continues the enumeration of light sensors started using yFirstLightSensor(). |
| lightsensor→registerTimedReportCallback(callback) |
| Registers the callback function that is invoked on every periodic timed notification. |
| lightsensor→registerValueCallback(callback) |
| Registers the callback function that is invoked on every change of advertised value. |
| lightsensor→set_highestValue(newval) |
| Changes the recorded maximal value observed for the ambient light. |
| lightsensor→set_logFrequency(newval) |

Changes the datalogger recording frequency for this function.

lightsensor→set_logicalName(newval)

Changes the logical name of the light sensor.

lightsensor→set_lowestValue(newval)

Changes the recorded minimal value observed for the ambient light.

lightsensor→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

lightsensor→set_resolution(newval)

Changes the resolution of the measured physical values.

lightsensor→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

lightsensor→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YLightSensor.FindLightSensor() yFindLightSensor()YLightSensor.FindLightSensor()

YLightSensor

Retrieves a light sensor for a given identifier.

| | |
|----------------|---|
| js | <code>function yFindLightSensor(func)</code> |
| node.js | <code>function FindLightSensor(func)</code> |
| php | <code>function yFindLightSensor(\$func)</code> |
| cpp | <code>YLightSensor* yFindLightSensor(const string& func)</code> |
| m | <code>YLightSensor* yFindLightSensor(NSString* func)</code> |
| pas | <code>function yFindLightSensor(func: string): TYLightSensor</code> |
| vb | <code>function yFindLightSensor(ByVal func As String) As YLightSensor</code> |
| cs | <code>YLightSensor FindLightSensor(string func)</code> |
| java | <code>YLightSensor FindLightSensor(String func)</code> |
| py | <code>def FindLightSensor(func)</code> |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the light sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YLightSensor.isOnline()` to test if the light sensor is indeed online at a given time. In case of ambiguity when looking for a light sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the light sensor

Returns :

a `YLightSensor` object allowing you to drive the light sensor.

YLightSensor.FirstLightSensor()**YLightSensor****yFirstLightSensor()YLightSensor.FirstLightSensor()**

Starts the enumeration of light sensors currently accessible.

| | |
|--------|--|
| js | function yFirstLightSensor() |
| nodejs | function FirstLightSensor() |
| php | function yFirstLightSensor() |
| cpp | YLightSensor* yFirstLightSensor() |
| m | YLightSensor* yFirstLightSensor() |
| pas | function yFirstLightSensor(): TYLightSensor |
| vb | function yFirstLightSensor() As YLightSensor |
| cs | YLightSensor FirstLightSensor() |
| java | YLightSensor FirstLightSensor() |
| py | def FirstLightSensor() |

Use the method `YLightSensor.nextLightSensor()` to iterate on next light sensors.

Returns :

a pointer to a `YLightSensor` object, corresponding to the first light sensor currently online, or a `null` pointer if there are none.

lightsensor→calibrate(lightsensor.calibrate())**YLightSensor**

Changes the sensor-specific calibration parameter so that the current value matches a desired target (linear scaling).

| | |
|--------|---|
| js | function calibrate(calibratedVal) |
| nodejs | function calibrate(calibratedVal) |
| php | function calibrate(\$calibratedVal) |
| cpp | int calibrate(double calibratedVal) |
| m | -(int) calibrate : (double) calibratedVal |
| pas | function calibrate(calibratedVal: double): integer |
| vb | function calibrate(ByVal calibratedVal As Double) As Integer |
| cs | int calibrate(double calibratedVal) |
| java | int calibrate(double calibratedVal) |
| py | def calibrate(calibratedVal) |
| cmd | YLightSensor target calibrate calibratedVal |

Parameters :

calibratedVal the desired target value.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→calibrateFromPoints() lightsensor.calibrateFromPoints()

YLightSensor

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```

js   function calibrateFromPoints( rawValues, refValues)
nodejs function calibrateFromPoints( rawValues, refValues)
php  function calibrateFromPoints( $rawValues, $refValues)
cpp   int calibrateFromPoints( vector<double> rawValues,
                             vector<double> refValues)

m    -(int) calibrateFromPoints : (NSMutableArray*) rawValues
                  : (NSMutableArray*) refValues

pas  function calibrateFromPoints( rawValues: TDoubleArray,
                                 refValues: TDoubleArray): LongInt

vb   procedure calibrateFromPoints( )

cs   int calibrateFromPoints( List<double> rawValues,
                           List<double> refValues)

java int calibrateFromPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def calibrateFromPoints( rawValues, refValues)

cmd  YLightSensor target calibrateFromPoints rawValues refValues

```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.
refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→describe()lightsensor.describe()**YLightSensor**

Returns a short text that describes unambiguously the instance of the light sensor in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the light sensor (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

lightsensor→get_advertisedValue()
lightsensor→advertisedValue()
lightsensor.get_advertisedValue()**YLightSensor**

Returns the current value of the light sensor (no more than 6 characters).

| | |
|----------------------|--|
| <code>js</code> | <code>function get_advertisedValue()</code> |
| <code>node.js</code> | <code>function get_advertisedValue()</code> |
| <code>php</code> | <code>function get_advertisedValue()</code> |
| <code>cpp</code> | <code>string get_advertisedValue()</code> |
| <code>m</code> | <code>-(NSString*) advertisedValue</code> |
| <code>pas</code> | <code>function get_advertisedValue(): string</code> |
| <code>vb</code> | <code>function get_advertisedValue() As String</code> |
| <code>cs</code> | <code>string get_advertisedValue()</code> |
| <code>java</code> | <code>String get_advertisedValue()</code> |
| <code>py</code> | <code>def get_advertisedValue()</code> |
| <code>cmd</code> | <code>YLightSensor target get_advertisedValue</code> |

Returns :

a string corresponding to the current value of the light sensor (no more than 6 characters). On failure, throws an exception or returns `Y_ADVERTISEDVALUE_INVALID`.

lightsensor→get_currentRawValue()
lightsensor→currentRawValue()
lightsensor.get_currentRawValue()**YLightSensor**

Returns the unrounded and uncalibrated raw value returned by the sensor.

js function **get_currentRawValue()**
nodejs function **get_currentRawValue()**
php function **get_currentRawValue()**
cpp double **get_currentRawValue()**
m -(double) currentRawValue
pas function **get_currentRawValue()**: double
vb function **get_currentRawValue()** As Double
cs double **get_currentRawValue()**
java double **get_currentRawValue()**
py def **get_currentRawValue()**
cmd YLightSensor target **get_currentRawValue**

Returns :

a floating point number corresponding to the unrounded and uncalibrated raw value returned by the sensor

On failure, throws an exception or returns **Y_CURRENTRAWVALUE_INVALID**.

lightsensor→get_currentValue()
lightsensor→currentValue()
lightsensor.get_currentValue()

YLightSensor

Returns the current measure for the ambient light.

| | |
|---------------|---|
| js | function get_currentValue() |
| nodejs | function get_currentValue() |
| php | function get_currentValue() |
| cpp | double get_currentValue() |
| m | -(double) currentValue |
| pas | function get_currentValue() : double |
| vb | function get_currentValue() As Double |
| cs | double get_currentValue() |
| java | double get_currentValue() |
| py | def get_currentValue() |
| cmd | YLightSensor target get_currentValue |

Returns :

a floating point number corresponding to the current measure for the ambient light

On failure, throws an exception or returns **Y_CURRENTVALUE_INVALID**.

lightsensor→get_errorMessage()
lightsensor→errorMessage()
lightsensor.get_errorMessage()**YLightSensor**

Returns the error message of the latest error with the light sensor.

| | |
|--------|--|
| js | function get_errorMessage() |
| nodejs | function get_errorMessage() |
| php | function get_errorMessage() |
| cpp | string get_errorMessage() |
| m | -(NSString*) errorMessage |
| pas | function get_errorMessage(): string |
| vb | function get_errorMessage() As String |
| cs | string get_errorMessage() |
| java | String get_errorMessage() |
| py | def get_errorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the light sensor object

lightsensor→get_errorType()**YLightSensor****lightsensor→errorType()lightsensor.get_errorType()**

Returns the numerical error code of the latest error with the light sensor.

| | |
|--------|--|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType() : YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the light sensor object

lightsensor→get_friendlyName()
lightsensor→friendlyName()
lightsensor.get_friendlyName()

YLightSensor

Returns a global identifier of the light sensor in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the light sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the light sensor (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the light sensor using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

lightsensor→get_functionDescriptor()
lightsensor→functionDescriptor()
lightsensor.get_functionDescriptor()**YLightSensor**

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

lightsensor→get_functionId()**YLightSensor****lightsensor→functionId()lightsensor.get_functionId()**

Returns the hardware identifier of the light sensor, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | - (NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the light sensor (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

lightsensor→get_hardwareId()
lightsensor→hardwareId()
lightsensor.get_hardwareId()**YLightSensor**

Returns the unique hardware identifier of the light sensor in the form SERIAL.FUNCTIONID.

| | |
|---------|---|
| js | function get_hardwareId() |
| node.js | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the light sensor. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the light sensor (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

lightsensor→get_highestValue()
lightsensor→highestValue()
lightsensor.get_highestValue()

YLightSensor

Returns the maximal value observed for the ambient light.

```
js function get_highestValue( )  
nodejs function get_highestValue( )  
php function get_highestValue( )  
cpp double get_highestValue( )  
m -(double) highestValue  
pas function get_highestValue( ): double  
vb function get_highestValue( ) As Double  
cs double get_highestValue( )  
java double get_highestValue( )  
py def get_highestValue( )  
cmd YLightSensor target get_highestValue
```

Returns :

a floating point number corresponding to the maximal value observed for the ambient light

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

lightsensor→get_logFrequency()
lightsensor→logFrequency()
lightsensor.get_logFrequency()**YLightSensor**

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

| | |
|--------|---|
| js | function get_logFrequency() |
| nodejs | function get_logFrequency() |
| php | function get_logFrequency() |
| cpp | string get_logFrequency() |
| m | -(NSString*) logFrequency |
| pas | function get_logFrequency() : string |
| vb | function get_logFrequency() As String |
| cs | string get_logFrequency() |
| java | String get_logFrequency() |
| py | def get_logFrequency() |
| cmd | YLightSensor target get_logFrequency |

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns **Y_LOGFREQUENCY_INVALID**.

lightsensor→get_logicalName()
lightsensor→logicalName()
lightsensor.get_logicalName()

YLightSensor

Returns the logical name of the light sensor.

```
js function get_logicalName( )
nodejs function get_logicalName( )
php function get_logicalName( )
cpp string get_logicalName( )
m -(NSString*) logicalName
pas function get_logicalName( ): string
vb function get_logicalName( ) As String
cs string get_logicalName( )
java String get_logicalName( )
py def get_logicalName( )
cmd YLightSensor target get_logicalName
```

Returns :

a string corresponding to the logical name of the light sensor. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

lightsensor→get_lowestValue()
lightsensor→lowestValue()
lightsensor.get_lowestValue()

YLightSensor

Returns the minimal value observed for the ambient light.

| | |
|---------|--|
| js | function get_lowestValue() |
| node.js | function get_lowestValue() |
| php | function get_lowestValue() |
| cpp | double get_lowestValue() |
| m | -(double) lowestValue |
| pas | function get_lowestValue(): double |
| vb | function get_lowestValue() As Double |
| cs | double get_lowestValue() |
| java | double get_lowestValue() |
| py | def get_lowestValue() |
| cmd | YLightSensor target get_lowestValue |

Returns :

a floating point number corresponding to the minimal value observed for the ambient light

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

lightsensor→get_module()**YLightSensor****lightsensor→module()lightsensor.get_module()**

Gets the `YModule` object for the device on which the function is located.

| | |
|---------|---|
| js | function get_module() |
| node.js | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | - (YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

lightsensor→get_module_async()**YLightSensor****lightsensor→module_async()**

Gets the YModule object for the device on which the function is located (asynchronous version).

```
js   function get_module_async( callback, context)
nodejs function get_module_async( callback, context)
```

If the function cannot be located on any module, the returned YModule object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested YModule object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

`lightsensor→get_recordedData()`
`lightsensor→recordedData()`
`lightsensor.get_recordedData()`

YLightSensor

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the `DataSet` class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measurement, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of `YDataSet`, providing access to historical data. Past measures can be loaded progressively using methods from the `YDataSet` object.

lightsensor→get_reportFrequency()
lightsensor→reportFrequency()
lightsensor.get_reportFrequency()**YLightSensor**

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
js   function get_reportFrequency( )  
nodejs function get_reportFrequency( )  
php  function get_reportFrequency( )  
cpp   string get_reportFrequency( )  
m    -(NSString*) reportFrequency  
pas   function get_reportFrequency( ): string  
vb    function get_reportFrequency( ) As String  
cs    string get_reportFrequency( )  
java  String get_reportFrequency( )  
py    def get_reportFrequency( )  
cmd   YLightSensor target get_reportFrequency
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns `Y_REPORTFREQUENCY_INVALID`.

lightsensor→get_resolution()**YLightSensor****lightsensor→resolution()lightsensor.get_resolution()**

Returns the resolution of the measured values.

```
js function get_resolution( )
node.js function get_resolution( )
php function get_resolution( )
cpp double get_resolution( )
m -(double) resolution
pas function get_resolution( ): double
vb function get_resolution( ) As Double
cs double get_resolution( )
java double get_resolution( )
py def get_resolution( )
cmd YLightSensor target get_resolution
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

lightsensor→get_unit()**YLightSensor****lightsensor→unit()lightsensor.get_unit()**

Returns the measuring unit for the ambient light.

| | |
|--------|---------------------------------------|
| js | function get_unit() |
| nodejs | function get_unit() |
| php | function get_unit() |
| cpp | string get_unit() |
| m | -(NSString*) unit |
| pas | function get_unit() : string |
| vb | function get_unit() As String |
| cs | string get_unit() |
| java | String get_unit() |
| py | def get_unit() |
| cmd | YLightSensor target get_unit |

Returns :

a string corresponding to the measuring unit for the ambient light

On failure, throws an exception or returns Y_UNIT_INVALID.

lightsensor→get(userData)**YLightSensor****lightsensor→userData()lightsensor.get(userData)**

Returns the value of the userData attribute, as previously stored using method set(userData).

```
js function get(userData) 
node.js function get(userData) 
php function get(userData) 
cpp void * get(userData) 
m -(void*) userData 
pas function get(userData): Tobject 
vb function get(userData) As Object 
cs object get(userData) 
java Object get(userData) 
py def get(userData)
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

lightsensor→isOnline()lightsensor.isOnline()**YLightSensor**

Checks if the light sensor is currently reachable, without raising any error.

| | |
|---------|---|
| js | function isOnline () |
| node.js | function isOnline () |
| php | function isOnline () |
| cpp | bool isOnline () |
| m | -(BOOL) isOnline |
| pas | function isOnline (): boolean |
| vb | function isOnline () As Boolean |
| cs | bool isOnline () |
| java | boolean isOnline () |
| py | def isOnline () |

If there is a cached value for the light sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the light sensor.

Returns :

true if the light sensor can be reached, and false otherwise

lightsensor→isOnline_async()

YLightSensor

Checks if the light sensor is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context )
nodejs function isOnline_async( callback, context )
```

If there is a cached value for the light sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

lightsensor→load()lightsensor.load()**YLightSensor**

Preloads the light sensor cache with a specified validity duration.

| | |
|----------------|--|
| js | <code>function load(msValidity)</code> |
| node.js | <code>function load(msValidity)</code> |
| php | <code>function load(\$msValidity)</code> |
| cpp | <code>YRETCODE load(int msValidity)</code> |
| m | <code>-(YRETCODE) load : (int) msValidity</code> |
| pas | <code>function load(msValidity: integer): YRETCODE</code> |
| vb | <code>function load(ByVal msValidity As Integer) As YRETCODE</code> |
| cs | <code>YRETCODE load(int msValidity)</code> |
| java | <code>int load(long msValidity)</code> |
| py | <code>def load(msValidity)</code> |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

lightsensor→loadCalibrationPoints()

YLightSensor

Retrieves error correction data points previously entered using the method `calibrateFromPoints`.

```

js   function loadCalibrationPoints( rawValues, refValues)
nodejs function loadCalibrationPoints( rawValues, refValues)
php   function loadCalibrationPoints( &$rawValues, &$refValues)
cpp   int loadCalibrationPoints( vector<double>& rawValues,
                                vector<double>& refValues)
m    -(int) loadCalibrationPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues
pas  function loadCalibrationPoints( var rawValues: TDoubleArray,
                           var refValues: TDoubleArray): LongInt
vb   procedure loadCalibrationPoints( )
cs   int loadCalibrationPoints( List<double> rawValues,
                           List<double> refValues)
java int loadCalibrationPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)
py   def loadCalibrationPoints( rawValues, refValues)
cmd  YLightSensor target loadCalibrationPoints rawValues refValues

```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→load_async()

YLightSensor

Preloads the light sensor cache with a specified validity duration (asynchronous version).

```
js   function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

lightsensor→nextLightSensor()
lightsensor.nextLightSensor()**YLightSensor**

Continues the enumeration of light sensors started using `yFirstLightSensor()`.

`js` **function nextLightSensor()**
`node.js` **function nextLightSensor()**
`php` **function nextLightSensor()**
`cpp` **YLightSensor * nextLightSensor()**
`m` **-(YLightSensor*) nextLightSensor**
`pas` **function nextLightSensor(): TYLightSensor**
`vb` **function nextLightSensor() As YLightSensor**
`cs` **YLightSensor nextLightSensor()**
`java` **YLightSensor nextLightSensor()**
`py` **def nextLightSensor()**

Returns :

a pointer to a `YLightSensor` object, corresponding to a light sensor currently online, or a null pointer if there are no more light sensors to enumerate.

lightsensor→registerTimedReportCallback() lightsensor.registerTimedReportCallback()

YLightSensor

Registers the callback function that is invoked on every periodic timed notification.

| | |
|----------------------|---|
| <code>js</code> | <code>function registerTimedReportCallback(callback)</code> |
| <code>node.js</code> | <code>function registerTimedReportCallback(callback)</code> |
| <code>php</code> | <code>function registerTimedReportCallback(\$callback)</code> |
| <code>cpp</code> | <code>int registerTimedReportCallback(YLightSensorTimedReportCallback callback)</code> |
| <code>m</code> | <code>-(int) registerTimedReportCallback : (YLightSensorTimedReportCallback) callback</code> |
| <code>pas</code> | <code>function registerTimedReportCallback(callback: TYLightSensorTimedReportCallback): LongInt</code> |
| <code>vb</code> | <code>function registerTimedReportCallback() As Integer</code> |
| <code>cs</code> | <code>int registerTimedReportCallback(TimedReportCallback callback)</code> |
| <code>java</code> | <code>int registerTimedReportCallback(TimedReportCallback callback)</code> |
| <code>py</code> | <code>def registerTimedReportCallback(callback)</code> |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

lightsensor→registerValueCallback() lightsensor.registerValueCallback()

YLightSensor

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YLightSensorValueCallback callback )
m    -(int) registerValueCallback : (YLightSensorValueCallback) callback
pas   function registerValueCallback( callback: TYLightSensorValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

lightsensor→set_highestValue()
lightsensor→setHighestValue()
lightsensor.set_highestValue()**YLightSensor**

Changes the recorded maximal value observed for the ambiant light.

| | |
|--------|--|
| js | function set_highestValue(newval) |
| nodejs | function set_highestValue(newval) |
| php | function set_highestValue(\$newval) |
| cpp | int set_highestValue(double newval) |
| m | -(int) setHighestValue : (double) newval |
| pas | function set_highestValue(newval: double): integer |
| vb | function set_highestValue(ByVal newval As Double) As Integer |
| cs | int set_highestValue(double newval) |
| java | int set_highestValue(double newval) |
| py | def set_highestValue(newval) |
| cmd | YLightSensor target set_highestValue newval |

Parameters :

newval a floating point number corresponding to the recorded maximal value observed for the ambiant light

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→set_logFrequency()
lightsensor→setLogFrequency()
lightsensor.set_logFrequency()

YLightSensor

Changes the datalogger recording frequency for this function.

```
js   function set_logFrequency( newval)
nodejs function set_logFrequency( newval)
php  function set_logFrequency( $newval)
cpp   int set_logFrequency( const string& newval)
m    -(int) setLogFrequency : (NSString*) newval
pas   function set_logFrequency( newval: string): integer
vb    function set_logFrequency( ByVal newval As String) As Integer
cs    int set_logFrequency( string newval)
java  int set_logFrequency( String newval)
py    def set_logFrequency( newval)
cmd   YLightSensor target set_logFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→set_logicalName()
lightsensor→setLogicalName()
lightsensor.set_logicalName()

YLightSensor

Changes the logical name of the light sensor.

| | |
|---------------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YLightSensor target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the light sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

lightsensor→set_lowestValue()
lightsensor→setLowestValue()
lightsensor.set_lowestValue()

YLightSensor

Changes the recorded minimal value observed for the ambient light.

```
js function set_lowestValue( newval)
nodejs function set_lowestValue( newval)
php function set_lowestValue( $newval)
cpp int set_lowestValue( double newval)
m -(int) setLowestValue : (double) newval
pas function set_lowestValue( newval: double): integer
vb function set_lowestValue( ByVal newval As Double) As Integer
cs int set_lowestValue( double newval)
java int set_lowestValue( double newval)
py def set_lowestValue( newval)
cmd YLightSensor target set_lowestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed for the ambient light

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→set_reportFrequency()
lightsensor→setReportFrequency()
lightsensor.set_reportFrequency()

YLightSensor

Changes the timed value notification frequency for this function.

| | |
|--------|---|
| js | function set_reportFrequency(newval) |
| nodejs | function set_reportFrequency(newval) |
| php | function set_reportFrequency(\$newval) |
| cpp | int set_reportFrequency(const string& newval) |
| m | -(int) setReportFrequency : (NSString*) newval |
| pas | function set_reportFrequency(newval: string): integer |
| vb | function set_reportFrequency(ByVal newval As String) As Integer |
| cs | int set_reportFrequency(string newval) |
| java | int set_reportFrequency(String newval) |
| py | def set_reportFrequency(newval) |
| cmd | YLightSensor target set_reportFrequency newval |

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

**lightsensor→set_resolution()
lightsensor→setResolution()
lightsensor.set_resolution()****YLightSensor**

Changes the resolution of the measured physical values.

| | |
|--------|--|
| js | function set_resolution(newval) |
| nodejs | function set_resolution(newval) |
| php | function set_resolution(\$newval) |
| cpp | int set_resolution(double newval) |
| m | -(int) setResolution : (double) newval |
| pas | function set_resolution(newval: double): integer |
| vb | function set_resolution(ByVal newval As Double) As Integer |
| cs | int set_resolution(double newval) |
| java | int set_resolution(double newval) |
| py | def set_resolution(newval) |
| cmd | YLightSensor target set_resolution newval |

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→set(userData)
lightsensor→setUserData()
lightsensor.set(userData)

YLightSensor

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|---|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData \$data) |
| cpp | void set(userData void* data) |
| m | -(void) setUserData : (void*) data |
| pas | procedure set(userData data: Tobject) |
| vb | procedure set(userData ByVal data As Object) |
| cs | void set(userData object data) |
| java | void set(userData Object data) |
| py | def set(userData data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

lightsensor→wait_async()

YLightSensor

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.23. Magnetometer function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

| | |
|--------|--|
| js | <script type='text/javascript' src='yocto_magnetometer.js'></script> |
| nodejs | var yoctolib = require('yoctolib'); |
| php | var YMagnetometer = yoctolib.YMagnetometer; |
| cpp | require_once('yocto_magnetometer.php'); |
| m | #include "yocto_magnetometer.h" |
| pas | #import "yocto_magnetometer.h" |
| vb | uses yocto_magnetometer; |
| cs | yocto_magnetometer.vb |
| java | yocto_magnetometer.cs |
| py | import com.yoctopuce.YoctoAPI.YMagnetometer; |
| | from yocto_magnetometer import * |

Global functions

yFindMagnetometer(func)

Retrieves a magnetometer for a given identifier.

yFirstMagnetometer()

Starts the enumeration of magnetometers currently accessible.

YMagnetometer methods

magnetometer→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

magnetometer→describe()

Returns a short text that describes unambiguously the instance of the magnetometer in the form TYPE (NAME) = SERIAL . FUNCTIONID.

magnetometer→get_advertisedValue()

Returns the current value of the magnetometer (no more than 6 characters).

magnetometer→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor.

magnetometer→get_currentValue()

Returns the current value of the magnetic field.

magnetometer→get_errorMessage()

Returns the error message of the latest error with the magnetometer.

magnetometer→get_errorType()

Returns the numerical error code of the latest error with the magnetometer.

magnetometer→get_friendlyName()

Returns a global identifier of the magnetometer in the format MODULE_NAME . FUNCTION_NAME.

magnetometer→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

magnetometer→get_functionId()

Returns the hardware identifier of the magnetometer, without reference to the module.

magnetometer→get_hardwareId()

Returns the unique hardware identifier of the magnetometer in the form SERIAL . FUNCTIONID.

| | |
|---|--|
| magnetometer→get_highestValue() | Returns the maximal value observed for the magnetic field since the device was started. |
| magnetometer→get_logFrequency() | Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory. |
| magnetometer→get_logicalName() | Returns the logical name of the magnetometer. |
| magnetometer→get_lowestValue() | Returns the minimal value observed for the magnetic field since the device was started. |
| magnetometer→get_module() | Gets the YModule object for the device on which the function is located. |
| magnetometer→get_module_async(callback, context) | Gets the YModule object for the device on which the function is located (asynchronous version). |
| magnetometer→get_recordedData(startTime, endTime) | Retrieves a DataSet object holding historical data for this sensor, for a specified time interval. |
| magnetometer→get_reportFrequency() | Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function. |
| magnetometer→get_resolution() | Returns the resolution of the measured values. |
| magnetometer→get_unit() | Returns the measuring unit for the magnetic field. |
| magnetometer→get_userData() | Returns the value of the userData attribute, as previously stored using method set(userData). |
| magnetometer→get_xValue() | Returns the X component of the magnetic field, as a floating point number. |
| magnetometer→get_yValue() | Returns the Y component of the magnetic field, as a floating point number. |
| magnetometer→get_zValue() | Returns the Z component of the magnetic field, as a floating point number. |
| magnetometer→isOnline() | Checks if the magnetometer is currently reachable, without raising any error. |
| magnetometer→isOnline_async(callback, context) | Checks if the magnetometer is currently reachable, without raising any error (asynchronous version). |
| magnetometer→load(msValidity) | Preloads the magnetometer cache with a specified validity duration. |
| magnetometer→loadCalibrationPoints(rawValues, refValues) | Retrieves error correction data points previously entered using the method calibrateFromPoints. |
| magnetometer→load_async(msValidity, callback, context) | Preloads the magnetometer cache with a specified validity duration (asynchronous version). |
| magnetometer→nextMagnetometer() | Continues the enumeration of magnetometers started using yFirstMagnetometer(). |
| magnetometer→registerTimedReportCallback(callback) | Registers the callback function that is invoked on every periodic timed notification. |
| magnetometer→registerValueCallback(callback) | Registers the callback function that is invoked on every change of advertised value. |

magnetometer→set_highestValue(newval)

Changes the recorded maximal value observed.

magnetometer→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

magnetometer→set_logicalName(newval)

Changes the logical name of the magnetometer.

magnetometer→set_lowestValue(newval)

Changes the recorded minimal value observed.

magnetometer→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

magnetometer→set_resolution(newval)

Changes the resolution of the measured physical values.

magnetometer→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

magnetometer→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

Y Magnetometer.FindMagnetometer()**Y Magnetometer****yFindMagnetometer()****Y Magnetometer.FindMagnetometer()**

Retrieves a magnetometer for a given identifier.

| | |
|--------|---|
| js | function yFindMagnetometer(func) |
| nodejs | function FindMagnetometer(func) |
| php | function yFindMagnetometer(\$func) |
| cpp | Y Magnetometer* yFindMagnetometer(const string& func) |
| m | Y Magnetometer* yFindMagnetometer(NSString* func) |
| pas | function yFindMagnetometer(func: string): TYMagnetometer |
| vb | function yFindMagnetometer(ByVal func As String) As YMagnetometer |
| cs | Y Magnetometer FindMagnetometer(string func) |
| java | Y Magnetometer FindMagnetometer(String func) |
| py | def FindMagnetometer(func) |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the magnetometer is online at the time it is invoked. The returned object is nevertheless valid. Use the method `Y Magnetometer.isOnline()` to test if the magnetometer is indeed online at a given time. In case of ambiguity when looking for a magnetometer by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the magnetometer

Returns :

a `Y Magnetometer` object allowing you to drive the magnetometer.

Y Magnetometer.FirstMagnetometer() yFirstMagnetometer() Y Magnetometer.FirstMagnetometer()

Y Magnetometer

Starts the enumeration of magnetometers currently accessible.

```
js function yFirstMagnetometer( )
nodejs function FirstMagnetometer( )
php function yFirstMagnetometer( )
cpp YMagnetometer* yFirstMagnetometer( )
m YMagnetometer* yFirstMagnetometer( )
pas function yFirstMagnetometer( ): TYMagnetometer
vb function yFirstMagnetometer( ) As YMagnetometer
cs YMagnetometer FirstMagnetometer( )
java YMagnetometer FirstMagnetometer( )
py def FirstMagnetometer( )
```

Use the method `YMagnetometer.nextMagnetometer()` to iterate on next magnetometers.

Returns :

a pointer to a `YMagnetometer` object, corresponding to the first magnetometer currently online, or a null pointer if there are none.

magnetometer→calibrateFromPoints() magnetometer.calibrateFromPoints()

YMagnetometer

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```

js   function calibrateFromPoints( rawValues, refValues)
nodejs function calibrateFromPoints( rawValues, refValues)
php   function calibrateFromPoints( $rawValues, $refValues)
cpp   int calibrateFromPoints( vector<double> rawValues,
                           vector<double> refValues)
m    -(int) calibrateFromPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues
pas  function calibrateFromPoints( rawValues: TDoubleArray,
                           refValues: TDoubleArray): LongInt
vb   procedure calibrateFromPoints( )
cs   int calibrateFromPoints( List<double> rawValues,
                           List<double> refValues)
java int calibrateFromPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)
py   def calibrateFromPoints( rawValues, refValues)
cmd YMagnetometer target calibrateFromPoints rawValues refValues

```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

magnetometer→describe()magnetometer.describe()**YMagnetometer**

Returns a short text that describes unambiguously the instance of the magnetometer in the form
 TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the magnetometer (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

magnetometer→get_advertisedValue()
magnetometer→advertisedValue()
magnetometer.get_advertisedValue()

YMagnetometer

Returns the current value of the magnetometer (no more than 6 characters).

```
js function get_advertisedValue( )  
nodejs function get_advertisedValue( )  
php function get_advertisedValue( )  
cpp string get_advertisedValue( )  
m -(NSString*) advertisedValue  
pas function get_advertisedValue( ): string  
vb function get_advertisedValue( ) As String  
cs string get_advertisedValue( )  
java String get_advertisedValue( )  
py def get_advertisedValue( )  
cmd YMagnetometer target get_advertisedValue
```

Returns :

a string corresponding to the current value of the magnetometer (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

magnetometer→get_currentRawValue()
magnetometer→currentRawValue()
magnetometer.get_currentRawValue()

YMagnetometer

Returns the uncalibrated, unrounded raw value returned by the sensor.

| | |
|---------------|--|
| js | function get_currentRawValue() |
| nodejs | function get_currentRawValue() |
| php | function get_currentRawValue() |
| cpp | double get_currentRawValue() |
| m | -(double) currentRawValue |
| pas | function get_currentRawValue(): double |
| vb | function get_currentRawValue() As Double |
| cs | double get_currentRawValue() |
| java | double get_currentRawValue() |
| py | def get_currentRawValue() |
| cmd | Y Magnetometer target get_currentRawValue |

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor

On failure, throws an exception or returns **Y_CURRENTRAWVALUE_INVALID**.

magnetometer→get_currentValue()
magnetometer→currentValue()
magnetometer.get_currentValue()

YMagnetometer

Returns the current value of the magnetic field.

```
js function get_currentValue( )  
nodejs function get_currentValue( )  
php function get_currentValue( )  
cpp double get_currentValue( )  
m -(double) currentValue  
pas function get_currentValue( ): double  
vb function get_currentValue( ) As Double  
cs double get_currentValue( )  
java double get_currentValue( )  
py def get_currentValue( )  
cmd YMagnetometer target get_currentValue
```

Returns :

a floating point number corresponding to the current value of the magnetic field

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

magnetometer→getErrorMessage()
magnetometer→errorMessage()
magnetometer.getErrorMessage()

YMagnetometer

Returns the error message of the latest error with the magnetometer.

| | |
|---------|--|
| js | function getErrorMessage() |
| node.js | function getErrorMessage() |
| php | function getErrorMessage() |
| cpp | string getErrorMessage() |
| m | -(NSString*) errorMessage |
| pas | function getErrorMessage() : string |
| vb | function getErrorMessage() As String |
| cs | string getErrorMessage() |
| java | String getErrorMessage() |
| py | def getErrorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the magnetometer object

magnetometer→get_errorType()
magnetometer→errorType()
magnetometer.get_errorType()**YMagnetometer**

Returns the numerical error code of the latest error with the magnetometer.

| | |
|--------|---------------------------------------|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType(): YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the magnetometer object

magnetometer→get_friendlyName()
magnetometer→friendlyName()
magnetometer.get_friendlyName()

YMagnetometer

Returns a global identifier of the magnetometer in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|-------------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the magnetometer if they are defined, otherwise the serial number of the module and the hardware identifier of the magnetometer (for exemple: MyCustomName . relay1)

Returns :

a string that uniquely identifies the magnetometer using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

magnetometer→get_functionDescriptor()
magnetometer→functionDescriptor()
magnetometer.get_functionDescriptor()**YMagnetometer**

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|---|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

magnetometer→get_functionId()
magnetometer→functionId()
magnetometer.get_functionId()

YMagnetometer

Returns the hardware identifier of the magnetometer, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the magnetometer (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

magnetometer→get_hardwareId()
magnetometer→hardwareId()
magnetometer.get_hardwareId()**YMagnetometer**

Returns the unique hardware identifier of the magnetometer in the form SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function get_hardwareId() |
| nodejs | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the magnetometer. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the magnetometer (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

magnetometer→get_highestValue()
magnetometer→highestValue()
magnetometer.get_highestValue()

YMagnetometer

Returns the maximal value observed for the magnetic field since the device was started.

| | |
|----------------|---|
| js | function get_highestValue() |
| node.js | function get_highestValue() |
| php | function get_highestValue() |
| cpp | double get_highestValue() |
| m | -(double) highestValue |
| pas | function get_highestValue() : double |
| vb | function get_highestValue() As Double |
| cs | double get_highestValue() |
| java | double get_highestValue() |
| py | def get_highestValue() |
| cmd | Y Magnetometer target get_highestValue |

Returns :

a floating point number corresponding to the maximal value observed for the magnetic field since the device was started

On failure, throws an exception or returns **Y_HIGHESTVALUE_INVALID**.

magnetometer→get_logFrequency()
magnetometer→logFrequency()
magnetometer.get_logFrequency()**YMagnetometer**

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
js   function get_logFrequency( )  
nodejs function get_logFrequency( )  
php  function get_logFrequency( )  
cpp   string get_logFrequency( )  
m    -(NSString*) logFrequency  
pas   function get_logFrequency( ):string  
vb    function get_logFrequency( ) As String  
cs    string get_logFrequency( )  
java  String get_logFrequency( )  
py    def get_logFrequency( )  
cmd   YMagnetometer target get_logFrequency
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

magnetometer→get_logicalName()
magnetometer→logicalName()
magnetometer.get_logicalName()

YMagnetometer

Returns the logical name of the magnetometer.

```
js   function get_logicalName( )  
nodejs function get_logicalName( )  
php  function get_logicalName( )  
cpp   string get_logicalName( )  
m    -(NSString*) logicalName  
pas   function get_logicalName( ): string  
vb    function get_logicalName( ) As String  
cs    string get_logicalName( )  
java  String get_logicalName( )  
py    def get_logicalName( )  
cmd   YMagnetometer target get_logicalName
```

Returns :

a string corresponding to the logical name of the magnetometer. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

magnetometer→get_lowestValue()
magnetometer→lowestValue()
magnetometer.get_lowestValue()

YMagnetometer

Returns the minimal value observed for the magnetic field since the device was started.

js function **get_lowestValue()**
nodejs function **get_lowestValue()**
php function **get_lowestValue()**
cpp double **get_lowestValue()**
m -(double) lowestValue
pas function **get_lowestValue()**: double
vb function **get_lowestValue()** As Double
cs double **get_lowestValue()**
java double **get_lowestValue()**
py def **get_lowestValue()**
cmd YMagnetometer **target get_lowestValue**

Returns :

a floating point number corresponding to the minimal value observed for the magnetic field since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

magnetometer→get_module()
magnetometer→module()
magnetometer.get_module()

YMagnetometer

Gets the **YModule** object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of **YModule** is not shown as on-line.

Returns :

an instance of **YModule**

magnetometer→get_module_async()
magnetometer→module_async()**YMagnetometer**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

```
magnetometer→get_recordedData()  
magnetometer→recordedData()  
magnetometer.get_recordedData()
```

YMagnetometer

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
js function get_recordedData( startTime, endTime)
nodejs function get_recordedData( startTime, endTime)
php function get_recordedData( $startTime, $endTime)
cpp YDataSet get_recordedData( s64 startTime, s64 endTime)
m -(YDataSet*) recordedData : (s64) startTime
                           : (s64) endTime
pas function get_recordedData( startTime: int64, endTime: int64): TYDataSet
vb function get_recordedData( ) As YDataSet
cs YDataSet get_recordedData( long startTime, long endTime)
java YDataSet get_recordedData( long startTime, long endTime)
py def get_recordedData( startTime, endTime)
cmd YMagnetometer target get_recordedData startTime endTime
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the `DataSet` class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measurement, without ending limit.

Returns :

an instance of `YDataSet`, providing access to historical data. Past measures can be loaded progressively using methods from the `YDataSet` object.

magnetometer→get_reportFrequency()
magnetometer→reportFrequency()
magnetometer.get_reportFrequency()**YMagnetometer**

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
js function get_reportFrequency( )
nodejs function get_reportFrequency( )
php function get_reportFrequency( )
cpp string get_reportFrequency( )
m -(NSString*) reportFrequency
pas function get_reportFrequency( ): string
vb function get_reportFrequency( ) As String
cs string get_reportFrequency( )
java String get_reportFrequency( )
py def get_reportFrequency( )
cmd YMagnetometer target get_reportFrequency
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

magnetometer→get_resolution()
magnetometer→resolution()
magnetometer.get_resolution()

YMagnetometer

Returns the resolution of the measured values.

```
js   function get_resolution( )  
nodejs function get_resolution( )  
php  function get_resolution( )  
cpp   double get_resolution( )  
m    -(double) resolution  
pas   function get_resolution( ): double  
vb    function get_resolution( ) As Double  
cs    double get_resolution( )  
java  double get_resolution( )  
py    def get_resolution( )  
cmd   YMagnetometer target get_resolution
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

magnetometer→get_unit()**YMagnetometer****magnetometer→unit()magnetometer.get_unit()**

Returns the measuring unit for the magnetic field.

| | |
|---------|---------------------------------------|
| js | function get_unit() |
| node.js | function get_unit() |
| php | function get_unit() |
| cpp | string get_unit() |
| m | -(NSString*) unit |
| pas | function get_unit() : string |
| vb | function get_unit() As String |
| cs | string get_unit() |
| java | String get_unit() |
| py | def get_unit() |
| cmd | Y Magnetometer target get_unit |

Returns :

a string corresponding to the measuring unit for the magnetic field

On failure, throws an exception or returns Y_UNIT_INVALID.

magnetometer→get(userData)
magnetometer→userData()
magnetometer.get(userData())

YMagnetometer

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|---------|---|
| js | function get(userData) |
| node.js | function get(userData) |
| php | function get(userData) |
| cpp | void * get(userData) |
| m | -(void*) userData |
| pas | function get(userData) : Tobject |
| vb | function get(userData) As Object |
| cs | object get(userData) |
| java | Object get(userData) |
| py | def get(userData) |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

magnetometer→get_xValue()**YMagnetometer****magnetometer→xValue()magnetometer.get_xValue()**

Returns the X component of the magnetic field, as a floating point number.

```
js function get_xValue( )
node.js function get_xValue( )
php function get_xValue( )
cpp double get_xValue( )
m -(double) xValue
pas function get_xValue( ): double
vb function get_xValue( ) As Double
cs double get_xValue( )
java double get_xValue( )
py def get_xValue( )
cmd YMagnetometer target get_xValue
```

Returns :

a floating point number corresponding to the X component of the magnetic field, as a floating point number

On failure, throws an exception or returns Y_XVALUE_INVALID.

magnetometer→get_yValue()**YMagnetometer****magnetometer→yValue()magnetometer.get_yValue()**

Returns the Y component of the magnetic field, as a floating point number.

```
js function get_yValue( )
nodejs function get_yValue( )
php function get_yValue( )
cpp double get_yValue( )
m -(double) yValue
pas function get_yValue( ): double
vb function get_yValue( ) As Double
cs double get_yValue( )
java double get_yValue( )
py def get_yValue( )
cmd YMagnetometer target get_yValue
```

Returns :

a floating point number corresponding to the Y component of the magnetic field, as a floating point number

On failure, throws an exception or returns `Y_YVALUE_INVALID`.

magnetometer→get_zValue()**YMagnetometer****magnetometer→zValue()magnetometer.get_zValue()**

Returns the Z component of the magnetic field, as a floating point number.

```
js function get_zValue( )  
node.js function get_zValue( )  
php function get_zValue( )  
cpp double get_zValue( )  
m -(double) zValue  
pas function get_zValue( ): double  
vb function get_zValue( ) As Double  
cs double get_zValue( )  
java double get_zValue( )  
py def get_zValue( )  
cmd YMagnetometer target get_zValue
```

Returns :

a floating point number corresponding to the Z component of the magnetic field, as a floating point number

On failure, throws an exception or returns Y_ZVALUE_INVALID.

magnetometer→isOnline()magnetometer.isOnline()**YMagnetometer**

Checks if the magnetometer is currently reachable, without raising any error.

| | |
|---------|--|
| js | function isOnline() |
| node.js | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the magnetometer in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the magnetometer.

Returns :

`true` if the magnetometer can be reached, and `false` otherwise

magnetometer→isOnline_async()

YMagnetometer

Checks if the magnetometer is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context )
nodejs function isOnline_async( callback, context )
```

If there is a cached value for the magnetometer in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

magnetometer→load()magnetometer.load()**YMagnetometer**

Preloads the magnetometer cache with a specified validity duration.

| | |
|---------|--|
| js | function load(msValidity) |
| node.js | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | - (YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

magnetometer→loadCalibrationPoints() magnetometer.loadCalibrationPoints()

YMagnetometer

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```

js   function loadCalibrationPoints( rawValues, refValues)
nodejs function loadCalibrationPoints( rawValues, refValues)
php   function loadCalibrationPoints( &$rawValues, &$refValues)
cpp   int loadCalibrationPoints( vector<double>& rawValues,
                                vector<double>& refValues)
m    -(int) loadCalibrationPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues
pas  function loadCalibrationPoints( var rawValues: TDoubleArray,
                           var refValues: TDoubleArray): LongInt
vb   procedure loadCalibrationPoints( )
cs   int loadCalibrationPoints( List<double> rawValues,
                           List<double> refValues)
java int loadCalibrationPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)
py   def loadCalibrationPoints( rawValues, refValues)
cmd  YMagnetometer target loadCalibrationPoints rawValues refValues

```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

magnetometer→load_async()

YMagnetometer

Preloads the magnetometer cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

magnetometer→nextMagnetometer()
magnetometer.nextMagnetometer()**YMagnetometer**

Continues the enumeration of magnetometers started using `yFirstMagnetometer()`.

| | |
|----------------------|---|
| <code>js</code> | <code>function nextMagnetometer()</code> |
| <code>node.js</code> | <code>function nextMagnetometer()</code> |
| <code>php</code> | <code>function nextMagnetometer()</code> |
| <code>cpp</code> | <code>YMagnetometer * nextMagnetometer()</code> |
| <code>m</code> | <code>-(YMagnetometer*) nextMagnetometer</code> |
| <code>pas</code> | <code>function nextMagnetometer(): TYMagnetometer</code> |
| <code>vb</code> | <code>function nextMagnetometer() As YMagnetometer</code> |
| <code>cs</code> | <code>YMagnetometer nextMagnetometer()</code> |
| <code>java</code> | <code>YMagnetometer nextMagnetometer()</code> |
| <code>py</code> | <code>def nextMagnetometer()</code> |

Returns :

a pointer to a `YMagnetometer` object, corresponding to a magnetometer currently online, or a null pointer if there are no more magnetometers to enumerate.

magnetometer→registerTimedReportCallback() magnetometer.registerTimedReportCallback()

YMagnetometer

Registers the callback function that is invoked on every periodic timed notification.

| | |
|---------|---|
| js | function registerTimedReportCallback(callback) |
| node.js | function registerTimedReportCallback(callback) |
| php | function registerTimedReportCallback(\$callback) |
| cpp | int registerTimedReportCallback(YMagnetometerTimedReportCallback callback) |
| m | -(int) registerTimedReportCallback : (YMagnetometerTimedReportCallback) callback |
| pas | function registerTimedReportCallback(callback : TYMagnetometerTimedReportCallback): LongInt |
| vb | function registerTimedReportCallback() As Integer |
| cs | int registerTimedReportCallback(TimedReportCallback callback) |
| java | int registerTimedReportCallback(TimedReportCallback callback) |
| py | def registerTimedReportCallback(callback) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

magnetometer→registerValueCallback() magnetometer.registerValueCallback()

YMagnetometer

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YMagnetometerValueCallback callback )
m    -(int) registerValueCallback : (YMagnetometerValueCallback) callback
pas   function registerValueCallback( callback: TYMagnetometerValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

magnetometer→set_highestValue()
magnetometer→setHighestValue()
magnetometer.set_highestValue()

YMagnetometer

Changes the recorded maximal value observed.

```
js function set_highestValue( newval)
nodejs function set_highestValue( newval)
php function set_highestValue( $newval)
cpp int set_highestValue( double newval)
m -(int) setHighestValue : (double) newval
pas function set_highestValue( newval: double): integer
vb function set_highestValue( ByVal newval As Double) As Integer
cs int set_highestValue( double newval)
java int set_highestValue( double newval)
py def set_highestValue( newval)
cmd YMagnetometer target set_highestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

magnetometer→set_logFrequency()
magnetometer→setLogFrequency()
magnetometer.set_logFrequency()

YMagnetometer

Changes the datalogger recording frequency for this function.

```
js  function set_logFrequency( newval)
nodejs function set_logFrequency( newval)
php  function set_logFrequency( $newval)
cpp  int set_logFrequency( const string& newval)
m   -(int) setLogFrequency : (NSString*) newval
pas  function set_logFrequency( newval: string): integer
vb   function set_logFrequency( ByVal newval As String) As Integer
cs   int set_logFrequency( string newval)
java int set_logFrequency( String newval)
py   def set_logFrequency( newval)
cmd  YMagnetometer target set_logFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

magnetometer→set_logicalName()
magnetometer→setLogicalName()
magnetometer.set_logicalName()

YMagnetometer

Changes the logical name of the magnetometer.

| | |
|---------------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YMagnetometer target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the magnetometer.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

magnetometer→set_lowestValue()
magnetometer→setLowestValue()
magnetometer.set_lowestValue()

YMagnetometer

Changes the recorded minimal value observed.

```
js function set_lowestValue( newval)
nodejs function set_lowestValue( newval)
php function set_lowestValue( $newval)
cpp int set_lowestValue( double newval)
m -(int) setLowestValue : (double) newval
pas function set_lowestValue( newval: double): integer
vb function set_lowestValue( ByVal newval As Double) As Integer
cs int set_lowestValue( double newval)
java int set_lowestValue( double newval)
py def set_lowestValue( newval)
cmd YMagnetometer target set_lowestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

magnetometer→set_reportFrequency()
magnetometer→setReportFrequency()
magnetometer.set_reportFrequency()

YMagnetometer

Changes the timed value notification frequency for this function.

| | |
|---------------|---|
| js | function set_reportFrequency(newval) |
| nodejs | function set_reportFrequency(newval) |
| php | function set_reportFrequency(\$newval) |
| cpp | int set_reportFrequency(const string& newval) |
| m | -(int) setReportFrequency : (NSString*) newval |
| pas | function set_reportFrequency(newval: string): integer |
| vb | function set_reportFrequency(ByVal newval As String) As Integer |
| cs | int set_reportFrequency(string newval) |
| java | int set_reportFrequency(String newval) |
| py | def set_reportFrequency(newval) |
| cmd | YMagnetometer target set_reportFrequency newval |

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

magnetometer→set_resolution()
magnetometer→setResolution()
magnetometer.set_resolution()

YMagnetometer

Changes the resolution of the measured physical values.

```
js function set_resolution( newval)
nodejs function set_resolution( newval)
php function set_resolution( $newval)
cpp int set_resolution( double newval)
m -(int) setResolution : (double) newval
pas function set_resolution( newval: double): integer
vb function set_resolution( ByVal newval As Double) As Integer
cs int set_resolution( double newval)
java int set_resolution( double newval)
py def set_resolution( newval)
cmd YMagnetometer target set_resolution newval
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

magnetometer→set(userData)
magnetometer→setUserData()
magnetometer.set(userData)

YMagnetometer

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|---|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData \$data) |
| cpp | void set(userData void* data) |
| m | -(void) set(userData : (void*) data) |
| pas | procedure set(userData data: Tobject) |
| vb | procedure set(userData ByVal data As Object) |
| cs | void set(userData object data) |
| java | void set(userData Object data) |
| py | def set(userData data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

magnetometer→wait_async()**YMagnetometer**

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js   function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.24. Measured value

YMeasure objects are used within the API to represent a value measured at a specified time. These objects are used in particular in conjunction with the YDataSet class.

In order to use the functions described here, you should include:

| | |
|---------|---|
| js | <script type='text/javascript' src='yocto_api.js'></script> |
| node.js | var yoctolib = require('yoctolib'); |
| | var YAPI = yoctolib.YAPI; |
| | var YModule = yoctolib.YModule; |
| php | require_once('yocto_api.php'); |
| cpp | #include "yocto_api.h" |
| m | #import "yocto_api.h" |
| pas | uses yocto_api; |
| vb | yocto_api.vb |
| cs | yocto_api.cs |
| java | import com.yoctopuce.YoctoAPI.YModule; |
| py | from yocto_api import * |

YMeasure methods

measure→get_averageValue()

Returns the average value observed during the time interval covered by this measure.

measure→get_endTimeUTC()

Returns the end time of the measure, relative to the Jan 1, 1970 UTC (Unix timestamp).

measure→get_maxValue()

Returns the largest value observed during the time interval covered by this measure.

measure→get_minValue()

Returns the smallest value observed during the time interval covered by this measure.

measure→get_startTimeUTC()

Returns the start time of the measure, relative to the Jan 1, 1970 UTC (Unix timestamp).

measure→get_averageValue()
measure→averageValue()
measure.get_averageValue()

YMeasure

Returns the average value observed during the time interval covered by this measure.

js function **get_averageValue()**
nodejs function **get_averageValue()**
php function **get_averageValue()**
cpp double **get_averageValue()**
m -(double) **averageValue**
pas function **get_averageValue()**: double
vb function **get_averageValue()** As Double
cs double **get_averageValue()**
java double **get_averageValue()**
py def **get_averageValue()**

Returns :

a floating-point number corresponding to the average value observed.

measure→get_endTimeUTC()**YMeasure****measure→endTimeUTC()measure.get_endTimeUTC()**

Returns the end time of the measure, relative to the Jan 1, 1970 UTC (Unix timestamp).

```
js    function get_endTimeUTC( )  
nodejs function get_endTimeUTC( )  
php   function get_endTimeUTC( )  
cpp   double get_endTimeUTC( )  
m     -(double) endTimeUTC  
pas   function get_endTimeUTC( ): double  
vb    function get_endTimeUTC( ) As Double  
cs    double get_endTimeUTC( )  
java  double get_endTimeUTC( )  
py    def get_endTimeUTC( )
```

When the recording rate is higher than 1 sample per second, the timestamp may have a fractional part.

Returns :

an floating point number corresponding to the number of seconds between the Jan 1, 1970 UTC and the end of this measure.

measure→get_maxValue()**YMeasure****measure→maxValue()measure.get_maxValue()**

Returns the largest value observed during the time interval covered by this measure.

| | |
|---------|---|
| js | function get_maxValue() |
| node.js | function get_maxValue() |
| php | function get_maxValue() |
| cpp | double get_maxValue() |
| m | -(double) maxValue |
| pas | function get_maxValue() : double |
| vb | function get_maxValue() As Double |
| cs | double get_maxValue() |
| java | double get_maxValue() |
| py | def get_maxValue() |

Returns :

a floating-point number corresponding to the largest value observed.

measure→get_minValue()**YMeasure****measure→minValue()measure.get_minValue()**

Returns the smallest value observed during the time interval covered by this measure.

| | |
|--------|---|
| js | function get_minValue() |
| nodejs | function get_minValue() |
| php | function get_minValue() |
| cpp | double get_minValue() |
| m | -(double) minValue |
| pas | function get_minValue(): double |
| vb | function get_minValue() As Double |
| cs | double get_minValue() |
| java | double get_minValue() |
| py | def get_minValue() |

Returns :

a floating-point number corresponding to the smallest value observed.

measure→getStartTimeUTC()
measure→startTimeUTC()
measure.getStartTimeUTC()**YMeasure**

Returns the start time of the measure, relative to the Jan 1, 1970 UTC (Unix timestamp).

js function **getStartTimeUTC()**
nodejs function **getStartTimeUTC()**
php function **getStartTimeUTC()**
cpp double **getStartTimeUTC()**
m -(double) startTimeUTC
pas function **getStartTimeUTC(): double**
vb function **getStartTimeUTC() As Double**
cs double **getStartTimeUTC()**
java double **getStartTimeUTC()**
py def **getStartTimeUTC()**

When the recording rate is higher than 1 sample per second, the timestamp may have a fractional part.

Returns :

an floating point number corresponding to the number of seconds between the Jan 1, 1970 UTC and the beginning of this measure.

3.25. Module control interface

This interface is identical for all Yoctopuce USB modules. It can be used to control the module global parameters, and to enumerate the functions provided by each module.

In order to use the functions described here, you should include:

| | |
|---------|---|
| js | <script type='text/javascript' src='yocto_api.js'></script> |
| node.js | var yoctolib = require('yoctolib'); |
| | var YAPI = yoctolib.YAPI; |
| | var YModule = yoctolib.YModule; |
| php | require_once('yocto_api.php'); |
| cpp | #include "yocto_api.h" |
| m | #import "yocto_api.h" |
| pas | uses yocto_api; |
| vb | yocto_api.vb |
| cs | yocto_api.cs |
| java | import com.yoctopuce.YoctoAPI.YModule; |
| py | from yocto_api import * |

Global functions

yFindModule(func)

Allows you to find a module from its serial number or from its logical name.

yFirstModule()

Starts the enumeration of modules currently accessible.

YModule methods

module→describe()

Returns a descriptive text that identifies the module.

module→download(pathname)

Downloads the specified built-in file and returns a binary buffer with its content.

module→functionCount()

Returns the number of functions (beside the "module" interface) available on the module.

module→functionId(functionIndex)

Retrieves the hardware identifier of the *n*th function on the module.

module→functionName(functionIndex)

Retrieves the logical name of the *n*th function on the module.

module→functionValue(functionIndex)

Retrieves the advertised value of the *n*th function on the module.

module→get_beacon()

Returns the state of the localization beacon.

module→get_errorMessage()

Returns the error message of the latest error with this module object.

module→get_errorType()

Returns the numerical error code of the latest error with this module object.

module→get_firmwareRelease()

Returns the version of the firmware embedded in the module.

module→get_hardwareId()

Returns the unique hardware identifier of the module.

module→get_icon2d()

3. Reference

| |
|---|
| Returns the icon of the module. |
| module→get_lastLogs() Returns a string with last logs of the module. |
| module→get_logicalName() Returns the logical name of the module. |
| module→get_luminosity() Returns the luminosity of the module informative leds (from 0 to 100). |
| module→get_persistentSettings() Returns the current state of persistent module settings. |
| module→get_productId() Returns the USB device identifier of the module. |
| module→get_productName() Returns the commercial name of the module, as set by the factory. |
| module→get_productRelease() Returns the hardware release version of the module. |
| module→get_rebootCountdown() Returns the remaining number of seconds before the module restarts, or zero when no reboot has been scheduled. |
| module→get_serialNumber() Returns the serial number of the module, as set by the factory. |
| module→get_upTime() Returns the number of milliseconds spent since the module was powered on. |
| module→get_usbBandwidth() Returns the number of USB interfaces used by the module. |
| module→get_usbCurrent() Returns the current consumed by the module on the USB bus, in milli-amps. |
| module→get(userData) Returns the value of the userData attribute, as previously stored using method <code>set(userData)</code> . |
| module→isOnline() Checks if the module is currently reachable, without raising any error. |
| module→isOnline_async(callback, context) Checks if the module is currently reachable, without raising any error. |
| module→load(msValidity) Preloads the module cache with a specified validity duration. |
| module→load_async(msValidity, callback, context) Preloads the module cache with a specified validity duration (asynchronous version). |
| module→nextModule() Continues the module enumeration started using <code>yFirstModule()</code> . |
| module→reboot(secBeforeReboot) Schedules a simple module reboot after the given number of seconds. |
| module→registerLogCallback(callback) todo |
| module→revertFromFlash() Reloads the settings stored in the nonvolatile memory, as when the module is powered on. |
| module→saveToFlash() Saves current settings in the nonvolatile memory of the module. |

module→set_beacon(newval)

Turns on or off the module localization beacon.

module→set_logicalName(newval)

Changes the logical name of the module.

module→set_luminosity(newval)

Changes the luminosity of the module informative leds.

module→set_usbBandwidth(newval)

Changes the number of USB interfaces used by the module.

module→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

module→triggerFirmwareUpdate(secBeforeReboot)

Schedules a module reboot into special firmware update mode.

module→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YModule.FindModule() yFindModule()YModule.FindModule()

YModule

Allows you to find a module from its serial number or from its logical name.

```
js function yFindModule( func)
node.js function FindModule( func)
php function yFindModule( $func)
cpp YModule* yFindModule( string func)
m +(YModule*) yFindModule : (NSString*) func
pas function yFindModule( func: string): TYModule
vb function yFindModule( ByVal func As String) As YModule
cs YModule FindModule( string func)
java YModule FindModule( String func)
py def FindModule( func)
```

This function does not require that the module is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YModule.isOnline()` to test if the module is indeed online at a given time. In case of ambiguity when looking for a module by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string containing either the serial number or the logical name of the desired module

Returns :

a `YModule` object allowing you to drive the module or get additional information on the module.

YModule.FirstModule()**YModule****yFirstModule()YModule.FirstModule()**

Starts the enumeration of modules currently accessible.

| | |
|--------|--|
| js | function yFirstModule() |
| nodejs | function FirstModule() |
| php | function yFirstModule() |
| cpp | YModule* yFirstModule() |
| m | YModule* yFirstModule() |
| pas | function yFirstModule(): TYModule |
| vb | function yFirstModule() As YModule |
| cs | YModule FirstModule() |
| java | YModule FirstModule() |
| py | def FirstModule() |

Use the method `YModule.nextModule()` to iterate on the next modules.

Returns :

a pointer to a `YModule` object, corresponding to the first module currently online, or a `null` pointer if there are none.

module→describe()module.describe()**YModule**

Returns a descriptive text that identifies the module.

| | |
|--------|--|
| js | function describe () |
| nodejs | function describe () |
| php | function describe () |
| cpp | string describe () |
| m | - (NSString*) describe |
| pas | function describe (): string |
| vb | function describe () As String |
| cs | string describe () |
| java | String describe () |
| py | def describe () |

The text may include either the logical name or the serial number of the module.

Returns :

a string that describes the module

module→download()module.download()**YModule**

Downloads the specified built-in file and returns a binary buffer with its content.

| | |
|---------|---|
| js | function download(pathname) |
| node.js | function download(pathname) |
| php | function download(\$pathname) |
| cpp | string download(string pathname) |
| m | - (NSData*) download : (NSString*) pathname |
| pas | function download(pathname: string): TByteArray |
| vb | function download() As Byte |
| py | def download(pathname) |
| cmd | YModule target download pathname |

Parameters :

pathname name of the new file to load

Returns :

a binary buffer with the file content

On failure, throws an exception or returns an empty content.

module→functionCount()module.functionCount()**YModule**

Returns the number of functions (beside the "module" interface) available on the module.

| | |
|--------|---|
| js | function functionCount() |
| nodejs | function functionCount() |
| php | function functionCount() |
| cpp | int functionCount() |
| m | - (int) functionCount |
| pas | function functionCount() : integer |
| vb | function functionCount() As Integer |
| cs | int functionCount() |
| py | def functionCount() |

Returns :

the number of functions on the module

On failure, throws an exception or returns a negative error code.

module→functionId()module.functionId()**YModule**

Retrieves the hardware identifier of the *n*th function on the module.

| | |
|---------|---|
| js | function functionId(functionIndex) |
| node.js | function functionId(functionIndex) |
| php | function functionId(\$functionIndex) |
| cpp | string functionId(int functionIndex) |
| m | -(NSString*) functionId : (int) functionIndex |
| pas | function functionId(functionIndex: integer): string |
| vb | function functionId(ByVal functionIndex As Integer) As String |
| cs | string functionId(int functionIndex) |
| py | def functionId(functionIndex) |

Parameters :

functionIndex the index of the function for which the information is desired, starting at 0 for the first function.

Returns :

a string corresponding to the unambiguous hardware identifier of the requested module function

On failure, throws an exception or returns an empty string.

module→functionName()module.functionName()**YModule**

Retrieves the logical name of the *n*th function on the module.

```
js  function functionName( functionIndex)
nodejs function functionName( functionIndex)
php  function functionName( $functionIndex)
cpp   string functionName( int functionIndex)
m    -(NSString*) functionName : (int) functionIndex
pas   function functionName( functionIndex: integer): string
vb    function functionName( ByVal functionIndex As Integer) As String
cs    string functionName( int functionIndex)
py    def functionName( functionIndex)
```

Parameters :

functionIndex the index of the function for which the information is desired, starting at 0 for the first function.

Returns :

a string corresponding to the logical name of the requested module function

On failure, throws an exception or returns an empty string.

module→functionValue()module.functionValue()**YModule**

Retrieves the advertised value of the *n*th function on the module.

| | |
|---------|--|
| js | function functionValue(functionIndex) |
| node.js | function functionValue(functionIndex) |
| php | function functionValue(\$functionIndex) |
| cpp | string functionValue(int functionIndex) |
| m | -NSString* functionValue : (int) functionIndex |
| pas | function functionValue(functionIndex: integer): string |
| vb | function functionValue(ByVal functionIndex As Integer) As String |
| cs | string functionValue(int functionIndex) |
| py | def functionValue(functionIndex) |

Parameters :

functionIndex the index of the function for which the information is desired, starting at 0 for the first function.

Returns :

a short string (up to 6 characters) corresponding to the advertised value of the requested module function

On failure, throws an exception or returns an empty string.

module→get_beacon()
module→beacon()module.get_beacon()**YModule**

Returns the state of the localization beacon.

| | |
|---------|---|
| js | function get_beacon() |
| node.js | function get_beacon() |
| php | function get_beacon() |
| cpp | Y_BEACON_enum get_beacon() |
| m | -(Y_BEACON_enum) beacon |
| pas | function get_beacon() : Integer |
| vb | function get_beacon() As Integer |
| cs | int get_beacon() |
| java | int get_beacon() |
| py | def get_beacon() |
| cmd | YModule target get_beacon |

Returns :

either Y_BEACON_OFF or Y_BEACON_ON, according to the state of the localization beacon

On failure, throws an exception or returns Y_BEACON_INVALID.

module→getErrorMessage() **YModule**
module→errorMessage()module.getErrorMessage()

Returns the error message of the latest error with this module object.

| | |
|---------|--|
| js | function getErrorMessage() |
| node.js | function getErrorMessage() |
| php | function getErrorMessage() |
| cpp | string getErrorMessage() |
| m | -(NSString*) errorMessage |
| pas | function getErrorMessage() : string |
| vb | function getErrorMessage() As String |
| cs | string getErrorMessage() |
| java | String getErrorMessage() |
| py | def getErrorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using this module object

**module→get_errorType()
module→errorType()module.get_errorType()****YModule**

Returns the numerical error code of the latest error with this module object.

| | |
|---------|--|
| js | function get_errorType() |
| node.js | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType() : YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using this module object

module→get_firmwareRelease()
module→firmwareRelease()
module.get_firmwareRelease()

YModule

Returns the version of the firmware embedded in the module.

| | |
|---------------|--|
| js | function get_firmwareRelease() |
| nodejs | function get_firmwareRelease() |
| php | function get_firmwareRelease() |
| cpp | string get_firmwareRelease() |
| m | -(NSString*) firmwareRelease |
| pas | function get_firmwareRelease() : string |
| vb | function get_firmwareRelease() As String |
| cs | string get_firmwareRelease() |
| java | String get_firmwareRelease() |
| py | def get_firmwareRelease() |
| cmd | YModule target get_firmwareRelease |

Returns :

a string corresponding to the version of the firmware embedded in the module

On failure, throws an exception or returns **Y_FIRMWARERELEASE_INVALID**.

module→get_hwId()**YModule****module→hardwareId()module.get_hwId()**

Returns the unique hardware identifier of the module.

| | |
|---------|---------------------------------------|
| js | function get_hwId() |
| node.js | function get_hwId() |
| php | function get_hwId() |
| cpp | string get_hwId() |
| m | -(NSString*) hardwareId |
| vb | function get_hwId() As String |
| cs | string get_hwId() |
| java | String get_hwId() |
| py | def get_hwId() |

The unique hardware identifier is made of the device serial number followed by string ".module".

Returns :

a string that uniquely identifies the module

module→get_icon2d()
module→icon2d()module.get_icon2d()**YModule**

Returns the icon of the module.

| | |
|---------|---|
| js | function get_icon2d() |
| node.js | function get_icon2d() |
| php | function get_icon2d() |
| cpp | string get_icon2d() |
| m | -(NSData*) icon2d |
| pas | function get_icon2d(): TByteArray |
| vb | function get_icon2d() As Byte |
| py | def get_icon2d() |
| cmd | YModule target get_icon2d |

The icon is a PNG image and does not exceeds 1536 bytes.

Returns :

a binary buffer with module icon, in png format.

**module→get_lastLogs()
module→lastLogs()module.get_lastLogs()****YModule**

Returns a string with last logs of the module.

```
js function get_lastLogs( )  
node.js function get_lastLogs( )  
php function get_lastLogs( )  
cpp string get_lastLogs( )  
m -(NSString*) lastLogs  
pas function get_lastLogs( ): string  
vb function get_lastLogs( ) As String  
cs string get_lastLogs( )  
java String get_lastLogs( )  
py def get_lastLogs( )  
cmd YModule target get_lastLogs
```

This method return only logs that are still in the module.

Returns :

a string with last logs of the module.

| | |
|---|----------------|
| module→get_logicalName() | YModule |
| module→logicalName()module.get_logicalName() | |

Returns the logical name of the module.

```
js   function get_logicalName( )
nodejs function get_logicalName( )
php  function get_logicalName( )
cpp   string get_logicalName( )
m    -(NSString*) logicalName
pas   function get_logicalName( ): string
vb    function get_logicalName( ) As String
cs   string get_logicalName( )
java  String get_logicalName( )
py    def get_logicalName( )
cmd   YModule target get_logicalName
```

Returns :

a string corresponding to the logical name of the module

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

module→get_luminosity() **YModule**
module→luminosity()module.get_luminosity()

Returns the luminosity of the module informative leds (from 0 to 100).

```
js function get_luminosity( )
node.js function get_luminosity( )
php function get_luminosity( )
cpp int get_luminosity( )
m -(int) luminosity
pas function get_luminosity( ): LongInt
vb function get_luminosity( ) As Integer
cs int get_luminosity( )
java int get_luminosity( )
py def get_luminosity( )
cmd YModule target get_luminosity
```

Returns :

an integer corresponding to the luminosity of the module informative leds (from 0 to 100)

On failure, throws an exception or returns `Y_LUMINOSITY_INVALID`.

module→get_persistentSettings()
module→persistentSettings()
module.get_persistentSettings()

YModule

Returns the current state of persistent module settings.

| | |
|---------------|--|
| js | function get_persistentSettings() |
| nodejs | function get_persistentSettings() |
| php | function get_persistentSettings() |
| cpp | Y_PERSISTENTSETTINGS_enum get_persistentSettings() |
| m | -(Y_PERSISTENTSETTINGS_enum) persistentSettings |
| pas | function get_persistentSettings() : Integer |
| vb | function get_persistentSettings() As Integer |
| cs | int get_persistentSettings() |
| java | int get_persistentSettings() |
| py | def get_persistentSettings() |
| cmd | YModule target get_persistentSettings |

Returns :

a value among Y_PERSISTENTSETTINGS_LOADED, Y_PERSISTENTSETTINGS_SAVED and Y_PERSISTENTSETTINGS_MODIFIED corresponding to the current state of persistent module settings

On failure, throws an exception or returns Y_PERSISTENTSETTINGS_INVALID.

module→get_productId() **YModule**
module→productId()module.get_productId()

Returns the USB device identifier of the module.

| | |
|---------|---|
| js | function get_productId() |
| node.js | function get_productId() |
| php | function get_productId() |
| cpp | int get_productId() |
| m | -(int) productId |
| pas | function get_productId() : LongInt |
| vb | function get_productId() As Integer |
| cs | int get_productId() |
| java | int get_productId() |
| py | def get_productId() |
| cmd | YModule target get_productId |

Returns :

an integer corresponding to the USB device identifier of the module

On failure, throws an exception or returns Y_PRODUCTID_INVALID.

module→get_productName()**YModule****module→productName()module.get_productName()**

Returns the commercial name of the module, as set by the factory.

| | |
|--------|--|
| js | function get_productName() |
| nodejs | function get_productName() |
| php | function get_productName() |
| cpp | string get_productName() |
| m | -(NSString*) productName |
| pas | function get_productName(): string |
| vb | function get_productName() As String |
| cs | string get_productName() |
| java | String get_productName() |
| py | def get_productName() |
| cmd | YModule target get_productName |

Returns :

a string corresponding to the commercial name of the module, as set by the factory

On failure, throws an exception or returns Y_PRODUCTNAME_INVALID.

module→get_productRelease()
module→productRelease()
module.get_productRelease()

YModule

Returns the hardware release version of the module.

```
js function get_productRelease( )  
nodejs function get_productRelease( )  
php function get_productRelease( )  
cpp int get_productRelease( )  
m -(int) productRelease  
pas function get_productRelease( ): LongInt  
vb function get_productRelease( ) As Integer  
cs int get_productRelease( )  
java int get_productRelease( )  
py def get_productRelease( )  
cmd YModule target get_productRelease
```

Returns :

an integer corresponding to the hardware release version of the module

On failure, throws an exception or returns Y_PRODUCTRELEASE_INVALID.

module→get_rebootCountdown()
module→rebootCountdown()
module.get_rebootCountdown()

YModule

Returns the remaining number of seconds before the module restarts, or zero when no reboot has been scheduled.

| | |
|--------|---|
| js | function get_rebootCountdown() |
| nodejs | function get_rebootCountdown() |
| php | function get_rebootCountdown() |
| cpp | int get_rebootCountdown() |
| m | -(int) rebootCountdown |
| pas | function get_rebootCountdown(): LongInt |
| vb | function get_rebootCountdown() As Integer |
| cs | int get_rebootCountdown() |
| java | int get_rebootCountdown() |
| py | def get_rebootCountdown() |
| cmd | YModule target get_rebootCountdown |

Returns :

an integer corresponding to the remaining number of seconds before the module restarts, or zero when no reboot has been scheduled

On failure, throws an exception or returns **Y_REBOOTCOUNTDOWN_INVALID**.

module→get_serialNumber() **YModule**
module→serialNumber()module.get_serialNumber()

Returns the serial number of the module, as set by the factory.

| | |
|---------|---|
| js | function get_serialNumber() |
| node.js | function get_serialNumber() |
| php | function get_serialNumber() |
| cpp | string get_serialNumber() |
| m | -(NSString*) serialNumber |
| pas | function get_serialNumber(): string |
| vb | function get_serialNumber() As String |
| cs | string get_serialNumber() |
| java | String get_serialNumber() |
| py | def get_serialNumber() |
| cmd | YModule target get_serialNumber |

Returns :

a string corresponding to the serial number of the module, as set by the factory

On failure, throws an exception or returns **Y_SERIALNUMBER_INVALID**.

module→get_upTime() **YModule**
module→upTime()module.get_upTime()

Returns the number of milliseconds spent since the module was powered on.

| | |
|--------|---------------------------------------|
| js | function get_upTime() |
| nodejs | function get_upTime() |
| php | function get_upTime() |
| cpp | s64 get_upTime() |
| m | -(s64) upTime |
| pas | function get_upTime(): int64 |
| vb | function get_upTime() As Long |
| cs | long get_upTime() |
| java | long get_upTime() |
| py | def get_upTime() |
| cmd | YModule target get_upTime |

Returns :

an integer corresponding to the number of milliseconds spent since the module was powered on

On failure, throws an exception or returns **Y_UPTIME_INVALID**.

module→get_usbBandwidth()
module→usbBandwidth()
module.get_usbBandwidth()

YModule

Returns the number of USB interfaces used by the module.

```
js function get_usbBandwidth( )
nodejs function get_usbBandwidth( )
php function get_usbBandwidth( )
cpp Y_USBWIDTH_enum get_usbBandwidth( )
m -(Y_USBWIDTH_enum) usbBandwidth
pas function get_usbBandwidth( ): Integer
vb function get_usbBandwidth( ) As Integer
cs int get_usbBandwidth( )
java int get_usbBandwidth( )
py def get_usbBandwidth( )
cmd YModule target get_usbBandwidth
```

Returns :

either Y_USBWIDTH_SIMPLE or Y_USBWIDTH_DOUBLE, according to the number of USB interfaces used by the module

On failure, throws an exception or returns Y_USBWIDTH_INVALID.

| | |
|---|----------------|
| module→get_usbCurrent() | YModule |
| module→usbCurrent() module.get_usbCurrent() | |

Returns the current consumed by the module on the USB bus, in milli-amps.

| | |
|--------|--|
| js | function get_usbCurrent() |
| nodejs | function get_usbCurrent() |
| php | function get_usbCurrent() |
| cpp | int get_usbCurrent() |
| m | -(int) usbCurrent |
| pas | function get_usbCurrent() : LongInt |
| vb | function get_usbCurrent() As Integer |
| cs | int get_usbCurrent() |
| java | int get_usbCurrent() |
| py | def get_usbCurrent() |
| cmd | YModule target get_usbCurrent |

Returns :

an integer corresponding to the current consumed by the module on the USB bus, in milli-amps

On failure, throws an exception or returns **Y_USBCURRENT_INVALID**.

module→get(userData)
module→userData()module.get(userData)**YModule**

Returns the value of the userData attribute, as previously stored using method set(userData).

| | |
|---------|---|
| js | function get(userData) |
| node.js | function get(userData) |
| php | function get(userData) |
| cpp | void * get(userData) |
| m | -(void*) userData |
| pas | function get(userData) : TObject |
| vb | function get(userData) As Object |
| cs | object get(userData) |
| java | Object get(userData) |
| py | def get(userData) |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

module→isOnline()|module.isOnline()**YModule**

Checks if the module is currently reachable, without raising any error.

| | |
|---------|---|
| js | function isOnline () |
| node.js | function isOnline () |
| php | function isOnline () |
| cpp | bool isOnline () |
| m | -(BOOL) isOnline |
| pas | function isOnline (): boolean |
| vb | function isOnline () As Boolean |
| cs | bool isOnline () |
| java | boolean isOnline () |
| py | def isOnline () |

If there are valid cached values for the module, that have not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the requested module.

Returns :

true if the module can be reached, and false otherwise

module→isOnline_async()**YModule**

Checks if the module is currently reachable, without raising any error.

```
js  function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there are valid cached values for the module, that have not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the requested module.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox Javascript VM that does not implement context switching during blocking I/O calls.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving module object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

module→load()module.load()**YModule**

Preloads the module cache with a specified validity duration.

| | |
|----------------------|--|
| <code>js</code> | <code>function load(msValidity)</code> |
| <code>node.js</code> | <code>function load(msValidity)</code> |
| <code>php</code> | <code>function load(\$msValidity)</code> |
| <code>cpp</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>m</code> | <code>-(YRETCODE) load : (int) msValidity</code> |
| <code>pas</code> | <code>function load(msValidity: integer): YRETCODE</code> |
| <code>vb</code> | <code>function load(ByVal msValidity As Integer) As YRETCODE</code> |
| <code>cs</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>java</code> | <code>int load(long msValidity)</code> |
| <code>py</code> | <code>def load(msValidity)</code> |

By default, whenever accessing a device, all module attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded module parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

module→load_async()

YModule

Preloads the module cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all module attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

msValidity an integer corresponding to the validity of the loaded module parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving module object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

module→nextModule()|module.nextModule()**YModule**

Continues the module enumeration started using `yFirstModule()`.

| | |
|---------|--|
| js | function nextModule() |
| node.js | function nextModule() |
| php | function nextModule() |
| cpp | YModule * nextModule() |
| m | -(YModule *) nextModule |
| pas | function nextModule() : TYModule |
| vb | function nextModule() As YModule |
| cs | YModule nextModule() |
| java | YModule nextModule() |
| py | def nextModule() |

Returns :

a pointer to a `YModule` object, corresponding to the next module found, or a `null` pointer if there are no more modules to enumerate.

module→reboot()module.reboot()**YModule**

Schedules a simple module reboot after the given number of seconds.

```
js function reboot( secBeforeReboot)
nodejs function reboot( secBeforeReboot)
php function reboot( $secBeforeReboot)
cpp int reboot( int secBeforeReboot)
m -(int) reboot : (int) secBeforeReboot
pas function reboot( secBeforeReboot: LongInt): LongInt
vb function reboot( ) As Integer
cs int reboot( int secBeforeReboot)
java int reboot( int secBeforeReboot)
py def reboot( secBeforeReboot)
cmd YModule target reboot secBeforeReboot
```

Parameters :

secBeforeReboot number of seconds before rebooting

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

**module→registerLogCallback()
module.registerLogCallback()****YModule**

todo

| | |
|-----|---|
| cpp | void registerLogCallback(YModuleLogCallback callback) |
| m | -(void) registerLogCallback : (YModuleLogCallback) callback |
| vb | function registerLogCallback(ByVal callback As YModuleLogCallback) As Integer |
| cs | int registerLogCallback(LogCallback callback) |
| py | def registerLogCallback(callback) |

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

module→revertFromFlash()
module.revertFromFlash()**YModule**

Reloads the settings stored in the nonvolatile memory, as when the module is powered on.

| | |
|---------|--|
| js | function revertFromFlash() |
| node.js | function revertFromFlash() |
| php | function revertFromFlash() |
| cpp | int revertFromFlash() |
| m | -(int) revertFromFlash |
| pas | function revertFromFlash(): LongInt |
| vb | function revertFromFlash() As Integer |
| cs | int revertFromFlash() |
| java | int revertFromFlash() |
| py | def revertFromFlash() |
| cmd | YModule target revertFromFlash |

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

module→saveToFlash()module.saveToFlash()**YModule**

Saves current settings in the nonvolatile memory of the module.

| | |
|---------|---|
| js | function saveToFlash() |
| node.js | function saveToFlash() |
| php | function saveToFlash() |
| cpp | int saveToFlash() |
| m | -(int) saveToFlash |
| pas | function saveToFlash() : LongInt |
| vb | function saveToFlash() As Integer |
| cs | int saveToFlash() |
| java | int saveToFlash() |
| py | def saveToFlash() |
| cmd | YModule target saveToFlash |

Warning: the number of allowed save operations during a module life is limited (about 100000 cycles). Do not call this function within a loop.

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

module→set_beacon()
module→setBeacon()**module.set_beacon()****YModule**

Turns on or off the module localization beacon.

| | |
|---------|---|
| js | function set_beacon(newval) |
| node.js | function set_beacon(newval) |
| php | function set_beacon(\$newval) |
| cpp | int set_beacon(Y_BEACON_enum newval) |
| m | -(int) setBeacon : (Y_BEACON_enum) newval |
| pas | function set_beacon(newval: Integer): integer |
| vb | function set_beacon(ByVal newval As Integer) As Integer |
| cs | int set_beacon(int newval) |
| java | int set_beacon(int newval) |
| py | def set_beacon(newval) |
| cmd | YModule target set_beacon newval |

Parameters :

newval either Y_BEACON_OFF or Y_BEACON_ON

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

| | |
|--|----------------|
| module->set_logicalName() | YModule |
| module->setLogicalName()module.set_logicalName() | |

Changes the logical name of the module.

| | |
|--------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YModule target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the logical name of the module

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

module→set_luminosity() YModule
module→setLuminosity()module.set_luminosity()

Changes the luminosity of the module informative leds.

| | |
|---------|---|
| js | function set_luminosity(newval) |
| node.js | function set_luminosity(newval) |
| php | function set_luminosity(\$newval) |
| cpp | int set_luminosity(int newval) |
| m | -(int) setLuminosity : (int) newval |
| pas | function set_luminosity(newval: LongInt): integer |
| vb | function set_luminosity(ByVal newval As Integer) As Integer |
| cs | int set_luminosity(int newval) |
| java | int set_luminosity(int newval) |
| py | def set_luminosity(newval) |
| cmd | YModule target set_luminosity newval |

The parameter is a value between 0 and 100. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval an integer corresponding to the luminosity of the module informative leds

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

module→set_usbBandwidth()
module→setUsbBandwidth()
module.set_usbBandwidth()

YModule

Changes the number of USB interfaces used by the module.

| | |
|---------------|---|
| js | function set_usbBandwidth(newval) |
| nodejs | function set_usbBandwidth(newval) |
| php | function set_usbBandwidth(\$newval) |
| cpp | int set_usbBandwidth(Y_USBBANDWIDTH_enum newval) |
| m | -(int) setUsbBandwidth : (Y_USBBANDWIDTH_enum) newval |
| pas | function set_usbBandwidth(newval: Integer): integer |
| vb | function set_usbBandwidth(ByVal newval As Integer) As Integer |
| cs | int set_usbBandwidth(int newval) |
| java | int set_usbBandwidth(int newval) |
| py | def set_usbBandwidth(newval) |
| cmd | YModule target set_usbBandwidth newval |

You must reboot the module after changing this setting.

Parameters :

newval either **Y_USBBANDWIDTH_SIMPLE** or **Y_USBBANDWIDTH_DOUBLE**, according to the number of USB interfaces used by the module

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

module→set(userData) **YModule**
module→setUserData()module.set(userData)

Stores a user context provided as argument in the userData attribute of the function.

```
js   function set(userData) data
node.js function set(userData) data
php  function set(userData) $data
cpp   void set(userData void* data)
m    -(void) setUserData : (void*) data
pas   procedure set(userData data: Tobject)
vb    procedure set(userData ByVal data As Object)
cs    void set(userData object data)
java  void set(userData Object data)
py    def set(userData data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

**module→triggerFirmwareUpdate()
module.triggerFirmwareUpdate()****YModule**

Schedules a module reboot into special firmware update mode.

```
js function triggerFirmwareUpdate( secBeforeReboot)
nodejs function triggerFirmwareUpdate( secBeforeReboot)
php function triggerFirmwareUpdate( $secBeforeReboot)
cpp int triggerFirmwareUpdate( int secBeforeReboot)
m -(int) triggerFirmwareUpdate : (int) secBeforeReboot
pas function triggerFirmwareUpdate( secBeforeReboot: LongInt): LongInt
vb function triggerFirmwareUpdate( ) As Integer
cs int triggerFirmwareUpdate( int secBeforeReboot)
java int triggerFirmwareUpdate( int secBeforeReboot)
py def triggerFirmwareUpdate( secBeforeReboot)
cmd YModule target triggerFirmwareUpdate secBeforeReboot
```

Parameters :

secBeforeReboot number of seconds before rebooting

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

module→wait_async()

YModule

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.26. Network function interface

YNetwork objects provide access to TCP/IP parameters of Yoctopuce modules that include a built-in network interface.

In order to use the functions described here, you should include:

| | |
|---------|---|
| js | <script type='text/javascript' src='yocto_network.js'></script> |
| node.js | var yoctolib = require('yoctolib'); |
| | var YNetwork = yoctolib.YNetwork; |
| php | require_once('yocto_network.php'); |
| cpp | #include "yocto_network.h" |
| m | #import "yocto_network.h" |
| pas | uses yocto_network; |
| vb | yocto_network.vb |
| cs | yocto_network.cs |
| java | import com.yoctopuce.YoctoAPI.YNetwork; |
| py | from yocto_network import * |

Global functions

yFindNetwork(func)

Retrieves a network interface for a given identifier.

yFirstNetwork()

Starts the enumeration of network interfaces currently accessible.

YNetwork methods

network→callbackLogin(username, password)

Connects to the notification callback and saves the credentials required to log into it.

network→describe()

Returns a short text that describes unambiguously the instance of the network interface in the form TYPE (NAME) = SERIAL . FUNCTIONID.

network→get_adminPassword()

Returns a hash string if a password has been set for user "admin", or an empty string otherwise.

network→get_advertisedValue()

Returns the current value of the network interface (no more than 6 characters).

network→get_callbackCredentials()

Returns a hashed version of the notification callback credentials if set, or an empty string otherwise.

network→get_callbackEncoding()

Returns the encoding standard to use for representing notification values.

network→get_callbackMaxDelay()

Returns the maximum waiting time between two callback notifications, in seconds.

network→get_callbackMethod()

Returns the HTTP method used to notify callbacks for significant state changes.

network→get_callbackMinDelay()

Returns the minimum waiting time between two callback notifications, in seconds.

network→get_callbackUrl()

Returns the callback URL to notify of significant state changes.

network→get_discoverable()

Returns the activation state of the multicast announce protocols to allow easy discovery of the module in the network neighborhood (uPnP/Bonjour protocol).

3. Reference

| | |
|--|--|
| network→get_errorMessage() | Returns the error message of the latest error with the network interface. |
| network→get_errorType() | Returns the numerical error code of the latest error with the network interface. |
| network→get_friendlyName() | Returns a global identifier of the network interface in the format MODULE_NAME . FUNCTION_NAME. |
| network→get_functionDescriptor() | Returns a unique identifier of type YFUN_DESCR corresponding to the function. |
| network→get_functionId() | Returns the hardware identifier of the network interface, without reference to the module. |
| network→get_hardwareId() | Returns the unique hardware identifier of the network interface in the form SERIAL . FUNCTIONID. |
| network→get_ipAddress() | Returns the IP address currently in use by the device. |
| network→get_logicalName() | Returns the logical name of the network interface. |
| network→get_macAddress() | Returns the MAC address of the network interface. |
| network→get_module() | Gets the YModule object for the device on which the function is located. |
| network→get_module_async(callback, context) | Gets the YModule object for the device on which the function is located (asynchronous version). |
| network→get_poeCurrent() | Returns the current consumed by the module from Power-over-Ethernet (PoE), in milli-amps. |
| network→get_primaryDNS() | Returns the IP address of the primary name server to be used by the module. |
| network→get_readiness() | Returns the current established working mode of the network interface. |
| network→get_router() | Returns the IP address of the router on the device subnet (default gateway). |
| network→get_secondaryDNS() | Returns the IP address of the secondary name server to be used by the module. |
| network→get_subnetMask() | Returns the subnet mask currently used by the device. |
| network→get_userData() | Returns the value of the userData attribute, as previously stored using method set(userData). |
| network→get_userPassword() | Returns a hash string if a password has been set for "user" user, or an empty string otherwise. |
| network→get_wwwWatchdogDelay() | Returns the allowed downtime of the WWW link (in seconds) before triggering an automated reboot to try to recover Internet connectivity. |
| network→isOnline() | Checks if the network interface is currently reachable, without raising any error. |
| network→isOnline_async(callback, context) | Checks if the network interface is currently reachable, without raising any error (asynchronous version). |

network→load(msValidity)

Preloads the network interface cache with a specified validity duration.

network→load_async(msValidity, callback, context)

Preloads the network interface cache with a specified validity duration (asynchronous version).

network→nextNetwork()

Continues the enumeration of network interfaces started using `yFirstNetwork()`.

network→ping(host)

Pings `str_host` to test the network connectivity.

network→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

network→set_adminPassword(newval)

Changes the password for the "admin" user.

network→set_callbackCredentials(newval)

Changes the credentials required to connect to the callback address.

network→set_callbackEncoding(newval)

Changes the encoding standard to use for representing notification values.

network→set_callbackMaxDelay(newval)

Changes the maximum waiting time between two callback notifications, in seconds.

network→set_callbackMethod(newval)

Changes the HTTP method used to notify callbacks for significant state changes.

network→set_callbackMinDelay(newval)

Changes the minimum waiting time between two callback notifications, in seconds.

network→set_callbackUrl(newval)

Changes the callback URL to notify significant state changes.

network→set_discoverable(newval)

Changes the activation state of the multicast announce protocols to allow easy discovery of the module in the network neighborhood (uPnP/Bonjour protocol).

network→set_logicalName(newval)

Changes the logical name of the network interface.

network→set_primaryDNS(newval)

Changes the IP address of the primary name server to be used by the module.

network→set_secondaryDNS(newval)

Changes the IP address of the secondary name server to be used by the module.

network→set_userData(data)

Stores a user context provided as argument in the `userData` attribute of the function.

network→set_userPassword(newval)

Changes the password for the "user" user.

network→set_wwwWatchdogDelay(newval)

Changes the allowed downtime of the WWW link (in seconds) before triggering an automated reboot to try to recover Internet connectivity.

network→useDHCP(fallbackIpAddr, fallbackSubnetMaskLen, fallbackRouter)

Changes the configuration of the network interface to enable the use of an IP address received from a DHCP server.

network→useStaticIP(ipAddress, subnetMaskLen, router)

Changes the configuration of the network interface to use a static IP address.

network→wait_async(callback, context)

3. Reference

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YNetwork.FindNetwork() yFindNetwork()YNetwork.FindNetwork()

YNetwork

Retrieves a network interface for a given identifier.

| | |
|----------------------|---|
| <code>js</code> | <code>function yFindNetwork(func)</code> |
| <code>node.js</code> | <code>function FindNetwork(func)</code> |
| <code>php</code> | <code>function yFindNetwork(\$func)</code> |
| <code>cpp</code> | <code>YNetwork* yFindNetwork(const string& func)</code> |
| <code>m</code> | <code>YNetwork* yFindNetwork(NSString* func)</code> |
| <code>pas</code> | <code>function yFindNetwork(func: string): TYNetwork</code> |
| <code>vb</code> | <code>function yFindNetwork(ByVal func As String) As YNetwork</code> |
| <code>cs</code> | <code>YNetwork FindNetwork(string func)</code> |
| <code>java</code> | <code>YNetwork FindNetwork(String func)</code> |
| <code>py</code> | <code>def FindNetwork(func)</code> |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the network interface is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YNetwork.isOnline()` to test if the network interface is indeed online at a given time. In case of ambiguity when looking for a network interface by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the network interface

Returns :

a `YNetwork` object allowing you to drive the network interface.

YNetwork.FirstNetwork()**YNetwork****yFirstNetwork() YNetwork.FirstNetwork()**

Starts the enumeration of network interfaces currently accessible.

| | |
|---------|--|
| js | function yFirstNetwork() |
| node.js | function FirstNetwork() |
| php | function yFirstNetwork() |
| cpp | YNetwork* yFirstNetwork() |
| m | YNetwork* yFirstNetwork() |
| pas | function yFirstNetwork() : TYNetwork |
| vb | function yFirstNetwork() As YNetwork |
| cs | YNetwork FirstNetwork() |
| java | YNetwork FirstNetwork() |
| py | def FirstNetwork() |

Use the method `YNetwork.nextNetwork()` to iterate on next network interfaces.

Returns :

a pointer to a `YNetwork` object, corresponding to the first network interface currently online, or a null pointer if there are none.

network→callbackLogin()network.callbackLogin()**YNetwork**

Connects to the notification callback and saves the credentials required to log into it.

```

js   function callbackLogin( username, password)
node.js function callbackLogin( username, password)
php  function callbackLogin( $username, $password)
cpp   int callbackLogin( string username, string password)
m    -(int) callbackLogin : (NSString*) username : (NSString*) password
pas   function callbackLogin( username: string, password: string): integer
vb    function callbackLogin( ByVal username As String,
                           ByVal password As String) As Integer
cs    int callbackLogin( string username, string password)
java  int callbackLogin( String username, String password)
py    def callbackLogin( username, password)
cmd   YNetwork target callbackLogin username password

```

The password is not stored into the module, only a hashed copy of the credentials are saved. Remember to call the saveToFlash() method of the module if the modification must be kept.

Parameters :

username username required to log to the callback
password password required to log to the callback

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→describe()network.describe()**YNetwork**

Returns a short text that describes unambiguously the instance of the network interface in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the network interface (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

network→get_adminPassword()
network→adminPassword()
network.get_adminPassword()

YNetwork

Returns a hash string if a password has been set for user "admin", or an empty string otherwise.

| | |
|---------|---|
| js | function get_adminPassword() |
| node.js | function get_adminPassword() |
| php | function get_adminPassword() |
| cpp | string get_adminPassword() |
| m | -(NSString*) adminPassword |
| pas | function get_adminPassword(): string |
| vb | function get_adminPassword() As String |
| cs | string get_adminPassword() |
| java | String get_adminPassword() |
| py | def get_adminPassword() |
| cmd | YNetwork target get_adminPassword |

Returns :

a string corresponding to a hash string if a password has been set for user "admin", or an empty string otherwise

On failure, throws an exception or returns Y_ADMINPASSWORD_INVALID.

network→get_advertisedValue()
network→advertisedValue()
network.get_advertisedValue()**YNetwork**

Returns the current value of the network interface (no more than 6 characters).

| | |
|--------|---|
| js | function get_advertisedValue() |
| nodejs | function get_advertisedValue() |
| php | function get_advertisedValue() |
| cpp | string get_advertisedValue() |
| m | -(NSString*) advertisedValue |
| pas | function get_advertisedValue(): string |
| vb | function get_advertisedValue() As String |
| cs | string get_advertisedValue() |
| java | String get_advertisedValue() |
| py | def get_advertisedValue() |
| cmd | YNetwork target get_advertisedValue |

Returns :

a string corresponding to the current value of the network interface (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

network→get_callbackCredentials()
network→callbackCredentials()
network.get_callbackCredentials()

YNetwork

Returns a hashed version of the notification callback credentials if set, or an empty string otherwise.

| | |
|----------------|--|
| js | function get_callbackCredentials() |
| node.js | function get_callbackCredentials() |
| php | function get_callbackCredentials() |
| cpp | string get_callbackCredentials() |
| m | -(NSString*) callbackCredentials |
| pas | function get_callbackCredentials(): string |
| vb | function get_callbackCredentials() As String |
| cs | string get_callbackCredentials() |
| java | String get_callbackCredentials() |
| py | def get_callbackCredentials() |
| cmd | YNetwork target get_callbackCredentials |

Returns :

a string corresponding to a hashed version of the notification callback credentials if set, or an empty string otherwise

On failure, throws an exception or returns **Y_CALLBACKCREDENTIALS_INVALID**.

network→get_callbackEncoding()
network→callbackEncoding()
network.get_callbackEncoding()

YNetwork

Returns the encoding standard to use for representing notification values.

```
js function get_callbackEncoding( )  
nodejs function get_callbackEncoding( )  
php function get_callbackEncoding( )  
cpp Y_CALLBACKENCODING_enum get_callbackEncoding( )  
m -(Y_CALLBACKENCODING_enum) callbackEncoding  
pas function get_callbackEncoding( ): Integer  
vb function get_callbackEncoding( ) As Integer  
cs int get_callbackEncoding( )  
java int get_callbackEncoding( )  
py def get_callbackEncoding( )  
cmd YNetwork target get_callbackEncoding
```

Returns :

a value among Y_CALLBACKENCODING_FORM, Y_CALLBACKENCODING_JSON, Y_CALLBACKENCODING_JSON_ARRAY, Y_CALLBACKENCODING_CSV and Y_CALLBACKENCODING_YOCTO_API corresponding to the encoding standard to use for representing notification values

On failure, throws an exception or returns Y_CALLBACKENCODING_INVALID.

network→get_callbackMaxDelay()
network→callbackMaxDelay()
network.get_callbackMaxDelay()

YNetwork

Returns the maximum waiting time between two callback notifications, in seconds.

| | |
|----------------|--|
| js | function get_callbackMaxDelay() |
| node.js | function get_callbackMaxDelay() |
| php | function get_callbackMaxDelay() |
| cpp | int get_callbackMaxDelay() |
| m | -(int) callbackMaxDelay |
| pas | function get_callbackMaxDelay() : LongInt |
| vb | function get_callbackMaxDelay() As Integer |
| cs | int get_callbackMaxDelay() |
| java | int get_callbackMaxDelay() |
| py | def get_callbackMaxDelay() |
| cmd | YNetwork target get_callbackMaxDelay |

Returns :

an integer corresponding to the maximum waiting time between two callback notifications, in seconds

On failure, throws an exception or returns **Y_CALLBACKMAXDELAY_INVALID**.

**network→get_callbackMethod()
network→callbackMethod()
network.get_callbackMethod()****YNetwork**

Returns the HTTP method used to notify callbacks for significant state changes.

| | |
|--------|---|
| js | function get_callbackMethod() |
| nodejs | function get_callbackMethod() |
| php | function get_callbackMethod() |
| cpp | Y_CALLBACKMETHOD_enum get_callbackMethod() |
| m | -(Y_CALLBACKMETHOD_enum) callbackMethod |
| pas | function get_callbackMethod(): Integer |
| vb | function get_callbackMethod() As Integer |
| cs | int get_callbackMethod() |
| java | int get_callbackMethod() |
| py | def get_callbackMethod() |
| cmd | YNetwork target get_callbackMethod |

Returns :

a value among Y_CALLBACKMETHOD_POST, Y_CALLBACKMETHOD_GET and Y_CALLBACKMETHOD_PUT corresponding to the HTTP method used to notify callbacks for significant state changes

On failure, throws an exception or returns Y_CALLBACKMETHOD_INVALID.

network→get_callbackMinDelay()
network→callbackMinDelay()
network.get_callbackMinDelay()

YNetwork

Returns the minimum waiting time between two callback notifications, in seconds.

| | |
|----------------------|--|
| <code>js</code> | <code>function get_callbackMinDelay()</code> |
| <code>node.js</code> | <code>function get_callbackMinDelay()</code> |
| <code>php</code> | <code>function get_callbackMinDelay()</code> |
| <code>cpp</code> | <code>int get_callbackMinDelay()</code> |
| <code>m</code> | <code>-(int) callbackMinDelay</code> |
| <code>pas</code> | <code>function get_callbackMinDelay(): LongInt</code> |
| <code>vb</code> | <code>function get_callbackMinDelay() As Integer</code> |
| <code>cs</code> | <code>int get_callbackMinDelay()</code> |
| <code>java</code> | <code>int get_callbackMinDelay()</code> |
| <code>py</code> | <code>def get_callbackMinDelay()</code> |
| <code>cmd</code> | <code>YNetwork target get_callbackMinDelay</code> |

Returns :

an integer corresponding to the minimum waiting time between two callback notifications, in seconds

On failure, throws an exception or returns `Y_CALLBACKMINDELAY_INVALID`.

network→get_callbackUrl()**YNetwork****network→callbackUrl()network.get_callbackUrl()**

Returns the callback URL to notify of significant state changes.

| | |
|---------|--|
| js | function get_callbackUrl() |
| node.js | function get_callbackUrl() |
| php | function get_callbackUrl() |
| cpp | string get_callbackUrl() |
| m | - (NSString*) callbackUrl |
| pas | function get_callbackUrl() : string |
| vb | function get_callbackUrl() As String |
| cs | string get_callbackUrl() |
| java | String get_callbackUrl() |
| py | def get_callbackUrl() |
| cmd | YNetwork target get_callbackUrl |

Returns :

a string corresponding to the callback URL to notify of significant state changes

On failure, throws an exception or returns Y_CALLBACKURL_INVALID.

network→get_discoverable()**YNetwork****network→discoverable()network.get_discoverable()**

Returns the activation state of the multicast announce protocols to allow easy discovery of the module in the network neighborhood (uPnP/Bonjour protocol).

| | |
|---------|--|
| js | function get_discoverable() |
| node.js | function get_discoverable() |
| php | function get_discoverable() |
| cpp | Y_DISCOVERABLE_enum get_discoverable() |
| m | -(Y_DISCOVERABLE_enum) discoverable |
| pas | function get_discoverable() : Integer |
| vb | function get_discoverable() As Integer |
| cs | int get_discoverable() |
| java | int get_discoverable() |
| py | def get_discoverable() |
| cmd | YNetwork target get_discoverable |

Returns :

either Y_DISCOVERABLE_FALSE or Y_DISCOVERABLE_TRUE, according to the activation state of the multicast announce protocols to allow easy discovery of the module in the network neighborhood (uPnP/Bonjour protocol)

On failure, throws an exception or returns Y_DISCOVERABLE_INVALID.

network→get_errorMessage()
network→errorMessage()
network.get_errorMessage()**YNetwork**

Returns the error message of the latest error with the network interface.

| | |
|--------|--|
| js | function get_errorMessage() |
| nodejs | function get_errorMessage() |
| php | function get_errorMessage() |
| cpp | string get_errorMessage() |
| m | -(NSString*) errorMessage |
| pas | function get_errorMessage(): string |
| vb | function get_errorMessage() As String |
| cs | string get_errorMessage() |
| java | String get_errorMessage() |
| py | def get_errorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the network interface object

network→get_errorType()**YNetwork****network→errorType()network.get_errorType()**

Returns the numerical error code of the latest error with the network interface.

| | |
|--------|--|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType() : YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the network interface object

network→get_friendlyName()**YNetwork****network→friendlyName()network.get_friendlyName()**

Returns a global identifier of the network interface in the format MODULE_NAME.FUNCTION_NAME.

| | |
|--------|------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the network interface if they are defined, otherwise the serial number of the module and the hardware identifier of the network interface (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the network interface using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

network→get_functionDescriptor()
network→functionDescriptor()
network.get_functionDescriptor()

YNetwork

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

network→get_functionId()**YNetwork****network→functionId()network.get_functionId()**

Returns the hardware identifier of the network interface, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the network interface (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

network→get_hardwareId()**YNetwork****network→hardwareId()network.get_hardwareId()**

Returns the unique hardware identifier of the network interface in the form SERIAL.FUNCTIONID.

| | |
|--------|---|
| js | function get_hardwareId() |
| nodejs | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the network interface. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the network interface (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

network→get_ipAddress()**YNetwork****network→ipAddress()network.get_ipAddress()**

Returns the IP address currently in use by the device.

```
js function get_ipAddress( )
node.js function get_ipAddress( )
php function get_ipAddress( )
cpp string get_ipAddress( )
m -(NSString*) ipAddress
pas function get_ipAddress( ): string
vb function get_ipAddress( ) As String
cs string get_ipAddress( )
java String get_ipAddress( )
py def get_ipAddress( )
cmd YNetwork target get_ipAddress
```

The address may have been configured statically, or provided by a DHCP server.

Returns :

a string corresponding to the IP address currently in use by the device

On failure, throws an exception or returns Y_IPADDRESS_INVALID.

network→get_logicalName()**YNetwork****network→logicalName()network.get_logicalName()**

Returns the logical name of the network interface.

| | |
|--------|--|
| js | function get_logicalName() |
| nodejs | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | -(NSString*) logicalName |
| pas | function get_logicalName(): string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YNetwork target get_logicalName |

Returns :

a string corresponding to the logical name of the network interface. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

network→get_macAddress()
network→macAddress()network.get_macAddress()**YNetwork**

Returns the MAC address of the network interface.

```
js function get_macAddress( )
node.js function get_macAddress( )
php function get_macAddress( )
cpp string get_macAddress( )
m -(NSString*) macAddress
pas function get_macAddress( ): string
vb function get_macAddress( ) As String
cs string get_macAddress( )
java String get_macAddress( )
py def get_macAddress( )
cmd YNetwork target get_macAddress
```

The MAC address is also available on a sticker on the module, in both numeric and barcode forms.

Returns :

a string corresponding to the MAC address of the network interface

On failure, throws an exception or returns Y_MACADDRESS_INVALID.

network→get_module()**YNetwork****network→module()network.get_module()**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

network→get_module_async()
network→module_async()**YNetwork**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

network→get_poeCurrent()**YNetwork****network→poeCurrent()network.get_poeCurrent()**

Returns the current consumed by the module from Power-over-Ethernet (PoE), in milli-amps.

```
js function get_poeCurrent( )
nodejs function get_poeCurrent( )
php function get_poeCurrent( )
cpp int get_poeCurrent( )
m -(int) poeCurrent
pas function get_poeCurrent( ): LongInt
vb function get_poeCurrent( ) As Integer
cs int get_poeCurrent( )
java int get_poeCurrent( )
py def get_poeCurrent( )
cmd YNetwork target get_poeCurrent
```

The current consumption is measured after converting PoE source to 5 Volt, and should never exceed 1800 mA.

Returns :

an integer corresponding to the current consumed by the module from Power-over-Ethernet (PoE), in milli-amps

On failure, throws an exception or returns `Y_POECURRENT_INVALID`.

network→get_primaryDNS()**YNetwork****network→primaryDNS()network.get_primaryDNS()**

Returns the IP address of the primary name server to be used by the module.

| | |
|---------|---|
| js | function get_primaryDNS() |
| node.js | function get_primaryDNS() |
| php | function get_primaryDNS() |
| cpp | string get_primaryDNS() |
| m | - (NSString*) primaryDNS |
| pas | function get_primaryDNS(): string |
| vb | function get_primaryDNS() As String |
| cs | string get_primaryDNS() |
| java | String get_primaryDNS() |
| py | def get_primaryDNS() |
| cmd | YNetwork target get_primaryDNS |

Returns :

a string corresponding to the IP address of the primary name server to be used by the module

On failure, throws an exception or returns **Y_PRIMARYDNS_INVALID**.

network→get_readiness() network→readiness()network.get_readiness()

YNetwork

Returns the current established working mode of the network interface.

| | |
|--------|--|
| js | function get_readiness() |
| nodejs | function get_readiness() |
| php | function get_readiness() |
| cpp | Y_READINESS_enum get_readiness() |
| m | -(Y_READINESS_enum) readiness |
| pas | function get_readiness() : Integer |
| vb | function get_readiness() As Integer |
| cs | int get_readiness() |
| java | int getReadiness() |
| py | def get_readiness() |
| cmd | YNetwork target get_readiness |

Level zero (DOWN_0) means that no hardware link has been detected. Either there is no signal on the network cable, or the selected wireless access point cannot be detected. Level 1 (LIVE_1) is reached when the network is detected, but is not yet connected. For a wireless network, this shows that the requested SSID is present. Level 2 (LINK_2) is reached when the hardware connection is established. For a wired network connection, level 2 means that the cable is attached at both ends. For a connection to a wireless access point, it shows that the security parameters are properly configured. For an ad-hoc wireless connection, it means that there is at least one other device connected on the ad-hoc network. Level 3 (DHCP_3) is reached when an IP address has been obtained using DHCP. Level 4 (DNS_4) is reached when the DNS server is reachable on the network. Level 5 (WWW_5) is reached when global connectivity is demonstrated by properly loading the current time from an NTP server.

Returns :

a value among Y_READINESS_DOWN, Y_READINESS_EXISTS, Y_READINESS_LINKED, Y_READINESS_LAN_OK and Y_READINESS_WWW_OK corresponding to the current established working mode of the network interface

On failure, throws an exception or returns Y_READINESS_INVALID.

network→get_router()
network→router()network.get_router()**YNetwork**

Returns the IP address of the router on the device subnet (default gateway).

| | |
|---------|---|
| js | function get_router() |
| node.js | function get_router() |
| php | function get_router() |
| cpp | string get_router() |
| m | -(NSString*) router |
| pas | function get_router(): string |
| vb | function get_router() As String |
| cs | string get_router() |
| java | String get_router() |
| py | def get_router() |
| cmd | YNetwork target get_router |

Returns :

a string corresponding to the IP address of the router on the device subnet (default gateway)

On failure, throws an exception or returns Y_ROUTER_INVALID.

network→get_secondaryDNS()
network→secondaryDNS()
network.get_secondaryDNS()**YNetwork**

Returns the IP address of the secondary name server to be used by the module.

| | |
|---------------------|---|
| <code>js</code> | function get_secondaryDNS() |
| <code>nodejs</code> | function get_secondaryDNS() |
| <code>php</code> | function get_secondaryDNS() |
| <code>cpp</code> | string get_secondaryDNS() |
| <code>m</code> | -(NSString*) secondaryDNS |
| <code>pas</code> | function get_secondaryDNS() : string |
| <code>vb</code> | function get_secondaryDNS() As String |
| <code>cs</code> | string get_secondaryDNS() |
| <code>java</code> | String get_secondaryDNS() |
| <code>py</code> | def get_secondaryDNS() |
| <code>cmd</code> | YNetwork target get_secondaryDNS |

Returns :

a string corresponding to the IP address of the secondary name server to be used by the module

On failure, throws an exception or returns `Y_SECONDARYDNS_INVALID`.

network→get_subnetMask()**YNetwork****network→subnetMask()network.get_subnetMask()**

Returns the subnet mask currently used by the device.

```
js function get_subnetMask( )
node.js function get_subnetMask( )
php function get_subnetMask( )
cpp string get_subnetMask( )
m -(NSString*) subnetMask
pas function get_subnetMask( ): string
vb function get_subnetMask( ) As String
cs string get_subnetMask( )
java String get_subnetMask( )
py def get_subnetMask( )
cmd YNetwork target get_subnetMask
```

Returns :

a string corresponding to the subnet mask currently used by the device

On failure, throws an exception or returns Y_SUBNETMASK_INVALID.

network→get(userData)**YNetwork****network→userData()network.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|---|
| js | <code>function get(userData) </code> |
| nodejs | <code>function get(userData) </code> |
| php | <code>function get(userData) </code> |
| cpp | <code>void * get(userData) </code> |
| m | <code>-(void*) userData</code> |
| pas | <code>function get(userData): Tobject</code> |
| vb | <code>function get(userData) As Object</code> |
| cs | <code>object get(userData) </code> |
| java | <code>Object get(userData) </code> |
| py | <code>def get(userData) </code> |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

network→get_userPassword()
network→userPassword()
network.get_userPassword()**YNetwork**

Returns a hash string if a password has been set for "user" user, or an empty string otherwise.

| | |
|--------|--|
| js | function get_userPassword() |
| nodejs | function get_userPassword() |
| php | function get_userPassword() |
| cpp | string get_userPassword() |
| m | -(NSString*) userPassword |
| pas | function get_userPassword(): string |
| vb | function get_userPassword() As String |
| cs | string get_userPassword() |
| java | String get_userPassword() |
| py | def get_userPassword() |
| cmd | YNetwork target get_userPassword |

Returns :

a string corresponding to a hash string if a password has been set for "user" user, or an empty string otherwise

On failure, throws an exception or returns Y_USERPASSWORD_INVALID.

network→get_wwwWatchdogDelay()
network→wwwWatchdogDelay()
network.get_wwwWatchdogDelay()

YNetwork

Returns the allowed downtime of the WWW link (in seconds) before triggering an automated reboot to try to recover Internet connectivity.

| | |
|---------------|--|
| js | function get_wwwWatchdogDelay() |
| nodejs | function get_wwwWatchdogDelay() |
| php | function get_wwwWatchdogDelay() |
| cpp | int get_wwwWatchdogDelay() |
| m | -(int) wwwWatchdogDelay |
| pas | function get_wwwWatchdogDelay(): LongInt |
| vb | function get_wwwWatchdogDelay() As Integer |
| cs | int get_wwwWatchdogDelay() |
| java | int get_wwwWatchdogDelay() |
| py | def get_wwwWatchdogDelay() |
| cmd | YNetwork target get_wwwWatchdogDelay |

A zero value disables automated reboot in case of Internet connectivity loss.

Returns :

an integer corresponding to the allowed downtime of the WWW link (in seconds) before triggering an automated reboot to try to recover Internet connectivity

On failure, throws an exception or returns **Y_WWWWATCHDOGDELAY_INVALID**.

network→isOnline()network.isOnline()**YNetwork**

Checks if the network interface is currently reachable, without raising any error.

| | |
|--------|---|
| js | function isOnline () |
| nodejs | function isOnline () |
| php | function isOnline () |
| cpp | bool isOnline () |
| m | - (BOOL) isOnline |
| pas | function isOnline (): boolean |
| vb | function isOnline () As Boolean |
| cs | bool isOnline () |
| java | boolean isOnline () |
| py | def isOnline () |

If there is a cached value for the network interface in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the network interface.

Returns :

true if the network interface can be reached, and false otherwise

network→isOnline_async()

YNetwork

Checks if the network interface is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the network interface in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

network→load()|network.load()

YNetwork

Preloads the network interface cache with a specified validity duration.

```
js function load( msValidity)
nodejs function load( msValidity)
php function load( $msValidity)
cpp YRETCODE load( int msValidity)
m -(YRETCODE) load : (int) msValidity
pas function load( msValidity: integer): YRETCODE
vb function load( ByVal msValidity As Integer) As YRETCODE
cs YRETCODE load( int msValidity)
java int load( long msValidity)
py def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

network→load_async()

YNetwork

Preloads the network interface cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

network→nextNetwork()network.nextNetwork()**YNetwork**

Continues the enumeration of network interfaces started using `yFirstNetwork()`.

| | |
|--------|---|
| js | function nextNetwork() |
| nodejs | function nextNetwork() |
| php | function nextNetwork() |
| cpp | YNetwork * nextNetwork() |
| m | -(YNetwork*) nextNetwork |
| pas | function nextNetwork() : TYNetwork |
| vb | function nextNetwork() As YNetwork |
| cs | YNetwork nextNetwork() |
| java | YNetwork nextNetwork() |
| py | def nextNetwork() |

Returns :

a pointer to a `YNetwork` object, corresponding to a network interface currently online, or a `null` pointer if there are no more network interfaces to enumerate.

network→ping()network.ping()

YNetwork

Pings str_host to test the network connectivity.

```
js function ping( host)
nodejs function ping( host)
php function ping( $host)
cpp string ping( string host)
m -(NSString*) ping : (NSString*) host
pas function ping( host: string): string
vb function ping( ) As String
cs string ping( string host)
java String ping( String host)
py def ping( host)
cmd YNetwork target ping host
```

Sends four ICMP ECHO_REQUEST requests from the module to the target str_host. This method returns a string with the result of the 4 ICMP ECHO_REQUEST requests.

Parameters :

host the hostname or the IP address of the target

Returns :

a string with the result of the ping.

**network→registerValueCallback()
network.registerValueCallback()****YNetwork**

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YNetworkValueCallback callback )
m    -(int) registerValueCallback : (YNetworkValueCallback) callback
pas   function registerValueCallback( callback: TYNetworkValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

network→set_adminPassword()
network→setAdminPassword()
network.set_adminPassword()

YNetwork

Changes the password for the "admin" user.

| | |
|---------|---|
| js | function set_adminPassword(newval) |
| node.js | function set_adminPassword(newval) |
| php | function set_adminPassword(\$newval) |
| cpp | int set_adminPassword(const string& newval) |
| m | -(int) setAdminPassword : (NSString*) newval |
| pas | function set_adminPassword(newval: string): integer |
| vb | function set_adminPassword(ByVal newval As String) As Integer |
| cs | int set_adminPassword(string newval) |
| java | int set_adminPassword(String newval) |
| py | def set_adminPassword(newval) |
| cmd | YNetwork target set_adminPassword newval |

This password becomes instantly required to perform any change of the module state. If the specified value is an empty string, a password is not required anymore. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the password for the "admin" user

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_callbackCredentials()
network→setCallbackCredentials()
network.set_callbackCredentials()

YNetwork

Changes the credentials required to connect to the callback address.

| | |
|--------|---|
| js | function set_callbackCredentials(newval) |
| nodejs | function set_callbackCredentials(newval) |
| php | function set_callbackCredentials(\$newval) |
| cpp | int set_callbackCredentials(const string& newval) |
| m | - (int) setCallbackCredentials : (NSString*) newval |
| pas | function set_callbackCredentials(newval: string): integer |
| vb | function set_callbackCredentials(ByVal newval As String) As Integer |
| cs | int set_callbackCredentials(string newval) |
| java | int set_callbackCredentials(String newval) |
| py | def set_callbackCredentials(newval) |
| cmd | YNetwork target set_callbackCredentials newval |

The credentials must be provided as returned by function `get_callbackCredentials`, in the form `username:hash`. The method used to compute the hash varies according to the authentication scheme implemented by the callback. For Basic authentication, the hash is the MD5 of the string `username:password`. For Digest authentication, the hash is the MD5 of the string `username:realm:password`. For a simpler way to configure callback credentials, use function `callbackLogin` instead. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the credentials required to connect to the callback address

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_callbackEncoding()
network→setCallbackEncoding()
network.set_callbackEncoding()

YNetwork

Changes the encoding standard to use for representing notification values.

| | |
|---------------|---|
| js | function set_callbackEncoding(newval) |
| nodejs | function set_callbackEncoding(newval) |
| php | function set_callbackEncoding(\$newval) |
| cpp | int set_callbackEncoding(Y_CALLBACKENCODING_enum newval) |
| m | -(int) setCallbackEncoding : (Y_CALLBACKENCODING_enum) newval |
| pas | function set_callbackEncoding(newval: Integer): integer |
| vb | function set_callbackEncoding(ByVal newval As Integer) As Integer |
| cs | int set_callbackEncoding(int newval) |
| java | int set_callbackEncoding(int newval) |
| py | def set_callbackEncoding(newval) |
| cmd | YNetwork target set_callbackEncoding newval |

Parameters :

newval a value among `Y_CALLBACKENCODING_FORM`, `Y_CALLBACKENCODING_JSON`, `Y_CALLBACKENCODING_JSON_ARRAY`, `Y_CALLBACKENCODING_CSV` and `Y_CALLBACKENCODING_YOCOTO_API` corresponding to the encoding standard to use for representing notification values

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_callbackMaxDelay()
network→setCallbackMaxDelay()
network.set_callbackMaxDelay()

YNetwork

Changes the maximum waiting time between two callback notifications, in seconds.

```
js function set_callbackMaxDelay( newval)
nodejs function set_callbackMaxDelay( newval)
php function set_callbackMaxDelay( $newval)
cpp int set_callbackMaxDelay( int newval)
m -(int) setCallbackMaxDelay : (int) newval
pas function set_callbackMaxDelay( newval: LongInt): integer
vb function set_callbackMaxDelay( ByVal newval As Integer) As Integer
cs int set_callbackMaxDelay( int newval)
java int set_callbackMaxDelay( int newval)
py def set_callbackMaxDelay( newval)
cmd YNetwork target set_callbackMaxDelay newval
```

Parameters :

newval an integer corresponding to the maximum waiting time between two callback notifications, in seconds

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_callbackMethod()
network→setCallbackMethod()
network.set_callbackMethod()

YNetwork

Changes the HTTP method used to notify callbacks for significant state changes.

| | |
|---------------|---|
| js | function set_callbackMethod(newval) |
| nodejs | function set_callbackMethod(newval) |
| php | function set_callbackMethod(\$newval) |
| cpp | int set_callbackMethod(Y_CALLBACKMETHOD_enum newval) |
| m | -(int) setCallbackMethod : (Y_CALLBACKMETHOD_enum) newval |
| pas | function set_callbackMethod(newval: Integer): integer |
| vb | function set_callbackMethod(ByVal newval As Integer) As Integer |
| cs | int set_callbackMethod(int newval) |
| java | int set_callbackMethod(int newval) |
| py | def set_callbackMethod(newval) |
| cmd | YNetwork target set_callbackMethod newval |

Parameters :

newval a value among `Y_CALLBACKMETHOD_POST`, `Y_CALLBACKMETHOD_GET` and `Y_CALLBACKMETHOD_PUT` corresponding to the HTTP method used to notify callbacks for significant state changes

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_callbackMinDelay()
network→setCallbackMinDelay()
network.set_callbackMinDelay()

YNetwork

Changes the minimum waiting time between two callback notifications, in seconds.

```
js function set_callbackMinDelay( newval)
nodejs function set_callbackMinDelay( newval)
php function set_callbackMinDelay( $newval)
cpp int set_callbackMinDelay( int newval)
m -(int) setCallbackMinDelay : (int) newval
pas function set_callbackMinDelay( newval: LongInt): integer
vb function set_callbackMinDelay( ByVal newval As Integer) As Integer
cs int set_callbackMinDelay( int newval)
java int set_callbackMinDelay( int newval)
py def set_callbackMinDelay( newval)
cmd YNetwork target set_callbackMinDelay newval
```

Parameters :

newval an integer corresponding to the minimum waiting time between two callback notifications, in seconds

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_callbackUrl()**YNetwork****network→setCallbackUrl()network.set_callbackUrl()**

Changes the callback URL to notify significant state changes.

| | |
|---------|---|
| js | function set_callbackUrl(newval) |
| node.js | function set_callbackUrl(newval) |
| php | function set_callbackUrl(\$newval) |
| cpp | int set_callbackUrl(const string& newval) |
| m | -(int) setCallbackUrl : (NSString*) newval |
| pas | function set_callbackUrl(newval: string): integer |
| vb | function set_callbackUrl(ByVal newval As String) As Integer |
| cs | int set_callbackUrl(string newval) |
| java | int set_callbackUrl(String newval) |
| py | def set_callbackUrl(newval) |
| cmd | YNetwork target set_callbackUrl newval |

Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the callback URL to notify significant state changes

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_discoverable()
network→setDiscoverable()
network.set_discoverable()

YNetwork

Changes the activation state of the multicast announce protocols to allow easy discovery of the module in the network neighborhood (uPnP/Bonjour protocol).

```
js function set_discoverable( newval)
nodejs function set_discoverable( newval)
php function set_discoverable( $newval)
cpp int set_discoverable( Y_DISCOVERABLE_enum newval)
m -(int) setDiscoverable : (Y_DISCOVERABLE_enum) newval
pas function set_discoverable( newval: Integer): integer
vb function set_discoverable( ByVal newval As Integer) As Integer
cs int set_discoverable( int newval)
java int set_discoverable( int newval)
py def set_discoverable( newval)
cmd YNetwork target set_discoverable newval
```

Parameters :

newval either **Y_DISCOVERABLE_FALSE** or **Y_DISCOVERABLE_TRUE**, according to the activation state of the multicast announce protocols to allow easy discovery of the module in the network neighborhood (uPnP/Bonjour protocol)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_logicalName()
network→setLogicalName()
network.set_logicalName()

YNetwork

Changes the logical name of the network interface.

| | |
|----------------|---|
| js | function set_logicalName(newval) |
| node.js | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YNetwork target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the network interface.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

network→set_primaryDNS()**YNetwork****network→setPrimaryDNS()network.set_primaryDNS()**

Changes the IP address of the primary name server to be used by the module.

| | |
|---------|--|
| js | function set_primaryDNS(newval) |
| node.js | function set_primaryDNS(newval) |
| php | function set_primaryDNS(\$newval) |
| cpp | int set_primaryDNS(const string& newval) |
| m | - (int) setPrimaryDNS : (NSString*) newval |
| pas | function set_primaryDNS(newval: string): integer |
| vb | function set_primaryDNS(ByVal newval As String) As Integer |
| cs | int set_primaryDNS(string newval) |
| java | int set_primaryDNS(String newval) |
| py | def set_primaryDNS(newval) |
| cmd | YNetwork target set_primaryDNS newval |

When using DHCP, if a value is specified, it overrides the value received from the DHCP server. Remember to call the `saveToFlash()` method and then to reboot the module to apply this setting.

Parameters :

newval a string corresponding to the IP address of the primary name server to be used by the module

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_secondaryDNS()
network→setSecondaryDNS()
network.set_secondaryDNS()

YNetwork

Changes the IP address of the secondary name server to be used by the module.

| | |
|----------------|--|
| js | function set_secondaryDNS(newval) |
| node.js | function set_secondaryDNS(newval) |
| php | function set_secondaryDNS(\$newval) |
| cpp | int set_secondaryDNS(const string& newval) |
| m | -(int) setSecondaryDNS : (NSString*) newval |
| pas | function set_secondaryDNS(newval: string): integer |
| vb | function set_secondaryDNS(ByVal newval As String) As Integer |
| cs | int set_secondaryDNS(string newval) |
| java | int set_secondaryDNS(String newval) |
| py | def set_secondaryDNS(newval) |
| cmd | YNetwork target set_secondaryDNS newval |

When using DHCP, if a value is specified, it overrides the value received from the DHCP server. Remember to call the `saveToFlash()` method and then to reboot the module to apply this setting.

Parameters :

newval a string corresponding to the IP address of the secondary name server to be used by the module

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set(userData)**YNetwork****network→setUserData()network.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

```
js   function setUserData( data)
node.js function setUserData( data)
php  function setUserData( $data)
cpp   void setUserData( void* data)
m    -(void) setUserData : (void*) data
pas   procedure setUserData( data: Tobject)
vb    procedure setUserData( ByVal data As Object)
cs    void setUserData( object data)
java  void setUserData( Object data)
py    def setUserData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

network→set_userPassword()
network→setUserPassword()
network.set_userPassword()

YNetwork

Changes the password for the "user" user.

| | |
|---------|--|
| js | function set_userPassword(newval) |
| node.js | function set_userPassword(newval) |
| php | function set_userPassword(\$newval) |
| cpp | int set_userPassword(const string& newval) |
| m | -(int) setUserPassword : (NSString*) newval |
| pas | function set_userPassword(newval: string): integer |
| vb | function set_userPassword(ByVal newval As String) As Integer |
| cs | int set_userPassword(string newval) |
| java | int set_userPassword(String newval) |
| py | def set_userPassword(newval) |
| cmd | YNetwork target set_userPassword newval |

This password becomes instantly required to perform any use of the module. If the specified value is an empty string, a password is not required anymore. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the password for the "user" user

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_wwwWatchdogDelay()
network→setWwwWatchdogDelay()
network.set_wwwWatchdogDelay()

YNetwork

Changes the allowed downtime of the WWW link (in seconds) before triggering an automated reboot to try to recover Internet connectivity.

```
js function set_wwwWatchdogDelay( newval)
nodejs function set_wwwWatchdogDelay( newval)
php function set_wwwWatchdogDelay( $newval)
cpp int set_wwwWatchdogDelay( int newval)
m -(int) setWwwWatchdogDelay : (int) newval
pas function set_wwwWatchdogDelay( newval: LongInt): integer
vb function set_wwwWatchdogDelay( ByVal newval As Integer) As Integer
cs int set_wwwWatchdogDelay( int newval)
java int set_wwwWatchdogDelay( int newval)
py def set_wwwWatchdogDelay( newval)
cmd YNetwork target set_wwwWatchdogDelay newval
```

A zero value disables automated reboot in case of Internet connectivity loss. The smallest valid non-zero timeout is 90 seconds.

Parameters :

newval an integer corresponding to the allowed downtime of the WWW link (in seconds) before triggering an automated reboot to try to recover Internet connectivity

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→useDHCP()network.useDHCP()**YNetwork**

Changes the configuration of the network interface to enable the use of an IP address received from a DHCP server.

```

js function useDHCP( fallbackIpAddr, fallbackSubnetMaskLen, fallbackRouter)
nodejs function useDHCP( fallbackIpAddr, fallbackSubnetMaskLen, fallbackRouter)
php function useDHCP( $fallbackIpAddr, $fallbackSubnetMaskLen, $fallbackRouter)
cpp int useDHCP( string fallbackIpAddr,
                  int fallbackSubnetMaskLen,
                  string fallbackRouter)

m -(int) useDHCP : (NSString*) fallbackIpAddr
                  : (int) fallbackSubnetMaskLen
                  : (NSString*) fallbackRouter

pas function useDHCP( fallbackIpAddr: string,
                      fallbackSubnetMaskLen: LongInt,
                      fallbackRouter: string): integer

vb function useDHCP( ByVal fallbackIpAddr As String,
                     ByVal fallbackSubnetMaskLen As Integer,
                     ByVal fallbackRouter As String) As Integer

cs int useDHCP( string fallbackIpAddr,
                 int fallbackSubnetMaskLen,
                 string fallbackRouter)

java int useDHCP( String fallbackIpAddr,
                  int fallbackSubnetMaskLen,
                  String fallbackRouter)

py def useDHCP( fallbackIpAddr, fallbackSubnetMaskLen, fallbackRouter)
cmd YNetwork target useDHCP fallbackIpAddr fallbackSubnetMaskLen fallbackRouter

```

Until an address is received from a DHCP server, the module uses the IP parameters specified to this function. Remember to call the `saveToFlash()` method and then to reboot the module to apply this setting.

Parameters :

fallbackIpAddr fallback IP address, to be used when no DHCP reply is received
fallbackSubnetMaskLen fallback subnet mask length when no DHCP reply is received, as an integer (eg. 24 means 255.255.255.0)
fallbackRouter fallback router IP address, to be used when no DHCP reply is received

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→useStaticIP()network.useStaticIP()

YNetwork

Changes the configuration of the network interface to use a static IP address.

```

js function useStaticIP( ipAddress, subnetMaskLen, router)
nodejs function useStaticIP( ipAddress, subnetMaskLen, router)
php function useStaticIP( $ipAddress, $subnetMaskLen, $router)
cpp int useStaticIP( string ipAddress,
                     int subnetMaskLen,
                     string router)
m -(int) useStaticIP : (NSString*) ipAddress
                      : (int) subnetMaskLen
                      : (NSString*) router
pas function useStaticIP( ipAddress: string,
                           subnetMaskLen: LongInt,
                           router: string): integer
vb function useStaticIP( ByVal ipAddress As String,
                        ByVal subnetMaskLen As Integer,
                        ByVal router As String) As Integer
cs int useStaticIP( string ipAddress,
                    int subnetMaskLen,
                    string router)
java int useStaticIP( String ipAddress,
                      int subnetMaskLen,
                      String router)
py def useStaticIP( ipAddress, subnetMaskLen, router)
cmd YNetwork target useStaticIP ipAddress subnetMaskLen router

```

Remember to call the `saveToFlash()` method and then to reboot the module to apply this setting.

Parameters :

ipAddress device IP address
subnetMaskLen subnet mask length, as an integer (eg. 24 means 255.255.255.0)
router router IP address (default gateway)

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→wait_async()

YNetwork

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context )
nodejs function wait_async( callback, context )
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.27. OS control

The OScontrol object allows some control over the operating system running a VirtualHub. OsControl is available on the VirtualHub software only. This feature must be activated at the VirtualHub start up with -o option.

In order to use the functions described here, you should include:

| | |
|--------|---|
| js | <script type='text/javascript' src='yocto_oscontrol.js'></script> |
| nodejs | var yoctolib = require('yoctolib'); |
| | var YOsControl = yoctolib.YOsControl; |
| php | require_once('yocto_oscontrol.php'); |
| cpp | #include "yocto_oscontrol.h" |
| m | #import "yocto_oscontrol.h" |
| pas | uses yocto_oscontrol; |
| vb | yocto_oscontrol.vb |
| cs | yocto_oscontrol.cs |
| java | import com.yoctopuce.YoctoAPI.YOsControl; |
| py | from yocto_oscontrol import * |

Global functions

yFindOsControl(func)

Retrieves OS control for a given identifier.

yFirstOsControl()

Starts the enumeration of OS control currently accessible.

YOsControl methods

oscontrol→describe()

Returns a short text that describes unambiguously the instance of the OS control in the form TYPE (NAME)=SERIAL . FUNCTIONID.

oscontrol→get_advertisedValue()

Returns the current value of the OS control (no more than 6 characters).

oscontrol→get_errorMessage()

Returns the error message of the latest error with the OS control.

oscontrol→get_errorType()

Returns the numerical error code of the latest error with the OS control.

oscontrol→get_friendlyName()

Returns a global identifier of the OS control in the format MODULE_NAME . FUNCTION_NAME.

oscontrol→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

oscontrol→get_functionId()

Returns the hardware identifier of the OS control, without reference to the module.

oscontrol→get_hardwareId()

Returns the unique hardware identifier of the OS control in the form SERIAL . FUNCTIONID.

oscontrol→get_logicalName()

Returns the logical name of the OS control.

oscontrol→get_module()

Gets the YModule object for the device on which the function is located.

oscontrol→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

oscontrol->get_shutdownCountdown()

Returns the remaining number of seconds before the OS shutdown, or zero when no shutdown has been scheduled.

oscontrol->get(userData)

Returns the value of the userData attribute, as previously stored using method set(userData).

oscontrol->isOnline()

Checks if the OS control is currently reachable, without raising any error.

oscontrol->isOnline_async(callback, context)

Checks if the OS control is currently reachable, without raising any error (asynchronous version).

oscontrol->load(msValidity)

Preloads the OS control cache with a specified validity duration.

oscontrol->load_async(msValidity, callback, context)

Preloads the OS control cache with a specified validity duration (asynchronous version).

oscontrol->nextOsControl()

Continues the enumeration of OS control started using yFirstOsControl().

oscontrol->registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

oscontrol->set_logicalName(newval)

Changes the logical name of the OS control.

oscontrol->set(userData)

Stores a user context provided as argument in the userData attribute of the function.

oscontrol->shutdown(secBeforeShutDown)

Schedules an OS shutdown after a given number of seconds.

oscontrol->wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YOsControl.FindOsControl() yFindOsControl()YOsControl.FindOsControl()

YOsControl

Retrieves OS control for a given identifier.

```
js function yFindOsControl( func)
node.js function FindOsControl( func)
php function yFindOsControl( $func)
cpp YOsControl* yFindOsControl( const string& func)
m YOsControl* yFindOsControl( NSString* func)
pas function yFindOsControl( func: string): TYOsControl
vb function yFindOsControl( ByVal func As String) As YOsControl
cs YOsControl FindOsControl( string func)
java YOsControl FindOsControl( String func)
def FindOsControl( func)
py
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the OS control is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YOsControl.isOnline()` to test if the OS control is indeed online at a given time. In case of ambiguity when looking for OS control by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the OS control

Returns :

a `YOsControl` object allowing you to drive the OS control.

YOsControl.FirstOsControl()**YOsControl****yFirstOsControl()YOsControl.FirstOsControl()**

Starts the enumeration of OS control currently accessible.

| | |
|--------|--|
| js | function yFirstOsControl() |
| nodejs | function FirstOsControl() |
| php | function yFirstOsControl() |
| cpp | YOsControl* yFirstOsControl() |
| m | YOsControl* yFirstOsControl() |
| pas | function yFirstOsControl(): TYOsControl |
| vb | function yFirstOsControl() As YOsControl |
| cs | YOsControl FirstOsControl() |
| java | YOsControl FirstOsControl() |
| py | def FirstOsControl() |

Use the method `YOsControl.nextOsControl()` to iterate on next OS control.

Returns :

a pointer to a `YOsControl` object, corresponding to the first OS control currently online, or a null pointer if there are none.

oscontrol→describe()oscontrol.describe()**YOsControl**

Returns a short text that describes unambiguously the instance of the OS control in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the OS control (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

oscontrol→get_advertisedValue()
oscontrol→advertisedValue()
oscontrol.get_advertisedValue()

YOsControl

Returns the current value of the OS control (no more than 6 characters).

```
js function get_advertisedValue( )  
node.js function get_advertisedValue( )  
php function get_advertisedValue( )  
cpp string get_advertisedValue( )  
m -(NSString*) advertisedValue  
pas function get_advertisedValue( ): string  
vb function get_advertisedValue( ) As String  
cs string get_advertisedValue( )  
java String get_advertisedValue( )  
py def get_advertisedValue( )  
cmd YOsControl target get_advertisedValue
```

Returns :

a string corresponding to the current value of the OS control (no more than 6 characters). On failure, throws an exception or returns `Y_ADVERTISEDVALUE_INVALID`.

oscontrol→get_errorMessage()
oscontrol→errorMessage()
oscontrol.get_errorMessage()

YOsControl

Returns the error message of the latest error with the OS control.

| | |
|--------|--|
| js | function get_errorMessage() |
| nodejs | function get_errorMessage() |
| php | function get_errorMessage() |
| cpp | string get_errorMessage() |
| m | -(NSString*) errorMessage |
| pas | function get_errorMessage(): string |
| vb | function get_errorMessage() As String |
| cs | string get_errorMessage() |
| java | String get_errorMessage() |
| py | def get_errorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the OS control object

oscontrol→get_errorType()**YOsControl****oscontrol→errorType()oscontrol.get_errorType()**

Returns the numerical error code of the latest error with the OS control.

| | |
|--------|--|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType() : YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the OS control object

oscontrol→get_friendlyName()
oscontrol→friendlyName()
oscontrol.get_friendlyName()**YOsControl**

Returns a global identifier of the OS control in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the OS control if they are defined, otherwise the serial number of the module and the hardware identifier of the OS control (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the OS control using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

oscontrol→get_functionDescriptor()
oscontrol→functionDescriptor()
oscontrol.get_functionDescriptor()**YOsControl**

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

oscontrol→get_functionId()**YOsControl****oscontrol→functionId()oscontrol.get_functionId()**

Returns the hardware identifier of the OS control, without reference to the module.

| | |
|---------|--|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the OS control (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

oscontrol→get_hardwareId()**YOsControl****oscontrol→hardwareId()oscontrol.get_hardwareId()**

Returns the unique hardware identifier of the OS control in the form SERIAL.FUNCTIONID.

| | |
|--------|---|
| js | function get_hardwareId() |
| nodejs | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the OS control. (for example RELAY01-123456.relay1)

Returns :

a string that uniquely identifies the OS control (ex: RELAY01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

oscontrol→get_logicalName()
oscontrol→logicalName()
oscontrol.get_logicalName()**YOsControl**

Returns the logical name of the OS control.

| | |
|--------|---------------------------------------|
| js | function get_logicalName() |
| nodejs | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | -(NSString*) logicalName |
| pas | function get_logicalName(): string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YOsControl target get_logicalName |

Returns :

a string corresponding to the logical name of the OS control. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

oscontrol→get_module()**YOsControl****oscontrol→module()oscontrol.get_module()**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

oscontrol→get_module_async()
oscontrol→module_async()**YOsControl**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

oscontrol→get_shutdownCountdown()
oscontrol→shutdownCountdown()
oscontrol.get_shutdownCountdown()**YOsControl**

Returns the remaining number of seconds before the OS shutdown, or zero when no shutdown has been scheduled.

```
js function get_shutdownCountdown( )
nodejs function get_shutdownCountdown( )
php function get_shutdownCountdown( )
cpp int get_shutdownCountdown( )
m -(int) shutdownCountdown
pas function get_shutdownCountdown( ): LongInt
vb function get_shutdownCountdown( ) As Integer
cs int get_shutdownCountdown( )
java int get_shutdownCountdown( )
py def get_shutdownCountdown( )
cmd YOscControl target get_shutdownCountdown
```

Returns :

an integer corresponding to the remaining number of seconds before the OS shutdown, or zero when no shutdown has been scheduled

On failure, throws an exception or returns `Y_SHUTDOWNCOUNTDOWN_INVALID`.

oscontrol→get(userData)**YOsControl****oscontrol→userData()oscontrol.get(userData)**

Returns the value of the userData attribute, as previously stored using method set(userData).

| | |
|---------|---|
| js | function get(userData) |
| node.js | function get(userData) |
| php | function get(userData) |
| cpp | void * get(userData) |
| m | -(void*) userData |
| pas | function get(userData) : Tobject |
| vb | function get(userData) As Object |
| cs | object get(userData) |
| java | Object get(userData) |
| py | def get(userData) |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

oscontrol→isOnline()oscontrol.isOnline()**YOsControl**

Checks if the OS control is currently reachable, without raising any error.

| | |
|---------|--|
| js | function isOnline() |
| node.js | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the OS control in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the OS control.

Returns :

`true` if the OS control can be reached, and `false` otherwise

oscontrol→isOnline_async()

YOsControl

Checks if the OS control is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context )
nodejs function isOnline_async( callback, context )
```

If there is a cached value for the OS control in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

oscontrol→load()oscontrol.load()**YOsControl**

Preloads the OS control cache with a specified validity duration.

| | |
|----------------------|--|
| <code>js</code> | <code>function load(msValidity)</code> |
| <code>node.js</code> | <code>function load(msValidity)</code> |
| <code>php</code> | <code>function load(\$msValidity)</code> |
| <code>cpp</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>m</code> | <code>-(YRETCODE) load : (int) msValidity</code> |
| <code>pas</code> | <code>function load(msValidity: integer): YRETCODE</code> |
| <code>vb</code> | <code>function load(ByVal msValidity As Integer) As YRETCODE</code> |
| <code>cs</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>java</code> | <code>int load(long msValidity)</code> |
| <code>py</code> | <code>def load(msValidity)</code> |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

`YAPI_SUCCESS` when the call succeeds. On failure, throws an exception or returns a negative error code.

oscontrol→load_async()**YOsControl**

Preloads the OS control cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

oscontrol→nextOsControl()**YOsControl****oscontrol.nextOsControl()**

Continues the enumeration of OS control started using `yFirstOsControl()`.

| | |
|--------|--|
| js | <code>function nextOsControl()</code> |
| nodejs | <code>function nextOsControl()</code> |
| php | <code>function nextOsControl()</code> |
| cpp | <code>YOsControl * nextOsControl()</code> |
| m | <code>-(YOsControl*) nextOsControl</code> |
| pas | <code>function nextOsControl(): TYOsControl</code> |
| vb | <code>function nextOsControl() As YOsControl</code> |
| cs | <code>YOsControl nextOsControl()</code> |
| java | <code>YOsControl nextOsControl()</code> |
| py | <code>def nextOsControl()</code> |

Returns :

a pointer to a `YOsControl` object, corresponding to OS control currently online, or a null pointer if there are no more OS control to enumerate.

**oscontrol→registerValueCallback()
oscontrol.registerValueCallback()****YOsControl**

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YOsControlValueCallback callback )
m    -(int) registerValueCallback : (YOsControlValueCallback) callback
pas   function registerValueCallback( callback: TYOsControlValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

oscontrol→set_logicalName()
oscontrol→setLogicalName()
oscontrol.set_logicalName()

YOsControl

Changes the logical name of the OS control.

| | |
|---------|---|
| js | function set_logicalName(newval) |
| node.js | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YOsControl target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the OS control.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

oscontrol→set(userData)**YOsControl****oscontrol→setUserData()oscontrol.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|--|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData) |
| cpp | void set(userData) void* data |
| m | -(void) setUserData : (void*) data |
| pas | procedure set(userData) data : Tobject |
| vb | procedure set(userData) ByVal data As Object |
| cs | void set(userData) object data |
| java | void set(userData) Object data |
| py | def set(userData) data |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

oscontrol→shutdown()oscontrol.shutdown()**YOsControl**

Schedules an OS shutdown after a given number of seconds.

```
js function shutdown( secBeforeShutDown)
nodejs function shutdown( secBeforeShutDown)
php function shutdown( $secBeforeShutDown)
cpp int shutdown( int secBeforeShutDown)
m -(int) shutdown : (int) secBeforeShutDown
pas function shutdown( secBeforeShutDown: LongInt): LongInt
vb function shutdown( ) As Integer
cs int shutdown( int secBeforeShutDown)
java int shutdown( int secBeforeShutDown)
py def shutdown( secBeforeShutDown)
cmd YOsControl target shutdown secBeforeShutDown
```

Parameters :

secBeforeShutDown number of seconds before shutdown

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

oscontrol→wait_async()

YOsControl

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.28. Power function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

| | |
|--------|---|
| js | <script type='text/javascript' src='yocto_power.js'></script> |
| nodejs | var yoctolib = require('yoctolib'); |
| | var YPower = yoctolib.YPower; |
| php | require_once('yocto_power.php'); |
| cpp | #include "yocto_power.h" |
| m | #import "yocto_power.h" |
| pas | uses yocto_power; |
| vb | yocto_power.vb |
| cs | yocto_power.cs |
| java | import com.yoctopuce.YoctoAPI.YPower; |
| py | from yocto_power import * |

Global functions

yFindPower(func)

Retrieves a electrical power sensor for a given identifier.

yFirstPower()

Starts the enumeration of electrical power sensors currently accessible.

YPower methods

power→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

power→describe()

Returns a short text that describes unambiguously the instance of the electrical power sensor in the form TYPE (NAME)=SERIAL.FUNCTIONID.

power→get_advertisedValue()

Returns the current value of the electrical power sensor (no more than 6 characters).

power→get_cosPhi()

Returns the power factor (the ratio between the real power consumed, measured in W, and the apparent power provided, measured in VA).

power→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor.

power→get_currentValue()

Returns the current measure for the electrical power.

power→get_errorMessage()

Returns the error message of the latest error with the electrical power sensor.

power→get_errorType()

Returns the numerical error code of the latest error with the electrical power sensor.

power→get_friendlyName()

Returns a global identifier of the electrical power sensor in the format MODULE_NAME.FUNCTION_NAME.

power→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

power→get_functionId()

3. Reference

| |
|--|
| Returns the hardware identifier of the electrical power sensor, without reference to the module. |
| power→get_hardwareId() |
| Returns the unique hardware identifier of the electrical power sensor in the form SERIAL.FUNCTIONID. |
| power→get_highestValue() |
| Returns the maximal value observed for the electrical power. |
| power→get_logFrequency() |
| Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory. |
| power→get_logicalName() |
| Returns the logical name of the electrical power sensor. |
| power→get_lowestValue() |
| Returns the minimal value observed for the electrical power. |
| power→get_meter() |
| Returns the energy counter, maintained by the wattmeter by integrating the power consumption over time. |
| power→get_meterTimer() |
| Returns the elapsed time since last energy counter reset, in seconds. |
| power→get_module() |
| Gets the YModule object for the device on which the function is located. |
| power→get_module_async(callback, context) |
| Gets the YModule object for the device on which the function is located (asynchronous version). |
| power→get_recordedData(startTime, endTime) |
| Retrieves a DataSet object holding historical data for this sensor, for a specified time interval. |
| power→get_reportFrequency() |
| Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function. |
| power→get_resolution() |
| Returns the resolution of the measured values. |
| power→get_unit() |
| Returns the measuring unit for the electrical power. |
| power→get(userData) |
| Returns the value of the userData attribute, as previously stored using method set(userData). |
| power→isOnline() |
| Checks if the electrical power sensor is currently reachable, without raising any error. |
| power→isOnline_async(callback, context) |
| Checks if the electrical power sensor is currently reachable, without raising any error (asynchronous version). |
| power→load(msValidity) |
| Preloads the electrical power sensor cache with a specified validity duration. |
| power→loadCalibrationPoints(rawValues, refValues) |
| Retrieves error correction data points previously entered using the method calibrateFromPoints. |
| power→load_async(msValidity, callback, context) |
| Preloads the electrical power sensor cache with a specified validity duration (asynchronous version). |
| power→nextPower() |
| Continues the enumeration of electrical power sensors started using yFirstPower(). |
| power→registerTimedReportCallback(callback) |
| Registers the callback function that is invoked on every periodic timed notification. |
| power→registerValueCallback(callback) |

Registers the callback function that is invoked on every change of advertised value.

power→reset()

Resets the energy counter.

power→set_highestValue(newval)

Changes the recorded maximal value observed pour the electrical power.

power→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

power→set_logicalName(newval)

Changes the logical name of the electrical power sensor.

power→set_lowestValue(newval)

Changes the recorded minimal value observed pour the electrical power.

power→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

power→set_resolution(newval)

Changes the resolution of the measured values.

power→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

power→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YPower.FindPower() yFindPower()YPower.FindPower()

YPower

Retrieves a electrical power sensor for a given identifier.

| | |
|---------|---|
| js | function yFindPower(func) |
| node.js | function FindPower(func) |
| php | function yFindPower(\$func) |
| cpp | YPower* yFindPower(const string& func) |
| m | YPower* yFindPower(NSString* func) |
| pas | function yFindPower(func: string): TYPower |
| vb | function yFindPower(ByVal func As String) As YPower |
| cs | YPower FindPower(string func) |
| java | YPower FindPower(String func) |
| py | def FindPower(func) |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the electrical power sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YPower.isOnline()` to test if the electrical power sensor is indeed online at a given time. In case of ambiguity when looking for a electrical power sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the electrical power sensor

Returns :

a `YPower` object allowing you to drive the electrical power sensor.

YPower.FirstPower()

YPower

yFirstPower() YPower.FirstPower()

Starts the enumeration of electrical power sensors currently accessible.

```
js function yFirstPower( )
nodejs function FirstPower( )
php function yFirstPower( )
cpp YPower* yFirstPower( )
m YPower* yFirstPower( )
pas function yFirstPower( ): TYPower
vb function yFirstPower( ) As YPower
cs YPower FirstPower( )
java YPower FirstPower( )
py def FirstPower( )
```

Use the method `YPower.nextPower()` to iterate on next electrical power sensors.

Returns :

a pointer to a `YPower` object, corresponding to the first electrical power sensor currently online, or a `null` pointer if there are none.

power→calibrateFromPoints() power.calibrateFromPoints()

YPower

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```

js   function calibrateFromPoints( rawValues, refValues)
nodejs function calibrateFromPoints( rawValues, refValues)
php   function calibrateFromPoints( $rawValues, $refValues)
cpp    int calibrateFromPoints( vector<double> rawValues,
                               vector<double> refValues)

m    -(int) calibrateFromPoints : (NSMutableArray*) rawValues
                : (NSMutableArray*) refValues

pas   function calibrateFromPoints( rawValues: TDoubleArray,
                                   refValues: TDoubleArray): LongInt

vb    procedure calibrateFromPoints( )

cs    int calibrateFromPoints( List<double> rawValues,
                           List<double> refValues)

java   int calibrateFromPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py    def calibrateFromPoints( rawValues, refValues)
cmd   YPower target calibrateFromPoints rawValues refValues

```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

power→describe()power.describe()**YPower**

Returns a short text that describes unambiguously the instance of the electrical power sensor in the form TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

```
a string that describes the electrical power sensor (ex:  
Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)
```

power→get_advertisedValue()
power→advertisedValue()
power.get_advertisedValue()

YPower

Returns the current value of the electrical power sensor (no more than 6 characters).

| | |
|--------|---|
| js | function get_advertisedValue() |
| nodejs | function get_advertisedValue() |
| php | function get_advertisedValue() |
| cpp | string get_advertisedValue() |
| m | -(NSString*) advertisedValue |
| pas | function get_advertisedValue(): string |
| vb | function get_advertisedValue() As String |
| cs | string get_advertisedValue() |
| java | String get_advertisedValue() |
| py | def get_advertisedValue() |
| cmd | YPower target get_advertisedValue |

Returns :

a string corresponding to the current value of the electrical power sensor (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

power→get_cosPhi()**YPower****power→cosPhi()power.get_cosPhi()**

Returns the power factor (the ratio between the real power consumed, measured in W, and the apparent power provided, measured in VA).

| | |
|--------|---|
| js | function get_cosPhi() |
| nodejs | function get_cosPhi() |
| php | function get_cosPhi() |
| cpp | double get_cosPhi() |
| m | -(double) cosPhi |
| pas | function get_cosPhi(): double |
| vb | function get_cosPhi() As Double |
| cs | double get_cosPhi() |
| java | double get_cosPhi() |
| py | def get_cosPhi() |
| cmd | YPower target get_cosPhi |

Returns :

a floating point number corresponding to the power factor (the ratio between the real power consumed, measured in W, and the apparent power provided, measured in VA)

On failure, throws an exception or returns Y_COSPHI_INVALID.

power→get_currentRawValue()
power→currentRawValue()
power.get_currentRawValue()

YPower

Returns the uncalibrated, unrounded raw value returned by the sensor.

js function **get_currentRawValue()**
nodejs function **get_currentRawValue()**
php function **get_currentRawValue()**
cpp double **get_currentRawValue()**
m -(double) currentRawValue
pas function **get_currentRawValue()**: double
vb function **get_currentRawValue()** As Double
cs double **get_currentRawValue()**
java double **get_currentRawValue()**
py def **get_currentRawValue()**
cmd YPower **target get_currentRawValue**

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

power→get_currentValue()**YPower****power→currentValue()power.get_currentValue()**

Returns the current measure for the electrical power.

```
js function get_currentValue( )  
nodejs function get_currentValue( )  
php function get_currentValue( )  
cpp double get_currentValue( )  
m -(double) currentValue  
pas function get_currentValue( ): double  
vb function get_currentValue( ) As Double  
cs double get_currentValue( )  
java double get_currentValue( )  
py def get_currentValue( )  
cmd YPower target get_currentValue
```

Returns :

a floating point number corresponding to the current measure for the electrical power

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

power→getErrorMessage()

YPower

power→errorMessage()power.getErrorMessage()

Returns the error message of the latest error with the electrical power sensor.

```
js function getErrorMessage( )
node.js function getErrorMessage( )
php function getErrorMessage( )
cpp string getErrorMessage( )
m -(NSString*) errorMessage
pas function getErrorMessage( ): string
vb function getErrorMessage( ) As String
cs string getErrorMessage( )
java String getErrorMessage( )
py def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the electrical power sensor object

power→get_errorType() power→errorType()power.get_errorType()

YPower

Returns the numerical error code of the latest error with the electrical power sensor.

| | |
|--------|--|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType(): YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the electrical power sensor object

power→get_friendlyName()

YPower

power→friendlyName()power.get_friendlyName()

Returns a global identifier of the electrical power sensor in the format MODULE_NAME.FUNCTION_NAME.

```
js function get_friendlyName( )  
nodejs function get_friendlyName( )  
php function get_friendlyName( )  
cpp string get_friendlyName( )  
m -(NSString*) friendlyName  
cs string get_friendlyName( )  
java String get_friendlyName( )  
py def get_friendlyName( )
```

The returned string uses the logical names of the module and of the electrical power sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the electrical power sensor (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the electrical power sensor using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

power→get_functionDescriptor()
power→functionDescriptor()
power.get_functionDescriptor()**YPower**

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

power→get_functionId()
power→functionId()power.get_functionId()**YPower**

Returns the hardware identifier of the electrical power sensor, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | - (NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the electrical power sensor (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

power→get_hardwareId()**YPower****power→hardwareId()power.get_hardwareId()**

Returns the unique hardware identifier of the electrical power sensor in the form SERIAL.FUNCTIONID.

| | |
|---------|---|
| js | function get_hardwareId() |
| node.js | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the electrical power sensor. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the electrical power sensor (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

power→get_highestValue()

YPower

power→highestValue()power.get_highestValue()

Returns the maximal value observed for the electrical power.

js function **get_highestValue()****node.js** function **get_highestValue()****php** function **get_highestValue()****cpp** double **get_highestValue()****m** -(double) highestValue**pas** function **get_highestValue(): double****vb** function **get_highestValue() As Double****cs** double **get_highestValue()****java** double **get_highestValue()****py** def **get_highestValue()****cmd** YPower target **get_highestValue****Returns :**

a floating point number corresponding to the maximal value observed for the electrical power

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

power→get_logFrequency()**YPower****power→logFrequency()power.get_logFrequency()**

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

| | |
|--------|--|
| js | function get_logFrequency() () |
| nodejs | function get_logFrequency() () |
| php | function get_logFrequency() () |
| cpp | string get_logFrequency() () |
| m | -(NSString*) logFrequency |
| pas | function get_logFrequency() (): string |
| vb | function get_logFrequency() () As String |
| cs | string get_logFrequency() () |
| java | String get_logFrequency() () |
| py | def get_logFrequency() () |
| cmd | YPower target get_logFrequency |

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

power→get_logicalName()

YPower

power→logicalName()power.get_logicalName()

Returns the logical name of the electrical power sensor.

| | |
|---------|--|
| js | function get_logicalName() |
| node.js | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | - (NSString*) logicalName |
| pas | function get_logicalName(): string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YPower target get_logicalName |

Returns :

a string corresponding to the logical name of the electrical power sensor. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

power→get_lowestValue()**YPower****power→lowestValue()power.get_lowestValue()**

Returns the minimal value observed for the electrical power.

```
js   function get_lowestValue( )  
nodejs function get_lowestValue( )  
php  function get_lowestValue( )  
cpp   double get_lowestValue( )  
m    -(double) lowestValue  
pas   function get_lowestValue( ): double  
vb    function get_lowestValue( ) As Double  
cs    double get_lowestValue( )  
java  double get_lowestValue( )  
py    def get_lowestValue( )  
cmd   YPower target get_lowestValue
```

Returns :

a floating point number corresponding to the minimal value observed for the electrical power

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

power→get_meter()
power→meter()power.get_meter()**YPower**

Returns the energy counter, maintained by the wattmeter by integrating the power consumption over time.

| | |
|--------|--|
| js | function get_meter() |
| nodejs | function get_meter() |
| php | function get_meter() |
| cpp | double get_meter() |
| m | -(double) meter |
| pas | function get_meter(): double |
| vb | function get_meter() As Double |
| cs | double get_meter() |
| java | double get_meter() |
| py | def get_meter() |
| cmd | YPower target get_meter |

Note that this counter is reset at each start of the device.

Returns :

a floating point number corresponding to the energy counter, maintained by the wattmeter by integrating the power consumption over time

On failure, throws an exception or returns **Y_METER_INVALID**.

power→get_meterTimer() power→meterTimer()power.get_meterTimer()

YPower

Returns the elapsed time since last energy counter reset, in seconds.

| | |
|--------|---|
| js | function get_meterTimer() |
| nodejs | function get_meterTimer() |
| php | function get_meterTimer() |
| cpp | int get_meterTimer() |
| m | -(int) meterTimer |
| pas | function get_meterTimer() : LongInt |
| vb | function get_meterTimer() As Integer |
| cs | int get_meterTimer() |
| java | int get_meterTimer() |
| py | def get_meterTimer() |
| cmd | YPower target get_meterTimer |

Returns :

an integer corresponding to the elapsed time since last energy counter reset, in seconds

On failure, throws an exception or returns Y_METERTIMER_INVALID.

**power→get_module()
power→module()power.get_module()****YPower**

Gets the `YModule` object for the device on which the function is located.

| | |
|---------|---|
| js | function get_module() |
| node.js | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

power→get_module_async() power→module_async()

YPower

Gets the YModule object for the device on which the function is located (asynchronous version).

```
js   function get_module_async( callback, context )
nodejs function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned YModule object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested YModule object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

`power→get_recordedData()`

YPower

power→recordedData() / power.get_recordedData()

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
js function get_recordedData( startTime, endTime)
nodejs function get_recordedData( startTime, endTime)
php function get_recordedData( $startTime, $endTime)
cpp YDataSet get_recordedData( s64 startTime, s64 endTime)
m -(YDataSet*) recordedData : (s64) startTime
                           : (s64) endTime
pas function get_recordedData( startTime: int64, endTime: int64): TYDataSet
vb function get_recordedData( ) As YDataSet
cs YDataSet get_recordedData( long startTime, long endTime)
java YDataSet get_recordedData( long startTime, long endTime)
py def get_recordedData( startTime, endTime)
cmd YPower target get_recordedData startTime endTime
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the `DataSet` class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of `YDataSet`, providing access to historical data. Past measures can be loaded progressively using methods from the `YDataSet` object.

power→get_reportFrequency()
power→reportFrequency()
power.get_reportFrequency()**YPower**

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

| | |
|--------|---|
| js | function get_reportFrequency() |
| nodejs | function get_reportFrequency() |
| php | function get_reportFrequency() |
| cpp | string get_reportFrequency() |
| m | -(NSString*) reportFrequency |
| pas | function get_reportFrequency() : string |
| vb | function get_reportFrequency() As String |
| cs | string get_reportFrequency() |
| java | String get_reportFrequency() |
| py | def get_reportFrequency() |
| cmd | YPower target get_reportFrequency |

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns **Y_REPORTFREQUENCY_INVALID**.

**power→get_resolution()
power→resolution()power.get_resolution()****YPower**

Returns the resolution of the measured values.

| | |
|---------|---|
| js | function get_resolution() |
| node.js | function get_resolution() |
| php | function get_resolution() |
| cpp | double get_resolution() |
| m | -(double) resolution |
| pas | function get_resolution() : double |
| vb | function get_resolution() As Double |
| cs | double get_resolution() |
| java | double get_resolution() |
| py | def get_resolution() |
| cmd | YPower target get_resolution |

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

power→get_unit()**YPower****power→unit()power.get_unit()**

Returns the measuring unit for the electrical power.

| | |
|--------|---------------------------------------|
| js | function get_unit() |
| nodejs | function get_unit() |
| php | function get_unit() |
| cpp | string get_unit() |
| m | -(NSString*) unit |
| pas | function get_unit() : string |
| vb | function get_unit() As String |
| cs | string get_unit() |
| java | String get_unit() |
| py | def get_unit() |
| cmd | YPower target get_unit |

Returns :

a string corresponding to the measuring unit for the electrical power

On failure, throws an exception or returns Y_UNIT_INVALID.

power→get(userData)
power→userData()power.get(userData())

YPower

Returns the value of the userData attribute, as previously stored using method set(userData).

```
js function get(userData) 
node.js function get(userData) 
php function get(userData) 
cpp void * get(userData) 
m -(void*) userData 
pas function get(userData): TObject 
vb function get(userData) As Object 
cs object get(userData) 
java Object get(userData) 
py def get(userData)
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

power→isOnline()power.isOnline()**YPower**

Checks if the electrical power sensor is currently reachable, without raising any error.

| | |
|---------|--|
| js | function isOnline() |
| node.js | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the electrical power sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the electrical power sensor.

Returns :

true if the electrical power sensor can be reached, and false otherwise

power→isOnline_async()

YPower

Checks if the electrical power sensor is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the electrical power sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

power→load()|power.load()**YPower**

Preloads the electrical power sensor cache with a specified validity duration.

| | |
|----------------------|--|
| <code>js</code> | <code>function load(msValidity)</code> |
| <code>node.js</code> | <code>function load(msValidity)</code> |
| <code>php</code> | <code>function load(\$msValidity)</code> |
| <code>cpp</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>m</code> | <code>-(YRETCODE) load : (int) msValidity</code> |
| <code>pas</code> | <code>function load(msValidity: integer): YRETCODE</code> |
| <code>vb</code> | <code>function load(ByVal msValidity As Integer) As YRETCODE</code> |
| <code>cs</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>java</code> | <code>int load(long msValidity)</code> |
| <code>py</code> | <code>def load(msValidity)</code> |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

power→loadCalibrationPoints() power.loadCalibrationPoints()

YPower

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```

js   function loadCalibrationPoints( rawValues, refValues)
nodejs function loadCalibrationPoints( rawValues, refValues)
php   function loadCalibrationPoints( &$rawValues, &$refValues)
cpp   int loadCalibrationPoints( vector<double>& rawValues,
                                vector<double>& refValues)
m    -(int) loadCalibrationPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues
pas  function loadCalibrationPoints( var rawValues: TDoubleArray,
                           var refValues: TDoubleArray): LongInt
vb   procedure loadCalibrationPoints( )
cs   int loadCalibrationPoints( List<double> rawValues,
                           List<double> refValues)
java int loadCalibrationPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)
py   def loadCalibrationPoints( rawValues, refValues)
cmd  YPower target loadCalibrationPoints rawValues refValues

```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

power→load_async()

YPower

Preloads the electrical power sensor cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

power→nextPower()power.nextPower()******YPower**

Continues the enumeration of electrical power sensors started using `yFirstPower()`.

| | |
|--------|---------------------------------------|
| js | function nextPower() |
| nodejs | function nextPower() |
| php | function nextPower() |
| cpp | YPower * nextPower() |
| m | -(YPower*) nextPower |
| pas | function nextPower() : TYPower |
| vb | function nextPower() As YPower |
| cs | YPower nextPower() |
| java | YPower nextPower() |
| py | def nextPower() |

Returns :

a pointer to a `YPower` object, corresponding to a electrical power sensor currently online, or a null pointer if there are no more electrical power sensors to enumerate.

power→registerTimedReportCallback() power.registerTimedReportCallback()

YPower

Registers the callback function that is invoked on every periodic timed notification.

| | |
|---------|--|
| js | function registerTimedReportCallback(callback) |
| node.js | function registerTimedReportCallback(callback) |
| php | function registerTimedReportCallback(\$callback) |
| cpp | int registerTimedReportCallback(YPowerTimedReportCallback callback) |
| m | -(int) registerTimedReportCallback : (YPowerTimedReportCallback) callback |
| pas | function registerTimedReportCallback(callback : TYPowerTimedReportCallback): LongInt |
| vb | function registerTimedReportCallback() As Integer |
| cs | int registerTimedReportCallback(TimedReportCallback callback) |
| java | int registerTimedReportCallback(TimedReportCallback callback) |
| py | def registerTimedReportCallback(callback) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

power→registerValueCallback() power.registerValueCallback()

YPower

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YPowerValueCallback callback )
m    -(int) registerValueCallback : (YPowerValueCallback) callback
pas   function registerValueCallback( callback: TYPowerValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

power→reset()power.reset()

YPower

Resets the energy counter.

| | |
|--------|-------------------------------------|
| js | function reset() |
| nodejs | function reset() |
| php | function reset() |
| cpp | int reset() |
| m | - (int) reset |
| pas | function reset(): LongInt |
| vb | function reset() As Integer |
| cs | int reset() |
| java | int reset() |
| py | def reset() |
| cmd | YPower target reset |

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

power→set_highestValue() power→setHighestValue()power.set_highestValue()

Changes the recorded maximal value observed pour the electrical power.

```
js function set_highestValue( newval)
node.js function set_highestValue( newval)
php function set_highestValue( $newval)
cpp int set_highestValue( double newval)
m -(int) setHighestValue : (double) newval
pas function set_highestValue( newval: double): integer
vb function set_highestValue( ByVal newval As Double) As Integer
cs int set_highestValue( double newval)
java int set_highestValue( double newval)
py def set_highestValue( newval)
cmd YPower target set_highestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed pour the electrical power

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

power→set_logFrequency()

YPower

power→setLogFrequency()power.set_logFrequency()

Changes the datalogger recording frequency for this function.

| | |
|----------------------|--|
| <code>js</code> | <code>function set_logFrequency(newval)</code> |
| <code>node.js</code> | <code>function set_logFrequency(newval)</code> |
| <code>php</code> | <code>function set_logFrequency(\$newval)</code> |
| <code>cpp</code> | <code>int set_logFrequency(const string& newval)</code> |
| <code>m</code> | <code>-(int) setLogFrequency : (NSString*) newval</code> |
| <code>pas</code> | <code>function set_logFrequency(newval: string): integer</code> |
| <code>vb</code> | <code>function set_logFrequency(ByVal newval As String) As Integer</code> |
| <code>cs</code> | <code>int set_logFrequency(string newval)</code> |
| <code>java</code> | <code>int set_logFrequency(String newval)</code> |
| <code>py</code> | <code>def set_logFrequency(newval)</code> |
| <code>cmd</code> | <code>YPower target set_logFrequency newval</code> |

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

power→set_logicalName() power→setLogicalName()power.set_logicalName()

Changes the logical name of the electrical power sensor.

```
js function set_logicalName( newval)
node.js function set_logicalName( newval)
php function set_logicalName( $newval)
cpp int set_logicalName( const string& newval)
m -(int) setLogicalName : (NSString*) newval
pas function set_logicalName( newval: string): integer
vb function set_logicalName( ByVal newval As String) As Integer
cs int set_logicalName( string newval)
java int set_logicalName( String newval)
py def set_logicalName( newval)
cmd YPower target set_logicalName newval
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the electrical power sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

power→set_lowestValue()

YPower

power→setLowestValue()power.set_lowestValue()

Changes the recorded minimal value observed pour the electrical power.

| | |
|---------------------|---|
| <code>js</code> | <code>function set_lowestValue(newval)</code> |
| <code>nodejs</code> | <code>function set_lowestValue(newval)</code> |
| <code>php</code> | <code>function set_lowestValue(\$newval)</code> |
| <code>cpp</code> | <code>int set_lowestValue(double newval)</code> |
| <code>m</code> | <code>-(int) setLowestValue : (double) newval</code> |
| <code>pas</code> | <code>function set_lowestValue(newval: double): integer</code> |
| <code>vb</code> | <code>function set_lowestValue(ByVal newval As Double) As Integer</code> |
| <code>cs</code> | <code>int set_lowestValue(double newval)</code> |
| <code>java</code> | <code>int set_lowestValue(double newval)</code> |
| <code>py</code> | <code>def set_lowestValue(newval)</code> |
| <code>cmd</code> | <code>YPower target set_lowestValue newval</code> |

Parameters :

newval a floating point number corresponding to the recorded minimal value observed pour the electrical power

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

power→set_reportFrequency()
power→setReportFrequency()
power.set_reportFrequency()

YPower

Changes the timed value notification frequency for this function.

```
js    function set_reportFrequency( newval)
nodejs function set_reportFrequency( newval)
php   function set_reportFrequency( $newval)
cpp   int set_reportFrequency( const string& newval)
m     -(int) setReportFrequency : (NSString*) newval
pas   function set_reportFrequency( newval: string): integer
vb    function set_reportFrequency( ByVal newval As String) As Integer
cs    int set_reportFrequency( string newval)
java  int set_reportFrequency( String newval)
py    def set_reportFrequency( newval)
cmd   YPower target set_reportFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

power→set_resolution() power→setResolution()power.set_resolution()

YPower

Changes the resolution of the measured values.

| | |
|--------|--|
| js | function set_resolution(newval) |
| nodejs | function set_resolution(newval) |
| php | function set_resolution(\$newval) |
| cpp | int set_resolution(double newval) |
| m | -(int) setResolution : (double) newval |
| pas | function set_resolution(newval: double): integer |
| vb | function set_resolution(ByVal newval As Double) As Integer |
| cs | int set_resolution(double newval) |
| java | int set_resolution(double newval) |
| py | def set_resolution(newval) |
| cmd | YPower target set_resolution newval |

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

power→set(userData)

YPower

power→setUserData()power.set(userData)

Stores a user context provided as argument in the userData attribute of the function.

```
js   function setUserData( data)
node.js function setUserData( data)
php  function setUserData( $data)
cpp   void setUserData( void* data)
m    -(void) setUserData : (void*) data
pas   procedure setUserData( data: Tobject)
vb    procedure setUserData( ByVal data As Object)
cs    void setUserData( object data)
java  void setUserData( Object data)
py    def setUserData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

power→wait_async()

YPower

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context )
nodejs function wait_async( callback, context )
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.29. Pressure function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_pressure.js'></script>
nodejs var yoctolib = require('yoctolib');
var YPressure = yoctolib.YPressure;
php require_once('yocto_pressure.php');
cpp #include "yocto_pressure.h"
m #import "yocto_pressure.h"
pas uses yocto_pressure;
vb yocto_pressure.vb
cs yocto_pressure.cs
java import com.yoctopuce.YoctoAPI.YPressure;
py from yocto_pressure import *

```

Global functions

yFindPressure(func)

Retrieves a pressure sensor for a given identifier.

yFirstPressure()

Starts the enumeration of pressure sensors currently accessible.

YPressure methods

pressure→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

pressure→describe()

Returns a short text that describes unambiguously the instance of the pressure sensor in the form TYPE (NAME) = SERIAL . FUNCTIONID.

pressure→get_advertisedValue()

Returns the current value of the pressure sensor (no more than 6 characters).

pressure→get_currentRawValue()

Returns the unrounded and uncalibrated raw value returned by the sensor.

pressure→get_currentValue()

Returns the current measure for the pressure.

pressure→get_errorMessage()

Returns the error message of the latest error with the pressure sensor.

pressure→get_errorType()

Returns the numerical error code of the latest error with the pressure sensor.

pressure→get_friendlyName()

Returns a global identifier of the pressure sensor in the format MODULE_NAME . FUNCTION_NAME.

pressure→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

pressure→get_functionId()

Returns the hardware identifier of the pressure sensor, without reference to the module.

pressure→get_hardwareId()

Returns the unique hardware identifier of the pressure sensor in the form SERIAL . FUNCTIONID.

pressure→get_highestValue()

Returns the maximal value observed for the pressure.

pressure→get_logFrequency()

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

pressure→get_logicalName()

Returns the logical name of the pressure sensor.

pressure→get_lowestValue()

Returns the minimal value observed for the pressure.

pressure→get_module()

Gets the YModule object for the device on which the function is located.

pressure→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

pressure→get_recordedData(startTime, endTime)

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

pressure→get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

pressure→get_resolution()

Returns the resolution of the measured values.

pressure→get_unit()

Returns the measuring unit for the pressure.

pressure→get(userData)

Returns the value of the userData attribute, as previously stored using method set(userData).

pressure→isOnline()

Checks if the pressure sensor is currently reachable, without raising any error.

pressure→isOnline_async(callback, context)

Checks if the pressure sensor is currently reachable, without raising any error (asynchronous version).

pressure→load(msValidity)

Preloads the pressure sensor cache with a specified validity duration.

pressure→loadCalibrationPoints(rawValues, refValues)

Retrieves error correction data points previously entered using the method calibrateFromPoints.

pressure→load_async(msValidity, callback, context)

Preloads the pressure sensor cache with a specified validity duration (asynchronous version).

pressure→nextPressure()

Continues the enumeration of pressure sensors started using yFirstPressure().

pressure→registerTimedReportCallback(callback)

Registers the callback function that is invoked on every periodic timed notification.

pressure→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

pressure→set_highestValue(newval)

Changes the recorded maximal value observed for the pressure.

pressure→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

pressure→set_logicalName(newval)

Changes the logical name of the pressure sensor.

3. Reference

pressure→set_lowestValue(newval)

Changes the recorded minimal value observed for the pressure.

pressure→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

pressure→set_resolution(newval)

Changes the resolution of the measured physical values.

pressure→set(userData)

Stores a user context provided as argument in the userData attribute of the function.

pressure→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YPressure.FindPressure() yFindPressure()YPressure.FindPressure()

YPressure

Retrieves a pressure sensor for a given identifier.

| | |
|---------|---|
| js | function yFindPressure(func) |
| node.js | function FindPressure(func) |
| php | function yFindPressure(\$func) |
| cpp | YPressure* yFindPressure(const string& func) |
| m | YPressure* yFindPressure(NSString* func) |
| pas | function yFindPressure(func: string): TYPressure |
| vb | function yFindPressure(ByVal func As String) As YPressure |
| cs | YPressure FindPressure(string func) |
| java | YPressure FindPressure(String func) |
| py | def FindPressure(func) |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the pressure sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YPressure.isOnline()` to test if the pressure sensor is indeed online at a given time. In case of ambiguity when looking for a pressure sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the pressure sensor

Returns :

a YPressure object allowing you to drive the pressure sensor.

YPressure.FirstPressure()**YPressure****yFirstPressure()YPressure.FirstPressure()**

Starts the enumeration of pressure sensors currently accessible.

| | |
|---------|---|
| js | function yFirstPressure() |
| node.js | function FirstPressure() |
| php | function yFirstPressure() |
| cpp | YPressure* yFirstPressure() |
| m | YPressure* yFirstPressure() |
| pas | function yFirstPressure() : TYPressure |
| vb | function yFirstPressure() As YPressure |
| cs | YPressure FirstPressure() |
| java | YPressure FirstPressure() |
| py | def FirstPressure() |

Use the method `YPressure.nextPressure()` to iterate on next pressure sensors.

Returns :

a pointer to a `YPressure` object, corresponding to the first pressure sensor currently online, or a null pointer if there are none.

pressure→calibrateFromPoints() pressure.calibrateFromPoints()

YPressure

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```

js   function calibrateFromPoints( rawValues, refValues)
nodejs function calibrateFromPoints( rawValues, refValues)
php  function calibrateFromPoints( $rawValues, $refValues)
cpp   int calibrateFromPoints( vector<double> rawValues,
                             vector<double> refValues)

m    -(int) calibrateFromPoints : (NSMutableArray*) rawValues
                  : (NSMutableArray*) refValues

pas  function calibrateFromPoints( rawValues: TDoubleArray,
                                 refValues: TDoubleArray): LongInt

vb   procedure calibrateFromPoints( )

cs   int calibrateFromPoints( List<double> rawValues,
                           List<double> refValues)

java int calibrateFromPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def calibrateFromPoints( rawValues, refValues)
cmd  YPressure target calibrateFromPoints rawValues refValues

```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.
refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

pressure→describe()pressure.describe()**YPressure**

Returns a short text that describes unambiguously the instance of the pressure sensor in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|---------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the pressure sensor (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

pressure→get_advertisedValue()
pressure→advertisedValue()
pressure.get_advertisedValue()

YPressure

Returns the current value of the pressure sensor (no more than 6 characters).

| | |
|----------------|--|
| js | function get_advertisedValue() |
| node.js | function get_advertisedValue() |
| php | function get_advertisedValue() |
| cpp | string get_advertisedValue() |
| m | -(NSString*) advertisedValue |
| pas | function get_advertisedValue() : string |
| vb | function get_advertisedValue() As String |
| cs | string get_advertisedValue() |
| java | String get_advertisedValue() |
| py | def get_advertisedValue() |
| cmd | YPressure target get_advertisedValue |

Returns :

a string corresponding to the current value of the pressure sensor (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

pressure→get_currentRawValue()
pressure→currentRawValue()
pressure.get_currentRawValue()

YPressure

Returns the unrounded and uncalibrated raw value returned by the sensor.

js function **get_currentRawValue()**
nodejs function **get_currentRawValue()**
php function **get_currentRawValue()**
cpp double **get_currentRawValue()**
m -(double) currentRawValue
pas function **get_currentRawValue(): double**
vb function **get_currentRawValue() As Double**
cs double **get_currentRawValue()**
java double **get_currentRawValue()**
py def **get_currentRawValue()**
cmd YPressure target **get_currentRawValue**

Returns :

a floating point number corresponding to the unrounded and uncalibrated raw value returned by the sensor

On failure, throws an exception or returns **Y_CURRENTRAWVALUE_INVALID**.

pressure→get_currentValue()**YPressure****pressure→currentValue()pressure.get_currentValue()**

Returns the current measure for the pressure.

| | |
|--------|---|
| js | function get_currentValue() |
| nodejs | function get_currentValue() |
| php | function get_currentValue() |
| cpp | double get_currentValue() |
| m | -(double) currentValue |
| pas | function get_currentValue(): double |
| vb | function get_currentValue() As Double |
| cs | double get_currentValue() |
| java | double get_currentValue() |
| py | def get_currentValue() |
| cmd | YPressure target get_currentValue |

Returns :

a floating point number corresponding to the current measure for the pressure

On failure, throws an exception or returns **Y_CURRENTVALUE_INVALID**.

pressure→get_errorMessage()
pressure→errorMessage()
pressure.get_errorMessage()**YPressure**

Returns the error message of the latest error with the pressure sensor.

| | |
|--------|--|
| js | function get_errorMessage() |
| nodejs | function get_errorMessage() |
| php | function get_errorMessage() |
| cpp | string get_errorMessage() |
| m | -(NSString*) errorMessage |
| pas | function get_errorMessage(): string |
| vb | function get_errorMessage() As String |
| cs | string get_errorMessage() |
| java | String get_errorMessage() |
| py | def get_errorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the pressure sensor object

pressure→get_errorType()**YPressure****pressure→errorType()pressure.get_errorType()**

Returns the numerical error code of the latest error with the pressure sensor.

| | |
|--------|--|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType(): YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the pressure sensor object

pressure→get_friendlyName()
pressure→friendlyName()
pressure.get_friendlyName()**YPressure**

Returns a global identifier of the pressure sensor in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the pressure sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the pressure sensor (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the pressure sensor using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

pressure→get_functionDescriptor()
pressure→functionDescriptor()
pressure.get_functionDescriptor()

YPressure

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

pressure→get_functionId()**YPressure****pressure→functionId()pressure.get_functionId()**

Returns the hardware identifier of the pressure sensor, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | - (NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the pressure sensor (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

pressure→get_hardwareId()**YPressure****pressure→hardwareId()|pressure.get_hardwareId()**

Returns the unique hardware identifier of the pressure sensor in the form SERIAL.FUNCTIONID.

| | |
|--------|---|
| js | function get_hardwareId() |
| nodejs | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the pressure sensor. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the pressure sensor (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

pressure→get_highestValue()
pressure→highestValue()
pressure.get_highestValue()

YPressure

Returns the maximal value observed for the pressure.

```
js function get_highestValue( )  
nodejs function get_highestValue( )  
php function get_highestValue( )  
cpp double get_highestValue( )  
m -(double) highestValue  
pas function get_highestValue( ): double  
vb function get_highestValue( ) As Double  
cs double get_highestValue( )  
java double get_highestValue( )  
py def get_highestValue( )  
cmd YPressure target get_highestValue
```

Returns :

a floating point number corresponding to the maximal value observed for the pressure

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

pressure→get_logFrequency()
pressure→logFrequency()
pressure.get_logFrequency()

YPressure

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
js   function get_logFrequency( )  
nodejs function get_logFrequency( )  
php  function get_logFrequency( )  
cpp   string get_logFrequency( )  
m    -(NSString*) logFrequency  
pas   function get_logFrequency( ): string  
vb    function get_logFrequency( ) As String  
cs    string get_logFrequency( )  
java  String get_logFrequency( )  
py    def get_logFrequency()  
cmd   YPressure target get_logFrequency
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

pressure→get_logicalName()**YPressure****pressure→logicalName()pressure.get_logicalName()**

Returns the logical name of the pressure sensor.

| | |
|---------|--|
| js | function get_logicalName() |
| node.js | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | -(NSString*) logicalName |
| pas | function get_logicalName() : string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YPressure target get_logicalName |

Returns :

a string corresponding to the logical name of the pressure sensor. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

pressure→get_lowestValue()**YPressure****pressure→lowestValue()pressure.get_lowestValue()**

Returns the minimal value observed for the pressure.

```
js function get_lowestValue( )
nodejs function get_lowestValue( )
php function get_lowestValue( )
cpp double get_lowestValue( )
m -(double) lowestValue
pas function get_lowestValue( ): double
vb function get_lowestValue( ) As Double
cs double get_lowestValue( )
java double get_lowestValue( )
py def get_lowestValue( )
cmd YPressure target get_lowestValue
```

Returns :

a floating point number corresponding to the minimal value observed for the pressure

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

pressure→get_module()
pressure→module()pressure.get_module()**YPressure**

Gets the `YModule` object for the device on which the function is located.

| | |
|---------|---|
| js | function get_module() |
| node.js | function get_module() |
| php | function get_module() |
| cpp | <code>YModule * get_module()</code> |
| m | <code>-(YModule*) module</code> |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | <code>YModule get_module()</code> |
| java | <code>YModule get_module()</code> |
| py | <code>def get_module()</code> |

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

pressure→get_module_async()
pressure→module_async()**YPressure**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js   function get_module_async( callback, context )
nodejs function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

```
pressure->get_recordedData()  
pressure->recordedData()  
pressure.get_recordedData()
```

YPressure

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the `DataSet` class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measurement, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of `YDataSet`, providing access to historical data. Past measures can be loaded progressively using methods from the `YDataSet` object.

pressure→get_reportFrequency()
pressure→reportFrequency()
pressure.get_reportFrequency()

YPressure

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
js   function get_reportFrequency( )  
nodejs function get_reportFrequency( )  
php  function get_reportFrequency( )  
cpp   string get_reportFrequency( )  
m    -(NSString*) reportFrequency  
pas   function get_reportFrequency( ): string  
vb    function get_reportFrequency( ) As String  
cs    string get_reportFrequency( )  
java  String get_reportFrequency( )  
py    def get_reportFrequency( )  
cmd   YPressure target get_reportFrequency
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns `Y_REPORTFREQUENCY_INVALID`.

pressure→get_resolution() YPressure
pressure→resolution()pressure.get_resolution()

Returns the resolution of the measured values.

```
js function get_resolution( )
node.js function get_resolution( )
php function get_resolution( )
cpp double get_resolution( )
m -(double) resolution
pas function get_resolution( ): double
vb function get_resolution( ) As Double
cs double get_resolution( )
java double get_resolution( )
py def get_resolution( )
cmd YPressure target get_resolution
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

pressure→get_unit()**YPressure****pressure→unit()pressure.get_unit()**

Returns the measuring unit for the pressure.

| | |
|--------|---------------------------------------|
| js | function get_unit() |
| nodejs | function get_unit() |
| php | function get_unit() |
| cpp | string get_unit() |
| m | -(NSString*) unit |
| pas | function get_unit() : string |
| vb | function get_unit() As String |
| cs | string get_unit() |
| java | String get_unit() |
| py | def get_unit() |
| cmd | YPressure target get_unit |

Returns :

a string corresponding to the measuring unit for the pressure

On failure, throws an exception or returns Y_UNIT_INVALID.

pressure→get(userData)**YPressure****pressure→userData()pressure.get(userData())**

Returns the value of the userData attribute, as previously stored using method set(userData).

```
js function get(userData) 
node.js function get(userData) 
php function get(userData) 
cpp void * get(userData) 
m -(void*) userData 
pas function get(userData): Tobject 
vb function get(userData) As Object 
cs object get(userData) 
java Object get(userData) 
py def get(userData)
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

pressure→isOnline()pressure.isOnline()**YPressure**

Checks if the pressure sensor is currently reachable, without raising any error.

| | |
|---------|--|
| js | function isOnline() |
| node.js | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | -(BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the pressure sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the pressure sensor.

Returns :

true if the pressure sensor can be reached, and false otherwise

pressure→isOnline_async()

YPressure

Checks if the pressure sensor is currently reachable, without raising any error (asynchronous version).

```
js   function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the pressure sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

pressure→load()pressure.load()

YPressure

Preloads the pressure sensor cache with a specified validity duration.

```
js function load( msValidity)
nodejs function load( msValidity)
php function load( $msValidity)
cpp YRETCODE load( int msValidity)
m -(YRETCODE) load : (int) msValidity
pas function load( msValidity: integer): YRETCODE
vb function load( ByVal msValidity As Integer) As YRETCODE
cs YRETCODE load( int msValidity)
java int load( long msValidity)
py def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

pressure→loadCalibrationPoints() pressure.loadCalibrationPoints()

YPressure

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```

js   function loadCalibrationPoints( rawValues, refValues)
nodejs function loadCalibrationPoints( rawValues, refValues)
php   function loadCalibrationPoints( &$rawValues, &$refValues)
cpp   int loadCalibrationPoints( vector<double>& rawValues,
                                vector<double>& refValues)
m    -(int) loadCalibrationPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues
pas  function loadCalibrationPoints( var rawValues: TDoubleArray,
                           var refValues: TDoubleArray): LongInt
vb   procedure loadCalibrationPoints( )
cs   int loadCalibrationPoints( List<double> rawValues,
                           List<double> refValues)
java int loadCalibrationPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)
py   def loadCalibrationPoints( rawValues, refValues)
cmd  YPressure target loadCalibrationPoints rawValues refValues

```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pressure→load_async()

YPressure

Preloads the pressure sensor cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

pressure→nextPressure()pressure.nextPressure()**YPressure**

Continues the enumeration of pressure sensors started using `yFirstPressure()`.

| | |
|--------|---|
| js | function nextPressure() |
| nodejs | function nextPressure() |
| php | function nextPressure() |
| cpp | YPressure * nextPressure() |
| m | -(YPressure*) nextPressure |
| pas | function nextPressure() : TYPressure |
| vb | function nextPressure() As YPressure |
| cs | YPressure nextPressure() |
| java | YPressure nextPressure() |
| py | def nextPressure() |

Returns :

a pointer to a `YPressure` object, corresponding to a pressure sensor currently online, or a `null` pointer if there are no more pressure sensors to enumerate.

pressure→registerTimedReportCallback() pressure.registerTimedReportCallback()

YPressure

Registers the callback function that is invoked on every periodic timed notification.

| | |
|---------|---|
| js | function registerTimedReportCallback(callback) |
| node.js | function registerTimedReportCallback(callback) |
| php | function registerTimedReportCallback(\$callback) |
| cpp | int registerTimedReportCallback(YPressureTimedReportCallback callback) |
| m | -(int) registerTimedReportCallback : (YPressureTimedReportCallback) callback |
| pas | function registerTimedReportCallback(callback : TYPressureTimedReportCallback): LongInt |
| vb | function registerTimedReportCallback() As Integer |
| cs | int registerTimedReportCallback(TimedReportCallback callback) |
| java | int registerTimedReportCallback(TimedReportCallback callback) |
| py | def registerTimedReportCallback(callback) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

**pressure→registerValueCallback()
pressure.registerValueCallback()****YPressure**

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YPressureValueCallback callback )
m    -(int) registerValueCallback : (YPressureValueCallback) callback
pas   function registerValueCallback( callback: TYPressureValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

pressure→set_highestValue()
pressure→setHighestValue()
pressure.set_highestValue()

YPressure

Changes the recorded maximal value observed for the pressure.

| | |
|---------------------|--|
| <code>js</code> | function set_highestValue(newval) |
| <code>nodejs</code> | function set_highestValue(newval) |
| <code>php</code> | function set_highestValue(\$newval) |
| <code>cpp</code> | int set_highestValue(double newval) |
| <code>m</code> | -(int) setHighestValue : (double) newval |
| <code>pas</code> | function set_highestValue(newval: double): integer |
| <code>vb</code> | function set_highestValue(ByVal newval As Double) As Integer |
| <code>cs</code> | int set_highestValue(double newval) |
| <code>java</code> | int set_highestValue(double newval) |
| <code>py</code> | def set_highestValue(newval) |
| <code>cmd</code> | YPressure target set_highestValue newval |

Parameters :

newval a floating point number corresponding to the recorded maximal value observed for the pressure

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

pressure→set_logFrequency()
pressure→setLogFrequency()
pressure.set_logFrequency()

YPressure

Changes the datalogger recording frequency for this function.

```
js   function set_logFrequency( newval)
nodejs function set_logFrequency( newval)
php  function set_logFrequency( $newval)
cpp   int set_logFrequency( const string& newval)
m    -(int) setLogFrequency : (NSString*) newval
pas   function set_logFrequency( newval: string): integer
vb    function set_logFrequency( ByVal newval As String) As Integer
cs    int set_logFrequency( string newval)
java  int set_logFrequency( String newval)
py    def set_logFrequency( newval)
cmd   YPressure target set_logFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pressure→set_logicalName()
pressure→setLogicalName()
pressure.set_logicalName()

YPressure

Changes the logical name of the pressure sensor.

| | |
|---------------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YPressure target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the pressure sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

pressure→set_lowestValue()
pressure→setLowestValue()
pressure.set_lowestValue()

YPressure

Changes the recorded minimal value observed for the pressure.

```
js function set_lowestValue( newval)
nodejs function set_lowestValue( newval)
php function set_lowestValue( $newval)
cpp int set_lowestValue( double newval)
m -(int) setLowestValue : (double) newval
pas function set_lowestValue( newval: double): integer
vb function set_lowestValue( ByVal newval As Double) As Integer
cs int set_lowestValue( double newval)
java int set_lowestValue( double newval)
py def set_lowestValue( newval)
cmd YPressure target set_lowestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed for the pressure

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pressure→set_reportFrequency()
pressure→setReportFrequency()
pressure.set_reportFrequency()

YPressure

Changes the timed value notification frequency for this function.

| | |
|---------|---|
| js | function set_reportFrequency(newval) |
| node.js | function set_reportFrequency(newval) |
| php | function set_reportFrequency(\$newval) |
| cpp | int set_reportFrequency(const string& newval) |
| m | -(int) setReportFrequency : (NSString*) newval |
| pas | function set_reportFrequency(newval: string): integer |
| vb | function set_reportFrequency(ByVal newval As String) As Integer |
| cs | int set_reportFrequency(string newval) |
| java | int set_reportFrequency(String newval) |
| py | def set_reportFrequency(newval) |
| cmd | YPressure target set_reportFrequency newval |

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pressure→set_resolution() pressure→setResolution()pressure.set_resolution()

YPressure

Changes the resolution of the measured physical values.

```
js function set_resolution( newval)
node.js function set_resolution( newval)
php function set_resolution( $newval)
cpp int set_resolution( double newval)
m -(int) setResolution : (double) newval
pas function set_resolution( newval: double): integer
vb function set_resolution( ByVal newval As Double) As Integer
cs int set_resolution( double newval)
java int set_resolution( double newval)
py def set_resolution( newval)
cmd YPressure target set_resolution newval
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pressure→set(userData)**YPressure****pressure→setUserData()|pressure.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|---|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData) |
| cpp | void set(userData) (void* data) |
| m | -(void) set(userData : (void*) data |
| pas | procedure set(userData : Tobject) |
| vb | procedure set(userData : ByVal data As Object) |
| cs | void set(userData : object data) |
| java | void set(userData : Object data) |
| py | def set(userData : data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

pressure→wait_async()

YPressure

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.30. Pwm function interface

The Yoctopuce application programming interface allows you to configure, start, and stop the PWM.

In order to use the functions described here, you should include:

| | |
|---------|---|
| js | <script type='text/javascript' src='yocto_pwmoutput.js'></script> |
| node.js | var yoctolib = require('yoctolib'); |
| | var YPwmOutput = yoctolib.YPwmOutput; |
| php | require_once('yocto_pwmoutput.php'); |
| cpp | #include "yocto_pwmoutput.h" |
| m | #import "yocto_pwmoutput.h" |
| pas | uses yocto_pwmoutput; |
| vb | yocto_pwmoutput.vb |
| cs | yocto_pwmoutput.cs |
| java | import com.yoctopuce.YoctoAPI.YPwmOutput; |
| py | from yocto_pwmoutput import * |

Global functions

yFindPwmOutput(func)

Retrieves a PWM for a given identifier.

yFirstPwmOutput()

Starts the enumeration of PWMs currently accessible.

YPwmOutput methods

pwmoutput→describe()

Returns a short text that describes unambiguously the instance of the PWM in the form TYPE (NAME)=SERIAL .FUNCTIONID.

pwmoutput→dutyCycleMove(target, ms_duration)

Performs a smooth change of the pulse duration toward a given value.

pwmoutput→get_advertisedValue()

Returns the current value of the PWM (no more than 6 characters).

pwmoutput→get_dutyCycle()

Returns the PWMs duty cyle as a floating point number between 0 an 1.

pwmoutput→get_dutyCycleAtPowerOn()

Returns the PWMs duty cycle at device power up as a floating point number between 0.0 and 100.

pwmoutput→get_enabled()

Returns the state of the PWMs.

pwmoutput→get_enabledAtPowerOn()

Returns the state of the PWMs at device power up.

pwmoutput→get_errorMessage()

Returns the error message of the latest error with the PWM.

pwmoutput→get_errorType()

Returns the numerical error code of the latest error with the PWM.

pwmoutput→get_frequency()

Returns the PWM frequency in Hz.

pwmoutput→get_friendlyName()

Returns a global identifier of the PWM in the format MODULE_NAME . FUNCTION_NAME.

pwmoutput→get_functionDescriptor()

3. Reference

| |
|---|
| Returns a unique identifier of type YFUN_DESCR corresponding to the function. |
| pwmoutput->get_functionId() Returns the hardware identifier of the PWM, without reference to the module. |
| pwmoutput->get_hardwareId() Returns the unique hardware identifier of the PWM in the form SERIAL.FUNCTIONID. |
| pwmoutput->get_logicalName() Returns the logical name of the PWM. |
| pwmoutput->get_module() Gets the YModule object for the device on which the function is located. |
| pwmoutput->get_module_async(callback, context) Gets the YModule object for the device on which the function is located (asynchronous version). |
| pwmoutput->get_period() Returns the PWM period in nanoseconds. |
| pwmoutput->get_pulseDuration() Returns the PWM pulse length in milliseconds. |
| pwmoutput->get_userData() Returns the value of the userData attribute, as previously stored using method set(userData). |
| pwmoutput->isOnline() Checks if the PWM is currently reachable, without raising any error. |
| pwmoutput->isOnline_async(callback, context) Checks if the PWM is currently reachable, without raising any error (asynchronous version). |
| pwmoutput->load(msValidity) Preloads the PWM cache with a specified validity duration. |
| pwmoutput->load_async(msValidity, callback, context) Preloads the PWM cache with a specified validity duration (asynchronous version). |
| pwmoutput->nextPwmOutput() Continues the enumeration of PWMs started using yFirstPwmOutput(). |
| pwmoutput->pulseDurationMove(ms_target, ms_duration) Performs a smooth change of the pulse duration toward a given value. |
| pwmoutput->registerValueCallback(callback) Registers the callback function that is invoked on every change of advertised value. |
| pwmoutput->set_dutyCycle(newval) Configures the PWMs duty cycle. |
| pwmoutput->set_dutyCycleAtPowerOn(newval) Configures the PWMs duty cycle at device power up. |
| pwmoutput->set_enabled(newval) Stops or starts the PWM. |
| pwmoutput->set_enabledAtPowerOn(newval) Configures the state of PWM at device power up. |
| pwmoutput->set_frequency(newval) Configures the PWM frequency. |
| pwmoutput->set_logicalName(newval) Changes the logical name of the PWM. |
| pwmoutput->set_period(newval) Configures the PWM period. |

pwmoutput→set_pulseDuration(newval)

Configures the PWM pulses length.

pwmoutput→set(userData)

Stores a user context provided as argument in the userData attribute of the function.

pwmoutput→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YPwmOutput.FindPwmOutput() yFindPwmOutput()YPwmOutput.FindPwmOutput()

Retrieves a PWM for a given identifier.

| | |
|----------------------|---|
| <code>js</code> | <code>function yFindPwmOutput(func)</code> |
| <code>node.js</code> | <code>function FindPwmOutput(func)</code> |
| <code>php</code> | <code>function yFindPwmOutput(\$func)</code> |
| <code>cpp</code> | <code>YPwmOutput* yFindPwmOutput(const string& func)</code> |
| <code>m</code> | <code>YPwmOutput* yFindPwmOutput(NSString* func)</code> |
| <code>pas</code> | <code>function yFindPwmOutput(func: string): TYPwmOutput</code> |
| <code>vb</code> | <code>function yFindPwmOutput(ByVal func As String) As YPwmOutput</code> |
| <code>cs</code> | <code>YPwmOutput FindPwmOutput(string func)</code> |
| <code>java</code> | <code>YPwmOutput FindPwmOutput(String func)</code> |
| <code>py</code> | <code>def FindPwmOutput(func)</code> |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the PWM is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YPwmOutput.isOnline()` to test if the PWM is indeed online at a given time. In case of ambiguity when looking for a PWM by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the PWM

Returns :

a `YPwmOutput` object allowing you to drive the PWM.

YPwmOutput.FirstPwmOutput()**yFirstPwmOutput()YPwmOutput.FirstPwmOutput()****YPwmOutput**

Starts the enumeration of PWMs currently accessible.

| | |
|---------|--|
| js | function yFirstPwmOutput() |
| node.js | function FirstPwmOutput() |
| php | function yFirstPwmOutput() |
| cpp | YPwmOutput* yFirstPwmOutput() |
| m | YPwmOutput* yFirstPwmOutput() |
| pas | function yFirstPwmOutput(): TYPwmOutput |
| vb | function yFirstPwmOutput() As YPwmOutput |
| cs | YPwmOutput FirstPwmOutput() |
| java | YPwmOutput FirstPwmOutput() |
| py | def FirstPwmOutput() |

Use the method `YPwmOutput.nextPwmOutput()` to iterate on next PWMs.

Returns :

a pointer to a `YPwmOutput` object, corresponding to the first PWM currently online, or a `null` pointer if there are none.

pwmoutput→describe()pwmoutput.describe()**YPwmOutput**

Returns a short text that describes unambiguously the instance of the PWM in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the PWM (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

pwmoutput→dutyCycleMove() pwmoutput.dutyCycleMove()

YPwmOutput

Performs a smooth change of the pulse duration toward a given value.

| | |
|--------|---|
| js | function dutyCycleMove(target, ms_duration) |
| nodejs | function dutyCycleMove(target, ms_duration) |
| php | function dutyCycleMove(\$target, \$ms_duration) |
| cpp | int dutyCycleMove(double target, int ms_duration) |
| m | -(int) dutyCycleMove : (double) target : (int) ms_duration |
| pas | function dutyCycleMove(target: double, ms_duration: LongInt): LongInt |
| vb | function dutyCycleMove() As Integer |
| cs | int dutyCycleMove(double target, int ms_duration) |
| java | int dutyCycleMove(double target, int ms_duration) |
| py | def dutyCycleMove(target, ms_duration) |
| cmd | YPwmOutput target dutyCycleMove target ms_duration |

Parameters :

target new duty cycle at the end of the transition (floating-point number, between 0 and 1)

ms_duration total duration of the transition, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

pwmoutput→get_advertisedValue()
pwmoutput→advertisedValue()
pwmoutput.get_advertisedValue()**YPwmOutput**

Returns the current value of the PWM (no more than 6 characters).

| | |
|--------|---|
| js | function get_advertisedValue() |
| nodejs | function get_advertisedValue() |
| php | function get_advertisedValue() |
| cpp | string get_advertisedValue() |
| m | -(NSString*) advertisedValue |
| pas | function get_advertisedValue(): string |
| vb | function get_advertisedValue() As String |
| cs | string get_advertisedValue() |
| java | String get_advertisedValue() |
| py | def get_advertisedValue() |
| cmd | YPwmOutput target get_advertisedValue |

Returns :

a string corresponding to the current value of the PWM (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

pwmoutput→get_dutyCycle()**YPwmOutput****pwmoutput→dutyCycle()pwmoutput.get_dutyCycle()**

Returns the PWMs dutty cyle as a floating point number between 0 an 1.

| | |
|--------|--|
| js | function get_dutyCycle() |
| nodejs | function get_dutyCycle() |
| php | function get_dutyCycle() |
| cpp | double get_dutyCycle() |
| m | -(double) dutyCycle |
| pas | function get_dutyCycle(): double |
| vb | function get_dutyCycle() As Double |
| cs | double get_dutyCycle() |
| java | double get_dutyCycle() |
| py | def get_dutyCycle() |
| cmd | YPwmOutput target get_dutyCycle |

Returns :

a floating point number corresponding to the PWMs dutty cyle as a floating point number between 0 an 1

On failure, throws an exception or returns **Y_DUTYCYCLE_INVALID**.

`pwmoutput->get_dutyCycleAtPowerOn()`
`pwmoutput->dutyCycleAtPowerOn()`
`pwmoutput.get_dutyCycleAtPowerOn()`

YPwmOutput

Returns the PWMs duty cycle at device power up as a floating point number between 0.0 and 100.

`js` `function get_dutyCycleAtPowerOn()`
`nodejs` `function get_dutyCycleAtPowerOn()`
`php` `function get_dutyCycleAtPowerOn()`
`cpp` `double get_dutyCycleAtPowerOn()`
`m` `-(double) dutyCycleAtPowerOn`
`pas` `function get_dutyCycleAtPowerOn(): double`
`vb` `function get_dutyCycleAtPowerOn() As Double`
`cs` `double get_dutyCycleAtPowerOn()`
`java` `double get_dutyCycleAtPowerOn()`
`py` `def get_dutyCycleAtPowerOn()`
`cmd` `YPwmOutput target get_dutyCycleAtPowerOn`

0%

Returns :

a floating point number corresponding to the PWMs duty cycle at device power up as a floating point number between 0.0 and 100

On failure, throws an exception or returns Y_DUTYCYCLEATPOWERON_INVALID.

pwmoutput→get_enabled()**YPwmOutput****pwmoutput→enabled()pwmoutput.get_enabled()**

Returns the state of the PWMs.

| | |
|--------|---|
| js | function get_enabled() |
| nodejs | function get_enabled() |
| php | function get_enabled() |
| cpp | Y_ENABLED_enum get_enabled() |
| m | -(Y_ENABLED_enum) enabled |
| pas | function get_enabled(): Integer |
| vb | function get_enabled() As Integer |
| cs | int get_enabled() |
| java | int get_enabled() |
| py | def get_enabled() |
| cmd | YPwmOutput target get_enabled |

Returns :

either Y_ENABLED_FALSE or Y_ENABLED_TRUE, according to the state of the PWMs

On failure, throws an exception or returns Y_ENABLED_INVALID.

pwmoutput→get_enabledAtPowerOn()
pwmoutput→enabledAtPowerOn()
pwmoutput.get_enabledAtPowerOn()

YPwmOutput

Returns the state of the PWMs at device power up.

```
js function get_enabledAtPowerOn( )
nodejs function get_enabledAtPowerOn( )
php function get_enabledAtPowerOn( )
cpp Y_ENABLEDATPOWERON_enum get_enabledAtPowerOn( )
m -(Y_ENABLEDATPOWERON_enum) enabledAtPowerOn
pas function get_enabledAtPowerOn( ): Integer
vb function get_enabledAtPowerOn( ) As Integer
cs int get_enabledAtPowerOn( )
java int get_enabledAtPowerOn( )
py def get_enabledAtPowerOn( )
cmd YPwmOutput target get_enabledAtPowerOn
```

Returns :

either Y_ENABLEDATPOWERON_FALSE or Y_ENABLEDATPOWERON_TRUE, according to the state of the PWMs at device power up

On failure, throws an exception or returns Y_ENABLEDATPOWERON_INVALID.

pwmoutput→get_errorMessage()
pwmoutput→errorMessage()
pwmoutput.get_errorMessage()**YPwmOutput**

Returns the error message of the latest error with the PWM.

| | |
|---------|---|
| js | function get_errorMessage() |
| node.js | function get_errorMessage() |
| php | function get_errorMessage() |
| cpp | string get_errorMessage() |
| m | -(NSString*) errorMessage |
| pas | function get_errorMessage() : string |
| vb | function get_errorMessage() As String |
| cs | string get_errorMessage() |
| java | String get_errorMessage() |
| py | def get_errorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the PWM object

pwmoutput→get_errorType()**YPwmOutput****pwmoutput→errorType()pwmoutput.get_errorType()**

Returns the numerical error code of the latest error with the PWM.

| | |
|---------|--|
| js | function get_errorType() |
| node.js | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType() : YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the PWM object

pwmoutput→get_frequency() pwmoutput→frequency()pwmoutput.get_frequency()

Returns the PWM frequency in Hz.

| | |
|--------|---|
| js | function get_frequency() |
| nodejs | function get_frequency() |
| php | function get_frequency() |
| cpp | int get_frequency() |
| m | -(int) frequency |
| pas | function get_frequency() : LongInt |
| vb | function get_frequency() As Integer |
| cs | int get_frequency() |
| java | int get_frequency() |
| py | def get_frequency() |
| cmd | YPwmOutput target get_frequency |

Returns :

an integer corresponding to the PWM frequency in Hz

On failure, throws an exception or returns Y_FREQUENCY_INVALID.

pwmoutput→get_friendlyName()
pwmoutput→friendlyName()
pwmoutput.get_friendlyName()

YPwmOutput

Returns a global identifier of the PWM in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the PWM if they are defined, otherwise the serial number of the module and the hardware identifier of the PWM (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the PWM using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

**pwmoutput→get_functionDescriptor()
pwmoutput→functionDescriptor()
pwmoutput.get_functionDescriptor()****YPwmOutput**

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

pwmoutput→get_functionId()**YPwmOutput****pwmoutput→functionId()pwmoutput.get_functionId()**

Returns the hardware identifier of the PWM, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the PWM (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

**pwmoutput→get_hardwareId()
pwmoutput→hardwareId()
pwmoutput.get_hardwareId()****YPwmOutput**

Returns the unique hardware identifier of the PWM in the form SERIAL.FUNCTIONID.

| | |
|---------|---|
| js | function get_hardwareId() |
| node.js | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the PWM. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the PWM (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

pwmoutput→get_logicalName()
pwmoutput→logicalName()
pwmoutput.get_logicalName()

YPwmOutput

Returns the logical name of the PWM.

| | |
|--------|--|
| js | function get_logicalName() |
| nodejs | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | -(NSString*) logicalName |
| pas | function get_logicalName() : string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YPwmOutput target get_logicalName |

Returns :

a string corresponding to the logical name of the PWM. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

pwmoutput→get_module()**YPwmOutput****pwmoutput→module()pwmoutput.get_module()**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

pwmoutput→get_module_async()
pwmoutput→module_async()**YPwmOutput**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

`js` `function get_module_async(callback, context)`
`node.js` `function get_module_async(callback, context)`

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

pwmoutput→get_period() pwmoutput→period()pwmoutput.get_period()

YPwmOutput

Returns the PWM period in nonaseconde.

| | |
|---------|---|
| js | function get_period() |
| node.js | function get_period() |
| php | function get_period() |
| cpp | double get_period() |
| m | -(double) period |
| pas | function get_period(): double |
| vb | function get_period() As Double |
| cs | double get_period() |
| java | double get_period() |
| py | def get_period() |
| cmd | YPwmOutput target get_period |

Returns :

a floating point number corresponding to the PWM period in nonaseconde

On failure, throws an exception or returns Y_PERIOD_INVALID.

pwmoutput→get_pulseDuration()
pwmoutput→pulseDuration()
pwmoutput.get_pulseDuration()**YPwmOutput**

Returns the PWM pulse length in milliseconds.

| | |
|--------|---|
| js | function get_pulseDuration() |
| nodejs | function get_pulseDuration() |
| php | function get_pulseDuration() |
| cpp | double get_pulseDuration() |
| m | -(double) pulseDuration |
| pas | function get_pulseDuration(): double |
| vb | function get_pulseDuration() As Double |
| cs | double get_pulseDuration() |
| java | double get_pulseDuration() |
| py | def get_pulseDuration() |
| cmd | YPwmOutput target get_pulseDuration |

Returns :

a floating point number corresponding to the PWM pulse length in milliseconds

On failure, throws an exception or returns Y_PULSE_DURATION_INVALID.

pwmoutput→get(userData)**YPwmOutput****pwmoutput→userData()pwmoutput.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|---|
| js | <code>function get(userData) </code> |
| nodejs | <code>function get(userData) </code> |
| php | <code>function get(userData) </code> |
| cpp | <code>void * get(userData) </code> |
| m | <code>-(void*) userData</code> |
| pas | <code>function get(userData): Tobject</code> |
| vb | <code>function get(userData) As Object</code> |
| cs | <code>object get(userData) </code> |
| java | <code>Object get(userData) </code> |
| py | <code>def get(userData) </code> |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

pwmoutput→isOnline()pwmoutput.isOnline()**YPwmOutput**

Checks if the PWM is currently reachable, without raising any error.

| | |
|--------|---------------------------------------|
| js | function isOnline() |
| nodejs | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the PWM in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the PWM.

Returns :

true if the PWM can be reached, and false otherwise

pwmoutput→isOnline_async()

YPwmOutput

Checks if the PWM is currently reachable, without raising any error (asynchronous version).

```
js   function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the PWM in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

pwmoutput→load()pwmoutput.load()

YPwmOutput

Preloads the PWM cache with a specified validity duration.

| | |
|--------|--|
| js | function load(msValidity) |
| nodejs | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | -(YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

pwmoutput→load_async()

YPwmOutput

Preloads the PWM cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

pwmoutput→nextPwmOutput()
pwmoutput.nextPwmOutput()**YPwmOutput**

Continues the enumeration of PWMs started using `yFirstPwmOutput()`.

| | |
|---------|---|
| js | function nextPwmOutput() |
| node.js | function nextPwmOutput() |
| php | function nextPwmOutput() |
| cpp | YPwmOutput * nextPwmOutput() |
| m | -(YPwmOutput*) nextPwmOutput |
| pas | function nextPwmOutput() : TYPwmOutput |
| vb | function nextPwmOutput() As YPwmOutput |
| cs | YPwmOutput nextPwmOutput() |
| java | YPwmOutput nextPwmOutput() |
| py | def nextPwmOutput() |

Returns :

a pointer to a `YPwmOutput` object, corresponding to a PWM currently online, or a null pointer if there are no more PWMs to enumerate.

pwmoutput→pulseDurationMove() pwmoutput.pulseDurationMove()

YPwmOutput

Performs a smooth change of the pulse duration toward a given value.

| | |
|--------|--|
| js | function pulseDurationMove(ms_target, ms_duration) |
| nodejs | function pulseDurationMove(ms_target, ms_duration) |
| php | function pulseDurationMove(\$ms_target, \$ms_duration) |
| cpp | int pulseDurationMove(double ms_target, int ms_duration) |
| m | -(int) pulseDurationMove : (double) ms_target : (int) ms_duration |
| pas | function pulseDurationMove(ms_target: double, ms_duration: LongInt): LongInt |
| vb | function pulseDurationMove() As Integer |
| cs | int pulseDurationMove(double ms_target, int ms_duration) |
| java | int pulseDurationMove(double ms_target, int ms_duration) |
| py | def pulseDurationMove(ms_target, ms_duration) |
| cmd | YPwmOutput target pulseDurationMove ms_target ms_duration |

Parameters :

ms_target new pulse duration at the end of the transition (floating-point number, representing the pulse duration in milliseconds)
ms_duration total duration of the transition, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

pwmoutput→registerValueCallback() pwmoutput.registerValueCallback()

YPwmOutput

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YPwmOutputValueCallback callback )
m    -(int) registerValueCallback : (YPwmOutputValueCallback) callback
pas   function registerValueCallback( callback: TYPwmOutputValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

pwmoutput→set_dutyCycle()
pwmoutput→setDutyCycle()
pwmoutput.set_dutyCycle()

YPwmOutput

Configures the PWMs duty cycle.

| | |
|---------------|---|
| js | function set_dutyCycle(newval) |
| nodejs | function set_dutyCycle(newval) |
| php | function set_dutyCycle(\$newval) |
| cpp | int set_dutyCycle(double newval) |
| m | -(int) setDutyCycle : (double) newval |
| pas | function set_dutyCycle(newval: double): integer |
| vb | function set_dutyCycle(ByVal newval As Double) As Integer |
| cs | int set_dutyCycle(double newval) |
| java | int set_dutyCycle(double newval) |
| py | def set_dutyCycle(newval) |
| cmd | YPwmOutput target set_dutyCycle newval |

Parameters :

newval a floating point number

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmoutput→set_dutyCycleAtPowerOn()
pwmoutput→setDutyCycleAtPowerOn()
pwmoutput.set_dutyCycleAtPowerOn()

YPwmOutput

Configures the PWMs duty cycle at device power up.

```
js function set_dutyCycleAtPowerOn( newval)
nodejs function set_dutyCycleAtPowerOn( newval)
php function set_dutyCycleAtPowerOn( $newval)
cpp int set_dutyCycleAtPowerOn( double newval)
m -(int) setDutyCycleAtPowerOn : (double) newval
pas function set_dutyCycleAtPowerOn( newval: double): integer
vb function set_dutyCycleAtPowerOn( ByVal newval As Double) As Integer
cs int set_dutyCycleAtPowerOn( double newval)
java int set_dutyCycleAtPowerOn( double newval)
py def set_dutyCycleAtPowerOn( newval)
cmd YPwmOutput target set_dutyCycleAtPowerOn newval
```

Remember to call the matching module `saveToFlash()` method, otherwise this call will have no effect.

Parameters :

newval a floating point number

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmoutput→set_enabled()**YPwmOutput****pwmoutput→setEnabled()pwmoutput.set_enabled()**

Stops or starts the PWM.

| | |
|--------|--|
| js | function set_enabled(newval) |
| nodejs | function set_enabled(newval) |
| php | function set_enabled(\$newval) |
| cpp | int set_enabled(Y_ENABLED_enum newval) |
| m | -(int) setEnabled : (Y_ENABLED_enum) newval |
| pas | function set_enabled(newval: Integer): integer |
| vb | function set_enabled(ByVal newval As Integer) As Integer |
| cs | int set_enabled(int newval) |
| java | int set_enabled(int newval) |
| py | def set_enabled(newval) |
| cmd | YPwmOutput target set_enabled newval |

Parameters :

newval either Y_ENABLED_FALSE or Y_ENABLED_TRUE

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmoutput→set_enabledAtPowerOn()
pwmoutput→setEnabledAtPowerOn()
pwmoutput.set_enabledAtPowerOn()

YPwmOutput

Configures the state of PWM at device power up.

| | |
|---------------|---|
| js | <code>function set_enabledAtPowerOn(newval)</code> |
| nodejs | <code>function set_enabledAtPowerOn(newval)</code> |
| php | <code>function set_enabledAtPowerOn(\$newval)</code> |
| cpp | <code>int set_enabledAtPowerOn(Y_ENABLEDATPOWERON_enum newval)</code> |
| m | <code>-(int) setEnabledAtPowerOn : (Y_ENABLEDATPOWERON_enum) newval</code> |
| pas | <code>function set_enabledAtPowerOn(newval: Integer): integer</code> |
| vb | <code>function set_enabledAtPowerOn(ByVal newval As Integer) As Integer</code> |
| cs | <code>int set_enabledAtPowerOn(int newval)</code> |
| java | <code>int set_enabledAtPowerOn(int newval)</code> |
| py | <code>def set_enabledAtPowerOn(newval)</code> |
| cmd | <code>YPwmOutput target set_enabledAtPowerOn newval</code> |

Remember to call the matching module `saveToFlash()` method, otherwise this call will have no effect.

Parameters :

newval either `Y_ENABLEDATPOWERON_FALSE` or `Y_ENABLEDATPOWERON_TRUE`

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmoutput→set_frequency()
pwmoutput→setFrequency()
pwmoutput.set_frequency()

YPwmOutput

Configures the PWM frequency.

```
js function set_frequency( newval)
node.js function set_frequency( newval)
php function set_frequency( $newval)
cpp int set_frequency( int newval)
m -(int) setFrequency : (int) newval
pas function set_frequency( newval: LongInt): integer
vb function set_frequency( ByVal newval As Integer) As Integer
cs int set_frequency( int newval)
java int set_frequency( int newval)
py def set_frequency( newval)
cmd YPwmOutput target set_frequency newval
```

The duty cycle is kept unchanged thanks to an automatic pulse width change.

Parameters :

newval an integer

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmoutput→set_logicalName()
pwmoutput→setLogicalName()
pwmoutput.set_logicalName()

YPwmOutput

Changes the logical name of the PWM.

| | |
|---------------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YPwmOutput target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the PWM.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

pwmoutput→set_period()**YPwmOutput****pwmoutput→setPeriod()pwmoutput.set_period()**

Configures the PWM period.

| | |
|---------|--|
| js | function set_period(newval) |
| node.js | function set_period(newval) |
| php | function set_period(\$newval) |
| cpp | int set_period(double newval) |
| m | -(int) setPeriod : (double) newval |
| pas | function set_period(newval: double): integer |
| vb | function set_period(ByVal newval As Double) As Integer |
| cs | int set_period(double newval) |
| java | int set_period(double newval) |
| py | def set_period(newval) |
| cmd | YPwmOutput target set_period newval |

Parameters :

newval a floating point number

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmoutput→set_pulseDuration()
pwmoutput→setPulseDuration()
pwmoutput.set_pulseDuration()

YPwmOutput

Configures the PWM pulses length.

```
js function set_pulseDuration( newval)
nodejs function set_pulseDuration( newval)
php function set_pulseDuration( $newval)
cpp int set_pulseDuration( double newval)
m -(int) setPulseDuration : (double) newval
pas function set_pulseDuration( newval: double): integer
vb function set_pulseDuration( ByVal newval As Double) As Integer
cs int set_pulseDuration( double newval)
java int set_pulseDuration( double newval)
py def set_pulseDuration( newval)
cmd YPwmOutput target set_pulseDuration newval
```

A pulse length cannot be longer than period, otherwise it is truncated.

Parameters :

newval a floating point number

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmoutput→set(userData)
pwmoutput→setUserData()
pwmoutput.set(userData)

YPwmOutput

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|---|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData \$data) |
| cpp | void set(userData void* data) |
| m | - (void) set(userData : (void*) data) |
| pas | procedure set(userData data: Tobject) |
| vb | procedure set(userData ByVal data As Object) |
| cs | void set(userData object data) |
| java | void set(userData Object data) |
| py | def set(userData data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

pwmoutput→wait_async()

YPwmOutput

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js   function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.31. PwmPowerSource function interface

The Yoctopuce application programming interface allows you to configure the voltage source used by all PWM on the same device.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_pwmpowersource.js'></script>
nodejs var yoctolib = require('yoctolib');
var YPwmPowerSource = yoctolib.YPwmPowerSource;
php require_once('yocto_pwmpowersource.php');
cpp #include "yocto_pwmpowersource.h"
m #import "yocto_pwmpowersource.h"
pas uses yocto_pwmpowersource;
vb yocto_pwmpowersource.vb
cs yocto_pwmpowersource.cs
java import com.yoctopuce.YoctoAPI.YPwmPowerSource;
py from yocto_pwmpowersource import *

```

Global functions

yFindPwmPowerSource(func)

Retrieves a voltage source for a given identifier.

yFirstPwmPowerSource()

Starts the enumeration of Voltage sources currently accessible.

YPwmPowerSource methods

pwmpowersource→describe()

Returns a short text that describes unambiguously the instance of the voltage source in the form
TYPE (NAME) = SERIAL . FUNCTIONID.

pwmpowersource→get_advertisedValue()

Returns the current value of the voltage source (no more than 6 characters).

pwmpowersource→get_errorMessage()

Returns the error message of the latest error with the voltage source.

pwmpowersource→get_errorType()

Returns the numerical error code of the latest error with the voltage source.

pwmpowersource→get_friendlyName()

Returns a global identifier of the voltage source in the format MODULE_NAME . FUNCTION_NAME.

pwmpowersource→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

pwmpowersource→get_functionId()

Returns the hardware identifier of the voltage source, without reference to the module.

pwmpowersource→get_hardwareId()

Returns the unique hardware identifier of the voltage source in the form SERIAL . FUNCTIONID.

pwmpowersource→get_logicalName()

Returns the logical name of the voltage source.

pwmpowersource→get_module()

Gets the YModule object for the device on which the function is located.

pwmpowersource→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

3. Reference

pwmpowersource→get_powerMode()

Returns the selected power source for the PWM on the same device

pwmpowersource→get(userData)

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

pwmpowersource→isOnline()

Checks if the voltage source is currently reachable, without raising any error.

pwmpowersource→isOnline_async(callback, context)

Checks if the voltage source is currently reachable, without raising any error (asynchronous version).

pwmpowersource→load(msValidity)

Preloads the voltage source cache with a specified validity duration.

pwmpowersource→load_async(msValidity, callback, context)

Preloads the voltage source cache with a specified validity duration (asynchronous version).

pwmpowersource→nextPwmPowerSource()

Continues the enumeration of Voltage sources started using `yFirstPwmPowerSource()`.

pwmpowersource→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

pwmpowersource→set_logicalName(newval)

Changes the logical name of the voltage source.

pwmpowersource→set_powerMode(newval)

Changes the PWM power source.

pwmpowersource→set(userData)

Stores a user context provided as argument in the userData attribute of the function.

pwmpowersource→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YPwmPowerSource.FindPwmPowerSource() yFindPwmPowerSource() YPwmPowerSource.FindPwmPowerSource()

YPwmPowerSource

Retrieves a voltage source for a given identifier.

| | |
|---------|---|
| js | function yFindPwmPowerSource(func) |
| node.js | function FindPwmPowerSource(func) |
| php | function yFindPwmPowerSource(\$func) |
| cpp | YPwmPowerSource* yFindPwmPowerSource(const string& func) |
| m | YPwmPowerSource* yFindPwmPowerSource(NSString* func) |
| pas | function yFindPwmPowerSource(func: string): TYPwmPowerSource |
| vb | function yFindPwmPowerSource(ByVal func As String) As YPwmPowerSource |
| cs | YPwmPowerSource FindPwmPowerSource(string func) |
| java | YPwmPowerSource FindPwmPowerSource(String func) |
| py | def FindPwmPowerSource(func) |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the voltage source is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YPwmPowerSource.isOnline()` to test if the voltage source is indeed online at a given time. In case of ambiguity when looking for a voltage source by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the voltage source

Returns :

a `YPwmPowerSource` object allowing you to drive the voltage source.

YPwmPowerSource.FirstPwmPowerSource() yFirstPwmPowerSource() YPwmPowerSource.FirstPwmPowerSource()

YPwmPowerSource

Starts the enumeration of Voltage sources currently accessible.

| | |
|--------|--|
| js | function yFirstPwmPowerSource() |
| nodejs | function FirstPwmPowerSource() |
| php | function yFirstPwmPowerSource() |
| cpp | YPwmPowerSource* yFirstPwmPowerSource() |
| m | YPwmPowerSource* yFirstPwmPowerSource() |
| pas | function yFirstPwmPowerSource() : TYPwmPowerSource |
| vb | function yFirstPwmPowerSource() As YPwmPowerSource |
| cs | YPwmPowerSource FirstPwmPowerSource() |
| java | YPwmPowerSource FirstPwmPowerSource() |
| py | def FirstPwmPowerSource() |

Use the method `YPwmPowerSource.nextPwmPowerSource()` to iterate on next Voltage sources.

Returns :

a pointer to a `YPwmPowerSource` object, corresponding to the first source currently online, or a null pointer if there are none.

pwmpowersource→describe()

pwmpowersource.describe()

YPwmPowerSource

Returns a short text that describes unambiguously the instance of the voltage source in the form TYPE (NAME) =SERIAL.FUNCTIONID.

| | |
|--------|---------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | - (NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the voltage source (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

pwmpowersource→get_advertisedValue()
pwmpowersource→advertisedValue()
pwmpowersource.get_advertisedValue()

YPwmPowerSource

Returns the current value of the voltage source (no more than 6 characters).

```
js function get_advertisedValue( )  
nodejs function get_advertisedValue( )  
php function get_advertisedValue( )  
cpp string get_advertisedValue( )  
m -(NSString*) advertisedValue  
pas function get_advertisedValue( ): string  
vb function get_advertisedValue( ) As String  
cs string get_advertisedValue( )  
java String get_advertisedValue( )  
py def get_advertisedValue( )  
cmd YPwmPowerSource target get_advertisedValue
```

Returns :

a string corresponding to the current value of the voltage source (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

pwmpowersource→getErrorMessage()
pwmpowersource→errorMessage()
pwmpowersource.getErrorMessage()**YPwmPowerSource**

Returns the error message of the latest error with the voltage source.

| | |
|---------|--|
| js | function getErrorMessage() |
| node.js | function getErrorMessage() |
| php | function getErrorMessage() |
| cpp | string getErrorMessage() |
| m | -(NSString*) errorMessage |
| pas | function getErrorMessage() : string |
| vb | function getErrorMessage() As String |
| cs | string getErrorMessage() |
| java | String getErrorMessage() |
| py | def getErrorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the voltage source object

pwmpowersource→get_errorType()
pwmpowersource→errorType()
pwmpowersource.get_errorType()

YPwmPowerSource

Returns the numerical error code of the latest error with the voltage source.

| | |
|--------|---------------------------------------|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType(): YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the voltage source object

pwmpowersource→get_friendlyName()
pwmpowersource→friendlyName()
pwmpowersource.get_friendlyName()

YPwmPowerSource

Returns a global identifier of the voltage source in the format MODULE_NAME . FUNCTION_NAME.

| | |
|---------|------------------------------|
| js | function get_friendlyName() |
| node.js | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the voltage source if they are defined, otherwise the serial number of the module and the hardware identifier of the voltage source (for exemple: MyCustomName . relay1)

Returns :

a string that uniquely identifies the voltage source using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

pwmpowersource→get_functionDescriptor()
pwmpowersource→functionDescriptor()
pwmpowersource.get_functionDescriptor()

YPwmPowerSource

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|---|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

pwmpowersource→get_functionId()
pwmpowersource→functionId()
pwmpowersource.get_functionId()

YPwmPowerSource

Returns the hardware identifier of the voltage source, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the voltage source (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

pwmpowersource→get_hardwareId()
pwmpowersource→hardwareId()
pwmpowersource.get_hardwareId()

YPwmPowerSource

Returns the unique hardware identifier of the voltage source in the form SERIAL.FUNCTIONID.

| | |
|--------|---|
| js | function get_hardwareId() |
| nodejs | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the voltage source. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the voltage source (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

pwmpowersource→get_logicalName()
pwmpowersource→logicalName()
pwmpowersource.get_logicalName()

YPwmPowerSource

Returns the logical name of the voltage source.

| | |
|---------------|---|
| js | function get_logicalName() |
| nodejs | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | -(NSString*) logicalName |
| pas | function get_logicalName() : string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YPwmPowerSource target get_logicalName |

Returns :

a string corresponding to the logical name of the voltage source. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

pwmpowersource→get_module()
pwmpowersource→module()
pwmpowersource.get_module()

YPwmPowerSource

Gets the **YModule** object for the device on which the function is located.

| | |
|--------|---|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of **YModule** is not shown as online.

Returns :

an instance of **YModule**

pwmpowersource→get_module_async()
pwmpowersource→module_async()**YPwmPowerSource**

Gets the YModule object for the device on which the function is located (asynchronous version).

```
js   function get_module_async( callback, context )
nodejs function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned YModule object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested YModule object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

pwmpowersource→get_powerMode()
pwmpowersource→powerMode()
pwmpowersource.get_powerMode()

YPwmPowerSource

Returns the selected power source for the PWM on the same device

| | |
|--------|---|
| js | function get_powerMode() |
| nodejs | function get_powerMode() |
| php | function get_powerMode() |
| cpp | Y_POWERMODE_enum get_powerMode() |
| m | -(Y_POWERMODE_enum) powerMode |
| pas | function get_powerMode() : Integer |
| vb | function get_powerMode() As Integer |
| cs | int get_powerMode() |
| java | int get_powerMode() |
| py | def get_powerMode() |

Returns :

a value among Y_POWERMODE_USB_5V, Y_POWERMODE_USB_3V, Y_POWERMODE_EXT_V and Y_POWERMODE_OPNDRN corresponding to the selected power source for the PWM on the same device

On failure, throws an exception or returns Y_POWERMODE_INVALID.

pwmpowersource→get(userData)
pwmpowersource→userData()
pwmpowersource.get(userData())

YPwmPowerSource

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|---------|---|
| js | function get(userData) |
| node.js | function get(userData) |
| php | function get(userData) |
| cpp | void * get(userData) |
| m | -(void*) userData |
| pas | function get(userData) : Tobject |
| vb | function get(userData) As Object |
| cs | object get(userData) |
| java | Object get(userData) |
| py | def get(userData) |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

pwmpowersource→isOnline()
pwmpowersource.isOnline()**YPwmPowerSource**

Checks if the voltage source is currently reachable, without raising any error.

| | |
|---------|--|
| js | function isOnline() |
| node.js | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | -BOOL isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the voltage source in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the voltage source.

Returns :

true if the voltage source can be reached, and false otherwise

pwmpowersource→isOnline_async()**YPwmPowerSource**

Checks if the voltage source is currently reachable, without raising any error (asynchronous version).

```
js   function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the voltage source in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

pwmpowersource→load()pwmpowersource.load()**YPwmPowerSource**

Preloads the voltage source cache with a specified validity duration.

| | |
|--------|--|
| js | function load(msValidity) |
| nodejs | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | -(YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

pwmpowersource→load_async()

YPwmPowerSource

Preloads the voltage source cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

pwmpowersource→nextPwmPowerSource()
pwmpowersource.nextPwmPowerSource()**YPwmPowerSource**

Continues the enumeration of Voltage sources started using `yFirstPwmPowerSource().`

| | |
|----------------------|--|
| <code>js</code> | <code>function nextPwmPowerSource()</code> |
| <code>node.js</code> | <code>function nextPwmPowerSource()</code> |
| <code>php</code> | <code>function nextPwmPowerSource()</code> |
| <code>cpp</code> | <code>YPwmPowerSource * nextPwmPowerSource()</code> |
| <code>m</code> | <code>-(YPwmPowerSource*) nextPwmPowerSource</code> |
| <code>pas</code> | <code>function nextPwmPowerSource(): TYPwmPowerSource</code> |
| <code>vb</code> | <code>function nextPwmPowerSource() As YPwmPowerSource</code> |
| <code>cs</code> | <code>YPwmPowerSource nextPwmPowerSource()</code> |
| <code>java</code> | <code>YPwmPowerSource nextPwmPowerSource()</code> |
| <code>py</code> | <code>def nextPwmPowerSource()</code> |

Returns :

a pointer to a `YPwmPowerSource` object, corresponding to a voltage source currently online, or a null pointer if there are no more Voltage sources to enumerate.

pwmpowersource→registerValueCallback() pwmpowersource.registerValueCallback()

YPwmPowerSource

Registers the callback function that is invoked on every change of advertised value.

| | |
|----------------------|---|
| <code>js</code> | function registerValueCallback(<i>callback</i>) |
| <code>node.js</code> | function registerValueCallback(<i>callback</i>) |
| <code>php</code> | function registerValueCallback(\$callback) |
| <code>cpp</code> | int registerValueCallback(YPwmPowerSourceValueCallback <i>callback</i>) |
| <code>m</code> | -(int) registerValueCallback : (YPwmPowerSourceValueCallback) <i>callback</i> |
| <code>pas</code> | function registerValueCallback(<i>callback</i>: TYPwmPowerSourceValueCallback): LongInt |
| <code>vb</code> | function registerValueCallback() As Integer |
| <code>cs</code> | int registerValueCallback(ValueCallback <i>callback</i>) |
| <code>java</code> | int registerValueCallback(UpdateCallback <i>callback</i>) |
| <code>py</code> | def registerValueCallback(<i>callback</i>) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

pwmpowersource→set_logicalName()
pwmpowersource→setLogicalName()
pwmpowersource.set_logicalName()

YPwmPowerSource

Changes the logical name of the voltage source.

```
js function set_logicalName( newval)
nodejs function set_logicalName( newval)
php function set_logicalName( $newval)
cpp int set_logicalName( const string& newval)
m -(int) setLogicalName : (NSString*) newval
pas function set_logicalName( newval: string): integer
vb function set_logicalName( ByVal newval As String) As Integer
cs int set_logicalName( string newval)
java int set_logicalName( String newval)
py def set_logicalName( newval)
cmd YPwmPowerSource target set_logicalName newval
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the voltage source.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

pwmpowersource→set_powerMode()
pwmpowersource→setPowerMode()
pwmpowersource.set_powerMode()

YPwmPowerSource

Changes the PWM power source.

| | |
|---------|--|
| js | function set_powerMode(newval) |
| node.js | function set_powerMode(newval) |
| php | function set_powerMode(\$newval) |
| cpp | int set_powerMode(Y_POWERMODE_enum newval) |
| m | -(int) setPowerMode : (Y_POWERMODE_enum) newval |
| pas | function set_powerMode(newval: Integer): integer |
| vb | function set_powerMode(ByVal newval As Integer) As Integer |
| cs | int set_powerMode(int newval) |
| java | int set_powerMode(int newval) |
| py | def set_powerMode(newval) |
| cmd | YPwmPowerSource target set_powerMode newval |

PWM can use isolated 5V from USB, isolated 3V from USB or voltage from an external power source. The PWM can also work in open drain mode. In that mode, the PWM actively pulls the line down. Warning: this setting is common to all PWM on the same device. If you change that parameter, all PWM located on the same device are affected. If you want the change to be kept after a device reboot, make sure to call the matching module `saveToFlash()`.

Parameters :

newval a value among `Y_POWERMODE_USB_5V`, `Y_POWERMODE_USB_3V`, `Y_POWERMODE_EXT_V` and `Y_POWERMODE_OPNDRN` corresponding to the PWM power source

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmpowersource→set(userData)
pwmpowersource→setUserData()
pwmpowersource.set(userData)

YPwmPowerSource

Stores a user context provided as argument in the userData attribute of the function.

| | |
|--------|--------------------------------|
| js | function set(userData) |
| nodejs | function set(userData) |
| php | function set(userData) |
| cpp | void set(userData) |
| m | -(void) set(userData) |
| pas | procedure set(userData) |
| vb | procedure set(userData) |
| cs | void set(userData) |
| java | void set(userData) |
| py | def set(userData) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

pwmpowersource→wait_async()

YPwmPowerSource

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

`js` `function wait_async(callback, context)`

`nodejs` `function wait_async(callback, context)`

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.32. Quaternion interface

The Yoctopuce API YQt class provides direct access to the Yocto3D attitude estimation using a quaternion. It is usually not needed to use the YQt class directly, as the YGyro class provides a more convenient higher-level interface.

In order to use the functions described here, you should include:

| | |
|--------|--|
| js | <script type='text/javascript' src='yocto_gyro.js'></script> |
| nodejs | var yoctolib = require('yoctolib'); |
| | var YGyro = yoctolib.YGyro; |
| php | require_once('yocto_gyro.php'); |
| cpp | #include "yocto_gyro.h" |
| m | #import "yocto_gyro.h" |
| pas | uses yocto_gyro; |
| vb | yocto_gyro.vb |
| cs | yocto_gyro.cs |
| java | import com.yoctopuce.YoctoAPI.YGyro; |
| py | from yocto_gyro import * |

Global functions

yFindQt(func)

Retrieves a quaternion component for a given identifier.

yFirstQt()

Starts the enumeration of quaternion components currently accessible.

YQt methods

qt→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

qt→describe()

Returns a short text that describes unambiguously the instance of the quaternion component in the form TYPE (NAME) = SERIAL . FUNCTIONID.

qt→get_advertisedValue()

Returns the current value of the quaternion component (no more than 6 characters).

qt→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor.

qt→get_currentValue()

Returns the current value of the value.

qt→get_errorMessage()

Returns the error message of the latest error with the quaternion component.

qt→get_errorType()

Returns the numerical error code of the latest error with the quaternion component.

qt→get_friendlyName()

Returns a global identifier of the quaternion component in the format MODULE_NAME . FUNCTION_NAME.

qt→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

qt→get_functionId()

Returns the hardware identifier of the quaternion component, without reference to the module.

qt→get_hardwareId()

| |
|--|
| Returns the unique hardware identifier of the quaternion component in the form SERIAL.FUNCTIONID. |
| qt→get_highestValue() |
| Returns the maximal value observed for the value since the device was started. |
| qt→get_logFrequency() |
| Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory. |
| qt→get_logicalName() |
| Returns the logical name of the quaternion component. |
| qt→get_lowestValue() |
| Returns the minimal value observed for the value since the device was started. |
| qt→get_module() |
| Gets the YModule object for the device on which the function is located. |
| qt→get_module_async(callback, context) |
| Gets the YModule object for the device on which the function is located (asynchronous version). |
| qt→get_recordedData(startTime, endTime) |
| Retrieves a DataSet object holding historical data for this sensor, for a specified time interval. |
| qt→get_reportFrequency() |
| Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function. |
| qt→get_resolution() |
| Returns the resolution of the measured values. |
| qt→get_unit() |
| Returns the measuring unit for the value. |
| qt→get_userData() |
| Returns the value of the userData attribute, as previously stored using method set(userData). |
| qt→isOnline() |
| Checks if the quaternion component is currently reachable, without raising any error. |
| qt→isOnline_async(callback, context) |
| Checks if the quaternion component is currently reachable, without raising any error (asynchronous version). |
| qt→load(msValidity) |
| Preloads the quaternion component cache with a specified validity duration. |
| qt→loadCalibrationPoints(rawValues, refValues) |
| Retrieves error correction data points previously entered using the method calibrateFromPoints. |
| qt→load_async(msValidity, callback, context) |
| Preloads the quaternion component cache with a specified validity duration (asynchronous version). |
| qt→nextQt() |
| Continues the enumeration of quaternion components started using yFirstQt(). |
| qt→registerTimedReportCallback(callback) |
| Registers the callback function that is invoked on every periodic timed notification. |
| qt→registerValueCallback(callback) |
| Registers the callback function that is invoked on every change of advertised value. |
| qt→set_highestValue(newval) |
| Changes the recorded maximal value observed. |
| qt→set_logFrequency(newval) |
| Changes the datalogger recording frequency for this function. |
| qt→set_logicalName(newval) |

3. Reference

Changes the logical name of the quaternion component.

qt→set_lowestValue(newval)

Changes the recorded minimal value observed.

qt→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

qt→set_resolution(newval)

Changes the resolution of the measured physical values.

qt→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

qt→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YQt.FindQt()**yFindQt()YQt.FindQt()****YQt**

Retrieves a quaternion component for a given identifier.

| | |
|----------------------|---|
| <code>js</code> | <code>function yFindQt(func)</code> |
| <code>node.js</code> | <code>function FindQt(func)</code> |
| <code>php</code> | <code>function yFindQt(\$func)</code> |
| <code>cpp</code> | <code>YQt* yFindQt(string func)</code> |
| <code>m</code> | <code>+ (YQt*) yFindQt : (NSString*) func</code> |
| <code>pas</code> | <code>function yFindQt(func: string): TYQt</code> |
| <code>vb</code> | <code>function yFindQt(ByVal func As String) As YQt</code> |
| <code>cs</code> | <code>YQt FindQt(string func)</code> |
| <code>java</code> | <code>YQt FindQt(String func)</code> |
| <code>py</code> | <code>def FindQt(func)</code> |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the quaternion component is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YQt.isOnline()` to test if the quaternion component is indeed online at a given time. In case of ambiguity when looking for a quaternion component by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the quaternion component

Returns :

a `YQt` object allowing you to drive the quaternion component.

YQt.FirstQt() yFirstQt()YQt.FirstQt()

YQt

Starts the enumeration of quaternion components currently accessible.

```
js function yFirstQt( )
node.js function FirstQt( )
php function yFirstQt( )
cpp YQt* yFirstQt( )
m YQt* yFirstQt( )
pas function yFirstQt( ): TYQt
vb function yFirstQt( ) As YQt
cs YQt FirstQt( )
java YQt FirstQt( )
def FirstQt( )
```

Use the method `YQt.nextQt()` to iterate on next quaternion components.

Returns :

a pointer to a `YQt` object, corresponding to the first quaternion component currently online, or a null pointer if there are none.

qt→calibrateFromPoints()qt.calibrateFromPoints()

YQt

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```

js   function calibrateFromPoints( rawValues, refValues)
nodejs function calibrateFromPoints( rawValues, refValues)
php  function calibrateFromPoints( $rawValues, $refValues)
cpp   int calibrateFromPoints( vector<double> rawValues,
                               vector<double> refValues)

m    -(int) calibrateFromPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues

pas  function calibrateFromPoints( rawValues: TDoubleArray,
                                   refValues: TDoubleArray): LongInt

vb   procedure calibrateFromPoints( )

cs   int calibrateFromPoints( List<double> rawValues,
                           List<double> refValues)

java int calibrateFromPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def calibrateFromPoints( rawValues, refValues)
cmd  YSensor target calibrateFromPoints rawValues refValues

```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.
refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

qt→describe()qt.describe()**YQt**

Returns a short text that describes unambiguously the instance of the quaternion component in the form TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|---------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | - (NSString*) describe |
| pas | function describe(): string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the quaternion component (ex:
Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

qt→get_advertisedValue()
qt→advertisedValue()qt.get_advertisedValue()

YQt

Returns the current value of the quaternion component (no more than 6 characters).

| | |
|--------|--|
| js | function get_advertisedValue() |
| nodejs | function get_advertisedValue() |
| php | function get_advertisedValue() |
| cpp | string get_advertisedValue() |
| m | -(NSString*) advertisedValue |
| pas | function get_advertisedValue() : string |
| vb | function get_advertisedValue() As String |
| cs | string get_advertisedValue() |
| java | String get_advertisedValue() |
| py | def get_advertisedValue() |
| cmd | YSensor target get_advertisedValue |

Returns :

a string corresponding to the current value of the quaternion component (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

qt→get_currentRawValue() YQt
qt→currentRawValue()qt.get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor.

```
js function get_currentRawValue( )  
node.js function get_currentRawValue( )  
php function get_currentRawValue( )  
cpp double get_currentRawValue( )  
m -(double) currentRawValue  
pas function get_currentRawValue( ): double  
vb function get_currentRawValue( ) As Double  
cs double get_currentRawValue( )  
java double get_currentRawValue( )  
py def get_currentRawValue( )  
cmd YSensor target get_currentRawValue
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

qt->get_currentValue() qt->currentValue()qt.get_currentValue()

YQt

Returns the current value of the value.

```
js function get_currentValue( )  
nodejs function get_currentValue( )  
php function get_currentValue( )  
cpp double get_currentValue( )  
m -(double) currentValue  
pas function get_currentValue( ): double  
vb function get_currentValue( ) As Double  
cs double get_currentValue( )  
java double get_currentValue( )  
py def get_currentValue( )  
cmd YSensor target get_currentValue
```

Returns :

a floating point number corresponding to the current value of the value

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

qt→get_errorMessage()
qt→errorMessage()qt.get_errorMessage()

YQt

Returns the error message of the latest error with the quaternion component.

```
js function get_errorMessage( )
node.js function get_errorMessage( )
php function get_errorMessage( )
cpp string get_errorMessage( )
m -(NSString*) errorMessage
pas function get_errorMessage( ): string
vb function get_errorMessage( ) As String
cs string get_errorMessage( )
java String get_errorMessage( )
py def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the quaternion component object

qt→get_errorType() qt→errorType()qt.get_errorType()

YQt

Returns the numerical error code of the latest error with the quaternion component.

```
js   function get_errorType( )  
nodejs function get_errorType( )  
php  function get_errorType( )  
cpp   YRETCODE get_errorType( )  
pas   function get_errorType( ): YRETCODE  
vb    function get_errorType( ) As YRETCODE  
cs    YRETCODE get_errorType( )  
java  int get_errorType( )  
py    def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the quaternion component object

qt→get_friendlyName()
qt→friendlyName()qt.get_friendlyName()**YQt**

Returns a global identifier of the quaternion component in the format MODULE_NAME.FUNCTION_NAME.

| | |
|--------|------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the quaternion component if they are defined, otherwise the serial number of the module and the hardware identifier of the quaternion component (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the quaternion component using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

qt->get_functionDescriptor()

YQt

qt->functionDescriptor()qt.get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|--------|--|
| js | function get_functionDescriptor() |
| nodejs | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

**qt→get_functionId()
qt→functionId()qt.get_functionId()****YQt**

Returns the hardware identifier of the quaternion component, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the quaternion component (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

qt→get_hardwareId()

YQt

qt→hardwareId()qt.get_hardwareId()

Returns the unique hardware identifier of the quaternion component in the form SERIAL.FUNCTIONID.

| | |
|--------|---|
| js | function get_hardwareId() |
| nodejs | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the quaternion component. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the quaternion component (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

qt→get_highestValue()
qt→highestValue()qt.get_highestValue()

YQt

Returns the maximal value observed for the value since the device was started.

```
js function get_highestValue( )  
node.js function get_highestValue( )  
php function get_highestValue( )  
cpp double get_highestValue( )  
m -(double) highestValue  
pas function get_highestValue( ): double  
vb function get_highestValue( ) As Double  
cs double get_highestValue( )  
java double get_highestValue( )  
py def get_highestValue( )  
cmd YSensor target get_highestValue
```

Returns :

a floating point number corresponding to the maximal value observed for the value since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

qt→get_logFrequency() qt→logFrequency()qt.get_logFrequency()

YQt

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

| | |
|--------|--|
| js | function get_logFrequency() |
| nodejs | function get_logFrequency() |
| php | function get_logFrequency() |
| cpp | string get_logFrequency() |
| m | -(NSString*) logFrequency |
| pas | function get_logFrequency() : string |
| vb | function get_logFrequency() As String |
| cs | string get_logFrequency() |
| java | String get_logFrequency() |
| py | def get_logFrequency() |
| cmd | YSensor target get_logFrequency |

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

qt→get_logicalName()
qt→logicalName()qt.get_logicalName()

YQt

Returns the logical name of the quaternion component.

```
js function get_logicalName( )  
node.js function get_logicalName( )  
php function get_logicalName( )  
cpp string get_logicalName( )  
m -(NSString*) logicalName  
pas function get_logicalName( ): string  
vb function get_logicalName( ) As String  
cs string get_logicalName( )  
java String get_logicalName( )  
py def get_logicalName( )  
cmd YSensor target get_logicalName
```

Returns :

a string corresponding to the logical name of the quaternion component. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

qt->get_lowestValue() qt->lowestValue()qt.get_lowestValue()

YQt

Returns the minimal value observed for the value since the device was started.

| | |
|--------|--|
| js | function get_lowestValue() |
| nodejs | function get_lowestValue() |
| php | function get_lowestValue() |
| cpp | double get_lowestValue() |
| m | -(double) lowestValue |
| pas | function get_lowestValue(): double |
| vb | function get_lowestValue() As Double |
| cs | double get_lowestValue() |
| java | double get_lowestValue() |
| py | def get_lowestValue() |
| cmd | YSensor target get_lowestValue |

Returns :

a floating point number corresponding to the minimal value observed for the value since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

**qt→get_module()
qt→module()qt.get_module()****YQt**

Gets the `YModule` object for the device on which the function is located.

| | |
|---------|---|
| js | function get_module() |
| node.js | function get_module() |
| php | function get_module() |
| cpp | <code>YModule * get_module()</code> |
| m | <code>-(YModule*) module</code> |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | <code>YModule get_module()</code> |
| java | <code>YModule get_module()</code> |
| py | <code>def get_module()</code> |

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

qt→get_module_async() qt→module_async()

YQt

Gets the YModule object for the device on which the function is located (asynchronous version).

```
js   function get_module_async( callback, context )
nodejs function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned YModule object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested YModule object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

qt→get_recordedData() qt→recordedData()qt.get_recordedData()

YQt

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

| | |
|---------|--|
| js | function get_recordedData(startTime, endTime) |
| node.js | function get_recordedData(startTime, endTime) |
| php | function get_recordedData(\$startTime, \$endTime) |
| cpp | YDataSet get_recordedData(s64 startTime, s64 endTime) |
| m | - (YDataSet*) recordedData : (s64) startTime : (s64) endTime |
| pas | function get_recordedData(startTime: int64, endTime: int64): TYDataSet |
| vb | function get_recordedData() As YDataSet |
| cs | YDataSet get_recordedData(long startTime, long endTime) |
| java | YDataSet get_recordedData(long startTime, long endTime) |
| py | def get_recordedData(startTime, endTime) |
| cmd | YSensor target get_recordedData startTime endTime |

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any meaasure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any meaasure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

qt→get_reportFrequency() qt→reportFrequency()qt.get_reportFrequency()

YQt

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
js    function get_reportFrequency( )  
nodejs function get_reportFrequency( )  
php   function get_reportFrequency( )  
cpp   string get_reportFrequency( )  
m     -(NSString*) reportFrequency  
pas   function get_reportFrequency( ): string  
vb    function get_reportFrequency( ) As String  
cs    string get_reportFrequency( )  
java  String get_reportFrequency( )  
py    def get_reportFrequency( )  
cmd   YSensor target get_reportFrequency
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

qt→get_resolution() qt→resolution()qt.get_resolution()

YQt

Returns the resolution of the measured values.

```
js function get_resolution( )
node.js function get_resolution( )
php function get_resolution( )
cpp double get_resolution( )
m -(double) resolution
pas function get_resolution( ): double
vb function get_resolution( ) As Double
cs double get_resolution( )
java double get_resolution( )
py def get_resolution( )
cmd YSensor target get_resolution
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

qt→get_unit() qt→unit()qt.get_unit()

YQt

Returns the measuring unit for the value.

| | |
|--------|---------------------------------------|
| js | function get_unit() |
| nodejs | function get_unit() |
| php | function get_unit() |
| cpp | string get_unit() |
| m | -(NSString*) unit |
| pas | function get_unit() : string |
| vb | function get_unit() As String |
| cs | string get_unit() |
| java | String get_unit() |
| py | def get_unit() |
| cmd | YSensor target get_unit |

Returns :

a string corresponding to the measuring unit for the value

On failure, throws an exception or returns Y_UNIT_INVALID.

qt→get(userData)
qt→userData()qt.get(userData)

YQt

Returns the value of the userData attribute, as previously stored using method set(userData).

```
js function get(userData) 
node.js function get(userData) 
php function get(userData) 
cpp void * get(userData) 
m -(void*) userData 
pas function get(userData): Tobject 
vb function get(userData) As Object 
cs object get(userData) 
java Object get(userData) 
py def get(userData)
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

qt→isOnline()qt.isOnline()**YQt**

Checks if the quaternion component is currently reachable, without raising any error.

| | |
|---------|---|
| js | function isOnline () |
| node.js | function isOnline () |
| php | function isOnline () |
| cpp | bool isOnline () |
| m | -(BOOL) isOnline |
| pas | function isOnline (): boolean |
| vb | function isOnline () As Boolean |
| cs | bool isOnline () |
| java | boolean isOnline () |
| py | def isOnline () |

If there is a cached value for the quaternion component in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the quaternion component.

Returns :

true if the quaternion component can be reached, and false otherwise

qt→isOnline_async()

YQt

Checks if the quaternion component is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the quaternion component in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

qt→load()qt.load()

YQt

Preloads the quaternion component cache with a specified validity duration.

| | |
|---------|--|
| js | function load (msValidity) |
| node.js | function load (msValidity) |
| php | function load (\$msValidity) |
| cpp | YRETCODE load (int msValidity) |
| m | -(YRETCODE) load : (int) msValidity |
| pas | function load (msValidity : integer): YRETCODE |
| vb | function load (ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load (int msValidity) |
| java | int load (long msValidity) |
| py | def load (msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

qt→loadCalibrationPoints()|qt.loadCalibrationPoints()

YQt

Retrieves error correction data points previously entered using the method `calibrateFromPoints`.

```
js function loadCalibrationPoints( rawValues, refValues)
nodejs function loadCalibrationPoints( rawValues, refValues)
php function loadCalibrationPoints( &$rawValues, &$refValues)
cpp int loadCalibrationPoints( vector<double>& rawValues,
                               vector<double>& refValues)
m -(int) loadCalibrationPoints : (NSMutableArray*) rawValues
                               : (NSMutableArray*) refValues
pas function loadCalibrationPoints( var rawValues: TDoubleArray,
                                     var refValues: TDoubleArray): LongInt
vb procedure loadCalibrationPoints( )
cs int loadCalibrationPoints( List<double> rawValues,
                             List<double> refValues)
java int loadCalibrationPoints( ArrayList<Double> rawValues,
                                ArrayList<Double> refValues)
py def loadCalibrationPoints( rawValues, refValues)
cmd YSensor target loadCalibrationPoints rawValues refValues
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

qt→load_async()

YQt

Preloads the quaternion component cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

qt→nextQt()qt.nextQt()**YQt**

Continues the enumeration of quaternion components started using `yFirstQt()`.

| | |
|--------|---------------------------------|
| js | function nextQt() |
| nodejs | function nextQt() |
| php | function nextQt() |
| cpp | YQt * nextQt() |
| m | -(YQt*) nextQt |
| pas | function nextQt() : TYQt |
| vb | function nextQt() As YQt |
| cs | YQt nextQt() |
| java | YQt nextQt() |
| py | def nextQt() |

Returns :

a pointer to a `YQt` object, corresponding to a quaternion component currently online, or a `null` pointer if there are no more quaternion components to enumerate.

qt→registerTimedReportCallback() qt.registerTimedReportCallback()

YQt

Registers the callback function that is invoked on every periodic timed notification.

| | |
|---------|---|
| js | function registerTimedReportCallback(callback) |
| node.js | function registerTimedReportCallback(callback) |
| php | function registerTimedReportCallback(\$callback) |
| cpp | int registerTimedReportCallback(YQtTimedReportCallback callback) |
| m | -(int) registerTimedReportCallback : (YQtTimedReportCallback) callback |
| pas | function registerTimedReportCallback(callback : TYQtTimedReportCallback): LongInt |
| vb | function registerTimedReportCallback() As Integer |
| cs | int registerTimedReportCallback(TimedReportCallback callback) |
| java | int registerTimedReportCallback(TimedReportCallback callback) |
| py | def registerTimedReportCallback(callback) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

qt→registerValueCallback() qt.registerValueCallback()

YQt

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback)
node.js function registerValueCallback( callback)
php  function registerValueCallback( $callback)
cpp   int registerValueCallback( YQtValueCallback callback)
m    -(int) registerValueCallback : (YQtValueCallback) callback
pas   function registerValueCallback( callback: TYQtValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback)
java  int registerValueCallback( UpdateCallback callback)
py    def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

qt→set_highestValue() qt→setHighestValue()qt.set_highestValue()

YQt

Changes the recorded maximal value observed.

```
js function set_highestValue( newval)
nodejs function set_highestValue( newval)
php function set_highestValue( $newval)
cpp int set_highestValue( double newval)
m -(int) setHighestValue : (double) newval
pas function set_highestValue( newval: double): integer
vb function set_highestValue( ByVal newval As Double) As Integer
cs int set_highestValue( double newval)
java int set_highestValue( double newval)
py def set_highestValue( newval)
cmd YSensor target set_highestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

qt→set_logFrequency() qt→setLogFrequency()qt.set_logFrequency()

YQt

Changes the datalogger recording frequency for this function.

```
js    function set_logFrequency( newval)
node.js function set_logFrequency( newval)
php   function set_logFrequency( $newval)
cpp   int set_logFrequency( const string& newval)
m     -(int) setLogFrequency : (NSString*) newval
pas   function set_logFrequency( newval: string): integer
vb    function set_logFrequency( ByVal newval As String) As Integer
cs    int set_logFrequency( string newval)
java  int set_logFrequency( String newval)
py    def set_logFrequency( newval)
cmd   YSensor target set_logFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

qt→set_logicalName() qt→setLogicalName()qt.set_logicalName()

YQt

Changes the logical name of the quaternion component.

| | |
|--------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YSensor target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the logical name of the quaternion component.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

qt→set_lowestValue() qt→setLowestValue()qt.set_lowestValue()

YQt

Changes the recorded minimal value observed.

```
js function set_lowestValue( newval)
node.js function set_lowestValue( newval)
php function set_lowestValue( $newval)
cpp int set_lowestValue( double newval)
m -(int) setLowestValue : (double) newval
pas function set_lowestValue( newval: double): integer
vb function set_lowestValue( ByVal newval As Double) As Integer
cs int set_lowestValue( double newval)
java int set_lowestValue( double newval)
py def set_lowestValue( newval)
cmd YSensor target set_lowestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

qt→set_reportFrequency()

YQt

qt→setReportFrequency()qt.set_reportFrequency()

Changes the timed value notification frequency for this function.

```
js   function set_reportFrequency( newval)
nodejs function set_reportFrequency( newval)
php  function set_reportFrequency( $newval)
cpp   int set_reportFrequency( const string& newval)
m    -(int) setReportFrequency : (NSString*) newval
pas   function set_reportFrequency( newval: string): integer
vb    function set_reportFrequency( ByVal newval As String) As Integer
cs    int set_reportFrequency( string newval)
java  int set_reportFrequency( String newval)
py    def set_reportFrequency( newval)
cmd   YSensor target set_reportFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

qt→set_resolution() qt→setResolution()qt.set_resolution()

YQt

Changes the resolution of the measured physical values.

```
js function set_resolution( newval)
node.js function set_resolution( newval)
php function set_resolution( $newval)
cpp int set_resolution( double newval)
m -(int) setResolution : (double) newval
pas function set_resolution( newval: double): integer
vb function set_resolution( ByVal newval As Double) As Integer
cs int set_resolution( double newval)
java int set_resolution( double newval)
py def set_resolution( newval)
cmd YSensor target set_resolution newval
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

qt→set(userData)
qt→setUserData()qt.set(userData)

YQt

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|--|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData) \$data |
| cpp | void set(userData) void* data |
| m | -(void) setUserData : (void*) data |
| pas | procedure set(userData) Tobject |
| vb | procedure set(userData) ByVal data As Object |
| cs | void set(userData) object data |
| java | void set(userData) Object data |
| py | def set(userData) data |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

qt→wait_async()

YQt

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.33. Real Time Clock function interface

The RealTimeClock function maintains and provides current date and time, even accross power cut lasting several days. It is the base for automated wake-up functions provided by the WakeUpScheduler. The current time may represent a local time as well as an UTC time, but no automatic time change will occur to account for daylight saving time.

In order to use the functions described here, you should include:

| | |
|---------|--|
| js | <script type='text/javascript' src='yocto_realtimedclock.js'></script> |
| node.js | var yoctolib = require('yoctolib'); |
| | var YRealTimeClock = yoctolib.YRealTimeClock; |
| php | require_once('yocto_realtimedclock.php'); |
| cpp | #include "yocto_realtimedclock.h" |
| m | #import "yocto_realtimedclock.h" |
| pas | uses yocto_realtimedclock; |
| vb | yocto_realtimedclock.vb |
| cs | yocto_realtimedclock.cs |
| java | import com.yoctopuce.YoctoAPI.YRealTimeClock; |
| py | from yocto_realtimedclock import * |

Global functions

yFindRealTimeClock(func)

Retrieves a clock for a given identifier.

yFirstRealTimeClock()

Starts the enumeration of clocks currently accessible.

YRealTimeClock methods

realtimeclock→describe()

Returns a short text that describes unambiguously the instance of the clock in the form TYPE (NAME)=SERIAL . FUNCTIONID.

realtimeclock→get_advertisedValue()

Returns the current value of the clock (no more than 6 characters).

realtimeclock→get_dateTime()

Returns the current time in the form "YYYY/MM/DD hh:mm:ss"

realtimeclock→get_errorMessage()

Returns the error message of the latest error with the clock.

realtimeclock→get_errorType()

Returns the numerical error code of the latest error with the clock.

realtimeclock→get_friendlyName()

Returns a global identifier of the clock in the format MODULE_NAME . FUNCTION_NAME.

realtimeclock→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

realtimeclock→get_functionId()

Returns the hardware identifier of the clock, without reference to the module.

realtimeclock→get_hardwareId()

Returns the unique hardware identifier of the clock in the form SERIAL . FUNCTIONID.

realtimeclock→get_logicalName()

Returns the logical name of the clock.

realtimeclock→get_module()

3. Reference

Gets the YModule object for the device on which the function is located.

realtimeclock→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

realtimeclock→get_timeSet()

Returns true if the clock has been set, and false otherwise.

realtimeclock→get_unixTime()

Returns the current time in Unix format (number of elapsed seconds since Jan 1st, 1970).

realtimeclock→get_userData()

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

realtimeclock→get_utcOffset()

Returns the number of seconds between current time and UTC time (time zone).

realtimeclock→isOnline()

Checks if the clock is currently reachable, without raising any error.

realtimeclock→isOnline_async(callback, context)

Checks if the clock is currently reachable, without raising any error (asynchronous version).

realtimeclock→load(msValidity)

Preloads the clock cache with a specified validity duration.

realtimeclock→load_async(msValidity, callback, context)

Preloads the clock cache with a specified validity duration (asynchronous version).

realtimeclock→nextRealTimeClock()

Continues the enumeration of clocks started using `yFirstRealTimeClock()`.

realtimeclock→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

realtimeclock→set_logicalName(newval)

Changes the logical name of the clock.

realtimeclock→set_unixTime(newval)

Changes the current time.

realtimeclock→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

realtimeclock→set_utcOffset(newval)

Changes the number of seconds between current time and UTC time (time zone).

realtimeclock→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YRealTimeClock.FindRealTimeClock()**YRealTimeClock****yFindRealTimeClock()****YRealTimeClock.FindRealTimeClock()**

Retrieves a clock for a given identifier.

| | |
|----------------------|---|
| <code>js</code> | <code>function yFindRealTimeClock(func)</code> |
| <code>node.js</code> | <code>function FindRealTimeClock(func)</code> |
| <code>php</code> | <code>function yFindRealTimeClock(\$func)</code> |
| <code>cpp</code> | <code>YRealTimeClock* yFindRealTimeClock(const string& func)</code> |
| <code>m</code> | <code>YRealTimeClock* yFindRealTimeClock(NSString* func)</code> |
| <code>pas</code> | <code>function yFindRealTimeClock(func: string): TYRealTimeClock</code> |
| <code>vb</code> | <code>function yFindRealTimeClock(ByVal func As String) As YRealTimeClock</code> |
| <code>cs</code> | <code>YRealTimeClock FindRealTimeClock(string func)</code> |
| <code>java</code> | <code>YRealTimeClock FindRealTimeClock(String func)</code> |
| <code>py</code> | <code>def FindRealTimeClock(func)</code> |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the clock is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YRealTimeClock.isOnline()` to test if the clock is indeed online at a given time. In case of ambiguity when looking for a clock by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the clock

Returns :

a `YRealTimeClock` object allowing you to drive the clock.

YRealTimeClock.FirstRealTimeClock()**YRealTimeClock****yFirstRealTimeClock()****YRealTimeClock.FirstRealTimeClock()**

Starts the enumeration of clocks currently accessible.

```
js function yFirstRealTimeClock( )  
nodejs function FirstRealTimeClock( )  
php function yFirstRealTimeClock( )  
cpp YRealTimeClock* yFirstRealTimeClock( )  
m YRealTimeClock* yFirstRealTimeClock( )  
pas function yFirstRealTimeClock( ):TYRealTimeClock  
vb function yFirstRealTimeClock( ) As YRealTimeClock  
cs YRealTimeClock FirstRealTimeClock( )  
java YRealTimeClock FirstRealTimeClock( )  
py def FirstRealTimeClock( )
```

Use the method `YRealTimeClock.nextRealTimeClock()` to iterate on next clocks.

Returns :

a pointer to a `YRealTimeClock` object, corresponding to the first clock currently online, or a null pointer if there are none.

realtimeclock→describe()realtimeclock.describe()**YRealTimeClock**

Returns a short text that describes unambiguously the instance of the clock in the form TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--|
| js | function describe () |
| nodejs | function describe () |
| php | function describe () |
| cpp | string describe () |
| m | -(NSString*) describe |
| pas | function describe (): string |
| vb | function describe () As String |
| cs | string describe () |
| java | String describe () |
| py | def describe () |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the clock (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

realtimeclock→get_advertisedValue()
realtimeclock→advertisedValue()
realtimeclock.get_advertisedValue()

YRealTimeClock

Returns the current value of the clock (no more than 6 characters).

```
js function get_advertisedValue( )  
nodejs function get_advertisedValue( )  
php function get_advertisedValue( )  
cpp string get_advertisedValue( )  
m -(NSString*) advertisedValue  
pas function get_advertisedValue( ): string  
vb function get_advertisedValue( ) As String  
cs string get_advertisedValue( )  
java String get_advertisedValue( )  
py def get_advertisedValue( )  
cmd YRealTimeClock target get_advertisedValue
```

Returns :

a string corresponding to the current value of the clock (no more than 6 characters). On failure, throws an exception or returns **Y_ADVERTISEDVALUE_INVALID**.

realtimeclock→get_dateTime()
realtimeclock→dateTime()
realtimeclock.get_dateTime()

YRealTimeClock

Returns the current time in the form "YYYY/MM/DD hh:mm:ss"

| | |
|--------|---|
| js | function get_dateTime() |
| nodejs | function get_dateTime() |
| php | function get_dateTime() |
| cpp | string get_dateTime() |
| m | -(NSString*) dateTime |
| pas | function get_dateTime() : string |
| vb | function get_dateTime() As String |
| cs | string get_dateTime() |
| java | String get_dateTime() |
| py | def get_dateTime() |

Returns :

a string corresponding to the current time in the form "YYYY/MM/DD hh:mm:ss"

On failure, throws an exception or returns **Y_DATETIME_INVALID**.

realtimeclock→getErrorMessage()
realtimeclock→errorMessage()
realtimeclock.getErrorMessage()

YRealTimeClock

Returns the error message of the latest error with the clock.

```
js function getErrorMessage( )  
nodejs function getErrorMessage( )  
php function getErrorMessage( )  
cpp string getErrorMessage( )  
m -(NSString*) errorMessage  
pas function getErrorMessage( ): string  
vb function getErrorMessage( ) As String  
cs string getErrorMessage( )  
java String getErrorMessage( )  
py def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the clock object

realtimeclock→get_errorType()
realtimeclock→errorType()
realtimeclock.get_errorType()

YRealTimeClock

Returns the numerical error code of the latest error with the clock.

| | |
|---------|--|
| js | function get_errorType() |
| node.js | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType(): YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the clock object

realtimeclock→get_friendlyName()
realtimeclock→friendlyName()
realtimeclock.get_friendlyName()**YRealTimeClock**

Returns a global identifier of the clock in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the clock if they are defined, otherwise the serial number of the module and the hardware identifier of the clock (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the clock using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

realtimeclock→get_functionDescriptor()
realtimeclock→functionDescriptor()
realtimeclock.get_functionDescriptor()

YRealTimeClock

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

**realtimeclock→get_functionId()
realtimeclock→functionId()
realtimeclock.get_functionId()****YRealTimeClock**

Returns the hardware identifier of the clock, without reference to the module.

| | |
|--------|---|
| js | function get_functionId() |
| nodejs | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the clock (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

realtimeclock→get_hardwareId()
realtimeclock→hardwareId()
realtimeclock.get_hardwareId()**YRealTimeClock**

Returns the unique hardware identifier of the clock in the form SERIAL.FUNCTIONID.

| | |
|---------|---|
| js | function get_hardwareId() |
| node.js | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the clock. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the clock (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

realtimeclock→get_logicalName()
realtimeclock→logicalName()
realtimeclock.get_logicalName()

YRealTimeClock

Returns the logical name of the clock.

```
js function get_logicalName( )  
nodejs function get_logicalName( )  
php function get_logicalName( )  
cpp string get_logicalName( )  
m -(NSString*) logicalName  
pas function get_logicalName( ): string  
vb function get_logicalName( ) As String  
cs string get_logicalName( )  
java String get_logicalName( )  
py def get_logicalName( )  
cmd YRealTimeClock target get_logicalName
```

Returns :

a string corresponding to the logical name of the clock. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

realtimeclock→get_module()**YRealTimeClock****realtimeclock→module()realtimeclock.get_module()**

Gets the **YModule** object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module(): TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of **YModule** is not shown as online.

Returns :

an instance of **YModule**

realtimeclock→get_module_async()
realtimeclock→module_async()**YRealTimeClock**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

realtimeclock→get_timeSet()**YRealTimeClock****realtimeclock→timeSet()realtimeclock.get_timeSet()**

Returns true if the clock has been set, and false otherwise.

```
js function get_timeSet( )
nodejs function get_timeSet( )
php function get_timeSet( )
cpp Y_TIMESET_enum get_timeSet( )
m -(Y_TIMESET_enum) timeSet
pas function get_timeSet( ): Integer
vb function get_timeSet( ) As Integer
cs int get_timeSet( )
java int get_timeSet( )
py def get_timeSet( )
cmd YRealTimeClock target get_timeSet
```

Returns :

either Y_TIMESET_FALSE or Y_TIMESET_TRUE, according to true if the clock has been set, and false otherwise

On failure, throws an exception or returns Y_TIMESET_INVALID.

realtimeclock→get_unixTime()
realtimeclock→unixTime()
realtimeclock.get_unixTime()**YRealTimeClock**

Returns the current time in Unix format (number of elapsed seconds since Jan 1st, 1970).

js function **get_unixTime()**
nodejs function **get_unixTime()**
php function **get_unixTime()**
cpp **s64 get_unixTime()**
m -(s64) unixTime
pas function **get_unixTime(): int64**
vb function **get_unixTime() As Long**
cs **long get_unixTime()**
java **long get_unixTime()**
py **def get_unixTime()**
cmd YRealTimeClock **target get_unixTime**

Returns :

an integer corresponding to the current time in Unix format (number of elapsed seconds since Jan 1st, 1970)

On failure, throws an exception or returns **Y_UNIXTIME_INVALID**.

realtimeclock→get(userData)
realtimeclock→userData()
realtimeclock.get(userData)

YRealTimeClock

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|---|
| js | function get(userData) |
| nodejs | function get(userData) |
| php | function get(userData) |
| cpp | void * get(userData) |
| m | -(void*) userData |
| pas | function get(userData) : Tobject |
| vb | function get(userData) As Object |
| cs | object get(userData) |
| java | Object get(userData) |
| py | def get(userData) |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

realtimeclock→get_utcOffset()
realtimeclock→utcOffset()
realtimeclock.get_utcOffset()**YRealTimeClock**

Returns the number of seconds between current time and UTC time (time zone).

js function **get_utcOffset()**
nodejs function **get_utcOffset()**
php function **get_utcOffset()**
cpp int **get_utcOffset()**
m -(int) **utcOffset**
pas function **get_utcOffset()**: LongInt
vb function **get_utcOffset()** As Integer
cs int **get_utcOffset()**
java int **get_utcOffset()**
py def **get_utcOffset()**
cmd YRealTimeClock **target get_utcOffset**

Returns :

an integer corresponding to the number of seconds between current time and UTC time (time zone)

On failure, throws an exception or returns **Y_UTCOFFSET_INVALID**.

realtimeclock→isOnline()|realtimeclock.isOnline()**YRealTimeClock**

Checks if the clock is currently reachable, without raising any error.

| | |
|---------|---|
| js | function isOnline () |
| node.js | function isOnline () |
| php | function isOnline () |
| cpp | bool isOnline () |
| m | -(BOOL) isOnline |
| pas | function isOnline (): boolean |
| vb | function isOnline () As Boolean |
| cs | bool isOnline () |
| java | boolean isOnline () |
| py | def isOnline () |

If there is a cached value for the clock in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the clock.

Returns :

true if the clock can be reached, and false otherwise

realtimeclock→isOnline_async()**YRealTimeClock**

Checks if the clock is currently reachable, without raising any error (asynchronous version).

```
js   function isOnline_async( callback, context )
nodejs function isOnline_async( callback, context )
```

If there is a cached value for the clock in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

realtimeclock→load()realtimeclock.load()**YRealTimeClock**

Preloads the clock cache with a specified validity duration.

| | |
|---------------|--|
| js | <code>function load(msValidity)</code> |
| nodejs | <code>function load(msValidity)</code> |
| php | <code>function load(\$msValidity)</code> |
| cpp | <code>YRETCODE load(int msValidity)</code> |
| m | <code>-(YRETCODE) load : (int) msValidity</code> |
| pas | <code>function load(msValidity: integer): YRETCODE</code> |
| vb | <code>function load(ByVal msValidity As Integer) As YRETCODE</code> |
| cs | <code>YRETCODE load(int msValidity)</code> |
| java | <code>int load(long msValidity)</code> |
| py | <code>def load(msValidity)</code> |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

realtimeclock→load_async()**YRealTimeClock**

Preloads the clock cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

realtimeclock→nextRealTimeClock()
realtimeclock.nextRealTimeClock()**YRealTimeClock**

Continues the enumeration of clocks started using `yFirstRealTimeClock()`.

| | |
|---------------------|--|
| <code>js</code> | <code>function nextRealTimeClock()</code> |
| <code>nodejs</code> | <code>function nextRealTimeClock()</code> |
| <code>php</code> | <code>function nextRealTimeClock()</code> |
| <code>cpp</code> | <code>YRealTimeClock * nextRealTimeClock()</code> |
| <code>m</code> | <code>-(YRealTimeClock*) nextRealTimeClock</code> |
| <code>pas</code> | <code>function nextRealTimeClock(): TYRealTimeClock</code> |
| <code>vb</code> | <code>function nextRealTimeClock() As YRealTimeClock</code> |
| <code>cs</code> | <code>YRealTimeClock nextRealTimeClock()</code> |
| <code>java</code> | <code>YRealTimeClock nextRealTimeClock()</code> |
| <code>py</code> | <code>def nextRealTimeClock()</code> |

Returns :

a pointer to a `YRealTimeClock` object, corresponding to a clock currently online, or a null pointer if there are no more clocks to enumerate.

**realtimeclock→registerValueCallback()
realtimeclock.registerValueCallback()****YRealTimeClock**

Registers the callback function that is invoked on every change of advertised value.

| | |
|---------|--|
| js | function registerValueCallback(callback) |
| node.js | function registerValueCallback(callback) |
| php | function registerValueCallback(\$callback) |
| cpp | int registerValueCallback(YRealTimeClockValueCallback callback) |
| m | -(int) registerValueCallback : (YRealTimeClockValueCallback) callback |
| pas | function registerValueCallback(callback : TYRealTimeClockValueCallback): LongInt |
| vb | function registerValueCallback() As Integer |
| cs | int registerValueCallback(ValueCallback callback) |
| java | int registerValueCallback(UpdateCallback callback) |
| py | def registerValueCallback(callback) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

realtimeclock→set_logicalName()
realtimeclock→setLogicalName()
realtimeclock.set_logicalName()

YRealTimeClock

Changes the logical name of the clock.

| | |
|---------------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YRealTimeClock target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the clock.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

realtimeclock→set_unixTime()
realtimeclock→setUnixTime()
realtimeclock.set_unixTime()

YRealTimeClock

Changes the current time.

```
js function set_unixTime( newval)
nodejs function set_unixTime( newval)
php function set_unixTime( $newval)
cpp int set_unixTime( s64 newval)
m -(int) setUnixTime : (s64) newval
pas function set_unixTime( newval: int64): integer
vb function set_unixTime( ByVal newval As Long) As Integer
cs int set_unixTime( long newval)
java int set_unixTime( long newval)
py def set_unixTime( newval)
cmd YRealTimeClock target set_unixTime newval
```

Time is specified in Unix format (number of elapsed seconds since Jan 1st, 1970). If current UTC time is known, utcOffset will be automatically adjusted for the new specified time.

Parameters :

newval an integer corresponding to the current time

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

realtimeclock→set(userData)
realtimeclock→setUserData()
realtimeclock.set(userData)

YRealTimeClock

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|---|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData \$data) |
| cpp | void set(userData void* data) |
| m | -(void) setUserData : (void*) data |
| pas | procedure set(userData data: Tobject) |
| vb | procedure set(userData ByVal data As Object) |
| cs | void set(userData object data) |
| java | void set(userData Object data) |
| py | def set(userData data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

realtimeclock→set_utcOffset()
realtimeclock→setUtcOffset()
realtimeclock.set_utcOffset()

YRealTimeClock

Changes the number of seconds between current time and UTC time (time zone).

```
js function set_utcOffset( newval)
nodejs function set_utcOffset( newval)
php function set_utcOffset( $newval)
cpp int set_utcOffset( int newval)
m -(int) setUtcOffset : (int) newval
pas function set_utcOffset( newval: LongInt): integer
vb function set_utcOffset( ByVal newval As Integer) As Integer
cs int set_utcOffset( int newval)
java int set_utcOffset( int newval)
py def set_utcOffset( newval)
cmd YRealTimeClock target set_utcOffset newval
```

The timezone is automatically rounded to the nearest multiple of 15 minutes. If current UTC time is known, the current time will automatically be updated according to the selected time zone.

Parameters :

newval an integer corresponding to the number of seconds between current time and UTC time (time zone)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

realtimeclock→wait_async()**YRealTimeClock**

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.34. Reference frame configuration

This class is used to setup the base orientation of the Yocto-3D, so that the orientation functions, relative to the earth surface plane, use the proper reference frame. The class also implements a tridimensional sensor calibration process, which can compensate for local variations of standard gravity and improve the precision of the tilt sensors.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_refframe.js'></script>
nodejs var yoctolib = require('yoctolib');
var YRefFrame = yoctolib.YRefFrame;
php require_once('yocto_refframe.php');
cpp #include "yocto_refframe.h"
m #import "yocto_refframe.h"
pas uses yocto_refframe;
vb yocto_refframe.vb
cs yocto_refframe.cs
java import com.yoctopuce.YoctoAPI.YRefFrame;
py from yocto_refframe import *

```

Global functions

yFindRefFrame(func)

Retrieves a reference frame for a given identifier.

yFirstRefFrame()

Starts the enumeration of reference frames currently accessible.

YRefFrame methods

refframe→cancel3DCalibration()

Aborts the sensors tridimensional calibration process et restores normal settings.

refframe→describe()

Returns a short text that describes unambiguously the instance of the reference frame in the form TYPE(NAME)=SERIAL.FUNCTIONID.

refframe→get_3DCalibrationHint()

Returns instructions to proceed to the tridimensional calibration initiated with method start3DCalibration.

refframe→get_3DCalibrationLogMsg()

Returns the latest log message from the calibration process.

refframe→get_3DCalibrationProgress()

Returns the global process indicator for the tridimensional calibration initiated with method start3DCalibration.

refframe→get_3DCalibrationStage()

Returns index of the current stage of the calibration initiated with method start3DCalibration.

refframe→get_3DCalibrationStageProgress()

Returns the process indicator for the current stage of the calibration initiated with method start3DCalibration.

refframe→get_advertisedValue()

Returns the current value of the reference frame (no more than 6 characters).

refframe→get_bearing()

Returns the reference bearing used by the compass.

refframe→get_errorMessage()

Returns the error message of the latest error with the reference frame.

refframe→get_errorType()

Returns the numerical error code of the latest error with the reference frame.

refframe→get_friendlyName()

Returns a global identifier of the reference frame in the format MODULE_NAME . FUNCTION_NAME.

refframe→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

refframe→get_functionId()

Returns the hardware identifier of the reference frame, without reference to the module.

refframe→get_hardwareId()

Returns the unique hardware identifier of the reference frame in the form SERIAL . FUNCTIONID.

refframe→get_logicalName()

Returns the logical name of the reference frame.

refframe→get_module()

Gets the YModule object for the device on which the function is located.

refframe→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

refframe→get_mountOrientation()

Returns the installation orientation of the device, as configured in order to define the reference frame for the compass and the pitch/roll tilt sensors.

refframe→get_mountPosition()

Returns the installation position of the device, as configured in order to define the reference frame for the compass and the pitch/roll tilt sensors.

refframe→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

refframe→isOnline()

Checks if the reference frame is currently reachable, without raising any error.

refframe→isOnline_async(callback, context)

Checks if the reference frame is currently reachable, without raising any error (asynchronous version).

refframe→load(msValidity)

Preloads the reference frame cache with a specified validity duration.

refframe→load_async(msValidity, callback, context)

Preloads the reference frame cache with a specified validity duration (asynchronous version).

refframe→more3DCalibration()

Continues the sensors tridimensional calibration process previously initiated using method start3DCalibration.

refframe→nextRefFrame()

Continues the enumeration of reference frames started using yFirstRefFrame().

refframe→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

refframe→save3DCalibration()

Applies the sensors tridimensional calibration parameters that have just been computed.

refframe→set_bearing(newval)

Changes the reference bearing used by the compass.

refframe→set_logicalName(newval)

3. Reference

Changes the logical name of the reference frame.

refframe→set_mountPosition(*position*, *orientation*)

Changes the compass and tilt sensor frame of reference.

refframe→set(userData)

Stores a user context provided as argument in the userData attribute of the function.

refframe→start3DCalibration()

Initiates the sensors tridimensional calibration process.

refframe→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YRefFrame.FindRefFrame()**YRefFrame****yFindRefFrame()YRefFrame.FindRefFrame()**

Retrieves a reference frame for a given identifier.

| | |
|----------------------|---|
| <code>js</code> | <code>function yFindRefFrame(func)</code> |
| <code>node.js</code> | <code>function FindRefFrame(func)</code> |
| <code>php</code> | <code>function yFindRefFrame(\$func)</code> |
| <code>cpp</code> | <code>YRefFrame* yFindRefFrame(const string& func)</code> |
| <code>m</code> | <code>YRefFrame* yFindRefFrame(NSString* func)</code> |
| <code>pas</code> | <code>function yFindRefFrame(func: string): TYRefFrame</code> |
| <code>vb</code> | <code>function yFindRefFrame(ByVal func As String) As YRefFrame</code> |
| <code>cs</code> | <code>YRefFrame FindRefFrame(string func)</code> |
| <code>java</code> | <code>YRefFrame FindRefFrame(String func)</code> |
| <code>py</code> | <code>def FindRefFrame(func)</code> |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the reference frame is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YRefFrame.isOnline()` to test if the reference frame is indeed online at a given time. In case of ambiguity when looking for a reference frame by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the reference frame

Returns :

a `YRefFrame` object allowing you to drive the reference frame.

YRefFrame.FirstRefFrame()**YRefFrame****yFirstRefFrame() YRefFrame.FirstRefFrame()**

Starts the enumeration of reference frames currently accessible.

| | |
|---------|--|
| js | function yFirstRefFrame() |
| node.js | function FirstRefFrame() |
| php | function yFirstRefFrame() |
| cpp | YRefFrame* yFirstRefFrame() |
| m | YRefFrame* yFirstRefFrame() |
| pas | function yFirstRefFrame(): TYRefFrame |
| vb | function yFirstRefFrame() As YRefFrame |
| cs | YRefFrame FirstRefFrame() |
| java | YRefFrame FirstRefFrame() |
| py | def FirstRefFrame() |

Use the method `YRefFrame.nextRefFrame()` to iterate on next reference frames.

Returns :

a pointer to a `YRefFrame` object, corresponding to the first reference frame currently online, or a null pointer if there are none.

refframe→cancel3DCalibration()
refframe.cancel3DCalibration()**YRefFrame**

Aborts the sensors tridimensional calibration process et restores normal settings.

| | |
|---------|--|
| js | function cancel3DCalibration() |
| node.js | function cancel3DCalibration() |
| php | function cancel3DCalibration() |
| cpp | int cancel3DCalibration() |
| m | -(int) cancel3DCalibration |
| pas | function cancel3DCalibration(): LongInt |
| vb | function cancel3DCalibration() As Integer |
| cs | int cancel3DCalibration() |
| java | int cancel3DCalibration() |
| py | def cancel3DCalibration() |
| cmd | YRefFrame target cancel3DCalibration |

On failure, throws an exception or returns a negative error code.

reframe→describe()reframe.describe()**YRefFrame**

Returns a short text that describes unambiguously the instance of the reference frame in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the reference frame (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

refframe→get_3DCalibrationHint()**YRefFrame****refframe→3DCalibrationHint()****refframe.get_3DCalibrationHint()**

Returns instructions to proceed to the tridimensional calibration initiated with method start3DCalibration.

| | |
|---------|--|
| js | function get_3DCalibrationHint() |
| node.js | function get_3DCalibrationHint() |
| php | function get_3DCalibrationHint() |
| cpp | string get_3DCalibrationHint() |
| m | -(NSString*) 3DCalibrationHint |
| pas | function get_3DCalibrationHint(): string |
| vb | function get_3DCalibrationHint() As String |
| cs | string get_3DCalibrationHint() |
| java | String get_3DCalibrationHint() |
| py | def get_3DCalibrationHint() |
| cmd | YRefFrame target get_3DCalibrationHint |

Returns :

a character string.

`refframe→get_3DCalibrationLogMsg()`
`refframe→3DCalibrationLogMsg()`
`refframe.get_3DCalibrationLogMsg()`

YRefFrame

Returns the latest log message from the calibration process.

```
js function get_3DCalibrationLogMsg( )
nodejs function get_3DCalibrationLogMsg( )
php function get_3DCalibrationLogMsg( )
cpp string get_3DCalibrationLogMsg( )
m -(NSString*) 3DCalibrationLogMsg
pas function get_3DCalibrationLogMsg( ): string
vb function get_3DCalibrationLogMsg( ) As String
cs string get_3DCalibrationLogMsg( )
java String get_3DCalibrationLogMsg( )
py def get_3DCalibrationLogMsg( )
cmd YRefFrame target get_3DCalibrationLogMsg
```

When no new message is available, returns an empty string.

Returns :

a character string.

refframe→get_3DCalibrationProgress()
refframe→3DCalibrationProgress()
refframe.get_3DCalibrationProgress()

YRefFrame

Returns the global process indicator for the tridimensional calibration initiated with method start3DCalibration.

| | |
|---------|---|
| js | function get_3DCalibrationProgress() |
| node.js | function get_3DCalibrationProgress() |
| php | function get_3DCalibrationProgress() |
| cpp | int get_3DCalibrationProgress() |
| m | -(int) 3DCalibrationProgress |
| pas | function get_3DCalibrationProgress(): LongInt |
| vb | function get_3DCalibrationProgress() As Integer |
| cs | int get_3DCalibrationProgress() |
| java | int get_3DCalibrationProgress() |
| py | def get_3DCalibrationProgress() |
| cmd | YRefFrame target get_3DCalibrationProgress |

Returns :

an integer between 0 (not started) and 100 (stage completed).

`refframe→get_3DCalibrationStage()`
`refframe→3DCalibrationStage()`
`refframe.get_3DCalibrationStage()`

YRefFrame

Returns index of the current stage of the calibration initiated with method `start3DCalibration`.

`js` `function get_3DCalibrationStage()`
`nodejs` `function get_3DCalibrationStage()`
`php` `function get_3DCalibrationStage()`
`cpp` `int get_3DCalibrationStage()`
`m` `-(int) 3DCalibrationStage`
`pas` `function get_3DCalibrationStage(): LongInt`
`vb` `function get_3DCalibrationStage() As Integer`
`cs` `int get_3DCalibrationStage()`
`java` `int get_3DCalibrationStage()`
`py` `def get_3DCalibrationStage()`
`cmd` `YRefFrame target get_3DCalibrationStage`

Returns :

an integer, growing each time a calibration stage is completed.

refframe→get_3DCalibrationStageProgress()
refframe→3DCalibrationStageProgress()
refframe.get_3DCalibrationStageProgress()

YRefFrame

Returns the process indicator for the current stage of the calibration initiated with method start3DCalibration.

```
js function get_3DCalibrationStageProgress( )
nodejs function get_3DCalibrationStageProgress( )
php function get_3DCalibrationStageProgress( )
cpp int get_3DCalibrationStageProgress( )
m -(int) 3DCalibrationStageProgress
pas function get_3DCalibrationStageProgress( ): LongInt
vb function get_3DCalibrationStageProgress( ) As Integer
cs int get_3DCalibrationStageProgress( )
java int get_3DCalibrationStageProgress( )
py def get_3DCalibrationStageProgress( )
cmd YRefFrame target get_3DCalibrationStageProgress
```

Returns :

an integer between 0 (not started) and 100 (stage completed).

refframe→get_advertisedValue()
refframe→advertisedValue()
refframe.get_advertisedValue()

YRefFrame

Returns the current value of the reference frame (no more than 6 characters).

| | |
|--------|---|
| js | function get_advertisedValue() |
| nodejs | function get_advertisedValue() |
| php | function get_advertisedValue() |
| cpp | string get_advertisedValue() |
| m | -(NSString*) advertisedValue |
| pas | function get_advertisedValue(): string |
| vb | function get_advertisedValue() As String |
| cs | string get_advertisedValue() |
| java | String get_advertisedValue() |
| py | def get_advertisedValue() |
| cmd | YRefFrame target get_advertisedValue |

Returns :

a string corresponding to the current value of the reference frame (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

refframe→get_bearing()**YRefFrame****refframe→bearing()refframe.get_bearing()**

Returns the reference bearing used by the compass.

| | |
|--------|--|
| js | function get_bearing() |
| nodejs | function get_bearing() |
| php | function get_bearing() |
| cpp | double get_bearing() |
| m | -(double) bearing |
| pas | function get_bearing(): double |
| vb | function get_bearing() As Double |
| cs | double get_bearing() |
| java | double get_bearing() |
| py | def get_bearing() |
| cmd | YRefFrame target get_bearing |

The relative bearing indicated by the compass is the difference between the measured magnetic heading and the reference bearing indicated here.

Returns :

a floating point number corresponding to the reference bearing used by the compass

On failure, throws an exception or returns **Y_BEARING_INVALID**.

refframe→get_errorMessage()
refframe→errorMessage()
refframe.get_errorMessage()**YRefFrame**

Returns the error message of the latest error with the reference frame.

| | |
|--------|--|
| js | function get_errorMessage() |
| nodejs | function get_errorMessage() |
| php | function get_errorMessage() |
| cpp | string get_errorMessage() |
| m | -(NSString*) errorMessage |
| pas | function get_errorMessage(): string |
| vb | function get_errorMessage() As String |
| cs | string get_errorMessage() |
| java | String get_errorMessage() |
| py | def get_errorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the reference frame object

refframe→get_errorType()**YRefFrame****refframe→errorType()refframe.get_errorType()**

Returns the numerical error code of the latest error with the reference frame.

| | |
|--------|--|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType() : YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the reference frame object

refframe→get_friendlyName()**YRefFrame****refframe→friendlyName()refframe.get_friendlyName()**

Returns a global identifier of the reference frame in the format MODULE_NAME . FUNCTION_NAME.

| | |
|---------|------------------------------|
| js | function get_friendlyName() |
| node.js | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the reference frame if they are defined, otherwise the serial number of the module and the hardware identifier of the reference frame (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the reference frame using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

refframe→get_functionDescriptor()
refframe→functionDescriptor()
refframe.get_functionDescriptor()

YRefFrame

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

refframe→get_functionId()**YRefFrame****refframe→functionId()refframe.get_functionId()**

Returns the hardware identifier of the reference frame, without reference to the module.

| | |
|---------|--|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the reference frame (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

refframe→get_hardwareId()**YRefFrame****refframe→hardwareId()refframe.get_hardwareId()**

Returns the unique hardware identifier of the reference frame in the form SERIAL.FUNCTIONID.

| | |
|--------|---|
| js | function get_hardwareId() |
| nodejs | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the reference frame. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the reference frame (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

refframe→get_logicalName()**YRefFrame****refframe→logicalName()refframe.get_logicalName()**

Returns the logical name of the reference frame.

| | |
|---------|--|
| js | function get_logicalName() |
| node.js | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | - (NSString*) logicalName |
| pas | function get_logicalName(): string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YRefFrame target get_logicalName |

Returns :

a string corresponding to the logical name of the reference frame. On failure, throws an exception or returns **Y_LOGICALNAME_INVALID**.

refframe→get_module()**YRefFrame****refframe→module()refframe.get_module()**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

refframe→get_module_async()**YRefFrame****refframe→module_async()**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

refframe→get_mountOrientation()
refframe→mountOrientation()
refframe.get_mountOrientation()

YRefFrame

Returns the installation orientation of the device, as configured in order to define the reference frame for the compass and the pitch/roll tilt sensors.

| | |
|----------------|--|
| js | function get_mountOrientation() |
| node.js | function get_mountOrientation() |
| php | function get_mountOrientation() |
| cpp | Y_MOUNTORIENTATION get_mountOrientation() |
| m | -(Y_MOUNTORIENTATION) mountOrientation |
| pas | function get_mountOrientation() : TYMOUNTORIENTATION |
| vb | function get_mountOrientation() As Y_MOUNTORIENTATION |
| cs | MOUNTORIENTATION get_mountOrientation() |
| java | MOUNTORIENTATION get_mountOrientation() |
| py | def get_mountOrientation() |
| cmd | YRefFrame target get_mountOrientation |

Returns :

a value among the enumeration **Y_MOUNTORIENTATION** (**Y_MOUNTORIENTATION_TWELVE**, **Y_MOUNTORIENTATION_THREE**, **Y_MOUNTORIENTATION_SIX**, **Y_MOUNTORIENTATION_NINE**) corresponding to the orientation of the "X" arrow on the device, as on a clock dial seen from an observer in the center of the box. On the bottom face, the 12H orientation points to the front, while on the top face, the 12H orientation points to the rear.

On failure, throws an exception or returns a negative error code.

refframe→get_mountPosition()**YRefFrame****refframe→mountPosition()****refframe.get_mountPosition()**

Returns the installation position of the device, as configured in order to define the reference frame for the compass and the pitch/roll tilt sensors.

```
js function get_mountPosition( )
nodejs function get_mountPosition( )
php function get_mountPosition( )
cpp Y_MOUNTPOSITION get_mountPosition( )
m -(Y_MOUNTPOSITION) mountPosition
pas function get_mountPosition( ): TYMOUNTPOSITION
vb function get_mountPosition( ) As Y_MOUNTPOSITION
cs MOUNTPOSITION get_mountPosition( )
java MOUNTPOSITION get_mountPosition( )
py def get_mountPosition( )
cmd YRefFrame target get_mountPosition
```

Returns :

a value among the `Y_MOUNTPOSITION` enumeration (`Y_MOUNTPOSITION_BOTTOM`, `Y_MOUNTPOSITION_TOP`, `Y_MOUNTPOSITION_FRONT`, `Y_MOUNTPOSITION_RIGHT`, `Y_MOUNTPOSITION_REAR`, `Y_MOUNTPOSITION_LEFT`), corresponding to the installation in a box, on one of the six faces.

On failure, throws an exception or returns a negative error code.

refframe→get(userData)**YRefFrame****refframe→userData()refframe.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|---|
| js | <code>function get(userData) </code> |
| nodejs | <code>function get(userData) </code> |
| php | <code>function get(userData) </code> |
| cpp | <code>void * get(userData) </code> |
| m | <code>-(void*) userData</code> |
| pas | <code>function get(userData): Tobject</code> |
| vb | <code>function get(userData) As Object</code> |
| cs | <code>object get(userData) </code> |
| java | <code>Object get(userData) </code> |
| py | <code>def get(userData) </code> |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

refframe→isOnline()refframe.isOnline()**YRefFrame**

Checks if the reference frame is currently reachable, without raising any error.

| | |
|--------|---------------------------------------|
| js | function isOnline() |
| nodejs | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the reference frame in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the reference frame.

Returns :

true if the reference frame can be reached, and false otherwise

refframe→isOnline_async()**YRefFrame**

Checks if the reference frame is currently reachable, without raising any error (asynchronous version).

```
js   function isOnline_async( callback, context )
nodejs function isOnline_async( callback, context )
```

If there is a cached value for the reference frame in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

refframe→load()refframe.load()**YRefFrame**

Preloads the reference frame cache with a specified validity duration.

| | |
|--------|--|
| js | function load(msValidity) |
| nodejs | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | - (YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

refframe→load_async()**YRefFrame**

Preloads the reference frame cache with a specified validity duration (asynchronous version).

```
js  function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

refframe→more3DCalibration()
refframe.more3DCalibration()**YRefFrame**

Continues the sensors tridimensional calibration process previously initiated using method `start3DCalibration`.

```
js function more3DCalibration( )
nodejs function more3DCalibration( )
php function more3DCalibration( )
cpp int more3DCalibration( )
m -(int) more3DCalibration
pas function more3DCalibration( ): LongInt
vb function more3DCalibration( ) As Integer
cs int more3DCalibration( )
java int more3DCalibration( )
py def more3DCalibration( )
cmd YRefFrame target more3DCalibration
```

This method should be called approximately 5 times per second, while positioning the device according to the instructions provided by method `get_3DCalibrationHint`. Note that the instructions change during the calibration process. On failure, throws an exception or returns a negative error code.

refframe→nextRefFrame()**YRefFrame**

Continues the enumeration of reference frames started using `yFirstRefFrame()`.

| | |
|---------|---|
| js | <code>function nextRefFrame()</code> |
| node.js | <code>function nextRefFrame()</code> |
| php | <code>function nextRefFrame()</code> |
| cpp | <code>YRefFrame * nextRefFrame()</code> |
| m | <code>-(YRefFrame*) nextRefFrame</code> |
| pas | <code>function nextRefFrame(): TYRefFrame</code> |
| vb | <code>function nextRefFrame() As YRefFrame</code> |
| cs | <code>YRefFrame nextRefFrame()</code> |
| java | <code>YRefFrame nextRefFrame()</code> |
| py | <code>def nextRefFrame()</code> |

Returns :

a pointer to a `YRefFrame` object, corresponding to a reference frame currently online, or a `null` pointer if there are no more reference frames to enumerate.

**reframe→registerValueCallback()
reframe.registerValueCallback()****YRefFrame**

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YRefFrameValueCallback callback )
m    -(int) registerValueCallback : (YRefFrameValueCallback) callback
pas   function registerValueCallback( callback: TYRefFrameValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

refframe→save3DCalibration()
refframe.save3DCalibration()**YRefFrame**

Applies the sensors tridimensional calibration parameters that have just been computed.

| | |
|---------|---|
| js | function save3DCalibration() |
| node.js | function save3DCalibration() |
| php | function save3DCalibration() |
| cpp | int save3DCalibration() |
| m | -(int) save3DCalibration |
| pas | function save3DCalibration() : LongInt |
| vb | function save3DCalibration() As Integer |
| cs | int save3DCalibration() |
| java | int save3DCalibration() |
| py | def save3DCalibration() |
| cmd | YRefFrame target save3DCalibration |

Remember to call the `saveToFlash()` method of the module if the changes must be kept when the device is restarted. On failure, throws an exception or returns a negative error code.

refframe→set_bearing() refframe→setBearing()refframe.set_bearing()

YRefFrame

Changes the reference bearing used by the compass.

| | |
|---------|---|
| js | function set_bearing(newval) |
| node.js | function set_bearing(newval) |
| php | function set_bearing(\$newval) |
| cpp | int set_bearing(double newval) |
| m | - (int) setBearing : (double) newval |
| pas | function set_bearing(newval: double): integer |
| vb | function set_bearing(ByVal newval As Double) As Integer |
| cs | int set_bearing(double newval) |
| java | int set_bearing(double newval) |
| py | def set_bearing(newval) |
| cmd | YRefFrame target set_bearing newval |

The relative bearing indicated by the compass is the difference between the measured magnetic heading and the reference bearing indicated here. For instance, if you setup as reference bearing the value of the earth magnetic declination, the compass will provide the orientation relative to the geographic North. Similarly, when the sensor is not mounted along the standard directions because it has an additional yaw angle, you can set this angle in the reference bearing so that the compass provides the expected natural direction. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a floating point number corresponding to the reference bearing used by the compass

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

refframe→set_logicalName()
refframe→setLogicalName()
refframe.set_logicalName()

YRefFrame

Changes the logical name of the reference frame.

| | |
|---------------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YRefFrame target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the reference frame.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

reframe→set_mountPosition()
reframe→setMountPosition()
reframe.set_mountPosition()

YRefFrame

Changes the compass and tilt sensor frame of reference.

```

js function set_mountPosition( position, orientation)
nodejs function set_mountPosition( position, orientation)
php function set_mountPosition( $position, $orientation)
cpp int set_mountPosition( Y_MOUNTPOSITION position,
                           Y_MOUNTORIENTATION orientation)
m -(int) setMountPosition : (Y_MOUNTPOSITION) position
                           : (Y_MOUNTORIENTATION) orientation
pas function set_mountPosition( position: TYMOUNTPOSITION,
                                 orientation: TYMOUNTORIENTATION): LongInt
vb function set_mountPosition( ) As Integer
cs int set_mountPosition( MOUNTPOSITION position,
                           MOUNTORIENTATION orientation)
java int set_mountPosition( MOUNTPOSITION position,
                           MOUNTORIENTATION orientation)
py def set_mountPosition( position, orientation)
cmd YRefFrame target set_mountPosition position orientation

```

The magnetic compass and the tilt sensors (pitch and roll) naturally work in the plane parallel to the earth surface. In case the device is not installed upright and horizontally, you must select its reference orientation (parallel to the earth surface) so that the measures are made relative to this position.

Parameters :

position a value among the Y_MOUNTPOSITION enumeration (Y_MOUNTPOSITION_BOTTOM, Y_MOUNTPOSITION_TOP, Y_MOUNTPOSITION_FRONT, Y_MOUNTPOSITION_RIGHT, Y_MOUNTPOSITION_REAR, Y_MOUNTPOSITION_LEFT), corresponding to the installation in a box, on one of the six faces.

orientation a value among the enumeration Y_MOUNTORIENTATION (Y_MOUNTORIENTATION_TWELVE, Y_MOUNTORIENTATION_THREE, Y_MOUNTORIENTATION_SIX, Y_MOUNTORIENTATION_NINE) corresponding to the orientation of the "X" arrow on the device, as on a clock dial seen from an observer in the center of the box. On the bottom face, the 12H orientation points to the front, while on the top face, the 12H orientation points to the rear. Remember to call the saveToFlash() method of the module if the modification must be kept.

refframe→set(userData)**YRefFrame****refframe→setUserData()|refframe.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|---|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData \$data) |
| cpp | void set(userData void* data) |
| m | -(void) setUserData : (void*) data |
| pas | procedure set(userData Tobject) |
| vb | procedure set(userData ByVal data As Object) |
| cs | void set(userData object data) |
| java | void set(userData Object data) |
| py | def set(userData data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

refframe→start3DCalibration()**YRefFrame**

Initiates the sensors tridimensional calibration process.

```
js function start3DCalibration( )
node.js function start3DCalibration( )
php function start3DCalibration( )
cpp int start3DCalibration( )
m -(int) start3DCalibration
pas function start3DCalibration( ): LongInt
vb function start3DCalibration( ) As Integer
cs int start3DCalibration( )
java int start3DCalibration( )
py def start3DCalibration( )
cmd YRefFrame target start3DCalibration
```

This calibration is used at low level for inertial position estimation and to enhance the precision of the tilt sensors. After calling this method, the device should be moved according to the instructions provided by method `get_3DCalibrationHint`, and `more3DCalibration` should be invoked about 5 times per second. The calibration procedure is completed when the method `get_3DCalibrationProgress` returns 100. At this point, the computed calibration parameters can be applied using method `save3DCalibration`. The calibration process can be canceled at any time using method `cancel3DCalibration`. On failure, throws an exception or returns a negative error code.

refframe→wait_async()**YRefFrame**

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context )
nodejs function wait_async( callback, context )
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.35. Relay function interface

The Yoctopuce application programming interface allows you to switch the relay state. This change is not persistent: the relay will automatically return to its idle position whenever power is lost or if the module is restarted. The library can also generate automatically short pulses of determined duration. On devices with two output for each relay (double throw), the two outputs are named A and B, with output A corresponding to the idle position (at power off) and the output B corresponding to the active state. If you prefer the alternate default state, simply switch your cables on the board.

In order to use the functions described here, you should include:

| | |
|---------|---|
| js | <script type='text/javascript' src='yocto_relay.js'></script> |
| node.js | var yoctolib = require('yoctolib'); |
| | var YRelay = yoctolib.YRelay; |
| php | require_once('yocto_relay.php'); |
| cpp | #include "yocto_relay.h" |
| m | #import "yocto_relay.h" |
| pas | uses yocto_relay; |
| vb | yocto_relay.vb |
| cs | yocto_relay.cs |
| java | import com.yoctopuce.YoctoAPI.YRelay; |
| py | from yocto_relay import * |

Global functions

yFindRelay(func)

Retrieves a relay for a given identifier.

yFirstRelay()

Starts the enumeration of relays currently accessible.

YRelay methods

relay->delayedPulse(ms_delay, ms_duration)

Schedules a pulse.

relay->describe()

Returns a short text that describes unambiguously the instance of the relay in the form TYPE (NAME)=SERIAL.FUNCTIONID.

relay->get_advertisedValue()

Returns the current value of the relay (no more than 6 characters).

relay->get_countdown()

Returns the number of milliseconds remaining before a pulse (delayedPulse() call). When there is no scheduled pulse, returns zero.

relay->get_errorMessage()

Returns the error message of the latest error with the relay.

relay->get_errorType()

Returns the numerical error code of the latest error with the relay.

relay->get_friendlyName()

Returns a global identifier of the relay in the format MODULE_NAME . FUNCTION_NAME.

relay->get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

relay->get_functionId()

Returns the hardware identifier of the relay, without reference to the module.

relay->get_hardwareId()

Returns the unique hardware identifier of the relay in the form SERIAL.FUNCTIONID.

relay→get_logicalName()

Returns the logical name of the relay.

relay→get_maxTimeOnStateA()

Retourne the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state A before automatically switching back in to B state.

relay→get_maxTimeOnStateB()

Retourne the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state B before automatically switching back in to A state.

relay→get_module()

Gets the YModule object for the device on which the function is located.

relay→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

relay→get_output()

Returns the output state of the relays, when used as a simple switch (single throw).

relay→get_pulseTimer()

Returns the number of milliseconds remaining before the relays is returned to idle position (state A), during a measured pulse generation.

relay→get_state()

Returns the state of the relays (A for the idle position, B for the active position).

relay→get_stateAtPowerOn()

Returns the state of the relays at device startup (A for the idle position, B for the active position, UNCHANGED for no change).

relay→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

relay→isOnline()

Checks if the relay is currently reachable, without raising any error.

relay→isOnline_async(callback, context)

Checks if the relay is currently reachable, without raising any error (asynchronous version).

relay→load(msValidity)

Preloads the relay cache with a specified validity duration.

relay→load_async(msValidity, callback, context)

Preloads the relay cache with a specified validity duration (asynchronous version).

relay→nextRelay()

Continues the enumeration of relays started using yFirstRelay().

relay→pulse(ms_duration)

Sets the relay to output B (active) for a specified duration, then brings it automatically back to output A (idle state).

relay→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

relay→set_logicalName(newval)

Changes the logical name of the relay.

relay→set_maxTimeOnStateA(newval)

Sets the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state A before automatically switching back in to B state.

relay→set_maxTimeOnStateB(newval)

3. Reference

Sets the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state B before automatically switching back in to A state.

relay→set_output(newval)

Changes the output state of the relays, when used as a simple switch (single throw).

relay→set_state(newval)

Changes the state of the relays (A for the idle position, B for the active position).

relay→set_stateAtPowerOn(newval)

Preset the state of the relays at device startup (A for the idle position, B for the active position, UNCHANGED for no modification).

relay→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

relay→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YRelay.FindRelay() yFindRelay()YRelay.FindRelay()

YRelay

Retrieves a relay for a given identifier.

| | |
|--------|---|
| js | function yFindRelay(func) |
| nodejs | function FindRelay(func) |
| php | function yFindRelay(\$func) |
| cpp | YRelay* yFindRelay(const string& func) |
| m | YRelay* yFindRelay(NSString* func) |
| pas | function yFindRelay(func: string): TYRelay |
| vb | function yFindRelay(ByVal func As String) As YRelay |
| cs | YRelay FindRelay(string func) |
| java | YRelay FindRelay(String func) |
| py | def FindRelay(func) |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the relay is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YRelay.isOnline()` to test if the relay is indeed online at a given time. In case of ambiguity when looking for a relay by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the relay

Returns :

a `YRelay` object allowing you to drive the relay.

YRelay.FirstRelay() yFirstRelay()YRelay.FirstRelay()

YRelay

Starts the enumeration of relays currently accessible.

```
js function yFirstRelay( )
node.js function FirstRelay( )
php function yFirstRelay( )
cpp YRelay* yFirstRelay( )
m YRelay* yFirstRelay( )
pas function yFirstRelay( ): TYRelay
vb function yFirstRelay( ) As YRelay
cs YRelay FirstRelay( )
java YRelay FirstRelay( )
def FirstRelay( )
```

Use the method `YRelay.nextRelay()` to iterate on next relays.

Returns :

a pointer to a `YRelay` object, corresponding to the first relay currently online, or a `null` pointer if there are none.

relay→delayedPulse()`relay.delayedPulse()`

YRelay

Schedules a pulse.

```
js function delayedPulse( ms_delay, ms_duration)
node.js function delayedPulse( ms_delay, ms_duration)
php function delayedPulse( $ms_delay, $ms_duration)
cpp int delayedPulse( int ms_delay, int ms_duration)
m -(int) delayedPulse : (int) ms_delay : (int) ms_duration
pas function delayedPulse( ms_delay: LongInt, ms_duration: LongInt): integer
vb function delayedPulse( ByVal ms_delay As Integer,
                           ByVal ms_duration As Integer) As Integer
cs int delayedPulse( int ms_delay, int ms_duration)
java int delayedPulse( int ms_delay, int ms_duration)
py def delayedPulse( ms_delay, ms_duration)
cmd YRelay target delayedPulse ms_delay ms_duration
```

Parameters :

ms_delay waiting time before the pulse, in millisecondes

ms_duration pulse duration, in millisecondes

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

relay→describe()relay.describe()**YRelay**

Returns a short text that describes unambiguously the instance of the relay in the form TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|---------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | - (NSString*) describe |
| pas | function describe(): string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the relay (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

relay→get_advertisedValue()**YRelay****relay→advertisedValue()relay.get_advertisedValue()**

Returns the current value of the relay (no more than 6 characters).

| | |
|--------|--|
| js | function get_advertisedValue() |
| nodejs | function get_advertisedValue() |
| php | function get_advertisedValue() |
| cpp | string get_advertisedValue() |
| m | -(NSString*) advertisedValue |
| pas | function get_advertisedValue() : string |
| vb | function get_advertisedValue() As String |
| cs | string get_advertisedValue() |
| java | String get_advertisedValue() |
| py | def get_advertisedValue() |
| cmd | YRelay target get_advertisedValue |

Returns :

a string corresponding to the current value of the relay (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

relay→get_countdown()

YRelay

relay→countdown()relay.get_countdown()

Returns the number of milliseconds remaining before a pulse (delayedPulse() call) When there is no scheduled pulse, returns zero.

| | |
|--------|--|
| js | function get_countdown() |
| nodejs | function get_countdown() |
| php | function get_countdown() |
| cpp | s64 get_countdown() |
| m | -(s64) countdown |
| pas | function get_countdown() : int64 |
| vb | function get_countdown() As Long |
| cs | long get_countdown() |
| java | long get_countdown() |
| py | def get_countdown() |
| cmd | YRelay target get_countdown |

Returns :

an integer corresponding to the number of milliseconds remaining before a pulse (delayedPulse() call) When there is no scheduled pulse, returns zero

On failure, throws an exception or returns Y_COUNTDOWN_INVALID.

relay→get_errorMessage() relay→errorMessage()relay.get_errorMessage()

YRelay

Returns the error message of the latest error with the relay.

```
js function get_errorMessage( )
nodejs function get_errorMessage( )
php function get_errorMessage( )
cpp string get_errorMessage( )
m -(NSString*) errorMessage
pas function get_errorMessage( ): string
vb function get_errorMessage( ) As String
cs string get_errorMessage( )
java String get_errorMessage( )
py def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the relay object

relay->get_errorType()
relay->errorType()relay.get_errorType()**YRelay**

Returns the numerical error code of the latest error with the relay.

| | |
|---------|--|
| js | function get_errorType() |
| node.js | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType() : YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the relay object

relay→get_friendlyName() relay→friendlyName()relay.get_friendlyName()

YRelay

Returns a global identifier of the relay in the format MODULE_NAME . FUNCTION_NAME.

```
js function get_friendlyName( )  
nodejs function get_friendlyName( )  
php function get_friendlyName( )  
cpp string get_friendlyName( )  
m -(NSString*) friendlyName  
cs string get_friendlyName( )  
java String get_friendlyName( )  
py def get_friendlyName( )
```

The returned string uses the logical names of the module and of the relay if they are defined, otherwise the serial number of the module and the hardware identifier of the relay (for exemple: MyCustomName . relay1)

Returns :

a string that uniquely identifies the relay using logical names (ex: MyCustomName . relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

relay→get_functionDescriptor()
relay→functionDescriptor()
relay.get_functionDescriptor()

YRelay

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|--------|--|
| js | function get_functionDescriptor() |
| nodejs | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

relay→get_functionId()**YRelay****relay→functionId()relay.get_functionId()**

Returns the hardware identifier of the relay, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the relay (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

relay→get_hardwareId()**YRelay****relay→hardwareId()relay.get_hardwareId()**

Returns the unique hardware identifier of the relay in the form SERIAL.FUNCTIONID.

| | |
|---------|---|
| js | function get_hardwareId() |
| node.js | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the relay. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the relay (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

relay→get_logicalName()**YRelay****relay→logicalName()relay.get_logicalName()**

Returns the logical name of the relay.

```
js   function get_logicalName( )  
nodejs function get_logicalName( )  
php  function get_logicalName( )  
cpp   string get_logicalName( )  
m    -(NSString*) logicalName  
pas   function get_logicalName( ): string  
vb    function get_logicalName( ) As String  
cs    string get_logicalName( )  
java  String get_logicalName( )  
py    def get_logicalName( )  
cmd   YRelay target get_logicalName
```

Returns :

a string corresponding to the logical name of the relay. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

`relay->get_maxTimeOnStateA()`
`relay->maxTimeOnStateA()`
`relay.get_maxTimeOnStateA()`

YRelay

Retourne the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state A before automatically switching back in to B state.

```
js function get_maxTimeOnStateA( )
nodejs function get_maxTimeOnStateA( )
php function get_maxTimeOnStateA( )
cpp s64 get_maxTimeOnStateA( )
m -(s64) maxTimeOnStateA
pas function get_maxTimeOnStateA( ): int64
vb function get_maxTimeOnStateA( ) As Long
cs long get_maxTimeOnStateA( )
java long get_maxTimeOnStateA( )
py def get_maxTimeOnStateA( )
cmd YRelay target get_maxTimeOnStateA
```

Zero means no maximum time.

Returns :

an integer

On failure, throws an exception or returns Y_MAXTIMEONSTATEA_INVALID.

relay→get_maxTimeOnStateB()
relay→maxTimeOnStateB()
relay.get_maxTimeOnStateB()

YRelay

Retourne the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state B before automatically switching back in to A state.

```
js function get_maxTimeOnStateB( )
nodejs function get_maxTimeOnStateB( )
php function get_maxTimeOnStateB( )
cpp s64 get_maxTimeOnStateB( )
m -(s64) maxTimeOnStateB
pas function get_maxTimeOnStateB( ): int64
vb function get_maxTimeOnStateB( ) As Long
cs long get_maxTimeOnStateB( )
java long get_maxTimeOnStateB( )
py def get_maxTimeOnStateB( )
cmd YRelay target get_maxTimeOnStateB
```

Zero means no maximum time.

Returns :

an integer

On failure, throws an exception or returns Y_MAXTIMEONSTATEB_INVALID.

relay->get_module()**YRelay****relay->module()relay.get_module()**

Gets the `YModule` object for the device on which the function is located.

| | |
|---------|---|
| js | function get_module() |
| node.js | function get_module() |
| php | function get_module() |
| cpp | <code>YModule * get_module()</code> |
| m | <code>-(YModule*) module</code> |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | <code>YModule get_module()</code> |
| java | <code>YModule get_module()</code> |
| py | <code>def get_module()</code> |

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

relay→get_module_async() relay→module_async()

YRelay

Gets the YModule object for the device on which the function is located (asynchronous version).

```
js   function get_module_async( callback, context )
nodejs function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned YModule object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested YModule object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

relay→get_output()**YRelay****relay→output()relay.get_output()**

Returns the output state of the relays, when used as a simple switch (single throw).

| | |
|---------|---|
| js | function get_output() |
| node.js | function get_output() |
| php | function get_output() |
| cpp | Y_OUTPUT_enum get_output() |
| m | -(Y_OUTPUT_enum) output |
| pas | function get_output() : Integer |
| vb | function get_output() As Integer |
| cs | int get_output() |
| java | int get_output() |
| py | def get_output() |
| cmd | YRelay target get_output |

Returns :

either Y_OUTPUT_OFF or Y_OUTPUT_ON, according to the output state of the relays, when used as a simple switch (single throw)

On failure, throws an exception or returns Y_OUTPUT_INVALID.

relay→get_pulseTimer()**YRelay****relay→pulseTimer()relay.get_pulseTimer()**

Returns the number of milliseconds remaining before the relays is returned to idle position (state A), during a measured pulse generation.

| | |
|--------|---|
| js | function get_pulseTimer() |
| nodejs | function get_pulseTimer() |
| php | function get_pulseTimer() |
| cpp | s64 get_pulseTimer() |
| m | -(s64) pulseTimer |
| pas | function get_pulseTimer(): int64 |
| vb | function get_pulseTimer() As Long |
| cs | long get_pulseTimer() |
| java | long get_pulseTimer() |
| py | def get_pulseTimer() |
| cmd | YRelay target get_pulseTimer |

When there is no ongoing pulse, returns zero.

Returns :

an integer corresponding to the number of milliseconds remaining before the relays is returned to idle position (state A), during a measured pulse generation

On failure, throws an exception or returns Y_PULSE_TIMER_INVALID.

relay->get_state()
relay->state()relay.get_state()**YRelay**

Returns the state of the relays (A for the idle position, B for the active position).

| | |
|---------|---|
| js | function get_state() |
| node.js | function get_state() |
| php | function get_state() |
| cpp | Y_STATE_enum get_state() |
| m | -(Y_STATE_enum) state |
| pas | function get_state(): Integer |
| vb | function get_state() As Integer |
| cs | int get_state() |
| java | int get_state() |
| py | def get_state() |
| cmd | YRelay target get_state |

Returns :

either Y_STATE_A or Y_STATE_B, according to the state of the relays (A for the idle position, B for the active position)

On failure, throws an exception or returns Y_STATE_INVALID.

relay→get_stateAtPowerOn()**YRelay****relay→stateAtPowerOn()relay.get_stateAtPowerOn()**

Returns the state of the relays at device startup (A for the idle position, B for the active position, UNCHANGED for no change).

| | |
|--------|--|
| js | function get_stateAtPowerOn() |
| nodejs | function get_stateAtPowerOn() |
| php | function get_stateAtPowerOn() |
| cpp | Y_STATEATPOWERON_enum get_stateAtPowerOn() |
| m | -(Y_STATEATPOWERON_enum) stateAtPowerOn |
| pas | function get_stateAtPowerOn() : Integer |
| vb | function get_stateAtPowerOn() As Integer |
| cs | int get_stateAtPowerOn() |
| java | int get_stateAtPowerOn() |
| py | def get_stateAtPowerOn() |
| cmd | YRelay target get_stateAtPowerOn |

Returns :

a value among Y_STATEATPOWERON_UNCHANGED, Y_STATEATPOWERON_A and Y_STATEATPOWERON_B corresponding to the state of the relays at device startup (A for the idle position, B for the active position, UNCHANGED for no change)

On failure, throws an exception or returns Y_STATEATPOWERON_INVALID.

relay→get(userData)
relay→userData()relay.get(userData)

YRelay

Returns the value of the userData attribute, as previously stored using method set(userData).

```
js function get(userData) 
node.js function get(userData) 
php function get(userData) 
cpp void * get(userData) 
m -(void*) userData 
pas function get(userData): Tobject 
vb function get(userData) As Object 
cs object get(userData) 
java Object get(userData) 
py def get(userData)
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

relay→isOnline()relay.isOnline()

YRelay

Checks if the relay is currently reachable, without raising any error.

| | |
|---------|---|
| js | function isOnline () |
| node.js | function isOnline () |
| php | function isOnline () |
| cpp | bool isOnline () |
| m | -(BOOL) isOnline |
| pas | function isOnline (): boolean |
| vb | function isOnline () As Boolean |
| cs | bool isOnline () |
| java | boolean isOnline () |
| py | def isOnline () |

If there is a cached value for the relay in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the relay.

Returns :

true if the relay can be reached, and false otherwise

relay→isOnline_async()

YRelay

Checks if the relay is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context )
nodejs function isOnline_async( callback, context )
```

If there is a cached value for the relay in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

relay→load()relay.load()

YRelay

Preloads the relay cache with a specified validity duration.

```
js function load( msValidity)
nodejs function load( msValidity)
php function load( $msValidity)
cpp YRETCODE load( int msValidity)
m -(YRETCODE) load : (int) msValidity
pas function load( msValidity: integer): YRETCODE
vb function load( ByVal msValidity As Integer) As YRETCODE
cs YRETCODE load( int msValidity)
java int load( long msValidity)
py def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

relay→load_async()

YRelay

Preloads the relay cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

relay→nextRelay()relay.nextRelay()******YRelay**

Continues the enumeration of relays started using `yFirstRelay()`.

| | |
|--------|--|
| js | <code>function nextRelay()</code> |
| nodejs | <code>function nextRelay()</code> |
| php | <code>function nextRelay()</code> |
| cpp | <code>YRelay * nextRelay()</code> |
| m | <code>-(YRelay*) nextRelay</code> |
| pas | <code>function nextRelay(): TYRelay</code> |
| vb | <code>function nextRelay() As YRelay</code> |
| cs | <code>YRelay nextRelay()</code> |
| java | <code>YRelay nextRelay()</code> |
| py | <code>def nextRelay()</code> |

Returns :

a pointer to a `YRelay` object, corresponding to a relay currently online, or a `null` pointer if there are no more relays to enumerate.

relay→pulse()relay.pulse()****

YRelay

Sets the relay to output B (active) for a specified duration, then brings it automatically back to output A (idle state).

| | |
|--------|--|
| js | function pulse(ms_duration) |
| nodejs | function pulse(ms_duration) |
| php | function pulse(\$ms_duration) |
| cpp | int pulse(int ms_duration) |
| m | -(int) pulse : (int) ms_duration |
| pas | function pulse(ms_duration: LongInt): integer |
| vb | function pulse(ByVal ms_duration As Integer) As Integer |
| cs | int pulse(int ms_duration) |
| java | int pulse(int ms_duration) |
| py | def pulse(ms_duration) |
| cmd | YRelay target pulse ms_duration |

Parameters :

ms_duration pulse duration, in millisecondes

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

relay→registerValueCallback() relay.registerValueCallback()

YRelay

Registers the callback function that is invoked on every change of advertised value.

| | |
|---------|--|
| js | function registerValueCallback(callback) |
| node.js | function registerValueCallback(callback) |
| php | function registerValueCallback(\$callback) |
| cpp | int registerValueCallback(YRelayValueCallback callback) |
| m | -(int) registerValueCallback : (YRelayValueCallback) callback |
| pas | function registerValueCallback(callback : TYRelayValueCallback): LongInt |
| vb | function registerValueCallback() As Integer |
| cs | int registerValueCallback(ValueCallback callback) |
| java | int registerValueCallback(UpdateCallback callback) |
| py | def registerValueCallback(callback) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

relay→set_logicalName()YRelay

Changes the logical name of the relay.

```
js    function set_logicalName( newval)
node.js function set_logicalName( newval)
php   function set_logicalName( $newval)
cpp   int set_logicalName( const string& newval)
m     -(int) setLogicalName : (NSString*) newval
pas   function set_logicalName( newval: string): integer
vb    function set_logicalName( ByVal newval As String) As Integer
cs    int set_logicalName( string newval)
java  int set_logicalName( String newval)
py    def set_logicalName( newval)
cmd   YRelay target set_logicalName newval
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the relay.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

relay→set_maxTimeOnStateA()
relay→setMaxTimeOnStateA()
relay.set_maxTimeOnStateA()

YRelay

Sets the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state A before automatically switching back in to B state.

| | |
|---------|---|
| js | function set_maxTimeOnStateA(newval) |
| node.js | function setMaxTimeOnStateA(newval) |
| php | function set_maxTimeOnStateA(\$newval) |
| cpp | int set_maxTimeOnStateA(s64 newval) |
| m | -(int) setMaxTimeOnStateA : (s64) newval |
| pas | function set_maxTimeOnStateA(newval: int64): integer |
| vb | function set_maxTimeOnStateA(ByVal newval As Long) As Integer |
| cs | int set_maxTimeOnStateA(long newval) |
| java | int set_maxTimeOnStateA(long newval) |
| py | def set_maxTimeOnStateA(newval) |
| cmd | YRelay target set_maxTimeOnStateA newval |

Use zero for no maximum time.

Parameters :

newval an integer

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

`relay->set_maxTimeOnStateB()`
`relay->setMaxTimeOnStateB()`
`relay.set_maxTimeOnStateB()`

YRelay

Sets the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state B before automatically switching back in to A state.

| | |
|---------------------|---|
| <code>js</code> | <code>function set_maxTimeOnStateB(newval)</code> |
| <code>nodejs</code> | <code>function set_maxTimeOnStateB(newval)</code> |
| <code>php</code> | <code>function set_maxTimeOnStateB(\$newval)</code> |
| <code>cpp</code> | <code>int set_maxTimeOnStateB(s64 newval)</code> |
| <code>m</code> | <code>-(int) setMaxTimeOnStateB : (s64) newval</code> |
| <code>pas</code> | <code>function set_maxTimeOnStateB(newval: int64): integer</code> |
| <code>vb</code> | <code>function set_maxTimeOnStateB(ByVal newval As Long) As Integer</code> |
| <code>cs</code> | <code>int set_maxTimeOnStateB(long newval)</code> |
| <code>java</code> | <code>int set_maxTimeOnStateB(long newval)</code> |
| <code>py</code> | <code>def set_maxTimeOnStateB(newval)</code> |
| <code>cmd</code> | <code>YRelay target set_maxTimeOnStateB newval</code> |

Use zero for no maximum time.

Parameters :

`newval` an integer

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

relay->set_output()**YRelay****relay->setOutput()relay.set_output()**

Changes the output state of the relays, when used as a simple switch (single throw).

| | |
|---------------------|---|
| <code>js</code> | <code>function set_output(newval)</code> |
| <code>nodejs</code> | <code>function set_output(newval)</code> |
| <code>php</code> | <code>function set_output(\$newval)</code> |
| <code>cpp</code> | <code>int set_output(Y_OUTPUT_enum newval)</code> |
| <code>m</code> | <code>-(int) setOutput : (Y_OUTPUT_enum) newval</code> |
| <code>pas</code> | <code>function set_output(newval: Integer): integer</code> |
| <code>vb</code> | <code>function set_output(ByVal newval As Integer) As Integer</code> |
| <code>cs</code> | <code>int set_output(int newval)</code> |
| <code>java</code> | <code>int set_output(int newval)</code> |
| <code>py</code> | <code>def set_output(newval)</code> |
| <code>cmd</code> | <code>YRelay target set_output newval</code> |

Parameters :

newval either Y_OUTPUT_OFF or Y_OUTPUT_ON, according to the output state of the relays, when used as a simple switch (single throw)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

relay→set_state()**YRelay****relay→setState()relay.set_state()**

Changes the state of the relays (A for the idle position, B for the active position).

| | |
|---------|--|
| js | function set_state(newval) |
| node.js | function set_state(newval) |
| php | function set_state(\$newval) |
| cpp | int set_state(Y_STATE_enum newval) |
| m | -(int) setState : (Y_STATE_enum) newval |
| pas | function set_state(newval: Integer): integer |
| vb | function set_state(ByVal newval As Integer) As Integer |
| cs | int set_state(int newval) |
| java | int set_state(int newval) |
| py | def set_state(newval) |
| cmd | YRelay target set_state newval |

Parameters :

newval either Y_STATE_A or Y_STATE_B, according to the state of the relays (A for the idle position, B for the active position)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

relay→set_stateAtPowerOn()
relay→setStateAtPowerOn()
relay.set_stateAtPowerOn()

YRelay

Preset the state of the relays at device startup (A for the idle position, B for the active position, UNCHANGED for no modification).

| | |
|---------------|---|
| js | function set_stateAtPowerOn(newval) |
| nodejs | function set_stateAtPowerOn(newval) |
| php | function set_stateAtPowerOn(\$newval) |
| cpp | int set_stateAtPowerOn(Y_STATEATPOWERON_enum newval) |
| m | -(int) setStateAtPowerOn : (Y_STATEATPOWERON_enum) newval |
| pas | function set_stateAtPowerOn(newval: Integer): integer |
| vb | function set_stateAtPowerOn(ByVal newval As Integer) As Integer |
| cs | int set_stateAtPowerOn(int newval) |
| java | int set_stateAtPowerOn(int newval) |
| py | def set_stateAtPowerOn(newval) |
| cmd | YRelay target set_stateAtPowerOn newval |

Remember to call the matching module `saveToFlash()` method, otherwise this call will have no effect.

Parameters :

newval a value among `Y_STATEATPOWERON_UNCHANGED`, `Y_STATEATPOWERON_A` and `Y_STATEATPOWERON_B`

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

relay→set(userData)
relay→setUserData()relay.set(userData)

YRelay

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|---|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData) |
| cpp | void set(userData) |
| m | -(void) setUserData : (void*) data |
| pas | procedure set(userData) (data : Tobject) |
| vb | procedure set(userData) ByVal data As Object) |
| cs | void set(userData) (object data) |
| java | void set(userData) (Object data) |
| py | def set(userData) (data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

relay→wait_async()

YRelay

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context )
nodejs function wait_async( callback, context )
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.36. Sensor function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_api.js'></script>
nodejs var yoctolib = require('yoctolib');
var YAPI = yoctolib.YAPI;
var YModule = yoctolib.YModule;
php require_once('yocto_api.php');
cpp #include "yocto_api.h"
m #import "yocto_api.h"
pas uses yocto_api;
vb yocto_api.vb
cs yocto_api.cs
java import com.yoctopuce.YoctoAPI.YModule;
py from yocto_api import *

```

Global functions

yFindSensor(func)

Retrieves a sensor for a given identifier.

yFirstSensor()

Starts the enumeration of sensors currently accessible.

YSensor methods

sensor->calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

sensor->describe()

Returns a short text that describes unambiguously the instance of the sensor in the form TYPE(NAME)=SERIAL.FUNCTIONID.

sensor->get_advertisedValue()

Returns the current value of the sensor (no more than 6 characters).

sensor->get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor.

sensor->get_currentValue()

Returns the current value of the measure.

sensor->get_errorMessage()

Returns the error message of the latest error with the sensor.

sensor->get_errorType()

Returns the numerical error code of the latest error with the sensor.

sensor->get_friendlyName()

Returns a global identifier of the sensor in the format MODULE_NAME . FUNCTION_NAME.

sensor->get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

sensor->get_functionId()

Returns the hardware identifier of the sensor, without reference to the module.

sensor->get_hardwareId()

Returns the unique hardware identifier of the sensor in the form SERIAL.FUNCTIONID.

sensor→get_highestValue()

Returns the maximal value observed for the measure since the device was started.

sensor→get_logFrequency()

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

sensor→get_logicalName()

Returns the logical name of the sensor.

sensor→get_lowestValue()

Returns the minimal value observed for the measure since the device was started.

sensor→get_module()

Gets the YModule object for the device on which the function is located.

sensor→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

sensor→get_recordedData(startTime, endTime)

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

sensor→get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

sensor→get_resolution()

Returns the resolution of the measured values.

sensor→get_unit()

Returns the measuring unit for the measure.

sensor→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

sensor→isOnline()

Checks if the sensor is currently reachable, without raising any error.

sensor→isOnline_async(callback, context)

Checks if the sensor is currently reachable, without raising any error (asynchronous version).

sensor→load(msValidity)

Preloads the sensor cache with a specified validity duration.

sensor→loadCalibrationPoints(rawValues, refValues)

Retrieves error correction data points previously entered using the method calibrateFromPoints.

sensor→load_async(msValidity, callback, context)

Preloads the sensor cache with a specified validity duration (asynchronous version).

sensor→nextSensor()

Continues the enumeration of sensors started using yFirstSensor().

sensor→registerTimedReportCallback(callback)

Registers the callback function that is invoked on every periodic timed notification.

sensor→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

sensor→set_highestValue(newval)

Changes the recorded maximal value observed.

sensor→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

sensor→set_logicalName(newval)

3. Reference

Changes the logical name of the sensor.

sensor→set_lowestValue(newval)

Changes the recorded minimal value observed.

sensor→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

sensor→set_resolution(newval)

Changes the resolution of the measured physical values.

sensor→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

sensor→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YSensor.FindSensor() yFindSensor()YSensor.FindSensor()

YSensor

Retrieves a sensor for a given identifier.

| | |
|---------------------|---|
| <code>js</code> | <code>function yFindSensor(func)</code> |
| <code>nodejs</code> | <code>function FindSensor(func)</code> |
| <code>php</code> | <code>function yFindSensor(\$func)</code> |
| <code>cpp</code> | <code>YSensor* yFindSensor(string func)</code> |
| <code>m</code> | <code>+YSensor*) yFindSensor : (NSString*) func</code> |
| <code>pas</code> | <code>function yFindSensor(func: string): TYSensor</code> |
| <code>vb</code> | <code>function yFindSensor(ByVal func As String) As YSensor</code> |
| <code>cs</code> | <code>YSensor FindSensor(string func)</code> |
| <code>java</code> | <code>YSensor FindSensor(String func)</code> |
| <code>py</code> | <code>def FindSensor(func)</code> |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YSensor.isOnline()` to test if the sensor is indeed online at a given time. In case of ambiguity when looking for a sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the sensor

Returns :

a `YSensor` object allowing you to drive the sensor.

YSensor.FirstSensor() yFirstSensor()YSensor.FirstSensor()

YSensor

Starts the enumeration of sensors currently accessible.

| | |
|---------|---|
| js | function yFirstSensor() |
| node.js | function FirstSensor() |
| php | function yFirstSensor() |
| cpp | YSensor* yFirstSensor() |
| m | YSensor* yFirstSensor() |
| pas | function yFirstSensor() : TYSensor |
| vb | function yFirstSensor() As YSensor |
| cs | YSensor FirstSensor() |
| java | YSensor FirstSensor() |
| py | def FirstSensor() |

Use the method `YSensor.nextSensor()` to iterate on next sensors.

Returns :

a pointer to a `YSensor` object, corresponding to the first sensor currently online, or a null pointer if there are none.

sensor→calibrateFromPoints() sensor.calibrateFromPoints()

YSensor

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```

js   function calibrateFromPoints( rawValues, refValues)
node.js function calibrateFromPoints( rawValues, refValues)
php  function calibrateFromPoints( $rawValues, $refValues)
cpp   int calibrateFromPoints( vector<double> rawValues,
                           vector<double> refValues)

m    -(int) calibrateFromPoints : (NSMutableArray*) rawValues
      : (NSMutableArray*) refValues

pas  function calibrateFromPoints( rawValues: TDoubleArray,
                                  refValues: TDoubleArray): LongInt

vb   procedure calibrateFromPoints( )

cs   int calibrateFromPoints( List<double> rawValues,
                           List<double> refValues)

java int calibrateFromPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def calibrateFromPoints( rawValues, refValues)
cmd  YSensor target calibrateFromPoints rawValues refValues

```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.
refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

sensor→describe()sensor.describe()**YSensor**

Returns a short text that describes unambiguously the instance of the sensor in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|---------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | - (NSString*) describe |
| pas | function describe(): string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the sensor (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

sensor→get_advertisedValue()
sensor→advertisedValue()
sensor.get_advertisedValue()

YSensor

Returns the current value of the sensor (no more than 6 characters).

| | |
|----------------------|--|
| <code>js</code> | function get_advertisedValue() |
| <code>node.js</code> | function get_advertisedValue() |
| <code>php</code> | function get_advertisedValue() |
| <code>cpp</code> | string get_advertisedValue() |
| <code>m</code> | -(NSString*) advertisedValue |
| <code>pas</code> | function get_advertisedValue() : string |
| <code>vb</code> | function get_advertisedValue() As String |
| <code>cs</code> | string get_advertisedValue() |
| <code>java</code> | String get_advertisedValue() |
| <code>py</code> | def get_advertisedValue() |
| <code>cmd</code> | YSensor target get_advertisedValue |

Returns :

a string corresponding to the current value of the sensor (no more than 6 characters). On failure, throws an exception or returns `Y_ADVERTISEDVALUE_INVALID`.

sensor→get_currentRawValue()
sensor→currentRawValue()
sensor.get_currentRawValue()

YSensor

Returns the uncalibrated, unrounded raw value returned by the sensor.

js function **get_currentRawValue()**
nodejs function **get_currentRawValue()**
php function **get_currentRawValue()**
cpp double **get_currentRawValue()**
m -(double) currentRawValue
pas function **get_currentRawValue(): double**
vb function **get_currentRawValue() As Double**
cs double **get_currentRawValue()**
java double **get_currentRawValue()**
py def **get_currentRawValue()**
cmd YSensor **target get_currentRawValue**

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor

On failure, throws an exception or returns **Y_CURRENTRAWVALUE_INVALID**.

sensor→get_currentValue()
sensor→currentValue()sensor.get_currentValue()**YSensor**

Returns the current value of the measure.

| | |
|--------|---|
| js | function get_currentValue() |
| nodejs | function get_currentValue() |
| php | function get_currentValue() |
| cpp | double get_currentValue() |
| m | -(double) currentValue |
| pas | function get_currentValue(): double |
| vb | function get_currentValue() As Double |
| cs | double get_currentValue() |
| java | double get_currentValue() |
| py | def get_currentValue() |
| cmd | YSensor target get_currentValue |

Returns :

a floating point number corresponding to the current value of the measure

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

sensor→get_errorMessage() YSensor
sensor→errorMessage()sensor.get_errorMessage()

Returns the error message of the latest error with the sensor.

```
js function get_errorMessage( )
node.js function get_errorMessage( )
php function get_errorMessage( )
cpp string get_errorMessage( )
m -(NSString*) errorMessage
pas function get_errorMessage( ): string
vb function get_errorMessage( ) As String
cs string get_errorMessage( )
java String get_errorMessage( )
py def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the sensor object

sensor→get_errorType()
sensor→errorType()sensor.get_errorType()**YSensor**

Returns the numerical error code of the latest error with the sensor.

| | |
|--------|--|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType(): YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the sensor object

sensor→get_friendlyName() YSensor
sensor→friendlyName() **sensor.get_friendlyName()**

Returns a global identifier of the sensor in the format MODULE_NAME . FUNCTION_NAME.

```
js function get_friendlyName( )  
node.js function get_friendlyName( )  
php function get_friendlyName( )  
cpp string get_friendlyName( )  
m -(NSString*) friendlyName  
cs string get_friendlyName( )  
java String get_friendlyName( )  
py def get_friendlyName( )
```

The returned string uses the logical names of the module and of the sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the sensor (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the sensor using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

sensor→get_functionDescriptor()
sensor→functionDescriptor()
sensor.get_functionDescriptor()

YSensor

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

sensor→get_functionId() YSensor
sensor→functionId()sensor.get_functionId()

Returns the hardware identifier of the sensor, without reference to the module.

```
js function get_functionId( )
node.js function get_functionId( )
php function get_functionId( )
cpp string get_functionId( )
m -(NSString*) functionId
vb function get_functionId( ) As String
cs string get_functionId( )
java String get_functionId( )
py def get_functionId( )
```

For example relay1

Returns :

a string that identifies the sensor (ex: relay1) On failure, throws an exception or returns Y_FUNCTIONID_INVALID.

sensor→get_hardwareId()
sensor→hardwareId()sensor.get_hardwareId()**YSensor**

Returns the unique hardware identifier of the sensor in the form SERIAL.FUNCTIONID.

| | |
|--------|---|
| js | function get_hardwareId() |
| nodejs | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the sensor. (for example RELAY01-123456.relay1)

Returns :

a string that uniquely identifies the sensor (ex: RELAY01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

sensor→get_highestValue() **YSensor**
sensor→highestValue()sensor.get_highestValue()

Returns the maximal value observed for the measure since the device was started.

```
js function get_highestValue( )  
node.js function get_highestValue( )  
php function get_highestValue( )  
cpp double get_highestValue( )  
m -(double) highestValue  
pas function get_highestValue( ): double  
vb function get_highestValue( ) As Double  
cs double get_highestValue( )  
java double get_highestValue( )  
py def get_highestValue( )  
cmd YSensor target get_highestValue
```

Returns :

a floating point number corresponding to the maximal value observed for the measure since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

sensor→get_logFrequency()**YSensor****sensor→logFrequency()sensor.get_logFrequency()**

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

| | |
|--------|--|
| js | function get_logFrequency() |
| nodejs | function get_logFrequency() |
| php | function get_logFrequency() |
| cpp | string get_logFrequency() |
| m | -(NSString*) logFrequency |
| pas | function get_logFrequency() : string |
| vb | function get_logFrequency() As String |
| cs | string get_logFrequency() |
| java | String get_logFrequency() |
| py | def get_logFrequency() |
| cmd | YSensor target get_logFrequency |

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

sensor→get_logicalName()
sensor→logicalName()sensor.get_logicalName()

YSensor

Returns the logical name of the sensor.

```
js function get_logicalName( )
node.js function get_logicalName( )
php function get_logicalName( )
cpp string get_logicalName( )
m -(NSString*) logicalName
pas function get_logicalName( ): string
vb function get_logicalName( ) As String
cs string get_logicalName( )
java String get_logicalName( )
py def get_logicalName( )
cmd YSensor target get_logicalName
```

Returns :

a string corresponding to the logical name of the sensor. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

sensor→get_lowestValue()**YSensor****sensor→lowestValue()sensor.get_lowestValue()**

Returns the minimal value observed for the measure since the device was started.

| | |
|--------|--|
| js | function get_lowestValue() |
| nodejs | function get_lowestValue() |
| php | function get_lowestValue() |
| cpp | double get_lowestValue() |
| m | -(double) lowestValue |
| pas | function get_lowestValue(): double |
| vb | function get_lowestValue() As Double |
| cs | double get_lowestValue() |
| java | double get_lowestValue() |
| py | def get_lowestValue() |
| cmd | YSensor target get_lowestValue |

Returns :

a floating point number corresponding to the minimal value observed for the measure since the device was started

On failure, throws an exception or returns **Y_LOWESTVALUE_INVALID**.

sensor→get_module()
sensor→module()sensor.get_module()**YSensor**

Gets the `YModule` object for the device on which the function is located.

| | |
|---------|---|
| js | function get_module() |
| node.js | function get_module() |
| php | function get_module() |
| cpp | <code>YModule * get_module()</code> |
| m | <code>-(YModule*) module</code> |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | <code>YModule get_module()</code> |
| java | <code>YModule get_module()</code> |
| py | <code>def get_module()</code> |

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

sensor→get_module_async()
sensor→module_async()**YSensor**

Gets the YModule object for the device on which the function is located (asynchronous version).

```
js   function get_module_async( callback, context )
nodejs function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned YModule object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested YModule object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

sensor→get_recordedData()

YSensor

sensor→recordedData() sensor.get_recordedData()

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the `DataSet` class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measurement, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measurement, without ending limit.

Returns :

an instance of `YDataSet`, providing access to historical data. Past measures can be loaded progressively using methods from the `YDataSet` object.

sensor→get_reportFrequency()
sensor→reportFrequency()
sensor.get_reportFrequency()**YSensor**

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

| | |
|--------|--|
| js | function get_reportFrequency() |
| nodejs | function get_reportFrequency() |
| php | function get_reportFrequency() |
| cpp | string get_reportFrequency() |
| m | -(NSString*) reportFrequency |
| pas | function get_reportFrequency() : string |
| vb | function get_reportFrequency() As String |
| cs | string get_reportFrequency() |
| java | String get_reportFrequency() |
| py | def get_reportFrequency() |
| cmd | YSensor target get_reportFrequency |

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns `Y_REPORTFREQUENCY_INVALID`.

sensor→get_resolution() YSensor
sensor→resolution()sensor.get_resolution()

Returns the resolution of the measured values.

```
js function get_resolution( )
node.js function get_resolution( )
php function get_resolution( )
cpp double get_resolution( )
m -(double) resolution
pas function get_resolution( ): double
vb function get_resolution( ) As Double
cs double get_resolution( )
java double get_resolution( )
py def get_resolution( )
cmd YSensor target get_resolution
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

sensor→get_unit()
sensor→unit()sensor.get_unit()**YSensor**

Returns the measuring unit for the measure.

| | |
|--------|---------------------------------------|
| js | function get_unit() |
| nodejs | function get_unit() |
| php | function get_unit() |
| cpp | string get_unit() |
| m | -(NSString*) unit |
| pas | function get_unit() : string |
| vb | function get_unit() As String |
| cs | string get_unit() |
| java | String get_unit() |
| py | def get_unit() |
| cmd | YSensor target get_unit |

Returns :

a string corresponding to the measuring unit for the measure

On failure, throws an exception or returns Y_UNIT_INVALID.

sensor→get(userData)
sensor→userData()sensor.get(userData())**YSensor**

Returns the value of the userData attribute, as previously stored using method set(userData).

```
js function get(userData) 
node.js function get(userData) 
php function get(userData) 
cpp void * get(userData) 
m -(void*) userData 
pas function get(userData): Tobject 
vb function get(userData) As Object 
cs object get(userData) 
java Object get(userData) 
py def get(userData)
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

sensor→isOnline()sensor.isOnline()**YSensor**

Checks if the sensor is currently reachable, without raising any error.

| | |
|---------|--|
| js | function isOnline() |
| node.js | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the sensor.

Returns :

`true` if the sensor can be reached, and `false` otherwise

sensor→isOnline_async()

YSensor

Checks if the sensor is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

sensor→load()|sensor.load()**YSensor**

Preloads the sensor cache with a specified validity duration.

| | |
|---------------------|--|
| <code>js</code> | <code>function load(msValidity)</code> |
| <code>nodejs</code> | <code>function load(msValidity)</code> |
| <code>php</code> | <code>function load(\$msValidity)</code> |
| <code>cpp</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>m</code> | <code>-(YRETCODE) load : (int) msValidity</code> |
| <code>pas</code> | <code>function load(msValidity: integer): YRETCODE</code> |
| <code>vb</code> | <code>function load(ByVal msValidity As Integer) As YRETCODE</code> |
| <code>cs</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>java</code> | <code>int load(long msValidity)</code> |
| <code>py</code> | <code>def load(msValidity)</code> |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

sensor→loadCalibrationPoints() sensor.loadCalibrationPoints()

YSensor

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```

js   function loadCalibrationPoints( rawValues, refValues)
nodejs function loadCalibrationPoints( rawValues, refValues)
php  function loadCalibrationPoints( &$rawValues, &$refValues)
cpp   int loadCalibrationPoints( vector<double>& rawValues,
                                vector<double>& refValues)

m    -(int) loadCalibrationPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues

pas  function loadCalibrationPoints( var rawValues: TDoubleArray,
                           var refValues: TDoubleArray): LongInt

vb   procedure loadCalibrationPoints( )
cs   int loadCalibrationPoints( List<double> rawValues,
                           List<double> refValues)

java int loadCalibrationPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def loadCalibrationPoints( rawValues, refValues)
cmd  YSensor target loadCalibrationPoints rawValues refValues

```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

sensor→load_async()

YSensor

Preloads the sensor cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

sensor→nextSensor()sensor.nextSensor()**YSensor**

Continues the enumeration of sensors started using `yFirstSensor()`.

| | |
|--------|---|
| js | function nextSensor() |
| nodejs | function nextSensor() |
| php | function nextSensor() |
| cpp | YSensor * nextSensor() |
| m | - (YSensor*) nextSensor |
| pas | function nextSensor() : TYSensor |
| vb | function nextSensor() As YSensor |
| cs | YSensor nextSensor() |
| java | YSensor nextSensor() |
| py | def nextSensor() |

Returns :

a pointer to a `YSensor` object, corresponding to a sensor currently online, or a `null` pointer if there are no more sensors to enumerate.

sensor→registerTimedReportCallback() sensor.registerTimedReportCallback()

YSensor

Registers the callback function that is invoked on every periodic timed notification.

```
js   function registerTimedReportCallback( callback )
nodejs function registerTimedReportCallback( callback )
php  function registerTimedReportCallback( $callback )
cpp   int registerTimedReportCallback( YSensorTimedReportCallback callback )
m     -(int) registerTimedReportCallback : (YSensorTimedReportCallback) callback
pas   function registerTimedReportCallback( callback: TYSensorTimedReportCallback): LongInt
vb    function registerTimedReportCallback( ) As Integer
cs    int registerTimedReportCallback( TimedReportCallback callback )
java  int registerTimedReportCallback( TimedReportCallback callback )
py    def registerTimedReportCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

sensor→registerValueCallback() sensor.registerValueCallback()

YSensor

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YSensorValueCallback callback )
m    -(int) registerValueCallback : (YSensorValueCallback) callback
pas   function registerValueCallback( callback: TYSensorValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

sensor→set_highestValue()
sensor→setHighestValue()sensor.set_highestValue()**YSensor**

Changes the recorded maximal value observed.

```
js   function set_highestValue( newval)
nodejs function set_highestValue( newval)
php  function set_highestValue( $newval)
cpp   int set_highestValue( double newval)
m    -(int) setHighestValue : (double) newval
pas   function set_highestValue( newval: double): integer
vb    function set_highestValue( ByVal newval As Double) As Integer
cs    int set_highestValue( double newval)
java  int set_highestValue( double newval)
py    def set_highestValue( newval)
cmd   YSensor target set_highestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

sensor→set_logFrequency()
sensor→setLogFrequency()
sensor.set_logFrequency()

YSensor

Changes the datalogger recording frequency for this function.

```
js  function set_logFrequency( newval)
nodejs function set_logFrequency( newval)
php  function set_logFrequency( $newval)
cpp  int set_logFrequency( const string& newval)
m   -(int) setLogFrequency : (NSString*) newval
pas  function set_logFrequency( newval: string): integer
vb   function set_logFrequency( ByVal newval As String) As Integer
cs   int set_logFrequency( string newval)
java int set_logFrequency( String newval)
py   def set_logFrequency( newval)
cmd  YSensor target set_logFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

| | |
|--|----------------|
| sensor→set_logicalName() | YSensor |
| sensor→setLogicalName()sensor.set_logicalName() | |

Changes the logical name of the sensor.

| | |
|---------------------|---|
| <code>js</code> | function set_logicalName(newval) |
| <code>nodejs</code> | function set_logicalName(newval) |
| <code>php</code> | function set_logicalName(\$newval) |
| <code>cpp</code> | int set_logicalName(const string& newval) |
| <code>m</code> | -(int) setLogicalName : (NSString*) newval |
| <code>pas</code> | function set_logicalName(newval: string): integer |
| <code>vb</code> | function set_logicalName(ByVal newval As String) As Integer |
| <code>cs</code> | int set_logicalName(string newval) |
| <code>java</code> | int set_logicalName(String newval) |
| <code>py</code> | def set_logicalName(newval) |
| <code>cmd</code> | YSensor target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the logical name of the sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

sensor→set_lowestValue() **YSensor**
sensor→setLowestValue()sensor.set_lowestValue()

Changes the recorded minimal value observed.

```
js function set_lowestValue( newval)
node.js function set_lowestValue( newval)
php function set_lowestValue( $newval)
cpp int set_lowestValue( double newval)
m -(int) setLowestValue : (double) newval
pas function set_lowestValue( newval: double): integer
vb function set_lowestValue( ByVal newval As Double) As Integer
cs int set_lowestValue( double newval)
java int set_lowestValue( double newval)
py def set_lowestValue( newval)
cmd YSensor target set_lowestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

sensor→set_reportFrequency()
sensor→setReportFrequency()
sensor.set_reportFrequency()

YSensor

Changes the timed value notification frequency for this function.

| | |
|---------------|---|
| js | function set_reportFrequency(newval) |
| nodejs | function set_reportFrequency(newval) |
| php | function set_reportFrequency(\$newval) |
| cpp | int set_reportFrequency(const string& newval) |
| m | -(int) setReportFrequency : (NSString*) newval |
| pas | function set_reportFrequency(newval: string): integer |
| vb | function set_reportFrequency(ByVal newval As String) As Integer |
| cs | int set_reportFrequency(string newval) |
| java | int set_reportFrequency(String newval) |
| py | def set_reportFrequency(newval) |
| cmd | YSensor target set_reportFrequency newval |

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

sensor→set_resolution() sensor→setResolution()sensor.set_resolution()

YSensor

Changes the resolution of the measured physical values.

```
js function set_resolution( newval)
node.js function set_resolution( newval)
php function set_resolution( $newval)
cpp int set_resolution( double newval)
m -(int) setResolution : (double) newval
pas function set_resolution( newval: double): integer
vb function set_resolution( ByVal newval As Double) As Integer
cs int set_resolution( double newval)
java int set_resolution( double newval)
py def set_resolution( newval)
cmd YSensor target set_resolution newval
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

sensor→set(userData)**YSensor****sensor→setUserData()|sensor.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|--|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData) \$data |
| cpp | void set(userData) void* data |
| m | -(void) setUserData : (void*) data |
| pas | procedure set(userData) Tobject |
| vb | procedure set(userData) ByVal data As Object |
| cs | void set(userData) object data |
| java | void set(userData) Object data |
| py | def set(userData) data |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

sensor→wait_async()

YSensor

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.37. Servo function interface

Yoctopuce application programming interface allows you not only to move a servo to a given position, but also to specify the time interval in which the move should be performed. This makes it possible to synchronize two servos involved in a same move.

In order to use the functions described here, you should include:

| | |
|---------|---|
| js | <script type='text/javascript' src='yocto_servo.js'></script> |
| node.js | var yoctolib = require('yoctolib'); |
| | var YServo = yoctolib.YServo; |
| php | require_once('yocto_servo.php'); |
| cpp | #include "yocto_servo.h" |
| m | #import "yocto_servo.h" |
| pas | uses yocto_servo; |
| vb | yocto_servo.vb |
| cs | yocto_servo.cs |
| java | import com.yoctopuce.YoctoAPI.YServo; |
| py | from yocto_servo import * |

Global functions

yFindServo(func)

Retrieves a servo for a given identifier.

yFirstServo()

Starts the enumeration of servos currently accessible.

YServo methods

servo->describe()

Returns a short text that describes unambiguously the instance of the servo in the form TYPE (NAME)=SERIAL.FUNCTIONID.

servo->get_advertisedValue()

Returns the current value of the servo (no more than 6 characters).

servo->get_enabled()

Returns the state of the servos.

servo->get_enabledAtPowerOn()

Returns the servo signal generator state at power up.

servo->get_errorMessage()

Returns the error message of the latest error with the servo.

servo->get_errorType()

Returns the numerical error code of the latest error with the servo.

servo->get_friendlyName()

Returns a global identifier of the servo in the format MODULE_NAME . FUNCTION_NAME.

servo->get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

servo->get_functionId()

Returns the hardware identifier of the servo, without reference to the module.

servo->get_hardwareId()

Returns the unique hardware identifier of the servo in the form SERIAL . FUNCTIONID.

servo->get_logicalName()

Returns the logical name of the servo.

3. Reference

servo→get_module()

Gets the YModule object for the device on which the function is located.

servo→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

servo→get_neutral()

Returns the duration in microseconds of a neutral pulse for the servo.

servo→get_position()

Returns the current servo position.

servo→get_positionAtPowerOn()

Returns the servo position at device power up.

servo→get_range()

Returns the current range of use of the servo.

servo→get_userData()

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

servo→isOnline()

Checks if the servo is currently reachable, without raising any error.

servo→isOnline_async(callback, context)

Checks if the servo is currently reachable, without raising any error (asynchronous version).

servo→load(msValidity)

Preloads the servo cache with a specified validity duration.

servo→load_async(msValidity, callback, context)

Preloads the servo cache with a specified validity duration (asynchronous version).

servo→move(target, ms_duration)

Performs a smooth move at constant speed toward a given position.

servo→nextServo()

Continues the enumeration of servos started using `yFirstServo()`.

servo→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

servo→set_enabled(newval)

Stops or starts the servo.

servo→set_enabledAtPowerOn(newval)

Configure the servo signal generator state at power up.

servo→set_logicalName(newval)

Changes the logical name of the servo.

servo→set_neutral(newval)

Changes the duration of the pulse corresponding to the neutral position of the servo.

servo→set_position(newval)

Changes immediately the servo driving position.

servo→set_positionAtPowerOn(newval)

Configure the servo position at device power up.

servo→set_range(newval)

Changes the range of use of the servo, specified in per cents.

servo→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

servo→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YServo.FindServo() yFindServo()YServo.FindServo()

YServo

Retrieves a servo for a given identifier.

```
js function yFindServo( func)
node.js function FindServo( func)
php function yFindServo( $func)
cpp YServo* yFindServo( const string& func)
m YServo* yFindServo( NSString* func)
pas function yFindServo( func: string): TYServo
vb function yFindServo( ByVal func As String) As YServo
cs YServo FindServo( string func)
java YServo FindServo( String func)
py def FindServo( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the servo is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YServo.isOnline()` to test if the servo is indeed online at a given time. In case of ambiguity when looking for a servo by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the servo

Returns :

a `YServo` object allowing you to drive the servo.

YServo.FirstServo()**YServo****yFirstServo()YServo.FirstServo()**

Starts the enumeration of servos currently accessible.

| | |
|--------|--|
| js | function yFirstServo() |
| nodejs | function FirstServo() |
| php | function yFirstServo() |
| cpp | YServo* yFirstServo() |
| m | YServo* yFirstServo() |
| pas | function yFirstServo() : TYServo |
| vb | function yFirstServo() As YServo |
| cs | YServo FirstServo() |
| java | YServo FirstServo() |
| py | def FirstServo() |

Use the method `YServo.nextServo()` to iterate on next servos.

Returns :

a pointer to a `YServo` object, corresponding to the first servo currently online, or a null pointer if there are none.

servo→describe()servo.describe()**YServo**

Returns a short text that describes unambiguously the instance of the servo in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|---------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | - (NSString*) describe |
| pas | function describe(): string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the servo (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

servo→get_advertisedValue()**YServo****servo→advertisedValue()servo.get_advertisedValue()**

Returns the current value of the servo (no more than 6 characters).

```
js function get_advertisedValue( )  
nodejs function get_advertisedValue( )  
php function get_advertisedValue( )  
cpp string get_advertisedValue( )  
m -(NSString*) advertisedValue  
pas function get_advertisedValue( ): string  
vb function get_advertisedValue( ) As String  
cs string get_advertisedValue( )  
java String get_advertisedValue( )  
py def get_advertisedValue( )  
cmd YServo target get_advertisedValue
```

Returns :

a string corresponding to the current value of the servo (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

servo→get_enabled()
servo→enabled()servo.get_enabled()**YServo**

Returns the state of the servos.

```
js function get_enabled( )
node.js function get_enabled( )
php function get_enabled( )
cpp Y_ENABLED_enum get_enabled( )
m -(Y_ENABLED_enum) enabled
pas function get_enabled( ): Integer
vb function get_enabled( ) As Integer
cs int get_enabled( )
java int get_enabled( )
py def get_enabled( )
cmd YServo target get_enabled
```

Returns :

either Y_ENABLED_FALSE or Y_ENABLED_TRUE, according to the state of the servos

On failure, throws an exception or returns Y_ENABLED_INVALID.

servo→get_enabledAtPowerOn()
servo→enabledAtPowerOn()
servo.get_enabledAtPowerOn()

YServo

Returns the servo signal generator state at power up.

```
js    function get_enabledAtPowerOn( )  
node.js function get_enabledAtPowerOn( )  
php   function get_enabledAtPowerOn( )  
cpp   Y_ENABLEDATPOWERON_enum get_enabledAtPowerOn( )  
m     -(Y_ENABLEDATPOWERON_enum) enabledAtPowerOn  
pas   function get_enabledAtPowerOn( ): Integer  
vb    function get_enabledAtPowerOn( ) As Integer  
cs    int get_enabledAtPowerOn( )  
java  int get_enabledAtPowerOn( )  
py    def get_enabledAtPowerOn( )  
cmd   YServo target get_enabledAtPowerOn
```

Returns :

either Y_ENABLEDATPOWERON_FALSE or Y_ENABLEDATPOWERON_TRUE, according to the servo signal generator state at power up

On failure, throws an exception or returns Y_ENABLEDATPOWERON_INVALID.

servo→getErrorMessage()**servo→errorMessage()servo.getErrorMessage()****YServo**

Returns the error message of the latest error with the servo.

```
js function getErrorMessage( )
node.js function getErrorMessage( )
php function getErrorMessage( )
cpp string getErrorMessage( )
m -(NSString*) errorMessage
pas function getErrorMessage( ): string
vb function getErrorMessage( ) As String
cs string getErrorMessage( )
java String getErrorMessage( )
py def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the servo object

servo→get_errorType()**YServo****servo→errorType()servo.get_errorType()**

Returns the numerical error code of the latest error with the servo.

| | |
|--------|--|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType(): YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the servo object

servo→get_friendlyName() YServo
servo→friendlyName()servo.get_friendlyName()

Returns a global identifier of the servo in the format MODULE_NAME . FUNCTION_NAME.

| | |
|---------|-------------------------------------|
| js | function get_friendlyName() |
| node.js | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | - (NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the servo if they are defined, otherwise the serial number of the module and the hardware identifier of the servo (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the servo using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

servo→get_functionDescriptor()
servo→functionDescriptor()
servo.get_functionDescriptor()

YServo

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

**servo→get_functionId()
servo→functionId()servo.get_functionId()****YServo**

Returns the hardware identifier of the servo, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the servo (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

servo→get_hardwareId()**YServo****servo→hardwareId()servo.get_hardwareId()**

Returns the unique hardware identifier of the servo in the form SERIAL.FUNCTIONID.

| | |
|--------|---|
| js | function get_hardwareId() |
| nodejs | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the servo. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the servo (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

servo→get_logicalName()**servo→logicalName()servo.get_logicalName()****YServo**

Returns the logical name of the servo.

| | |
|---------|--|
| js | function get_logicalName() |
| node.js | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | - (NSString*) logicalName |
| pas | function get_logicalName(): string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YServo target get_logicalName |

Returns :

a string corresponding to the logical name of the servo. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

servo→get_module()**YServo****servo→module()servo.get_module()**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

servo→get_module_async()
servo→module_async()**YServo**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

servo→get_neutral()
servo→neutral()servo.get_neutral()**YServo**

Returns the duration in microseconds of a neutral pulse for the servo.

| | |
|--------|---|
| js | function get_neutral() |
| nodejs | function get_neutral() |
| php | function get_neutral() |
| cpp | int get_neutral() |
| m | -(int) neutral |
| pas | function get_neutral() : LongInt |
| vb | function get_neutral() As Integer |
| cs | int get_neutral() |
| java | int get_neutral() |
| py | def get_neutral() |
| cmd | YServo target get_neutral |

Returns :

an integer corresponding to the duration in microseconds of a neutral pulse for the servo

On failure, throws an exception or returns **Y_NEUTRAL_INVALID**.

**servo→get_position()
servo→position()servo.get_position()****YServo**

Returns the current servo position.

| | |
|---------|--|
| js | function get_position() |
| node.js | function get_position() |
| php | function get_position() |
| cpp | int get_position() |
| m | -(int) position |
| pas | function get_position(): LongInt |
| vb | function get_position() As Integer |
| cs | int get_position() |
| java | int get_position() |
| py | def get_position() |
| cmd | YServo target get_position |

Returns :

an integer corresponding to the current servo position

On failure, throws an exception or returns Y_POSITION_INVALID.

servo→get_positionAtPowerOn()
servo→positionAtPowerOn()
servo.get_positionAtPowerOn()

YServo

Returns the servo position at device power up.

```
js    function get_positionAtPowerOn( )  
node.js function get_positionAtPowerOn( )  
php   function get_positionAtPowerOn( )  
cpp   int get_positionAtPowerOn( )  
m     -(int) positionAtPowerOn  
pas   function get_positionAtPowerOn( ): LongInt  
vb    function get_positionAtPowerOn( ) As Integer  
cs    int get_positionAtPowerOn( )  
java  int get_positionAtPowerOn( )  
py    def get_positionAtPowerOn( )  
cmd   YServo target get_positionAtPowerOn
```

Returns :

an integer corresponding to the servo position at device power up

On failure, throws an exception or returns Y_POSITIONATPOWERON_INVALID.

servo→get_range()**servo→range()servo.get_range()****YServo**

Returns the current range of use of the servo.

| | |
|---------|---|
| js | function get_range() |
| node.js | function get_range() |
| php | function get_range() |
| cpp | int get_range() |
| m | -(int) range |
| pas | function get_range() : LongInt |
| vb | function get_range() As Integer |
| cs | int get_range() |
| java | int get_range() |
| py | def get_range() |
| cmd | YServo target get_range |

Returns :

an integer corresponding to the current range of use of the servo

On failure, throws an exception or returns Y_RANGE_INVALID.

servo→get(userData)
servo→userData()servo.get(userData)**YServo**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|---|
| js | <code>function get(userData) </code> |
| nodejs | <code>function get(userData) </code> |
| php | <code>function get(userData) </code> |
| cpp | <code>void * get(userData) </code> |
| m | <code>-(void*) userData</code> |
| pas | <code>function get(userData): Tobject</code> |
| vb | <code>function get(userData) As Object</code> |
| cs | <code>object get(userData) </code> |
| java | <code>Object get(userData) </code> |
| py | <code>def get(userData) </code> |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

servo→isOnline()servo.isOnline()**YServo**

Checks if the servo is currently reachable, without raising any error.

| | |
|--------|---------------------------------------|
| js | function isOnline() |
| nodejs | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the servo in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the servo.

Returns :

true if the servo can be reached, and false otherwise

servo→isOnline_async()

YServo

Checks if the servo is currently reachable, without raising any error (asynchronous version).

```
js   function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the servo in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

servo→load()servo.load()**YServo**

Preloads the servo cache with a specified validity duration.

| | |
|--------|--|
| js | function load(msValidity) |
| nodejs | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | - (YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

servo→load_async()

YServo

Preloads the servo cache with a specified validity duration (asynchronous version).

```
js   function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

servo→move()servo.move()**YServo**

Performs a smooth move at constant speed toward a given position.

```
js function move( target, ms_duration)
nodejs function move( target, ms_duration)
php function move( $target, $ms_duration)
cpp int move( int target, int ms_duration)
m -(int) move : (int) target : (int) ms_duration
pas function move( target: LongInt, ms_duration: LongInt): integer
vb function move( ByVal target As Integer,
                  ByVal ms_duration As Integer) As Integer
cs int move( int target, int ms_duration)
java int move( int target, int ms_duration)
py def move( target, ms_duration)
cmd YServo target move target ms_duration
```

Parameters :

target new position at the end of the move

ms_duration total duration of the move, in milliseconds

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

servo→nextServo()servo.nextServo()**YServo**

Continues the enumeration of servos started using `yFirstServo()`.

| | |
|--------|---------------------------------------|
| js | function nextServo() |
| nodejs | function nextServo() |
| php | function nextServo() |
| cpp | YServo * nextServo() |
| m | -(YServo*) nextServo |
| pas | function nextServo() : TYServo |
| vb | function nextServo() As YServo |
| cs | YServo nextServo() |
| java | YServo nextServo() |
| py | def nextServo() |

Returns :

a pointer to a `YServo` object, corresponding to a servo currently online, or a `null` pointer if there are no more servos to enumerate.

**servo→registerValueCallback()
servo.registerValueCallback()****YServo**

Registers the callback function that is invoked on every change of advertised value.

| | |
|---------|--|
| js | function registerValueCallback(callback) |
| node.js | function registerValueCallback(callback) |
| php | function registerValueCallback(\$callback) |
| cpp | int registerValueCallback(YServoValueCallback callback) |
| m | -(int) registerValueCallback : (YServoValueCallback) callback |
| pas | function registerValueCallback(callback : TYServoValueCallback): LongInt |
| vb | function registerValueCallback() As Integer |
| cs | int registerValueCallback(ValueCallback callback) |
| java | int registerValueCallback(UpdateCallback callback) |
| py | def registerValueCallback(callback) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

servo→set_enabled()
servo→setEnabled()servo.set_enabled()**YServo**

Stops or starts the servo.

| | |
|--------|--|
| js | function set_enabled(newval) |
| nodejs | function set_enabled(newval) |
| php | function set_enabled(\$newval) |
| cpp | int set_enabled(Y_ENABLED_enum newval) |
| m | -(int) setEnabled : (Y_ENABLED_enum) newval |
| pas | function set_enabled(newval: Integer): integer |
| vb | function set_enabled(ByVal newval As Integer) As Integer |
| cs | int set_enabled(int newval) |
| java | int set_enabled(int newval) |
| py | def set_enabled(newval) |
| cmd | YServo target set_enabled newval |

Parameters :

newval either Y_ENABLED_FALSE or Y_ENABLED_TRUE

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

servo→set_enabledAtPowerOn()
servo→setEnabledAtPowerOn()
servo.set_enabledAtPowerOn()

YServo

Configure the servo signal generator state at power up.

```
js function set_enabledAtPowerOn( newval)
nodejs function set_enabledAtPowerOn( newval)
php function set_enabledAtPowerOn( $newval)
cpp int set_enabledAtPowerOn( Y_ENABLEDATPOWERON_enum newval)
m -(int) setEnabledAtPowerOn : (Y_ENABLEDATPOWERON_enum) newval
pas function set_enabledAtPowerOn( newval: Integer): integer
vb function set_enabledAtPowerOn( ByVal newval As Integer) As Integer
cs int set_enabledAtPowerOn( int newval)
java int set_enabledAtPowerOn( int newval)
py def set_enabledAtPowerOn( newval)
cmd YServo target set_enabledAtPowerOn newval
```

Remember to call the matching module `saveToFlash()` method, otherwise this call will have no effect.

Parameters :

newval either `Y_ENABLEDATPOWERON_FALSE` or `Y_ENABLEDATPOWERON_TRUE`

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

servo→set_logicalName()**YServo****servo→setLogicalName()servo.set_logicalName()**

Changes the logical name of the servo.

| | |
|---------------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YServo target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the servo.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

**servo→set_neutral()
servo→setNeutral()servo.set_neutral()****YServo**

Changes the duration of the pulse corresponding to the neutral position of the servo.

| | |
|---------|--|
| js | function set_neutral(newval) |
| node.js | function set_neutral(newval) |
| php | function set_neutral(\$newval) |
| cpp | int set_neutral(int newval) |
| m | -(int) setNeutral : (int) newval |
| pas | function set_neutral(newval: LongInt): integer |
| vb | function set_neutral(ByVal newval As Integer) As Integer |
| cs | int set_neutral(int newval) |
| java | int set_neutral(int newval) |
| py | def set_neutral(newval) |
| cmd | YServo target set_neutral newval |

The duration is specified in microseconds, and the standard value is 1500 [us]. This setting makes it possible to shift the range of use of the servo. Be aware that using a range higher than what is supported by the servo is likely to damage the servo.

Parameters :

newval an integer corresponding to the duration of the pulse corresponding to the neutral position of the servo

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

servo→set_position()

YServo

servo→setPosition()servo.set_position()

Changes immediately the servo driving position.

| | |
|--------|---|
| js | function set_position(newval) |
| nodejs | function set_position(newval) |
| php | function set_position(\$newval) |
| cpp | int set_position(int newval) |
| m | -(int) setPosition : (int) newval |
| pas | function set_position(newval: LongInt): integer |
| vb | function set_position(ByVal newval As Integer) As Integer |
| cs | int set_position(int newval) |
| java | int set_position(int newval) |
| py | def set_position(newval) |
| cmd | YServo target set_position newval |

Parameters :

newval an integer corresponding to immediately the servo driving position

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

servo→set_positionAtPowerOn()
servo→setPositionAtPowerOn()
servo.set_positionAtPowerOn()

YServo

Configure the servo position at device power up.

```
js function set_positionAtPowerOn( newval)
nodejs function set_positionAtPowerOn( newval)
php function set_positionAtPowerOn( $newval)
cpp int set_positionAtPowerOn( int newval)
m -(int) setPositionAtPowerOn : (int) newval
pas function set_positionAtPowerOn( newval: LongInt): integer
vb function set_positionAtPowerOn( ByVal newval As Integer) As Integer
cs int set_positionAtPowerOn( int newval)
java int set_positionAtPowerOn( int newval)
py def set_positionAtPowerOn( newval)
cmd YServo target set_positionAtPowerOn newval
```

Remember to call the matching module `saveToFlash()` method, otherwise this call will have no effect.

Parameters :

newval an integer

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

servo→set_range()

servo→setRange()servo.set_range()

YServo

Changes the range of use of the servo, specified in per cents.

| | |
|--------|--|
| js | function set_range(newval) |
| nodejs | function set_range(newval) |
| php | function set_range(\$newval) |
| cpp | int set_range(int newval) |
| m | -(int) setRange : (int) newval |
| pas | function set_range(newval: LongInt): integer |
| vb | function set_range(ByVal newval As Integer) As Integer |
| cs | int set_range(int newval) |
| java | int set_range(int newval) |
| py | def set_range(newval) |
| cmd | YServo target set_range newval |

A range of 100% corresponds to a standard control signal, that varies from 1 [ms] to 2 [ms]. When using a servo that supports a double range, from 0.5 [ms] to 2.5 [ms], you can select a range of 200%. Be aware that using a range higher than what is supported by the servo is likely to damage the servo.

Parameters :

newval an integer corresponding to the range of use of the servo, specified in per cents

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

servo→set(userData())
servo→setUserData()servo.set(userData())**YServo**

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|---|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData \$data) |
| cpp | void set(userData void* data) |
| m | -(void) setUserData : (void*) data |
| pas | procedure set(userData data: Tobject) |
| vb | procedure set(userData ByVal data As Object) |
| cs | void set(userData object data) |
| java | void set(userData Object data) |
| py | def set(userData data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

servo→wait_async()**YServo**

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.38. Temperature function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_temperature.js'></script>
nodejs var yoctolib = require('yoctolib');
var YTemperature = yoctolib.YTemperature;
php require_once('yocto_temperature.php');
cpp #include "yocto_temperature.h"
m #import "yocto_temperature.h"
pas uses yocto_temperature;
vb yocto_temperature.vb
cs yocto_temperature.cs
java import com.yoctopuce.YoctoAPI.YTemperature;
py from yocto_temperature import *

```

Global functions

yFindTemperature(func)

Retrieves a temperature sensor for a given identifier.

yFirstTemperature()

Starts the enumeration of temperature sensors currently accessible.

YTemperature methods

temperature→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

temperature→describe()

Returns a short text that describes unambiguously the instance of the temperature sensor in the form TYPE (NAME) = SERIAL . FUNCTIONID.

temperature→get_advertisedValue()

Returns the current value of the temperature sensor (no more than 6 characters).

temperature→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor.

temperature→get_currentValue()

Returns the current value of the temperature.

temperature→get_errorMessage()

Returns the error message of the latest error with the temperature sensor.

temperature→get_errorType()

Returns the numerical error code of the latest error with the temperature sensor.

temperature→get_friendlyName()

Returns a global identifier of the temperature sensor in the format MODULE_NAME . FUNCTION_NAME.

temperature→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

temperature→get_functionId()

Returns the hardware identifier of the temperature sensor, without reference to the module.

temperature→get_hardwareId()

Returns the unique hardware identifier of the temperature sensor in the form SERIAL . FUNCTIONID.

temperature→get_highestValue()

Returns the maximal value observed for the temperature since the device was started.

temperature→get_logFrequency()

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

temperature→get_logicalName()

Returns the logical name of the temperature sensor.

temperature→get_lowestValue()

Returns the minimal value observed for the temperature since the device was started.

temperature→get_module()

Gets the YModule object for the device on which the function is located.

temperature→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

temperature→get_recordedData(startTime, endTime)

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

temperature→get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

temperature→get_resolution()

Returns the resolution of the measured values.

temperature→get_sensorType()

Returns the temperature sensor type.

temperature→get_unit()

Returns the measuring unit for the temperature.

temperature→get(userData)

Returns the value of the userData attribute, as previously stored using method set(userData).

temperature→isOnline()

Checks if the temperature sensor is currently reachable, without raising any error.

temperature→isOnline_async(callback, context)

Checks if the temperature sensor is currently reachable, without raising any error (asynchronous version).

temperature→load(msValidity)

Preloads the temperature sensor cache with a specified validity duration.

temperature→loadCalibrationPoints(rawValues, refValues)

Retrieves error correction data points previously entered using the method calibrateFromPoints.

temperature→load_async(msValidity, callback, context)

Preloads the temperature sensor cache with a specified validity duration (asynchronous version).

temperature→nextTemperature()

Continues the enumeration of temperature sensors started using yFirstTemperature().

temperature→registerTimedReportCallback(callback)

Registers the callback function that is invoked on every periodic timed notification.

temperature→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

temperature→set_highestValue(newval)

Changes the recorded maximal value observed.

temperature→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

3. Reference

temperature→set_logicalName(newval)

Changes the logical name of the temperature sensor.

temperature→set_lowestValue(newval)

Changes the recorded minimal value observed.

temperature→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

temperature→set_resolution(newval)

Changes the resolution of the measured physical values.

temperature→set_sensorType(newval)

Modify the temperature sensor type.

temperature→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

temperature→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YTemperature.FindTemperature()**YTemperature****yFindTemperature()YTemperature.FindTemperature()**

Retrieves a temperature sensor for a given identifier.

| | |
|----------------------|---|
| <code>js</code> | <code>function yFindTemperature(func)</code> |
| <code>node.js</code> | <code>function FindTemperature(func)</code> |
| <code>php</code> | <code>function yFindTemperature(\$func)</code> |
| <code>cpp</code> | <code>YTemperature* yFindTemperature(const string& func)</code> |
| <code>m</code> | <code>YTemperature* yFindTemperature(NSString* func)</code> |
| <code>pas</code> | <code>function yFindTemperature(func: string): TYTemperature</code> |
| <code>vb</code> | <code>function yFindTemperature(ByVal func As String) As YTemperature</code> |
| <code>cs</code> | <code>YTemperature FindTemperature(string func)</code> |
| <code>java</code> | <code>YTemperature FindTemperature(String func)</code> |
| <code>py</code> | <code>def FindTemperature(func)</code> |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the temperature sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YTemperature.isOnline()` to test if the temperature sensor is indeed online at a given time. In case of ambiguity when looking for a temperature sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the temperature sensor

Returns :

a `YTemperature` object allowing you to drive the temperature sensor.

YTemperature.FirstTemperature()**YTemperature****yFirstTemperature()YTemperature.FirstTemperature()**

Starts the enumeration of temperature sensors currently accessible.

| | |
|---------|--|
| js | function yFirstTemperature() |
| node.js | function FirstTemperature() |
| php | function yFirstTemperature() |
| cpp | YTemperature* yFirstTemperature() |
| m | YTemperature* yFirstTemperature() |
| pas | function yFirstTemperature(): TYTemperature |
| vb | function yFirstTemperature() As YTemperature |
| cs | YTemperature FirstTemperature() |
| java | YTemperature FirstTemperature() |
| py | def FirstTemperature() |

Use the method `YTemperature.nextTemperature()` to iterate on next temperature sensors.

Returns :

a pointer to a `YTemperature` object, corresponding to the first temperature sensor currently online, or a null pointer if there are none.

temperature→calibrateFromPoints() temperature.calibrateFromPoints()

YTemperature

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```

js   function calibrateFromPoints( rawValues, refValues)
node.js function calibrateFromPoints( rawValues, refValues)
php  function calibrateFromPoints( $rawValues, $refValues)
cpp   int calibrateFromPoints( vector<double> rawValues,
                             vector<double> refValues)

m    -(int) calibrateFromPoints : (NSMutableArray*) rawValues
                  : (NSMutableArray*) refValues

pas  function calibrateFromPoints( rawValues: TDoubleArray,
                                 refValues: TDoubleArray): LongInt

vb   procedure calibrateFromPoints( )

cs   int calibrateFromPoints( List<double> rawValues,
                           List<double> refValues)

java int calibrateFromPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def calibrateFromPoints( rawValues, refValues)

cmd  YTemperature target calibrateFromPoints rawValues refValues

```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.
refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→describe()temperature.describe()**YTemperature**

Returns a short text that describes unambiguously the instance of the temperature sensor in the form TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|---------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | - (NSString*) describe |
| pas | function describe(): string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the temperature sensor (ex:
Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

| | |
|--|---------------------|
| temperature→get_advertisedValue() | YTemperature |
| temperature→advertisedValue() | |
| temperature.get_advertisedValue() | |

Returns the current value of the temperature sensor (no more than 6 characters).

```
js    function get_advertisedValue( )  
node.js function get_advertisedValue( )  
php   function get_advertisedValue( )  
cpp   string get_advertisedValue( )  
m     -(NSString*) advertisedValue  
pas   function get_advertisedValue( ): string  
vb    function get_advertisedValue( ) As String  
cs    string get_advertisedValue( )  
java  String get_advertisedValue( )  
py    def get_advertisedValue( )  
cmd   YTemperature target get_advertisedValue
```

Returns :

a string corresponding to the current value of the temperature sensor (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

temperature→get_currentRawValue()
temperature→currentRawValue()
temperature.get_currentRawValue()

YTemperature

Returns the uncalibrated, unrounded raw value returned by the sensor.

```
js function get_currentRawValue( )
nodejs function get_currentRawValue( )
php function get_currentRawValue( )
cpp double get_currentRawValue( )
m -(double) currentRawValue
pas function get_currentRawValue( ): double
vb function get_currentRawValue( ) As Double
cs double get_currentRawValue( )
java double get_currentRawValue( )
py def get_currentRawValue( )
cmd YTemperature target get_currentRawValue
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

temperature→get_currentValue()
temperature→currentValue()
temperature.get_currentValue()

YTemperature

Returns the current value of the temperature.

| | |
|---------|---|
| js | function get_currentValue() |
| node.js | function get_currentValue() |
| php | function get_currentValue() |
| cpp | double get_currentValue() |
| m | -(double) currentValue |
| pas | function get_currentValue() : double |
| vb | function get_currentValue() As Double |
| cs | double get_currentValue() |
| java | double get_currentValue() |
| py | def get_currentValue() |
| cmd | YTemperature target get_currentValue |

Returns :

a floating point number corresponding to the current value of the temperature

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

temperature→getErrorMessage()
temperature→errorMessage()
temperature.getErrorMessage()

YTemperature

Returns the error message of the latest error with the temperature sensor.

```
js function getErrorMessage( )  
nodejs function getErrorMessage( )  
php function getErrorMessage( )  
cpp string getErrorMessage( )  
m -(NSString*) errorMessage  
pas function getErrorMessage( ): string  
vb function getErrorMessage( ) As String  
cs string getErrorMessage( )  
java String getErrorMessage( )  
py def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the temperature sensor object

**temperature→get_errorType()
temperature→errorType()
temperature.get_errorType()****YTemperature**

Returns the numerical error code of the latest error with the temperature sensor.

| | |
|---------|---------------------------------------|
| js | function get_errorType() |
| node.js | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType(): YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the temperature sensor object

temperature→get_friendlyName()
temperature→friendlyName()
temperature.get_friendlyName()

YTemperature

Returns a global identifier of the temperature sensor in the format MODULE_NAME . FUNCTION_NAME.

```
js function get_friendlyName( )  
nodejs function get_friendlyName( )  
php function get_friendlyName( )  
cpp string get_friendlyName( )  
m -(NSString*) friendlyName  
cs string get_friendlyName( )  
java String get_friendlyName( )  
py def get_friendlyName( )
```

The returned string uses the logical names of the module and of the temperature sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the temperature sensor (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the temperature sensor using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

temperature→get_functionDescriptor()
temperature→functionDescriptor()
temperature.get_functionDescriptor()

YTemperature

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

temperature→get_functionId()
temperature→functionId()
temperature.get_functionId()

YTemperature

Returns the hardware identifier of the temperature sensor, without reference to the module.

| | |
|--------|---|
| js | function get_functionId() |
| nodejs | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the temperature sensor (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

temperature→get_hardwareId()
temperature→hardwareId()
temperature.get_hardwareId()**YTemperature**

Returns the unique hardware identifier of the temperature sensor in the form SERIAL.FUNCTIONID.

| | |
|---------|---|
| js | function get_hardwareId() |
| node.js | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the temperature sensor. (for example RELAY01-123456.relay1)

Returns :

a string that uniquely identifies the temperature sensor (ex: RELAY01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

temperature→get_highestValue()
temperature→highestValue()
temperature.get_highestValue()

YTemperature

Returns the maximal value observed for the temperature since the device was started.

```
js function get_highestValue( )  
nodejs function get_highestValue( )  
php function get_highestValue( )  
cpp double get_highestValue( )  
m -(double) highestValue  
pas function get_highestValue( ): double  
vb function get_highestValue( ) As Double  
cs double get_highestValue( )  
java double get_highestValue( )  
py def get_highestValue( )  
cmd YTemperature target get_highestValue
```

Returns :

a floating point number corresponding to the maximal value observed for the temperature since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

temperature→get_logFrequency()
temperature→logFrequency()
temperature.get_logFrequency()

YTemperature

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
js   function get_logFrequency( )  
nodejs function get_logFrequency( )  
php  function get_logFrequency( )  
cpp   string get_logFrequency( )  
m    -(NSString*) logFrequency  
pas   function get_logFrequency( ): string  
vb    function get_logFrequency( ) As String  
cs   string get_logFrequency( )  
java  String get_logFrequency( )  
py    def get_logFrequency()  
cmd   YTemperature target get_logFrequency
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns `Y_LOGFREQUENCY_INVALID`.

temperature→get_logicalName()
temperature→logicalName()
temperature.get_logicalName()

YTemperature

Returns the logical name of the temperature sensor.

| | |
|--------|---------------------------------------|
| js | function get_logicalName() |
| nodejs | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | -(NSString*) logicalName |
| pas | function get_logicalName(): string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YTemperature target get_logicalName |

Returns :

a string corresponding to the logical name of the temperature sensor. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

temperature→get_lowestValue()
temperature→lowestValue()
temperature.get_lowestValue()

YTemperature

Returns the minimal value observed for the temperature since the device was started.

| | |
|---------|--|
| js | function get_lowestValue() |
| node.js | function get_lowestValue() |
| php | function get_lowestValue() |
| cpp | double get_lowestValue() |
| m | -(double) lowestValue |
| pas | function get_lowestValue(): double |
| vb | function get_lowestValue() As Double |
| cs | double get_lowestValue() |
| java | double get_lowestValue() |
| py | def get_lowestValue() |
| cmd | YTemperature target get_lowestValue |

Returns :

a floating point number corresponding to the minimal value observed for the temperature since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

temperature→get_module() **YTemperature**
temperature→module()temperature.get_module()

Gets the `YModule` object for the device on which the function is located.

| | |
|----------------------|--|
| <code>js</code> | <code>function get_module()</code> |
| <code>node.js</code> | <code>function get_module()</code> |
| <code>php</code> | <code>function get_module()</code> |
| <code>cpp</code> | <code>YModule * get_module()</code> |
| <code>m</code> | <code>-(YModule*) module</code> |
| <code>pas</code> | <code>function get_module(): TYModule</code> |
| <code>vb</code> | <code>function get_module() As YModule</code> |
| <code>cs</code> | <code>YModule get_module()</code> |
| <code>java</code> | <code>YModule get_module()</code> |
| <code>py</code> | <code>def get_module()</code> |

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

temperature→get_module_async()
temperature→module_async()**YTemperature**

Gets the YModule object for the device on which the function is located (asynchronous version).

```
js   function get_module_async( callback, context )
nodejs function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned YModule object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested YModule object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

`temperature→get_recordedData()`
`temperature→recordedData()`
`temperature.get_recordedData()`

YTemperature

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the `DataSet` class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measurement, without ending limit.

Returns :

an instance of `YDataSet`, providing access to historical data. Past measures can be loaded progressively using methods from the `YDataSet` object.

temperature→get_reportFrequency()
temperature→reportFrequency()
temperature.get_reportFrequency()

YTemperature

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
js   function get_reportFrequency( )  
nodejs function get_reportFrequency( )  
php  function get_reportFrequency( )  
cpp   string get_reportFrequency( )  
m    -(NSString*) reportFrequency  
pas   function get_reportFrequency( ): string  
vb    function get_reportFrequency( ) As String  
cs    string get_reportFrequency( )  
java  String get_reportFrequency( )  
py    def get_reportFrequency( )  
cmd   YTemperature target get_reportFrequency
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns `Y_REPORTFREQUENCY_INVALID`.

temperature→get_resolution()
temperature→resolution()
temperature.get_resolution()

YTemperature

Returns the resolution of the measured values.

```
js function get_resolution( )
nodejs function get_resolution( )
php function get_resolution( )
cpp double get_resolution( )
m -(double) resolution
pas function get_resolution( ): double
vb function get_resolution( ) As Double
cs double get_resolution( )
java double get_resolution( )
py def get_resolution( )
cmd YTemperature target get_resolution
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

temperature→get_sensorType()
temperature→sensorType()
temperature.get_sensorType()

YTemperature

Returns the temperature sensor type.

| | |
|--------|--|
| js | function get_sensorType() |
| nodejs | function get_sensorType() |
| php | function get_sensorType() |
| cpp | Y_SENSORTYPE_enum get_sensorType() |
| m | -(Y_SENSORTYPE_enum) sensorType |
| pas | function get_sensorType() : Integer |
| vb | function get_sensorType() As Integer |
| cs | int get_sensorType() |
| java | int get_sensorType() |
| py | def get_sensorType() |
| cmd | YTemperature target get_sensorType |

Returns :

a value among Y_SENSORTYPE_DIGITAL, Y_SENSORTYPE_TYPE_K, Y_SENSORTYPE_TYPE_E, Y_SENSORTYPE_TYPE_J, Y_SENSORTYPE_TYPE_N, Y_SENSORTYPE_TYPE_R, Y_SENSORTYPE_TYPE_S, Y_SENSORTYPE_TYPE_T, Y_SENSORTYPE_PT100_4WIRES, Y_SENSORTYPE_PT100_3WIRES and Y_SENSORTYPE_PT100_2WIRES corresponding to the temperature sensor type

On failure, throws an exception or returns Y_SENSORTYPE_INVALID.

temperature→get_unit()
temperature→unit()temperature.get_unit()**YTemperature**

Returns the measuring unit for the temperature.

| | |
|---------|---------------------------------------|
| js | function get_unit() |
| node.js | function get_unit() |
| php | function get_unit() |
| cpp | string get_unit() |
| m | -(NSString*) unit |
| pas | function get_unit() : string |
| vb | function get_unit() As String |
| cs | string get_unit() |
| java | String get_unit() |
| py | def get_unit() |
| cmd | YTemperature target get_unit |

Returns :

a string corresponding to the measuring unit for the temperature

On failure, throws an exception or returns Y_UNIT_INVALID.

temperature→get(userData)**YTemperature****temperature→userData()temperature.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|---|
| js | <code>function get(userData) </code> |
| nodejs | <code>function get(userData) </code> |
| php | <code>function get(userData) </code> |
| cpp | <code>void * get(userData) </code> |
| m | <code>-(void*) userData</code> |
| pas | <code>function get(userData): Tobject</code> |
| vb | <code>function get(userData) As Object</code> |
| cs | <code>object get(userData) </code> |
| java | <code>Object get(userData) </code> |
| py | <code>def get(userData) </code> |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

temperature→isOnline()temperature.isOnline()**YTemperature**

Checks if the temperature sensor is currently reachable, without raising any error.

| | |
|--------|--|
| js | function isOnline() |
| nodejs | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the temperature sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the temperature sensor.

Returns :

true if the temperature sensor can be reached, and false otherwise

temperature→isOnline_async()**YTemperature**

Checks if the temperature sensor is currently reachable, without raising any error (asynchronous version).

```
js   function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the temperature sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

temperature→load()temperature.load()**YTemperature**

Preloads the temperature sensor cache with a specified validity duration.

| | |
|--------|--|
| js | function load(msValidity) |
| nodejs | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | -(YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

temperature→loadCalibrationPoints() temperature.loadCalibrationPoints()

YTemperature

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```

js   function loadCalibrationPoints( rawValues, refValues)
node.js function loadCalibrationPoints( rawValues, refValues)
php  function loadCalibrationPoints( &$rawValues, &$refValues)
cpp   int loadCalibrationPoints( vector<double>& rawValues,
                                vector<double>& refValues)

m    -(int) loadCalibrationPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues

pas  function loadCalibrationPoints( var rawValues: TDoubleArray,
                           var refValues: TDoubleArray): LongInt

vb   procedure loadCalibrationPoints( )
cs   int loadCalibrationPoints( List<double> rawValues,
                           List<double> refValues)

java int loadCalibrationPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def loadCalibrationPoints( rawValues, refValues)
cmd  YTemperature target loadCalibrationPoints rawValues refValues

```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→load_async()**YTemperature**

Preloads the temperature sensor cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

temperature→nextTemperature()
temperature.nextTemperature()**YTemperature**Continues the enumeration of temperature sensors started using `yFirstTemperature()`.

| | |
|---------------------|--|
| <code>js</code> | <code>function nextTemperature()</code> |
| <code>nodejs</code> | <code>function nextTemperature()</code> |
| <code>php</code> | <code>function nextTemperature()</code> |
| <code>cpp</code> | <code>YTemperature * nextTemperature()</code> |
| <code>m</code> | <code>-(YTemperature*) nextTemperature</code> |
| <code>pas</code> | <code>function nextTemperature(): TYTemperature</code> |
| <code>vb</code> | <code>function nextTemperature() As YTemperature</code> |
| <code>cs</code> | <code>YTemperature nextTemperature()</code> |
| <code>java</code> | <code>YTemperature nextTemperature()</code> |
| <code>py</code> | <code>def nextTemperature()</code> |

Returns :

a pointer to a `YTemperature` object, corresponding to a temperature sensor currently online, or a null pointer if there are no more temperature sensors to enumerate.

**temperature→registerTimedReportCallback()
temperature.registerTimedReportCallback()****YTemperature**

Registers the callback function that is invoked on every periodic timed notification.

```
js   function registerTimedReportCallback( callback )
node.js function registerTimedReportCallback( callback )
php  function registerTimedReportCallback( $callback )
cpp   int registerTimedReportCallback( YTemperatureTimedReportCallback callback )
m     -(int) registerTimedReportCallback : (YTemperatureTimedReportCallback) callback
pas   function registerTimedReportCallback( callback: TYTemperatureTimedReportCallback): LongInt
vb    function registerTimedReportCallback( ) As Integer
cs    int registerTimedReportCallback( TimedReportCallback callback )
java  int registerTimedReportCallback( TimedReportCallback callback )
py    def registerTimedReportCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

temperature→registerValueCallback() temperature.registerValueCallback()

YTemperature

Registers the callback function that is invoked on every change of advertised value.

| | |
|---------|--|
| js | function registerValueCallback(callback) |
| node.js | function registerValueCallback(callback) |
| php | function registerValueCallback(\$callback) |
| cpp | int registerValueCallback(YTemperatureValueCallback callback) |
| m | -(int) registerValueCallback : (YTemperatureValueCallback) callback |
| pas | function registerValueCallback(callback : TYTemperatureValueCallback): LongInt |
| vb | function registerValueCallback() As Integer |
| cs | int registerValueCallback(ValueCallback callback) |
| java | int registerValueCallback(UpdateCallback callback) |
| py | def registerValueCallback(callback) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

temperature→set_highestValue()
temperature→setHighestValue()
temperature.set_highestValue()

YTemperature

Changes the recorded maximal value observed.

```
js function set_highestValue( newval)
nodejs function set_highestValue( newval)
php function set_highestValue( $newval)
cpp int set_highestValue( double newval)
m -(int) setHighestValue : (double) newval
pas function set_highestValue( newval: double): integer
vb function set_highestValue( ByVal newval As Double) As Integer
cs int set_highestValue( double newval)
java int set_highestValue( double newval)
py def set_highestValue( newval)
cmd YTemperature target set_highestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→set_logFrequency()
temperature→setLogFrequency()
temperature.set_logFrequency()

YTemperature

Changes the datalogger recording frequency for this function.

| | |
|---------|--|
| js | function set_logFrequency(newval) |
| node.js | function set_logFrequency(newval) |
| php | function set_logFrequency(\$newval) |
| cpp | int set_logFrequency(const string& newval) |
| m | -(int) setLogFrequency : (NSString*) newval |
| pas | function set_logFrequency(newval: string): integer |
| vb | function set_logFrequency(ByVal newval As String) As Integer |
| cs | int set_logFrequency(string newval) |
| java | int set_logFrequency(String newval) |
| py | def set_logFrequency(newval) |
| cmd | YTemperature target set_logFrequency newval |

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→set_logicalName()
temperature→setLogicalName()
temperature.set_logicalName()

YTemperature

Changes the logical name of the temperature sensor.

```
js function set_logicalName( newval)
nodejs function set_logicalName( newval)
php function set_logicalName( $newval)
cpp int set_logicalName( const string& newval)
m -(int) setLogicalName : (NSString*) newval
pas function set_logicalName( newval: string): integer
vb function set_logicalName( ByVal newval As String) As Integer
cs int set_logicalName( string newval)
java int set_logicalName( String newval)
py def set_logicalName( newval)
cmd YTemperature target set_logicalName newval
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the temperature sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

temperature→set_lowestValue()
temperature→setLowestValue()
temperature.set_lowestValue()

YTemperature

Changes the recorded minimal value observed.

```
js function set_lowestValue( newval)
nodejs function set_lowestValue( newval)
php function set_lowestValue( $newval)
cpp int set_lowestValue( double newval)
m -(int) setLowestValue : (double) newval
pas function set_lowestValue( newval: double): integer
vb function set_lowestValue( ByVal newval As Double) As Integer
cs int set_lowestValue( double newval)
java int set_lowestValue( double newval)
py def set_lowestValue( newval)
cmd YTemperature target set_lowestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→set_reportFrequency()
temperature→setReportFrequency()
temperature.set_reportFrequency()

YTemperature

Changes the timed value notification frequency for this function.

```
js   function set_reportFrequency( newval)
nodejs function set_reportFrequency( newval)
php  function set_reportFrequency( $newval)
cpp   int set_reportFrequency( const string& newval)
m    -(int) setReportFrequency : (NSString*) newval
pas   function set_reportFrequency( newval: string): integer
vb    function set_reportFrequency( ByVal newval As String) As Integer
cs    int set_reportFrequency( string newval)
java  int set_reportFrequency( String newval)
py    def set_reportFrequency( newval)
cmd   YTemperature target set_reportFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→set_resolution()
temperature→setResolution()
temperature.set_resolution()

YTemperature

Changes the resolution of the measured physical values.

| | |
|---------|--|
| js | function set_resolution(newval) |
| node.js | function set_resolution(newval) |
| php | function set_resolution(\$newval) |
| cpp | int set_resolution(double newval) |
| m | -(int) setResolution : (double) newval |
| pas | function set_resolution(newval: double): integer |
| vb | function set_resolution(ByVal newval As Double) As Integer |
| cs | int set_resolution(double newval) |
| java | int set_resolution(double newval) |
| py | def set_resolution(newval) |
| cmd | YTemperature target set_resolution newval |

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→set_sensorType()
temperature→setSensorType()
temperature.set_sensorType()

YTemperature

Modify the temperature sensor type.

```

js function set_sensorType( newval)
nodejs function set_sensorType( newval)
php function set_sensorType( $newval)
cpp int set_sensorType( Y_SENSORTYPE_enum newval)
m -(int) setSensorType : (Y_SENSORTYPE_enum) newval
pas function set_sensorType( newval: Integer): integer
vb function set_sensorType( ByVal newval As Integer) As Integer
cs int set_sensorType( int newval)
java int set_sensorType( int newval)
py def set_sensorType( newval)
cmd YTemperature target set_sensorType newval

```

This function is used to define the type of thermocouple (K,E...) used with the device. This will have no effect if module is using a digital sensor. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a value among `Y_SENSORTYPE_DIGITAL`, `Y_SENSORTYPE_TYPE_K`,
`Y_SENSORTYPE_TYPE_E`, `Y_SENSORTYPE_TYPE_J`, `Y_SENSORTYPE_TYPE_N`,
`Y_SENSORTYPE_TYPE_R`, `Y_SENSORTYPE_TYPE_S`, `Y_SENSORTYPE_TYPE_T`,
`Y_SENSORTYPE_PT100_4WIRES`, `Y_SENSORTYPE_PT100_3WIRES` and
`Y_SENSORTYPE_PT100_2WIRES`

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→set(userData)
temperature→setUserData()
temperature.set(userData)

YTemperature

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|---|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData \$data) |
| cpp | void set(userData void* data) |
| m | -(void) setUserData : (void*) data |
| pas | procedure set(userData data: Tobject) |
| vb | procedure set(userData ByVal data As Object) |
| cs | void set(userData object data) |
| java | void set(userData Object data) |
| py | def set(userData data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

temperature→wait_async()**YTemperature**

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.39. Tilt function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

| | |
|--------|--|
| js | <script type='text/javascript' src='yocto_tilt.js'></script> |
| nodejs | var yoctolib = require('yoctolib'); |
| | var YTilt = yoctolib.YTilt; |
| php | require_once('yocto_tilt.php'); |
| cpp | #include "yocto_tilt.h" |
| m | #import "yocto_tilt.h" |
| pas | uses yocto_tilt; |
| vb | yocto_tilt.vb |
| cs | yocto_tilt.cs |
| java | import com.yoctopuce.YoctoAPI.YTilt; |
| py | from yocto_tilt import * |

Global functions

yFindTilt(func)

Retrieves a tilt sensor for a given identifier.

yFirstTilt()

Starts the enumeration of tilt sensors currently accessible.

YTilt methods

tilt→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

tilt→describe()

Returns a short text that describes unambiguously the instance of the tilt sensor in the form TYPE (NAME)=SERIAL . FUNCTIONID.

tilt→get_advertisedValue()

Returns the current value of the tilt sensor (no more than 6 characters).

tilt→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor.

tilt→get_currentValue()

Returns the current value of the inclination.

tilt→get_errorMessage()

Returns the error message of the latest error with the tilt sensor.

tilt→get_errorType()

Returns the numerical error code of the latest error with the tilt sensor.

tilt→get_friendlyName()

Returns a global identifier of the tilt sensor in the format MODULE_NAME . FUNCTION_NAME.

tilt→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

tilt→get_functionId()

Returns the hardware identifier of the tilt sensor, without reference to the module.

tilt→get_hardwareId()

Returns the unique hardware identifier of the tilt sensor in the form SERIAL . FUNCTIONID.

| | |
|---|--|
| tilt→get_highestValue() | Returns the maximal value observed for the inclination since the device was started. |
| tilt→get_logFrequency() | Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory. |
| tilt→get_logicalName() | Returns the logical name of the tilt sensor. |
| tilt→get_lowestValue() | Returns the minimal value observed for the inclination since the device was started. |
| tilt→get_module() | Gets the YModule object for the device on which the function is located. |
| tilt→get_module_async(callback, context) | Gets the YModule object for the device on which the function is located (asynchronous version). |
| tilt→get_recordedData(startTime, endTime) | Retrieves a DataSet object holding historical data for this sensor, for a specified time interval. |
| tilt→get_reportFrequency() | Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function. |
| tilt→get_resolution() | Returns the resolution of the measured values. |
| tilt→get_unit() | Returns the measuring unit for the inclination. |
| tilt→get(userData) | Returns the value of the userData attribute, as previously stored using method set(userData). |
| tilt→isOnline() | Checks if the tilt sensor is currently reachable, without raising any error. |
| tilt→isOnline_async(callback, context) | Checks if the tilt sensor is currently reachable, without raising any error (asynchronous version). |
| tilt→load(msValidity) | Preloads the tilt sensor cache with a specified validity duration. |
| tilt→loadCalibrationPoints(rawValues, refValues) | Retrieves error correction data points previously entered using the method calibrateFromPoints. |
| tilt→load_async(msValidity, callback, context) | Preloads the tilt sensor cache with a specified validity duration (asynchronous version). |
| tilt→nextTilt() | Continues the enumeration of tilt sensors started using yFirstTilt(). |
| tilt→registerTimedReportCallback(callback) | Registers the callback function that is invoked on every periodic timed notification. |
| tilt→registerValueCallback(callback) | Registers the callback function that is invoked on every change of advertised value. |
| tilt→set_highestValue(newval) | Changes the recorded maximal value observed. |
| tilt→set_logFrequency(newval) | Changes the datalogger recording frequency for this function. |
| tilt→set_logicalName(newval) | Changes the logical name of the tilt sensor. |

tilt→set_lowestValue(newval)

Changes the recorded minimal value observed.

tilt→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

tilt→set_resolution(newval)

Changes the resolution of the measured physical values.

tilt→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

tilt→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YTilt.FindTilt() yFindTilt()YTilt.FindTilt()

YTilt

Retrieves a tilt sensor for a given identifier.

```
js function yFindTilt( func)
node.js function FindTilt( func)
php function yFindTilt( $func)
cpp YTilt* yFindTilt( const string& func)
m YTilt* yFindTilt( NSString* func)
pas function yFindTilt( func: string): TYTilt
vb function yFindTilt( ByVal func As String) As YTilt
cs YTilt FindTilt( string func)
java YTilt FindTilt( String func)
def FindTilt( func)
py
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the tilt sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YTilt.isOnline()` to test if the tilt sensor is indeed online at a given time. In case of ambiguity when looking for a tilt sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the tilt sensor

Returns :

a `YTilt` object allowing you to drive the tilt sensor.

YTilt.FirstTilt()

YTilt

yFirstTilt()YTilt.FirstTilt()

Starts the enumeration of tilt sensors currently accessible.

```
js function yFirstTilt( )  
nodejs function FirstTilt( )  
php function yFirstTilt( )  
cpp YTilt* yFirstTilt( )  
m YTilt* yFirstTilt( )  
pas function yFirstTilt( ): TYTilt  
vb function yFirstTilt( ) As YTilt  
cs YTilt FirstTilt( )  
java YTilt FirstTilt( )  
py def FirstTilt( )
```

Use the method `YTilt.nextTilt()` to iterate on next tilt sensors.

Returns :

a pointer to a `YTilt` object, corresponding to the first tilt sensor currently online, or a `null` pointer if there are none.

tilt→calibrateFromPoints()tilt.calibrateFromPoints()

YTilt

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```

js   function calibrateFromPoints( rawValues, refValues)
nodejs function calibrateFromPoints( rawValues, refValues)
php  function calibrateFromPoints( $rawValues, $refValues)
cpp   int calibrateFromPoints( vector<double> rawValues,
                           vector<double> refValues)

m   -(int) calibrateFromPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues

pas  function calibrateFromPoints( rawValues: TDoubleArray,
                           refValues: TDoubleArray): LongInt

vb   procedure calibrateFromPoints( )

cs   int calibrateFromPoints( List<double> rawValues,
                           List<double> refValues)

java int calibrateFromPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def calibrateFromPoints( rawValues, refValues)
cmd  YTilt target calibrateFromPoints rawValues refValues

```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

tilt→describe()tilt.describe()**YTilt**

Returns a short text that describes unambiguously the instance of the tilt sensor in the form TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the tilt sensor (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

tilt→get_advertisedValue() YTilt
tilt→advertisedValue()tilt.get_advertisedValue()

Returns the current value of the tilt sensor (no more than 6 characters).

```
js function get_advertisedValue( )  
node.js function get_advertisedValue( )  
php function get_advertisedValue( )  
cpp string get_advertisedValue( )  
m -(NSString*) advertisedValue  
pas function get_advertisedValue( ): string  
vb function get_advertisedValue( ) As String  
cs string get_advertisedValue( )  
java String get_advertisedValue( )  
py def get_advertisedValue( )  
cmd YTilt target get_advertisedValue
```

Returns :

a string corresponding to the current value of the tilt sensor (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

tilt→get_currentRawValue()

YTilt

tilt→currentRawValue()tilt.get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor.

```
js function get_currentRawValue( )
nodejs function get_currentRawValue( )
php function get_currentRawValue( )
cpp double get_currentRawValue( )
m -(double) currentRawValue
pas function get_currentRawValue( ): double
vb function get_currentRawValue( ) As Double
cs double get_currentRawValue( )
java double get_currentRawValue( )
py def get_currentRawValue( )
cmd YTilt target get_currentRawValue
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

tilt→get_currentValue()
tilt→currentValue()tilt.get_currentValue()

YTilt

Returns the current value of the inclination.

```
js function get_currentValue( )
node.js function get_currentValue( )
php function get_currentValue( )
cpp double get_currentValue( )
m -(double) currentValue
pas function get_currentValue( ): double
vb function get_currentValue( ) As Double
cs double get_currentValue( )
java double get_currentValue( )
py def get_currentValue( )
cmd YTilt target get_currentValue
```

Returns :

a floating point number corresponding to the current value of the inclination

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

tilt→get_errorMessage()

YTilt

tilt→errorMessage()tilt.get_errorMessage()

Returns the error message of the latest error with the tilt sensor.

```
js   function get_errorMessage( )  
nodejs function get_errorMessage( )  
php  function get_errorMessage( )  
cpp   string get_errorMessage( )  
m    -(NSString*) errorMessage  
pas   function get_errorMessage( ): string  
vb    function get_errorMessage( ) As String  
cs    string get_errorMessage( )  
java  String get_errorMessage( )  
py    def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the tilt sensor object

tilt→get_errorType() tilt→errorType()tilt.get_errorType()

YTilt

Returns the numerical error code of the latest error with the tilt sensor.

```
js function get_errorType( )  
node.js function get_errorType( )  
php function get_errorType( )  
cpp YRETCODE get_errorType( )  
pas function get_errorType( ): YRETCODE  
vb function get_errorType( ) As YRETCODE  
cs YRETCODE get_errorType( )  
java int get_errorType( )  
py def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the tilt sensor object

tilt→get_friendlyName()

YTilt

tilt→friendlyName()tilt.get_friendlyName()

Returns a global identifier of the tilt sensor in the format MODULE_NAME . FUNCTION_NAME.

```
js function get_friendlyName( )  
nodejs function get_friendlyName( )  
php function get_friendlyName( )  
cpp string get_friendlyName( )  
m -(NSString*) friendlyName  
cs string get_friendlyName( )  
java String get_friendlyName( )  
py def get_friendlyName( )
```

The returned string uses the logical names of the module and of the tilt sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the tilt sensor (for exemple: MyCustomName . relay1)

Returns :

a string that uniquely identifies the tilt sensor using logical names (ex: MyCustomName . relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

tilt→get_functionDescriptor() tilt→functionDescriptor()tilt.get_functionDescriptor()

YTilt

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
js   function get_functionDescriptor( )
node.js function get_functionDescriptor( )
php  function get_functionDescriptor( )
cpp   YFUN_DESCR get_functionDescriptor( )
m    -(YFUN_DESCR) functionDescriptor
pas   function get_functionDescriptor( ): YFUN_DESCR
vb    function get_functionDescriptor( ) As YFUN_DESCR
cs    YFUN_DESCR get_functionDescriptor( )
java  String get_functionDescriptor( )
py    def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

tilt→get_functionId() tilt→functionId()tilt.get_functionId()

YTilt

Returns the hardware identifier of the tilt sensor, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the tilt sensor (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

tilt→get_hardwareId()
tilt→hardwareId() tilt.get_hardwareId()

YTilt

Returns the unique hardware identifier of the tilt sensor in the form SERIAL.FUNCTIONID.

| | |
|---------|---|
| js | function get_hardwareId() |
| node.js | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the tilt sensor. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the tilt sensor (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

tilt→get_highestValue()

YTilt

tilt→highestValue()tilt.get_highestValue()

Returns the maximal value observed for the inclination since the device was started.

```
js   function get_highestValue( )  
nodejs function get_highestValue( )  
php  function get_highestValue( )  
cpp   double get_highestValue( )  
m    -(double) highestValue  
pas   function get_highestValue( ): double  
vb    function get_highestValue( ) As Double  
cs    double get_highestValue( )  
java  double get_highestValue( )  
py    def get_highestValue( )  
cmd   YTilt target get_highestValue
```

Returns :

a floating point number corresponding to the maximal value observed for the inclination since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

tilt→get_logFrequency() YTilt
tilt→logFrequency()tilt.get_logFrequency()

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
js  function get_logFrequency( )  
nodejs function get_logFrequency( )  
php  function get_logFrequency( )  
cpp   string get_logFrequency( )  
m    -(NSString*) logFrequency  
pas   function get_logFrequency( ):string  
vb    function get_logFrequency( ) As String  
cs    string get_logFrequency( )  
java  String get_logFrequency( )  
py    def get_logFrequency( )  
cmd   YTilt target get_logFrequency
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

tilt→get_logicalName() tilt→logicalName()tilt.get_logicalName()

YTilt

Returns the logical name of the tilt sensor.

```
js function get_logicalName( )
nodejs function get_logicalName( )
php function get_logicalName( )
cpp string get_logicalName( )
m -(NSString*) logicalName
pas function get_logicalName( ): string
vb function get_logicalName( ) As String
cs string get_logicalName( )
java String get_logicalName( )
py def get_logicalName( )
cmd YTilt target get_logicalName
```

Returns :

a string corresponding to the logical name of the tilt sensor. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

tilt→get_lowestValue() tilt→lowestValue()tilt.get_lowestValue()

YTilt

Returns the minimal value observed for the inclination since the device was started.

```
js function get_lowestValue( )  
node.js function get_lowestValue( )  
php function get_lowestValue( )  
cpp double get_lowestValue( )  
m -(double) lowestValue  
pas function get_lowestValue( ): double  
vb function get_lowestValue( ) As Double  
cs double get_lowestValue( )  
java double get_lowestValue( )  
py def get_lowestValue( )  
cmd YTilt target get_lowestValue
```

Returns :

a floating point number corresponding to the minimal value observed for the inclination since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

tilt→get_module()

YTilt

tilt→module()tilt.get_module()

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

tilt→get_module_async() tilt→module_async()

YTilt

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

tilt→get_recordedData()

YTilt

tilt→recordedData(tilt.get_recordedData())

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```

js   function get_recordedData( startTime, endTime)
nodejs function get_recordedData( startTime, endTime)
php  function get_recordedData( $startTime, $endTime)
cpp   YDataSet get_recordedData( s64 startTime, s64 endTime)
m     -(YDataSet*) recordedData : (s64) startTime
                  : (s64) endTime

pas   function get_recordedData( startTime: int64, endTime: int64): TYDataSet
vb    function get_recordedData( ) As YDataSet
cs    YDataSet get_recordedData( long startTime, long endTime)
java   YDataSet get_recordedData( long startTime, long endTime)
py    def get_recordedData( startTime, endTime)
cmd   YTilt target get_recordedData startTime endTime

```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

tilt→get_reportFrequency() tilt→reportFrequency()tilt.get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
js  function get_reportFrequency( )  
nodejs function get_reportFrequency( )  
php  function get_reportFrequency( )  
cpp   string get_reportFrequency( )  
m    -(NSString*) reportFrequency  
pas   function get_reportFrequency( ): string  
vb    function get_reportFrequency( ) As String  
cs    string get_reportFrequency( )  
java  String get_reportFrequency( )  
py    def get_reportFrequency( )  
cmd   YTilt target get_reportFrequency
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

tilt→get_resolution()

YTilt

tilt→resolution()tilt.get_resolution()

Returns the resolution of the measured values.

| | |
|--------|---|
| js | function get_resolution() |
| nodejs | function get_resolution() |
| php | function get_resolution() |
| cpp | double get_resolution() |
| m | -(double) resolution |
| pas | function get_resolution(): double |
| vb | function get_resolution() As Double |
| cs | double get_resolution() |
| java | double get_resolution() |
| py | def get_resolution() |
| cmd | YTilt target get_resolution |

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

**tilt→get_unit()
tilt→unit()tilt.get_unit()****YTilt**

Returns the measuring unit for the inclination.

| | |
|---------|---------------------------------------|
| js | function get_unit() |
| node.js | function get_unit() |
| php | function get_unit() |
| cpp | string get_unit() |
| m | -(NSString*) unit |
| pas | function get_unit() : string |
| vb | function get_unit() As String |
| cs | string get_unit() |
| java | String get_unit() |
| py | def get_unit() |
| cmd | YTilt target get_unit |

Returns :

a string corresponding to the measuring unit for the inclination

On failure, throws an exception or returns Y_UNIT_INVALID.

tilt→get(userData)

YTilt

tilt→userData()tilt.get(userData)

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|---|
| js | <code>function get(userData) </code> |
| nodejs | <code>function get(userData) </code> |
| php | <code>function get(userData) </code> |
| cpp | <code>void * get(userData) </code> |
| m | <code>-(void*) userData</code> |
| pas | <code>function get(userData): Tobject</code> |
| vb | <code>function get(userData) As Object</code> |
| cs | <code>object get(userData) </code> |
| java | <code>Object get(userData) </code> |
| py | <code>def get(userData) </code> |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

tilt→isOnline()tilt.isOnline()

YTilt

Checks if the tilt sensor is currently reachable, without raising any error.

```
js function isOnline( )  
nodejs function isOnline( )  
php function isOnline( )  
cpp bool isOnline( )  
m -(BOOL) isOnline  
pas function isOnline( ): boolean  
vb function isOnline( ) As Boolean  
cs bool isOnline( )  
java boolean isOnline( )  
py def isOnline( )
```

If there is a cached value for the tilt sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the tilt sensor.

Returns :

true if the tilt sensor can be reached, and false otherwise

tilt→isOnline_async()

YTilt

Checks if the tilt sensor is currently reachable, without raising any error (asynchronous version).

```
js   function isOnline_async( callback, context )
nodejs function isOnline_async( callback, context )
```

If there is a cached value for the tilt sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

tilt→load()tilt.load()

YTilt

Preloads the tilt sensor cache with a specified validity duration.

| | |
|--------|--|
| js | function load(msValidity) |
| nodejs | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | - (YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

tilt→loadCalibrationPoints() tilt.loadCalibrationPoints()

YTilt

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```

js   function loadCalibrationPoints( rawValues, refValues)
nodejs function loadCalibrationPoints( rawValues, refValues)
php  function loadCalibrationPoints( &$rawValues, &$refValues)
cpp   int loadCalibrationPoints( vector<double>& rawValues,
                                vector<double>& refValues)

m    -(int) loadCalibrationPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues

pas  function loadCalibrationPoints( var rawValues: TDoubleArray,
                           var refValues: TDoubleArray): LongInt

vb   procedure loadCalibrationPoints( )
cs   int loadCalibrationPoints( List<double> rawValues,
                           List<double> refValues)

java int loadCalibrationPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def loadCalibrationPoints( rawValues, refValues)
cmd  YTilt target loadCalibrationPoints rawValues refValues

```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

tilt→load_async()

YTilt

Preloads the tilt sensor cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

tilt→nextTilt()tilt.nextTilt()**YTilt**

Continues the enumeration of tilt sensors started using `yFirstTilt()`.

| | |
|--------|--|
| js | <code>function nextTilt()</code> |
| nodejs | <code>function nextTilt()</code> |
| php | <code>function nextTilt()</code> |
| cpp | <code>YTilt * nextTilt()</code> |
| m | <code>-(YTilt*) nextTilt</code> |
| pas | <code>function nextTilt(): TYTilt</code> |
| vb | <code>function nextTilt() As YTilt</code> |
| cs | <code>YTilt nextTilt()</code> |
| java | <code>YTilt nextTilt()</code> |
| py | <code>def nextTilt()</code> |

Returns :

a pointer to a `YTilt` object, corresponding to a tilt sensor currently online, or a `null` pointer if there are no more tilt sensors to enumerate.

tilt→registerTimedReportCallback() tilt.registerTimedReportCallback()

YTilt

Registers the callback function that is invoked on every periodic timed notification.

```
js   function registerTimedReportCallback( callback )
node.js function registerTimedReportCallback( callback )
php  function registerTimedReportCallback( $callback )
cpp   int registerTimedReportCallback( YTiltTimedReportCallback callback )
m     -(int) registerTimedReportCallback : (YTiltTimedReportCallback) callback
pas   function registerTimedReportCallback( callback: YTiltTimedReportCallback): LongInt
vb    function registerTimedReportCallback( ) As Integer
cs    int registerTimedReportCallback( TimedReportCallback callback )
java  int registerTimedReportCallback( TimedReportCallback callback )
py    def registerTimedReportCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

tilt→registerValueCallback() tilt.registerValueCallback()

YTilt

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback)
nodejs function registerValueCallback( callback)
php  function registerValueCallback( $callback)
cpp   int registerValueCallback( YTiltValueCallback callback)
m    -(int) registerValueCallback : (YTiltValueCallback) callback
pas   function registerValueCallback( callback: TYTiltValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs   int registerValueCallback( ValueCallback callback)
java  int registerValueCallback( UpdateCallback callback)
py    def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

**tilt→set_highestValue()
tilt→setHighestValue()tilt.set_highestValue()**

YTilt

Changes the recorded maximal value observed.

```
js function set_highestValue( newval)
node.js function set_highestValue( newval)
php function set_highestValue( $newval)
cpp int set_highestValue( double newval)
m -(int) setHighestValue : (double) newval
pas function set_highestValue( newval: double): integer
vb function set_highestValue( ByVal newval As Double) As Integer
cs int set_highestValue( double newval)
java int set_highestValue( double newval)
py def set_highestValue( newval)
cmd YTilt target set_highestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

tilt→set_logFrequency() tilt→setLogFrequency()tilt.set_logFrequency()

YTilt

Changes the datalogger recording frequency for this function.

```
js   function set_logFrequency( newval)
nodejs function set_logFrequency( newval)
php  function set_logFrequency( $newval)
cpp   int set_logFrequency( const string& newval)
m    -(int) setLogFrequency : (NSString*) newval
pas   function set_logFrequency( newval: string): integer
vb    function set_logFrequency( ByVal newval As String) As Integer
cs    int set_logFrequency( string newval)
java  int set_logFrequency( String newval)
py    def set_logFrequency( newval)
cmd   YTilt target set_logFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

tilt→set_logicalName() YTilt**tilt→setLogicalName()**
tilt.set_logicalName()

Changes the logical name of the tilt sensor.

```
js function set_logicalName( newval)
node.js function set_logicalName( newval)
php function set_logicalName( $newval)
cpp int set_logicalName( const string& newval)
m -(int) setLogicalName : (NSString*) newval
pas function set_logicalName( newval: string): integer
vb function set_logicalName( ByVal newval As String) As Integer
cs int set_logicalName( string newval)
java int set_logicalName( String newval)
py def set_logicalName( newval)
cmd YTilt target set_logicalName newval
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the tilt sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

tilt→set_lowestValue()

YTilt

tilt→setLowestValue()tilt.set_lowestValue()

Changes the recorded minimal value observed.

```
js function set_lowestValue( newval)
nodejs function set_lowestValue( newval)
php function set_lowestValue( $newval)
cpp int set_lowestValue( double newval)
m -(int) setLowestValue : (double) newval
pas function set_lowestValue( newval: double): integer
vb function set_lowestValue( ByVal newval As Double) As Integer
cs int set_lowestValue( double newval)
java int set_lowestValue( double newval)
py def set_lowestValue( newval)
cmd YTilt target set_lowestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

tilt→set_reportFrequency() tilt→setReportFrequency()tilt.set_reportFrequency()

YTilt

Changes the timed value notification frequency for this function.

```
js   function set_reportFrequency( newval)
node.js function set_reportFrequency( newval)
php  function set_reportFrequency( $newval)
cpp   int set_reportFrequency( const string& newval)
m    -(int) setReportFrequency : (NSString*) newval
pas   function set_reportFrequency( newval: string): integer
vb    function set_reportFrequency( ByVal newval As String) As Integer
cs    int set_reportFrequency( string newval)
java  int set_reportFrequency( String newval)
py    def set_reportFrequency( newval)
cmd   YTilt target set_reportFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

tilt→set_resolution() tilt→setResolution()tilt.set_resolution()

YTilt

Changes the resolution of the measured physical values.

```
js function set_resolution( newval)
nodejs function set_resolution( newval)
php function set_resolution( $newval)
cpp int set_resolution( double newval)
m -(int) setResolution : (double) newval
pas function set_resolution( newval: double): integer
vb function set_resolution( ByVal newval As Double) As Integer
cs int set_resolution( double newval)
java int set_resolution( double newval)
py def set_resolution( newval)
cmd YTilt target set_resolution newval
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

tilt→set(userData)
tilt→setUserData()tilt.set(userData)

YTilt

Stores a user context provided as argument in the userData attribute of the function.

```
js   function set(userData) data
node.js function set(userData) data
php  function set(userData) $data
cpp   void set(userData void* data)
m    -(void) setUserData : (void*) data
pas   procedure set(userData data: Tobject)
vb    procedure set(userData ByVal data As Object)
cs    void set(userData object data)
java  void set(userData Object data)
py    def set(userData data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

tilt→wait_async()

YTilt

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context )
nodejs function wait_async( callback, context )
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.40. Voc function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

| | |
|--------|---|
| js | <script type='text/javascript' src='yocto_voc.js'></script> |
| nodejs | var yoctolib = require('yoctolib'); |
| | var YVoc = yoctolib.YVoc; |
| php | require_once('yocto_voc.php'); |
| cpp | #include "yocto_voc.h" |
| m | #import "yocto_voc.h" |
| pas | uses yocto_voc; |
| vb | yocto_voc.vb |
| cs | yocto_voc.cs |
| java | import com.yoctopuce.YoctoAPI.YVoc; |
| py | from yocto_voc import * |

Global functions

yFindVoc(func)

Retrieves a Volatile Organic Compound sensor for a given identifier.

yFirstVoc()

Starts the enumeration of Volatile Organic Compound sensors currently accessible.

YVoc methods

voc→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

voc→describe()

Returns a short text that describes unambiguously the instance of the Volatile Organic Compound sensor in the form TYPE (NAME) = SERIAL . FUNCTIONID.

voc→get_advertisedValue()

Returns the current value of the Volatile Organic Compound sensor (no more than 6 characters).

voc→get_currentRawValue()

Returns the unrounded and uncalibrated raw value returned by the sensor.

voc→get_currentValue()

Returns the current measure for the estimated VOC concentration.

voc→get_errorMessage()

Returns the error message of the latest error with the Volatile Organic Compound sensor.

voc→get_errorType()

Returns the numerical error code of the latest error with the Volatile Organic Compound sensor.

voc→get_friendlyName()

Returns a global identifier of the Volatile Organic Compound sensor in the format MODULE_NAME . FUNCTION_NAME.

voc→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

voc→get_functionId()

Returns the hardware identifier of the Volatile Organic Compound sensor, without reference to the module.

voc→get_hardwareId()

Returns the unique hardware identifier of the Volatile Organic Compound sensor in the form SERIAL.FUNCTIONID.

voc→get_highestValue()

Returns the maximal value observed for the estimated VOC concentration.

voc→get_logFrequency()

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

voc→get_logicalName()

Returns the logical name of the Volatile Organic Compound sensor.

voc→get_lowestValue()

Returns the minimal value observed for the estimated VOC concentration.

voc→get_module()

Gets the YModule object for the device on which the function is located.

voc→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

voc→get_recordedData(startTime, endTime)

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

voc→get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

voc→get_resolution()

Returns the resolution of the measured values.

voc→get_unit()

Returns the measuring unit for the estimated VOC concentration.

voc→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

voc→isOnline()

Checks if the Volatile Organic Compound sensor is currently reachable, without raising any error.

voc→isOnline_async(callback, context)

Checks if the Volatile Organic Compound sensor is currently reachable, without raising any error (asynchronous version).

voc→load(msValidity)

Preloads the Volatile Organic Compound sensor cache with a specified validity duration.

voc→loadCalibrationPoints(rawValues, refValues)

Retrieves error correction data points previously entered using the method calibrateFromPoints.

voc→load_async(msValidity, callback, context)

Preloads the Volatile Organic Compound sensor cache with a specified validity duration (asynchronous version).

voc→nextVoc()

Continues the enumeration of Volatile Organic Compound sensors started using yFirstVoc().

voc→registerTimedReportCallback(callback)

Registers the callback function that is invoked on every periodic timed notification.

voc→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

voc→set_highestValue(newval)

Changes the recorded maximal value observed for the estimated VOC concentration.

3. Reference

voc→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

voc→set_logicalName(newval)

Changes the logical name of the Volatile Organic Compound sensor.

voc→set_lowestValue(newval)

Changes the recorded minimal value observed for the estimated VOC concentration.

voc→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

voc→set_resolution(newval)

Changes the resolution of the measured physical values.

voc→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

voc→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YVoc.FindVoc() yFindVoc()YVoc.FindVoc()

YVoc

Retrieves a Volatile Organic Compound sensor for a given identifier.

| | |
|---------|---|
| js | function yFindVoc(func) |
| node.js | function FindVoc(func) |
| php | function yFindVoc(\$func) |
| cpp | YVoc* yFindVoc(const string& func) |
| m | YVoc* yFindVoc(NSString* func) |
| pas | function yFindVoc(func: string): TYVoc |
| vb | function yFindVoc(ByVal func As String) As YVoc |
| cs | YVoc FindVoc(string func) |
| java | YVoc FindVoc(String func) |
| py | def FindVoc(func) |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the Volatile Organic Compound sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YVoc.isOnline()` to test if the Volatile Organic Compound sensor is indeed online at a given time. In case of ambiguity when looking for a Volatile Organic Compound sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the Volatile Organic Compound sensor

Returns :

a YVoc object allowing you to drive the Volatile Organic Compound sensor.

YVoc.FirstVoc() yFirstVoc()YVoc.FirstVoc()

YVoc

Starts the enumeration of Volatile Organic Compound sensors currently accessible.

| | |
|---------|--------------------------------------|
| js | function yFirstVoc() |
| node.js | function FirstVoc() |
| php | function yFirstVoc() |
| cpp | YVoc* yFirstVoc() |
| m | YVoc* yFirstVoc() |
| pas | function yFirstVoc() : TYVoc |
| vb | function yFirstVoc() As YVoc |
| cs | YVoc FirstVoc() |
| java | YVoc FirstVoc() |
| py | def FirstVoc() |

Use the method `YVoc.nextVoc()` to iterate on next Volatile Organic Compound sensors.

Returns :

a pointer to a `YVoc` object, corresponding to the first Volatile Organic Compound sensor currently online, or a null pointer if there are none.

voc→calibrateFromPoints()|voc.calibrateFromPoints()

YVoc

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```

js function calibrateFromPoints( rawValues, refValues)
nodejs function calibrateFromPoints( rawValues, refValues)
php function calibrateFromPoints( $rawValues, $refValues)
cpp int calibrateFromPoints( vector<double> rawValues,
                           vector<double> refValues)
m -(int) calibrateFromPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues
pas function calibrateFromPoints( rawValues: TDoubleArray,
                                   refValues: TDoubleArray): LongInt
vb procedure calibrateFromPoints( )
cs int calibrateFromPoints( List<double> rawValues,
                           List<double> refValues)
java int calibrateFromPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)
py def calibrateFromPoints( rawValues, refValues)
cmd YVoc target calibrateFromPoints rawValues refValues

```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

voc→describe()voc.describe()**YVoc**

Returns a short text that describes unambiguously the instance of the Volatile Organic Compound sensor in the form TYPE (NAME)=SERIAL . FUNCTIONID.

| | |
|--------|---------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | - (NSString*) describe |
| pas | function describe(): string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the Volatile Organic Compound sensor (ex:
Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

voc→get_advertisedValue()**YVoc****voc→advertisedValue()voc.get_advertisedValue()**

Returns the current value of the Volatile Organic Compound sensor (no more than 6 characters).

| | |
|--------|--|
| js | function get_advertisedValue() |
| nodejs | function get_advertisedValue() |
| php | function get_advertisedValue() |
| cpp | string get_advertisedValue() |
| m | -(NSString*) advertisedValue |
| pas | function get_advertisedValue() : string |
| vb | function get_advertisedValue() As String |
| cs | string get_advertisedValue() |
| java | String get_advertisedValue() |
| py | def get_advertisedValue() |
| cmd | YVoc target get_advertisedValue |

Returns :

a string corresponding to the current value of the Volatile Organic Compound sensor (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

voc→get_currentRawValue()
voc→currentRawValue()voc.get_currentRawValue()**YVoc**

Returns the unrounded and uncalibrated raw value returned by the sensor.

```
js function get_currentRawValue( )
node.js function get_currentRawValue( )
php function get_currentRawValue( )
cpp double get_currentRawValue( )
m -(double) currentRawValue
pas function get_currentRawValue( ): double
vb function get_currentRawValue( ) As Double
cs double get_currentRawValue( )
java double get_currentRawValue( )
py def get_currentRawValue( )
cmd YVoc target get_currentRawValue
```

Returns :

a floating point number corresponding to the unrounded and uncalibrated raw value returned by the sensor

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

voc→get_currentValue()**YVoc****voc→currentValue()voc.get_currentValue()**

Returns the current measure for the estimated VOC concentration.

| | |
|---------|---|
| js | function get_currentValue() |
| node.js | function get_currentValue() |
| php | function get_currentValue() |
| cpp | double get_currentValue() |
| m | -(double) currentValue |
| pas | function get_currentValue(): double |
| vb | function get_currentValue() As Double |
| cs | double get_currentValue() |
| java | double get_currentValue() |
| py | def get_currentValue() |
| cmd | YVoc target get_currentValue |

Returns :

a floating point number corresponding to the current measure for the estimated VOC concentration

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

voc→get_errorMessage()
voc→errorMessage()voc.get_errorMessage()**YVoc**

Returns the error message of the latest error with the Volatile Organic Compound sensor.

| | |
|---------|---|
| js | function get_errorMessage() |
| node.js | function get_errorMessage() |
| php | function get_errorMessage() |
| cpp | string get_errorMessage() |
| m | - (NSString*) errorMessage |
| pas | function get_errorMessage(): string |
| vb | function get_errorMessage() As String |
| cs | string get_errorMessage() |
| java | String get_errorMessage() |
| py | def get_errorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the Volatile Organic Compound sensor object

voc→get_errorType()**YVoc****voc→errorType()voc.get_errorType()**

Returns the numerical error code of the latest error with the Volatile Organic Compound sensor.

| | |
|--------|--|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType() : YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the Volatile Organic Compound sensor object

voc→get_friendlyName()**YVoc****voc→friendlyName()voc.get_friendlyName()**

Returns a global identifier of the Volatile Organic Compound sensor in the format MODULE_NAME.FUNCTION_NAME.

```
js function get_friendlyName( )  
nodejs function get_friendlyName( )  
php function get_friendlyName( )  
cpp string get_friendlyName( )  
m -(NSString*) friendlyName  
cs string get_friendlyName( )  
java String get_friendlyName( )  
py def get_friendlyName( )
```

The returned string uses the logical names of the module and of the Volatile Organic Compound sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the Volatile Organic Compound sensor (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the Volatile Organic Compound sensor using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

voc→get_functionDescriptor()
voc→functionDescriptor()
voc.get_functionDescriptor()

YVoc

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

voc→get_functionId()
voc→functionId()voc.get_functionId()**YVoc**

Returns the hardware identifier of the Volatile Organic Compound sensor, without reference to the module.

| | |
|--------|---|
| js | function get_functionId() |
| nodejs | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the Volatile Organic Compound sensor (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

voc→get_hardwareId()**YVoc****voc→hardwareId()voc.get_hardwareId()**

Returns the unique hardware identifier of the Volatile Organic Compound sensor in the form SERIAL.FUNCTIONID.

| | |
|---------|--------------------------------------|
| js | function get_hardwareId() |
| node.js | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the Volatile Organic Compound sensor. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the Volatile Organic Compound sensor (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

voc→get_highestValue()**YVoc****voc→highestValue()voc.get_highestValue()**

Returns the maximal value observed for the estimated VOC concentration.

js function **get_highestValue()****node.js** function **get_highestValue()****php** function **get_highestValue()****cpp** double **get_highestValue()****m** -(double) highestValue**pas** function **get_highestValue(): double****vb** function **get_highestValue() As Double****cs** double **get_highestValue()****java** double **get_highestValue()****py** def **get_highestValue()****cmd** YVoc target **get_highestValue****Returns :**

a floating point number corresponding to the maximal value observed for the estimated VOC concentration

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

voc→get_logFrequency()**YVoc****voc→logFrequency()voc.get_logFrequency()**

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

| | |
|--------|--|
| js | function get_logFrequency() |
| nodejs | function get_logFrequency() |
| php | function get_logFrequency() |
| cpp | string get_logFrequency() |
| m | -(NSString*) logFrequency |
| pas | function get_logFrequency() : string |
| vb | function get_logFrequency() As String |
| cs | string get_logFrequency() |
| java | String get_logFrequency() |
| py | def get_logFrequency() |
| cmd | YVoc target get_logFrequency |

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

voc→get_logicalName()
voc→logicalName()voc.get_logicalName()**YVoc**

Returns the logical name of the Volatile Organic Compound sensor.

| | |
|---------|--|
| js | function get_logicalName() |
| node.js | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | -(NSString*) logicalName |
| pas | function get_logicalName(): string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YVoc target get_logicalName |

Returns :

a string corresponding to the logical name of the Volatile Organic Compound sensor. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

voc→get_lowestValue()**YVoc****voc→lowestValue()voc.get_lowestValue()**

Returns the minimal value observed for the estimated VOC concentration.

| | |
|--------|--|
| js | function get_lowestValue() |
| nodejs | function get_lowestValue() |
| php | function get_lowestValue() |
| cpp | double get_lowestValue() |
| m | -(double) lowestValue |
| pas | function get_lowestValue(): double |
| vb | function get_lowestValue() As Double |
| cs | double get_lowestValue() |
| java | double get_lowestValue() |
| py | def get_lowestValue() |
| cmd | YVoc target get_lowestValue |

Returns :

a floating point number corresponding to the minimal value observed for the estimated VOC concentration

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

**voc→get_module()
voc→module()voc.get_module()****YVoc**

Gets the `YModule` object for the device on which the function is located.

| | |
|---------|--|
| js | <code>function get_module()</code> |
| node.js | <code>function get_module()</code> |
| php | <code>function get_module()</code> |
| cpp | <code>YModule * get_module()</code> |
| m | <code>-(YModule*) module</code> |
| pas | <code>function get_module(): TYModule</code> |
| vb | <code>function get_module() As YModule</code> |
| cs | <code>YModule get_module()</code> |
| java | <code>YModule get_module()</code> |
| py | <code>def get_module()</code> |

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

voc→get_module_async()**YVoc****voc→module_async()**

Gets the YModule object for the device on which the function is located (asynchronous version).

```
js   function get_module_async( callback, context )
nodejs function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned YModule object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested YModule object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

voc→get_recordedData()

YYoc

voc→recordedData()voc.get_recordedData()

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the `DataSet` class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measurement, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measurement, without ending limit.

Returns :

an instance of `YDataSet`, providing access to historical data. Past measures can be loaded progressively using methods from the `YDataSet` object.

voc→get_reportFrequency()**YVoc****voc→reportFrequency()voc.get_reportFrequency()**

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

| | |
|---------|--|
| js | function get_reportFrequency() |
| node.js | function get_reportFrequency() |
| php | function get_reportFrequency() |
| cpp | string get_reportFrequency() |
| m | -(NSString*) reportFrequency |
| pas | function get_reportFrequency(): string |
| vb | function get_reportFrequency() As String |
| cs | string get_reportFrequency() |
| java | String get_reportFrequency() |
| py | def get_reportFrequency() |
| cmd | YVoc target get_reportFrequency |

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

voc→get_resolution()
voc→resolution()voc.get_resolution()**YVoc**

Returns the resolution of the measured values.

| | |
|---------|---|
| js | function get_resolution() |
| node.js | function get_resolution() |
| php | function get_resolution() |
| cpp | double get_resolution() |
| m | -(double) resolution |
| pas | function get_resolution() : double |
| vb | function get_resolution() As Double |
| cs | double get_resolution() |
| java | double get_resolution() |
| py | def get_resolution() |
| cmd | YVoc target get_resolution |

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

voc→get_unit()**YVoc****voc→unit()voc.get_unit()**

Returns the measuring unit for the estimated VOC concentration.

| | |
|--------|---------------------------------------|
| js | function get_unit() |
| nodejs | function get_unit() |
| php | function get_unit() |
| cpp | string get_unit() |
| m | -(NSString*) unit |
| pas | function get_unit() : string |
| vb | function get_unit() As String |
| cs | string get_unit() |
| java | String get_unit() |
| py | def get_unit() |
| cmd | YVoc target get_unit |

Returns :

a string corresponding to the measuring unit for the estimated VOC concentration

On failure, throws an exception or returns Y_UNIT_INVALID.

voc→get(userData)
voc→userData()voc.get(userData)**YVoc**

Returns the value of the userData attribute, as previously stored using method set(userData).

```
js function get(userData) 
node.js function get(userData) 
php function get(userData) 
cpp void * get(userData) 
m -(void*) userData 
pas function get(userData): Tobject 
vb function get(userData) As Object 
cs object get(userData) 
java Object get(userData) 
py def get(userData)
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

voc→isOnline()voc.isOnline()**YVoc**

Checks if the Volatile Organic Compound sensor is currently reachable, without raising any error.

| | |
|---------|--|
| js | function isOnline() |
| node.js | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the Volatile Organic Compound sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the Volatile Organic Compound sensor.

Returns :

`true` if the Volatile Organic Compound sensor can be reached, and `false` otherwise

voc→isOnline_async()**YVoc**

Checks if the Volatile Organic Compound sensor is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the Volatile Organic Compound sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

voc→load()|voc.load()**YVoc**

Preloads the Volatile Organic Compound sensor cache with a specified validity duration.

| | |
|---------|--|
| js | function load(msValidity) |
| node.js | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | - (YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

voc→loadCalibrationPoints() voc.loadCalibrationPoints()

YVoc

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```

js   function loadCalibrationPoints( rawValues, refValues)
nodejs function loadCalibrationPoints( rawValues, refValues)
php   function loadCalibrationPoints( &$rawValues, &$refValues)
cpp   int loadCalibrationPoints( vector<double>& rawValues,
                               vector<double>& refValues)
m    -(int) loadCalibrationPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues
pas  function loadCalibrationPoints( var rawValues: TDoubleArray,
                           var refValues: TDoubleArray): LongInt
vb   procedure loadCalibrationPoints( )
cs   int loadCalibrationPoints( List<double> rawValues,
                           List<double> refValues)
java int loadCalibrationPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)
py   def loadCalibrationPoints( rawValues, refValues)
cmd  YVoc target loadCalibrationPoints rawValues refValues

```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voc→load_async()**YVoc**

Preloads the Volatile Organic Compound sensor cache with a specified validity duration (asynchronous version).

```
js   function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

voc→nextVoc()voc.nextVoc()**YVoc**

Continues the enumeration of Volatile Organic Compound sensors started using `yFirstVoc()`.

| | |
|--------|--|
| js | <code>function nextVoc()</code> |
| nodejs | <code>function nextVoc()</code> |
| php | <code>function nextVoc()</code> |
| cpp | <code>YVoc * nextVoc()</code> |
| m | <code>-(YVoc*) nextVoc</code> |
| pas | <code>function nextVoc(): TYVoc</code> |
| vb | <code>function nextVoc() As YVoc</code> |
| cs | <code>YVoc nextVoc()</code> |
| java | <code>YVoc nextVoc()</code> |
| py | <code>def nextVoc()</code> |

Returns :

a pointer to a `YVoc` object, corresponding to a Volatile Organic Compound sensor currently online, or a `null` pointer if there are no more Volatile Organic Compound sensors to enumerate.

voc→registerTimedReportCallback() voc.registerTimedReportCallback()

YVoc

Registers the callback function that is invoked on every periodic timed notification.

| | |
|---------|--|
| js | function registerTimedReportCallback(callback) |
| node.js | function registerTimedReportCallback(callback) |
| php | function registerTimedReportCallback(\$callback) |
| cpp | int registerTimedReportCallback(YVocTimedReportCallback callback) |
| m | -(int) registerTimedReportCallback : (YVocTimedReportCallback) callback |
| pas | function registerTimedReportCallback(callback : TYVocTimedReportCallback): LongInt |
| vb | function registerTimedReportCallback() As Integer |
| cs | int registerTimedReportCallback(TimedReportCallback callback) |
| java | int registerTimedReportCallback(TimedReportCallback callback) |
| py | def registerTimedReportCallback(callback) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

**voc→registerValueCallback()
voc.registerValueCallback()****YVoc**

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YVocValueCallback callback )
m    -(int) registerValueCallback : (YVocValueCallback) callback
pas   function registerValueCallback( callback: TYVocValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

voc→set_highestValue()**YVoc****voc→setHighestValue()voc.set_highestValue()**

Changes the recorded maximal value observed for the estimated VOC concentration.

```
js function set_highestValue( newval)
nodejs function set_highestValue( newval)
php function set_highestValue( $newval)
cpp int set_highestValue( double newval)
m -(int) setHighestValue : (double) newval
pas function set_highestValue( newval: double): integer
vb function set_highestValue( ByVal newval As Double) As Integer
cs int set_highestValue( double newval)
java int set_highestValue( double newval)
py def set_highestValue( newval)
cmd YVoc target set_highestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed for the estimated VOC concentration

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voc→set_logFrequency()
voc→setLogFrequency()voc.set_logFrequency()**YVoc**

Changes the datalogger recording frequency for this function.

| | |
|---------|--|
| js | function set_logFrequency(newval) |
| node.js | function set_logFrequency(newval) |
| php | function set_logFrequency(\$newval) |
| cpp | int set_logFrequency(const string& newval) |
| m | - (int) setLogFrequency : (NSString*) newval |
| pas | function set_logFrequency(newval: string): integer |
| vb | function set_logFrequency(ByVal newval As String) As Integer |
| cs | int set_logFrequency(string newval) |
| java | int set_logFrequency(String newval) |
| py | def set_logFrequency(newval) |
| cmd | YVoc target set_logFrequency newval |

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voc→set_logicalName()**YVoc****voc→setLogicalName()voc.set_logicalName()**

Changes the logical name of the Volatile Organic Compound sensor.

| | |
|---------------|---|
| js | <code>function set_logicalName(newval)</code> |
| nodejs | <code>function set_logicalName(newval)</code> |
| php | <code>function set_logicalName(\$newval)</code> |
| cpp | <code>int set_logicalName(const string& newval)</code> |
| m | <code>-(int) setLogicalName : (NSString*) newval</code> |
| pas | <code>function set_logicalName(newval: string): integer</code> |
| vb | <code>function set_logicalName(ByVal newval As String) As Integer</code> |
| cs | <code>int set_logicalName(string newval)</code> |
| java | <code>int set_logicalName(String newval)</code> |
| py | <code>def set_logicalName(newval)</code> |
| cmd | <code>YVoc target set_logicalName newval</code> |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the Volatile Organic Compound sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

voc→set_lowestValue() voc→setLowestValue()voc.set_lowestValue()

YVoc

Changes the recorded minimal value observed for the estimated VOC concentration.

```
js function set_lowestValue( newval)
node.js function set_lowestValue( newval)
php function set_lowestValue( $newval)
cpp int set_lowestValue( double newval)
m -(int) setLowestValue : (double) newval
pas function set_lowestValue( newval: double): integer
vb function set_lowestValue( ByVal newval As Double) As Integer
cs int set_lowestValue( double newval)
java int set_lowestValue( double newval)
py def set_lowestValue( newval)
cmd YVoc target set_lowestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed for the estimated VOC concentration

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voc→set_reportFrequency()
voc→setReportFrequency()
voc.set_reportFrequency()

YVoc

Changes the timed value notification frequency for this function.

| | |
|---------|---|
| js | function set_reportFrequency(newval) |
| node.js | function set_reportFrequency(newval) |
| php | function set_reportFrequency(\$newval) |
| cpp | int set_reportFrequency(const string& newval) |
| m | -(int) setReportFrequency : (NSString*) newval |
| pas | function set_reportFrequency(newval: string): integer |
| vb | function set_reportFrequency(ByVal newval As String) As Integer |
| cs | int set_reportFrequency(string newval) |
| java | int set_reportFrequency(String newval) |
| py | def set_reportFrequency(newval) |
| cmd | YVoc target set_reportFrequency newval |

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voc->set_resolution() voc->setResolution()voc.set_resolution()

YVoc

Changes the resolution of the measured physical values.

```
js function set_resolution( newval)
node.js function set_resolution( newval)
php function set_resolution( $newval)
cpp int set_resolution( double newval)
m -(int) setResolution : (double) newval
pas function set_resolution( newval: double): integer
vb function set_resolution( ByVal newval As Double) As Integer
cs int set_resolution( double newval)
java int set_resolution( double newval)
py def set_resolution( newval)
cmd YVoc target set_resolution newval
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voc→set(userData)
voc→setUserData()voc.set(userData)**YVoc**

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|--|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData) \$data |
| cpp | void set(userData) void* data |
| m | -(void) set(userData) : (void*) data |
| pas | procedure set(userData) Tobject |
| vb | procedure set(userData) ByVal data As Object |
| cs | void set(userData) object data |
| java | void set(userData) Object data |
| py | def set(userData) data |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

voc→wait_async()**YVoc**

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

`js` **function wait_async(callback, context)**
`nodejs` **function wait_async(callback, context)**

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.41. Voltage function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

| | |
|--------|---|
| js | <script type='text/javascript' src='yocto_voltage.js'></script> |
| nodejs | var yoctolib = require('yoctolib'); |
| | var YVoltage = yoctolib.YVoltage; |
| php | require_once('yocto_voltage.php'); |
| cpp | #include "yocto_voltage.h" |
| m | #import "yocto_voltage.h" |
| pas | uses yocto_voltage; |
| vb | yocto_voltage.vb |
| cs | yocto_voltage.cs |
| java | import com.yoctopuce.YoctoAPI.YVoltage; |
| py | from yocto_voltage import * |

Global functions

yFindVoltage(func)

Retrieves a voltage sensor for a given identifier.

yFirstVoltage()

Starts the enumeration of voltage sensors currently accessible.

YVoltage methods

voltage→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

voltage→describe()

Returns a short text that describes unambiguously the instance of the voltage sensor in the form TYPE (NAME) = SERIAL . FUNCTIONID.

voltage→get_advertisedValue()

Returns the current value of the voltage sensor (no more than 6 characters).

voltage→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor.

voltage→get_currentValue()

Returns the current measure for the voltage.

voltage→get_errorMessage()

Returns the error message of the latest error with the voltage sensor.

voltage→get_errorType()

Returns the numerical error code of the latest error with the voltage sensor.

voltage→get_friendlyName()

Returns a global identifier of the voltage sensor in the format MODULE_NAME . FUNCTION_NAME.

voltage→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

voltage→get_functionId()

Returns the hardware identifier of the voltage sensor, without reference to the module.

voltage→get_hardwareId()

Returns the unique hardware identifier of the voltage sensor in the form SERIAL . FUNCTIONID.

| | |
|--|--|
| voltage→get_highestValue() | Returns the maximal value observed for the voltage. |
| voltage→get_logFrequency() | Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory. |
| voltage→get_logicalName() | Returns the logical name of the voltage sensor. |
| voltage→get_lowestValue() | Returns the minimal value observed for the voltage. |
| voltage→get_module() | Gets the YModule object for the device on which the function is located. |
| voltage→get_module_async(callback, context) | Gets the YModule object for the device on which the function is located (asynchronous version). |
| voltage→get_recordedData(startTime, endTime) | Retrieves a DataSet object holding historical data for this sensor, for a specified time interval. |
| voltage→get_reportFrequency() | Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function. |
| voltage→get_resolution() | Returns the resolution of the measured values. |
| voltage→get_unit() | Returns the measuring unit for the voltage. |
| voltage→get(userData) | Returns the value of the userData attribute, as previously stored using method set(userData). |
| voltage→isOnline() | Checks if the voltage sensor is currently reachable, without raising any error. |
| voltage→isOnline_async(callback, context) | Checks if the voltage sensor is currently reachable, without raising any error (asynchronous version). |
| voltage→load(msValidity) | Preloads the voltage sensor cache with a specified validity duration. |
| voltage→loadCalibrationPoints(rawValues, refValues) | Retrieves error correction data points previously entered using the method calibrateFromPoints. |
| voltage→load_async(msValidity, callback, context) | Preloads the voltage sensor cache with a specified validity duration (asynchronous version). |
| voltage→nextVoltage() | Continues the enumeration of voltage sensors started using yFirstVoltage(). |
| voltage→registerTimedReportCallback(callback) | Registers the callback function that is invoked on every periodic timed notification. |
| voltage→registerValueCallback(callback) | Registers the callback function that is invoked on every change of advertised value. |
| voltage→set_highestValue(newval) | Changes the recorded maximal value observed pour the voltage. |
| voltage→set_logFrequency(newval) | Changes the datalogger recording frequency for this function. |
| voltage→set_logicalName(newval) | Changes the logical name of the voltage sensor. |

voltage→set_lowestValue(newval)

Changes the recorded minimal value observed pour the voltage.

voltage→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

voltage→set_resolution(newval)

Changes the resolution of the measured values.

voltage→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

voltage→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YVoltage.FindVoltage() yFindVoltage()YVoltage.FindVoltage()

YVoltage

Retrieves a voltage sensor for a given identifier.

```
js function yFindVoltage( func)
node.js function FindVoltage( func)
php function yFindVoltage( $func)
cpp YVoltage* yFindVoltage( const string& func)
m YVoltage* yFindVoltage( NSString* func)
pas function yFindVoltage( func: string): TYVoltage
vb function yFindVoltage( ByVal func As String) As YVoltage
cs YVoltage FindVoltage( string func)
java YVoltage FindVoltage( String func)
py def FindVoltage( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the voltage sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YVoltage.isOnline()` to test if the voltage sensor is indeed online at a given time. In case of ambiguity when looking for a voltage sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the voltage sensor

Returns :

a `YVoltage` object allowing you to drive the voltage sensor.

YVoltage.FirstVoltage()

YVoltage

yFirstVoltage() YVoltage.FirstVoltage()

Starts the enumeration of voltage sensors currently accessible.

| | |
|--------|--|
| js | function yFirstVoltage() |
| nodejs | function FirstVoltage() |
| php | function yFirstVoltage() |
| cpp | YVoltage* yFirstVoltage() |
| m | YVoltage* yFirstVoltage() |
| pas | function yFirstVoltage() : TYVoltage |
| vb | function yFirstVoltage() As YVoltage |
| cs | YVoltage FirstVoltage() |
| java | YVoltage FirstVoltage() |
| py | def FirstVoltage() |

Use the method `YVoltage.nextVoltage()` to iterate on next voltage sensors.

Returns :

a pointer to a `YVoltage` object, corresponding to the first voltage sensor currently online, or a `null` pointer if there are none.

voltage→calibrateFromPoints() voltage.calibrateFromPoints()

YVoltage

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```

js   function calibrateFromPoints( rawValues, refValues)
nodejs function calibrateFromPoints( rawValues, refValues)
php   function calibrateFromPoints( $rawValues, $refValues)
cpp   int calibrateFromPoints( vector<double> rawValues,
                           vector<double> refValues)
m    -(int) calibrateFromPoints : (NSMutableArray*) rawValues
      : (NSMutableArray*) refValues
pas  function calibrateFromPoints( rawValues: TDoubleArray,
                                  refValues: TDoubleArray): LongInt
vb   procedure calibrateFromPoints( )
cs   int calibrateFromPoints( List<double> rawValues,
                           List<double> refValues)
java int calibrateFromPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)
py   def calibrateFromPoints( rawValues, refValues)
cmd  YVoltage target calibrateFromPoints rawValues refValues

```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

voltage→describe()voltage.describe()**YVoltage**

Returns a short text that describes unambiguously the instance of the voltage sensor in the form TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--|
| js | function describe () |
| nodejs | function describe () |
| php | function describe () |
| cpp | string describe () |
| m | -(NSString*) describe |
| pas | function describe (): string |
| vb | function describe () As String |
| cs | string describe () |
| java | String describe () |
| py | def describe () |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the voltage sensor (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

voltage→get_advertisedValue()
voltage→advertisedValue()
voltage.get_advertisedValue()

YVoltage

Returns the current value of the voltage sensor (no more than 6 characters).

```
js function get_advertisedValue( )  
nodejs function get_advertisedValue( )  
php function get_advertisedValue( )  
cpp string get_advertisedValue( )  
m -(NSString*) advertisedValue  
pas function get_advertisedValue( ): string  
vb function get_advertisedValue( ) As String  
cs string get_advertisedValue( )  
java String get_advertisedValue( )  
py def get_advertisedValue( )  
cmd YVoltage target get_advertisedValue
```

Returns :

a string corresponding to the current value of the voltage sensor (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

voltage→get_currentRawValue()
voltage→currentRawValue()
voltage.get_currentRawValue()

YVoltage

Returns the uncalibrated, unrounded raw value returned by the sensor.

| | |
|----------------------|--|
| <code>js</code> | function get_currentRawValue() |
| <code>node.js</code> | function get_currentRawValue() |
| <code>php</code> | function get_currentRawValue() |
| <code>cpp</code> | double get_currentRawValue() |
| <code>m</code> | -(double) currentRawValue |
| <code>pas</code> | function get_currentRawValue(): double |
| <code>vb</code> | function get_currentRawValue() As Double |
| <code>cs</code> | double get_currentRawValue() |
| <code>java</code> | double get_currentRawValue() |
| <code>py</code> | def get_currentRawValue() |
| <code>cmd</code> | YVoltage target get_currentRawValue |

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor

On failure, throws an exception or returns **Y_CURRENTRAWVALUE_INVALID**.

voltage→get_currentValue()**YVoltage****voltage→currentValue()voltage.get_currentValue()**

Returns the current measure for the voltage.

```
js function get_currentValue( )
node.js function get_currentValue( )
php function get_currentValue( )
cpp double get_currentValue( )
m -(double) currentValue
pas function get_currentValue( ): double
vb function get_currentValue( ) As Double
cs double get_currentValue( )
java double get_currentValue( )
py def get_currentValue( )
cmd YVoltage target get_currentValue
```

Returns :

a floating point number corresponding to the current measure for the voltage

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

voltage→getErrorMessage()**YVoltage****voltage→errorMessage()voltage.getErrorMessage()**

Returns the error message of the latest error with the voltage sensor.

| | |
|--------|--|
| js | function getErrorMessage() |
| nodejs | function getErrorMessage() |
| php | function getErrorMessage() |
| cpp | string getErrorMessage() |
| m | -(NSString*) errorMessage |
| pas | function getErrorMessage() : string |
| vb | function getErrorMessage() As String |
| cs | string getErrorMessage() |
| java | String getErrorMessage() |
| py | def getErrorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the voltage sensor object

voltage→get_errorType() **YVoltage**
voltage→errorType()voltage.get_errorType()

Returns the numerical error code of the latest error with the voltage sensor.

```
js function get_errorType( )  
node.js function get_errorType( )  
php function get_errorType( )  
cpp YRETCODE get_errorType( )  
pas function get_errorType( ): YRETCODE  
vb function get_errorType( ) As YRETCODE  
cs YRETCODE get_errorType( )  
java int get_errorType( )  
py def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the voltage sensor object

voltage→get_friendlyName()**YVoltage****voltage→friendlyName()voltage.get_friendlyName()**

Returns a global identifier of the voltage sensor in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|-------------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the voltage sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the voltage sensor (for exemple: MyCustomName . relay1)

Returns :

a string that uniquely identifies the voltage sensor using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

voltage→get_functionDescriptor()
voltage→functionDescriptor()
voltage.get_functionDescriptor()**YVoltage**

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|--------|---|
| js | function get_functionDescriptor() |
| nodejs | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

voltage→get_functionId()**YVoltage****voltage→functionId()voltage.get_functionId()**

Returns the hardware identifier of the voltage sensor, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the voltage sensor (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

voltage→get_hardwareId()**YVoltage****voltage→hardwareId()voltage.get_hardwareId()**

Returns the unique hardware identifier of the voltage sensor in the form SERIAL.FUNCTIONID.

| | |
|---------|--------------------------------------|
| js | function get_hardwareId() |
| node.js | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the voltage sensor. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the voltage sensor (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

voltage→get_highestValue()**YVoltage****voltage→highestValue()voltage.get_highestValue()**

Returns the maximal value observed for the voltage.

```
js function get_highestValue( )
nodejs function get_highestValue( )
php function get_highestValue( )
cpp double get_highestValue( )
m -(double) highestValue
pas function get_highestValue( ): double
vb function get_highestValue( ) As Double
cs double get_highestValue( )
java double get_highestValue( )
py def get_highestValue( )
cmd YVoltage target get_highestValue
```

Returns :

a floating point number corresponding to the maximal value observed for the voltage

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

voltage→get_logFrequency() YVoltage
voltage→logFrequency()voltage.get_logFrequency()

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
js  function get_logFrequency( )  
nodejs function get_logFrequency( )  
php  function get_logFrequency( )  
cpp   string get_logFrequency( )  
m    -(NSString*) logFrequency  
pas   function get_logFrequency( ):string  
vb    function get_logFrequency( ) As String  
cs    string get_logFrequency( )  
java  String get_logFrequency( )  
py    def get_logFrequency( )  
cmd   YVoltage target get_logFrequency
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

voltage→get_logicalName()**YVoltage****voltage→logicalName()voltage.get_logicalName()**

Returns the logical name of the voltage sensor.

```
js function get_logicalName( )
nodejs function get_logicalName( )
php function get_logicalName( )
cpp string get_logicalName( )
m -(NSString*) logicalName
pas function get_logicalName( ): string
vb function get_logicalName( ) As String
cs string get_logicalName( )
java String get_logicalName( )
py def get_logicalName( )
cmd YVoltage target get_logicalName
```

Returns :

a string corresponding to the logical name of the voltage sensor. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

voltage→get_lowestValue()**YVoltage****voltage→lowestValue()voltage.get_lowestValue()**

Returns the minimal value observed for the voltage.

js function **get_lowestValue()****node.js** function **get_lowestValue()****php** function **get_lowestValue()****cpp** double **get_lowestValue()****m** -(double) lowestValue**pas** function **get_lowestValue(): double****vb** function **get_lowestValue() As Double****cs** double **get_lowestValue()****java** double **get_lowestValue()****py** def **get_lowestValue()****cmd** YVoltage target **get_lowestValue****Returns :**

a floating point number corresponding to the minimal value observed for the voltage

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

voltage→get_module()**YVoltage****voltage→module()voltage.get_module()**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

voltage→get_module_async()
voltage→module_async()**YVoltage**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

voltage→get_recordedData()**YVoltage****voltage→recordedData()voltage.get_recordedData()**

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

| | |
|----------------------|--|
| <code>js</code> | <code>function get_recordedData(startTime, endTime)</code> |
| <code>node.js</code> | <code>function get_recordedData(startTime, endTime)</code> |
| <code>php</code> | <code>function get_recordedData(\$startTime, \$endTime)</code> |
| <code>cpp</code> | <code>YDataSet get_recordedData(s64 startTime, s64 endTime)</code> |
| <code>m</code> | <code>-(YDataSet*) recordedData : (s64) startTime : (s64) endTime</code> |
| <code>pas</code> | <code>function get_recordedData(startTime: int64, endTime: int64): TYDataSet</code> |
| <code>vb</code> | <code>function get_recordedData() As YDataSet</code> |
| <code>cs</code> | <code>YDataSet get_recordedData(long startTime, long endTime)</code> |
| <code>java</code> | <code>YDataSet get_recordedData(long startTime, long endTime)</code> |
| <code>py</code> | <code>def get_recordedData(startTime, endTime)</code> |
| <code>cmd</code> | <code>YVoltage target get_recordedData startTime endTime</code> |

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

voltage→get_reportFrequency()
voltage→reportFrequency()
voltage.get_reportFrequency()**YVoltage**

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

| | |
|--------|---|
| js | function get_reportFrequency() |
| nodejs | function get_reportFrequency() |
| php | function get_reportFrequency() |
| cpp | string get_reportFrequency() |
| m | -(NSString*) reportFrequency |
| pas | function get_reportFrequency(): string |
| vb | function get_reportFrequency() As String |
| cs | string get_reportFrequency() |
| java | String get_reportFrequency() |
| py | def get_reportFrequency() |
| cmd | YVoltage target get_reportFrequency |

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

voltage→get_resolution()**YVoltage****voltage→resolution()voltage.get_resolution()**

Returns the resolution of the measured values.

| | |
|--------|---|
| js | function get_resolution() |
| nodejs | function get_resolution() |
| php | function get_resolution() |
| cpp | double get_resolution() |
| m | -(double) resolution |
| pas | function get_resolution(): double |
| vb | function get_resolution() As Double |
| cs | double get_resolution() |
| java | double get_resolution() |
| py | def get_resolution() |
| cmd | YVoltage target get_resolution |

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

voltage→get_unit()
voltage→unit()voltage.get_unit()**YVoltage**

Returns the measuring unit for the voltage.

| | |
|---------|---------------------------------------|
| js | function get_unit() |
| node.js | function get_unit() |
| php | function get_unit() |
| cpp | string get_unit() |
| m | -(NSString*) unit |
| pas | function get_unit() : string |
| vb | function get_unit() As String |
| cs | string get_unit() |
| java | String get_unit() |
| py | def get_unit() |
| cmd | YVoltage target get_unit |

Returns :

a string corresponding to the measuring unit for the voltage

On failure, throws an exception or returns Y_UNIT_INVALID.

voltage→get(userData)**YVoltage****voltage→userData()voltage.get(userData())**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|--|
| js | <code>function get(userData) </code> |
| nodejs | <code>function get(userData) </code> |
| php | <code>function get(userData) </code> |
| cpp | <code>void * get(userData) </code> |
| m | <code>-(void*) userData </code> |
| pas | <code>function get(userData): Tobject </code> |
| vb | <code>function get(userData) As Object </code> |
| cs | <code>object get(userData) </code> |
| java | <code>Object get(userData) </code> |
| py | <code>def get(userData) </code> |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

voltage→isOnline()voltage.isOnline()**YVoltage**

Checks if the voltage sensor is currently reachable, without raising any error.

| | |
|--------|--|
| js | function isOnline() |
| nodejs | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the voltage sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the voltage sensor.

Returns :

true if the voltage sensor can be reached, and false otherwise

voltage→isOnline_async()**YVoltage**

Checks if the voltage sensor is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the voltage sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

voltage→load()voltage.load()**YVoltage**

Preloads the voltage sensor cache with a specified validity duration.

| | |
|--------|--|
| js | function load(msValidity) |
| nodejs | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | - (YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

voltage→loadCalibrationPoints() voltage.loadCalibrationPoints()

YVoltage

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```

js   function loadCalibrationPoints( rawValues, refValues)
nodejs function loadCalibrationPoints( rawValues, refValues)
php  function loadCalibrationPoints( &$rawValues, &$refValues)
cpp   int loadCalibrationPoints( vector<double>& rawValues,
                                vector<double>& refValues)

m    -(int) loadCalibrationPoints : (NSMutableArray*) rawValues
                           : (NSMutableArray*) refValues

pas  function loadCalibrationPoints( var rawValues: TDoubleArray,
                           var refValues: TDoubleArray): LongInt

vb   procedure loadCalibrationPoints( )
cs   int loadCalibrationPoints( List<double> rawValues,
                           List<double> refValues)

java int loadCalibrationPoints( ArrayList<Double> rawValues,
                           ArrayList<Double> refValues)

py   def loadCalibrationPoints( rawValues, refValues)
cmd  YVoltage target loadCalibrationPoints rawValues refValues

```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voltage→load_async()

YVoltage

Preloads the voltage sensor cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

voltage→nextVoltage()|voltage.nextVoltage()**YVoltage**

Continues the enumeration of voltage sensors started using `yFirstVoltage()`.

| | |
|--------|--|
| js | function nextVoltage() |
| nodejs | function nextVoltage() |
| php | function nextVoltage() |
| cpp | <code>YVoltage * nextVoltage()</code> |
| m | <code>-(YVoltage*) nextVoltage</code> |
| pas | function nextVoltage(): TYVoltage |
| vb | function nextVoltage() As YVoltage |
| cs | <code>YVoltage nextVoltage()</code> |
| java | <code>YVoltage nextVoltage()</code> |
| py | <code>def nextVoltage()</code> |

Returns :

a pointer to a `YVoltage` object, corresponding to a voltage sensor currently online, or a `null` pointer if there are no more voltage sensors to enumerate.

voltage→registerTimedReportCallback() voltage.registerTimedReportCallback()

YVoltage

Registers the callback function that is invoked on every periodic timed notification.

```
js   function registerTimedReportCallback( callback)
node.js function registerTimedReportCallback( callback)
php  function registerTimedReportCallback( $callback)
cpp   int registerTimedReportCallback( YVoltageTimedReportCallback callback)
m    -(int) registerTimedReportCallback : (YVoltageTimedReportCallback) callback
pas   function registerTimedReportCallback( callback: TYVoltageTimedReportCallback): LongInt
vb    function registerTimedReportCallback( ) As Integer
cs    int registerTimedReportCallback( TimedReportCallback callback)
java  int registerTimedReportCallback( TimedReportCallback callback)
py    def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

voltage→registerValueCallback() voltage.registerValueCallback()

YVoltage

Registers the callback function that is invoked on every change of advertised value.

| | |
|---------|--|
| js | function registerValueCallback(callback) |
| node.js | function registerValueCallback(callback) |
| php | function registerValueCallback(\$callback) |
| cpp | int registerValueCallback(YVoltageValueCallback callback) |
| m | -(int) registerValueCallback : (YVoltageValueCallback) callback |
| pas | function registerValueCallback(callback : TYVoltageValueCallback): LongInt |
| vb | function registerValueCallback() As Integer |
| cs | int registerValueCallback(ValueCallback callback) |
| java | int registerValueCallback(UpdateCallback callback) |
| py | def registerValueCallback(callback) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

voltage→set_highestValue()
voltage→setHighestValue()
voltage.set_highestValue()

YVoltage

Changes the recorded maximal value observed pour the voltage.

```
js function set_highestValue( newval)
nodejs function set_highestValue( newval)
php function set_highestValue( $newval)
cpp int set_highestValue( double newval)
m -(int) setHighestValue : (double) newval
pas function set_highestValue( newval: double): integer
vb function set_highestValue( ByVal newval As Double) As Integer
cs int set_highestValue( double newval)
java int set_highestValue( double newval)
py def set_highestValue( newval)
cmd YVoltage target set_highestValue newval
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed pour the voltage

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voltage→set_logFrequency()
voltage→setLogFrequency()
voltage.set_logFrequency()

YVoltage

Changes the datalogger recording frequency for this function.

| | |
|---------|--|
| js | function set_logFrequency(newval) |
| node.js | function set_logFrequency(newval) |
| php | function set_logFrequency(\$newval) |
| cpp | int set_logFrequency(const string& newval) |
| m | -(int) setLogFrequency : (NSString*) newval |
| pas | function set_logFrequency(newval: string): integer |
| vb | function set_logFrequency(ByVal newval As String) As Integer |
| cs | int set_logFrequency(string newval) |
| java | int set_logFrequency(String newval) |
| py | def set_logFrequency(newval) |
| cmd | YVoltage target set_logFrequency newval |

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voltage→set_logicalName() voltage→setLogicalName()voltage.set_logicalName()

YVoltage

Changes the logical name of the voltage sensor.

```
js function set_logicalName( newval)
node.js function set_logicalName( newval)
php function set_logicalName( $newval)
cpp int set_logicalName( const string& newval)
m -(int) setLogicalName : (NSString*) newval
pas function set_logicalName( newval: string): integer
vb function set_logicalName( ByVal newval As String) As Integer
cs int set_logicalName( string newval)
java int set_logicalName( String newval)
py def set_logicalName( newval)
cmd YVoltage target set_logicalName newval
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the voltage sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

voltage→set_lowestValue()**YVoltage****voltage→setLowestValue()voltage.set_lowestValue()**

Changes the recorded minimal value observed pour the voltage.

| | |
|--------|---|
| js | function set_lowestValue(newval) |
| nodejs | function set_lowestValue(newval) |
| php | function set_lowestValue(\$newval) |
| cpp | int set_lowestValue(double newval) |
| m | -(int) setLowestValue : (double) newval |
| pas | function set_lowestValue(newval: double): integer |
| vb | function set_lowestValue(ByVal newval As Double) As Integer |
| cs | int set_lowestValue(double newval) |
| java | int set_lowestValue(double newval) |
| py | def set_lowestValue(newval) |
| cmd | YVoltage target set_lowestValue newval |

Parameters :

newval a floating point number corresponding to the recorded minimal value observed pour the voltage

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voltage→set_reportFrequency()
voltage→setReportFrequency()
voltage.set_reportFrequency()**YVoltage**

Changes the timed value notification frequency for this function.

```
js    function set_reportFrequency( newval)
nodejs function set_reportFrequency( newval)
php   function set_reportFrequency( $newval)
cpp   int set_reportFrequency( const string& newval)
m     -(int) setReportFrequency : (NSString*) newval
pas   function set_reportFrequency( newval: string): integer
vb    function set_reportFrequency( ByVal newval As String) As Integer
cs    int set_reportFrequency( string newval)
java  int set_reportFrequency( String newval)
py    def set_reportFrequency( newval)
cmd   YVoltage target set_reportFrequency newval
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voltage→set_resolution()**YVoltage****voltage→setResolution()voltage.set_resolution()**

Changes the resolution of the measured values.

| | |
|--------|--|
| js | function set_resolution(newval) |
| nodejs | function set_resolution(newval) |
| php | function set_resolution(\$newval) |
| cpp | int set_resolution(double newval) |
| m | -(int) setResolution : (double) newval |
| pas | function set_resolution(newval: double): integer |
| vb | function set_resolution(ByVal newval As Double) As Integer |
| cs | int set_resolution(double newval) |
| java | int set_resolution(double newval) |
| py | def set_resolution(newval) |
| cmd | YVoltage target set_resolution newval |

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voltage→set(userData)**YVoltage****voltage→setUserData()|voltage.set(userData())**

Stores a user context provided as argument in the userData attribute of the function.

```
js   function set(userData) {  
node.js function set(userData) {  
php  function set(userData) {  
cpp   void set(userData) {  
m    -(void) setUserData : (void*) userData  
pas  procedure set(userData: Tobject);  
vb   procedure set(userData: ByVal data As Object);  
cs   void set(userData: object data);  
java void set(userData: Object data);  
py   def set(userData: data);
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

voltage→wait_async()**YVoltage**

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.42. Voltage source function interface

Yoctopuce application programming interface allows you to control the module voltage output. You affect absolute output values or make transitions

In order to use the functions described here, you should include:

| | |
|------|---|
| js | <script type='text/javascript' src='yocto_vsource.js'></script> |
| php | require_once('yocto_vsource.php'); |
| cpp | #include "yocto_vsource.h" |
| m | #import "yocto_vsource.h" |
| pas | uses yocto_vsource; |
| vb | yocto_vsource.vb |
| cs | yocto_vsource.cs |
| java | import com.yoctopuce.YoctoAPI.YVSource; |
| py | from yocto_vsource import * |

| Global functions | |
|--|--|
| yFindVSource(func) | Retrieves a voltage source for a given identifier. |
| yFirstVSource() | Starts the enumeration of voltage sources currently accessible. |
| YVSource methods | |
| vsource→describe() | Returns a short text that describes the function in the form TYPE (NAME) =SERIAL . FUNCTIONID. |
| vsource→get_advertisedValue() | Returns the current value of the voltage source (no more than 6 characters). |
| vsource→get_errorMessage() | Returns the error message of the latest error with this function. |
| vsource→get_errorType() | Returns the numerical error code of the latest error with this function. |
| vsource→get_extPowerFailure() | Returns true if external power supply voltage is too low. |
| vsource→get_failure() | Returns true if the module is in failure mode. |
| vsource→get_friendlyName() | Returns a global identifier of the function in the format MODULE_NAME . FUNCTION_NAME. |
| vsource→get_functionDescriptor() | Returns a unique identifier of type YFUN_DESCR corresponding to the function. |
| vsource→get_functionId() | Returns the hardware identifier of the function, without reference to the module. |
| vsource→get_hardwareId() | Returns the unique hardware identifier of the function in the form SERIAL . FUNCTIONID. |
| vsource→get_logicalName() | Returns the logical name of the voltage source. |
| vsource→get_module() | Gets the YModule object for the device on which the function is located. |
| vsource→get_module_async(callback, context) | |

Gets the YModule object for the device on which the function is located (asynchronous version).

vsouce→get_overCurrent()

Returns true if the appliance connected to the device is too greedy .

vsouce→get_overHeat()

Returns TRUE if the module is overheating.

vsouce→get_overLoad()

Returns true if the device is not able to maintain the requested voltage output .

vsouce→get_regulationFailure()

Returns true if the voltage output is too high regarding the requested voltage .

vsouce→get_unit()

Returns the measuring unit for the voltage.

vsouce→get(userData)

Returns the value of the userData attribute, as previously stored using method set(userData).

vsouce→get_voltage()

Returns the voltage output command (mV)

vsouce→isOnline()

Checks if the function is currently reachable, without raising any error.

vsouce→isOnline_async(callback, context)

Checks if the function is currently reachable, without raising any error (asynchronous version).

vsouce→load(msValidity)

Preloads the function cache with a specified validity duration.

vsouce→load_async(msValidity, callback, context)

Preloads the function cache with a specified validity duration (asynchronous version).

vsouce→nextVSource()

Continues the enumeration of voltage sources started using yFirstVSource().

vsouce→pulse(voltage, ms_duration)

Sets device output to a specific volatage, for a specified duration, then brings it automatically to 0V.

vsouce→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

vsouce→set_logicalName(newval)

Changes the logical name of the voltage source.

vsouce→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

vsouce→set_voltage(newval)

Tunes the device output voltage (milliVolts).

vsouce→voltageMove(target, ms_duration)

Performs a smooth move at constant speed toward a given value.

vsouce→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

yFindVSource() —**YVSource****YVSource.FindVSource()YVSource.FindVSource()**

Retrieves a voltage source for a given identifier.

```
js function yFindVSource( func)
php function yFindVSource( $func)
cpp YVSource* yFindVSource( const string& func)
m YVSource* yFindVSource( NSString* func)
pas function yFindVSource( func: string): TYVSource
vb function yFindVSource( ByVal func As String) As YVSource
cs YVSource FindVSource( string func)
java YVSource FindVSource( String func)
py def FindVSource( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the voltage source is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YVSource.isOnline()` to test if the voltage source is indeed online at a given time. In case of ambiguity when looking for a voltage source by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the voltage source

Returns :

a `YVSource` object allowing you to drive the voltage source.

yFirstVSource() —**YVSource****YVSource.FirstVSource()YVSource.FirstVSource()**

Starts the enumeration of voltage sources currently accessible.

```
js   function yFirstVSource( )  
php  function yFirstVSource( )  
cpp  YVSource* yFirstVSource( )  
m    YVSource* yFirstVSource( )  
pas   function yFirstVSource( ): TYVSource  
vb    function yFirstVSource( ) As YVSource  
cs    YVSource FirstVSource( )  
java  YVSource FirstVSource( )  
py    def FirstVSource( )
```

Use the method `YVSource.nextVSource()` to iterate on next voltage sources.

Returns :

a pointer to a `YVSource` object, corresponding to the first voltage source currently online, or a null pointer if there are none.

vsources->describe()**YVSource**

Returns a short text that describes the function in the form TYPE (NAME)=SERIAL . FUNCTIONID.

| | |
|------|---------------------------------------|
| js | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | - (NSString*) describe |
| pas | function describe(): string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the function (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

vsource→get_advertisedValue()
vsource→advertisedValue()
vsource.get_advertisedValue()

YVSource

Returns the current value of the voltage source (no more than 6 characters).

| | |
|------|--|
| js | function get_advertisedValue() |
| php | function get_advertisedValue() |
| cpp | string get_advertisedValue() |
| m | -(NSString*) advertisedValue |
| pas | function get_advertisedValue() : string |
| vb | function get_advertisedValue() As String |
| cs | string get_advertisedValue() |
| java | String get_advertisedValue() |
| py | def get_advertisedValue() |
| cmd | YVSource target get_advertisedValue |

Returns :

a string corresponding to the current value of the voltage source (no more than 6 characters)

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

vsOURCE→get_errorMessage()
vsOURCE→errorMessage()
vsOURCE.get_errorMessage()**YVSource**

Returns the error message of the latest error with this function.

```
js  function get_errorMessage( )  
php function get_errorMessage( )  
cpp string get_errorMessage( )  
m -(NSString*) errorMessage  
pas function get_errorMessage( ):string  
vb function get_errorMessage( ) As String  
cs string get_errorMessage( )  
java String get_errorMessage( )  
py def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using this function object

vsource→get_errorType()**YVSource****vsource→errorType()vsource.get_errorType()**

Returns the numerical error code of the latest error with this function.

```
js  function get_errorType( )
php function get_errorType( )
cpp YRETCODE get_errorType( )
pas function get_errorType( ): YRETCODE
vb  function get_errorType( ) As YRETCODE
cs  YRETCODE get_errorType( )
java int get_errorType( )
py  def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using this function object

vsOURCE→get_extPowerFailure()
vsOURCE→extPowerFailure()
vsOURCE.get_extPowerFailure()

YVSource

Returns true if external power supply voltage is too low.

```
js function get_extPowerFailure( )
php function get_extPowerFailure( )
cpp Y_EXTPOWERFAILURE_enum get_extPowerFailure( )
m -(Y_EXTPOWERFAILURE_enum) extPowerFailure
pas function get_extPowerFailure( ): Integer
vb function get_extPowerFailure( ) As Integer
cs int get_extPowerFailure( )
java int get_extPowerFailure( )
py def get_extPowerFailure( )
cmd YVSource target get_extPowerFailure
```

Returns :

either Y_EXTPOWERFAILURE_FALSE or Y_EXTPOWERFAILURE_TRUE, according to true if external power supply voltage is too low

On failure, throws an exception or returns Y_EXTPOWERFAILURE_INVALID.

vsource→get_failure()
vsource→failure()vsource.get_failure()**YVSource**

Returns true if the module is in failure mode.

```
js function get_failure( )
php function get_failure( )
cpp Y_FAILURE_enum get_failure( )
m -(Y_FAILURE_enum) failure
pas function get_failure( ): Integer
vb function get_failure( ) As Integer
cs int get_failure( )
java int get_failure( )
py def get_failure( )
cmd YVSource target get_failure
```

More information can be obtained by testing get_overheat, get_overcurrent etc... When a error condition is met, the output voltage is set to zéro and cannot be changed until the reset() function is called.

Returns :

either Y_FAILURE_FALSE or Y_FAILURE_TRUE, according to true if the module is in failure mode

On failure, throws an exception or returns Y_FAILURE_INVALID.

vsOURCE→get_friendlyName()
vsOURCE→friendlyName()**YVSource**

Returns a global identifier of the function in the format MODULE_NAME . FUNCTION_NAME.

js **function get_friendlyName()**
php **function get_friendlyName()**
cpp **virtual string get_friendlyName()**
m **-NSString* friendlyName**
cs **override string get_friendlyName()**
java **String get_friendlyName()**

The returned string uses the logical names of the module and of the function if they are defined, otherwise the serial number of the module and the hardware identifier of the function (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the function using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

vsource→get_functionDescriptor()
vsource→functionDescriptor()
vsource.get_vsourceDescriptor()

YVSource

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
js  function get_functionDescriptor( )  
php function get_functionDescriptor( )  
cpp YFUN_DESCR get_functionDescriptor( )  
m -(YFUN_DESCR) functionDescriptor  
pas function get_functionDescriptor( ): YFUN_DESCR  
vb  function get_functionDescriptor( ) As YFUN_DESCR  
cs   YFUN_DESCR get_functionDescriptor( )  
java String get_functionDescriptor( )  
py   def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

vsource→get_functionId()
vsource→functionId()**YVSource**

Returns the hardware identifier of the function, without reference to the module.

| | |
|------|---|
| js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | - (NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |

For example `relay1`

Returns :

a string that identifies the function (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

vsource→get_hardwareId()
vsource→hardwareId()**YVSource**

Returns the unique hardware identifier of the function in the form SERIAL.FUNCTIONID.

```
js   function get_hardwareId( )
php  function get_hardwareId( )
cpp  string get_hardwareId( )
m    -(NSString*) hardwareId
vb   function get_hardwareId( ) As String
cs   string get_hardwareId( )
java String get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the function. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the function (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

vsource→get_logicalName()**YVSource****vsource→logicalName()vsource.get_logicalName()**

Returns the logical name of the voltage source.

```
js function get_logicalName( )
php function get_logicalName( )
cpp string get_logicalName( )
m -(NSString*) logicalName
pas function get_logicalName( ): string
vb function get_logicalName( ) As String
cs string get_logicalName( )
java String get_logicalName( )
py def get_logicalName( )
cmd YVSource target get_logicalName
```

Returns :

a string corresponding to the logical name of the voltage source

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

vsource→get_module()**YVSource****vsource→module()vsource.get_module()**

Gets the YModule object for the device on which the function is located.

```
js   function get_module( )
php  function get_module( )
cpp  YModule * get_module( )
m    -(YModule*) module
pas   function get_module( ): TYModule
vb    function get_module( ) As YModule
cs    YModule get_module( )
java  YModule get_module( )
py    def get_module( )
```

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

vsource→get_module_async()
vsource→module_async()**YVSource**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

`js` **function get_module_async(callback, context)**

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

vsource→get_overCurrent()**YVSource****vsource→overCurrent()vsource.get_overCurrent()**

Returns true if the appliance connected to the device is too greedy .

```
js   function get_overCurrent( )  
php  function get_overCurrent( )  
cpp  Y_OVERCURRENT_enum get_overCurrent( )  
m    -(Y_OVERCURRENT_enum) overCurrent  
pas   function get_overCurrent( ): Integer  
vb    function get_overCurrent( ) As Integer  
cs    int get_overCurrent( )  
java  int get_overCurrent( )  
py    def get_overCurrent( )  
cmd   YVSource target get_overCurrent
```

Returns :

either Y_OVERCURRENT_FALSE or Y_OVERCURRENT_TRUE, according to true if the appliance connected to the device is too greedy

On failure, throws an exception or returns Y_OVERCURRENT_INVALID.

vsouce→get_overHeat()**YVSource****vsouce→overHeat()|vsouce.get_overHeat()**

Returns TRUE if the module is overheating.

```
js function get_overHeat( )  
php function get_overHeat( )  
cpp Y_OVERHEAT_enum get_overHeat( )  
m -(Y_OVERHEAT_enum) overHeat  
pas function get_overHeat( ): Integer  
vb function get_overHeat( ) As Integer  
cs int get_overHeat( )  
java int get_overHeat( )  
py def get_overHeat( )  
cmd YVSource target get_overHeat
```

Returns :

either Y_OVERHEAT_FALSE or Y_OVERHEAT_TRUE, according to TRUE if the module is overheating

On failure, throws an exception or returns Y_OVERHEAT_INVALID.

vsource→get_overLoad()**YVSource****vsource→overLoad()vsource.get_overLoad()**

Returns true if the device is not able to maintain the requested voltage output .

```
js   function get_overLoad( )  
php  function get_overLoad( )  
cpp  Y_OVERLOAD_enum get_overLoad( )  
m    -(Y_OVERLOAD_enum) overLoad  
pas   function get_overLoad( ): Integer  
vb    function get_overLoad( ) As Integer  
cs    int get_overLoad( )  
java  int get_overLoad( )  
py    def get_overLoad( )  
cmd   YVSource target get_overLoad
```

Returns :

either Y_OVERLOAD_FALSE or Y_OVERLOAD_TRUE, according to true if the device is not able to maintain the requested voltage output

On failure, throws an exception or returns Y_OVERLOAD_INVALID.

vsOURCE→get_regulationFailure()**YVSource****vsOURCE→regulationFailure()****vsOURCE.get_regulationFailure()**

Returns true if the voltage output is too high regarding the requested voltage .

```
js function get_regulationFailure( )
php function get_regulationFailure( )
cpp Y_REGULATIONFAILURE_enum get_regulationFailure( )
m -(Y_REGULATIONFAILURE_enum) regulationFailure
pas function get_regulationFailure( ): Integer
vb function get_regulationFailure( ) As Integer
cs int get_regulationFailure( )
java int get_regulationFailure( )
py def get_regulationFailure( )
cmd YVSource target get_regulationFailure
```

Returns :

either Y_REGULATIONFAILURE_FALSE or Y_REGULATIONFAILURE_TRUE, according to true if the voltage output is too high regarding the requested voltage

On failure, throws an exception or returns Y_REGULATIONFAILURE_INVALID.

vsource→get_unit()**YVSource****vsource→unit()vsource.get_unit()**

Returns the measuring unit for the voltage.

```
js   function get_unit( )  
php  function get_unit( )  
cpp  string get_unit( )  
m    -(NSString*) unit  
pas  function get_unit( ): string  
vb   function get_unit( ) As String  
cs   string get_unit( )  
java String get_unit( )  
py   def get_unit( )  
cmd  YVSource target get_unit
```

Returns :

a string corresponding to the measuring unit for the voltage

On failure, throws an exception or returns Y_UNIT_INVALID.

vsouce→get(userData)**YVSource****vsouce→userData()|vsouce.get(userData)**

Returns the value of the userData attribute, as previously stored using method set(userData).

| | |
|------|----------------------------------|
| js | function get(userData) |
| php | function get(userData) |
| cpp | void * get(userData) |
| m | -(void*) userData |
| pas | function get(userData): Tobject |
| vb | function get(userData) As Object |
| cs | object get(userData) |
| java | Object get(userData) |
| py | def get(userData) |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

vsource→get_voltage()**YVSource****vsource→voltage()vsource.get_voltage()**

Returns the voltage output command (mV)

| | |
|------|---|
| js | function get_voltage() |
| php | function get_voltage() |
| cpp | int get_voltage() |
| m | -(int) voltage |
| pas | function get_voltage() : LongInt |
| vb | function get_voltage() As Integer |
| cs | int get_voltage() |
| java | int get_voltage() |
| py | def get_voltage() |

Returns :

an integer corresponding to the voltage output command (mV)

On failure, throws an exception or returns Y_VOLTAGE_INVALID.

vsource→isOnline()|vsource.isOnline()**YVSource**

Checks if the function is currently reachable, without raising any error.

| | |
|------|---|
| js | function isOnline () |
| php | function isOnline () |
| cpp | bool isOnline () |
| m | -BOOL) isOnline |
| pas | function isOnline (): boolean |
| vb | function isOnline () As Boolean |
| cs | bool isOnline () |
| java | boolean isOnline () |
| py | def isOnline () |

If there is a cached value for the function in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

Returns :

true if the function can be reached, and false otherwise

vsource→isOnline_async()**YVSource**

Checks if the function is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context)
```

If there is a cached value for the function in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox Javascript VM that does not implement context switching during blocking I/O calls.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

vsources→load()|vsources.load()**YVSource**

Preloads the function cache with a specified validity duration.

| | |
|------|--|
| js | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | -(YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

`YAPI_SUCCESS` when the call succeeds. On failure, throws an exception or returns a negative error code.

vsource→load_async()

YVSource

Preloads the function cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

vsource→nextVSource()vsource.nextVSource()**YVSource**

Continues the enumeration of voltage sources started using `yFirstVSource()`.

| | |
|-------------------|---|
| <code>js</code> | <code>function nextVSource()</code> |
| <code>php</code> | <code>function nextVSource()</code> |
| <code>cpp</code> | <code>YVSource * nextVSource()</code> |
| <code>m</code> | <code>-(YVSource*) nextVSource</code> |
| <code>pas</code> | <code>function nextVSource(): TYVSource</code> |
| <code>vb</code> | <code>function nextVSource() As YVSource</code> |
| <code>cs</code> | <code>YVSource nextVSource()</code> |
| <code>java</code> | <code>YVSource nextVSource()</code> |
| <code>py</code> | <code>def nextVSource()</code> |

Returns :

a pointer to a `YVSource` object, corresponding to a voltage source currently online, or a `null` pointer if there are no more voltage sources to enumerate.

**vsource→pulse()
vsource.pulse()****YVSource**

Sets device output to a specific voltage, for a specified duration, then brings it automatically to 0V.

| | |
|-------------|---|
| js | function pulse(voltage, ms_duration) |
| php | function pulse(\$voltage, \$ms_duration) |
| cpp | int pulse(int voltage, int ms_duration) |
| m | -(int) pulse : (int) voltage : (int) ms_duration |
| pas | function pulse(voltage: integer, ms_duration: integer): integer |
| vb | function pulse(ByVal voltage As Integer, ByVal ms_duration As Integer) As Integer |
| cs | int pulse(int voltage, int ms_duration) |
| java | int pulse(int voltage, int ms_duration) |
| py | def pulse(voltage, ms_duration) |
| cmd | YVSource target pulse voltage ms_duration |

Parameters :

voltage pulse voltage, in millivolts
ms_duration pulse duration, in milliseconds

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

**vsources->registerValueCallback()
vsources.registerValueCallback()****YVSource**

Registers the callback function that is invoked on every change of advertised value.

```
js function registerValueCallback( callback)
php function registerValueCallback( $callback)
cpp void registerValueCallback( YDisplayUpdateCallback callback)
pas procedure registerValueCallback( callback: TGenericUpdateCallback)
vb procedure registerValueCallback( ByVal callback As GenericUpdateCallback)
cs void registerValueCallback( UpdateCallback callback)
java void registerValueCallback( UpdateCallback callback)
py def registerValueCallback( callback)
m -(void) registerValueCallback : (YFunctionUpdateCallback) callback
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

vsource→set_logicalName()
vsource→setLogicalName()
vsource.set_logicalName()

YVSource

Changes the logical name of the voltage source.

| | |
|------|---|
| js | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YVSource target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the voltage source

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

vsouce→set(userData)**YVSource****vsouce→setUserData()|vsouce.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

```
js function set(userData| userData)
php function set(userData| $data)
cpp void set(userData( void* data)
m -(void) setUserData : (void*) data
pas procedure set(userData( data: Tobject)
vb procedure set(userData( ByVal data As Object)
cs void set(userData( object data)
java void set(userData( Object data)
py def set(userData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

vsource→set_voltage()**YVSource****vsource→setVoltage()vsource.set_voltage()**

Tunes the device output voltage (milliVolts).

```
js   function set_voltage( newval)
php  function set_voltage( $newval)
cpp  int set_voltage( int newval)
m    -(int) setVoltage : (int) newval
pas   function set_voltage( newval: LongInt): integer
vb    function set_voltage( ByVal newval As Integer) As Integer
cs    int set_voltage( int newval)
java  int set_voltage( int newval)
py    def set_voltage( newval)
cmd   YVSource target set_voltage newval
```

Parameters :

newval an integer

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

vsOURCE→voltageMove()vsOURCE.voltageMove()**YVSource**

Performs a smooth move at constant speed toward a given value.

```
js function voltageMove( target, ms_duration)
php function voltageMove( $target, $ms_duration)
cpp int voltageMove( int target, int ms_duration)
m -(int) voltageMove : (int) target : (int) ms_duration
pas function voltageMove( target: integer, ms_duration: integer): integer
vb function voltageMove( ByVal target As Integer,
                           ByVal ms_duration As Integer) As Integer
cs int voltageMove( int target, int ms_duration)
java int voltageMove( int target, int ms_duration)
py def voltageMove( target, ms_duration)
cmd YVSource target voltageMove target ms_duration
```

Parameters :

target new output value at end of transition, in millivolts.

ms_duration transition duration, in milliseconds

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

vsource→wait_async()**YVSource**

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

js `function wait_async(callback, context)`

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result

context caller-specific object that is passed as-is to the callback function

Returns :

nothing :

3.43. WakeUpMonitor function interface

The WakeUpMonitor function handles globally all wake-up sources, as well as automated sleep mode.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_wakeupmonitor.js'></script>
nodejs var yoctolib = require('yoctolib');
var YWakeUpMonitor = yoctolib.YWakeUpMonitor;
require_once('yocto_wakeupmonitor.php');
php #include "yocto_wakeupmonitor.h"
cpp #import "yocto_wakeupmonitor.h"
m uses yocto_wakeupmonitor;
pas yocto_wakeupmonitor.vb
cs yocto_wakeupmonitor.cs
java import com.yoctopuce.YoctoAPI.YWakeUpMonitor;
py from yocto_wakeupmonitor import *

```

Global functions

yFindWakeUpMonitor(func)

Retrieves a monitor for a given identifier.

yFirstWakeUpMonitor()

Starts the enumeration of monitors currently accessible.

YWakeUpMonitor methods

wakeupmonitor→describe()

Returns a short text that describes unambiguously the instance of the monitor in the form TYPE (NAME) = SERIAL . FUNCTIONID.

wakeupmonitor→get_advertisedValue()

Returns the current value of the monitor (no more than 6 characters).

wakeupmonitor→get_errorMessage()

Returns the error message of the latest error with the monitor.

wakeupmonitor→get_errorType()

Returns the numerical error code of the latest error with the monitor.

wakeupmonitor→get_friendlyName()

Returns a global identifier of the monitor in the format MODULE _ NAME . FUNCTION _ NAME.

wakeupmonitor→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

wakeupmonitor→get_functionId()

Returns the hardware identifier of the monitor, without reference to the module.

wakeupmonitor→get_hardwareId()

Returns the unique hardware identifier of the monitor in the form SERIAL . FUNCTIONID.

wakeupmonitor→get_logicalName()

Returns the logical name of the monitor.

wakeupmonitor→get_module()

Gets the YModule object for the device on which the function is located.

wakeupmonitor→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

wakeupmonitor→get_nextWakeUp()

| |
|--|
| Returns the next scheduled wake up date/time (UNIX format) |
| wakeupmonitor→get_powerDuration() |
| Returns the maximal wake up time (in seconds) before automatically going to sleep. |
| wakeupmonitor→get_sleepCountdown() |
| Returns the delay before the next sleep period. |
| wakeupmonitor→get_userData() |
| Returns the value of the userData attribute, as previously stored using method set(userData). |
| wakeupmonitor→get_wakeUpReason() |
| Returns the latest wake up reason. |
| wakeupmonitor→get_wakeUpState() |
| Returns the current state of the monitor |
| wakeupmonitor→isOnline() |
| Checks if the monitor is currently reachable, without raising any error. |
| wakeupmonitor→isOnline_async(callback, context) |
| Checks if the monitor is currently reachable, without raising any error (asynchronous version). |
| wakeupmonitor→load(msValidity) |
| Preloads the monitor cache with a specified validity duration. |
| wakeupmonitor→load_async(msValidity, callback, context) |
| Preloads the monitor cache with a specified validity duration (asynchronous version). |
| wakeupmonitor→nextWakeUpMonitor() |
| Continues the enumeration of monitors started using yFirstWakeUpMonitor(). |
| wakeupmonitor→registerValueCallback(callback) |
| Registers the callback function that is invoked on every change of advertised value. |
| wakeupmonitor→resetSleepCountDown() |
| Resets the sleep countdown. |
| wakeupmonitor→set_logicalName(newval) |
| Changes the logical name of the monitor. |
| wakeupmonitor→set_nextWakeUp(newval) |
| Changes the days of the week when a wake up must take place. |
| wakeupmonitor→set_powerDuration(newval) |
| Changes the maximal wake up time (seconds) before automatically going to sleep. |
| wakeupmonitor→set_sleepCountdown(newval) |
| Changes the delay before the next sleep period. |
| wakeupmonitor→set_userData(data) |
| Stores a user context provided as argument in the userData attribute of the function. |
| wakeupmonitor→sleep(secBeforeSleep) |
| Goes to sleep until the next wake up condition is met, the RTC time must have been set before calling this function. |
| wakeupmonitor→sleepFor(secUntilWakeUp, secBeforeSleep) |
| Goes to sleep for a specific duration or until the next wake up condition is met, the RTC time must have been set before calling this function. |
| wakeupmonitor→sleepUntil(wakeUpTime, secBeforeSleep) |
| Go to sleep until a specific date is reached or until the next wake up condition is met, the RTC time must have been set before calling this function. |
| wakeupmonitor→wait_async(callback, context) |

3. Reference

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

wakeupmonitor→wakeUp()

Forces a wake up.

YWakeUpMonitor.FindWakeUpMonitor()

yFindWakeUpMonitor()

YWakeUpMonitor.FindWakeUpMonitor()

YWakeUpMonitor

Retrieves a monitor for a given identifier.

| | |
|----------------------|---|
| <code>js</code> | <code>function yFindWakeUpMonitor(func)</code> |
| <code>node.js</code> | <code>function FindWakeUpMonitor(func)</code> |
| <code>php</code> | <code>function yFindWakeUpMonitor(\$func)</code> |
| <code>cpp</code> | <code>YWakeUpMonitor* yFindWakeUpMonitor(const string& func)</code> |
| <code>m</code> | <code>YWakeUpMonitor* yFindWakeUpMonitor(NSString* func)</code> |
| <code>pas</code> | <code>function yFindWakeUpMonitor(func: string): TYWakeUpMonitor</code> |
| <code>vb</code> | <code>function yFindWakeUpMonitor(ByVal func As String) As YWakeUpMonitor</code> |
| <code>cs</code> | <code>YWakeUpMonitor FindWakeUpMonitor(string func)</code> |
| <code>java</code> | <code>YWakeUpMonitor FindWakeUpMonitor(String func)</code> |
| <code>py</code> | <code>def FindWakeUpMonitor(func)</code> |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the monitor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YWakeUpMonitor.isOnline()` to test if the monitor is indeed online at a given time. In case of ambiguity when looking for a monitor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the monitor

Returns :

a `YWakeUpMonitor` object allowing you to drive the monitor.

YWakeUpMonitor.FirstWakeUpMonitor()**YWakeUpMonitor****yFirstWakeUpMonitor()****YWakeUpMonitor.FirstWakeUpMonitor()**

Starts the enumeration of monitors currently accessible.

| | |
|--------|--|
| js | function yFirstWakeUpMonitor() |
| nodejs | function FirstWakeUpMonitor() |
| php | function yFirstWakeUpMonitor() |
| cpp | YWakeUpMonitor* yFirstWakeUpMonitor() |
| m | YWakeUpMonitor* yFirstWakeUpMonitor() |
| pas | function yFirstWakeUpMonitor(): TYWakeUpMonitor |
| vb | function yFirstWakeUpMonitor() As YWakeUpMonitor |
| cs | YWakeUpMonitor FirstWakeUpMonitor() |
| java | YWakeUpMonitor FirstWakeUpMonitor() |
| py | def FirstWakeUpMonitor() |

Use the method `YWakeUpMonitor.nextWakeUpMonitor()` to iterate on next monitors.

Returns :

a pointer to a `YWakeUpMonitor` object, corresponding to the first monitor currently online, or a null pointer if there are none.

wakeupmonitor→describe() wakeupmonitor.describe()

YWakeUpMonitor

Returns a short text that describes unambiguously the instance of the monitor in the form TYPE (NAME) =SERIAL.FUNCTIONID.

| | |
|--------|--|
| js | function describe () |
| nodejs | function describe () |
| php | function describe () |
| cpp | string describe () |
| m | -(NSString*) describe |
| pas | function describe (): string |
| vb | function describe () As String |
| cs | string describe () |
| java | String describe () |
| py | def describe () |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the monitor (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

wakeupmonitor→get_advertisedValue()
wakeupmonitor→advertisedValue()
wakeupmonitor.get_advertisedValue()

YWakeUpMonitor

Returns the current value of the monitor (no more than 6 characters).

```
js function get_advertisedValue( )  
nodejs function get_advertisedValue( )  
php function get_advertisedValue( )  
cpp string get_advertisedValue( )  
m -(NSString*) advertisedValue  
pas function get_advertisedValue( ): string  
vb function get_advertisedValue( ) As String  
cs string get_advertisedValue( )  
java String get_advertisedValue( )  
py def get_advertisedValue( )  
cmd YWakeUpMonitor target get_advertisedValue
```

Returns :

a string corresponding to the current value of the monitor (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

**wakeupmonitor→getErrorMessage()
wakeupmonitor→errorMessage()
wakeupmonitor.getErrorMessage()****YWakeUpMonitor**

Returns the error message of the latest error with the monitor.

| | |
|---------|--|
| js | function getErrorMessage() |
| node.js | function getErrorMessage() |
| php | function getErrorMessage() |
| cpp | string getErrorMessage() |
| m | -(NSString*) errorMessage |
| pas | function getErrorMessage() : string |
| vb | function getErrorMessage() As String |
| cs | string getErrorMessage() |
| java | String getErrorMessage() |
| py | def getErrorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the monitor object

wakeupmonitor→get_errorType()
wakeupmonitor→errorType()
wakeupmonitor.get_errorType()**YWakeUpMonitor**

Returns the numerical error code of the latest error with the monitor.

| | |
|--------|---------------------------------------|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType(): YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the monitor object

wakeupmonitor→get_friendlyName()
wakeupmonitor→friendlyName()
wakeupmonitor.get_friendlyName()

YWakeUpMonitor

Returns a global identifier of the monitor in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the monitor if they are defined, otherwise the serial number of the module and the hardware identifier of the monitor (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the monitor using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

wakeupmonitor→get_functionDescriptor()
wakeupmonitor→functionDescriptor()
wakeupmonitor.get_functionDescriptor()

YWakeUpMonitor

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|--------|--|
| js | function get_functionDescriptor() |
| nodejs | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor(): YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

wakeupmonitor→get_functionId()
wakeupmonitor→functionId()
wakeupmonitor.get_functionId()**YWakeUpMonitor**

Returns the hardware identifier of the monitor, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the monitor (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

wakeupmonitor→get_hardwareId()
wakeupmonitor→hardwareId()
wakeupmonitor.get_hardwareId()**YWakeUpMonitor**

Returns the unique hardware identifier of the monitor in the form SERIAL.FUNCTIONID.

| | |
|---------|--------------------------------------|
| js | function get_hardwareId() |
| node.js | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the monitor. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the monitor (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

wakeupmonitor→get_logicalName()
wakeupmonitor→logicalName()
wakeupmonitor.get_logicalName()

YWakeUpMonitor

Returns the logical name of the monitor.

```
js function get_logicalName( )  
nodejs function get_logicalName( )  
php function get_logicalName( )  
cpp string get_logicalName( )  
m -(NSString*) logicalName  
pas function get_logicalName( ): string  
vb function get_logicalName( ) As String  
cs string get_logicalName( )  
java String get_logicalName( )  
py def get_logicalName( )  
cmd YWakeUpMonitor target get_logicalName
```

Returns :

a string corresponding to the logical name of the monitor. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

wakeupmonitor→get_module()**YWakeUpMonitor****wakeupmonitor→module()****wakeupmonitor.get_module()**

Gets the `YModule` object for the device on which the function is located.

| | |
|--------|---|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | <code>YModule * get_module()</code> |
| m | <code>-(YModule*) module</code> |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | <code>YModule get_module()</code> |
| java | <code>YModule get_module()</code> |
| py | <code>def get_module()</code> |

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

wakeupmonitor→get_module_async()**YWakeUpMonitor****wakeupmonitor→module_async()**

Gets the YModule object for the device on which the function is located (asynchronous version).

```
js   function get_module_async( callback, context)
nodejs function get_module_async( callback, context)
```

If the function cannot be located on any module, the returned YModule object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested YModule object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

wakeupmonitor→get_nextWakeUp()
wakeupmonitor→nextWakeUp()
wakeupmonitor.get_nextWakeUp()**YWakeUpMonitor**

Returns the next scheduled wake up date/time (UNIX format)

| | |
|--------|------------------------------------|
| js | function get_nextWakeUp() |
| nodejs | function get_nextWakeUp() |
| php | function get_nextWakeUp() |
| cpp | s64 get_nextWakeUp() |
| m | -(s64) nextWakeUp |
| pas | function get_nextWakeUp(): int64 |
| vb | function get_nextWakeUp() As Long |
| cs | long get_nextWakeUp() |
| java | long get_nextWakeUp() |
| py | def get_nextWakeUp() |

Returns :

an integer corresponding to the next scheduled wake up date/time (UNIX format)

On failure, throws an exception or returns Y_NEXTWAKEUP_INVALID.

wakeupmonitor→get_powerDuration()
wakeupmonitor→powerDuration()
wakeupmonitor.get_powerDuration()**YWakeUpMonitor**

Returns the maximal wake up time (in seconds) before automatically going to sleep.

| | |
|---------|---|
| js | function get_powerDuration() |
| node.js | function get_powerDuration() |
| php | function get_powerDuration() |
| cpp | int get_powerDuration() |
| m | -(int) powerDuration |
| pas | function get_powerDuration() : LongInt |
| vb | function get_powerDuration() As Integer |
| cs | int get_powerDuration() |
| java | int get_powerDuration() |
| py | def get_powerDuration() |
| cmd | YWakeUpMonitor target get_powerDuration |

Returns :

an integer corresponding to the maximal wake up time (in seconds) before automatically going to sleep

On failure, throws an exception or returns **Y_POWERDURATION_INVALID**.

wakeupmonitor→get_sleepCountdown()
wakeupmonitor→sleepCountdown()
wakeupmonitor.get_sleepCountdown()**YWakeUpMonitor**

Returns the delay before the next sleep period.

| | |
|--------|---|
| js | function get_sleepCountdown() |
| nodejs | function get_sleepCountdown() |
| php | function get_sleepCountdown() |
| cpp | int get_sleepCountdown() |
| m | -(int) sleepCountdown |
| pas | function get_sleepCountdown(): LongInt |
| vb | function get_sleepCountdown() As Integer |
| cs | int get_sleepCountdown() |
| java | int get_sleepCountdown() |
| py | def get_sleepCountdown() |
| cmd | YWakeUpMonitor target get_sleepCountdown |

Returns :

an integer corresponding to the delay before the next sleep period

On failure, throws an exception or returns Y_SLEEPCOUNTDOWN_INVALID.

wakeupmonitor→get(userData)
wakeupmonitor→userData()
wakeupmonitor.get(userData)

YWakeUpMonitor

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|---|
| js | function get(userData) |
| nodejs | function get(userData) |
| php | function get(userData) |
| cpp | void * get(userData) |
| m | -(void*) userData |
| pas | function get(userData) : Tobject |
| vb | function get(userData) As Object |
| cs | object get(userData) |
| java | Object get(userData) |
| py | def get(userData) |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

wakeupmonitor→get_wakeUpReason()
wakeupmonitor→wakeUpReason()
wakeupmonitor.get_wakeUpReason()

YWakeUpMonitor

Returns the latest wake up reason.

| | |
|--------|---|
| js | function get_wakeUpReason() |
| nodejs | function get_wakeUpReason() |
| php | function get_wakeUpReason() |
| cpp | Y_WAKEUPREASON_enum get_wakeUpReason() |
| m | -(Y_WAKEUPREASON_enum) wakeUpReason |
| pas | function get_wakeUpReason(): Integer |
| vb | function get_wakeUpReason() As Integer |
| cs | int get_wakeUpReason() |
| java | int get_wakeUpReason() |
| py | def get_wakeUpReason() |
| cmd | YWakeUpMonitor target get_wakeUpReason |

Returns :

a value among Y_WAKEUPREASON_USBPOWER, Y_WAKEUPREASON_EXTPOWER,
Y_WAKEUPREASON_ENDOFSLEEP, Y_WAKEUPREASON_EXTSIG1,
Y_WAKEUPREASON_EXTSIG2, Y_WAKEUPREASON_EXTSIG3,
Y_WAKEUPREASON_EXTSIG4, Y_WAKEUPREASON_SCHEDULE1,
Y_WAKEUPREASON_SCHEDULE2, Y_WAKEUPREASON_SCHEDULE3,
Y_WAKEUPREASON_SCHEDULE4, Y_WAKEUPREASON_SCHEDULE5 and
Y_WAKEUPREASON_SCHEDULE6 corresponding to the latest wake up reason

On failure, throws an exception or returns Y_WAKEUPREASON_INVALID.

wakeupmonitor→get_wakeUpState()
wakeupmonitor→wakeUpState()
wakeupmonitor.get_wakeUpState()

YWakeUpMonitor

Returns the current state of the monitor

| | |
|---------|---|
| js | function get_wakeUpState() |
| node.js | function get_wakeUpState() |
| php | function get_wakeUpState() |
| cpp | Y_WAKEUPSTATE_enum get_wakeUpState() |
| m | -(Y_WAKEUPSTATE_enum) wakeUpState |
| pas | function get_wakeUpState() : Integer |
| vb | function get_wakeUpState() As Integer |
| cs | int get_wakeUpState() |
| java | int get_wakeUpState() |
| py | def get_wakeUpState() |

Returns :

either Y_WAKEUPSTATE_SLEEPING or Y_WAKEUPSTATE_AWAKE, according to the current state of the monitor

On failure, throws an exception or returns Y_WAKEUPSTATE_INVALID.

wakeupmonitor→isOnline()wakeupmonitor.isOnline()**YWakeUpMonitor**

Checks if the monitor is currently reachable, without raising any error.

| | |
|--------|---------------------------------------|
| js | function isOnline() |
| nodejs | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the monitor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the monitor.

Returns :

true if the monitor can be reached, and false otherwise

wakeupmonitor→isOnline_async()**YWakeUpMonitor**

Checks if the monitor is currently reachable, without raising any error (asynchronous version).

| | |
|---------|---|
| js | function isOnline_async(callback, context) |
| node.js | function isOnline_async(callback, context) |

If there is a cached value for the monitor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

wakeupmonitor→load()wakeupmonitor.load()**YWakeUpMonitor**

Preloads the monitor cache with a specified validity duration.

| | |
|--------|--|
| js | function load(msValidity) |
| nodejs | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | - (YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

wakeupmonitor→load_async()

YWakeUpMonitor

Preloads the monitor cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

wakeupmonitor→nextWakeUpMonitor()
wakeupmonitor.nextWakeUpMonitor()**YWakeUpMonitor**

Continues the enumeration of monitors started using `yFirstWakeUpMonitor()`.

| | |
|----------------------|--|
| <code>js</code> | <code>function nextWakeUpMonitor()</code> |
| <code>node.js</code> | <code>function nextWakeUpMonitor()</code> |
| <code>php</code> | <code>function nextWakeUpMonitor()</code> |
| <code>cpp</code> | <code>YWakeUpMonitor * nextWakeUpMonitor()</code> |
| <code>m</code> | <code>-(YWakeUpMonitor*) nextWakeUpMonitor</code> |
| <code>pas</code> | <code>function nextWakeUpMonitor(): TYWakeUpMonitor</code> |
| <code>vb</code> | <code>function nextWakeUpMonitor() As YWakeUpMonitor</code> |
| <code>cs</code> | <code>YWakeUpMonitor nextWakeUpMonitor()</code> |
| <code>java</code> | <code>YWakeUpMonitor nextWakeUpMonitor()</code> |
| <code>py</code> | <code>def nextWakeUpMonitor()</code> |

Returns :

a pointer to a `YWakeUpMonitor` object, corresponding to a monitor currently online, or a null pointer if there are no more monitors to enumerate.

wakeupmonitor→registerValueCallback() wakeupmonitor.registerValueCallback()

YWakeUpMonitor

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback)
nodejs function registerValueCallback( callback)
php  function registerValueCallback( $callback)
cpp   int registerValueCallback( YWakeUpMonitorValueCallback callback)
m     -(int) registerValueCallback : (YWakeUpMonitorValueCallback) callback
pas   function registerValueCallback( callback: TYWakeUpMonitorValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs   int registerValueCallback( ValueCallback callback)
java  int registerValueCallback( UpdateCallback callback)
py    def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

wakeupmonitor→resetSleepCountDown()
wakeupmonitor.resetSleepCountDown()**YWakeUpMonitor**

Resets the sleep countdown.

| | |
|---------|---|
| js | function resetSleepCountDown() |
| node.js | function resetSleepCountDown() |
| php | function resetSleepCountDown() |
| cpp | int resetSleepCountDown() |
| m | - (int) resetSleepCountDown |
| pas | function resetSleepCountDown(): LongInt |
| vb | function resetSleepCountDown() As Integer |
| cs | int resetSleepCountDown() |
| java | int resetSleepCountDown() |
| py | def resetSleepCountDown() |
| cmd | YWakeUpMonitor target resetSleepCountDown |

Returns :

YAPI_SUCCESS if the call succeeds. On failure, throws an exception or returns a negative error code.

wakeupmonitor→set_logicalName()
wakeupmonitor→setLogicalName()
wakeupmonitor.set_logicalName()

YWakeUpMonitor

Changes the logical name of the monitor.

| | |
|----------------|---|
| js | function set_logicalName(newval) |
| node.js | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YWakeUpMonitor target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the monitor.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

wakeupmonitor→set_nextWakeUp()
wakeupmonitor→setNextWakeUp()
wakeupmonitor.set_nextWakeUp()

YWakeUpMonitor

Changes the days of the week when a wake up must take place.

| | |
|--------|---|
| js | function set_nextWakeUp(newval) |
| nodejs | function set_nextWakeUp(newval) |
| php | function set_nextWakeUp(\$newval) |
| cpp | int set_nextWakeUp(s64 newval) |
| m | -(int) setNextWakeUp : (s64) newval |
| pas | function set_nextWakeUp(newval: int64): integer |
| vb | function set_nextWakeUp(ByVal newval As Long) As Integer |
| cs | int set_nextWakeUp(long newval) |
| java | int set_nextWakeUp(long newval) |
| py | def set_nextWakeUp(newval) |
| cmd | YWakeUpMonitor target set_nextWakeUp newval |

Parameters :

newval an integer corresponding to the days of the week when a wake up must take place

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupmonitor→set_powerDuration()
wakeupmonitor→setPowerDuration()
wakeupmonitor.set_powerDuration()

YWakeUpMonitor

Changes the maximal wake up time (seconds) before automatically going to sleep.

| | |
|---------------|--|
| js | function set_powerDuration(newval) |
| nodejs | function set_powerDuration(newval) |
| php | function set_powerDuration(\$newval) |
| cpp | int set_powerDuration(int newval) |
| m | -(int) setPowerDuration : (int) newval |
| pas | function set_powerDuration(newval: LongInt): integer |
| vb | function set_powerDuration(ByVal newval As Integer) As Integer |
| cs | int set_powerDuration(int newval) |
| java | int set_powerDuration(int newval) |
| py | def set_powerDuration(newval) |
| cmd | YWakeUpMonitor target set_powerDuration newval |

Parameters :

newval an integer corresponding to the maximal wake up time (seconds) before automatically going to sleep

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupmonitor→set_sleepCountdown()
wakeupmonitor→setSleepCountdown()
wakeupmonitor.set_sleepCountdown()

YWakeUpMonitor

Changes the delay before the next sleep period.

```
js function set_sleepCountdown( newval)
nodejs function set_sleepCountdown( newval)
php function set_sleepCountdown( $newval)
cpp int set_sleepCountdown( int newval)
m -(int) setSleepCountdown : (int) newval
pas function set_sleepCountdown( newval: LongInt): integer
vb function set_sleepCountdown( ByVal newval As Integer) As Integer
cs int set_sleepCountdown( int newval)
java int set_sleepCountdown( int newval)
py def set_sleepCountdown( newval)
cmd YWakeUpMonitor target set_sleepCountdown newval
```

Parameters :

newval an integer corresponding to the delay before the next sleep period

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupmonitor→**set(userData)**
wakeupmonitor→**setUserData()**
wakeupmonitor.set(userData)

YWakeUpMonitor

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|---|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData \$data) |
| cpp | void set(userData void* data) |
| m | -(void) setUserData : (void*) data |
| pas | procedure set(userData data: Tobject) |
| vb | procedure set(userData ByVal data As Object) |
| cs | void set(userData object data) |
| java | void set(userData Object data) |
| py | def set(userData data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

wakeupmonitor→sleep()wakeupmonitor.sleep()**YWakeUpMonitor**

Goes to sleep until the next wake up condition is met, the RTC time must have been set before calling this function.

| | |
|--------|--|
| js | function sleep(secBeforeSleep) |
| nodejs | function sleep(secBeforeSleep) |
| php | function sleep(\$secBeforeSleep) |
| cpp | int sleep(int secBeforeSleep) |
| m | - (int) sleep : (int) secBeforeSleep |
| pas | function sleep(secBeforeSleep: LongInt): LongInt |
| vb | function sleep() As Integer |
| cs | int sleep(int secBeforeSleep) |
| java | int sleep(int secBeforeSleep) |
| py | def sleep(secBeforeSleep) |
| cmd | YWakeUpMonitor target sleep secBeforeSleep |

Parameters :

secBeforeSleep number of seconds before going into sleep mode,

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

wakeupmonitor→sleepFor() wakeupmonitor.sleepFor()

YWakeUpMonitor

Goes to sleep for a specific duration or until the next wake up condition is met, the RTC time must have been set before calling this function.

```

js   function sleepFor( secUntilWakeUp, secBeforeSleep)
nodejs function sleepFor( secUntilWakeUp, secBeforeSleep)
php  function sleepFor( $secUntilWakeUp, $secBeforeSleep)
cpp   int sleepFor( int secUntilWakeUp, int secBeforeSleep)
m    -(int) sleepFor : (int) secUntilWakeUp : (int) secBeforeSleep
pas   function sleepFor( secUntilWakeUp: LongInt,
                        secBeforeSleep: LongInt): LongInt

vb   function sleepFor( ) As Integer
cs   int sleepFor( int secUntilWakeUp, int secBeforeSleep)
java int sleepFor( int secUntilWakeUp, int secBeforeSleep)
py   def sleepFor( secUntilWakeUp, secBeforeSleep)
cmd  YWakeUpMonitor target sleepFor secUntilWakeUp secBeforeSleep

```

The count down before sleep can be canceled with resetSleepCountDown.

Parameters :

secUntilWakeUp sleep duration, in secondes
secBeforeSleep number of seconds before going into sleep mode

Returns :

YAPI_SUCCESS if the call succeeds. On failure, throws an exception or returns a negative error code.

wakeupmonitor→sleepUntil() wakeupmonitor.sleepUntil()

YWakeUpMonitor

Go to sleep until a specific date is reached or until the next wake up condition is met, the RTC time must have been set before calling this function.

```

js   function sleepUntil( wakeUpTime, secBeforeSleep)
nodejs function sleepUntil( wakeUpTime, secBeforeSleep)
php  function sleepUntil( $wakeUpTime, $secBeforeSleep)
cpp   int sleepUntil( int wakeUpTime, int secBeforeSleep)
m    -(int) sleepUntil : (int) wakeUpTime : (int) secBeforeSleep
pas   function sleepUntil( wakeUpTime: LongInt,
                           secBeforeSleep: LongInt): LongInt
vb    function sleepUntil( ) As Integer
cs    int sleepUntil( int wakeUpTime, int secBeforeSleep)
java  int sleepUntil( int wakeUpTime, int secBeforeSleep)
py    def sleepUntil( wakeUpTime, secBeforeSleep)
cmd   YWakeUpMonitor target sleepUntil wakeUpTime secBeforeSleep

```

The count down before sleep can be canceled with resetSleepCountDown.

Parameters :

wakeUpTime wake-up datetime (UNIX format)
secBeforeSleep number of seconds before going into sleep mode

Returns :

YAPI_SUCCESS if the call succeeds. On failure, throws an exception or returns a negative error code.

wakeupmonitor→wait_async()

YWakeUpMonitor

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

`js` `function wait_async(callback, context)`

`nodejs` `function wait_async(callback, context)`

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

wakeupmonitor→wakeUp()wakeupmonitor.wakeUp()**YWakeUpMonitor**

Forces a wake up.

| | |
|--------|--------------------------------------|
| js | function wakeUp() |
| nodejs | function wakeUp() |
| php | function wakeUp() |
| cpp | int wakeUp() |
| m | - (int) wakeUp |
| pas | function wakeUp(): LongInt |
| vb | function wakeUp() As Integer |
| cs | int wakeUp() |
| java | int wakeUp() |
| py | def wakeUp() |
| cmd | YWakeUpMonitor target wakeUp |

3.44. WakeUpSchedule function interface

The WakeUpSchedule function implements a wake up condition. The wake up time is specified as a set of months and/or days and/or hours and/or minutes when the wake up should happen.

In order to use the functions described here, you should include:

| | |
|--------|--|
| js | <script type='text/javascript' src='yocto_wakeupschedule.js'></script> |
| nodejs | var yoctolib = require('yoctolib'); |
| | var YWakeUpSchedule = yoctolib.YWakeUpSchedule; |
| php | require_once('yocto_wakeupschedule.php'); |
| cpp | #include "yocto_wakeupschedule.h" |
| m | #import "yocto_wakeupschedule.h" |
| pas | uses yocto_wakeupschedule; |
| vb | yocto_wakeupschedule.vb |
| cs | yocto_wakeupschedule.cs |
| java | import com.yoctopuce.YoctoAPI.YWakeUpSchedule; |
| py | from yocto_wakeupschedule import * |

Global functions

yFindWakeUpSchedule(func)

Retrieves a wake up schedule for a given identifier.

yFirstWakeUpSchedule()

Starts the enumeration of wake up schedules currently accessible.

YWakeUpSchedule methods

wakeupschedule→describe()

Returns a short text that describes unambiguously the instance of the wake up schedule in the form
TYPE (NAME) = SERIAL . FUNCTIONID.

wakeupschedule→get_advertisedValue()

Returns the current value of the wake up schedule (no more than 6 characters).

wakeupschedule→get_errorMessage()

Returns the error message of the latest error with the wake up schedule.

wakeupschedule→get_errorType()

Returns the numerical error code of the latest error with the wake up schedule.

wakeupschedule→get_friendlyName()

Returns a global identifier of the wake up schedule in the format MODULE_NAME . FUNCTION_NAME.

wakeupschedule→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

wakeupschedule→get_functionId()

Returns the hardware identifier of the wake up schedule, without reference to the module.

wakeupschedule→get_hardwareId()

Returns the unique hardware identifier of the wake up schedule in the form SERIAL . FUNCTIONID.

wakeupschedule→get_hours()

Returns the hours scheduled for wake up.

wakeupschedule→get_logicalName()

Returns the logical name of the wake up schedule.

wakeupschedule→get_minutes()

Returns all the minutes of each hour that are scheduled for wake up.

wakeupschedule→get_minutesA()

3. Reference

Returns the minutes in the 00-29 interval of each hour scheduled for wake up.

wakeupschedule→get_minutesB()

Returns the minutes in the 30-59 interval of each hour scheduled for wake up.

wakeupschedule→get_module()

Gets the YModule object for the device on which the function is located.

wakeupschedule→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

wakeupschedule→get_monthDays()

Returns the days of the month scheduled for wake up.

wakeupschedule→get_months()

Returns the months scheduled for wake up.

wakeupschedule→get_nextOccurrence()

Returns the date/time (seconds) of the next wake up occurrence

wakeupschedule→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

wakeupschedule→get_weekDays()

Returns the days of the week scheduled for wake up.

wakeupschedule→isOnline()

Checks if the wake up schedule is currently reachable, without raising any error.

wakeupschedule→isOnline_async(callback, context)

Checks if the wake up schedule is currently reachable, without raising any error (asynchronous version).

wakeupschedule→load(msValidity)

Preloads the wake up schedule cache with a specified validity duration.

wakeupschedule→load_async(msValidity, callback, context)

Preloads the wake up schedule cache with a specified validity duration (asynchronous version).

wakeupschedule→nextWakeUpSchedule()

Continues the enumeration of wake up schedules started using yFirstWakeUpSchedule().

wakeupschedule→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

wakeupschedule→set_hours(newval)

Changes the hours when a wake up must take place.

wakeupschedule→set_logicalName(newval)

Changes the logical name of the wake up schedule.

wakeupschedule→set_minutes(bitmap)

Changes all the minutes where a wake up must take place.

wakeupschedule→set_minutesA(newval)

Changes the minutes in the 00-29 interval when a wake up must take place.

wakeupschedule→set_minutesB(newval)

Changes the minutes in the 30-59 interval when a wake up must take place.

wakeupschedule→set_monthDays(newval)

Changes the days of the month when a wake up must take place.

wakeupschedule→set_months(newval)

Changes the months when a wake up must take place.

wakeupschedule→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

wakeupschedule→set_weekDays(newval)

Changes the days of the week when a wake up must take place.

wakeupschedule→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YWakeUpSchedule.FindWakeUpSchedule()

yFindWakeUpSchedule()

YWakeUpSchedule.FindWakeUpSchedule()

YWakeUpSchedule

Retrieves a wake up schedule for a given identifier.

| | |
|--------|---|
| js | function yFindWakeUpSchedule(func) |
| nodejs | function FindWakeUpSchedule(func) |
| php | function yFindWakeUpSchedule(\$func) |
| cpp | YWakeUpSchedule* yFindWakeUpSchedule(const string& func) |
| m | YWakeUpSchedule* yFindWakeUpSchedule(NSString* func) |
| pas | function yFindWakeUpSchedule(func: string): TYWakeUpSchedule |
| vb | function yFindWakeUpSchedule(ByVal func As String) As YWakeUpSchedule |
| cs | YWakeUpSchedule FindWakeUpSchedule(string func) |
| java | YWakeUpSchedule FindWakeUpSchedule(String func) |
| py | def FindWakeUpSchedule(func) |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the wake up schedule is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YWakeUpSchedule.isOnline()` to test if the wake up schedule is indeed online at a given time. In case of ambiguity when looking for a wake up schedule by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the wake up schedule

Returns :

a `YWakeUpSchedule` object allowing you to drive the wake up schedule.

YWakeUpSchedule.FirstWakeUpSchedule()**YWakeUpSchedule****yFirstWakeUpSchedule()****YWakeUpSchedule.FirstWakeUpSchedule()**

Starts the enumeration of wake up schedules currently accessible.

| | |
|----------------------|---|
| <code>js</code> | function yFirstWakeUpSchedule() |
| <code>node.js</code> | function FirstWakeUpSchedule() |
| <code>php</code> | function yFirstWakeUpSchedule() |
| <code>cpp</code> | YWakeUpSchedule* yFirstWakeUpSchedule() |
| <code>m</code> | YWakeUpSchedule* yFirstWakeUpSchedule() |
| <code>pas</code> | function yFirstWakeUpSchedule() : TYWakeUpSchedule |
| <code>vb</code> | function yFirstWakeUpSchedule() As YWakeUpSchedule |
| <code>cs</code> | YWakeUpSchedule FirstWakeUpSchedule() |
| <code>java</code> | YWakeUpSchedule FirstWakeUpSchedule() |
| <code>py</code> | def FirstWakeUpSchedule() |

Use the method `YWakeUpSchedule.nextWakeUpSchedule()` to iterate on next wake up schedules.

Returns :

a pointer to a `YWakeUpSchedule` object, corresponding to the first wake up schedule currently online, or a null pointer if there are none.

wakeupschedule→describe()
wakeupschedule.describe()**YWakeUpSchedule**

Returns a short text that describes unambiguously the instance of the wake up schedule in the form
TYPE (NAME)=SERIAL . FUNCTIONID.

| | |
|--------|--|
| js | function describe () |
| nodejs | function describe () |
| php | function describe () |
| cpp | string describe () |
| m | - (NSString*) describe |
| pas | function describe (): string |
| vb | function describe () As String |
| cs | string describe () |
| java | String describe () |
| py | def describe () |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the wake up schedule (ex:
Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

wakeupschedule→get_advertisedValue()
wakeupschedule→advertisedValue()
wakeupschedule.get_advertisedValue()

YWakeUpSchedule

Returns the current value of the wake up schedule (no more than 6 characters).

| | |
|---------------|---|
| js | function get_advertisedValue() |
| nodejs | function get_advertisedValue() |
| php | function get_advertisedValue() |
| cpp | string get_advertisedValue() |
| m | -(NSString*) advertisedValue |
| pas | function get_advertisedValue() : string |
| vb | function get_advertisedValue() As String |
| cs | string get_advertisedValue() |
| java | String get_advertisedValue() |
| py | def get_advertisedValue() |
| cmd | YWakeUpSchedule target get_advertisedValue |

Returns :

a string corresponding to the current value of the wake up schedule (no more than 6 characters). On failure, throws an exception or returns **Y_ADVERTISEDVALUE_INVALID**.

wakeupschedule→get_errorMessage()
wakeupschedule→errorMessage()
wakeupschedule.get_errorMessage()**YWakeUpSchedule**

Returns the error message of the latest error with the wake up schedule.

| | |
|--------|--|
| js | function get_errorMessage() |
| nodejs | function get_errorMessage() |
| php | function get_errorMessage() |
| cpp | string get_errorMessage() |
| m | -(NSString*) errorMessage |
| pas | function get_errorMessage(): string |
| vb | function get_errorMessage() As String |
| cs | string get_errorMessage() |
| java | String get_errorMessage() |
| py | def get_errorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the wake up schedule object

wakeupschedule→get_errorType()
wakeupschedule→errorType()
wakeupschedule.get_errorType()

YWakeUpSchedule

Returns the numerical error code of the latest error with the wake up schedule.

| | |
|---------|--|
| js | function get_errorType() |
| node.js | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType(): YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the wake up schedule object

wakeupschedule→get_friendlyName()
wakeupschedule→friendlyName()
wakeupschedule.get_friendlyName()

YWakeUpSchedule

Returns a global identifier of the wake up schedule in the format MODULE_NAME.FUNCTION_NAME.

```
js function get_friendlyName( )  
nodejs function get_friendlyName( )  
php function get_friendlyName( )  
cpp string get_friendlyName( )  
m -(NSString*) friendlyName  
cs string get_friendlyName( )  
java String get_friendlyName( )  
py def get_friendlyName( )
```

The returned string uses the logical names of the module and of the wake up schedule if they are defined, otherwise the serial number of the module and the hardware identifier of the wake up schedule (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the wake up schedule using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

wakeupschedule→get_functionDescriptor()
wakeupschedule→functionDescriptor()
wakeupschedule.get_functionDescriptor()

YWakeUpSchedule

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

wakeupschedule→get_functionId()
wakeupschedule→functionId()
wakeupschedule.get_functionId()**YWakeUpSchedule**

Returns the hardware identifier of the wake up schedule, without reference to the module.

| | |
|--------|---|
| js | function get_functionId() |
| nodejs | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the wake up schedule (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

wakeupschedule→get_hwid()
wakeupschedule→hardwareId()
wakeupschedule.get_hwid()

YWakeUpSchedule

Returns the unique hardware identifier of the wake up schedule in the form SERIAL.FUNCTIONID.

```
js function get_hwid( )  
nodejs function get_hwid( )  
php function get_hwid( )  
cpp string get_hwid( )  
m -(NSString*) hardwareId  
vb function get_hwid( ) As String  
cs string get_hwid( )  
java String get_hwid( )  
py def get_hwid( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the wake up schedule. (for example RELAY01-123456.relay1)

Returns :

a string that uniquely identifies the wake up schedule (ex: RELAY01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

wakeupschedule→get_hours()
wakeupschedule→hours()
wakeupschedule.get_hours()**YWakeUpSchedule**

Returns the hours scheduled for wake up.

| | |
|--------|---|
| js | function get_hours() |
| nodejs | function get_hours() |
| php | function get_hours() |
| cpp | int get_hours() |
| m | -(int) hours |
| pas | function get_hours() : LongInt |
| vb | function get_hours() As Integer |
| cs | int get_hours() |
| java | int get_hours() |
| py | def get_hours() |
| cmd | YWakeUpSchedule target get_hours |

Returns :

an integer corresponding to the hours scheduled for wake up

On failure, throws an exception or returns Y_HOURS_INVALID.

wakeupschedule→get_logicalName()
wakeupschedule→logicalName()
wakeupschedule.get_logicalName()

YWakeUpSchedule

Returns the logical name of the wake up schedule.

```
js function get_logicalName( )  
nodejs function get_logicalName( )  
php function get_logicalName( )  
cpp string get_logicalName( )  
m -(NSString*) logicalName  
pas function get_logicalName( ): string  
vb function get_logicalName( ) As String  
cs string get_logicalName( )  
java String get_logicalName( )  
py def get_logicalName( )  
cmd YWakeUpSchedule target get_logicalName
```

Returns :

a string corresponding to the logical name of the wake up schedule. On failure, throws an exception or returns `Y_LOGICALNAME_INVALID`.

wakeupschedule→get_minutes()
wakeupschedule→minutes()
wakeupschedule.get_minutes()

YWakeUpSchedule

Returns all the minutes of each hour that are scheduled for wake up.

| | |
|--------|------------------------------------|
| js | function get_minutes() |
| nodejs | function get_minutes() |
| php | function get_minutes() |
| cpp | s64 get_minutes() |
| m | -(s64) minutes |
| pas | function get_minutes(): int64 |
| vb | function get_minutes() As Long |
| cs | long get_minutes() |
| java | long get_minutes() |
| py | def get_minutes() |
| cmd | YWakeUpSchedule target get_minutes |

wakeupschedule→get_minutesA()
wakeupschedule→minutesA()
wakeupschedule.get_minutesA()

YWakeUpSchedule

Returns the minutes in the 00-29 interval of each hour scheduled for wake up.

| | |
|--------|-------------------------------------|
| js | function get_minutesA() |
| nodejs | function get_minutesA() |
| php | function get_minutesA() |
| cpp | int get_minutesA() |
| m | -(int) minutesA |
| pas | function get_minutesA(): LongInt |
| vb | function get_minutesA() As Integer |
| cs | int get_minutesA() |
| java | int get_minutesA() |
| py | def get_minutesA() |
| cmd | YWakeUpSchedule target get_minutesA |

Returns :

an integer corresponding to the minutes in the 00-29 interval of each hour scheduled for wake up

On failure, throws an exception or returns Y_MINUTESA_INVALID.

wakeupschedule→get_minutesB()
wakeupschedule→minutesB()
wakeupschedule.get_minutesB()

YWakeUpSchedule

Returns the minutes in the 30-59 interval of each hour scheduled for wake up.

| | |
|--------|-------------------------------------|
| js | function get_minutesB() |
| nodejs | function get_minutesB() |
| php | function get_minutesB() |
| cpp | int get_minutesB() |
| m | -(int) minutesB |
| pas | function get_minutesB(): LongInt |
| vb | function get_minutesB() As Integer |
| cs | int get_minutesB() |
| java | int get_minutesB() |
| py | def get_minutesB() |
| cmd | YWakeUpSchedule target get_minutesB |

Returns :

an integer corresponding to the minutes in the 30-59 interval of each hour scheduled for wake up

On failure, throws an exception or returns Y_MINUTESB_INVALID.

wakeupschedule→get_module()
wakeupschedule→module()
wakeupschedule.get_module()

YWakeUpSchedule

Gets the **YModule** object for the device on which the function is located.

| | |
|--------|---|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of **YModule** is not shown as on-line.

Returns :

an instance of **YModule**

wakeupschedule→get_module_async()**YWakeUpSchedule****wakeupschedule→module_async()**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context)
node.js function get_module_async( callback, context)
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

wakeupschedule→get_monthDays()
wakeupschedule→monthDays()
wakeupschedule.get_monthDays()

YWakeUpSchedule

Returns the days of the month scheduled for wake up.

| | |
|---------|--------------------------------------|
| js | function get_monthDays() |
| node.js | function get_monthDays() |
| php | function get_monthDays() |
| cpp | int get_monthDays() |
| m | -(int) monthDays |
| pas | function get_monthDays(): LongInt |
| vb | function get_monthDays() As Integer |
| cs | int get_monthDays() |
| java | int get_monthDays() |
| py | def get_monthDays() |
| cmd | YWakeUpSchedule target get_monthDays |

Returns :

an integer corresponding to the days of the month scheduled for wake up

On failure, throws an exception or returns Y_MONTHDAYS_INVALID.

wakeupschedule→get_months()
wakeupschedule→months()
wakeupschedule.get_months()**YWakeUpSchedule**

Returns the months scheduled for wake up.

| | |
|--------|--|
| js | function get_months() |
| nodejs | function get_months() |
| php | function get_months() |
| cpp | int get_months() |
| m | -(int) months |
| pas | function get_months() : LongInt |
| vb | function get_months() As Integer |
| cs | int get_months() |
| java | int get_months() |
| py | def get_months() |
| cmd | YWakeUpSchedule target get_months |

Returns :

an integer corresponding to the months scheduled for wake up

On failure, throws an exception or returns Y_MONTHS_INVALID.

wakeupschedule→get_nextOccurence()
wakeupschedule→nextOccurence()
wakeupschedule.get_nextOccurence()

YWakeUpSchedule

Returns the date/time (seconds) of the next wake up occurence

| | |
|---------------|--|
| js | function get_nextOccurence() |
| nodejs | function get_nextOccurence() |
| php | function get_nextOccurence() |
| cpp | s64 get_nextOccurence() |
| m | -(s64) nextOccurence |
| pas | function get_nextOccurence() : int64 |
| vb | function get_nextOccurence() As Long |
| cs | long get_nextOccurence() |
| java | long get_nextOccurence() |
| py | def get_nextOccurence() |

Returns :

an integer corresponding to the date/time (seconds) of the next wake up occurence

On failure, throws an exception or returns **Y_NEXTOCCURENCE_INVALID**.

wakeupschedule→get(userData)
wakeupschedule→userData()
wakeupschedule.get(userData)**YWakeUpSchedule**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|---|
| js | function get(userData) { |
| nodejs | function get(userData) { |
| php | function get(userData) { |
| cpp | void * get(userData) { |
| m | -(void*) userData |
| pas | function get(userData) : Tobject { |
| vb | function get(userData) As Object |
| cs | object get(userData) { |
| java | Object get(userData) { |
| py | def get(userData) : |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

wakeupschedule→get_weekDays()
wakeupschedule→weekDays()
wakeupschedule.get_weekDays()

YWakeUpSchedule

Returns the days of the week scheduled for wake up.

| | |
|--------|-------------------------------------|
| js | function get_weekDays() |
| nodejs | function get_weekDays() |
| php | function get_weekDays() |
| cpp | int get_weekDays() |
| m | -(int) weekDays |
| pas | function get_weekDays(): LongInt |
| vb | function get_weekDays() As Integer |
| cs | int get_weekDays() |
| java | int get_weekDays() |
| py | def get_weekDays() |
| cmd | YWakeUpSchedule target get_weekDays |

Returns :

an integer corresponding to the days of the week scheduled for wake up

On failure, throws an exception or returns Y_WEEKDAYS_INVALID.

wakeupschedule→isOnline()
wakeupschedule.isOnline()**YWakeUpSchedule**

Checks if the wake up schedule is currently reachable, without raising any error.

| | |
|---------|---------------------------------------|
| js | function isOnline() |
| node.js | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | -BOOL isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the wake up schedule in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the wake up schedule.

Returns :

true if the wake up schedule can be reached, and false otherwise

wakeupschedule→isOnline_async()**YWakeUpSchedule**

Checks if the wake up schedule is currently reachable, without raising any error (asynchronous version).

```
js   function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the wake up schedule in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

wakeupschedule→load()wakeupschedule.load()**YWakeUpSchedule**

Preloads the wake up schedule cache with a specified validity duration.

| | |
|--------|--|
| js | function load(msValidity) |
| nodejs | function load(msValidity) |
| php | function load(\$msValidity) |
| cpp | YRETCODE load(int msValidity) |
| m | - (YRETCODE) load : (int) msValidity |
| pas | function load(msValidity: integer): YRETCODE |
| vb | function load(ByVal msValidity As Integer) As YRETCODE |
| cs | YRETCODE load(int msValidity) |
| java | int load(long msValidity) |
| py | def load(msValidity) |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

wakeupschedule→load_async()**YWakeUpSchedule**

Preloads the wake up schedule cache with a specified validity duration (asynchronous version).

```
js  function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

wakeupschedule→nextWakeUpSchedule()
wakeupschedule.nextWakeUpSchedule()**YWakeUpSchedule**

Continues the enumeration of wake up schedules started using `yFirstWakeUpSchedule()`.

| | |
|----------------------|--|
| <code>js</code> | <code>function nextWakeUpSchedule()</code> |
| <code>node.js</code> | <code>function nextWakeUpSchedule()</code> |
| <code>php</code> | <code>function nextWakeUpSchedule()</code> |
| <code>cpp</code> | <code>YWakeUpSchedule * nextWakeUpSchedule()</code> |
| <code>m</code> | <code>-(YWakeUpSchedule*) nextWakeUpSchedule</code> |
| <code>pas</code> | <code>function nextWakeUpSchedule(): TYWakeUpSchedule</code> |
| <code>vb</code> | <code>function nextWakeUpSchedule() As YWakeUpSchedule</code> |
| <code>cs</code> | <code>YWakeUpSchedule nextWakeUpSchedule()</code> |
| <code>java</code> | <code>YWakeUpSchedule nextWakeUpSchedule()</code> |
| <code>py</code> | <code>def nextWakeUpSchedule()</code> |

Returns :

a pointer to a `YWakeUpSchedule` object, corresponding to a wake up schedule currently online, or a null pointer if there are no more wake up schedules to enumerate.

wakeupschedule→registerValueCallback() wakeupschedule.registerValueCallback()

YWakeUpSchedule

Registers the callback function that is invoked on every change of advertised value.

| | |
|----------------------|--|
| <code>js</code> | <code>function registerValueCallback(callback)</code> |
| <code>node.js</code> | <code>function registerValueCallback(callback)</code> |
| <code>php</code> | <code>function registerValueCallback(\$callback)</code> |
| <code>cpp</code> | <code>int registerValueCallback(YWakeUpScheduleValueCallback callback)</code> |
| <code>m</code> | <code>-(int) registerValueCallback : (YWakeUpScheduleValueCallback) callback</code> |
| <code>pas</code> | <code>function registerValueCallback(callback: TYWakeUpScheduleValueCallback): LongInt</code> |
| <code>vb</code> | <code>function registerValueCallback() As Integer</code> |
| <code>cs</code> | <code>int registerValueCallback(ValueCallback callback)</code> |
| <code>java</code> | <code>int registerValueCallback(UpdateCallback callback)</code> |
| <code>py</code> | <code>def registerValueCallback(callback)</code> |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

wakeupschedule→set_hours()
wakeupschedule→setHours()
wakeupschedule.set_hours()

YWakeUpSchedule

Changes the hours when a wake up must take place.

```
js function set_hours( newval)
nodejs function set_hours( newval)
php function set_hours( $newval)
cpp int set_hours( int newval)
m -(int) setHours : (int) newval
pas function set_hours( newval: LongInt): integer
vb function set_hours( ByVal newval As Integer) As Integer
cs int set_hours( int newval)
java int set_hours( int newval)
py def set_hours( newval)
cmd YWakeUpSchedule target set_hours newval
```

Parameters :

newval an integer corresponding to the hours when a wake up must take place

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupschedule→set_logicalName()
wakeupschedule→setLogicalName()
wakeupschedule.set_logicalName()

YWakeUpSchedule

Changes the logical name of the wake up schedule.

| | |
|----------------|---|
| js | function set_logicalName(newval) |
| node.js | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YWakeUpSchedule target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the wake up schedule.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

wakeupschedule→set_minutes()
wakeupschedule→setMinutes()
wakeupschedule.set_minutes()

YWakeUpSchedule

Changes all the minutes where a wake up must take place.

```
js function set_minutes( bitmap)
nodejs function set_minutes( bitmap)
php function set_minutes( $bitmap)
cpp int set_minutes( s64 bitmap)
m -(int) setMinutes : (s64) bitmap
pas function set_minutes( bitmap: int64): LongInt
vb function set_minutes( ) As Integer
cs int set_minutes( long bitmap)
java int set_minutes( long bitmap)
py def set_minutes( bitmap)
cmd YWakeUpSchedule target set_minutes bitmap
```

Parameters :

bitmap Minutes 00-59 of each hour scheduled for wake up.

Returns :

YAPI_SUCCESS if the call succeeds. On failure, throws an exception or returns a negative error code.

wakeupschedule→set_minutesA()
wakeupschedule→setMinutesA()
wakeupschedule.set_minutesA()

YWakeUpSchedule

Changes the minutes in the 00-29 interval when a wake up must take place.

| | |
|---------|--|
| js | function set_minutesA(newval) |
| node.js | function set_minutesA(newval) |
| php | function set_minutesA(\$newval) |
| cpp | int set_minutesA(int newval) |
| m | -(int) setMinutesA : (int) newval |
| pas | function set_minutesA(newval: LongInt): integer |
| vb | function set_minutesA(ByVal newval As Integer) As Integer |
| cs | int set_minutesA(int newval) |
| java | int set_minutesA(int newval) |
| py | def set_minutesA(newval) |
| cmd | YWakeUpSchedule target set_minutesA newval |

Parameters :

newval an integer corresponding to the minutes in the 00-29 interval when a wake up must take place

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupschedule→set_minutesB()
wakeupschedule→setMinutesB()
wakeupschedule.set_minutesB()

YWakeUpSchedule

Changes the minutes in the 30-59 interval when a wake up must take place.

| | |
|--------|--|
| js | function set_minutesB(newval) |
| nodejs | function set_minutesB(newval) |
| php | function set_minutesB(\$newval) |
| cpp | int set_minutesB(int newval) |
| m | -(int) setMinutesB : (int) newval |
| pas | function set_minutesB(newval: LongInt): integer |
| vb | function set_minutesB(ByVal newval As Integer) As Integer |
| cs | int set_minutesB(int newval) |
| java | int set_minutesB(int newval) |
| py | def set_minutesB(newval) |
| cmd | YWakeUpSchedule target set_minutesB newval |

Parameters :

newval an integer corresponding to the minutes in the 30-59 interval when a wake up must take place

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupschedule→**set_monthDays()**
wakeupschedule→**setMonthDays()**
wakeupschedule.set_monthDays()

YWakeUpSchedule

Changes the days of the month when a wake up must take place.

| | |
|---------|--|
| js | function set_monthDays(newval) |
| node.js | function set_monthDays(newval) |
| php | function set_monthDays(\$newval) |
| cpp | int set_monthDays(int newval) |
| m | -(int) setMonthDays : (int) newval |
| pas | function set_monthDays(newval: LongInt): integer |
| vb | function set_monthDays(ByVal newval As Integer) As Integer |
| cs | int set_monthDays(int newval) |
| java | int set_monthDays(int newval) |
| py | def set_monthDays(newval) |
| cmd | YWakeUpSchedule target set_monthDays newval |

Parameters :

newval an integer corresponding to the days of the month when a wake up must take place

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupschedule→set_months()
wakeupschedule→setMonths()
wakeupschedule.set_months()

YWakeUpSchedule

Changes the months when a wake up must take place.

```
js function set_months( newval)
nodejs function set_months( newval)
php function set_months( $newval)
cpp int set_months( int newval)
m -(int) setMonths : (int) newval
pas function set_months( newval: LongInt): integer
vb function set_months( ByVal newval As Integer) As Integer
cs int set_months( int newval)
java int set_months( int newval)
py def set_months( newval)
cmd YWakeUpSchedule target set_months newval
```

Parameters :

newval an integer corresponding to the months when a wake up must take place

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupschedule→set(userData)
wakeupschedule→setUserData()
wakeupschedule.set(userData)

YWakeUpSchedule

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|--|
| js | function setUserData(data) |
| node.js | function setUserData(data) |
| php | function setUserData(\$data) |
| cpp | void setUserData(void* data) |
| m | -(void) setUserData : (void*) data |
| pas | procedure setUserData(data: Tobject) |
| vb | procedure setUserData(ByVal data As Object) |
| cs | void setUserData(object data) |
| java | void setUserData(Object data) |
| py | def setUserData(data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

wakeupschedule→set_weekDays()
wakeupschedule→setWeekDays()
wakeupschedule.set_weekDays()

YWakeUpSchedule

Changes the days of the week when a wake up must take place.

```
js function set_weekDays( newval)
nodejs function set_weekDays( newval)
php function set_weekDays( $newval)
cpp int set_weekDays( int newval)
m -(int) setWeekDays : (int) newval
pas function set_weekDays( newval: LongInt): integer
vb function set_weekDays( ByVal newval As Integer) As Integer
cs int set_weekDays( int newval)
java int set_weekDays( int newval)
py def set_weekDays( newval)
cmd YWakeUpSchedule target set_weekDays newval
```

Parameters :

newval an integer corresponding to the days of the week when a wake up must take place

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupschedule→wait_async()**YWakeUpSchedule**

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.45. Watchdog function interface

The watchdog function works like a relay and can cause a brief power cut to an appliance after a preset delay to force this appliance to reset. The Watchdog must be called from time to time to reset the timer and prevent the appliance reset. The watchdog can be driven directly with *pulse* and *delayedpulse* methods to switch off an appliance for a given duration.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_watchdog.js'></script>
nodejs var yoctolib = require('yoctolib');
var YWatchdog = yoctolib.YWatchdog;
php require_once('yocto_watchdog.php');
cpp #include "yocto_watchdog.h"
m #import "yocto_watchdog.h"
pas uses yocto_watchdog;
vb yocto_watchdog.vb
cs yocto_watchdog.cs
java import com.yoctopuce.YoctoAPI.YWatchdog;
py from yocto_watchdog import *

```

Global functions

yFindWatchdog(func)

Retrieves a watchdog for a given identifier.

yFirstWatchdog()

Starts the enumeration of watchdog currently accessible.

YWatchdog methods

watchdog→delayedPulse(ms_delay, ms_duration)

Schedules a pulse.

watchdog→describe()

Returns a short text that describes unambiguously the instance of the watchdog in the form TYPE(NAME)=SERIAL.FUNCTIONID.

watchdog→get_advertisedValue()

Returns the current value of the watchdog (no more than 6 characters).

watchdog→get_autoStart()

Returns the watchdog running state at module power up.

watchdog→get_countdown()

Returns the number of milliseconds remaining before a pulse (delayedPulse() call). When there is no scheduled pulse, returns zero.

watchdog→get_errorMessage()

Returns the error message of the latest error with the watchdog.

watchdog→get_errorType()

Returns the numerical error code of the latest error with the watchdog.

watchdog→get_friendlyName()

Returns a global identifier of the watchdog in the format MODULE_NAME.FUNCTION_NAME.

watchdog→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

watchdog→get_functionId()

Returns the hardware identifier of the watchdog, without reference to the module.

watchdog->get_hardwareId()

Returns the unique hardware identifier of the watchdog in the form SERIAL.FUNCTIONID.

watchdog->get_logicalName()

Returns the logical name of the watchdog.

watchdog->get_maxTimeOnStateA()

Retourne the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state A before automatically switching back in to B state.

watchdog->get_maxTimeOnStateB()

Retourne the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state B before automatically switching back in to A state.

watchdog->get_module()

Gets the YModule object for the device on which the function is located.

watchdog->get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

watchdog->get_output()

Returns the output state of the watchdog, when used as a simple switch (single throw).

watchdog->get_pulseTimer()

Returns the number of milliseconds remaining before the watchdog is returned to idle position (state A), during a measured pulse generation.

watchdog->get_running()

Returns the watchdog running state.

watchdog->get_state()

Returns the state of the watchdog (A for the idle position, B for the active position).

watchdog->get_stateAtPowerOn()

Returns the state of the watchdog at device startup (A for the idle position, B for the active position, UNCHANGED for no change).

watchdog->get_triggerDelay()

Returns the waiting duration before a reset is automatically triggered by the watchdog, in milliseconds.

watchdog->get_triggerDuration()

Returns the duration of resets caused by the watchdog, in milliseconds.

watchdog->get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

watchdog->isOnline()

Checks if the watchdog is currently reachable, without raising any error.

watchdog->isOnline_async(callback, context)

Checks if the watchdog is currently reachable, without raising any error (asynchronous version).

watchdog->load(msValidity)

Preloads the watchdog cache with a specified validity duration.

watchdog->load_async(msValidity, callback, context)

Preloads the watchdog cache with a specified validity duration (asynchronous version).

watchdog->nextWatchdog()

Continues the enumeration of watchdog started using yFirstWatchdog().

watchdog->pulse(ms_duration)

Sets the relay to output B (active) for a specified duration, then brings it automatically back to output A (idle state).

watchdog->registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

3. Reference

watchdog→resetWatchdog()

Resets the watchdog.

watchdog→set_autoStart(newval)

Changes the watchdog running state at module power up.

watchdog→set_logicalName(newval)

Changes the logical name of the watchdog.

watchdog→set_maxTimeOnStateA(newval)

Sets the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state A before automatically switching back in to B state.

watchdog→set_maxTimeOnStateB(newval)

Sets the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state B before automatically switching back in to A state.

watchdog→set_output(newval)

Changes the output state of the watchdog, when used as a simple switch (single throw).

watchdog→set_running(newval)

Changes the running state of the watchdog.

watchdog→set_state(newval)

Changes the state of the watchdog (A for the idle position, B for the active position).

watchdog→set_stateAtPowerOn(newval)

Preset the state of the watchdog at device startup (A for the idle position, B for the active position, UNCHANGED for no modification).

watchdog→set_triggerDelay(newval)

Changes the waiting delay before a reset is triggered by the watchdog, in milliseconds.

watchdog→set_triggerDuration(newval)

Changes the duration of resets caused by the watchdog, in milliseconds.

watchdog→set(userData,data)

Stores a user context provided as argument in the userData attribute of the function.

watchdog→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YWatchdog.FindWatchdog()**yFindWatchdog()YWatchdog.FindWatchdog()****YWatchdog**

Retrieves a watchdog for a given identifier.

| | |
|----------------------|---|
| <code>js</code> | <code>function yFindWatchdog(func)</code> |
| <code>node.js</code> | <code>function FindWatchdog(func)</code> |
| <code>php</code> | <code>function yFindWatchdog(\$func)</code> |
| <code>cpp</code> | <code>YWatchdog* yFindWatchdog(const string& func)</code> |
| <code>m</code> | <code>YWatchdog* yFindWatchdog(NSString* func)</code> |
| <code>pas</code> | <code>function yFindWatchdog(func: string): TYWatchdog</code> |
| <code>vb</code> | <code>function yFindWatchdog(ByVal func As String) As YWatchdog</code> |
| <code>cs</code> | <code>YWatchdog FindWatchdog(string func)</code> |
| <code>java</code> | <code>YWatchdog FindWatchdog(String func)</code> |
| <code>py</code> | <code>def FindWatchdog(func)</code> |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the watchdog is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YWatchdog.isOnline()` to test if the watchdog is indeed online at a given time. In case of ambiguity when looking for a watchdog by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the watchdog

Returns :

a `YWatchdog` object allowing you to drive the watchdog.

YWatchdog.FirstWatchdog()**YWatchdog****yFirstWatchdog() YWatchdog.FirstWatchdog()**

Starts the enumeration of watchdog currently accessible.

```
js function yFirstWatchdog( )
node.js function FirstWatchdog( )
php function yFirstWatchdog( )
cpp YWatchdog* yFirstWatchdog( )
m YWatchdog* yFirstWatchdog( )
pas function yFirstWatchdog( ): TYWatchdog
vb function yFirstWatchdog( ) As YWatchdog
cs YWatchdog FirstWatchdog()
java YWatchdog FirstWatchdog()
def FirstWatchdog( )
```

Use the method `YWatchdog.nextWatchdog()` to iterate on next watchdog.

Returns :

a pointer to a `YWatchdog` object, corresponding to the first watchdog currently online, or a `null` pointer if there are none.

watchdog→delayedPulse()watchdog.delayedPulse()

YWatchdog

Schedules a pulse.

```
js function delayedPulse( ms_delay, ms_duration)
node.js function delayedPulse( ms_delay, ms_duration)
php function delayedPulse( $ms_delay, $ms_duration)
cpp int delayedPulse( int ms_delay, int ms_duration)
m -(int) delayedPulse : (int) ms_delay : (int) ms_duration
pas function delayedPulse( ms_delay: LongInt, ms_duration: LongInt): integer
vb function delayedPulse( ByVal ms_delay As Integer,
                           ByVal ms_duration As Integer) As Integer
cs int delayedPulse( int ms_delay, int ms_duration)
java int delayedPulse( int ms_delay, int ms_duration)
py def delayedPulse( ms_delay, ms_duration)
cmd YWatchdog target delayedPulse ms_delay ms_duration
```

Parameters :

ms_delay waiting time before the pulse, in millisecondes

ms_duration pulse duration, in millisecondes

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→describe()watchdog.describe()**YWatchdog**

Returns a short text that describes unambiguously the instance of the watchdog in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | - (NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the watchdog (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

watchdog→get_advertisedValue()
watchdog→advertisedValue()
watchdog.get_advertisedValue()

YWatchdog

Returns the current value of the watchdog (no more than 6 characters).

```
js    function get_advertisedValue( )  
node.js function get_advertisedValue( )  
php   function get_advertisedValue( )  
cpp   string get_advertisedValue( )  
m     -(NSString*) advertisedValue  
pas   function get_advertisedValue( ): string  
vb    function get_advertisedValue( ) As String  
cs    string get_advertisedValue( )  
java  String get_advertisedValue( )  
py    def get_advertisedValue( )  
cmd   YWatchdog target get_advertisedValue
```

Returns :

a string corresponding to the current value of the watchdog (no more than 6 characters). On failure, throws an exception or returns `Y_ADVERTISEDVALUE_INVALID`.

watchdog→get_autoStart()**YWatchdog****watchdog→autoStart()watchdog.get_autoStart()**

Returns the watchdog runing state at module power up.

| | |
|---------|---|
| js | function get_autoStart() |
| node.js | function get_autoStart() |
| php | function get_autoStart() |
| cpp | Y_AUTOSTART_enum get_autoStart() |
| m | -(Y_AUTOSTART_enum) autoStart |
| pas | function get_autoStart(): Integer |
| vb | function get_autoStart() As Integer |
| cs | int get_autoStart() |
| java | int get_autoStart() |
| py | def get_autoStart() |
| cmd | YWatchdog target get_autoStart |

Returns :

either Y_AUTOSTART_OFF or Y_AUTOSTART_ON, according to the watchdog runing state at module power up

On failure, throws an exception or returns Y_AUTOSTART_INVALID.

watchdog→get_countdown()**YWatchdog****watchdog→countdown()watchdog.get_countdown()**

Returns the number of milliseconds remaining before a pulse (delayedPulse() call) When there is no scheduled pulse, returns zero.

| | |
|--------|--|
| js | function get_countdown() |
| nodejs | function get_countdown() |
| php | function get_countdown() |
| cpp | s64 get_countdown() |
| m | -(s64) countdown |
| pas | function get_countdown(): int64 |
| vb | function get_countdown() As Long |
| cs | long get_countdown() |
| java | long get_countdown() |
| py | def get_countdown() |
| cmd | YWatchdog target get_countdown |

Returns :

an integer corresponding to the number of milliseconds remaining before a pulse (delayedPulse() call) When there is no scheduled pulse, returns zero

On failure, throws an exception or returns Y_COUNTDOWN_INVALID.

watchdog→get_errorMessage()
watchdog→errorMessage()
watchdog.get_errorMessage()**YWatchdog**

Returns the error message of the latest error with the watchdog.

| | |
|--------|--|
| js | function get_errorMessage() |
| nodejs | function get_errorMessage() |
| php | function get_errorMessage() |
| cpp | string get_errorMessage() |
| m | -(NSString*) errorMessage |
| pas | function get_errorMessage(): string |
| vb | function get_errorMessage() As String |
| cs | string get_errorMessage() |
| java | String get_errorMessage() |
| py | def get_errorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the watchdog object

watchdog→get_errorType()**YWatchdog****watchdog→errorType()watchdog.get_errorType()**

Returns the numerical error code of the latest error with the watchdog.

| | |
|--------|--|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType(): YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the watchdog object

watchdog→get_friendlyName()
watchdog→friendlyName()
watchdog.get_friendlyName()

YWatchdog

Returns a global identifier of the watchdog in the format MODULE_NAME . FUNCTION_NAME.

| | |
|--------|------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the watchdog if they are defined, otherwise the serial number of the module and the hardware identifier of the watchdog (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the watchdog using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

watchdog→get_functionDescriptor()
watchdog→functionDescriptor()
watchdog.get_functionDescriptor()

YWatchdog

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

watchdog→get_functionId()**YWatchdog****watchdog→functionId()watchdog.get_functionId()**

Returns the hardware identifier of the watchdog, without reference to the module.

| | |
|---------|--|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the watchdog (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

watchdog→get_hardwareId()**YWatchdog****watchdog→hardwareId()watchdog.get_hardwareId()**

Returns the unique hardware identifier of the watchdog in the form SERIAL.FUNCTIONID.

| | |
|--------|---|
| js | function get_hardwareId() |
| nodejs | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the watchdog. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the watchdog (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

watchdog→get_logicalName()
watchdog→logicalName()
watchdog.get_logicalName()

YWatchdog

Returns the logical name of the watchdog.

```
js function get_logicalName( )  
nodejs function get_logicalName( )  
php function get_logicalName( )  
cpp string get_logicalName( )  
m -(NSString*) logicalName  
pas function get_logicalName( ): string  
vb function get_logicalName( ) As String  
cs string get_logicalName( )  
java String get_logicalName( )  
py def get_logicalName( )  
cmd YWatchdog target get_logicalName
```

Returns :

a string corresponding to the logical name of the watchdog. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

watchdog→get_maxTimeOnStateA()
watchdog→maxTimeOnStateA()
watchdog.get_maxTimeOnStateA()

YWatchdog

Retourne the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state A before automatically switching back in to B state.

```
js function get_maxTimeOnStateA( )
nodejs function get_maxTimeOnStateA( )
php function get_maxTimeOnStateA( )
cpp s64 get_maxTimeOnStateA( )
m -(s64) maxTimeOnStateA
pas function get_maxTimeOnStateA( ): int64
vb function get_maxTimeOnStateA( ) As Long
cs long get_maxTimeOnStateA( )
java long get_maxTimeOnStateA( )
py def get_maxTimeOnStateA( )
cmd YWatchdog target get_maxTimeOnStateA
```

Zero means no maximum time.

Returns :
an integer

On failure, throws an exception or returns Y_MAXTIMEONSTATEA_INVALID.

watchdog→get_maxTimeOnStateB()
watchdog→maxTimeOnStateB()
watchdog.get_maxTimeOnStateB()

YWatchdog

Retourne the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state B before automatically switching back in to A state.

```
js function get_maxTimeOnStateB( )
nodejs function get_maxTimeOnStateB( )
php function get_maxTimeOnStateB( )
cpp s64 get_maxTimeOnStateB( )
m -(s64) maxTimeOnStateB
pas function get_maxTimeOnStateB( ): int64
vb function get_maxTimeOnStateB( ) As Long
cs long get_maxTimeOnStateB( )
java long get_maxTimeOnStateB( )
py def get_maxTimeOnStateB( )
cmd YWatchdog target get_maxTimeOnStateB
```

Zero means no maximum time.

Returns :

an integer

On failure, throws an exception or returns Y_MAXTIMEONSTATEB_INVALID.

watchdog→get_module()**YWatchdog****watchdog→module()watchdog.get_module()**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

watchdog→get_module_async()
watchdog→module_async()**YWatchdog**

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

watchdog→get_output()**YWatchdog****watchdog→output()watchdog.get_output()**

Returns the output state of the watchdog, when used as a simple switch (single throw).

| | |
|--------|--|
| js | function get_output() |
| nodejs | function get_output() |
| php | function get_output() |
| cpp | Y_OUTPUT_enum get_output() |
| m | -(Y_OUTPUT_enum) output |
| pas | function get_output(): Integer |
| vb | function get_output() As Integer |
| cs | int get_output() |
| java | int get_output() |
| py | def get_output() |
| cmd | YWatchdog target get_output |

Returns :

either Y_OUTPUT_OFF or Y_OUTPUT_ON, according to the output state of the watchdog, when used as a simple switch (single throw)

On failure, throws an exception or returns Y_OUTPUT_INVALID.

watchdog→get_pulseTimer()**YWatchdog****watchdog→pulseTimer()watchdog.get_pulseTimer()**

Returns the number of milliseconds remaining before the watchdog is returned to idle position (state A), during a measured pulse generation.

| | |
|--------|---|
| js | function get_pulseTimer() |
| nodejs | function get_pulseTimer() |
| php | function get_pulseTimer() |
| cpp | s64 get_pulseTimer() |
| m | -(s64) pulseTimer |
| pas | function get_pulseTimer(): int64 |
| vb | function get_pulseTimer() As Long |
| cs | long get_pulseTimer() |
| java | long get_pulseTimer() |
| py | def get_pulseTimer() |
| cmd | YWatchdog target get_pulseTimer |

When there is no ongoing pulse, returns zero.

Returns :

an integer corresponding to the number of milliseconds remaining before the watchdog is returned to idle position (state A), during a measured pulse generation

On failure, throws an exception or returns **Y_PULSE_TIMER_INVALID**.

watchdog→get_running()**YWatchdog****watchdog→running()watchdog.get_running()**

Returns the watchdog running state.

```
js function get_running( )
nodejs function get_running( )
php function get_running( )
cpp Y_RUNNING_enum get_running( )
m -(Y_RUNNING_enum) running
pas function get_running( ): Integer
vb function get_running( ) As Integer
cs int get_running( )
java int get_running( )
py def get_running( )
cmd YWatchdog target get_running
```

Returns :

either Y_RUNNING_OFF or Y_RUNNING_ON, according to the watchdog running state

On failure, throws an exception or returns Y_RUNNING_INVALID.

watchdog→get_state()
watchdog→state()watchdog.get_state()**YWatchdog**

Returns the state of the watchdog (A for the idle position, B for the active position).

| | |
|---------|---|
| js | function get_state() |
| node.js | function get_state() |
| php | function get_state() |
| cpp | Y_STATE_enum get_state() |
| m | -(Y_STATE_enum) state |
| pas | function get_state(): Integer |
| vb | function get_state() As Integer |
| cs | int get_state() |
| java | int get_state() |
| py | def get_state() |
| cmd | YWatchdog target get_state |

Returns :

either Y_STATE_A or Y_STATE_B, according to the state of the watchdog (A for the idle position, B for the active position)

On failure, throws an exception or returns Y_STATE_INVALID.

watchdog→get_stateAtPowerOn()
watchdog→stateAtPowerOn()
watchdog.get_stateAtPowerOn()

YWatchdog

Returns the state of the watchdog at device startup (A for the idle position, B for the active position, UNCHANGED for no change).

| | |
|----------------|--|
| js | function get_stateAtPowerOn() |
| node.js | function get_stateAtPowerOn() |
| php | function get_stateAtPowerOn() |
| cpp | Y_STATEATPOWERON_enum get_stateAtPowerOn() |
| m | -(Y_STATEATPOWERON_enum) stateAtPowerOn |
| pas | function get_stateAtPowerOn() : Integer |
| vb | function get_stateAtPowerOn() As Integer |
| cs | int get_stateAtPowerOn() |
| java | int get_stateAtPowerOn() |
| py | def get_stateAtPowerOn() |
| cmd | YWatchdog target get_stateAtPowerOn |

Returns :

a value among Y_STATEATPOWERON_UNCHANGED, Y_STATEATPOWERON_A and Y_STATEATPOWERON_B corresponding to the state of the watchdog at device startup (A for the idle position, B for the active position, UNCHANGED for no change)

On failure, throws an exception or returns Y_STATEATPOWERON_INVALID.

watchdog→get_triggerDelay()
watchdog→triggerDelay()
watchdog.get_triggerDelay()**YWatchdog**

Returns the waiting duration before a reset is automatically triggered by the watchdog, in milliseconds.

| | |
|--------|--------------------------------------|
| js | function get_triggerDelay() |
| nodejs | function get_triggerDelay() |
| php | function get_triggerDelay() |
| cpp | s64 get_triggerDelay() |
| m | -(s64) triggerDelay |
| pas | function get_triggerDelay(): int64 |
| vb | function get_triggerDelay() As Long |
| cs | long get_triggerDelay() |
| java | long get_triggerDelay() |
| py | def get_triggerDelay() |
| cmd | YWatchdog target get_triggerDelay |

Returns :

an integer corresponding to the waiting duration before a reset is automatically triggered by the watchdog, in milliseconds

On failure, throws an exception or returns Y_TRIGGERDELAY_INVALID.

watchdog→get_triggerDuration()
watchdog→triggerDuration()
watchdog.get_triggerDuration()**YWatchdog**

Returns the duration of resets caused by the watchdog, in milliseconds.

| | |
|----------------------|--|
| <code>js</code> | <code>function get_triggerDuration()</code> |
| <code>node.js</code> | <code>function get_triggerDuration()</code> |
| <code>php</code> | <code>function get_triggerDuration()</code> |
| <code>cpp</code> | <code>s64 get_triggerDuration()</code> |
| <code>m</code> | <code>-(s64) triggerDuration</code> |
| <code>pas</code> | <code>function get_triggerDuration(): int64</code> |
| <code>vb</code> | <code>function get_triggerDuration() As Long</code> |
| <code>cs</code> | <code>long get_triggerDuration()</code> |
| <code>java</code> | <code>long get_triggerDuration()</code> |
| <code>py</code> | <code>def get_triggerDuration()</code> |
| <code>cmd</code> | <code>YWatchdog target get_triggerDuration</code> |

Returns :

an integer corresponding to the duration of resets caused by the watchdog, in milliseconds

On failure, throws an exception or returns `Y_TRIGGERDURATION_INVALID`.

watchdog→get(userData)**YWatchdog****watchdog→userData()watchdog.get(userData())**

Returns the value of the userData attribute, as previously stored using method set(userData).

```
js function get(userData) 
node.js function get(userData) 
php function get(userData) 
cpp void * get(userData) 
m -(void*) userData 
pas function get(userData): Tobject 
vb function get(userData) As Object 
cs object get(userData) 
java Object get(userData) 
py def get(userData)
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

watchdog→isOnline()watchdog.isOnline()**YWatchdog**

Checks if the watchdog is currently reachable, without raising any error.

| | |
|---------|--|
| js | function isOnline() |
| node.js | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the watchdog in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the watchdog.

Returns :

`true` if the watchdog can be reached, and `false` otherwise

watchdog→isOnline_async()

YWatchdog

Checks if the watchdog is currently reachable, without raising any error (asynchronous version).

```
js  function isOnline_async( callback, context )
nodejs function isOnline_async( callback, context )
```

If there is a cached value for the watchdog in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result
context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

watchdog→load()watchdog.load()**YWatchdog**

Preloads the watchdog cache with a specified validity duration.

| | |
|----------------------|--|
| <code>js</code> | <code>function load(msValidity)</code> |
| <code>node.js</code> | <code>function load(msValidity)</code> |
| <code>php</code> | <code>function load(\$msValidity)</code> |
| <code>cpp</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>m</code> | <code>-(YRETCODE) load : (int) msValidity</code> |
| <code>pas</code> | <code>function load(msValidity: integer): YRETCODE</code> |
| <code>vb</code> | <code>function load(ByVal msValidity As Integer) As YRETCODE</code> |
| <code>cs</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>java</code> | <code>int load(long msValidity)</code> |
| <code>py</code> | <code>def load(msValidity)</code> |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

watchdog→load_async()

YWatchdog

Preloads the watchdog cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

watchdog→nextWatchdog()
watchdog.nextWatchdog()**YWatchdog**

Continues the enumeration of watchdog started using `yFirstWatchdog()`.

| | |
|--------|--|
| js | <code>function nextWatchdog()</code> |
| nodejs | <code>function nextWatchdog()</code> |
| php | <code>function nextWatchdog()</code> |
| cpp | <code>YWatchdog * nextWatchdog()</code> |
| m | <code>-(YWatchdog*) nextWatchdog</code> |
| pas | <code>function nextWatchdog(): TYWatchdog</code> |
| vb | <code>function nextWatchdog() As YWatchdog</code> |
| cs | <code>YWatchdog nextWatchdog()</code> |
| java | <code>YWatchdog nextWatchdog()</code> |
| py | <code>def nextWatchdog()</code> |

Returns :

a pointer to a `YWatchdog` object, corresponding to a watchdog currently online, or a `null` pointer if there are no more watchdog to enumerate.

watchdog→pulse()watchdog.pulse()**YWatchdog**

Sets the relay to output B (active) for a specified duration, then brings it automatically back to output A (idle state).

| | |
|--------|---|
| js | function pulse(ms_duration) |
| nodejs | function pulse(ms_duration) |
| php | function pulse(\$ms_duration) |
| cpp | int pulse(int ms_duration) |
| m | - (int) pulse : (int) ms_duration |
| pas | function pulse(ms_duration: LongInt): integer |
| vb | function pulse(ByVal ms_duration As Integer) As Integer |
| cs | int pulse(int ms_duration) |
| java | int pulse(int ms_duration) |
| py | def pulse(ms_duration) |
| cmd | YWatchdog target pulse ms_duration |

Parameters :**ms_duration** pulse duration, in millisecondes**Returns :**

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→registerValueCallback() watchdog.registerValueCallback()

YWatchdog

Registers the callback function that is invoked on every change of advertised value.

| | |
|---------|---|
| js | function registerValueCallback(callback) |
| node.js | function registerValueCallback(callback) |
| php | function registerValueCallback(\$callback) |
| cpp | int registerValueCallback(YWatchdogValueCallback callback) |
| m | -(int) registerValueCallback : (YWatchdogValueCallback) callback |
| pas | function registerValueCallback(callback : TYWatchdogValueCallback): LongInt |
| vb | function registerValueCallback() As Integer |
| cs | int registerValueCallback(ValueCallback callback) |
| java | int registerValueCallback(UpdateCallback callback) |
| py | def registerValueCallback(callback) |

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

**watchdog→resetWatchdog()
watchdog.resetWatchdog()****YWatchdog**

Resets the watchdog.

```
js function resetWatchdog( )  
node.js function resetWatchdog( )  
php function resetWatchdog( )  
cpp int resetWatchdog( )  
m -(int) resetWatchdog  
pas function resetWatchdog( ): integer  
vb function resetWatchdog( ) As Integer  
cs int resetWatchdog( )  
java int resetWatchdog( )  
py def resetWatchdog( )  
cmd YWatchdog target resetWatchdog
```

When the watchdog is running, this function must be called on a regular basis to prevent the watchdog to trigger

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set_autoStart()**YWatchdog****watchdog→setAutoStart()|watchdog.set_autoStart()**

Changes the watchdog runningstae at module power up.

| | |
|---------------|--|
| js | <code>function set_autoStart(newval)</code> |
| nodejs | <code>function set_autoStart(newval)</code> |
| php | <code>function set_autoStart(\$newval)</code> |
| cpp | <code>int set_autoStart(Y_AUTOSTART_enum newval)</code> |
| m | <code>-(int) setAutoStart : (Y_AUTOSTART_enum) newval</code> |
| pas | <code>function set_autoStart(newval: Integer): integer</code> |
| vb | <code>function set_autoStart(ByVal newval As Integer) As Integer</code> |
| cs | <code>int set_autoStart(int newval)</code> |
| java | <code>int set_autoStart(int newval)</code> |
| py | <code>def set_autoStart(newval)</code> |
| cmd | <code>YWatchdog target set_autoStart newval</code> |

Remember to call the `saveToFlash()` method and then to reboot the module to apply this setting.

Parameters :

newval either `Y_AUTOSTART_OFF` or `Y_AUTOSTART_ON`, according to the watchdog runningstae at module power up

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set_logicalName()
watchdog→setLogicalName()
watchdog.set_logicalName()

YWatchdog

Changes the logical name of the watchdog.

| | |
|--------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YWatchdog target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the watchdog.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

watchdog→set_maxTimeOnStateA()
watchdog→setMaxTimeOnStateA()
watchdog.set_maxTimeOnStateA()

YWatchdog

Sets the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state A before automatically switching back in to B state.

| | |
|--------|---|
| js | function set_maxTimeOnStateA(newval) |
| nodejs | function setMaxTimeOnStateA(newval) |
| php | function set_maxTimeOnStateA(\$newval) |
| cpp | int set_maxTimeOnStateA(s64 newval) |
| m | -(int) setMaxTimeOnStateA : (s64) newval |
| pas | function set_maxTimeOnStateA(newval: int64): integer |
| vb | function set_maxTimeOnStateA(ByVal newval As Long) As Integer |
| cs | int set_maxTimeOnStateA(long newval) |
| java | int set_maxTimeOnStateA(long newval) |
| py | def set_maxTimeOnStateA(newval) |
| cmd | YWatchdog target set_maxTimeOnStateA newval |

Use zero for no maximum time.

Parameters :

newval an integer

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set_maxTimeOnStateB()
watchdog→setMaxTimeOnStateB()
watchdog.set_maxTimeOnStateB()

YWatchdog

Sets the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state B before automatically switching back in to A state.

```
js function set_maxTimeOnStateB( newval)
nodejs function set_maxTimeOnStateB( newval)
php function set_maxTimeOnStateB( $newval)
cpp int set_maxTimeOnStateB( s64 newval)
m -(int) setMaxTimeOnStateB : (s64) newval
pas function set_maxTimeOnStateB( newval: int64): integer
vb function set_maxTimeOnStateB( ByVal newval As Long) As Integer
cs int set_maxTimeOnStateB( long newval)
java int set_maxTimeOnStateB( long newval)
py def set_maxTimeOnStateB( newval)
cmd YWatchdog target set_maxTimeOnStateB newval
```

Use zero for no maximum time.

Parameters :

newval an integer

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set_output()**YWatchdog****watchdog→setOutput()watchdog.set_output()**

Changes the output state of the watchdog, when used as a simple switch (single throw).

| | |
|---------------|---|
| js | function set_output(newval) |
| nodejs | function set_output(newval) |
| php | function set_output(\$newval) |
| cpp | int set_output(Y_OUTPUT_enum newval) |
| m | -(int) setOutput : (Y_OUTPUT_enum) newval |
| pas | function set_output(newval: Integer): integer |
| vb | function set_output(ByVal newval As Integer) As Integer |
| cs | int set_output(int newval) |
| java | int set_output(int newval) |
| py | def set_output(newval) |
| cmd | YWatchdog target set_output newval |

Parameters :

newval either **Y_OUTPUT_OFF** or **Y_OUTPUT_ON**, according to the output state of the watchdog, when used as a simple switch (single throw)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set_running()**YWatchdog****watchdog→setRunning()watchdog.set_running()**

Changes the running state of the watchdog.

```
js function set_running( newval)
node.js function set_running( newval)
php function set_running( $newval)
cpp int set_running( Y_RUNNING_enum newval)
m -(int) setRunning : (Y_RUNNING_enum) newval
pas function set_running( newval: Integer): integer
vb function set_running( ByVal newval As Integer) As Integer
cs int set_running( int newval)
java int set_running( int newval)
py def set_running( newval)
cmd YWatchdog target set_running newval
```

Parameters :

newval either Y_RUNNING_OFF or Y_RUNNING_ON, according to the running state of the watchdog

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set_state()**YWatchdog****watchdog→setState()watchdog.set_state()**

Changes the state of the watchdog (A for the idle position, B for the active position).

| | |
|--------|--|
| js | function set_state(newval) |
| nodejs | function set_state(newval) |
| php | function set_state(\$newval) |
| cpp | int set_state(Y_STATE_enum newval) |
| m | -(int) setState : (Y_STATE_enum) newval |
| pas | function set_state(newval: Integer): integer |
| vb | function set_state(ByVal newval As Integer) As Integer |
| cs | int set_state(int newval) |
| java | int set_state(int newval) |
| py | def set_state(newval) |
| cmd | YWatchdog target set_state newval |

Parameters :

newval either `Y_STATE_A` or `Y_STATE_B`, according to the state of the watchdog (A for the idle position, B for the active position)

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set_stateAtPowerOn()
watchdog→setStateAtPowerOn()
watchdog.set_stateAtPowerOn()

YWatchdog

Preset the state of the watchdog at device startup (A for the idle position, B for the active position, UNCHANGED for no modification).

| | |
|--------|---|
| js | function set_stateAtPowerOn(newval) |
| nodejs | function set_stateAtPowerOn(newval) |
| php | function set_stateAtPowerOn(\$newval) |
| cpp | int set_stateAtPowerOn(Y_STATEATPOWERON_enum newval) |
| m | - (int) setStateAtPowerOn : (Y_STATEATPOWERON_enum) newval |
| pas | function set_stateAtPowerOn(newval: Integer): integer |
| vb | function set_stateAtPowerOn(ByVal newval As Integer) As Integer |
| cs | int set_stateAtPowerOn(int newval) |
| java | int set_stateAtPowerOn(int newval) |
| py | def set_stateAtPowerOn(newval) |
| cmd | YWatchdog target set_stateAtPowerOn newval |

Remember to call the matching module `saveToFlash()` method, otherwise this call will have no effect.

Parameters :

newval a value among `Y_STATEATPOWERON_UNCHANGED`, `Y_STATEATPOWERON_A` and `Y_STATEATPOWERON_B`

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

**watchdog→set_triggerDelay()
watchdog→setTriggerDelay()
watchdog.set_triggerDelay()****YWatchdog**

Changes the waiting delay before a reset is triggered by the watchdog, in milliseconds.

| | |
|--------|--|
| js | function set_triggerDelay(newval) |
| nodejs | function set_triggerDelay(newval) |
| php | function set_triggerDelay(\$newval) |
| cpp | int set_triggerDelay(s64 newval) |
| m | -(int) setTriggerDelay : (s64) newval |
| pas | function set_triggerDelay(newval: int64): integer |
| vb | function set_triggerDelay(ByVal newval As Long) As Integer |
| cs | int set_triggerDelay(long newval) |
| java | int set_triggerDelay(long newval) |
| py | def set_triggerDelay(newval) |
| cmd | YWatchdog target set_triggerDelay newval |

Parameters :

newval an integer corresponding to the waiting delay before a reset is triggered by the watchdog, in milliseconds

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

**watchdog→set_triggerDuration()
watchdog→setTriggerDuration()
watchdog.set_triggerDuration()****YWatchdog**

Changes the duration of resets caused by the watchdog, in milliseconds.

```
js function set_triggerDuration( newval)
nodejs function set_triggerDuration( newval)
php function set_triggerDuration( $newval)
cpp int set_triggerDuration( s64 newval)
m -(int) setTriggerDuration : (s64) newval
pas function set_triggerDuration( newval: int64): integer
vb function set_triggerDuration( ByVal newval As Long) As Integer
cs int set_triggerDuration( long newval)
java int set_triggerDuration( long newval)
py def set_triggerDuration( newval)
cmd YWatchdog target set_triggerDuration newval
```

Parameters :

newval an integer corresponding to the duration of resets caused by the watchdog, in milliseconds

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set(userData)**YWatchdog****watchdog→setUserData()watchdog.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|---|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData \$data) |
| cpp | void set(userData void* data) |
| m | -(void) setUserData : (void*) data |
| pas | procedure set(userData Tobject) |
| vb | procedure set(userData ByVal data As Object) |
| cs | void set(userData object data) |
| java | void set(userData Object data) |
| py | def set(userData data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

watchdog→wait_async()

YWatchdog

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

3.46. Wireless function interface

YWireless functions provides control over wireless network parameters and status for devices that are wireless-enabled.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_wireless.js'></script>
nodejs var yoctolib = require('yoctolib');
var YWireless = yoctolib.YWireless;
php require_once('yocto_wireless.php');
cpp #include "yocto_wireless.h"
m #import "yocto_wireless.h"
pas uses yocto_wireless;
vb yocto_wireless.vb
cs yocto_wireless.cs
java import com.yoctopuce.YoctoAPI.YWireless;
py from yocto_wireless import *

```

Global functions

yFindWireless(func)

Retrieves a wireless lan interface for a given identifier.

yFirstWireless()

Starts the enumeration of wireless lan interfaces currently accessible.

YWireless methods

wireless→adhocNetwork(ssid, securityKey)

Changes the configuration of the wireless lan interface to create an ad-hoc wireless network, without using an access point.

wireless→describe()

Returns a short text that describes unambiguously the instance of the wireless lan interface in the form TYPE (NAME)=SERIAL . FUNCTIONID.

wireless→get_advertisedValue()

Returns the current value of the wireless lan interface (no more than 6 characters).

wireless→get_channel()

Returns the 802.11 channel currently used, or 0 when the selected network has not been found.

wireless→get_detectedWlans()

Returns a list of YWlanRecord objects that describe detected Wireless networks.

wireless→get_errorMessage()

Returns the error message of the latest error with the wireless lan interface.

wireless→get_errorType()

Returns the numerical error code of the latest error with the wireless lan interface.

wireless→get_friendlyName()

Returns a global identifier of the wireless lan interface in the format MODULE_NAME . FUNCTION_NAME.

wireless→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

wireless→get_functionId()

Returns the hardware identifier of the wireless lan interface, without reference to the module.

wireless→get_hardwareId()

Returns the unique hardware identifier of the wireless lan interface in the form SERIAL . FUNCTIONID.

3. Reference

wireless→get_linkQuality()

Returns the link quality, expressed in percent.

wireless→get_logicalName()

Returns the logical name of the wireless lan interface.

wireless→get_message()

Returns the latest status message from the wireless interface.

wireless→get_module()

Gets the YModule object for the device on which the function is located.

wireless→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

wireless→get_security()

Returns the security algorithm used by the selected wireless network.

wireless→get_ssid()

Returns the wireless network name (SSID).

wireless→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

wireless→isOnline()

Checks if the wireless lan interface is currently reachable, without raising any error.

wireless→isOnline_async(callback, context)

Checks if the wireless lan interface is currently reachable, without raising any error (asynchronous version).

wireless→joinNetwork(ssid, securityKey)

Changes the configuration of the wireless lan interface to connect to an existing access point (infrastructure mode).

wireless→load(msValidity)

Preloads the wireless lan interface cache with a specified validity duration.

wireless→load_async(msValidity, callback, context)

Preloads the wireless lan interface cache with a specified validity duration (asynchronous version).

wireless→nextWireless()

Continues the enumeration of wireless lan interfaces started using yFirstWireless().

wireless→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

wireless→set_logicalName(newval)

Changes the logical name of the wireless lan interface.

wireless→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

wireless→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YWireless.FindWireless()**YWireless****yFindWireless()YWireless.FindWireless()**

Retrieves a wireless lan interface for a given identifier.

| | |
|---------------------|---|
| <code>js</code> | <code>function yFindWireless(func)</code> |
| <code>nodejs</code> | <code>function FindWireless(func)</code> |
| <code>php</code> | <code>function yFindWireless(\$func)</code> |
| <code>cpp</code> | <code>YWireless* yFindWireless(string func)</code> |
| <code>m</code> | <code>+ (YWireless*) yFindWireless : (NSString*) func</code> |
| <code>pas</code> | <code>function yFindWireless(func: string): TYWireless</code> |
| <code>vb</code> | <code>function yFindWireless(ByVal func As String) As YWireless</code> |
| <code>cs</code> | <code>YWireless FindWireless(string func)</code> |
| <code>java</code> | <code>YWireless FindWireless(String func)</code> |
| <code>py</code> | <code>def FindWireless(func)</code> |

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the wireless lan interface is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YWireless.isOnline()` to test if the wireless lan interface is indeed online at a given time. In case of ambiguity when looking for a wireless lan interface by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the wireless lan interface

Returns :

a `YWireless` object allowing you to drive the wireless lan interface.

YWireless.FirstWireless() yFirstWireless()YWireless.FirstWireless()

YWireless

Starts the enumeration of wireless lan interfaces currently accessible.

| | |
|---------|--|
| js | function yFirstWireless() |
| node.js | function FirstWireless() |
| php | function yFirstWireless() |
| cpp | YWireless* yFirstWireless() |
| m | YWireless* yFirstWireless() |
| pas | function yFirstWireless() : TYWireless |
| vb | function yFirstWireless() As YWireless |
| cs | YWireless FirstWireless() |
| java | YWireless FirstWireless() |
| py | def FirstWireless() |

Use the method `YWireless.nextWireless()` to iterate on next wireless lan interfaces.

Returns :

a pointer to a `YWireless` object, corresponding to the first wireless lan interface currently online, or a null pointer if there are none.

wireless→adhocNetwork()wireless.adhocNetwork()**YWireless**

Changes the configuration of the wireless lan interface to create an ad-hoc wireless network, without using an access point.

```

js   function adhocNetwork( ssid, securityKey)
nodejs function adhocNetwork( ssid, securityKey)
php  function adhocNetwork( $ssid, $securityKey)
cpp   int adhocNetwork( string ssid, string securityKey)
m    -(int) adhocNetwork : (NSString*) ssid
      : (NSString*) securityKey
pas   function adhocNetwork( ssid: string, securityKey: string): integer
vb    function adhocNetwork( ByVal ssid As String,
                           ByVal securityKey As String) As Integer
cs    int adhocNetwork( string ssid, string securityKey)
java  int adhocNetwork( String ssid, String securityKey)
py    def adhocNetwork( ssid, securityKey)
cmd   YWireless target adhocNetwork ssid securityKey

```

If a security key is specified, the network is protected by WEP128, since WPA is not standardized for ad-hoc networks. Remember to call the `saveToFlash()` method and then to reboot the module to apply this setting.

Parameters :

ssid the name of the network to connect to
securityKey the network key, as a character string

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

wireless→describe(wireless.describe())**YWireless**

Returns a short text that describes unambiguously the instance of the wireless lan interface in the form TYPE (NAME)=SERIAL.FUNCTIONID.

| | |
|--------|--------------------------------------|
| js | function describe() |
| nodejs | function describe() |
| php | function describe() |
| cpp | string describe() |
| m | -(NSString*) describe |
| pas | function describe() : string |
| vb | function describe() As String |
| cs | string describe() |
| java | String describe() |
| py | def describe() |

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the wireless lan interface (ex:
Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

wireless→get_advertisedValue()
wireless→advertisedValue()
wireless.get_advertisedValue()**YWireless**

Returns the current value of the wireless lan interface (no more than 6 characters).

| | |
|---------------------|--|
| <code>js</code> | <code>function get_advertisedValue()</code> |
| <code>nodejs</code> | <code>function get_advertisedValue()</code> |
| <code>php</code> | <code>function get_advertisedValue()</code> |
| <code>cpp</code> | <code>string get_advertisedValue()</code> |
| <code>m</code> | <code>-(NSString*) advertisedValue</code> |
| <code>pas</code> | <code>function get_advertisedValue(): string</code> |
| <code>vb</code> | <code>function get_advertisedValue() As String</code> |
| <code>cs</code> | <code>string get_advertisedValue()</code> |
| <code>java</code> | <code>String get_advertisedValue()</code> |
| <code>py</code> | <code>def get_advertisedValue()</code> |
| <code>cmd</code> | <code>YWireless target get_advertisedValue</code> |

Returns :

a string corresponding to the current value of the wireless lan interface (no more than 6 characters). On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

wireless→get_channel()**YWireless****wireless→channel()wireless.get_channel()**

Returns the 802.11 channel currently used, or 0 when the selected network has not been found.

| | |
|---------|---|
| js | function get_channel() |
| node.js | function get_channel() |
| php | function get_channel() |
| cpp | int get_channel() |
| m | -(int) channel |
| pas | function get_channel() : LongInt |
| vb | function get_channel() As Integer |
| cs | int get_channel() |
| java | int get_channel() |
| py | def get_channel() |
| cmd | YWireless target get_channel |

Returns :

an integer corresponding to the 802.11 channel currently used, or 0 when the selected network has not been found

On failure, throws an exception or returns Y_CHANNEL_INVALID.

wireless→get_detectedWlans()
wireless→detectedWlans()
wireless.get_detectedWlans()

YWireless

Returns a list of YWlanRecord objects that describe detected Wireless networks.

| | |
|---------|---|
| js | function get_detectedWlans() |
| node.js | function get_detectedWlans() |
| php | function get_detectedWlans() |
| cpp | vector<YWlanRecord> get_detectedWlans() |
| m | -(NSMutableArray*) detectedWlans |
| pas | function get_detectedWlans(): TYWlanRecordArray |
| vb | function get_detectedWlans() As List |
| cs | List<YWlanRecord> get_detectedWlans() |
| java | ArrayList<YWlanRecord> get_detectedWlans() |
| py | def get_detectedWlans() |
| cmd | YWireless target get_detectedWlans |

This list is not updated when the module is already connected to an acces point (infrastructure mode). To force an update of this list, adhocNetwork() must be called to disconnect the module from the current network. The returned list must be unallocated by the caller.

Returns :

a list of YWlanRecord objects, containing the SSID, channel, link quality and the type of security of the wireless network.

On failure, throws an exception or returns an empty list.

wireless→get_errorMessage()
wireless→errorMessage()
wireless.get_errorMessage()**YWireless**

Returns the error message of the latest error with the wireless lan interface.

| | |
|--------|--|
| js | function get_errorMessage() |
| nodejs | function get_errorMessage() |
| php | function get_errorMessage() |
| cpp | string get_errorMessage() |
| m | -(NSString*) errorMessage |
| pas | function get_errorMessage(): string |
| vb | function get_errorMessage() As String |
| cs | string get_errorMessage() |
| java | String get_errorMessage() |
| py | def get_errorMessage() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the wireless lan interface object

wireless→get_errorType()**YWireless****wireless→errorType()wireless.get_errorType()**

Returns the numerical error code of the latest error with the wireless lan interface.

| | |
|--------|--|
| js | function get_errorType() |
| nodejs | function get_errorType() |
| php | function get_errorType() |
| cpp | YRETCODE get_errorType() |
| pas | function get_errorType() : YRETCODE |
| vb | function get_errorType() As YRETCODE |
| cs | YRETCODE get_errorType() |
| java | int get_errorType() |
| py | def get_errorType() |

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the wireless lan interface object

wireless→get_friendlyName()**YWireless****wireless→friendlyName()wireless.get_friendlyName()**

Returns a global identifier of the wireless lan interface in the format MODULE_NAME.FUNCTION_NAME.

| | |
|--------|------------------------------|
| js | function get_friendlyName() |
| nodejs | function get_friendlyName() |
| php | function get_friendlyName() |
| cpp | string get_friendlyName() |
| m | -(NSString*) friendlyName |
| cs | string get_friendlyName() |
| java | String get_friendlyName() |
| py | def get_friendlyName() |

The returned string uses the logical names of the module and of the wireless lan interface if they are defined, otherwise the serial number of the module and the hardware identifier of the wireless lan interface (for exemple: MyCustomName.relay1)

Returns :

a string that uniquely identifies the wireless lan interface using logical names (ex: MyCustomName.relay1) On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

wireless→get_functionDescriptor()
wireless→functionDescriptor()
wireless.get_functionDescriptor()

YWireless

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

| | |
|---------|--|
| js | function get_functionDescriptor() |
| node.js | function get_functionDescriptor() |
| php | function get_functionDescriptor() |
| cpp | YFUN_DESCR get_functionDescriptor() |
| m | -(YFUN_DESCR) functionDescriptor |
| pas | function get_functionDescriptor() : YFUN_DESCR |
| vb | function get_functionDescriptor() As YFUN_DESCR |
| cs | YFUN_DESCR get_functionDescriptor() |
| java | String get_functionDescriptor() |
| py | def get_functionDescriptor() |

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

wireless→get_functionId()**YWireless****wireless→functionId()wireless.get_functionId()**

Returns the hardware identifier of the wireless lan interface, without reference to the module.

| | |
|---------|---|
| js | function get_functionId() |
| node.js | function get_functionId() |
| php | function get_functionId() |
| cpp | string get_functionId() |
| m | -(NSString*) functionId |
| vb | function get_functionId() As String |
| cs | string get_functionId() |
| java | String get_functionId() |
| py | def get_functionId() |

For example `relay1`

Returns :

a string that identifies the wireless lan interface (ex: `relay1`) On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

wireless→get_hardwareId()**YWireless****wireless→hardwareId()wireless.get_hardwareId()**

Returns the unique hardware identifier of the wireless lan interface in the form SERIAL.FUNCTIONID.

| | |
|--------|---|
| js | function get_hardwareId() |
| nodejs | function get_hardwareId() |
| php | function get_hardwareId() |
| cpp | string get_hardwareId() |
| m | -(NSString*) hardwareId |
| vb | function get_hardwareId() As String |
| cs | string get_hardwareId() |
| java | String get_hardwareId() |
| py | def get_hardwareId() |

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the wireless lan interface. (for example RELAYL01-123456.relay1)

Returns :

a string that uniquely identifies the wireless lan interface (ex: RELAYL01-123456.relay1) On failure, throws an exception or returns Y_HARDWAREID_INVALID.

wireless→get_linkQuality()**YWireless****wireless→linkQuality()wireless.get_linkQuality()**

Returns the link quality, expressed in percent.

```
js function get_linkQuality( )  
node.js function get_linkQuality( )  
php function get_linkQuality( )  
cpp int get_linkQuality( )  
m -(int) linkQuality  
pas function get_linkQuality( ): LongInt  
vb function get_linkQuality( ) As Integer  
cs int get_linkQuality( )  
java int get_linkQuality( )  
py def get_linkQuality( )  
cmd YWireless target get_linkQuality
```

Returns :

an integer corresponding to the link quality, expressed in percent

On failure, throws an exception or returns Y_LINKQUALITY_INVALID.

wireless→get_logicalName()**YWireless****wireless→logicalName()wireless.get_logicalName()**

Returns the logical name of the wireless lan interface.

| | |
|--------|--|
| js | function get_logicalName() |
| nodejs | function get_logicalName() |
| php | function get_logicalName() |
| cpp | string get_logicalName() |
| m | -(NSString*) logicalName |
| pas | function get_logicalName(): string |
| vb | function get_logicalName() As String |
| cs | string get_logicalName() |
| java | String get_logicalName() |
| py | def get_logicalName() |
| cmd | YWireless target get_logicalName |

Returns :

a string corresponding to the logical name of the wireless lan interface. On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

wireless→get_message()**YWireless****wireless→message()wireless.get_message()**

Returns the latest status message from the wireless interface.

| | |
|---------|---|
| js | function get_message() |
| node.js | function get_message() |
| php | function get_message() |
| cpp | string get_message() |
| m | -(NSString*) message |
| pas | function get_message() : string |
| vb | function get_message() As String |
| cs | string get_message() |
| java | String get_message() |
| py | def get_message() |
| cmd | YWireless target get_message |

Returns :

a string corresponding to the latest status message from the wireless interface

On failure, throws an exception or returns Y_MESSAGE_INVALID.

wireless→get_module()**YWireless****wireless→module()wireless.get_module()**

Gets the YModule object for the device on which the function is located.

| | |
|--------|--|
| js | function get_module() |
| nodejs | function get_module() |
| php | function get_module() |
| cpp | YModule * get_module() |
| m | -(YModule*) module |
| pas | function get_module() : TYModule |
| vb | function get_module() As YModule |
| cs | YModule get_module() |
| java | YModule get_module() |
| py | def get_module() |

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

wireless→get_module_async() wireless→module_async()

YWireless

Gets the `YModule` object for the device on which the function is located (asynchronous version).

```
js  function get_module_async( callback, context )
node.js function get_module_async( callback, context )
```

If the function cannot be located on any module, the returned `YModule` object does not show as online. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking Firefox javascript VM that does not implement context switching during blocking I/O calls. See the documentation section on asynchronous Javascript calls for more details.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the requested `YModule` object

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

wireless→get_security()**YWireless****wireless→security()wireless.get_security()**

Returns the security algorithm used by the selected wireless network.

| | |
|--------|--|
| js | function get_security() |
| nodejs | function get_security() |
| php | function get_security() |
| cpp | Y_SECURITY_enum get_security() |
| m | -(Y_SECURITY_enum) security |
| pas | function get_security() : Integer |
| vb | function get_security() As Integer |
| cs | int get_security() |
| java | int get_security() |
| py | def get_security() |
| cmd | YWireless target get_security |

Returns :

a value among Y_SECURITY_UNKNOWN, Y_SECURITY_OPEN, Y_SECURITY_WEP, Y_SECURITY_WPA and Y_SECURITY_WPA2 corresponding to the security algorithm used by the selected wireless network

On failure, throws an exception or returns Y_SECURITY_INVALID.

wireless→get_ssid()**YWireless****wireless→ssid()wireless.get_ssid()**

Returns the wireless network name (SSID).

```
js function get_ssid( )
node.js function get_ssid( )
php function get_ssid( )
cpp string get_ssid( )
m -(NSString*) ssid
pas function get_ssid( ): string
vb function get_ssid( ) As String
cs string get_ssid( )
java String get_ssid( )
py def get_ssid( )
cmd YWireless target get_ssid
```

Returns :

a string corresponding to the wireless network name (SSID)

On failure, throws an exception or returns Y_SSID_INVALID.

wireless→get(userData)**YWireless****wireless→userData()wireless.get(userData())**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

| | |
|--------|--|
| js | <code>function get(userData) </code> |
| nodejs | <code>function get(userData) </code> |
| php | <code>function get(userData) </code> |
| cpp | <code>void * get(userData) </code> |
| m | <code>-(void*) userData </code> |
| pas | <code>function get(userData): Tobject </code> |
| vb | <code>function get(userData) As Object </code> |
| cs | <code>object get(userData) </code> |
| java | <code>Object get(userData) </code> |
| py | <code>def get(userData) </code> |

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

wireless→isOnline()|wireless.isOnline()**YWireless**

Checks if the wireless lan interface is currently reachable, without raising any error.

| | |
|--------|---------------------------------------|
| js | function isOnline() |
| nodejs | function isOnline() |
| php | function isOnline() |
| cpp | bool isOnline() |
| m | - (BOOL) isOnline |
| pas | function isOnline() : boolean |
| vb | function isOnline() As Boolean |
| cs | bool isOnline() |
| java | boolean isOnline() |
| py | def isOnline() |

If there is a cached value for the wireless lan interface in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the wireless lan interface.

Returns :

true if the wireless lan interface can be reached, and false otherwise

wireless→isOnline_async()

YWireless

Checks if the wireless lan interface is currently reachable, without raising any error (asynchronous version).

```
js function isOnline_async( callback, context)
nodejs function isOnline_async( callback, context)
```

If there is a cached value for the wireless lan interface in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the boolean result

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

wireless→joinNetwork()wireless.joinNetwork()**YWireless**

Changes the configuration of the wireless lan interface to connect to an existing access point (infrastructure mode).

```

js   function joinNetwork( ssid, securityKey)
nodejs function joinNetwork( ssid, securityKey)
php  function joinNetwork( $ssid, $securityKey)
cpp   int joinNetwork( string ssid, string securityKey)
m    -(int) joinNetwork : (NSString*) ssid
      : (NSString*) securityKey
pas   function joinNetwork( ssid: string, securityKey: string): integer
vb    function joinNetwork( ByVal ssid As String,
                           ByVal securityKey As String) As Integer
cs    int joinNetwork( string ssid, string securityKey)
java  int joinNetwork( String ssid, String securityKey)
py    def joinNetwork( ssid, securityKey)
cmd   YWireless target joinNetwork ssid securityKey

```

Remember to call the `saveToFlash()` method and then to reboot the module to apply this setting.

Parameters :

ssid the name of the network to connect to
securityKey the network key, as a character string

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

wireless→load()wireless.load()**YWireless**

Preloads the wireless lan interface cache with a specified validity duration.

| | |
|---------------------|--|
| <code>js</code> | <code>function load(msValidity)</code> |
| <code>nodejs</code> | <code>function load(msValidity)</code> |
| <code>php</code> | <code>function load(\$msValidity)</code> |
| <code>cpp</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>m</code> | <code>-(YRETCODE) load : (int) msValidity</code> |
| <code>pas</code> | <code>function load(msValidity: integer): YRETCODE</code> |
| <code>vb</code> | <code>function load(ByVal msValidity As Integer) As YRETCODE</code> |
| <code>cs</code> | <code>YRETCODE load(int msValidity)</code> |
| <code>java</code> | <code>int load(long msValidity)</code> |
| <code>py</code> | <code>def load(msValidity)</code> |

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

wireless→load_async()

YWireless

Preloads the wireless lan interface cache with a specified validity duration (asynchronous version).

```
js function load_async( msValidity, callback, context)
nodejs function load_async( msValidity, callback, context)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance. This asynchronous version exists only in Javascript. It uses a callback instead of a return value in order to avoid blocking the Javascript virtual machine.

Parameters :

msValidity an integer corresponding to the validity of the loaded function parameters, in milliseconds

callback callback function that is invoked when the result is known. The callback function receives three arguments: the caller-specific context object, the receiving function object and the error code (or YAPI_SUCCESS)

context caller-specific object that is passed as-is to the callback function

Returns :

nothing : the result is provided to the callback.

wireless→nextWireless()wireless.nextWireless()**YWireless**

Continues the enumeration of wireless lan interfaces started using `yFirstWireless()`.

| | |
|---------------------|--|
| <code>js</code> | <code>function nextWireless()</code> |
| <code>nodejs</code> | <code>function nextWireless()</code> |
| <code>php</code> | <code>function nextWireless()</code> |
| <code>cpp</code> | <code>YWireless * nextWireless()</code> |
| <code>m</code> | <code>-(YWireless*) nextWireless</code> |
| <code>pas</code> | <code>function nextWireless(): TYWireless</code> |
| <code>vb</code> | <code>function nextWireless() As YWireless</code> |
| <code>cs</code> | <code>YWireless nextWireless()</code> |
| <code>java</code> | <code>YWireless nextWireless()</code> |
| <code>py</code> | <code>def nextWireless()</code> |

Returns :

a pointer to a `YWireless` object, corresponding to a wireless lan interface currently online, or a `null` pointer if there are no more wireless lan interfaces to enumerate.

wireless→registerValueCallback() wireless.registerValueCallback()

YWireless

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback )
node.js function registerValueCallback( callback )
php  function registerValueCallback( $callback )
cpp   int registerValueCallback( YWirelessValueCallback callback )
m    -(int) registerValueCallback : (YWirelessValueCallback) callback
pas   function registerValueCallback( callback: TYWirelessValueCallback): LongInt
vb    function registerValueCallback( ) As Integer
cs    int registerValueCallback( ValueCallback callback )
java  int registerValueCallback( UpdateCallback callback )
py    def registerValueCallback( callback )
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

wireless→set_logicalName()
wireless→setLogicalName()
wireless.set_logicalName()

YWireless

Changes the logical name of the wireless lan interface.

| | |
|---------------|---|
| js | function set_logicalName(newval) |
| nodejs | function set_logicalName(newval) |
| php | function set_logicalName(\$newval) |
| cpp | int set_logicalName(const string& newval) |
| m | -(int) setLogicalName : (NSString*) newval |
| pas | function set_logicalName(newval: string): integer |
| vb | function set_logicalName(ByVal newval As String) As Integer |
| cs | int set_logicalName(string newval) |
| java | int set_logicalName(String newval) |
| py | def set_logicalName(newval) |
| cmd | YWireless target set_logicalName newval |

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the wireless lan interface.

Returns :

`YAPI_SUCCESS` if the call succeeds. On failure, throws an exception or returns a negative error code.

wireless→set(userData)**YWireless****wireless→setUserData(wireless.set(userData))**

Stores a user context provided as argument in the userData attribute of the function.

| | |
|---------|---|
| js | function set(userData) |
| node.js | function set(userData) |
| php | function set(userData \$data) |
| cpp | void set(userData void* data) |
| m | -(void) setUserData : (void*) data |
| pas | procedure set(userData data: Tobject) |
| vb | procedure set(userData ByVal data As Object) |
| cs | void set(userData object data) |
| java | void set(userData Object data) |
| py | def set(userData data) |

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

wireless→wait_async()

YWireless

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

```
js  function wait_async( callback, context)
```

```
nodejs function wait_async( callback, context)
```

The callback function can therefore freely issue synchronous or asynchronous commands, without risking to block the Javascript VM.

Parameters :

callback callback function that is invoked when all pending commands on the module are completed. The callback function receives two arguments: the caller-specific context object and the receiving function object.

context caller-specific object that is passed as-is to the callback function

Returns :

nothing.

Index

A

Accelerometer 36
adhocNetwork, YWireless 1728
AnButton 82

B

Blueprint 10

C

calibrate, YLightSensor 765
calibrateFromPoints, YAccelerometer 40
calibrateFromPoints, YCarbonDioxide 128
calibrateFromPoints, YCompass 204
calibrateFromPoints, YCurrent 248
calibrateFromPoints, YGenericSensor 557
calibrateFromPoints, YGyro 607
calibrateFromPoints, YHumidity 691
calibrateFromPoints, YLightSensor 766
calibrateFromPoints, YMagnetometer 809
calibrateFromPoints, YPower 995
calibrateFromPoints, YPressure 1042
calibrateFromPoints, YQt 1154
calibrateFromPoints,YSensor 1308
calibrateFromPoints, YTemperature 1390
calibrateFromPoints, YTilt 1435
calibrateFromPoints, YVoc 1478
calibrateFromPoints, YVoltage 1521
callbackLogin, YNetwork 908
cancel3DCalibration, YRefFrame 1228
CarbonDioxide 124
CheckLogicalName, YAPI 12
clear, YDisplayLayer 460
clearConsole, YDisplayLayer 461
Clock 1193
ColorLed 167
Compass 200
Configuration 1224
consoleOut, YDisplayLayer 462
copyLayerContent, YDisplay 412
Current 244

D

Data 322, 332, 345
DataLogger 287
delayedPulse, YDigitalIO 364
delayedPulse, YRelay 1268
delayedPulse, YWatchdog 1680
describe, YAccelerometer 41
describe, YAnButton 86
describe, YCarbonDioxide 129
describe, YColorLed 170
describe, YCompass 205

describe, YCurrent 249
describe, YDataLogger 290
describe, YDigitalIO 365
describe, YDisplay 413
describe, YDualPower 494
describe, YFiles 523
describe, YGenericSensor 558
describe, YGyro 608
describe, YHubPort 661
describe, YHumidity 692
describe, YLed 733
describe, YLightSensor 767
describe, YMagnetometer 810
describe, YModule 861
describe, YNetwork 909
describe, YOsControl 967
describe, YPower 996
describe, YPressure 1043
describe, YPwmOutput 1085
describe, YPwmPowerSource 1126
describe, YQt 1155
describe, YRealTimeClock 1196
describe, YRefFrame 1229
describe, YRelay 1269
describe, YSensor 1309
describe, YServo 1351
describe, YTemperature 1391
describe, YTilt 1436
describe, YVoc 1479
describe, YVoltage 1522
describe, YVSource 1563
describe, YWakeUpMonitor 1600
describe, YWakeUpSchedule 1639
describe, YWatchdog 1681
describe, YWireless 1729
Digital 360
DisableExceptions, YAPI 13
Display 408
DisplayLayer 459
download, YFiles 524
download, YModule 862
download_async, YFiles 525
drawBar, YDisplayLayer 463
drawBitmap, YDisplayLayer 464
drawCircle, YDisplayLayer 465
drawDisc, YDisplayLayer 466
drawImage, YDisplayLayer 467
drawPixel, YDisplayLayer 468
drawRect, YDisplayLayer 469
drawText, YDisplayLayer 470
dutyCycleMove, YPwmOutput 1086
Dynamic 3

E

EnableExceptions, YAPI 14
EnableUSBHost, YAPI 15
Error 7
External 491

F

fade, YDisplay 414
Files 3, 520
FindAccelerometer, YAccelerometer 38
FindAnButton, YAnButton 84
FindCarbonDioxide, YCarbonDioxide 126
FindColorLed, YColorLed 168
FindCompass, YCompass 202
FindCurrent, YCurrent 246
FindDataLogger, YDataLogger 288
FindDigitalIO, YDigitalIO 362
FindDisplay, YDisplay 410
FindDualPower, YDualPower 492
FindFiles, YFiles 521
FindGenericSensor, YGenericSensor 555
FindGyro, YGyro 605
FindHubPort, YHubPort 659
FindHumidity, YHumidity 689
FindLed, YLed 731
FindLightSensor, YLightSensor 763
FindMagnetometer, YMagnetometer 807
FindModule, YModule 859
FindNetwork, YNetwork 906
FindOsControl, YOsControl 965
FindPower, YPower 993
FindPressure, YPressure 1040
FindPwmOutput, YPwmOutput 1083
FindPwmPowerSource, YPwmPowerSource 1124
FindQt, YQt 1152
FindRealTimeClock, YRealTimeClock 1194
FindRefFrame, YRefFrame 1226
FindRelay, YRelay 1266
FindSensor, YSensor 1306
FindServo,YServo 1349
FindTemperature, YTemperature 1388
FindTilt, YTilt 1433
FindVoc, YVoc 1476
FindVoltage, YVoltage 1519
FindVSource, YVSource 1561
FindWakeUpMonitor, YWakeUpMonitor 1598
FindWakeUpSchedule, YWakeUpSchedule 1637
FindWatchdog, YWatchdog 1678
FindWireless, YWireless 1726
FirstAccelerometer, YAccelerometer 39
FirstAnButton, YAnButton 85
FirstCarbonDioxide, YCarbonDioxide 127
FirstColorLed, YColorLed 169
FirstCompass, YCompass 203
FirstCurrent, YCurrent 247
FirstDataLogger, YDataLogger 289
FirstDigitalIO, YDigitalIO 363

FirstDisplay, YDisplay 411
FirstDualPower, YDualPower 493
FirstFiles, YFiles 522
FirstGenericSensor, YGenericSensor 556
FirstGyro, YGyro 606
FirstHubPort, YHubPort 660
FirstHumidity, YHumidity 690
FirstLed, YLed 732
FirstLightSensor, YLightSensor 764
FirstMagnetometer, YMagnetometer 808
FirstModule, YModule 860
FirstNetwork, YNetwork 907
FirstOsControl, YOsControl 966
FirstPower, YPower 994
FirstPressure, YPressure 1041
FirstPwmOutput, YPwmOutput 1084
FirstPwmPowerSource, YPwmPowerSource 1125
FirstQt, YQt 1153
FirstRealTimeClock, YRealTimeClock 1195
FirstRefFrame, YRefFrame 1227
FirstRelay, YRelay 1267
FirstSensor, YSensor 1307
FirstServo, YServo 1350
FirstTemperature, YTemperature 1389
FirstTilt, YTilt 1434
FirstVoc, YVoc 1477
FirstVoltage, YVoltage 1520
FirstVSource, YVSource 1562
FirstWakeUpMonitor, YWakeUpMonitor 1599
FirstWakeUpSchedule, YWakeUpSchedule 1638
FirstWatchdog, YWatchdog 1679
FirstWireless, YWireless 1727
forgetAllDataStreams, YDataLogger 291
format_fs, YFiles 526
Formatted 322
Frame 1224
FreeAPI, YAPI 16
functionCount, YModule 863
functionId, YModule 864
functionName, YModule 865
Functions 11
functionValue, YModule 866

G

General 11
GenericSensor 553
get_3DCalibrationHint, YRefFrame 1230
get_3DCalibrationLogMsg, YRefFrame 1231
get_3DCalibrationProgress, YRefFrame 1232
get_3DCalibrationStage, YRefFrame 1233
get_3DCalibrationStageProgress, YRefFrame 1234
get_adminPassword, YNetwork 910
get_advertisedValue, YAccelerometer 42
get_advertisedValue, YAnButton 87
get_advertisedValue, YCarbonDioxide 130
get_advertisedValue, YColorLed 171
get_advertisedValue, YCompass 206

get_advertisedValue, YCurrent 250
get_advertisedValue, YDataLogger 292
get_advertisedValue, YDigitalIO 366
get_advertisedValue, YDisplay 415
get_advertisedValue, YDualPower 495
get_advertisedValue, YFiles 527
get_advertisedValue, YGenericSensor 559
get_advertisedValue, YGyro 609
get_advertisedValue, YHubPort 662
get_advertisedValue, YHumidity 693
get_advertisedValue, YLed 734
get_advertisedValue, YLightSensor 768
get_advertisedValue, YMagnetometer 811
get_advertisedValue, YNetwork 911
get_advertisedValue, YOsControl 968
get_advertisedValue, YPower 997
get_advertisedValue, YPressure 1044
get_advertisedValue, YPwmOutput 1087
get_advertisedValue, YPwmPowerSource 1127
get_advertisedValue, YQt 1156
get_advertisedValue, YRealTimeClock 1197
get_advertisedValue, YRefFrame 1235
get_advertisedValue, YRelay 1270
get_advertisedValue, YSensor 1310
get_advertisedValue, YServo 1352
get_advertisedValue, YTemperature 1392
get_advertisedValue, YTilt 1437
get_advertisedValue, YVoc 1480
get_advertisedValue, YVoltage 1523
get_advertisedValue, YVSource 1564
get_advertisedValue, YWakeUpMonitor 1601
get_advertisedValue, YWakeUpSchedule 1640
get_advertisedValue, YWatchdog 1682
get_advertisedValue, YWireless 1730
get_analogCalibration, YAnButton 88
get_autoStart, YDataLogger 293
get_autoStart, YWatchdog 1683
get_averageValue, YDataRun 322
get_averageValue, YDataStream 346
get_averageValue, YMeasure 851
get_baudRate, YHubPort 663
get_beacon, YModule 867
get_bearing, YRefFrame 1236
get_bitDirection, YDigitalIO 367
get_bitOpenDrain, YDigitalIO 368
get_bitPolarity, YDigitalIO 369
get_bitState, YDigitalIO 370
get_blinking, YLed 735
get_brightness, YDisplay 416
get_calibratedValue, YAnButton 89
get_calibrationMax, YAnButton 90
get_calibrationMin, YAnButton 91
get_callbackCredentials, YNetwork 912
get_callbackEncoding, YNetwork 913
get_callbackMaxDelay, YNetwork 914
get_callbackMethod, YNetwork 915
get_callbackMinDelay, YNetwork 916
get_callbackUrl, YNetwork 917
get_channel, YWireless 1731
get_columnCount, YDataStream 347
get_columnNames, YDataStream 348
get_cosPhi, YPower 998
get_countdown, YRelay 1271
get_countdown, YWatchdog 1684
get_currentRawValue, YAccelerometer 43
get_currentRawValue, YCarbonDioxide 131
get_currentRawValue, YCompass 207
get_currentRawValue, YCurrent 251
get_currentRawValue, YGenericSensor 560
get_currentRawValue, YGyro 610
get_currentRawValue, YHumidity 694
get_currentRawValue, YLightSensor 769
get_currentRawValue, YMagnetometer 812
get_currentRawValue, YPower 999
get_currentRawValue, YPressure 1045
get_currentRawValue, YQt 1157
get_currentRawValue, YSensor 1311
get_currentRawValue, YTemperature 1393
get_currentRawValue, YTilt 1438
get_currentRawValue, YVoc 1481
get_currentRawValue, YVoltage 1524
get_currentRunIndex, YDataLogger 294
get_currentValue, YAccelerometer 44
get_currentValue, YCarbonDioxide 132
get_currentValue, YCompass 208
get_currentValue, YCurrent 252
get_currentValue, YGenericSensor 561
get_currentValue, YGyro 611
get_currentValue, YHumidity 695
get_currentValue, YLightSensor 770
get_currentValue, YMagnetometer 813
get_currentValue, YPower 1000
get_currentValue, YPressure 1046
get_currentValue, YQt 1158
get_currentValue, YSensor 1312
get_currentValue, YTemperature 1394
get_currentValue, YTilt 1439
get_currentValue, YVoc 1482
get_currentValue, YVoltage 1525
get_data, YDataStream 349
get_dataRows, YDataStream 350
get_dataSamplesIntervalMs, YDataStream 351
get_dataSets, YDataLogger 295
get_dataStreams, YDataLogger 296
get_dateTime, YRealTimeClock 1198
get_detectedWlans, YWireless 1732
get_discoverable, YNetwork 918
get_display, YDisplayLayer 471
get_displayHeight, YDisplay 417
get_displayHeight, YDisplayLayer 472
get_displayLayer, YDisplay 418
get_displayType, YDisplay 419
get_displayWidth, YDisplay 420
get_displayWidth, YDisplayLayer 473
get_duration, YDataRun 323
get_duration, YDataStream 352
get_dutyCycle, YPwmOutput 1088
get_dutyCycleAtPowerOn, YPwmOutput 1089

get_enabled, YDisplay 421
get_enabled, YHubPort 664
get_enabled, YPwmOutput 1090
get_enabled, YServo 1353
get_enabledAtPowerOn, YPwmOutput 1091
get_enabledAtPowerOn, YServo 1354
get_endTimeUTC, YDataSet 333
get_endTimeUTC, YMeasure 852
getErrorMessage, YAccelerometer 45
getErrorMessage, YAnButton 92
getErrorMessage, YCarbonDioxide 133
getErrorMessage, YColorLed 172
getErrorMessage, YCompass 209
getErrorMessage, YCurrent 253
getErrorMessage, YDataLogger 297
getErrorMessage, YDigitalIO 371
getErrorMessage, YDisplay 422
getErrorMessage, YDualPower 496
getErrorMessage, YFiles 528
getErrorMessage, YGenericSensor 562
getErrorMessage, YGyro 612
getErrorMessage, YHubPort 665
getErrorMessage, YHumidity 696
getErrorMessage, YLed 736
getErrorMessage, YLightSensor 771
getErrorMessage, YMagnetometer 814
getErrorMessage, YModule 868
getErrorMessage, YNetwork 919
getErrorMessage, YOsControl 969
getErrorMessage, YPower 1001
getErrorMessage, YPressure 1047
getErrorMessage, YPwmOutput 1092
getErrorMessage, YPwmPowerSource 1128
getErrorMessage, YQt 1159
getErrorMessage, YRealTimeClock 1199
getErrorMessage, YRefFrame 1237
getErrorMessage, YRelay 1272
getErrorMessage, YSensor 1313
getErrorMessage, YServo 1355
getErrorMessage, YTemperature 1395
getErrorMessage, YTilt 1440
getErrorMessage, YVoc 1483
getErrorMessage, YVoltage 1526
getErrorMessage, YVSource 1565
getErrorMessage, YWakeUpMonitor 1602
getErrorMessage, YWakeUpSchedule 1641
getErrorMessage, YWatchdog 1685
getErrorMessage, YWireless 1733
get_errorType, YAccelerometer 46
get_errorType, YAnButton 93
get_errorType, YCarbonDioxide 134
get_errorType, YColorLed 173
get_errorType, YCompass 210
get_errorType, YCurrent 254
get_errorType, YDataLogger 298
get_errorType, YDigitalIO 372
get_errorType, YDisplay 423
get_errorType, YDualPower 497
get_errorType, YFiles 529
get_errorType, YGenericSensor 563
get_errorType, YGyro 613
get_errorType, YHubPort 666
get_errorType, YHumidity 697
get_errorType, YLed 737
get_errorType, YLightSensor 772
get_errorType, YMagnetometer 815
get_errorType, YModule 869
get_errorType, YNetwork 920
get_errorType, YOsControl 970
get_errorType, YPower 1002
get_errorType, YPressure 1048
get_errorType, YPwmOutput 1093
get_errorType, YPwmPowerSource 1129
get_errorType, YQt 1160
get_errorType, YRealTimeClock 1200
get_errorType, YRefFrame 1238
get_errorType, YRelay 1273
get_errorType, YSensor 1314
get_errorType, YServo 1356
get_errorType, YTemperature 1396
get_errorType, YTilt 1441
get_errorType, YVoc 1484
get_errorType, YVoltage 1527
get_errorType, YVSource 1566
get_errorType, YWakeUpMonitor 1603
get_errorType, YWakeUpSchedule 1642
get_errorType, YWatchdog 1686
get_errorType, YWireless 1734
get_extPowerFailure, YVSource 1567
get_extVoltage, YDualPower 498
get_failure, YVSource 1568
get_filesCount, YFiles 530
get_firmwareRelease, YModule 870
get_freeSpace, YFiles 531
get_frequency, YPwmOutput 1094
get_friendlyName, YAccelerometer 47
get_friendlyName, YAnButton 94
get_friendlyName, YCarbonDioxide 135
get_friendlyName, YColorLed 174
get_friendlyName, YCompass 211
get_friendlyName, YCurrent 255
get_friendlyName, YDataLogger 299
get_friendlyName, YDigitalIO 373
get_friendlyName, YDisplay 424
get_friendlyName, YDualPower 499
get_friendlyName, YFiles 532
get_friendlyName, YGenericSensor 564
get_friendlyName, YGyro 614
get_friendlyName, YHubPort 667
get_friendlyName, YHumidity 698
get_friendlyName, YLed 738
get_friendlyName, YLightSensor 773
get_friendlyName, YMagnetometer 816
get_friendlyName, YNetwork 921
get_friendlyName, YOsControl 971
get_friendlyName, YPower 1003
get_friendlyName, YPressure 1049
get_friendlyName, YPwmOutput 1095

get_friendlyName, YPwmPowerSource 1130
get_friendlyName, YQt 1161
get_friendlyName, YRealTimeClock 1201
get_friendlyName, YRefFrame 1239
get_friendlyName, YRelay 1274
get_friendlyName, YSensor 1315
get_friendlyName, YServo 1357
get_friendlyName, YTTemperature 1397
get_friendlyName, YTilt 1442
get_friendlyName, YVoc 1485
get_friendlyName, YVoltage 1528
get_friendlyName, YVSource 1569
get_friendlyName, YWakeUpMonitor 1604
get_friendlyName, YWakeUpSchedule 1643
get_friendlyName, YWatchdog 1687
get_friendlyName, YWireless 1735
get_functionDescriptor, YAccelerometer 48
get_functionDescriptor, YAnButton 95
get_functionDescriptor, YCarbonDioxide 136
get_functionDescriptor, YColorLed 175
get_functionDescriptor, YCompass 212
get_functionDescriptor, YCurrent 256
get_functionDescriptor, YDataLogger 300
get_functionDescriptor, YDigitalIO 374
get_functionDescriptor, YDisplay 425
get_functionDescriptor, YDualPower 500
get_functionDescriptor, YFiles 533
get_functionDescriptor, YGenericSensor 565
get_functionDescriptor, YGyro 615
get_functionDescriptor, YHubPort 668
get_functionDescriptor, YHumidity 699
get_functionDescriptor, YLed 739
get_functionDescriptor, YLightSensor 774
get_functionDescriptor, YMagnetometer 817
get_functionDescriptor, YNetwork 922
get_functionDescriptor, YOsControl 972
get_functionDescriptor, YPower 1004
get_functionDescriptor, YPressure 1050
get_functionDescriptor, YPwmOutput 1096
get_functionDescriptor, YPwmPowerSource 1131
get_functionDescriptor, YQt 1162
get_functionDescriptor, YRealTimeClock 1202
get_functionDescriptor, YRefFrame 1240
get_functionDescriptor, YRelay 1275
get_functionDescriptor, YSensor 1316
get_functionDescriptor, YServo 1358
get_functionDescriptor, YTTemperature 1398
get_functionDescriptor, YTilt 1443
get_functionDescriptor, YVoc 1486
get_functionDescriptor, YVoltage 1529
get_functionDescriptor, YVSource 1570
get_functionDescriptor, YWakeUpMonitor 1605
get_functionDescriptor, YWakeUpSchedule 1644
get_functionDescriptor, YWatchdog 1688
get_functionDescriptor, YWireless 1736
get_functionId, YAccelerometer 49
get_functionId, YAnButton 96
get_functionId, YCarbonDioxide 137
get_functionId, YColorLed 176
get_functionId, YCompass 213
get_functionId, YCurrent 257
get_functionId, YDataLogger 301
get_functionId, YDataSet 334
get_functionId, YDigitalIO 375
get_functionId, YDisplay 426
get_functionId, YDualPower 501
get_functionId, YFiles 534
get_functionId, YGenericSensor 566
get_functionId, YGyro 616
get_functionId, YHubPort 669
get_functionId, YHumidity 700
get_functionId, YLed 740
get_functionId, YLightSensor 775
get_functionId, YMagnetometer 818
get_functionId, YNetwork 923
get_functionId, YOsControl 973
get_functionId, YPower 1005
get_functionId, YPressure 1051
get_functionId, YPwmOutput 1097
get_functionId, YPwmPowerSource 1132
get_functionId, YQt 1163
get_functionId, YRealTimeClock 1203
get_functionId, YRefFrame 1241
get_functionId, YRelay 1276
get_functionId, YSensor 1317
get_functionId, YServo 1359
get_functionId, YTTemperature 1399
get_functionId, YTilt 1444
get_functionId, YVoc 1487
get_functionId, YVoltage 1530
get_functionId, YVSource 1571
get_functionId, YWakeUpMonitor 1606
get_functionId, YWakeUpSchedule 1645
get_functionId, YWatchdog 1689
get_functionId, YWireless 1737
get_hardwareId, YAccelerometer 50
get_hardwareId, YAnButton 97
get_hardwareId, YCarbonDioxide 138
get_hardwareId, YColorLed 177
get_hardwareId, YCompass 214
get_hardwareId, YCurrent 258
get_hardwareId, YDataLogger 302
get_hardwareId, YDataSet 335
get_hardwareId, YDigitalIO 376
get_hardwareId, YDisplay 427
get_hardwareId, YDualPower 502
get_hardwareId, YFiles 535
get_hardwareId, YGenericSensor 567
get_hardwareId, YGyro 617
get_hardwareId, YHubPort 670
get_hardwareId, YHumidity 701
get_hardwareId, YLed 741
get_hardwareId, YLightSensor 776
get_hardwareId, YMagnetometer 819
get_hardwareId, YModule 871
get_hardwareId, YNetwork 924
get_hardwareId, YOsControl 974
get_hardwareId, YPower 1006

get_hardwareId, YPressure 1052
get_hardwareId, YPwmOutput 1098
get_hardwareId, YPwmPowerSource 1133
get_hardwareId, YQt 1164
get_hardwareId, YRealTimeClock 1204
get_hardwareId, YRefFrame 1242
get_hardwareId, YRelay 1277
get_hardwareId, YSensor 1318
get_hardwareId,YServo 1360
get_hardwareId, YTemperature 1400
get_hardwareId, YTilt 1445
get_hardwareId, YVoc 1488
get_hardwareId, YVoltage 1531
get_hardwareId, YVSource 1572
get_hardwareId, YWakeUpMonitor 1607
get_hardwareId, YWakeUpSchedule 1646
get_hardwareId, YWatchdog 1690
get_hardwareId, YWireless 1738
get_heading, YGyro 618
get_highestValue, YAccelerometer 51
get_highestValue, YCarbonDioxide 139
get_highestValue, YCompass 215
get_highestValue, YCurrent 259
get_highestValue, YGenericSensor 568
get_highestValue, YGyro 619
get_highestValue, YHumidity 702
get_highestValue, YLightSensor 777
get_highestValue, YMagnetometer 820
get_highestValue, YPower 1007
get_highestValue, YPressure 1053
get_highestValue, YQt 1165
get_highestValue, YSensor 1319
get_highestValue, YTemperature 1401
get_highestValue, YTilt 1446
get_highestValue, YVoc 1489
get_highestValue, YVoltage 1532
get_hours, YWakeUpSchedule 1647
get_hslColor, YColorLed 178
get_icon2d, YModule 872
get_ipAddress, YNetwork 925
get_isPressed, YAnButton 98
get_lastLogs, YModule 873
get_lastTimePressed, YAnButton 99
get_lastTimeReleased, YAnButton 100
get_layerCount, YDisplay 428
get_layerHeight, YDisplay 429
get_layerHeight, YDisplayLayer 474
get_layerWidth, YDisplay 430
get_layerWidth, YDisplayLayer 475
get_linkQuality, YWireless 1739
get_list, YFiles 536
get_logFrequency, YAccelerometer 52
get_logFrequency, YCarbonDioxide 140
get_logFrequency, YCompass 216
get_logFrequency, YCurrent 260
get_logFrequency, YGenericSensor 569
get_logFrequency, YGyro 620
get_logFrequency, YHumidity 703
get_logFrequency, YLightSensor 778
get_logFrequency, YMagnetometer 821
get_logFrequency, YPower 1008
get_logFrequency, YPressure 1054
get_logFrequency, YQt 1166
get_logFrequency, YSensor 1320
get_logFrequency, YTemperature 1402
get_logFrequency, YTilt 1447
get_logFrequency, YVoc 1490
get_logFrequency, YVoltage 1533
get_logicalName, YAccelerometer 53
get_logicalName, YAnButton 101
get_logicalName, YCarbonDioxide 141
get_logicalName, YColorLed 179
get_logicalName, YCompass 217
get_logicalName, YCurrent 261
get_logicalName, YDataLogger 303
get_logicalName, YDigitalIO 377
get_logicalName, YDisplay 431
get_logicalName, YDualPower 503
get_logicalName, YFiles 537
get_logicalName, YGenericSensor 570
get_logicalName, YGyro 621
get_logicalName, YHubPort 671
get_logicalName, YHumidity 704
get_logicalName, YLed 742
get_logicalName, YLightSensor 779
get_logicalName, YMagnetometer 822
get_logicalName, YModule 874
get_logicalName, YNetwork 926
get_logicalName, YOsControl 975
get_logicalName, YPower 1009
get_logicalName, YPressure 1055
get_logicalName, YPwmOutput 1099
get_logicalName, YPwmPowerSource 1134
get_logicalName, YQt 1167
get_logicalName, YRealTimeClock 1205
get_logicalName, YRefFrame 1243
get_logicalName, YRelay 1278
get_logicalName, YSensor 1321
get_logicalName, YServo 1361
get_logicalName, YTemperature 1403
get_logicalName, YTilt 1448
get_logicalName, YVoc 1491
get_logicalName, YVoltage 1534
get_logicalName, YVSource 1573
get_logicalName, YWakeUpMonitor 1608
get_logicalName, YWakeUpSchedule 1648
get_logicalName, YWatchdog 1691
get_logicalName, YWireless 1740
get_lowestValue, YAccelerometer 54
get_lowestValue, YCarbonDioxide 142
get_lowestValue, YCompass 218
get_lowestValue, YCurrent 262
get_lowestValue, YGenericSensor 571
get_lowestValue, YGyro 622
get_lowestValue, YHumidity 705
get_lowestValue, YLightSensor 780
get_lowestValue, YMagnetometer 823
get_lowestValue, YPower 1010

get_lowestValue, YPressure 1056
get_lowestValue, YQt 1168
get_lowestValue, YSensor 1322
get_lowestValue, YTemperature 1404
get_lowestValue, YTilt 1449
get_lowestValue, YVoc 1492
get_lowestValue, YVoltage 1535
get_luminosity, YLed 743
get_luminosity, YModule 875
get_macAddress, YNetwork 927
get_magneticHeading, YCompass 219
get_maxTimeOnStateA, YRelay 1279
get_maxTimeOnStateA, YWatchdog 1692
get_maxTimeOnStateB, YRelay 1280
get_maxTimeOnStateB, YWatchdog 1693
get_maxValue, YDataRun 324
get_maxValue, YDataStream 353
get_maxValue, YMeasure 853
get_measureNames, YDataRun 325
get_measures, YDataSet 336
get_message, YWireless 1741
get_meter, YPower 1011
get_meterTimer, YPower 1012
get_minutes, YWakeUpSchedule 1649
get_minutesA, YWakeUpSchedule 1650
get_minutesB, YWakeUpSchedule 1651
get_minValue, YDataRun 326
get_minValue, YDataStream 354
get_minValue, YMeasure 854
get_module, YAccelerometer 55
get_module, YAnButton 102
get_module, YCarbonDioxide 143
get_module, YColorLed 180
get_module, YCompass 220
get_module, YCurrent 263
get_module, YDataLogger 304
get_module, YDigitalIO 378
get_module, YDisplay 432
get_module, YDualPower 504
get_module, YFiles 538
get_module, YGenericSensor 572
get_module, YGyro 623
get_module, YHubPort 672
get_module, YHumidity 706
get_module, YLed 744
get_module, YLightSensor 781
get_module, YMagnetometer 824
get_module, YNetwork 928
get_module, YOsControl 976
get_module, YPower 1013
get_module, YPressure 1057
get_module, YPwmOutput 1100
get_module, YPwmPowerSource 1135
get_module, YQt 1169
get_module, YRealTimeClock 1206
get_module, YRefFrame 1244
get_module, YRelay 1281
get_module, YSensor 1323
get_module, YServo 1362
get_module, YTemperature 1405
get_module, YTilt 1450
get_module, YVoc 1493
get_module, YVoltage 1536
get_module, YVSource 1574
get_module, YWakeUpMonitor 1609
get_module, YWakeUpSchedule 1652
get_module, YWatchdog 1694
get_module, YWireless 1742
get_module_async, YAccelerometer 56
get_module_async, YAnButton 103
get_module_async, YCarbonDioxide 144
get_module_async, YColorLed 181
get_module_async, YCompass 221
get_module_async, YCurrent 264
get_module_async, YDataLogger 305
get_module_async, YDigitalIO 379
get_module_async, YDisplay 433
get_module_async, YDualPower 505
get_module_async, YFiles 539
get_module_async, YGenericSensor 573
get_module_async, YGyro 624
get_module_async, YHubPort 673
get_module_async, YHumidity 707
get_module_async, YLed 745
get_module_async, YLightSensor 782
get_module_async, YMagnetometer 825
get_module_async, YNetwork 929
get_module_async, YOsControl 977
get_module_async, YPower 1014
get_module_async, YPressure 1058
get_module_async, YPwmOutput 1101
get_module_async, YPwmPowerSource 1136
get_module_async, YQt 1170
get_module_async, YRealTimeClock 1207
get_module_async, YRefFrame 1245
get_module_async, YRelay 1282
get_module_async, YSensor 1324
get_module_async, YServo 1363
get_module_async, YTemperature 1406
get_module_async, YTilt 1451
get_module_async, YVoc 1494
get_module_async, YVoltage 1537
get_module_async, YVSource 1575
get_module_async, YWakeUpMonitor 1610
get_module_async, YWakeUpSchedule 1653
get_module_async, YWatchdog 1695
get_module_async, YWireless 1743
get_monthDays, YWakeUpSchedule 1654
get_months, YWakeUpSchedule 1655
get_mountOrientation, YRefFrame 1246
get_mountPosition, YRefFrame 1247
get_neutral, YServo 1364
get_nextOccurrence, YWakeUpSchedule 1656
get_nextWakeUp, YWakeUpMonitor 1611
get_orientation, YDisplay 434
get_output, YRelay 1283
get_output, YWatchdog 1696
get_outputVoltage, YDigitalIO 380

get_overCurrent, YVSource 1576
get_overHeat, YVSource 1577
get_overLoad, YVSource 1578
get_period, YPwmOutput 1102
get_persistentSettings, YModule 876
get_pitch, YGyro 625
get_poeCurrent, YNetwork 930
get_portDirection, YDigitalIO 381
get_portOpenDrain, YDigitalIO 382
get_portPolarity, YDigitalIO 383
get_portSize, YDigitalIO 384
get_portState, YDigitalIO 385
get_portState, YHubPort 674
get_position, YServo 1365
get_positionAtPowerOn, YServo 1366
get_power, YLed 746
get_powerControl, YDualPower 506
get_powerDuration, YWakeUpMonitor 1612
get_powerMode, YPwmPowerSource 1137
get_powerState, YDualPower 507
get_preview, YDataSet 337
get_primaryDNS, YNetwork 931
get_productId, YModule 877
get_productName, YModule 878
get_productRelease, YModule 879
get_progress, YDataSet 338
get_pulseCounter, YAnButton 104
get_pulseDuration, YPwmOutput 1103
get_pulseTimer, YAnButton 105
get_pulseTimer, YRelay 1284
get_pulseTimer, YWatchdog 1697
get_quaternionW, YGyro 626
get_quaternionX, YGyro 627
get_quaternionY, YGyro 628
get_quaternionZ, YGyro 629
get_range, YServo 1367
get_rawValue, YAnButton 106
get_readiness, YNetwork 932
get_rebootCountdown, YModule 880
get_recordedData, YAccelerometer 57
get_recordedData, YCarbonDioxide 145
get_recordedData, YCompass 222
get_recordedData, YCurrent 265
get_recordedData, YGenericSensor 574
get_recordedData, YGyro 630
get_recordedData, YHumidity 708
get_recordedData, YLightSensor 783
get_recordedData, YMagnetometer 826
get_recordedData, YPower 1015
get_recordedData, YPressure 1059
get_recordedData, YQt 1171
get_recordedData, YSensor 1325
get_recordedData, YTemperature 1407
get_recordedData, YTilt 1452
get_recordedData, YVoc 1495
get_recordedData, YVoltage 1538
get_recording, YDataLogger 306
get_regulationFailure, YVSource 1579
get_reportFrequency, YAccelerometer 58
get_reportFrequency, YCarbonDioxide 146
get_reportFrequency, YCompass 223
get_reportFrequency, YCurrent 266
get_reportFrequency, YGenericSensor 575
get_reportFrequency, YGyro 631
get_reportFrequency, YHumidity 709
get_reportFrequency, YLightSensor 784
get_reportFrequency, YMagnetometer 827
get_reportFrequency, YPower 1016
get_reportFrequency, YPressure 1060
get_reportFrequency, YQt 1172
get_reportFrequency, YSensor 1326
get_reportFrequency, YTemperature 1408
get_reportFrequency, YTilt 1453
get_reportFrequency, YVoc 1496
get_reportFrequency, YVoltage 1539
get_resolution, YAccelerometer 59
get_resolution, YCarbonDioxide 147
get_resolution, YCompass 224
get_resolution, YCurrent 267
get_resolution, YGenericSensor 576
get_resolution, YGyro 632
get_resolution, YHumidity 710
get_resolution, YLightSensor 785
get_resolution, YMagnetometer 828
get_resolution, YPower 1017
get_resolution, YPressure 1061
get_resolution, YQt 1173
get_resolution, YSensor 1327
get_resolution, YTemperature 1409
get_resolution, YTilt 1454
get_resolution, YVoc 1497
get_resolution, YVoltage 1540
get_rgbColor, YColorLed 182
get_rgbColorAtPowerOn, YColorLed 183
get_roll, YGyro 633
get_router, YNetwork 933
getRowCount, YDataStream 355
get_runIndex, YDataStream 356
get_running, YWatchdog 1698
get_secondaryDNS, YNetwork 934
get_security, YWireless 1744
get_sensitivity, YAnButton 107
get_sensorType, YTemperature 1410
get_serialNumber, YModule 881
get_shutdownCountdown, YOsControl 978
get_signalRange, YGenericSensor 577
get_signalUnit, YGenericSensor 578
get_signalValue, YGenericSensor 579
get_sleepCountdown, YWakeUpMonitor 1613
get_ssid, YWireless 1745
get_startTime, YDataStream 357
getStartTimeUTC, YDataRun 327
getStartTimeUTC, YDataSet 339
getStartTimeUTC, YDataStream 358
getStartTimeUTC, YMeasure 855
get_startupSeq, YDisplay 435
get_state, YRelay 1285
get_state, YWatchdog 1699

get_stateAtPowerOn, YRelay 1286
get_stateAtPowerOn, YWatchdog 1700
get_subnetMask, YNetwork 935
get_summary, YDataSet 340
get_timeSet, YRealTimeClock 1208
get_timeUTC, YDataLogger 307
get_triggerDelay, YWatchdog 1701
get_triggerDuration, YWatchdog 1702
get_unit, YAccelerometer 60
get_unit, YCarbonDioxide 148
get_unit, YCompass 225
get_unit, YCurrent 268
get_unit, YDataSet 341
get_unit, YGenericSensor 580
get_unit, YGyro 634
get_unit, YHumidity 711
get_unit, YLightSensor 786
get_unit, YMagnetometer 829
get_unit, YPower 1018
get_unit, YPressure 1062
get_unit, YQt 1174
get_unit,YSensor 1328
get_unit, YTemperature 1411
get_unit, YTilt 1455
get_unit, YVoc 1498
get_unit, YVoltage 1541
get_unit, YVSource 1580
get_unixTime, YRealTimeClock 1209
get_upTime, YModule 882
get_usbBandwidth, YModule 883
get_usbCurrent, YModule 884
get_userData, YAccelerometer 61
get_userData, YAnButton 108
get_userData, YCarbonDioxide 149
get_userData, YColorLed 184
get_userData, YCompass 226
get_userData, YCurrent 269
get_userData, YDataLogger 308
get_userData, YDigitalIO 386
get_userData, YDisplay 436
get_userData, YDualPower 508
get_userData, YFiles 540
get_userData, YGenericSensor 581
get_userData, YGyro 635
get_userData, YHubPort 675
get_userData, YHumidity 712
get_userData, YLed 747
get_userData, YLightSensor 787
get_userData, YMagnetometer 830
get_userData, YModule 885
get_userData, YNetwork 936
get_userData, YOsControl 979
get_userData, YPower 1019
get_userData, YPressure 1063
get_userData, YPwmOutput 1104
get_userData, YPwmPowerSource 1138
get_userData, YQt 1175
get_userData, YRealTimeClock 1210
get_userData, YRefFrame 1248

get(userData, YRelay 1287
get(userData, YSensor 1329
get(userData, YServo 1368
get(userData, YTemperature 1412
get(userData, YTilt 1456
get(userData, YVoc 1499
get(userData, YVoltage 1542
get(userData, YVSource 1581
get(userData, YWakeUpMonitor 1614
get(userData, YWakeUpSchedule 1657
get(userData, YWatchdog 1703
get(userData, YWireless 1746
get(userPassword, YNetwork 937
get_utcOffset, YRealTimeClock 1211
get_valueCount, YDataRun 328
get_valueInterval, YDataRun 329
get_valueRange, YGenericSensor 582
get_voltage, YVSource 1582
get_wakeUpReason, YWakeUpMonitor 1615
get_wakeUpState, YWakeUpMonitor 1616
get_weekDays, YWakeUpSchedule 1658
get_wwwWatchdogDelay, YNetwork 938
get_xValue, YAccelerometer 62
get_xValue, YGyro 636
get_xValue, YMagnetometer 831
get_yValue, YAccelerometer 63
get_yValue, YGyro 637
get_yValue, YMagnetometer 832
get_zValue, YAccelerometer 64
get_zValue, YGyro 638
get_zValue, YMagnetometer 833
GetAPIVersion, YAPI 17
GetTickCount, YAPI 18
Gyroscope 603

H

HandleEvents, YAPI 19
hide, YDisplayLayer 476
hslMove, YColorLed 185
Humidity 687

I

InitAPI, YAPI 20
Interface 36, 82, 124, 167, 200, 244, 287, 360, 408, 459, 491, 520, 553, 603, 658, 687, 730, 761, 805, 857, 903, 991, 1038, 1081, 1123, 1150, 1193, 1264, 1304, 1347, 1386, 1431, 1474, 1517, 1560, 1596, 1635, 1676, 1725
Introduction 1
isOnline, YAccelerometer 65
isOnline, YAnButton 109
isOnline, YCarbonDioxide 150
isOnline, YColorLed 186
isOnline, YCompass 227
isOnline, YCurrent 270
isOnline, YDataLogger 309
isOnline, YDigitalIO 387
isOnline, YDisplay 437

isOnline, YDualPower 509
isOnline, YFiles 541
isOnline, YGenericSensor 583
isOnline, YGyro 639
isOnline, YHubPort 676
isOnline, YHumidity 713
isOnline, YLed 748
isOnline, YLightSensor 788
isOnline, YMagnetometer 834
isOnline, YModule 886
isOnline, YNetwork 939
isOnline, YOsControl 980
isOnline, YPower 1020
isOnline, YPressure 1064
isOnline, YPwmOutput 1105
isOnline, YPwmPowerSource 1139
isOnline, YQt 1176
isOnline, YRealTimeClock 1212
isOnline, YRefFrame 1249
isOnline, YRelay 1289
isOnline, YSensor 1330
isOnline,YServo 1369
isOnline, YTemperature 1413
isOnline, YTilt 1457
isOnline, YVoc 1500
isOnline, YVoltage 1543
isOnline, YVSource 1583
isOnline, YWakeUpMonitor 1617
isOnline, YWakeUpSchedule 1659
isOnline, YWatchdog 1704
isOnline, YWireless 1747
isOnline_async, YAccelerometer 66
isOnline_async, YAnButton 110
isOnline_async, YCarbonDioxide 151
isOnline_async, YColorLed 187
isOnline_async, YCompass 228
isOnline_async, YCurrent 271
isOnline_async, YDataLogger 310
isOnline_async, YDigitalIO 388
isOnline_async, YDisplay 438
isOnline_async, YDualPower 510
isOnline_async, YFiles 542
isOnline_async, YGenericSensor 584
isOnline_async, YGyro 640
isOnline_async, YHubPort 677
isOnline_async, YHumidity 714
isOnline_async, YLed 749
isOnline_async, YLightSensor 789
isOnline_async, YMagnetometer 835
isOnline_async, YModule 887
isOnline_async, YNetwork 940
isOnline_async, YOsControl 981
isOnline_async, YPower 1021
isOnline_async, YPressure 1065
isOnline_async, YPwmOutput 1106
isOnline_async, YPwmPowerSource 1140
isOnline_async, YQt 1177
isOnline_async, YRealTimeClock 1213
isOnline_async, YRefFrame 1250

isOnline_async, YRelay 1289
isOnline_async, YSensor 1331
isOnline_async, YServo 1370
isOnline_async, YTemperature 1414
isOnline_async, YTilt 1458
isOnline_async, YVoc 1501
isOnline_async, YVoltage 1544
isOnline_async, YVSource 1584
isOnline_async, YWakeUpMonitor 1618
isOnline_async, YWakeUpSchedule 1660
isOnline_async, YWatchdog 1705
isOnline_async, YWireless 1748

J

joinNetwork, YWireless 1749

L

Library 3
LightSensor 761
lineTo, YDisplayLayer 477
load, YAccelerometer 67
load, YAnButton 111
load, YCarbonDioxide 152
load, YColorLed 188
load, YCompass 229
load, YCurrent 272
load, YDataLogger 311
load, YDigitalIO 389
load, YDisplay 439
load, YDualPower 511
load, YFiles 543
load, YGenericSensor 585
load, YGyro 641
load, YHubPort 678
load, YHumidity 715
load, YLed 750
load, YLightSensor 790
load, YMagnetometer 836
load, YModule 888
load, YNetwork 941
load, YOsControl 982
load, YPower 1022
load, YPressure 1066
load, YPwmOutput 1107
load, YPwmPowerSource 1141
load, YQt 1178
load, YRealTimeClock 1214
load, YRefFrame 1251
load, YRelay 1290
load, YSensor 1332
load, YServo 1371
load, YTemperature 1415
load, YTilt 1459
load, YVoc 1502
load, YVoltage 1545
load, YVSource 1585
load, YWakeUpMonitor 1619
load, YWakeUpSchedule 1661

load, YWatchdog 1706
load, YWireless 1750
load_async, YAccelerometer 69
load_async, YAnButton 112
load_async, YCarbonDioxide 154
load_async, YColorLed 189
load_async, YCompass 231
load_async, YCurrent 274
load_async, YDataLogger 312
load_async, YDigitalIO 390
load_async, YDisplay 440
load_async, YDualPower 512
load_async, YFiles 544
load_async, YGenericSensor 587
load_async, YGyro 643
load_async, YHubPort 679
load_async, YHumidity 717
load_async, YLed 751
load_async, YLightSensor 792
load_async, YMagnetometer 838
load_async, YModule 889
load_async, YNetwork 942
load_async, YOsControl 983
load_async, YPower 1024
load_async, YPressure 1068
load_async, YPwmOutput 1108
load_async, YPwmPowerSource 1142
load_async, YQt 1180
load_async, YRealTimeClock 1215
load_async, YRefFrame 1252
load_async, YRelay 1291
load_async, YSensor 1334
load_async, YServo 1372
load_async, YTemperature 1417
load_async, YTilt 1461
load_async, YVoc 1504
load_async, YVoltage 1547
load_async, YVSource 1586
load_async, YWakeUpMonitor 1620
load_async, YWakeUpSchedule 1662
load_async, YWatchdog 1707
load_async, YWireless 1751
loadCalibrationPoints, YAccelerometer 68
loadCalibrationPoints, YCarbonDioxide 153
loadCalibrationPoints, YCompass 230
loadCalibrationPoints, YCurrent 273
loadCalibrationPoints, YGenericSensor 586
loadCalibrationPoints, YGyro 642
loadCalibrationPoints, YHumidity 716
loadCalibrationPoints, YLightSensor 791
loadCalibrationPoints, YMagnetometer 837
loadCalibrationPoints, YPower 1023
loadCalibrationPoints, YPressure 1067
loadCalibrationPoints, YQt 1179
loadCalibrationPoints, YSensor 1333
loadCalibrationPoints, YTemperature 1416
loadCalibrationPoints, YTilt 1460
loadCalibrationPoints, YVoc 1503
loadCalibrationPoints, YVoltage 1546

loadMore, YDataSet 342
loadMore_async, YDataSet 343

M

Magnetometer 805
Measured 851
Module 5, 857
more3DCalibration, YRefFrame 1253
move, YServo 1373
moveTo, YDisplayLayer 478

N

Network 903
newSequence, YDisplay 441
nextAccelerometer, YAccelerometer 70
nextAnButton, YAnButton 113
nextCarbonDioxide, YCarbonDioxide 155
nextColorLed, YColorLed 190
nextCompass, YCompass 232
nextCurrent, YCurrent 275
nextDataLogger, YDataLogger 313
nextDigitalIO, YDigitalIO 391
nextDisplay, YDisplay 442
nextDualPower, YDualPower 513
nextFiles, YFiles 545
nextGenericSensor, YGenericSensor 588
nextGyro, YGyro 644
nextHubPort, YHubPort 680
nextHumidity, YHumidity 718
nextLed, YLed 752
nextLightSensor, YLightSensor 793
nextMagnetometer, YMagnetometer 839
nextModule, YModule 890
nextNetwork, YNetwork 943
nextOsControl, YOsControl 984
nextPower, YPower 1025
nextPressure, YPressure 1069
nextPwmOutput, YPwmOutput 1109
nextPwmPowerSource, YPwmPowerSource 1143
nextQt, YQt 1181
nextRealTimeClock, YRealTimeClock 1216
nextRefFrame, YRefFrame 1254
nextRelay, YRelay 1292
nextSensor, YSensor 1335
nextServo, YServo 1374
nextTemperature, YTemperature 1418
nextTilt, YTilt 1462
nextVoc, YVoc 1505
nextVoltage, YVoltage 1548
nextVSource, YVSource 1587
nextWakeUpMonitor, YWakeUpMonitor 1621
nextWakeUpSchedule, YWakeUpSchedule 1663
nextWatchdog, YWatchdog 1708
nextWireless, YWireless 1752

O

Object 459

P

pauseSequence, YDisplay 443
ping, YNetwork 944
playSequence, YDisplay 444
Port 658
Power 491, 991
PreregisterHub, YAPI 21
Pressure 1038
pulse, YDigitalIO 392
pulse, YRelay 1293
pulse, YVSource 1588
pulse, YWatchdog 1709
pulseDurationMove, YPwmOutput 1110
PwmPowerSource 1123
Python 3

Q

Quaternion 1150

R

Real 1193
reboot, YModule 891
Recorded 332
Reference 10, 1224
registerAnglesCallback, YGyro 645
RegisterDeviceArrivalCallback, YAPI 22
RegisterDeviceRemovalCallback, YAPI 23
RegisterHub, YAPI 24
RegisterHubDiscoveryCallback, YAPI 25
registerLogCallback, YModule 892
RegisterLogFunction, YAPI 26
registerQuaternionCallback, YGyro 646
registerTimedReportCallback, YAccelerometer 71
registerTimedReportCallback, YCarbonDioxide 156
registerTimedReportCallback, YCompass 233
registerTimedReportCallback, YCurrent 276
registerTimedReportCallback, YGenericSensor 589
registerTimedReportCallback, YGyro 647
registerTimedReportCallback, YHumidity 719
registerTimedReportCallback, YLightSensor 794
registerTimedReportCallback, YMagnetometer 840
registerTimedReportCallback, YPower 1026
registerTimedReportCallback, YPressure 1070
registerTimedReportCallback, YQt 1182
registerTimedReportCallback, YSensor 1336
registerTimedReportCallback, YTemperature 1419
registerTimedReportCallback, YTilt 1463
registerTimedReportCallback, YVoc 1506
registerTimedReportCallback, YVoltage 1549

registerValueCallback, YAccelerometer 72
registerValueCallback, YAnButton 114
registerValueCallback, YCarbonDioxide 157
registerValueCallback, YColorLed 191
registerValueCallback, YCompass 234
registerValueCallback, YCurrent 277
registerValueCallback, YDataLogger 314
registerValueCallback, YDigitalIO 393
registerValueCallback, YDisplay 445
registerValueCallback, YDualPower 514
registerValueCallback, YFiles 546
registerValueCallback, YGenericSensor 590
registerValueCallback, YGyro 648
registerValueCallback, YHubPort 681
registerValueCallback, YHumidity 720
registerValueCallback, YLed 753
registerValueCallback, YLightSensor 795
registerValueCallback, YMagnetometer 841
registerValueCallback, YNetwork 945
registerValueCallback, YOsControl 985
registerValueCallback, YPower 1027
registerValueCallback, YPressure 1071
registerValueCallback, YPwmOutput 1111
registerValueCallback, YPwmPowerSource 1144
registerValueCallback, YQt 1183
registerValueCallback, YRealTimeClock 1217
registerValueCallback, YRefFrame 1255
registerValueCallback, YRelay 1294
registerValueCallback, YSensor 1337
registerValueCallback, YServo 1375
registerValueCallback, YTemperature 1420
registerValueCallback, YTilt 1464
registerValueCallback, YVoc 1507
registerValueCallback, YVoltage 1550
registerValueCallback, YVSource 1589
registerValueCallback, YWakeUpMonitor 1622
registerValueCallback, YWakeUpSchedule 1664
registerValueCallback, YWatchdog 1710
registerValueCallback, YWireless 1753
Relay 1264
remove, YFiles 547
reset, YDisplayLayer 479
reset, YPower 1028
resetAll, YDisplay 446
resetCounter, YAnButton 115
resetSleepCountDown, YWakeUpMonitor 1623
resetWatchdog, YWatchdog 1711
revertFromFlash, YModule 893
rgbMove, YColorLed 192

S

save3DCalibration, YRefFrame 1256
saveSequence, YDisplay 447
saveToFlash, YModule 894
SelectArchitecture, YAPI 27
selectColorPen, YDisplayLayer 480
selectEraser, YDisplayLayer 481
selectFont, YDisplayLayer 482
selectGrayPen, YDisplayLayer 483

Sensor 1304
Sequence 322, 332, 345
Servo 1347
set_adminPassword, YNetwork 946
set_analogCalibration, YAnButton 116
set_autoStart, YDataLogger 315
set_autoStart, YWatchdog 1712
set_beacon, YModule 895
set_bearing, YRefFrame 1257
set_bitDirection, YDigitalIO 394
set_bitOpenDrain, YDigitalIO 395
set_bitPolarity, YDigitalIO 396
set_bitState, YDigitalIO 397
set_blinking, YLed 754
set_brightness, YDisplay 448
set_calibrationMax, YAnButton 117
set_calibrationMin, YAnButton 118
set_callbackCredentials, YNetwork 947
set_callbackEncoding, YNetwork 948
set_callbackMaxDelay, YNetwork 949
set_callbackMethod, YNetwork 950
set_callbackMinDelay, YNetwork 951
set_callbackUrl, YNetwork 952
set_discoverable, YNetwork 953
set_dutyCycle, YPwmOutput 1112
set_dutyCycleAtPowerOn, YPwmOutput 1113
set_enabled, YDisplay 449
set_enabled, YHubPort 682
set_enabled, YPwmOutput 1114
set_enabled, YServo 1376
set_enabledAtPowerOn, YPwmOutput 1115
set_enabledAtPowerOn, YServo 1377
set_frequency, YPwmOutput 1116
set_highestValue, YAccelerometer 73
set_highestValue, YCarbonDioxide 158
set_highestValue, YCompass 235
set_highestValue, YCurrent 278
set_highestValue, YGenericSensor 591
set_highestValue, YGyro 649
set_highestValue, YHumidity 721
set_highestValue, YLightSensor 796
set_highestValue, YMagnetometer 842
set_highestValue, YPower 1029
set_highestValue, YPressure 1072
set_highestValue, YQt 1184
set_highestValue, YSensor 1338
set_highestValue, YTTemperature 1421
set_highestValue, YTilt 1465
set_highestValue, YVoc 1508
set_highestValue, YVoltage 1551
set_hours, YWakeUpSchedule 1665
set_hslColor, YColorLed 193
set_logFrequency, YAccelerometer 74
set_logFrequency, YCarbonDioxide 159
set_logFrequency, YCompass 236
set_logFrequency, YCurrent 279
set_logFrequency, YGenericSensor 592
set_logFrequency, YGyro 650
set_logFrequency, YHumidity 722
set_logFrequency, YLightSensor 797
set_logFrequency, YMagnetometer 843
set_logFrequency, YPower 1030
set_logFrequency, YPressure 1073
set_logFrequency, YQt 1185
set_logFrequency, YSensor 1339
set_logFrequency, YTTemperature 1422
set_logFrequency, YTilt 1466
set_logFrequency, YVoc 1509
set_logFrequency, YVoltage 1552
set_logicalName, YAccelerometer 75
set_logicalName, YAnButton 119
set_logicalName, YCarbonDioxide 160
set_logicalName, YColorLed 194
set_logicalName, YCompass 237
set_logicalName, YCurrent 280
set_logicalName, YDataLogger 316
set_logicalName, YDigitalIO 398
set_logicalName, YDisplay 450
set_logicalName, YDualPower 515
set_logicalName, YFiles 548
set_logicalName, YGenericSensor 593
set_logicalName, YGyro 651
set_logicalName, YHubPort 683
set_logicalName, YHumidity 723
set_logicalName, YLed 755
set_logicalName, YLightSensor 798
set_logicalName, YMagnetometer 844
set_logicalName, YModule 896
set_logicalName, YNetwork 954
set_logicalName, YOsControl 986
set_logicalName, YPower 1031
set_logicalName, YPressure 1074
set_logicalName, YPwmOutput 1117
set_logicalName, YPwmPowerSource 1145
set_logicalName, YQt 1186
set_logicalName, YRealTimeClock 1218
set_logicalName, YRefFrame 1258
set_logicalName, YRelay 1295
set_logicalName, YSensor 1340
set_logicalName, YServo 1378
set_logicalName, YTTemperature 1423
set_logicalName, YTilt 1467
set_logicalName, YVoc 1510
set_logicalName, YVoltage 1553
set_logicalName, YVSource 1590
set_logicalName, YWakeUpMonitor 1624
set_logicalName, YWakeUpSchedule 1666
set_logicalName, YWatchdog 1713
set_logicalName, YWireless 1754
set_lowestValue, YAccelerometer 76
set_lowestValue, YCarbonDioxide 161
set_lowestValue, YCompass 238
set_lowestValue, YCurrent 281
set_lowestValue, YGenericSensor 594
set_lowestValue, YGyro 652
set_lowestValue, YHumidity 724
set_lowestValue, YLightSensor 799
set_lowestValue, YMagnetometer 845

set_lowestValue, YPower 1032
set_lowestValue, YPressure 1075
set_lowestValue, YQt 1187
set_lowestValue, YSensor 1341
set_lowestValue, YTemperature 1424
set_lowestValue, YTilt 1468
set_lowestValue, YVoc 1511
set_lowestValue, YVoltage 1554
set_luminosity, YLed 756
set_luminosity, YModule 897
set_maxTimeOnStateA, YRelay 1296
set_maxTimeOnStateA, YWatchdog 1714
set_maxTimeOnStateB, YRelay 1297
set_maxTimeOnStateB, YWatchdog 1715
set_minutes, YWakeUpSchedule 1667
set_minutesA, YWakeUpSchedule 1668
set_minutesB, YWakeUpSchedule 1669
set_monthDays, YWakeUpSchedule 1670
set_months, YWakeUpSchedule 1671
set_mountPosition, YRefFrame 1259
set_neutral,YServo 1379
set_nextWakeUp, YWakeUpMonitor 1625
set_orientation, YDisplay 451
set_output, YRelay 1298
set_output, YWatchdog 1716
set_outputVoltage, YDigitalIO 399
set_period, YPwmOutput 1118
set_portDirection, YDigitalIO 400
set_portOpenDrain, YDigitalIO 401
set_portPolarity, YDigitalIO 402
set_portState, YDigitalIO 403
set_position, YServo 1380
set_positionAtPowerOn, YServo 1381
set_power, YLed 757
set_powerControl, YDualPower 516
set_powerDuration, YWakeUpMonitor 1626
set_powerMode, YPwmPowerSource 1146
set_primaryDNS, YNetwork 955
set_pulseDuration, YPwmOutput 1119
set_range, YServo 1382
set_recording, YDataLogger 317
set_reportFrequency, YAccelerometer 77
set_reportFrequency, YCarbonDioxide 162
set_reportFrequency, YCompass 239
set_reportFrequency, YCurrent 282
set_reportFrequency, YGenericSensor 595
set_reportFrequency, YGyro 653
set_reportFrequency, YHumidity 725
set_reportFrequency, YLightSensor 800
set_reportFrequency, YMagnetometer 846
set_reportFrequency, YPower 1033
set_reportFrequency, YPressure 1076
set_reportFrequency, YQt 1188
set_reportFrequency, YSensor 1342
set_reportFrequency, YTemperature 1425
set_reportFrequency, YTilt 1469
set_reportFrequency, YVoc 1512
set_reportFrequency, YVoltage 1555
set_resolution, YAccelerometer 78
set_resolution, YCarbonDioxide 163
set_resolution, YCompass 240
set_resolution, YCurrent 283
set_resolution, YGenericSensor 596
set_resolution, YGyro 654
set_resolution, YHumidity 726
set_resolution, YLightSensor 801
set_resolution, YMagnetometer 847
set_resolution, YPower 1034
set_resolution, YPressure 1077
set_resolution, YQt 1189
set_resolution, YSensor 1343
set_resolution, YTemperature 1426
set_resolution, YTilt 1470
set_resolution, YVoc 1513
set_resolution, YVoltage 1556
set_rgbColor, YColorLed 195
set_rgbColorAtPowerOn, YColorLed 196
set_running, YWatchdog 1717
set_secondaryDNS, YNetwork 956
set_sensitivity, YAnButton 120
set_sensorType, YTemperature 1427
set_signalRange, YGenericSensor 597
set_sleepCountdown, YWakeUpMonitor 1627
set_startupSeq, YDisplay 452
set_state, YRelay 1299
set_state, YWatchdog 1718
set_stateAtPowerOn, YRelay 1300
set_stateAtPowerOn, YWatchdog 1719
set_timeUTC, YDataLogger 318
set_triggerDelay, YWatchdog 1720
set_triggerDuration, YWatchdog 1721
set_unit, YGenericSensor 598
set_unixTime, YRealTimeClock 1219
set_usbBandwidth, YModule 898
set_userData, YAccelerometer 79
set_userData, YAnButton 121
set_userData, YCarbonDioxide 164
set_userData, YColorLed 197
set_userData, YCompass 241
set_userData, YCurrent 284
set_userData, YDataLogger 319
set_userData, YDigitalIO 404
set_userData, YDisplay 453
set_userData, YDualPower 517
set_userData, YFiles 549
set_userData, YGenericSensor 599
set_userData, YGyro 655
set_userData, YHubPort 684
set_userData, YHumidity 727
set_userData, YLed 758
set_userData, YLightSensor 802
set_userData, YMagnetometer 848
set_userData, YModule 899
set_userData, YNetwork 957
set_userData, YOsControl 987
set_userData, YPower 1035
set_userData, YPressure 1078
set_userData, YPwmOutput 1120

set(userData, YPwmPowerSource 1147
set(userData, YQt 1190
set(userData, YRealTimeClock 1220
set(userData, YRefFrame 1260
set(userData, YRelay 1301
set(userData, YSensor 1344
set(userData, YServo 1383
set(userData, YTemperature 1428
set(userData, YTilt 1471
set(userData, YVoc 1514
set(userData, YVoltage 1557
set(userData, YVSource 1591
set(userData, YWakeUpMonitor 1628
set(userData, YWakeUpSchedule 1672
set(userData, YWatchdog 1722
set(userData, YWireless 1755
set(userPassword, YNetwork 958
set(utcOffset, YRealTimeClock 1221
set(valueInterval, YDataRun 330
set(valueRange, YGenericSensor 600
set(voltage, YVSource 1592
set(weekDays, YWakeUpSchedule 1673
set(wwwWatchdogDelay, YNetwork 959
setAntialiasingMode, YDisplayLayer 484
setConsoleBackground, YDisplayLayer 485
setConsoleMargins, YDisplayLayer 486
setConsoleWordWrap, YDisplayLayer 487
SetDelegate, YAPI 28
setLayerPosition, YDisplayLayer 488
SetTimeout, YAPI 29
shutdown, YOsControl 988
Sleep, YAPI 30
sleep, YWakeUpMonitor 1629
sleepFor, YWakeUpMonitor 1630
sleepUntil, YWakeUpMonitor 1631
Source 3, 1560
start3DCalibration, YRefFrame 1261
stopSequence, YDisplay 454
Supply 491
swapLayerContent, YDisplay 455

T

Temperature 1386
Tilt 1431
Time 1193
toggle_bitState, YDigitalIO 405
triggerFirmwareUpdate, YModule 900
TriggerHubDiscovery, YAPI 31

U

Unformatted 345
unhide, YDisplayLayer 489
UnregisterHub, YAPI 32
UpdateDeviceList, YAPI 33
UpdateDeviceList_async, YAPI 34
upload, YDisplay 456
upload, YFiles 550
useDHCP, YNetwork 960

useStaticIP, YNetwork 961

V

Value 851
Voltage 1517, 1560
voltageMove, YVSource 1593

W

wait_async, YAccelerometer 80
wait_async, YAnButton 122
wait_async, YCarbonDioxide 165
wait_async, YColorLed 198
wait_async, YCompass 242
wait_async, YCurrent 285
wait_async, YDataLogger 320
wait_async, YDigitalIO 406
wait_async, YDisplay 457
wait_async, YDualPower 518
wait_async, YFiles 551
wait_async, YGenericSensor 601
wait_async, YGyro 656
wait_async, YHubPort 685
wait_async, YHumidity 728
wait_async, YLed 759
wait_async, YLightSensor 803
wait_async, YMagnetometer 849
wait_async, YModule 901
wait_async, YNetwork 962
wait_async, YOsControl 989
wait_async, YPower 1036
wait_async, YPressure 1079
wait_async, YPwmOutput 1121
wait_async, YPwmPowerSource 1148
wait_async, YQt 1191
wait_async, YRealTimeClock 1222
wait_async, YRefFrame 1262
wait_async, YRelay 1302
wait_async, YSensor 1345
wait_async, YServo 1384
wait_async, YTemperature 1429
wait_async, YTilt 1472
wait_async, YVoc 1515
wait_async, YVoltage 1558
wait_async, YVSource 1594
wait_async, YWakeUpMonitor 1632
wait_async, YWakeUpSchedule 1674
wait_async, YWatchdog 1723
wait_async, YWireless 1756
wakeUp, YWakeUpMonitor 1633
WakeUpMonitor 1596
WakeUpSchedule 1635
Watchdog 1676
Wireless 1725

Y

YAccelerometer 38-80
YAnButton 84-122

YAPI 12-34
YCarbonDioxide 126-165
yCheckLogicalName 12
YColorLed 168-198
YCompass 202-242
YCurrent 246-285
YDataLogger 288-320
YDataRun 322-330
YDataSet 333-343
YDataStream 346-358
YDigitalIO 362-406
yDisableExceptions 13
YDisplay 410-457
YDisplayLayer 460-489
YDualPower 492-518
yEnableExceptions 14
yEnableUSBHost 15
YFiles 521-551
yFindAccelerometer 38
yFindAnButton 84
yFindCarbonDioxide 126
yFindColorLed 168
yFindCompass 202
yFindCurrent 246
yFindDataLogger 288
yFindDigitalIO 362
yFindDisplay 410
yFindDualPower 492
yFindFiles 521
yFindGenericSensor 555
yFindGyro 605
yFindHubPort 659
yFindHumidity 689
yFindLed 731
yFindLightSensor 763
yFindMagnetometer 807
yFindModule 859
yFindNetwork 906
yFindOsControl 965
yFindPower 993
yFindPressure 1040
yFindPwmOutput 1083
yFindPwmPowerSource 1124
yFindQt 1152
yFindRealTimeClock 1194
yFindRefFrame 1226
yFindRelay 1266
yFindSensor 1306
yFindServo 1349
yFindTemperature 1388
yFindTilt 1433
yFindVoc 1476
yFindVoltage 1519
yFindVSource 1561
yFindWakeUpMonitor 1598
yFindWakeUpSchedule 1637
yFindWatchdog 1678
yFindWireless 1726
yFirstAccelerometer 39
yFirstAnButton 85
yFirstCarbonDioxide 127
yFirstColorLed 169
yFirstCompass 203
yFirstCurrent 247
yFirstDataLogger 289
yFirstDigitalIO 363
yFirstDisplay 411
yFirstDualPower 493
yFirstFiles 522
yFirstGenericSensor 556
yFirstGyro 606
yFirstHubPort 660
yFirstHumidity 690
yFirstLed 732
yFirstLightSensor 764
yFirstMagnetometer 808
yFirstModule 860
yFirstNetwork 907
yFirstOsControl 966
yFirstPower 994
yFirstPressure 1041
yFirstPwmOutput 1084
yFirstPwmPowerSource 1125
yFirstQt 1153
yFirstRealTimeClock 1195
yFirstRefFrame 1227
yFirstRelay 1267
yFirstSensor 1307
yFirstServo 1350
yFirstTemperature 1389
yFirstTilt 1434
yFirstVoc 1477
yFirstVoltage 1520
yFirstVSource 1562
yFirstWakeUpMonitor 1599
yFirstWakeUpSchedule 1638
yFirstWatchdog 1679
yFirstWireless 1727
yFreeAPI 16
YGenericSensor 555-601
yGetAPIVersion 17
yGetTickCount 18
YGyro 605-656
yHandleEvents 19
YHubPort 659-685
YHumidity 689-728
yInitAPI 20
YLed 731-759
YLightSensor 763-803
YMagnetometer 807-849
YMeasure 851-855
YModule 859-901
YNetwork 906-962
Yocto-Demo 3
Yocto-hub 658
YOscControl 965-989
YPower 993-1036
yPreregisterHub 21

YPressure 1040-1079
YPwmOutput 1083-1121
YPwmPowerSource 1124-1148
YQt 1152-1191
YRealTimeClock 1194-1222
YRefFrame 1226-1262
yRegisterDeviceArrivalCallback 22
yRegisterDeviceRemovalCallback 23
yRegisterHub 24
yRegisterHubDiscoveryCallback 25
yRegisterLogFunction 26
YRelay 1266-1302
ySelectArchitecture 27
YSensor 1306-1345
YServo 1349-1384

ySetDelegate 28
ySetTimeout 29
ySleep 30
YTemperature 1388-1429
YTilt 1433-1472
yTriggerHubDiscovery 31
yUnregisterHub 32
yUpdateDeviceList 33
yUpdateDeviceList_async 34
YVoc 1476-1515
YVoltage 1519-1558
YVSource 1561-1594
YWakeUpMonitor 1598-1633
YWakeUpSchedule 1637-1674
YWatchdog 1678-1723
YWireless 1726-1756