



PYTHON API Reference

Table of contents

1. Introduction	1
2. Using the Yocto-Demo with Python	3
2.1. Source files	3
2.2. Dynamic library	3
2.3. Control of the Led function	3
2.4. Control of the module part	5
2.5. Error handling	7
Blueprint	10
3. Reference	10
3.1. General functions	11
3.2. Accelerometer function interface	32
3.3. Altitude function interface	74
3.4. AnButton function interface	116
3.5. CarbonDioxide function interface	154
3.6. ColorLed function interface	193
3.7. Compass function interface	222
3.8. Current function interface	262
3.9. DataLogger function interface	301
3.10. Formatted data sequence	335
3.11. Recorded data sequence	345
3.12. Unformatted data sequence	357
3.13. Digital IO function interface	372
3.14. Display function interface	416
3.15. DisplayLayer object interface	463
3.16. External power supply control interface	495
3.17. Files function interface	520
3.18. GenericSensor function interface	548
3.19. Gyroscope function interface	597
3.20. Yocto-hub port interface	648
3.21. Humidity function interface	673
3.22. Led function interface	712
3.23. LightSensor function interface	739
3.24. Magnetometer function interface	781

3.25. Measured value	823
3.26. Module control interface	829
3.27. Motor function interface	876
3.28. Network function interface	917
3.29. OS control	974
3.30. Power function interface	997
3.31. Pressure function interface	1040
3.32. PwmInput function interface	1079
3.33. Pwm function interface	1127
3.34. PwmPowerSource function interface	1165
3.35. Quaternion interface	1188
3.36. Real Time Clock function interface	1227
3.37. Reference frame configuration	1254
3.38. Relay function interface	1290
3.39. Sensor function interface	1326
3.40. SerialPort function interface	1365
3.41. Servo function interface	1422
3.42. Temperature function interface	1457
3.43. Tilt function interface	1498
3.44. Voc function interface	1537
3.45. Voltage function interface	1576
3.46. Voltage source function interface	1615
3.47. WakeUpMonitor function interface	1643
3.48. WakeUpSchedule function interface	1678
3.49. Watchdog function interface	1715
3.50. Wireless function interface	1760
Index	1791

1. Introduction

This manual is intended to be used as a reference for Yoctopuce Python library, in order to interface your code with USB sensors and controllers.

The next chapter is taken from the free USB device Yocto-Demo, in order to provide a concrete examples of how the library is used within a program.

The remaining part of the manual is a function-by-function, class-by-class documentation of the API. The first section describes all general-purpose global function, while the forthcoming sections describe the various classes that you may have to use depending on the Yoctopuce device being used. For more informations regarding the purpose and the usage of a given device attribute, please refer to the extended discussion provided in the device-specific user manual.

2. Using the Yocto-Demo with Python

Python is an interpreted object oriented language developed by Guido van Rossum. Among its advantages is the fact that it is free, and the fact that it is available for most platforms, Windows as well as UNIX. It is an ideal language to write small scripts on a napkin. The Yoctopuce library is compatible with Python 2.6+ and 3+. It works under Windows, Mac OS X, and Linux, Intel as well as ARM. The library was tested with Python 2.6 and Python 3.2. Python interpreters are available on the Python web site¹.

2.1. Source files

The Yoctopuce library classes² for Python that you will use are provided as source files. Copy all the content of the *Sources* directory in the directory of your choice and add this directory to the *PYTHONPATH* environment variable. If you use an IDE to program in Python, refer to its documentation to configure it so that it automatically finds the API source files.

2.2. Dynamic library

A section of the low-level library is written in C, but you should not need to interact directly with it: it is provided as a DLL under Windows, as a .so files under UNIX, and as a .dylib file under Mac OS X. Everything was done to ensure the simplest possible interaction from Python: the distinct versions of the dynamic library corresponding to the distinct operating systems and architectures are stored in the *cdll* directory. The API automatically loads the correct file during its initialization. You should not have to worry about it.

If you ever need to recompile the dynamic library, its complete source code is located in the Yoctopuce C++ library.

In order to keep them simple, all the examples provided in this documentation are console applications. Naturally, the libraries function in a strictly identical manner if you integrate them in an application with a graphical interface.

2.3. Control of the Led function

A few lines of code are enough to use a Yocto-Demo. Here is the skeleton of a Python code snippet to use the Led function.

¹ <http://www.python.org/download/>

² www.yoctopuce.com/EN/libraries.php

```
[...]
errmsg=YRefParam()
#Get access to your device, connected locally on USB for instance
YAPI.RegisterHub("usb",errmsg)
led = YLed.FindLed("YCTOPOC1-123456.led")

# Hot-plug is easy: just check that the device is online
if led.isOnline():
    #Use led.set_power()
    ...
[...]
```

Let's look at these lines in more details.

YAPI.RegisterHub

The `yAPI.RegisterHub` function initializes the Yoctopuce API and indicates where the modules should be looked for. When used with the parameter "`usb`", it will use the modules locally connected to the computer running the library. If the initialization does not succeed, this function returns a value different from `YAPI.SUCCESS` and `errmsg` contains the error message.

YLed.FindLed

The `YLed.FindLed` function allows you to find a led from the serial number of the module on which it resides and from its function name. You can use logical names as well, as long as you have initialized them. Let us imagine a Yocto-Demo module with serial number `YCTOPOC1-123456` which you have named "`MyModule`", and for which you have given the `led` function the name "`MyFunction`". The following five calls are strictly equivalent, as long as "`MyFunction`" is defined only once.

```
led = YLed.FindLed("YCTOPOC1-123456.led")
led = YLed.FindLed("YCTOPOC1-123456.MyFunction")
led = YLed.FindLed("MyModule.led")
led = YLed.FindLed("MyModule.MyFunction")
led = YLed.FindLed("MyFunction")
```

`YLed.FindLed` returns an object which you can then use at will to control the led.

isOnline

The `isOnline()` method of the object returned by `YLed.FindLed` allows you to know if the corresponding module is present and in working order.

set_power

The `set_power()` function of the objet returned by `YLed.FindLed` allows you to turn on and off the led. The argument is `YLed.POWER_ON` or `YLed.POWER_OFF`. In the reference on the programming interface, you will find more methods to precisely control the luminosity and make the led blink automatically.

A real example

Launch Python and open the corresponding sample script provided in the directory **Examples/Doc-GettingStarted-Yocto-Demo** of the Yoctopuce library.

In this example, you will recognize the functions explained above, but this time used with all side materials needed to make it work nicely as a small demo.

```
#!/usr/bin/python
# -*- coding: utf-8 -*-
import os,sys
from yocto_api import *
from yocto_led import *

def usage():
    scriptname = os.path.basename(sys.argv[0])
    print("Usage:")
```

```

print(scriptname+' <serial_number>')
print(scriptname+' <logical_name>')
print(scriptname+' any ')
sys.exit()

def die(msg):
    sys.exit(msg+' (check USB cable)')

def setLedState(led,state):
    if led.isOnline():
        if state :
            led.set_power(YLed.POWER_ON)
        else:
            led.set_power(YLed.POWER_OFF)
    else:
        print('Module not connected (check identification and USB cable)')

errmsg=YRefParam()

if len(sys.argv)<2 : usage()

target=sys.argv[1]

# Setup the API to use local USB devices
if YAPI.RegisterHub("usb", errmsg)!= YAPI.SUCCESS:
    sys.exit("init error"+errmsg.value)

if target=='any':
    # retreive any RGB led
    led = YLed.FirstLed()
    if led is None :
        die('No module connected')
else:
    led= YLed.FindLed(target + '.led')

if not(led.isOnline()):die('device not connected')

print('0: turn test led OFF')
print('1: turn test led ON')
print('x: exit')

try: input = raw_input # python 2.x fix
except: pass

c= input("command:")

while c!='x':
    if c=='0' : setLedState(led,False);
    elif c=='1' :setLedState(led,True);
    c= input("command:")

```

2.4. Control of the module part

Each module can be controlled in a similar manner, you can find below a simple sample program displaying the main parameters of the module and enabling you to activate the localization beacon.

```

#!/usr/bin/python
# -*- coding: utf-8 -*-
import os,sys
from yocto_api import *

def usage():
    sys.exit("usage: demo <serial or logical name> [ON/OFF]")

errmsg =YRefParam()
if YAPI.RegisterHub("usb", errmsg) != YAPI.SUCCESS:
    sys.exit("RegisterHub error: " + str(errmsg))

if len(sys.argv)<2 : usage()

m = YModule.FindModule(sys.argv[1]) ## use serial or logical name

```

```

if m.isOnline():
    if len(sys.argv) > 2:
        if sys.argv[2].upper() == "ON" : m.set_beacon(YModule.BEACON_ON)
        if sys.argv[2].upper() == "OFF" : m.set_beacon(YModule.BEACON_OFF)

    print("serial:      " + m.get_serialNumber())
    print("logical name: " + m.get_logicalName())
    print("luminosity:   " + str(m.get_luminosity()))
    if m.get_beacon() == YModule.BEACON_ON:
        print("beacon:      ON")
    else:
        print("beacon:      OFF")
    print("upTime:       " + str(m.get_upTime()/1000)+" sec")
    print("USB current:  " + str(m.get_usbCurrent())+" mA")
    print("logs:\n" + m.get_lastLogs())
else:
    print(sys.argv[1] + " not connected (check identification and USB cable)")

```

Each property `xxx` of the module can be read thanks to a method of type `YModule.get_xxxx()`, and properties which are not read-only can be modified with the help of the `YModule.set_xxx()` method. For more details regarding the used functions, refer to the API chapters.

Changing the module settings

When you want to modify the settings of a module, you only need to call the corresponding `YModule.set_xxx()` function. However, this modification is performed only in the random access memory (RAM) of the module: if the module is restarted, the modifications are lost. To memorize them persistently, it is necessary to ask the module to save its current configuration in its permanent memory. To do so, use the `YModule.saveToFlash()` method. Inversely, it is possible to force the module to forget its current settings by using the `YModule.revertFromFlash()` method. The short example below allows you to modify the logical name of a module.

```

#!/usr/bin/python
# -*- coding: utf-8 -*-
import os,sys
from yocto_api import *

def usage():
    sys.exit("usage: demo <serial or logical name> <new logical name>")

if len(sys.argv) != 3 : usage()

errormsg =YRefParam()
if YAPI.RegisterHub("usb", errormsg) != YAPI.SUCCESS:
    sys.exit("RegisterHub error: " + str(errormsg))

m = YModule.FindModule(sys.argv[1]) # use serial or logical name

if m.isOnline():
    newname = sys.argv[2]
    if not YAPI.CheckLogicalName(newname):
        sys.exit("Invalid name (" + newname + ")")
    m.set_logicalName(newname)
    m.saveToFlash() # do not forget this
    print ("Module: serial= " + m.get_serialNumber() + " / name= " + m.get_logicalName())
else:
    sys.exit("not connected (check identification and USB cable)")

```

Warning: the number of write cycles of the nonvolatile memory of the module is limited. When this limit is reached, nothing guarantees that the saving process is performed correctly. This limit, linked to the technology employed by the module micro-processor, is located at about 100000 cycles. In short, you can use the `YModule.saveToFlash()` function only 100000 times in the life of the module. Make sure you do not call this function within a loop.

List the modules

Obtaining the list of the connected modules is performed with the `YModule.yFirstModule()` function which returns the first module found. Then, you only need to call the `nextModule()` function of this object to find the following modules, and this as long as the returned value is not null. Below a short example listing the connected modules.

```
#!/usr/bin/python
# -*- coding: utf-8 -*-
import os,sys

from yocto_api import *

errmsg=YRefParam()

# Setup the API to use local USB devices
if YAPI.RegisterHub("usb", errmsg)!= YAPI.SUCCESS:
    sys.exit("init error"+str(errmsg))

print('Device list')

module = YModule.FirstModule()
while module is not None:
    print(module.get_serialNumber()+' ('+module.get_productName()+')')
    module = module.nextModule()
```

2.5. Error handling

When you implement a program which must interact with USB modules, you cannot disregard error handling. Inevitably, there will be a time when a user will have unplugged the device, either before running the software, or even while the software is running. The Yoctopuce library is designed to help you support this kind of behavior, but your code must nevertheless be conceived to interpret in the best possible way the errors indicated by the library.

The simplest way to work around the problem is the one used in the short examples provided in this chapter: before accessing a module, check that it is online with the `isOnline` function, and then hope that it will stay so during the fraction of a second necessary for the following code lines to run. This method is not perfect, but it can be sufficient in some cases. You must however be aware that you cannot completely exclude an error which would occur after the call to `isOnline` and which could crash the software. The only way to prevent this is to implement one of the two error handling techniques described below.

The method recommended by most programming languages for unpredictable error handling is the use of exceptions. By default, it is the behavior of the Yoctopuce library. If an error happens while you try to access a module, the library throws an exception. In this case, there are three possibilities:

- If your code catches the exception and handles it, everything goes well.
- If your program is running in debug mode, you can relatively easily determine where the problem happened and view the explanatory message linked to the exception.
- Otherwise... the exception makes your program crash, bang!

As this latest situation is not the most desirable, the Yoctopuce library offers another possibility for error handling, allowing you to create a robust program without needing to catch exceptions at every line of code. You simply need to call the `yDisableExceptions()` function to commute the library to a mode where exceptions for all the functions are systematically replaced by specific return values, which can be tested by the caller when necessary. For each function, the name of each return value in case of error is systematically documented in the library reference. The name always follows the same logic: a `get_state()` method returns a `Y_STATE_INVALID` value, a `get_currentValue` method returns a `Y_CURRENTVALUE_INVALID` value, and so on. In any case, the returned value is of the expected type and is not a null pointer which would risk crashing your program. At worst, if you display the value without testing it, it will be outside the expected bounds for the returned value. In the case of functions which do not normally return information, the return value is `YAPI_SUCCESS` if everything went well, and a different error code in case of failure.

When you work without exceptions, you can obtain an error code and an error message explaining the source of the error. You can request them from the object which returned the error, calling the `errType()` and `errMessage()` methods. Their returned values contain the same information as in the exceptions when they are active.

3. Reference

3.1. General functions

These general functions should be used to initialize and configure the Yoctopuce library. In most cases, a simple call to function `yRegisterHub()` should be enough. The module-specific functions `yFind...()` or `yFirst...()` should then be used to retrieve an object that provides interaction with the module.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_api.js'></script>
node.js var yoctolib = require('yoctolib');
var YAPI = yoctolib.YAPI;
var YModule = yoctolib.YModule;
php require_once('yocto_api.php');
cpp #include "yocto_api.h"
m #import "yocto_api.h"
pas uses yocto_api;
vb yocto_api.vb
cs yocto_api.cs
java import com.yoctopuce.YoctoAPI.YModule;
py from yocto_api import *

```

Global functions

`yCheckLogicalName(name)`

Checks if a given string is valid as logical name for a module or a function.

`yDisableExceptions()`

Disables the use of exceptions to report runtime errors.

`yEnableExceptions()`

Re-enables the use of exceptions for runtime error handling.

`yEnableUSBHost(osContext)`

This function is used only on Android.

`yFreeAPI()`

Frees dynamically allocated memory blocks used by the Yoctopuce library.

`yGetAPIVersion()`

Returns the version identifier for the Yoctopuce library in use.

`yGetTickCount()`

Returns the current value of a monotone millisecond-based time counter.

`yHandleEvents(errmsg)`

Maintains the device-to-library communication channel.

`yInitAPI(mode, errmsg)`

Initializes the Yoctopuce programming library explicitly.

`yPreregisterHub(url, errmsg)`

Fault-tolerant alternative to RegisterHub().

`yRegisterDeviceArrivalCallback(arrivalCallback)`

Register a callback function, to be called each time a device is plugged.

`yRegisterDeviceRemovalCallback(removalCallback)`

Register a callback function, to be called each time a device is unplugged.

`yRegisterHub(url, errmsg)`

Setup the Yoctopuce library to use modules connected on a given machine.

`yRegisterHubDiscoveryCallback(hubDiscoveryCallback)`

3. Reference

Register a callback function, to be called each time an Network Hub send an SSDP message.

yRegisterLogFunction(logfun)

Registers a log callback function.

ySelectArchitecture(arch)

Select the architecture or the library to be loaded to access to USB.

ySetDelegate(object)

(Objective-C only) Register an object that must follow the protocol YDeviceHotPlug.

ySetTimeout(callback, ms_timeout, arguments)

Invoke the specified callback function after a given timeout.

ySleep(ms_duration, errmsg)

Pauses the execution flow for a specified duration.

yTriggerHubDiscovery(errmsg)

Force a hub discovery, if a callback as been registered with yRegisterDeviceRemovalCallback it will be called for each net work hub that will respond to the discovery.

yUnregisterHub(url)

Setup the Yoctopuce library to no more use modules connected on a previously registered machine with RegisterHub.

yUpdateDeviceList(errmsg)

Triggers a (re)detection of connected Yoctopuce modules.

yUpdateDeviceList_async(callback, context)

Triggers a (re)detection of connected Yoctopuce modules.

YAPI.CheckLogicalName()**YAPI****yCheckLogicalName()YAPI.CheckLogicalName()**

Checks if a given string is valid as logical name for a module or a function.

```
def CheckLogicalName( name)
```

A valid logical name has a maximum of 19 characters, all among A..Z, a..z, 0..9, _, and -. If you try to configure a logical name with an incorrect string, the invalid characters are ignored.

Parameters :

name a string containing the name to check.

Returns :

`true` if the name is valid, `false` otherwise.

YAPI.DisableExceptions()

YAPI

yDisableExceptions()YAPI.DisableExceptions()

Disables the use of exceptions to report runtime errors.

```
def DisableExceptions( )
```

When exceptions are disabled, every function returns a specific error value which depends on its type and which is documented in this reference manual.

YAPI.EnableExceptions()**YAPI****yEnableExceptions()YAPI.EnableExceptions()**

Re-enables the use of exceptions for runtime error handling.

```
def EnableExceptions( )
```

Be aware than when exceptions are enabled, every function that fails triggers an exception. If the exception is not caught by the user code, it either fires the debugger or aborts (i.e. crash) the program. On failure, throws an exception or returns a negative error code.

YAPI.FreeAPI() yFreeAPI()YAPI.FreeAPI()

YAPI

Frees dynamically allocated memory blocks used by the Yoctopuce library.

```
def FreeAPI( )
```

It is generally not required to call this function, unless you want to free all dynamically allocated memory blocks in order to track a memory leak for instance. You should not call any other library function after calling `yFreeAPI()`, or your program will crash.

YAPI.GetAPIVersion() yGetAPIVersion()YAPI.GetAPIVersion()

YAPI

Returns the version identifier for the Yoctopuce library in use.

```
def GetAPIVersion( )
```

The version is a string in the form "Major.Minor.Build", for instance "1.01.5535". For languages using an external DLL (for instance C#, VisualBasic or Delphi), the character string includes as well the DLL version, for instance "1.01.5535 (1.01.5439)".

If you want to verify in your code that the library version is compatible with the version that you have used during development, verify that the major number is strictly equal and that the minor number is greater or equal. The build number is not relevant with respect to the library compatibility.

Returns :

a character string describing the library version.

YAPI.GetTickCount() yGetTickCount()YAPI.GetTickCount()

YAPI

Returns the current value of a monotone millisecond-based time counter.

```
def GetTickCount( )
```

This counter can be used to compute delays in relation with Yoctopuce devices, which also uses the millisecond as timebase.

Returns :

a long integer corresponding to the millisecond counter.

YAPI.HandleEvents()**YAPI****yHandleEvents()YAPI.HandleEvents()**

Maintains the device-to-library communication channel.

```
def HandleEvents( errmsg=None)
```

If your program includes significant loops, you may want to include a call to this function to make sure that the library takes care of the information pushed by the modules on the communication channels. This is not strictly necessary, but it may improve the reactivity of the library for the following commands.

This function may signal an error in case there is a communication problem while contacting a module.

Parameters :

errmsg a string passed by reference to receive any error message.

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

YAPI.InitAPI() yInitAPI()YAPI.InitAPI()

YAPI

Initializes the Yoctopuce programming library explicitly.

```
def InitAPI( mode, errmsg=None)
```

It is not strictly needed to call `yInitAPI()`, as the library is automatically initialized when calling `yRegisterHub()` for the first time.

When `Y_DETECT_NONE` is used as detection mode, you must explicitly use `yRegisterHub()` to point the API to the VirtualHub on which your devices are connected before trying to access them.

Parameters :

mode an integer corresponding to the type of automatic device detection to use. Possible values are `Y_DETECT_NONE`, `Y_DETECT_USB`, `Y_DETECT_NET`, and `Y_DETECT_ALL`.

errmsg a string passed by reference to receive any error message.

Returns :

`YAPI_SUCCESS` when the call succeeds.

On failure, throws an exception or returns a negative error code.

YAPI.PreregisterHub() yPreregisterHub()YAPI.PreregisterHub()

YAPI

Fault-tolerant alternative to RegisterHub().

```
def PreregisterHub( url, errmsg=None)
```

This function has the same purpose and same arguments as RegisterHub(), but does not trigger an error when the selected hub is not available at the time of the function call. This makes it possible to register a network hub independently of the current connectivity, and to try to contact it only when a device is actively needed.

Parameters :

url a string containing either "usb", "callback" or the root URL of the hub to monitor
errmsg a string passed by reference to receive any error message.

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

YAPI.RegisterDeviceArrivalCallback()
yRegisterDeviceArrivalCallback()
YAPI.RegisterDeviceArrivalCallback()**YAPI**

Register a callback function, to be called each time a device is plugged.

```
def RegisterDeviceArrivalCallback( arrivalCallback )
```

This callback will be invoked while `yUpdateDeviceList` is running. You will have to call this function on a regular basis.

Parameters :

`arrivalCallback` a procedure taking a `YModule` parameter, or null

YAPI.RegisterDeviceRemovalCallback()
yRegisterDeviceRemovalCallback()
YAPI.RegisterDeviceRemovalCallback()**YAPI**

Register a callback function, to be called each time a device is unplugged.

```
def RegisterDeviceRemovalCallback( removalCallback )
```

This callback will be invoked while `yUpdateDeviceList` is running. You will have to call this function on a regular basis.

Parameters :

`removalCallback` a procedure taking a `YModule` parameter, or null

YAPI.RegisterHub()

YAPI

yRegisterHub()YAPI.RegisterHub()

Setup the Yoctopuce library to use modules connected on a given machine.

```
def RegisterHub( url, errmsg=None)
```

The parameter will determine how the API will work. Use the following values:

usb: When the **usb** keyword is used, the API will work with devices connected directly to the USB bus. Some programming languages such as Javascript, PHP, and Java don't provide direct access to USB hardware, so **usb** will not work with these. In this case, use a VirtualHub or a networked YoctoHub (see below).

x.x.x.x or **hostname**: The API will use the devices connected to the host with the given IP address or hostname. That host can be a regular computer running a VirtualHub, or a networked YoctoHub such as YoctoHub-Ethernet or YoctoHub-Wireless. If you want to use the VirtualHub running on your local computer, use the IP address 127.0.0.1.

callback: This keyword makes the API run in "*HTTP Callback*" mode. This is a special mode allowing to take control of Yoctopuce devices through a NAT filter when using a VirtualHub or a networked YoctoHub. You only need to configure your hub to call your server script on a regular basis. This mode is currently available for PHP and Node.js only.

Be aware that only one application can use direct USB access at a given time on a machine. Multiple access would cause conflicts while trying to access the USB modules. In particular, this means that you must stop the VirtualHub software before starting an application that uses direct USB access. The workaround for this limitation is to setup the library to use the VirtualHub rather than direct USB access.

If access control has been activated on the hub, virtual or not, you want to reach, the URL parameter should look like:

```
http://username:password@address:port
```

You can call *RegisterHub* several times to connect to several machines.

Parameters :

- url** a string containing either "usb", "callback" or the root URL of the hub to monitor
- errmsg** a string passed by reference to receive any error message.

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

YAPI.RegisterHubDiscoveryCallback() yRegisterHubDiscoveryCallback() YAPI.RegisterHubDiscoveryCallback()

YAPI

Register a callback function, to be called each time an Network Hub send an SSDP message.

```
def RegisterHubDiscoveryCallback( hubDiscoveryCallback)
```

The callback has two string parameter, the first one contain the serial number of the hub and the second contain the URL of the network hub (this URL can be passed to RegisterHub). This callback will be invoked while yUpdateDeviceList is running. You will have to call this function on a regular basis.

Parameters :

hubDiscoveryCallback a procedure taking two string parameter, or null

YAPI.RegisterLogFunction()**YAPI****yRegisterLogFunction()YAPI.RegisterLogFunction()**

Registers a log callback function.

```
def RegisterLogFunction( logfun )
```

This callback will be called each time the API have something to say. Quite useful to debug the API.

Parameters :

logfun a procedure taking a string parameter, or null

YAPI.SelectArchitecture()**YAPI****ySelectArchitecture()YAPI.SelectArchitecture()**

Select the architecture or the library to be loaded to access to USB.

```
def SelectArchitecture( arch)
```

By default, the Python library automatically detects the appropriate library to use. However, for Linux ARM, it is not possible to reliably distinguish between a Hard Float (armhf) and a Soft Float (armel) install. For this case, it is therefore recommended to manually select the proper architecture by calling `SelectArchitecture()` before any other call to the library.

Parameters :

arch A string containing the architecture to use. Possible values are: "armhf", "armel", "i386", "x86_64", "32bit", "64bit"

Returns :

nothing.

On failure, throws an exception.

YAPI.Sleep() ySleep()YAPI.Sleep()

YAPI

Pauses the execution flow for a specified duration.

```
def Sleep( ms_duration, errmsg=None)
```

This function implements a passive waiting loop, meaning that it does not consume CPU cycles significantly. The processor is left available for other threads and processes. During the pause, the library nevertheless reads from time to time information from the Yoctopuce modules by calling `yHandleEvents()`, in order to stay up-to-date.

This function may signal an error in case there is a communication problem while contacting a module.

Parameters :

`ms_duration` an integer corresponding to the duration of the pause, in milliseconds.

`errmsg` a string passed by reference to receive any error message.

Returns :

`YAPI_SUCCESS` when the call succeeds.

On failure, throws an exception or returns a negative error code.

YAPI.TriggerHubDiscovery()**YAPI****yTriggerHubDiscovery()YAPI.TriggerHubDiscovery()**

Force a hub discovery, if a callback has been registered with yRegisterDeviceRemovalCallback it will be called for each network hub that will respond to the discovery.

```
def TriggerHubDiscovery( errmsg=None)
```

Parameters :

errmsg a string passed by reference to receive any error message.

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

YAPI.UnregisterHub() yUnregisterHub()YAPI.UnregisterHub()

YAPI

Setup the Yoctopuce library to no more use modules connected on a previously registered machine with RegisterHub.

```
def UnregisterHub( url)
```

Parameters :

url a string containing either "usb" or the

YAPI.UpdateDeviceList()**YAPI****yUpdateDeviceList()YAPI.UpdateDeviceList()**

Triggers a (re)detection of connected Yoctopuce modules.

```
def UpdateDeviceList( errmsg=None)
```

The library searches the machines or USB ports previously registered using `yRegisterHub()`, and invokes any user-defined callback function in case a change in the list of connected devices is detected.

This function can be called as frequently as desired to refresh the device list and to make the application aware of hot-plug events.

Parameters :

`errmsg` a string passed by reference to receive any error message.

Returns :

`YAPI_SUCCESS` when the call succeeds.

On failure, throws an exception or returns a negative error code.

3.2. Accelerometer function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_accelerometer.js'></script>
nodejs var yoctolib = require('yoctolib');
var YAccelerometer = yoctolib.YAccelerometer;
php require_once('yocto_accelerometer.php');
cpp #include "yocto_accelerometer.h"
m #import "yocto_accelerometer.h"
pas uses yocto_accelerometer;
vb yocto_accelerometer.vb
cs yocto_accelerometer.cs
java import com.yoctopuce.YoctoAPI.YAccelerometer;
py from yocto_accelerometer import *

```

Global functions

yFindAccelerometer(func)

Retrieves an accelerometer for a given identifier.

yFirstAccelerometer()

Starts the enumeration of accelerometers currently accessible.

YAccelerometer methods

accelerometer→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

accelerometer→describe()

Returns a short text that describes unambiguously the instance of the accelerometer in the form TYPE (NAME) = SERIAL . FUNCTIONID.

accelerometer→get_advertisedValue()

Returns the current value of the accelerometer (no more than 6 characters).

accelerometer→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in g, as a floating point number.

accelerometer→get_currentValue()

Returns the current value of the acceleration, in g, as a floating point number.

accelerometer→get_errorMessage()

Returns the error message of the latest error with the accelerometer.

accelerometer→get_errorType()

Returns the numerical error code of the latest error with the accelerometer.

accelerometer→get_friendlyName()

Returns a global identifier of the accelerometer in the format MODULE_NAME . FUNCTION_NAME.

accelerometer→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

accelerometer→get_functionId()

Returns the hardware identifier of the accelerometer, without reference to the module.

accelerometer→get_hardwareId()

Returns the unique hardware identifier of the accelerometer in the form SERIAL . FUNCTIONID.

accelerometer→get_highestValue()	Returns the maximal value observed for the acceleration since the device was started.
accelerometer→get_logFrequency()	Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.
accelerometer→get_logicalName()	Returns the logical name of the accelerometer.
accelerometer→get_lowestValue()	Returns the minimal value observed for the acceleration since the device was started.
accelerometer→get_module()	Gets the YModule object for the device on which the function is located.
accelerometer→get_module_async(callback, context)	Gets the YModule object for the device on which the function is located (asynchronous version).
accelerometer→get_recordedData(startTime, endTime)	Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.
accelerometer→get_reportFrequency()	Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.
accelerometer→get_resolution()	Returns the resolution of the measured values.
accelerometer→get_unit()	Returns the measuring unit for the acceleration.
accelerometer→get(userData)	Returns the value of the userData attribute, as previously stored using method set(userData).
accelerometer→get_xValue()	Returns the X component of the acceleration, as a floating point number.
accelerometer→get_yValue()	Returns the Y component of the acceleration, as a floating point number.
accelerometer→get_zValue()	Returns the Z component of the acceleration, as a floating point number.
accelerometer→isOnline()	Checks if the accelerometer is currently reachable, without raising any error.
accelerometer→isOnline_async(callback, context)	Checks if the accelerometer is currently reachable, without raising any error (asynchronous version).
accelerometer→load(msValidity)	Preloads the accelerometer cache with a specified validity duration.
accelerometer→loadCalibrationPoints(rawValues, refValues)	Retrieves error correction data points previously entered using the method calibrateFromPoints.
accelerometer→load_async(msValidity, callback, context)	Preloads the accelerometer cache with a specified validity duration (asynchronous version).
accelerometer→nextAccelerometer()	Continues the enumeration of accelerometers started using yFirstAccelerometer().
accelerometer→registerTimedReportCallback(callback)	Registers the callback function that is invoked on every periodic timed notification.
accelerometer→registerValueCallback(callback)	Registers the callback function that is invoked on every change of advertised value.

3. Reference

accelerometer→set_highestValue(newval)

Changes the recorded maximal value observed.

accelerometer→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

accelerometer→set_logicalName(newval)

Changes the logical name of the accelerometer.

accelerometer→set_lowestValue(newval)

Changes the recorded minimal value observed.

accelerometer→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

accelerometer→set_resolution(newval)

Changes the resolution of the measured physical values.

accelerometer→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

accelerometer→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YAccelerometer.FindAccelerometer() yFindAccelerometer() YAccelerometer.FindAccelerometer()

YAccelerometer

Retrieves an accelerometer for a given identifier.

```
def FindAccelerometer( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the accelerometer is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YAccelerometer.isOnline()` to test if the accelerometer is indeed online at a given time. In case of ambiguity when looking for an accelerometer by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the accelerometer

Returns :

a `YAccelerometer` object allowing you to drive the accelerometer.

YAccelerometer.FirstAccelerometer()

YAccelerometer

yFirstAccelerometer()

YAccelerometer.FirstAccelerometer()

Starts the enumeration of accelerometers currently accessible.

```
def FirstAccelerometer( )
```

Use the method `YAccelerometer.nextAccelerometer()` to iterate on next accelerometers.

Returns :

a pointer to a `YAccelerometer` object, corresponding to the first accelerometer currently online, or a null pointer if there are none.

accelerometer→calibrateFromPoints()
accelerometer.calibrateFromPoints()**YAccelerometer**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

accelerometer→describe()accelerometer.describe()**YAccelerometer**

Returns a short text that describes unambiguously the instance of the accelerometer in the form
TYPE (NAME)=SERIAL . FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the accelerometer (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

accelerometer→get_advertisedValue()

YAccelerometer

accelerometer→advertisedValue()

accelerometer.get_advertisedValue()

Returns the current value of the accelerometer (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the accelerometer (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

accelerometer→get_currentRawValue()
accelerometer→currentRawValue()
accelerometer.get_currentRawValue()

YAccelerometer

Returns the uncalibrated, unrounded raw value returned by the sensor, in g, as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in g, as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

accelerometer→get_currentValue()
accelerometer→currentValue()
accelerometer.get_currentValue()

YAccelerometer

Returns the current value of the acceleration, in g, as a floating point number.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current value of the acceleration, in g, as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

accelerometer→get_errorMessage()
accelerometer→errorMessage()
accelerometer.get_errorMessage()

YAccelerometer

Returns the error message of the latest error with the accelerometer.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the accelerometer object

accelerometer→get_errorType()
accelerometer→errorType()
accelerometer.get_errorType()

YAccelerometer

Returns the numerical error code of the latest error with the accelerometer.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the accelerometer object

accelerometer→get_friendlyName()
accelerometer→friendlyName()
accelerometer.get_friendlyName()

YAccelerometer

Returns a global identifier of the accelerometer in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the accelerometer if they are defined, otherwise the serial number of the module and the hardware identifier of the accelerometer (for example: MyCustomName . relay1)

Returns :

a string that uniquely identifies the accelerometer using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

`accelerometer→get_functionDescriptor()`
`accelerometer→functionDescriptor()`
`accelerometer.get_functionDescriptor()`

YAccelerometer

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

`accelerometer→get_functionId()`
`accelerometer→functionId()`
`accelerometer.get_functionId()`

YAccelerometer

Returns the hardware identifier of the accelerometer, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the accelerometer (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

accelerometer→get.hardwareId()

YAccelerometer

accelerometer→hardwareId()

accelerometer.get.hardwareId()

Returns the unique hardware identifier of the accelerometer in the form SERIAL.FUNCTIONID.

def get.hardwareId()

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the accelerometer (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the accelerometer (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

accelerometer→get_highestValue()
accelerometer→highestValue()
accelerometer.get_highestValue()

YAccelerometer

Returns the maximal value observed for the acceleration since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the acceleration since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

accelerometer→get_logFrequency()
accelerometer→logFrequency()
accelerometer.get_logFrequency()

YAccelerometer

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

accelerometer→get_logicalName()
accelerometer→logicalName()
accelerometer.get_logicalName()

YAccelerometer

Returns the logical name of the accelerometer.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the accelerometer.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

accelerometer→get_lowestValue()
accelerometer→lowestValue()
accelerometer.get_lowestValue()

YAccelerometer

Returns the minimal value observed for the acceleration since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the acceleration since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

accelerometer→get_module()**YAccelerometer****accelerometer→module()accelerometer.get_module()**

Gets the **YModule** object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of **YModule** is not shown as online.

Returns :

an instance of **YModule**

accelerometer→get_recordedData()
accelerometer→recordedData()
accelerometer.get_recordedData()

YAccelerometer

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime)
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

accelerometer→get_reportFrequency()
accelerometer→reportFrequency()
accelerometer.get_reportFrequency()

YAccelerometer

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

accelerometer→get_resolution()
accelerometer→resolution()
accelerometer.get_resolution()

YAccelerometer

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

accelerometer→get_unit()

YAccelerometer

accelerometer→unit()accelerometer.get_unit()

Returns the measuring unit for the acceleration.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the acceleration

On failure, throws an exception or returns Y_UNIT_INVALID.

accelerometer→get(userData)
accelerometer→userData()
accelerometer.get(userData())

YAccelerometer

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

`def get(userData()`

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

accelerometer→get_xValue()

YAccelerometer

accelerometer→xValue()accelerometer.get_xValue()

Returns the X component of the acceleration, as a floating point number.

```
def get_xValue( )
```

Returns :

a floating point number corresponding to the X component of the acceleration, as a floating point number

On failure, throws an exception or returns Y_XVALUE_INVALID.

accelerometer→get_yValue()

YAccelerometer

accelerometer→yValue()accelerometer.get_yValue()

Returns the Y component of the acceleration, as a floating point number.

```
def get_yValue( )
```

Returns :

a floating point number corresponding to the Y component of the acceleration, as a floating point number

On failure, throws an exception or returns `Y_YVALUE_INVALID`.

accelerometer→get_zValue()

YAccelerometer

accelerometer→zValue()accelerometer.get_zValue()

Returns the Z component of the acceleration, as a floating point number.

```
def get_zValue( )
```

Returns :

a floating point number corresponding to the Z component of the acceleration, as a floating point number

On failure, throws an exception or returns Y_ZVALUE_INVALID.

accelerometer→isOnline()**YAccelerometer**

Checks if the accelerometer is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the accelerometer in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the accelerometer.

Returns :

`true` if the accelerometer can be reached, and `false` otherwise

accelerometer→load()accelerometer.load()**YAccelerometer**

Preloads the accelerometer cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

accelerometer→loadCalibrationPoints()
accelerometer.loadCalibrationPoints()**YAccelerometer**

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

accelerometer→nextAccelerometer()
accelerometer.nextAccelerometer()

YAccelerometer

Continues the enumeration of accelerometers started using `yFirstAccelerometer()`.

```
def nextAccelerometer( )
```

Returns :

a pointer to a `YAccelerometer` object, corresponding to an accelerometer currently online, or a `null` pointer if there are no more accelerometers to enumerate.

accelerometer→registerTimedReportCallback()
accelerometer.registerTimedReportCallback()**YAccelerometer**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

**accelerometer→registerValueCallback()
accelerometer.registerValueCallback()****YAccelerometer**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

accelerometer→set_highestValue()
accelerometer→setHighestValue()
accelerometer.set_highestValue()

YAccelerometer

Changes the recorded maximal value observed.

```
def set_highestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

accelerometer→set_logFrequency()
accelerometer→setLogFrequency()
accelerometer.set_logFrequency()

YAccelerometer

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

accelerometer→set_logicalName()
accelerometer→setLogicalName()
accelerometer.set_logicalName()

YAccelerometer

Changes the logical name of the accelerometer.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the logical name of the accelerometer.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

`accelerometer→set_lowestValue()`
`accelerometer→setLowestValue()`
`accelerometer.set_lowestValue()`

YAccelerometer

Changes the recorded minimal value observed.

```
def set_lowestValue( newval )
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

accelerometer→set_reportFrequency()
accelerometer→setReportFrequency()
accelerometer.set_reportFrequency()

YAccelerometer

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

accelerometer→set_resolution()
accelerometer→setResolution()
accelerometer.set_resolution()

YAccelerometer

Changes the resolution of the measured physical values.

```
def set_resolution( newval )
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

accelerometer→set(userData)
accelerometer→setUserData()
accelerometer.set(userData)

YAccelerometer

Stores a user context provided as argument in the userData attribute of the function.

```
def setUserData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.3. Altitude function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_altitude.js'></script>
nodejs var yoctolib = require('yoctolib');
var YAltitude = yoctolib.YAltitude;
php require_once('yocto_altitude.php');
cpp #include "yocto_altitude.h"
m #import "yocto_altitude.h"
pas uses yocto_altitude;
vb yocto_altitude.vb
cs yocto_altitude.cs
java import com.yoctopuce.YoctoAPI.YAltitude;
py from yocto_altitude import *

```

Global functions

yFindAltitude(func)

Retrieves an altimeter for a given identifier.

yFirstAltitude()

Starts the enumeration of altimeters currently accessible.

YAltitude methods

altitude→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

altitude→describe()

Returns a short text that describes unambiguously the instance of the altimeter in the form TYPE(NAME)=SERIAL.FUNCTIONID.

altitude→get_advertisedValue()

Returns the current value of the altimeter (no more than 6 characters).

altitude→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in meters, as a floating point number.

altitude→get_currentValue()

Returns the current value of the altitude, in meters, as a floating point number.

altitude→get_errorMessage()

Returns the error message of the latest error with the altimeter.

altitude→get_errorType()

Returns the numerical error code of the latest error with the altimeter.

altitude→get_friendlyName()

Returns a global identifier of the altimeter in the format MODULE_NAME . FUNCTION_NAME.

altitude→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

altitude→get_functionId()

Returns the hardware identifier of the altimeter, without reference to the module.

altitude→get_hardwareId()

Returns the unique hardware identifier of the altimeter in the form SERIAL.FUNCTIONID.

altitude→get_highestValue()

Returns the maximal value observed for the altitude since the device was started.

altitude→get_logFrequency()

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

altitude→get_logicalName()

Returns the logical name of the altimeter.

altitude→get_lowestValue()

Returns the minimal value observed for the altitude since the device was started.

altitude→get_module()

Gets the YModule object for the device on which the function is located.

altitude→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

altitude→get_qnh()

Returns the barometric pressure adjusted to sea level used to compute the altitude (QNH).

altitude→get_recordedData(startTime, endTime)

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

altitude→get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

altitude→get_resolution()

Returns the resolution of the measured values.

altitude→get_unit()

Returns the measuring unit for the altitude.

altitude→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

altitude→isOnline()

Checks if the altimeter is currently reachable, without raising any error.

altitude→isOnline_async(callback, context)

Checks if the altimeter is currently reachable, without raising any error (asynchronous version).

altitude→load(msValidity)

Preloads the altimeter cache with a specified validity duration.

altitude→loadCalibrationPoints(rawValues, refValues)

Retrieves error correction data points previously entered using the method calibrateFromPoints.

altitude→load_async(msValidity, callback, context)

Preloads the altimeter cache with a specified validity duration (asynchronous version).

altitude→nextAltitude()

Continues the enumeration of altimeters started using yFirstAltitude().

altitude→registerTimedReportCallback(callback)

Registers the callback function that is invoked on every periodic timed notification.

altitude→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

altitude→set_currentValue(newval)

Changes the current estimated altitude.

altitude→set_highestValue(newval)

Changes the recorded maximal value observed.

3. Reference

altitude→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

altitude→set_logicalName(newval)

Changes the logical name of the altimeter.

altitude→set_lowestValue(newval)

Changes the recorded minimal value observed.

altitude→set_qnh(newval)

Changes the barometric pressure adjusted to sea level used to compute the altitude (QNH).

altitude→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

altitude→set_resolution(newval)

Changes the resolution of the measured physical values.

altitude→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

altitude→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YAltitude.FindAltitude()**YAltitude****yFindAltitude()YAltitude.FindAltitude()**

Retrieves an altimeter for a given identifier.

```
def FindAltitude( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the altimeter is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YAltitude.isOnline()` to test if the altimeter is indeed online at a given time. In case of ambiguity when looking for an altimeter by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the altimeter

Returns :

a `YAltitude` object allowing you to drive the altimeter.

YAltitude.FirstAltitude()

YAltitude

yFirstAltitude()YAltitude.FirstAltitude()

Starts the enumeration of altimeters currently accessible.

```
def FirstAltitude( )
```

Use the method `YAltitude.nextAltitude()` to iterate on next altimeters.

Returns :

a pointer to a `YAltitude` object, corresponding to the first altimeter currently online, or a `null` pointer if there are none.

altitude→calibrateFromPoints()
altitude.calibrateFromPoints()**YAltitude**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

altitude→describe()**YAltitude**

Returns a short text that describes unambiguously the instance of the altimeter in the form
TYPE (NAME)=SERIAL . FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the altimeter (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

altitude→get_advertisedValue()
altitude→advertisedValue()
altitude.get_advertisedValue()

YAltitude

Returns the current value of the altimeter (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the altimeter (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

altitude→get_currentRawValue()	YAltitude
altitude→currentRawValue()	
altitude.get_currentRawValue()	

Returns the uncalibrated, unrounded raw value returned by the sensor, in meters, as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in meters, as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

altitude→get_currentValue()	YAltitude
altitude→currentValue()altitude.get_currentValue()	

Returns the current value of the altitude, in meters, as a floating point number.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current value of the altitude, in meters, as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

altitude→get_errorMessage()

YAltitude

altitude→errorMessage()altitude.get_errorMessage()

Returns the error message of the latest error with the altimeter.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the altimeter object

altitude→get_errorType()**YAltitude****altitude→errorType()altitude.get_errorType()**

Returns the numerical error code of the latest error with the altimeter.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the altimeter object

altitude→get_friendlyName()	YAltitude
altitude→friendlyName()altitude.get_friendlyName()	

Returns a global identifier of the altimeter in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the altimeter if they are defined, otherwise the serial number of the module and the hardware identifier of the altimeter (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the altimeter using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

`altitude->get_functionDescriptor()`
`altitude->functionDescriptor()`
`altitude.get_functionDescriptor()`

`YAltitude`

Returns a unique identifier of type `YFUN_DESCR` corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of `YFunction` reference the same physical function on the same physical device.

Returns :

an identifier of type `YFUN_DESCR`.

If the function has never been contacted, the returned value is `Y_FUNCTIONDESCRIPTOR_INVALID`.

altitude→get_functionId()

YAltitude

altitude→functionId()altitude.get_functionId()

Returns the hardware identifier of the altimeter, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the altimeter (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

altitude→get_hardwareId()**YAltitude****altitude→hardwareId()altitude.get_hardwareId()**

Returns the unique hardware identifier of the altimeter in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the altimeter (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the altimeter (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

altitude→get_highestValue()

YAltitude

altitude→highestValue()altitude.get_highestValue()

Returns the maximal value observed for the altitude since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the altitude since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

altitude→get_logFrequency()**YAltitude****altitude→logFrequency()altitude.get_logFrequency()**

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

altitude→get_logicalName()

YAltitude

altitude→logicalName()altitude.get_logicalName()

Returns the logical name of the altimeter.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the altimeter.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

altitude→get_lowestValue()**YAltitude****altitude→lowestValue()altitude.get_lowestValue()**

Returns the minimal value observed for the altitude since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the altitude since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

altitude→get_module()**YAltitude****altitude→module()altitude.get_module()**

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

altitude→get_qnh()**YAltitude****altitude→qnh()altitude.get_qnh()**

Returns the barometric pressure adjusted to sea level used to compute the altitude (QNH).

```
def get_qnh( )
```

Returns :

a floating point number corresponding to the barometric pressure adjusted to sea level used to compute the altitude (QNH)

On failure, throws an exception or returns Y_QNH_INVALID.

altitude→get_recordedData()	YAltitude
altitude→recordedData()altitude.get_recordedData()	

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime )
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any meaasure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any meaasure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

altitude→get_reportFrequency()
altitude→reportFrequency()
altitude.get_reportFrequency()

YAltitude

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

altitude→get_resolution()

YAltitude

altitude→resolution()altitude.get_resolution()

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

altitude→get_unit()**YAltitude****altitude→unit()altitude.get_unit()**

Returns the measuring unit for the altitude.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the altitude

On failure, throws an exception or returns Y_UNIT_INVALID.

altitude→get(userData)

YAltitude

altitude→userData()altitude.get(userData)

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

altitude→isOnline()altitude.isOnline()**YAltitude**

Checks if the altimeter is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the altimeter in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the altimeter.

Returns :

`true` if the altimeter can be reached, and `false` otherwise

altitude→load()altitude.load()**YAltitude**

Preloads the altimeter cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

altitude→loadCalibrationPoints()
altitude.loadCalibrationPoints()**YAltitude**

Retrieves error correction data points previously entered using the method `calibrateFromPoints`.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

altitude→nextAltitude()altitude.nextAltitude()

YAltitude

Continues the enumeration of altimeters started using `yFirstAltitude()`.

```
def nextAltitude( )
```

Returns :

a pointer to a `YAltitude` object, corresponding to an altimeter currently online, or a null pointer if there are no more altimeters to enumerate.

**altitude→registerTimedReportCallback()
altitude.registerTimedReportCallback()****YAltitude**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

altitude→registerValueCallback()
altitude.registerValueCallback()**YAltitude**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

altitude->set_currentValue()	YAltitude
altitude->setCurrentValue()	
altitude.set_currentValue()	

Changes the current estimated altitude.

```
def set_currentValue( newval)
```

This allows to compensate for ambient pressure variations and to work in relative mode.

Parameters :

newval a floating point number corresponding to the current estimated altitude

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

altitude→set_highestValue()
altitude→setHighestValue()
altitude.set_highestValue()

YAltitude

Changes the recorded maximal value observed.

```
def set_highestValue( newval )
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

altitude→set_logFrequency()
altitude→setLogFrequency()
altitude.set_logFrequency()

YAltitude

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval)
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

altitude→set_logicalName()	YAltitude
altitude→setLogicalName()	altitude.set_logicalName()

Changes the logical name of the altimeter.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the altimeter.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

altitude→set_lowestValue()	YAltitude
altitude→setLowestValue()altitude.set_lowestValue()	

Changes the recorded minimal value observed.

```
def set_lowestValue( newval )
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

altitude→set_qnh()**YAltitude****altitude→setQnh()altitude.set_qnh()**

Changes the barometric pressure adjusted to sea level used to compute the altitude (QNH).

```
def set_qnh( newval)
```

This enables you to compensate for atmospheric pressure changes due to weather conditions.

Parameters :

newval a floating point number corresponding to the barometric pressure adjusted to sea level used to compute the altitude (QNH)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

altitude→set_reportFrequency()
altitude→setReportFrequency()
altitude.set_reportFrequency()

YAltitude

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

altitude→set_resolution()	YAltitude
altitude→setResolution()altitude.set_resolution()	

Changes the resolution of the measured physical values.

```
def set_resolution( newval)
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

altitude→set(userData)**YAltitude****altitude→setUserData()altitude.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData) data
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.4. AnButton function interface

Yoctopuce application programming interface allows you to measure the state of a simple button as well as to read an analog potentiometer (variable resistance). This can be used for instance with a continuous rotating knob, a throttle grip or a joystick. The module is capable to calibrate itself on min and max values, in order to compute a calibrated value that varies proportionally with the potentiometer position, regardless of its total resistance.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_anbutton.js'></script>
nodejs var yoctolib = require('yoctolib');
var YAnButton = yoctolib.YAnButton;
php require_once('yocto_anbutton.php');
cpp #include "yocto_anbutton.h"
m #import "yocto_anbutton.h"
pas uses yocto_anbutton;
vb yocto_anbutton.vb
cs yocto_anbutton.cs
java import com.yoctopuce.YoctoAPI.YAnButton;
py from yocto_anbutton import *

```

Global functions

yFindAnButton(func)

Retrieves an analog input for a given identifier.

yFirstAnButton()

Starts the enumeration of analog inputs currently accessible.

YAnButton methods

anbutton→describe()

Returns a short text that describes unambiguously the instance of the analog input in the form TYPE (NAME)=SERIAL.FUNCTIONID.

anbutton→get_advertisedValue()

Returns the current value of the analog input (no more than 6 characters).

anbutton→get_analogCalibration()

Tells if a calibration process is currently ongoing.

anbutton→get_calibratedValue()

Returns the current calibrated input value (between 0 and 1000, included).

anbutton→get_calibrationMax()

Returns the maximal value measured during the calibration (between 0 and 4095, included).

anbutton→get_calibrationMin()

Returns the minimal value measured during the calibration (between 0 and 4095, included).

anbutton→get_errorMessage()

Returns the error message of the latest error with the analog input.

anbutton→get_errorType()

Returns the numerical error code of the latest error with the analog input.

anbutton→get_friendlyName()

Returns a global identifier of the analog input in the format MODULE_NAME . FUNCTION_NAME.

anbutton→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

anbutton→get_functionId()

Returns the hardware identifier of the analog input, without reference to the module.

anbutton→get_hardwareId()

Returns the unique hardware identifier of the analog input in the form SERIAL.FUNCTIONID.

anbutton→get_isPressed()

Returns true if the input (considered as binary) is active (closed contact), and false otherwise.

anbutton→get_lastTimePressed()

Returns the number of elapsed milliseconds between the module power on and the last time the input button was pressed (the input contact transitioned from open to closed).

anbutton→get_lastTimeReleased()

Returns the number of elapsed milliseconds between the module power on and the last time the input button was released (the input contact transitioned from closed to open).

anbutton→get_logicalName()

Returns the logical name of the analog input.

anbutton→get_module()

Gets the YModule object for the device on which the function is located.

anbutton→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

anbutton→get_pulseCounter()

Returns the pulse counter value

anbutton→get_pulseTimer()

Returns the timer of the pulses counter (ms)

anbutton→get_rawValue()

Returns the current measured input value as-is (between 0 and 4095, included).

anbutton→get_sensitivity()

Returns the sensibility for the input (between 1 and 1000) for triggering user callbacks.

anbutton→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

anbutton→isOnline()

Checks if the analog input is currently reachable, without raising any error.

anbutton→isOnline_async(callback, context)

Checks if the analog input is currently reachable, without raising any error (asynchronous version).

anbutton→load(msValidity)

Preloads the analog input cache with a specified validity duration.

anbutton→load_async(msValidity, callback, context)

Preloads the analog input cache with a specified validity duration (asynchronous version).

anbutton→nextAnButton()

Continues the enumeration of analog inputs started using yFirstAnButton().

anbutton→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

anbutton→resetCounter()

Returns the pulse counter value as well as his timer

anbutton→set_analogCalibration(newval)

Starts or stops the calibration process.

anbutton→set_calibrationMax(newval)

3. Reference

Changes the maximal calibration value for the input (between 0 and 4095, included), without actually starting the automated calibration.

anbutton→set_calibrationMin(newval)

Changes the minimal calibration value for the input (between 0 and 4095, included), without actually starting the automated calibration.

anbutton→set_logicalName(newval)

Changes the logical name of the analog input.

anbutton→set_sensitivity(newval)

Changes the sensibility for the input (between 1 and 1000) for triggering user callbacks.

anbutton→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

anbutton→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YAnButton.FindAnButton()**YAnButton****yFindAnButton()YAnButton.FindAnButton()**

Retrieves an analog input for a given identifier.

```
def FindAnButton( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the analog input is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YAnButton.isOnline()` to test if the analog input is indeed online at a given time. In case of ambiguity when looking for an analog input by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the analog input

Returns :

a `YAnButton` object allowing you to drive the analog input.

YAnButton.FirstAnButton()

YAnButton

yFirstAnButton()YAnButton.FirstAnButton()

Starts the enumeration of analog inputs currently accessible.

```
def FirstAnButton( )
```

Use the method `YAnButton.nextAnButton()` to iterate on next analog inputs.

Returns :

a pointer to a `YAnButton` object, corresponding to the first analog input currently online, or a null pointer if there are none.

anbutton→describe()anbutton.describe()**YAnButton**

Returns a short text that describes unambiguously the instance of the analog input in the form TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the analog input (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

anbutton→get_advertisedValue()
anbutton→advertisedValue()
anbutton.get_advertisedValue()

YAnButton

Returns the current value of the analog input (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the analog input (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

anbutton→get_analogCalibration()
anbutton→analogCalibration()
anbutton.get_analogCalibration()

YAnButton

Tells if a calibration process is currently ongoing.

```
def get_analogCalibration( )
```

Returns :

either Y_ANALOGCALIBRATION_OFF or Y_ANALOGCALIBRATION_ON

On failure, throws an exception or returns Y_ANALOGCALIBRATION_INVALID.

anbutton→get_calibratedValue()
anbutton→calibratedValue()
anbutton.get_calibratedValue()

YAnButton

Returns the current calibrated input value (between 0 and 1000, included).

```
def get_calibratedValue( )
```

Returns :

an integer corresponding to the current calibrated input value (between 0 and 1000, included)

On failure, throws an exception or returns Y_CALIBRATEDVALUE_INVALID.

anbutton→get_calibrationMax()
anbutton→calibrationMax()
anbutton.get_calibrationMax()

YAnButton

Returns the maximal value measured during the calibration (between 0 and 4095, included).

```
def get_calibrationMax( )
```

Returns :

an integer corresponding to the maximal value measured during the calibration (between 0 and 4095, included)

On failure, throws an exception or returns Y_CALIBRATIONMAX_INVALID.

anbutton→get_calibrationMin()
anbutton→calibrationMin()
anbutton.get_calibrationMin()

YAnButton

Returns the minimal value measured during the calibration (between 0 and 4095, included).

```
def get_calibrationMin( )
```

Returns :

an integer corresponding to the minimal value measured during the calibration (between 0 and 4095, included)

On failure, throws an exception or returns Y_CALIBRATIONMIN_INVALID.

anbutton→getErrorMessage()
anbutton→errorMessage()
anbutton.getErrorMessage()

YAnButton

Returns the error message of the latest error with the analog input.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the analog input object

anbutton→get_errorType()

YAnButton

anbutton→errorType()anbutton.get_errorType()

Returns the numerical error code of the latest error with the analog input.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the analog input object

anbutton→get_friendlyName()
anbutton→friendlyName()
anbutton.get_friendlyName()

YAnButton

Returns a global identifier of the analog input in the format MODULE_NAME . FUNCTION_NAME.

def get_friendlyName()

The returned string uses the logical names of the module and of the analog input if they are defined, otherwise the serial number of the module and the hardware identifier of the analog input (for example: MyCustomName . relay1)

Returns :

a string that uniquely identifies the analog input using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

anbutton→get_functionDescriptor()
anbutton→functionDescriptor()
anbutton.get_functionDescriptor()

YAnButton

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

anbutton→get_functionId()**YAnButton****anbutton→functionId()anbutton.get_functionId()**

Returns the hardware identifier of the analog input, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the analog input (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

anbutton→get_hardwareId()

YAnButton

anbutton→hardwareId()anbutton.get_hardwareId()

Returns the unique hardware identifier of the analog input in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the analog input (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the analog input (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

anbutton→get_isPressed()**YAnButton****anbutton→isPressed()anbutton.get_isPressed()**

Returns true if the input (considered as binary) is active (closed contact), and false otherwise.

```
def get_isPressed( )
```

Returns :

either Y_ISPRESSED_FALSE or Y_ISPRESSED_TRUE, according to true if the input (considered as binary) is active (closed contact), and false otherwise

On failure, throws an exception or returns Y_ISPRESSED_INVALID.

anbutton→get_lastTimePressed()
anbutton→lastTimePressed()
anbutton.get_lastTimePressed()

YAnButton

Returns the number of elapsed milliseconds between the module power on and the last time the input button was pressed (the input contact transitioned from open to closed).

```
def get_lastTimePressed( )
```

Returns :

an integer corresponding to the number of elapsed milliseconds between the module power on and the last time the input button was pressed (the input contact transitioned from open to closed)

On failure, throws an exception or returns Y_LASTTIMEPRESSED_INVALID.

anbutton→get_lastTimeReleased()
anbutton→lastTimeReleased()
anbutton.get_lastTimeReleased()

YAnButton

Returns the number of elapsed milliseconds between the module power on and the last time the input button was released (the input contact transitioned from closed to open).

```
def get_lastTimeReleased( )
```

Returns :

an integer corresponding to the number of elapsed milliseconds between the module power on and the last time the input button was released (the input contact transitioned from closed to open)

On failure, throws an exception or returns Y_LASTTIMERELEASED_INVALID.

anbutton→get_logicalName()

YAnButton

anbutton→logicalName()anbutton.get_logicalName()

Returns the logical name of the analog input.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the analog input.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

anbutton→get_module()**YAnButton****anbutton→module()anbutton.get_module()**

Gets the YModule object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

anbutton→get_pulseCounter()
anbutton→pulseCounter()
anbutton.get_pulseCounter()

YAnButton

Returns the pulse counter value

```
def get_pulseCounter( )
```

Returns :

an integer corresponding to the pulse counter value

On failure, throws an exception or returns Y_PULSECOUNTERR_INVALID.

anbutton→get_pulseTimer()**YAnButton****anbutton→pulseTimer()anbutton.get_pulseTimer()**

Returns the timer of the pulses counter (ms)

```
def get_pulseTimer( )
```

Returns :

an integer corresponding to the timer of the pulses counter (ms)

On failure, throws an exception or returns Y_PULSE_TIMER_INVALID.

anbutton→get_rawValue()

YAnButton

anbutton→rawValue()anbutton.get_rawValue()

Returns the current measured input value as-is (between 0 and 4095, included).

```
def get_rawValue( )
```

Returns :

an integer corresponding to the current measured input value as-is (between 0 and 4095, included)

On failure, throws an exception or returns Y_RAWVALUE_INVALID.

anbutton→get_sensitivity()**YAnButton****anbutton→sensitivity()|anbutton.get_sensitivity()**

Returns the sensibility for the input (between 1 and 1000) for triggering user callbacks.

```
def get_sensitivity( )
```

Returns :

an integer corresponding to the sensibility for the input (between 1 and 1000) for triggering user callbacks

On failure, throws an exception or returns Y_SENSITIVITY_INVALID.

anbutton→get(userData)

YAnButton

anbutton→userData()anbutton.get(userData)

Returns the value of the userData attribute, as previously stored using method set(userData).

```
def get(userData) :
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

anbutton→isOnline()|anbutton.isOnline()**YAnButton**

Checks if the analog input is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the analog input in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the analog input.

Returns :

`true` if the analog input can be reached, and `false` otherwise

anbutton→load()**YAnButton**

Preloads the analog input cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

anbutton→nextAnButton()**YAnButton**

Continues the enumeration of analog inputs started using `yFirstAnButton()`.

```
def nextAnButton( )
```

Returns :

a pointer to a `YAnButton` object, corresponding to an analog input currently online, or a null pointer if there are no more analog inputs to enumerate.

**anbutton→registerValueCallback()
anbutton.registerValueCallback()****YAnButton**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

anbutton→resetCounter()|anbutton.resetCounter()**YAnButton**

Returns the pulse counter value as well as his timer

```
def resetCounter( )
```

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

anbutton→set_analogCalibration()
anbutton→setAnalogCalibration()
anbutton.set_analogCalibration()

YAnButton

Starts or stops the calibration process.

```
def set_analogCalibration( newval)
```

Remember to call the `saveToFlash()` method of the module at the end of the calibration if the modification must be kept.

Parameters :

newval either `Y_ANALOGCALIBRATION_OFF` or `Y_ANALOGCALIBRATION_ON`

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

anbutton→set_calibrationMax()
anbutton→setCalibrationMax()
anbutton.set_calibrationMax()

YAnButton

Changes the maximal calibration value for the input (between 0 and 4095, included), without actually starting the automated calibration.

```
def set_calibrationMax( newval )
```

Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval an integer corresponding to the maximal calibration value for the input (between 0 and 4095, included), without actually starting the automated calibration

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

anbutton→set_calibrationMin()
anbutton→setCalibrationMin()
anbutton.set_calibrationMin()

YAnButton

Changes the minimal calibration value for the input (between 0 and 4095, included), without actually starting the automated calibration.

```
def set_calibrationMin( newval)
```

Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval an integer corresponding to the minimal calibration value for the input (between 0 and 4095, included), without actually starting the automated calibration

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

anbutton→set_logicalName()
anbutton→setLogicalName()
anbutton.set_logicalName()

YAnButton

Changes the logical name of the analog input.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the logical name of the analog input.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

anbutton→set_sensitivity()**YAnButton****anbutton→setSensitivity()anbutton.set_sensitivity()**

Changes the sensibility for the input (between 1 and 1000) for triggering user callbacks.

```
def set_sensitivity( newval)
```

The sensibility is used to filter variations around a fixed value, but does not preclude the transmission of events when the input value evolves constantly in the same direction. Special case: when the value 1000 is used, the callback will only be thrown when the logical state of the input switches from pressed to released and back. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval an integer corresponding to the sensibility for the input (between 1 and 1000) for triggering user callbacks

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

anbutton→set(userData)**anbutton→setUserData()anbutton.set(userData)**

YAnButton

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData| data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.5. CarbonDioxide function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_carbondioxide.js'></script>
nodejs var yoctolib = require('yoctolib');
var YCarbonDioxide = yoctolib.YCarbonDioxide;
php require_once('yocto_carbondioxide.php');
cpp #include "yocto_carbondioxide.h"
m #import "yocto_carbondioxide.h"
pas uses yocto_carbondioxide;
vb yocto_carbondioxide.vb
cs yocto_carbondioxide.cs
java import com.yoctopuce.YoctoAPI.YCarbonDioxide;
py from yocto_carbondioxide import *

```

Global functions

yFindCarbonDioxide(func)

Retrieves a CO2 sensor for a given identifier.

yFirstCarbonDioxide()

Starts the enumeration of CO2 sensors currently accessible.

YCarbonDioxide methods

carbondioxide→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

carbondioxide→describe()

Returns a short text that describes unambiguously the instance of the CO2 sensor in the form TYPE(NAME)=SERIAL.FUNCTIONID.

carbondioxide→get_advertisedValue()

Returns the current value of the CO2 sensor (no more than 6 characters).

carbondioxide→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in ppm (vol), as a floating point number.

carbondioxide→get_currentValue()

Returns the current value of the CO2 concentration, in ppm (vol), as a floating point number.

carbondioxide→get_errorMessage()

Returns the error message of the latest error with the CO2 sensor.

carbondioxide→get_errorType()

Returns the numerical error code of the latest error with the CO2 sensor.

carbondioxide→get_friendlyName()

Returns a global identifier of the CO2 sensor in the format MODULE_NAME . FUNCTION_NAME.

carbondioxide→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

carbondioxide→get_functionId()

Returns the hardware identifier of the CO2 sensor, without reference to the module.

carbondioxide→get_hardwareId()

Returns the unique hardware identifier of the CO2 sensor in the form SERIAL.FUNCTIONID.
carbondioxide→get_highestValue()
Returns the maximal value observed for the CO2 concentration since the device was started.
carbondioxide→get_logFrequency()
Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.
carbondioxide→get_logicalName()
Returns the logical name of the CO2 sensor.
carbondioxide→get_lowestValue()
Returns the minimal value observed for the CO2 concentration since the device was started.
carbondioxide→get_module()
Gets the YModule object for the device on which the function is located.
carbondioxide→get_module_async(callback, context)
Gets the YModule object for the device on which the function is located (asynchronous version).
carbondioxide→get_recordedData(startTime, endTime)
Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.
carbondioxide→get_reportFrequency()
Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.
carbondioxide→get_resolution()
Returns the resolution of the measured values.
carbondioxide→get_unit()
Returns the measuring unit for the CO2 concentration.
carbondioxide→get(userData)
Returns the value of the userData attribute, as previously stored using method set(userData).
carbondioxide→isOnline()
Checks if the CO2 sensor is currently reachable, without raising any error.
carbondioxide→isOnline_async(callback, context)
Checks if the CO2 sensor is currently reachable, without raising any error (asynchronous version).
carbondioxide→load(msValidity)
Preloads the CO2 sensor cache with a specified validity duration.
carbondioxide→loadCalibrationPoints(rawValues, refValues)
Retrieves error correction data points previously entered using the method calibrateFromPoints.
carbondioxide→load_async(msValidity, callback, context)
Preloads the CO2 sensor cache with a specified validity duration (asynchronous version).
carbondioxide→nextCarbonDioxide()
Continues the enumeration of CO2 sensors started using yFirstCarbonDioxide().
carbondioxide→registerTimedReportCallback(callback)
Registers the callback function that is invoked on every periodic timed notification.
carbondioxide→registerValueCallback(callback)
Registers the callback function that is invoked on every change of advertised value.
carbondioxide→set_highestValue(newval)
Changes the recorded maximal value observed.
carbondioxide→set_logFrequency(newval)
Changes the datalogger recording frequency for this function.
carbondioxide→set_logicalName(newval)

3. Reference

Changes the logical name of the CO2 sensor.

carbondioxide→set_lowestValue(newval)

Changes the recorded minimal value observed.

carbondioxide→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

carbondioxide→set_resolution(newval)

Changes the resolution of the measured physical values.

carbondioxide→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

carbondioxide→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YCarbonDioxide.FindCarbonDioxide() yFindCarbonDioxide() YCarbonDioxide.FindCarbonDioxide()

YCarbonDioxide

Retrieves a CO2 sensor for a given identifier.

```
def FindCarbonDioxide( func )
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the CO2 sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YCarbonDioxide.isOnline()` to test if the CO2 sensor is indeed online at a given time. In case of ambiguity when looking for a CO2 sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the CO2 sensor

Returns :

a `YCarbonDioxide` object allowing you to drive the CO2 sensor.

YCarbonDioxide.FirstCarbonDioxide()

YCarbonDioxide

yFirstCarbonDioxide()

YCarbonDioxide.FirstCarbonDioxide()

Starts the enumeration of CO2 sensors currently accessible.

```
def FirstCarbonDioxide( )
```

Use the method `YCarbonDioxide.nextCarbonDioxide()` to iterate on next CO2 sensors.

Returns :

a pointer to a `YCarbonDioxide` object, corresponding to the first CO2 sensor currently online, or a null pointer if there are none.

**carbondioxide→calibrateFromPoints()
carbondioxide.calibrateFromPoints()****YCarbonDioxide**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

carbondioxide→describe()carbon dioxide.describe()**YCarbonDioxide**

Returns a short text that describes unambiguously the instance of the CO2 sensor in the form
TYPE (NAME)=SERIAL . FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the CO2 sensor (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

carbondioxide→get_advertisedValue()
carbondioxide→advertisedValue()
carbondioxide.get_advertisedValue()

YCarbonDioxide

Returns the current value of the CO2 sensor (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the CO2 sensor (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

carbon dioxide → get_currentRawValue()
carbon dioxide → currentRawValue()
carbon dioxide.get_currentRawValue()

YCarbonDioxide

Returns the uncalibrated, unrounded raw value returned by the sensor, in ppm (vol), as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in ppm (vol), as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

carbondioxide→get_currentValue()
carbondioxide→currentValue()
carbondioxide.get_currentValue()

YCarbonDioxide

Returns the current value of the CO2 concentration, in ppm (vol), as a floating point number.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current value of the CO2 concentration, in ppm (vol), as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

carbondioxide→get_errorMessage()
carbondioxide→errorMessage()
carbondioxide.get_errorMessage()

YCarbonDioxide

Returns the error message of the latest error with the CO2 sensor.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the CO2 sensor object

carbondioxide→get_errorType()
carbondioxide→errorType()
carbondioxide.get_errorType()

YCarbonDioxide

Returns the numerical error code of the latest error with the CO2 sensor.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the CO2 sensor object

carbondioxide→get_friendlyName()
carbondioxide→friendlyName()
carbondioxide.get_friendlyName()

YCarbonDioxide

Returns a global identifier of the CO2 sensor in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the CO2 sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the CO2 sensor (for example: MyCustomName . relay1)

Returns :

a string that uniquely identifies the CO2 sensor using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

carbondioxide→get_functionDescriptor()
carbondioxide→functionDescriptor()
carbondioxide.get_functionDescriptor()

YCarbonDioxide

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

carbondioxide→get_functionId()
carbondioxide→functionId()
carbondioxide.get_functionId()

YCarbonDioxide

Returns the hardware identifier of the CO2 sensor, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the CO2 sensor (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

carbondioxide→get.hardwareId()
carbondioxide→hardwareId()
carbondioxide.get.hardwareId()

YCarbonDioxide

Returns the unique hardware identifier of the CO2 sensor in the form SERIAL.FUNCTIONID.

def get.hardwareId()

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the CO2 sensor (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the CO2 sensor (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

carbondioxide→get_highestValue()
carbondioxide→highestValue()
carbondioxide.get_highestValue()

YCarbonDioxide

Returns the maximal value observed for the CO2 concentration since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the CO2 concentration since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

carbondioxide→get_logFrequency()
carbondioxide→logFrequency()
carbondioxide.get_logFrequency()

YCarbonDioxide

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

carbondioxide→get_logicalName()
carbondioxide→logicalName()
carbondioxide.get_logicalName()

YCarbonDioxide

Returns the logical name of the CO2 sensor.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the CO2 sensor.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

carbondioxide→get_lowestValue()
carbondioxide→lowestValue()
carbondioxide.get_lowestValue()

YCarbonDioxide

Returns the minimal value observed for the CO₂ concentration since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the CO₂ concentration since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

carbondioxide→get_module()
carbondioxide→module()
carbondioxide.get_module()

YCarbonDioxide

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

carbondioxide→get_recordedData()
carbondioxide→recordedData()
carbondioxide.get_recordedData()

YCarbonDioxide

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime)
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

carbondioxide→get_reportFrequency()

YCarbonDioxide

carbondioxide→reportFrequency()

carbondioxide.get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

carbondioxide→get_resolution()
carbondioxide→resolution()
carbondioxide.get_resolution()

YCarbonDioxide

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

carbondioxide→get_unit()

YCarbonDioxide

carbondioxide→unit()carbondioxide.get_unit()

Returns the measuring unit for the CO2 concentration.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the CO2 concentration

On failure, throws an exception or returns Y_UNIT_INVALID.

carbondioxide→get(userData)
carbondioxide→userData()
carbondioxide.get(userData)

YCarbonDioxide

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

carbondioxide→isOnline()carbon dioxide.isOnline()

YCarbonDioxide

Checks if the CO2 sensor is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the CO2 sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the CO2 sensor.

Returns :

true if the CO2 sensor can be reached, and false otherwise

carbondioxide→load()carbon dioxide.load()**YCarbonDioxide**

Preloads the CO2 sensor cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

**carbon dioxide → loadCalibrationPoints()
carbon dioxide.loadCalibrationPoints()****YCarbonDioxide**

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

carbondioxide→nextCarbonDioxide()
carbondioxide.nextCarbonDioxide()**YCarbonDioxide**

Continues the enumeration of CO2 sensors started using `yFirstCarbonDioxide()`.

```
def nextCarbonDioxide( )
```

Returns :

a pointer to a `YCarbonDioxide` object, corresponding to a CO2 sensor currently online, or a `null` pointer if there are no more CO2 sensors to enumerate.

carbon dioxide → registerTimedReportCallback()
carbon dioxide.registerTimedReportCallback()**YCarbonDioxide**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

carbondioxide→registerValueCallback()
carbondioxide.registerValueCallback()**YCarbonDioxide**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

carbondioxide→set_highestValue()
carbondioxide→setHighestValue()
carbondioxide.set_highestValue()

YCarbonDioxide

Changes the recorded maximal value observed.

```
def set_highestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

carbondioxide→set_logFrequency()
carbondioxide→setLogFrequency()
carbondioxide.set_logFrequency()

YCarbonDioxide

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval)
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

carbondioxide→set_logicalName()
carbondioxide→setLogicalName()
carbondioxide.set_logicalName()

YCarbonDioxide

Changes the logical name of the CO2 sensor.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the CO2 sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

carbondioxide→set_lowestValue()
carbondioxide→setLowestValue()
carbondioxide.set_lowestValue()

YCarbonDioxide

Changes the recorded minimal value observed.

```
def set_lowestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

carbon dioxide → set_reportFrequency()
carbon dioxide → setReportFrequency()
carbon dioxide.set_reportFrequency()**YCarbonDioxide**

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

carbondioxide→set_resolution()
carbondioxide→setResolution()
carbondioxide.set_resolution()

YCarbonDioxide

Changes the resolution of the measured physical values.

```
def set_resolution( newval )
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

carbondioxide→set(userData)
carbondioxide→setUserData()
carbondioxide.set(userData)

YCarbonDioxide

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.6. ColorLed function interface

Yoctopuce application programming interface allows you to drive a color led using RGB coordinates as well as HSL coordinates. The module performs all conversions from RGB to HSL automatically. It is then self-evident to turn on a led with a given hue and to progressively vary its saturation or lightness. If needed, you can find more information on the difference between RGB and HSL in the section following this one.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_colorled.js'></script>
node.js	var yoctolib = require('yoctolib');
php	var YColorLed = yoctolib.YColorLed;
cpp	require_once('yocto_colorled.php');
m	#include "yocto_colorled.h"
pas	#import "yocto_colorled.h"
vb	uses yocto_colorled;
cs	yocto_colorled.vb
java	yocto_colorled.cs
py	import com.yoctopuce.YoctoAPI.YColorLed;
	from yocto_colorled import *

Global functions

yFindColorLed(func)

Retrieves an RGB led for a given identifier.

yFirstColorLed()

Starts the enumeration of RGB leds currently accessible.

YColorLed methods

colorled→describe()

Returns a short text that describes unambiguously the instance of the RGB led in the form TYPE (NAME)=SERIAL . FUNCTIONID.

colorled→get_advertisedValue()

Returns the current value of the RGB led (no more than 6 characters).

colorled→get_errorMessage()

Returns the error message of the latest error with the RGB led.

colorled→get_errorType()

Returns the numerical error code of the latest error with the RGB led.

colorled→get_friendlyName()

Returns a global identifier of the RGB led in the format MODULE _ NAME . FUNCTION _ NAME.

colorled→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

colorled→get_functionId()

Returns the hardware identifier of the RGB led, without reference to the module.

colorled→get_hardwareId()

Returns the unique hardware identifier of the RGB led in the form SERIAL . FUNCTIONID.

colorled→get_hslColor()

Returns the current HSL color of the led.

colorled→get_logicalName()

Returns the logical name of the RGB led.

3. Reference

colorled→get_module()

Gets the YModule object for the device on which the function is located.

colorled→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

colorled→get_rgbColor()

Returns the current RGB color of the led.

colorled→get_rgbColorAtPowerOn()

Returns the configured color to be displayed when the module is turned on.

colorled→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

colorled→hslMove(hsl_target, ms_duration)

Performs a smooth transition in the HSL color space between the current color and a target color.

colorled→isOnline()

Checks if the RGB led is currently reachable, without raising any error.

colorled→isOnline_async(callback, context)

Checks if the RGB led is currently reachable, without raising any error (asynchronous version).

colorled→load(msValidity)

Preloads the RGB led cache with a specified validity duration.

colorled→load_async(msValidity, callback, context)

Preloads the RGB led cache with a specified validity duration (asynchronous version).

colorled→nextColorLed()

Continues the enumeration of RGB leds started using yFirstColorLed().

colorled→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

colorled→rgbMove(rgb_target, ms_duration)

Performs a smooth transition in the RGB color space between the current color and a target color.

colorled→set_hslColor(newval)

Changes the current color of the led, using a color HSL.

colorled→set_logicalName(newval)

Changes the logical name of the RGB led.

colorled→set_rgbColor(newval)

Changes the current color of the led, using a RGB color.

colorled→set_rgbColorAtPowerOn(newval)

Changes the color that the led will display by default when the module is turned on.

colorled→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

colorled→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YColorLed.FindColorLed() yFindColorLed()YColorLed.FindColorLed()

YColorLed

Retrieves an RGB led for a given identifier.

```
def FindColorLed( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the RGB led is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YColorLed.isOnline()` to test if the RGB led is indeed online at a given time. In case of ambiguity when looking for an RGB led by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the RGB led

Returns :

a `YColorLed` object allowing you to drive the RGB led.

YColorLed.FirstColorLed()

YColorLed

yFirstColorLed()YColorLed.FirstColorLed()

Starts the enumeration of RGB leds currently accessible.

```
def FirstColorLed( )
```

Use the method `YColorLed.nextColorLed()` to iterate on next RGB leds.

Returns :

a pointer to a `YColorLed` object, corresponding to the first RGB led currently online, or a `null` pointer if there are none.

colorled→describe()colorled.describe()**YColorLed**

Returns a short text that describes unambiguously the instance of the RGB led in the form TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the RGB led (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

colorled→get_advertisedValue()
colorled→advertisedValue()
colorled.get_advertisedValue()

YColorLed

Returns the current value of the RGB led (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the RGB led (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

colorled→get_errorMessage()
colorled→errorMessage()
colorled.get_errorMessage()

YColorLed

Returns the error message of the latest error with the RGB led.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the RGB led object

colorled→get_errorType()

YColorLed

colorled→errorType()colorled.get_errorType()

Returns the numerical error code of the latest error with the RGB led.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the RGB led object

colorled→get_friendlyName()**YColorLed****colorled→friendlyName()colorled.get_friendlyName()**

Returns a global identifier of the RGB led in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the RGB led if they are defined, otherwise the serial number of the module and the hardware identifier of the RGB led (for example: MyCustomName . relay1)

Returns :

a string that uniquely identifies the RGB led using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

colorled→get_functionDescriptor()
colorled→functionDescriptor()
colorled.get_functionDescriptor()

YColorLed

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

colorled→get_functionId()**YColorLed****colorled→functionId()colorled.get_functionId()**

Returns the hardware identifier of the RGB led, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the RGB led (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

colorled→get.hardwareId()

YColorLed

colorled→hardwareId()colorled.get.hardwareId()

Returns the unique hardware identifier of the RGB led in the form SERIAL.FUNCTIONID.

```
def get.hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the RGB led (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the RGB led (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

colorled→get_hslColor()**colorled→hslColor()colorled.get_hslColor()**

YColorLed

Returns the current HSL color of the led.

```
def get_hslColor( )
```

Returns :

an integer corresponding to the current HSL color of the led

On failure, throws an exception or returns Y_HSLCOLOR_INVALID.

colorled→get_logicalName()

YColorLed

colorled→logicalName()colorled.get_logicalName()

Returns the logical name of the RGB led.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the RGB led.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

colorled→get_module()**YColorLed****colorled→module()colorled.get_module()**

Gets the YModule object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

colorled→get_rgbColor()

YColorLed

colorled→rgbColor()colorled.get_rgbColor()

Returns the current RGB color of the led.

```
def get_rgbColor( )
```

Returns :

an integer corresponding to the current RGB color of the led

On failure, throws an exception or returns Y_RGBCOLOR_INVALID.

colorled→get_rgbColorAtPowerOn()**YColorLed****colorled→rgbColorAtPowerOn()****colorled.get_rgbColorAtPowerOn()**

Returns the configured color to be displayed when the module is turned on.

```
def get_rgbColorAtPowerOn( )
```

Returns :

an integer corresponding to the configured color to be displayed when the module is turned on

On failure, throws an exception or returns Y_RGBCOLORATPOWERON_INVALID.

colorled→get(userData)

YColorLed

colorled→userData()colorled.get(userData)

Returns the value of the userData attribute, as previously stored using method set(userData).

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

colorled→hsIMove()colorled.hsIMove()**YColorLed**

Performs a smooth transition in the HSL color space between the current color and a target color.

```
def hsIMove( hsl_target, ms_duration)
```

Parameters :

hsl_target desired HSL color at the end of the transition

ms_duration duration of the transition, in millisecond

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

colorled→isOnline()colorled.isOnline()**YColorLed**

Checks if the RGB led is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the RGB led in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the RGB led.

Returns :

`true` if the RGB led can be reached, and `false` otherwise

colorled→load()colorled.load()**YColorLed**

Preloads the RGB led cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

colorled→nextColorLed()colorled.nextColorLed()

YColorLed

Continues the enumeration of RGB leds started using `yFirstColorLed()`.

```
def nextColorLed( )
```

Returns :

a pointer to a `YColorLed` object, corresponding to an RGB led currently online, or a null pointer if there are no more RGB leds to enumerate.

colorled→registerValueCallback()
colorled.registerValueCallback()**YColorLed**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

colorled→rgbMove()colorled.rgbMove()**YColorLed**

Performs a smooth transition in the RGB color space between the current color and a target color.

```
def rgbMove( rgb_target, ms_duration)
```

Parameters :

rgb_target desired RGB color at the end of the transition

ms_duration duration of the transition, in millisecond

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

colorled→set_hslColor()**YColorLed****colorled→setHslColor()colorled.set_hslColor()**

Changes the current color of the led, using a color HSL.

```
def set_hslColor( newval)
```

Encoding is done as follows: 0xHHSSL.

Parameters :

newval an integer corresponding to the current color of the led, using a color HSL

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

colorled→set_logicalName()
colorled→setLogicalName()
colorled.set_logicalName()

YColorLed

Changes the logical name of the RGB led.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the RGB led.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

colorled→set_rgbColor()**YColorLed****colorled→setRgbColor()colorled.set_rgbColor()**

Changes the current color of the led, using a RGB color.

```
def set_rgbColor( newval )
```

Encoding is done as follows: 0xRRGGBB.

Parameters :

newval an integer corresponding to the current color of the led, using a RGB color

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

colorled→set_rgbColorAtPowerOn()
colorled→setRgbColorAtPowerOn()
colorled.set_rgbColorAtPowerOn()

YColorLed

Changes the color that the led will display by default when the module is turned on.

```
def set_rgbColorAtPowerOn( newval)
```

This color will be displayed as soon as the module is powered on. Remember to call the saveToFlash() method of the module if the change should be kept.

Parameters :

newval an integer corresponding to the color that the led will display by default when the module is turned on

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

colorled→set(userData)**YColorLed****colorled→setUserData()colorled.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.7. Compass function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_compass.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YCompass = yoctolib.YCompass;
php	require_once('yocto_compass.php');
cpp	#include "yocto_compass.h"
m	#import "yocto_compass.h"
pas	uses yocto_compass;
vb	yocto_compass.vb
cs	yocto_compass.cs
java	import com.yoctopuce.YoctoAPI.YCompass;
py	from yocto_compass import *

Global functions

yFindCompass(func)

Retrieves a compass for a given identifier.

yFirstCompass()

Starts the enumeration of compasses currently accessible.

YCompass methods

compass→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

compass→describe()

Returns a short text that describes unambiguously the instance of the compass in the form TYPE(NAME)=SERIAL.FUNCTIONID.

compass→get_advertisedValue()

Returns the current value of the compass (no more than 6 characters).

compass→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in degrees, as a floating point number.

compass→get_currentValue()

Returns the current value of the relative bearing, in degrees, as a floating point number.

compass→get_errorMessage()

Returns the error message of the latest error with the compass.

compass→get_errorType()

Returns the numerical error code of the latest error with the compass.

compass→get_friendlyName()

Returns a global identifier of the compass in the format MODULE_NAME.FUNCTION_NAME.

compass→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

compass→get_functionId()

Returns the hardware identifier of the compass, without reference to the module.

compass→get_hardwareId()

Returns the unique hardware identifier of the compass in the form SERIAL.FUNCTIONID.

compass→get_highestValue()

Returns the maximal value observed for the relative bearing since the device was started.

compass→get_logFrequency()

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

compass→get_logicalName()

Returns the logical name of the compass.

compass→get_lowestValue()

Returns the minimal value observed for the relative bearing since the device was started.

compass→get_magneticHeading()

Returns the magnetic heading, regardless of the configured bearing.

compass→get_module()

Gets the YModule object for the device on which the function is located.

compass→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

compass→get_recordedData(startTime, endTime)

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

compass→get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

compass→get_resolution()

Returns the resolution of the measured values.

compass→get_unit()

Returns the measuring unit for the relative bearing.

compass→get(userData)

Returns the value of the userData attribute, as previously stored using method set(userData).

compass→isOnline()

Checks if the compass is currently reachable, without raising any error.

compass→isOnline_async(callback, context)

Checks if the compass is currently reachable, without raising any error (asynchronous version).

compass→load(msValidity)

Preloads the compass cache with a specified validity duration.

compass→loadCalibrationPoints(rawValues, refValues)

Retrieves error correction data points previously entered using the method calibrateFromPoints.

compass→load_async(msValidity, callback, context)

Preloads the compass cache with a specified validity duration (asynchronous version).

compass→nextCompass()

Continues the enumeration of compasses started using yFirstCompass().

compass→registerTimedReportCallback(callback)

Registers the callback function that is invoked on every periodic timed notification.

compass→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

compass→set_highestValue(newval)

Changes the recorded maximal value observed.

compass→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

3. Reference

compass→set_logicalName(newval)

Changes the logical name of the compass.

compass→set_lowestValue(newval)

Changes the recorded minimal value observed.

compass→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

compass→set_resolution(newval)

Changes the resolution of the measured physical values.

compass→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

compass→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YCompass.FindCompass() yFindCompass()YCompass.FindCompass()

YCompass

Retrieves a compass for a given identifier.

```
def FindCompass( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the compass is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YCompass.isOnline()` to test if the compass is indeed online at a given time. In case of ambiguity when looking for a compass by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the compass

Returns :

a `YCompass` object allowing you to drive the compass.

YCompass.FirstCompass()

YCompass

yFirstCompass()YCompass.FirstCompass()

Starts the enumeration of compasses currently accessible.

```
def FirstCompass( )
```

Use the method `YCompass .nextCompass()` to iterate on next compasses.

Returns :

a pointer to a `YCompass` object, corresponding to the first compass currently online, or a `null` pointer if there are none.

compass→calibrateFromPoints()
compass.calibrateFromPoints()**YCompass**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

compass→describe()compass.describe()**YCompass**

Returns a short text that describes unambiguously the instance of the compass in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the compass (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

compass→get_advertisedValue()
compass→advertisedValue()
compass.get_advertisedValue()

YCompass

Returns the current value of the compass (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the compass (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

compass→get_currentRawValue()
compass→currentRawValue()
compass.get_currentRawValue()

YCompass

Returns the uncalibrated, unrounded raw value returned by the sensor, in degrees, as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in degrees, as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

compass→get_currentValue()
compass→currentValue()
compass.get_currentValue()

YCompass

Returns the current value of the relative bearing, in degrees, as a floating point number.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current value of the relative bearing, in degrees, as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

compass→get_errorMessage()
compass→errorMessage()
compass.get_errorMessage()

YCompass

Returns the error message of the latest error with the compass.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the compass object

compass→get_errorType()**YCompass****compass→errorType()compass.get_errorType()**

Returns the numerical error code of the latest error with the compass.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the compass object

compass→get_friendlyName()
compass→friendlyName()
compass.get_friendlyName()

YCompass

Returns a global identifier of the compass in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the compass if they are defined, otherwise the serial number of the module and the hardware identifier of the compass (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the compass using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

compass→get_functionDescriptor()
compass→functionDescriptor()
compass.get_functionDescriptor()

YCompass

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

compass→get_functionId()

YCompass

compass→functionId()compass.get_functionId()

Returns the hardware identifier of the compass, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the compass (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

compass→get_hardwareId()	YCompass
compass→hardwareId()compass.get_hardwareId()	

Returns the unique hardware identifier of the compass in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the compass (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the compass (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

compass→get_highestValue()
compass→highestValue()
compass.get_highestValue()

YCompass

Returns the maximal value observed for the relative bearing since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the relative bearing since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

compass→get_logFrequency()
compass→logFrequency()
compass.get_logFrequency()

YCompass

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

compass→get_logicalName()

YCompass

compass→logicalName()compass.get_logicalName()

Returns the logical name of the compass.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the compass.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

compass→get_lowestValue()**YCompass****compass→lowestValue()compass.get_lowestValue()**

Returns the minimal value observed for the relative bearing since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the relative bearing since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

compass→get_magneticHeading()
compass→magneticHeading()
compass.get_magneticHeading()

YCompass

Returns the magnetic heading, regardless of the configured bearing.

```
def get_magneticHeading( )
```

Returns :

a floating point number corresponding to the magnetic heading, regardless of the configured bearing

On failure, throws an exception or returns Y_MAGNETICHEADING_INVALID.

compass→get_module()**YCompass****compass→module()compass.get_module()**

Gets the YModule object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

compass→get_recordedData()
compass→recordedData()
compass.get_recordedData()

YCompass

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime )
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

compass→get_reportFrequency()
compass→reportFrequency()
compass.get_reportFrequency()

YCompass

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

compass→get_resolution()

YCompass

compass→resolution()compass.get_resolution()

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

compass→get_unit()**YCompass****compass→unit()compass.get_unit()**

Returns the measuring unit for the relative bearing.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the relative bearing

On failure, throws an exception or returns Y_UNIT_INVALID.

compass→get(userData)

YCompass

compass→userData()compass.get(userData)

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

compass→isOnline()compass.isOnline()**YCompass**

Checks if the compass is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the compass in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the compass.

Returns :

`true` if the compass can be reached, and `false` otherwise

compass→load()compass.load()**YCompass**

Preloads the compass cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

compass→loadCalibrationPoints()
compass.loadCalibrationPoints()**YCompass**

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

compass→nextCompass()compass.nextCompass()

YCompass

Continues the enumeration of compasses started using `yFirstCompass()`.

```
def nextCompass( )
```

Returns :

a pointer to a `YCompass` object, corresponding to a compass currently online, or a `null` pointer if there are no more compasses to enumerate.

**compass→registerTimedReportCallback()
compass.registerTimedReportCallback()****YCompass**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

**compass→registerValueCallback()
compass.registerValueCallback()****YCompass**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

compass→set_highestValue()
compass→setHighestValue()
compass.set_highestValue()

YCompass

Changes the recorded maximal value observed.

```
def set_highestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

compass→set_logFrequency()
compass→setLogFrequency()
compass.set_logFrequency()

YCompass

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

compass→set_logicalName()
compass→setLogicalName()
compass.set_logicalName()

YCompass

Changes the logical name of the compass.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the logical name of the compass.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

compass→set_lowestValue()
compass→setLowestValue()
compass.set_lowestValue()

YCompass

Changes the recorded minimal value observed.

```
def set_lowestValue( newval )
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

compass→set_reportFrequency()
compass→setReportFrequency()
compass.set_reportFrequency()

YCompass

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

compass→set_resolution()

YCompass

compass→setResolution()compass.set_resolution()

Changes the resolution of the measured physical values.

```
def set_resolution( newval)
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

compass→set(userData)**YCompass****compass→setUserData()compass.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.8. Current function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_current.js'></script>
nodejs var yoctolib = require('yoctolib');
var YCurrent = yoctolib.YCurrent;
php require_once('yocto_current.php');
cpp #include "yocto_current.h"
m #import "yocto_current.h"
pas uses yocto_current;
vb yocto_current.vb
cs yocto_current.cs
java import com.yoctopuce.YoctoAPI.YCurrent;
py from yocto_current import *

```

Global functions

yFindCurrent(func)

Retrieves a current sensor for a given identifier.

yFirstCurrent()

Starts the enumeration of current sensors currently accessible.

YCurrent methods

current→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

current→describe()

Returns a short text that describes unambiguously the instance of the current sensor in the form TYPE (NAME) = SERIAL . FUNCTIONID.

current→get_advertisedValue()

Returns the current value of the current sensor (no more than 6 characters).

current→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in mA, as a floating point number.

current→get_currentValue()

Returns the current value of the current, in mA, as a floating point number.

current→get_errorMessage()

Returns the error message of the latest error with the current sensor.

current→get_errorType()

Returns the numerical error code of the latest error with the current sensor.

current→get_friendlyName()

Returns a global identifier of the current sensor in the format MODULE_NAME . FUNCTION_NAME.

current→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

current→get_functionId()

Returns the hardware identifier of the current sensor, without reference to the module.

current→get_hardwareId()

Returns the unique hardware identifier of the current sensor in the form SERIAL . FUNCTIONID.

current→get_highestValue()

Returns the maximal value observed for the current since the device was started.

current→get_logFrequency()

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

current→get_logicalName()

Returns the logical name of the current sensor.

current→get_lowestValue()

Returns the minimal value observed for the current since the device was started.

current→get_module()

Gets the YModule object for the device on which the function is located.

current→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

current→get_recordedData(startTime, endTime)

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

current→get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

current→get_resolution()

Returns the resolution of the measured values.

current→get_unit()

Returns the measuring unit for the current.

current→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

current→isOnline()

Checks if the current sensor is currently reachable, without raising any error.

current→isOnline_async(callback, context)

Checks if the current sensor is currently reachable, without raising any error (asynchronous version).

current→load(msValidity)

Preloads the current sensor cache with a specified validity duration.

current→loadCalibrationPoints(rawValues, refValues)

Retrieves error correction data points previously entered using the method calibrateFromPoints.

current→load_async(msValidity, callback, context)

Preloads the current sensor cache with a specified validity duration (asynchronous version).

current→nextCurrent()

Continues the enumeration of current sensors started using yFirstCurrent().

current→registerTimedReportCallback(callback)

Registers the callback function that is invoked on every periodic timed notification.

current→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

current→set_highestValue(newval)

Changes the recorded maximal value observed.

current→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

current→set_logicalName(newval)

Changes the logical name of the current sensor.

3. Reference

current→set_lowestValue(newval)

Changes the recorded minimal value observed.

current→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

current→set_resolution(newval)

Changes the resolution of the measured physical values.

current→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

current→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YCurrent.FindCurrent()**YCurrent****yFindCurrent() YCurrent.FindCurrent()**

Retrieves a current sensor for a given identifier.

```
def FindCurrent( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the current sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YCurrent.isOnline()` to test if the current sensor is indeed online at a given time. In case of ambiguity when looking for a current sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the current sensor

Returns :

a `YCurrent` object allowing you to drive the current sensor.

YCurrent.FirstCurrent()

YCurrent

yFirstCurrent()YCurrent.FirstCurrent()

Starts the enumeration of current sensors currently accessible.

```
def FirstCurrent( )
```

Use the method `YCurrent.nextCurrent()` to iterate on next current sensors.

Returns :

a pointer to a `YCurrent` object, corresponding to the first current sensor currently online, or a null pointer if there are none.

current→calibrateFromPoints()
current.calibrateFromPoints()**YCurrent**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

current→describe()current.describe()**YCurrent**

Returns a short text that describes unambiguously the instance of the current sensor in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the current sensor (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

current→get_advertisedValue()
current→advertisedValue()
current.get_advertisedValue()

YCurrent

Returns the current value of the current sensor (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the current sensor (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

current→get_currentRawValue()
current→currentRawValue()
current.get_currentRawValue()

YCurrent

Returns the uncalibrated, unrounded raw value returned by the sensor, in mA, as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in mA, as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

current→get_currentValue()**YCurrent****current→currentValue()current.get_currentValue()**

Returns the current value of the current, in mA, as a floating point number.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current value of the current, in mA, as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

current→get_errorMessage() YCurrent
current→errorMessage()current.getErrorMessage()

Returns the error message of the latest error with the current sensor.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the current sensor object

current→get_errorType()**YCurrent****current→errorType()current.get_errorType()**

Returns the numerical error code of the latest error with the current sensor.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the current sensor object

current→get_friendlyName()	YCurrent
current→friendlyName()current.get_friendlyName()	

Returns a global identifier of the current sensor in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the current sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the current sensor (for example: MyCustomName . relay1)

Returns :

a string that uniquely identifies the current sensor using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

current→get_functionDescriptor()
current→functionDescriptor()
current.get_functionDescriptor()

YCurrent

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

current→get_functionId()

YCurrent

current→functionId()current.get_functionId()

Returns the hardware identifier of the current sensor, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the current sensor (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

current→get_hardwareId()**YCurrent****current→hardwareId()current.get_hardwareId()**

Returns the unique hardware identifier of the current sensor in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the current sensor (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the current sensor (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

current→get_highestValue()

YCurrent

current→highestValue()current.get_highestValue()

Returns the maximal value observed for the current since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the current since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

current→get_logFrequency()**YCurrent****current→logFrequency()current.get_logFrequency()**

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

current→get_logicalName()

YCurrent

current→logicalName()current.get_logicalName()

Returns the logical name of the current sensor.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the current sensor.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

current→get_lowestValue()**YCurrent****current→lowestValue()current.get_lowestValue()**

Returns the minimal value observed for the current since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the current since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

current→get_module()**YCurrent****current→module()current.get_module()**

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

current→get_recordedData()**YCurrent****current→recordedData()current.get_recordedData()**

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime)
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

current→get_reportFrequency()
current→reportFrequency()
current.get_reportFrequency()

YCurrent

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

current→get_resolution()**YCurrent****current→resolution()current.get_resolution()**

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

current→get_unit()

YCurrent

current→unit()current.get_unit()

Returns the measuring unit for the current.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the current

On failure, throws an exception or returns Y_UNIT_INVALID.

current→get(userData)**YCurrent****current→userData()current.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

current→isOnline()current.isOnline()**YCurrent**

Checks if the current sensor is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the current sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the current sensor.

Returns :

true if the current sensor can be reached, and false otherwise

current→load()current.load()**YCurrent**

Preloads the current sensor cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

current→loadCalibrationPoints()
current.loadCalibrationPoints()**YCurrent**

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

current→nextCurrent()current.nextCurrent()**YCurrent**

Continues the enumeration of current sensors started using `yFirstCurrent()`.

```
def nextCurrent( )
```

Returns :

a pointer to a `YCurrent` object, corresponding to a current sensor currently online, or a null pointer if there are no more current sensors to enumerate.

**current→registerTimedReportCallback()
current.registerTimedReportCallback()****YCurrent**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

current→registerValueCallback()
current.registerValueCallback()**YCurrent**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

`current→set_highestValue()`
`current→setHighestValue()`
`current.set_highestValue()`

YCurrent

Changes the recorded maximal value observed.

```
def set_highestValue( newval )
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

current→set_logFrequency()
current→setLogFrequency()
current.set_logFrequency()

YCurrent

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval)
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

current→set_logicalName()	YCurrent
current→setLogicalName()current.set_logicalName()	

Changes the logical name of the current sensor.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the current sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

current→set_lowestValue()**YCurrent****current→setLowestValue()current.set_lowestValue()**

Changes the recorded minimal value observed.

```
def set_lowestValue( newval )
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

current→set_reportFrequency()
current→setReportFrequency()
current.set_reportFrequency()

YCurrent

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

current→set_resolution()**YCurrent****current→setResolution()current.set_resolution()**

Changes the resolution of the measured physical values.

```
def set_resolution( newval )
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

current→set(userData)

YCurrent

current→setUserData()current.set(userData)

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.9. DataLogger function interface

Yoctopuce sensors include a non-volatile memory capable of storing ongoing measured data automatically, without requiring a permanent connection to a computer. The DataLogger function controls the global parameters of the internal data logger.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_datalogger.js'></script>
node.js	var yoctolib = require('yoctolib');
php	var YDataLogger = yoctolib.YDataLogger;
require_once('yocto_datalogger.php');	
cpp	#include "yocto_datalogger.h"
m	#import "yocto_datalogger.h"
pas	uses yocto_datalogger;
vb	yocto_datalogger.vb
cs	yocto_datalogger.cs
java	import com.yoctopuce.YoctoAPI.YDataLogger;
py	from yocto_datalogger import *

Global functions

yFindDataLogger(func)

Retrieves a data logger for a given identifier.

yFirstDataLogger()

Starts the enumeration of data loggers currently accessible.

YDataLogger methods

datalogger→describe()

Returns a short text that describes unambiguously the instance of the data logger in the form TYPE (NAME)=SERIAL.FUNCTIONID.

datalogger→forgetAllDataStreams()

Clears the data logger memory and discards all recorded data streams.

datalogger→get_advertisedValue()

Returns the current value of the data logger (no more than 6 characters).

datalogger→get_autoStart()

Returns the default activation state of the data logger on power up.

datalogger→get_beaconDriven()

Return true if the data logger is synchronised with the localization beacon.

datalogger→get_currentRunIndex()

Returns the current run number, corresponding to the number of times the module was powered on with the dataLogger enabled at some point.

datalogger→get_dataSets()

Returns a list of YDataSet objects that can be used to retrieve all measures stored by the data logger.

datalogger→get_dataStreams(v)

Builds a list of all data streams hold by the data logger (legacy method).

datalogger→get_errorMessage()

Returns the error message of the latest error with the data logger.

datalogger→get_errorType()

Returns the numerical error code of the latest error with the data logger.

datalogger→get_friendlyName()

datalogger→get_functionDescriptor()	Returns a global identifier of the data logger in the format MODULE_NAME . FUNCTION_NAME.
datalogger→get_functionId()	Returns a unique identifier of type YFUN_DESCR corresponding to the function.
datalogger→get_hardwareId()	Returns the hardware identifier of the data logger, without reference to the module.
datalogger→get_logicalName()	Returns the unique hardware identifier of the data logger in the form SERIAL . FUNCTIONID.
datalogger→get_module()	Returns the logical name of the data logger.
datalogger→get_module_async(callback, context)	Gets the YModule object for the device on which the function is located.
datalogger→get_recording()	Gets the YModule object for the device on which the function is located (asynchronous version).
datalogger→get_timeUTC()	Returns the current activation state of the data logger.
datalogger→get_userData()	Returns the Unix timestamp for current UTC time, if known.
datalogger→isOnline()	Returns the value of the userData attribute, as previously stored using method set(userData).
datalogger→isOnline_async(callback, context)	Checks if the data logger is currently reachable, without raising any error.
datalogger→load(msValidity)	Checks if the data logger is currently reachable, without raising any error (asynchronous version).
datalogger→load_async(msValidity, callback, context)	Preloads the data logger cache with a specified validity duration.
datalogger→nextDataLogger()	Preloads the data logger cache with a specified validity duration (asynchronous version).
datalogger→registerValueCallback(callback)	Continues the enumeration of data loggers started using yFirstDataLogger().
datalogger→set_autoStart(newval)	Registers the callback function that is invoked on every change of advertised value.
datalogger→set_beaconDriven(newval)	Changes the default activation state of the data logger on power up.
datalogger→set_logicalName(newval)	Changes the type of synchronisation of the data logger.
datalogger→set_recording(newval)	Changes the logical name of the data logger.
datalogger→set_timeUTC(newval)	Changes the activation state of the data logger to start/stop recording data.
datalogger→set_userData(data)	Changes the current UTC time reference used for recorded data.
datalogger→wait_async(callback, context)	Stores a user context provided as argument in the userData attribute of the function.

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YDataLogger.FindDataLogger() yFindDataLogger()YDataLogger.FindDataLogger()

YDataLogger

Retrieves a data logger for a given identifier.

```
def FindDataLogger( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the data logger is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YDataLogger.isOnline()` to test if the data logger is indeed online at a given time. In case of ambiguity when looking for a data logger by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the data logger

Returns :

a `YDataLogger` object allowing you to drive the data logger.

YDataLogger.FirstDataLogger()**yFirstDataLogger()YDataLogger.FirstDataLogger()****YDataLogger**

Starts the enumeration of data loggers currently accessible.

```
def FirstDataLogger( )
```

Use the method `YDataLogger.nextDataLogger()` to iterate on next data loggers.

Returns :

a pointer to a `YDataLogger` object, corresponding to the first data logger currently online, or a null pointer if there are none.

datalogger→describe()datalogger.describe()**YDataLogger**

Returns a short text that describes unambiguously the instance of the data logger in the form
TYPE (NAME)=SERIAL . FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the data logger (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

**datalogger→forgetAllDataStreams()
datalogger.forgetAllDataStreams()****YDataLogger**

Clears the data logger memory and discards all recorded data streams.

```
def forgetAllDataStreams( )
```

This method also resets the current run index to zero.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

datalogger→get_advertisedValue()
datalogger→advertisedValue()
datalogger.get_advertisedValue()

YDataLogger

Returns the current value of the data logger (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the data logger (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

datalogger→get_autoStart()**YDataLogger****datalogger→autoStart()datalogger.get_autoStart()**

Returns the default activation state of the data logger on power up.

```
def get_autoStart( )
```

Returns :

either Y_AUTOSTART_OFF or Y_AUTOSTART_ON, according to the default activation state of the data logger on power up

On failure, throws an exception or returns Y_AUTOSTART_INVALID.

datalogger→get_beaconDriven()
datalogger→beaconDriven()
datalogger.get_beaconDriven()

YDataLogger

Return true if the data logger is synchronised with the localization beacon.

```
def get_beaconDriven( )
```

Returns :

either Y_BEACONDRAIVEN_OFF or Y_BEACONDRAIVEN_ON

On failure, throws an exception or returns Y_BEACONDRAIVEN_INVALID.

datalogger→get_currentRunIndex()
datalogger→currentRunIndex()
datalogger.get_currentRunIndex()

YDataLogger

Returns the current run number, corresponding to the number of times the module was powered on with the dataLogger enabled at some point.

```
def get_currentRunIndex( )
```

Returns :

an integer corresponding to the current run number, corresponding to the number of times the module was powered on with the dataLogger enabled at some point

On failure, throws an exception or returns Y_CURRENTRUNINDEX_INVALID.

datalogger→get_dataSets()**YDataLogger****datalogger→dataSets()datalogger.get_dataSets()**

Returns a list of YDataSet objects that can be used to retrieve all measures stored by the data logger.

```
def get_dataSets( )
```

This function only works if the device uses a recent firmware, as YDataSet objects are not supported by firmwares older than version 13000.

Returns :

a list of YDataSet object.

On failure, throws an exception or returns an empty list.

datalogger→get_dataStreams()
datalogger→dataStreams()
datalogger.get_dataStreams()**YDataLogger**

Builds a list of all data streams hold by the data logger (legacy method).

```
def get_dataStreams( v)
```

The caller must pass by reference an empty array to hold YDataStream objects, and the function fills it with objects describing available data sequences.

This is the old way to retrieve data from the DataLogger. For new applications, you should rather use `get_dataSets()` method, or call directly `get_recordedData()` on the sensor object.

Parameters :

v an array of YDataStream objects to be filled in

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

datalogger→get_errorMessage()
datalogger→errorMessage()
datalogger.get_errorMessage()

YDataLogger

Returns the error message of the latest error with the data logger.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the data logger object

datalogger→get_errorType()**YDataLogger****datalogger→errorType()datalogger.get_errorType()**

Returns the numerical error code of the latest error with the data logger.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the data logger object

datalogger→get_friendlyName()
datalogger→friendlyName()
datalogger.get_friendlyName()

YDataLogger

Returns a global identifier of the data logger in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the data logger if they are defined, otherwise the serial number of the module and the hardware identifier of the data logger (for example: MyCustomName . relay1)

Returns :

a string that uniquely identifies the data logger using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

datalogger→get_functionDescriptor()
datalogger→functionDescriptor()
datalogger.get_functionDescriptor()

YDataLogger

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

def get_functionDescriptor()

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

datalogger→get_functionId()

YDataLogger

datalogger→functionId()datalogger.get_functionId()

Returns the hardware identifier of the data logger, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the data logger (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

datalogger→get_hwId()
datalogger→hardwareId()
datalogger.get_hwId()

YDataLogger

Returns the unique hardware identifier of the data logger in the form SERIAL.FUNCTIONID.

def get_hwId()

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the data logger (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the data logger (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

datalogger→get_logicalName()
datalogger→logicalName()
datalogger.get_logicalName()

YDataLogger

Returns the logical name of the data logger.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the data logger.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

datalogger→get_module()**YDataLogger****datalogger→module()datalogger.get_module()**

Gets the YModule object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

datalogger→get_recording()

YDataLogger

datalogger→recording()datalogger.get_recording()

Returns the current activation state of the data logger.

```
def get_recording( )
```

Returns :

either Y_RECORDING_OFF or Y_RECORDING_ON, according to the current activation state of the data logger

On failure, throws an exception or returns Y_RECORDING_INVALID.

datalogger→get_timeUTC()**YDataLogger****datalogger→timeUTC()datalogger.get_timeUTC()**

Returns the Unix timestamp for current UTC time, if known.

```
def get_timeUTC( )
```

Returns :

an integer corresponding to the Unix timestamp for current UTC time, if known

On failure, throws an exception or returns Y_TIMEUTC_INVALID.

datalogger→get(userData)

YDataLogger

datalogger→userData()datalogger.get(userData)

Returns the value of the userData attribute, as previously stored using method set(userData).

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

datalogger→isOnline()datalogger.isOnline()**YDataLogger**

Checks if the data logger is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the data logger in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the data logger.

Returns :

`true` if the data logger can be reached, and `false` otherwise

datalogger→load()datalogger.load()**YDataLogger**

Preloads the data logger cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

datalogger→nextDataLogger()
datalogger.nextDataLogger()**YDataLogger**

Continues the enumeration of data loggers started using `yFirstDataLogger()`.

```
def nextDataLogger( )
```

Returns :

a pointer to a `YDataLogger` object, corresponding to a data logger currently online, or a `null` pointer if there are no more data loggers to enumerate.

**datalogger→registerValueCallback()
datalogger.registerValueCallback()****YDataLogger**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

datalogger→set_autoStart()**YDataLogger****datalogger→setAutoStart()datalogger.set_autoStart()**

Changes the default activation state of the data logger on power up.

```
def set_autoStart( newval)
```

Remember to call the saveToFlash() method of the module if the modification must be kept.

Parameters :

newval either Y_AUTOSTART_OFF or Y_AUTOSTART_ON, according to the default activation state of the data logger on power up

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

datalogger→set_beaconDriven()
datalogger→setBeaconDriven()
datalogger.set_beaconDriven()

YDataLogger

Changes the type of synchronisation of the data logger.

```
def set_beaconDriven( newval )
```

Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval either `Y_BEACONDRIVEN_OFF` or `Y_BEACONDRIVEN_ON`, according to the type of synchronisation of the data logger

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

datalogger→set_logicalName()
datalogger→setLogicalName()
datalogger.set_logicalName()

YDataLogger

Changes the logical name of the data logger.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the logical name of the data logger.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

datalogger→set_recording()
datalogger→setRecording()
datalogger.set_recording()

YDataLogger

Changes the activation state of the data logger to start/stop recording data.

```
def set_recording( newval )
```

Parameters :

newval either Y_RECORDING_OFF or Y_RECORDING_ON, according to the activation state of the data logger to start/stop recording data

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

datalogger→set_timeUTC()**datalogger→setTimeUTC()datalogger.set_timeUTC()****YDataLogger**

Changes the current UTC time reference used for recorded data.

```
def set_timeUTC( newval)
```

Parameters :

newval an integer corresponding to the current UTC time reference used for recorded data

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

datalogger→set(userData)

YDataLogger

datalogger→setUserData()datalogger.set(userData)

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.10. Formatted data sequence

A run is a continuous interval of time during which a module was powered on. A data run provides easy access to all data collected during a given run, providing on-the-fly resampling at the desired reporting rate.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_datalogger.js'></script>
node.js	var yoctolib = require('yoctolib');
	var YDataLogger = yoctolib.YDataLogger;
php	require_once('yocto_datalogger.php');
cpp	#include "yocto_datalogger.h"
m	#import "yocto_datalogger.h"
pas	uses yocto_datalogger;
vb	yocto_datalogger.vb
cs	yocto_datalogger.cs
java	import com.yoctopuce.YoctoAPI.YDataLogger;
py	from yocto_datalogger import *

YDataRun methods

datarun→get_averageValue(measureName, pos)

Returns the average value of the measure observed at the specified time period.

datarun→get_duration()

Returns the duration (in seconds) of the data run.

datarun→get_maxValue(measureName, pos)

Returns the maximal value of the measure observed at the specified time period.

datarun→get_measureNames()

Returns the names of the measures recorded by the data logger.

datarun→get_minValue(measureName, pos)

Returns the minimal value of the measure observed at the specified time period.

datarun→get_startTimeUTC()

Returns the start time of the data run, relative to the Jan 1, 1970.

datarun→get_valueCount()

Returns the number of values accessible in this run, given the selected data samples interval.

datarun→get_valueInterval()

Returns the number of seconds covered by each value in this run.

datarun→set_valueInterval(valueInterval)

Changes the number of seconds covered by each value in this run.

datarun→get_averageValue() YDataRun
datarun→averageValue()datarun.get_averageValue()

Returns the average value of the measure observed at the specified time period.

```
def get_averageValue( measureName, pos)
```

Parameters :

measureName the name of the desired measure (one of the names returned by
get_measureNames)

pos the position index, between 0 and the value returned by get_valueCount

Returns :

a floating point number (the average value)

On failure, throws an exception or returns Y_AVERAGEVALUE_INVALID.

datarun→get_duration()**YDataRun****datarun→duration()datarun.get_duration()**

Returns the duration (in seconds) of the data run.

```
def get_duration( )
```

When the datalogger is actively recording and the specified run is the current run, calling this method reloads last sequence(s) from device to make sure it includes the latest recorded data.

Returns :

an unsigned number corresponding to the number of seconds between the beginning of the run (when the module was powered up) and the last recorded measure.

datarun→get_maxValue()**YDataRun****datarun→maxValue()datarun.get_maxValue()**

Returns the maximal value of the measure observed at the specified time period.

```
def get_maxValue( measureName, pos)
```

Parameters :

measureName the name of the desired measure (one of the names returned by `get_measureNames`)

pos the position index, between 0 and the value returned by `get_valueCount`

Returns :

a floating point number (the maximal value)

On failure, throws an exception or returns `Y_MAXVALUE_INVALID`.

datarun→get_measureNames()
datarun→measureNames()
datarun.get_measureNames()

YDataRun

Returns the names of the measures recorded by the data logger.

def get_measureNames()

In most case, the measure names match the hardware identifier of the sensor that produced the data.

Returns :

a list of strings (the measure names) On failure, throws an exception or returns an empty array.

datarun→get_minValue()**YDataRun****datarun→minValue()datarun.get_minValue()**

Returns the minimal value of the measure observed at the specified time period.

```
def get_minValue( measureName, pos)
```

Parameters :

measureName the name of the desired measure (one of the names returned by `get_measureNames`)

pos the position index, between 0 and the value returned by `get_valueCount`

Returns :

a floating point number (the minimal value)

On failure, throws an exception or returns `Y_MINVALUE_INVALID`.

datarun→getStartTimeUTC()
datarun→startTimeUTC()**YDataRun**

Returns the start time of the data run, relative to the Jan 1, 1970.

If the UTC time was not set in the datalogger at any time during the recording of this data run, and if this is not the current run, this method returns 0.

Returns :

an unsigned number corresponding to the number of seconds between the Jan 1, 1970 and the beginning of this data run (i.e. Unix time representation of the absolute time).

datarun→get_valueCount()

YDataRun

datarun→valueCount()datarun.get_valueCount()

Returns the number of values accessible in this run, given the selected data samples interval.

def get_valueCount()

When the datalogger is actively recording and the specified run is the current run, calling this method reloads last sequence(s) from device to make sure it includes the latest recorded data.

Returns :

an unsigned number corresponding to the run duration divided by the samples interval.

datarun→get_valueInterval()**YDataRun****datarun→valueInterval()datarun.get_valueInterval()**

Returns the number of seconds covered by each value in this run.

```
def get_valueInterval( )
```

By default, the value interval is set to the coarsest data rate archived in the data logger flash for this run. The value interval can however be configured at will to a different rate when desired.

Returns :

an unsigned number corresponding to a number of seconds covered by each data sample in the Run.

`datarun→set_valueInterval()`
`datarun→setValueInterval()`
`datarun.set_valueInterval()`

YDataRun

Changes the number of seconds covered by each value in this run.

def set_valueInterval(valueInterval)

By default, the value interval is set to the coarsest data rate archived in the data logger flash for this run. The value interval can however be configured at will to a different rate when desired.

Parameters :

valueInterval an integer number of seconds.

Returns :

nothing

3.11. Recorded data sequence

YDataSet objects make it possible to retrieve a set of recorded measures for a given sensor and a specified time interval. They can be used to load data points with a progress report. When the YDataSet object is instantiated by the `get_recordedData()` function, no data is yet loaded from the module. It is only when the `loadMore()` method is called over and over than data will be effectively loaded from the dataLogger.

A preview of available measures is available using the function `get_preview()` as soon as `loadMore()` has been called once. Measures themselves are available using function `get_measures()` when loaded by subsequent calls to `loadMore()`.

This class can only be used on devices that use a recent firmware, as YDataSet objects are not supported by firmwares older than version 13000.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_api.js'></script>
nodejs var yoctolib = require('yoctolib');
var YAPI = yoctolib.YAPI;
var YModule = yoctolib.YModule;
php require_once('yocto_api.php');
cpp #include "yocto_api.h"
m #import "yocto_api.h"
pas uses yocto_api;
vb yocto_api.vb
cs yocto_api.cs
java import com.yoctopuce.YoctoAPI.YModule;
py from yocto_api import *

```

YDataSet methods

`dataset→get_endTimeUTC()`

Returns the end time of the dataset, relative to the Jan 1, 1970.

`dataset→get_functionId()`

Returns the hardware identifier of the function that performed the measure, without reference to the module.

`dataset→get_hardwareId()`

Returns the unique hardware identifier of the function who performed the measures, in the form SERIAL.FUNCTIONID.

`dataset→get_measures()`

Returns all measured values currently available for this DataSet, as a list of YMeasure objects.

`dataset→get_preview()`

Returns a condensed version of the measures that can retrieved in this YDataSet, as a list of YMeasure objects.

`dataset→get_progress()`

Returns the progress of the downloads of the measures from the data logger, on a scale from 0 to 100.

`dataset→get_startTimeUTC()`

Returns the start time of the dataset, relative to the Jan 1, 1970.

`dataset→get_summary()`

Returns an YMeasure object which summarizes the whole DataSet.

`dataset→get_unit()`

Returns the measuring unit for the measured value.

3. Reference

dataset→loadMore()

Loads the the next block of measures from the dataLogger, and updates the progress indicator.

dataset→loadMore_async(callback, context)

Loads the the next block of measures from the dataLogger asynchronously.

dataset→get_endTimeUTC()**YDataSet****dataset→endTimeUTC()dataset.get_endTimeUTC()**

Returns the end time of the dataset, relative to the Jan 1, 1970.

```
def get_endTimeUTC( )
```

When the YDataSet is created, the end time is the value passed in parameter to the `get_dataSet()` function. After the very first call to `loadMore()`, the end time is updated to reflect the timestamp of the last measure actually found in the dataLogger within the specified range.

Returns :

an unsigned number corresponding to the number of seconds between the Jan 1, 1970 and the end of this data set (i.e. Unix time representation of the absolute time).

dataset→get_functionId()

YDataSet

dataset→functionId()dataset.get_functionId()

Returns the hardware identifier of the function that performed the measure, without reference to the module.

```
def get_functionId( )
```

For example `temperature1`.

Returns :

a string that identifies the function (ex: `temperature1`)

dataset→get_hardwareId()**YDataSet****dataset→hardwareId()dataset.get_hardwareId()**

Returns the unique hardware identifier of the function who performed the measures, in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the function (for example THRMCPL1-123456.temperature1)

Returns :

a string that uniquely identifies the function (ex: THRMCPL1-123456.temperature1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

dataset→get_measures() **YDataSet**
dataset→measures()dataset.get_measures()

Returns all measured values currently available for this DataSet, as a list of YMeasure objects.

```
def get_measures( )
```

Each item includes: - the start of the measure time interval - the end of the measure time interval - the minimal value observed during the time interval - the average value observed during the time interval - the maximal value observed during the time interval

Before calling this method, you should call `loadMore()` to load data from the device. You may have to call `loadMore()` several time until all rows are loaded, but you can start looking at available data rows before the load is complete.

The oldest measures are always loaded first, and the most recent measures will be loaded last. As a result, timestamps are normally sorted in ascending order within the measure table, unless there was an unexpected adjustment of the datalogger UTC clock.

Returns :

a table of records, where each record depicts the measured value for a given time interval

On failure, throws an exception or returns an empty array.

dataset→get_preview()**YDataSet****dataset→preview()dataset.get_preview()**

Returns a condensed version of the measures that can retrieved in this YDataSet, as a list of YMeasure objects.

```
def get_preview( )
```

Each item includes: - the start of a time interval - the end of a time interval - the minimal value observed during the time interval - the average value observed during the time interval - the maximal value observed during the time interval

This preview is available as soon as `loadMore()` has been called for the first time.

Returns :

a table of records, where each record depicts the measured values during a time interval

On failure, throws an exception or returns an empty array.

dataset→get_progress()

YDataSet

dataset→progress()dataset.get_progress()

Returns the progress of the downloads of the measures from the data logger, on a scale from 0 to 100.

```
def get_progress( )
```

When the object is instantiated by `get_dataSet`, the progress is zero. Each time `loadMore()` is invoked, the progress is updated, to reach the value 100 only once all measures have been loaded.

Returns :

an integer in the range 0 to 100 (percentage of completion).

dataset→getStartTimeUTC()**YDataSet****dataset→startTimeUTC()dataset.getStartTimeUTC()**

Returns the start time of the dataset, relative to the Jan 1, 1970.

```
def getStartTimeUTC( )
```

When the YDataSet is created, the start time is the value passed in parameter to the `get_dataSet()` function. After the very first call to `loadMore()`, the start time is updated to reflect the timestamp of the first measure actually found in the dataLogger within the specified range.

Returns :

an unsigned number corresponding to the number of seconds between the Jan 1, 1970 and the beginning of this data set (i.e. Unix time representation of the absolute time).

dataset→get_summary()**YDataSet****dataset→summary()dataset.get_summary()**

Returns an YMeasure object which summarizes the whole DataSet.

```
def get_summary( )
```

In includes the following information: - the start of a time interval - the end of a time interval - the minimal value observed during the time interval - the average value observed during the time interval - the maximal value observed during the time interval

This summary is available as soon as `loadMore()` has been called for the first time.

Returns :

an YMeasure object

dataset→get_unit()**YDataSet****dataset→unit()dataset.get_unit()**

Returns the measuring unit for the measured value.

```
def get_unit( )
```

Returns :

a string that represents a physical unit.

On failure, throws an exception or returns Y_UNIT_INVALID.

dataset→loadMore()dataset.loadMore()

YDataSet

Loads the the next block of measures from the dataLogger, and updates the progress indicator.

```
def loadMore( )
```

Returns :

an integer in the range 0 to 100 (percentage of completion), or a negative error code in case of failure.

On failure, throws an exception or returns a negative error code.

3.12. Unformatted data sequence

YDataStream objects represent bare recorded measure sequences, exactly as found within the data logger present on Yoctopuce sensors.

In most cases, it is not necessary to use YDataStream objects directly, as the YDataSet objects (returned by the `get_recordedData()` method from sensors and the `get_dataSets()` method from the data logger) provide a more convenient interface.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_api.js'></script>
nodejs var yoctolib = require('yoctolib');
var YAPI = yoctolib.YAPI;
var YModule = yoctolib.YModule;
php require_once('yocto_api.php');
cpp #include "yocto_api.h"
m #import "yocto_api.h"
pas uses yocto_api;
vb yocto_api.vb
cs yocto_api.cs
java import com.yoctopuce.YoctoAPI.YModule;
py from yocto_api import *

```

YDataStream methods

`datastream→get_averageValue()`

Returns the average of all measures observed within this stream.

`datastream→get_columnCount()`

Returns the number of data columns present in this stream.

`datastream→get_columnNames()`

Returns the title (or meaning) of each data column present in this stream.

`datastream→get_data(row, col)`

Returns a single measure from the data stream, specified by its row and column index.

`datastream→get_dataRows()`

Returns the whole data set contained in the stream, as a bidimensional table of numbers.

`datastream→get_dataSamplesIntervalMs()`

Returns the number of milliseconds between two consecutive rows of this data stream.

`datastream→get_duration()`

Returns the approximate duration of this stream, in seconds.

`datastream→get_maxValue()`

Returns the largest measure observed within this stream.

`datastream→get_minValue()`

Returns the smallest measure observed within this stream.

`datastream→getRowCount()`

Returns the number of data rows present in this stream.

`datastream→get_runIndex()`

Returns the run index of the data stream.

`datastream→get_startTime()`

Returns the relative start time of the data stream, measured in seconds.

`datastream→get_startTimeUTC()`

3. Reference

Returns the start time of the data stream, relative to the Jan 1, 1970.

datastream→get_averageValue()
datastream→averageValue()
datastream.get_averageValue()

YDataStream

Returns the average of all measures observed within this stream.

```
def get_averageValue( )
```

If the device uses a firmware older than version 13000, this method will always return Y_DATA_INVALID.

Returns :

a floating-point number corresponding to the average value, or Y_DATA_INVALID if the stream is not yet complete (still recording).

On failure, throws an exception or returns Y_DATA_INVALID.

datastream→get_columnCount()
datastream→columnCount()
datastream.get_columnCount()

YDataStream

Returns the number of data columns present in this stream.

```
def get_columnCount( )
```

The meaning of the values present in each column can be obtained using the method `get_columnNames()`.

If the device uses a firmware older than version 13000, this method fetches the whole data stream from the device if not yet done, which can cause a little delay.

Returns :

an unsigned number corresponding to the number of columns.

On failure, throws an exception or returns zero.

datastream→get_columnNames()
datastream→columnNames()
datastream.get_columnNames()

YDataStream

Returns the title (or meaning) of each data column present in this stream.

```
def get_columnNames( )
```

In most case, the title of the data column is the hardware identifier of the sensor that produced the data. For streams recorded at a lower recording rate, the dataLogger stores the min, average and max value during each measure interval into three columns with suffixes _min, _avg and _max respectively.

If the device uses a firmware older than version 13000, this method fetches the whole data stream from the device if not yet done, which can cause a little delay.

Returns :

a list containing as many strings as there are columns in the data stream.

On failure, throws an exception or returns an empty array.

datastream→get_data()
datastream→data()datastream.get_data()**YDataStream**

Returns a single measure from the data stream, specified by its row and column index.

```
def get_data( row, col)
```

The meaning of the values present in each column can be obtained using the method `get_columnNames()`.

This method fetches the whole data stream from the device, if not yet done.

Parameters :

row row index

col column index

Returns :

a floating-point number

On failure, throws an exception or returns Y_DATA_INVALID.

datastream→get_dataRows()**YDataStream****datastream→dataRows()datastream.get_dataRows()**

Returns the whole data set contained in the stream, as a bidimensional table of numbers.

```
def get_dataRows( )
```

The meaning of the values present in each column can be obtained using the method `get_columnNames()`.

This method fetches the whole data stream from the device, if not yet done.

Returns :

a list containing as many elements as there are rows in the data stream. Each row itself is a list of floating-point numbers.

On failure, throws an exception or returns an empty array.

datastream→get_dataSamplesIntervalMs()
datastream→dataSamplesIntervalMs()
datastream.get_dataSamplesIntervalMs()

YDataStream

Returns the number of milliseconds between two consecutive rows of this data stream.

```
def get_dataSamplesIntervalMs( )
```

By default, the data logger records one row per second, but the recording frequency can be changed for each device function

Returns :

an unsigned number corresponding to a number of milliseconds.

datastream→get_duration()**YDataStream****datastream→duration()datastream.get_duration()**

Returns the approximate duration of this stream, in seconds.

```
def get_duration( )
```

Returns :

the number of seconds covered by this stream.

On failure, throws an exception or returns Y_DURATION_INVALID.

datastream→get_maxValue() **YDataStream**
datastream→maxValue()datastream.get_maxValue()

Returns the largest measure observed within this stream.

```
def get_maxValue( )
```

If the device uses a firmware older than version 13000, this method will always return Y_DATA_INVALID.

Returns :

a floating-point number corresponding to the largest value, or Y_DATA_INVALID if the stream is not yet complete (still recording).

On failure, throws an exception or returns Y_DATA_INVALID.

datastream→get_minValue()**YDataStream****datastream→minValue()datastream.get_minValue()**

Returns the smallest measure observed within this stream.

```
def get_minValue( )
```

If the device uses a firmware older than version 13000, this method will always return Y_DATA_INVALID.

Returns :

a floating-point number corresponding to the smallest value, or Y_DATA_INVALID if the stream is not yet complete (still recording).

On failure, throws an exception or returns Y_DATA_INVALID.

datastream→getRowCount() **YDataStream**
datastream→rowCount()datastream.getRowCount()

Returns the number of data rows present in this stream.

```
def getRowCount( )
```

If the device uses a firmware older than version 13000, this method fetches the whole data stream from the device if not yet done, which can cause a little delay.

Returns :

an unsigned number corresponding to the number of rows.

On failure, throws an exception or returns zero.

datastream→get_runIndex()**YDataStream****datastream→runIndex()datastream.get_runIndex()**

Returns the run index of the data stream.

```
def get_runIndex( )
```

A run can be made of multiple datastreams, for different time intervals.

Returns :

an unsigned number corresponding to the run index.

datastream→getStartTime() YDataStream
datastream→startTime()datastream.getStartTime()

Returns the relative start time of the data stream, measured in seconds.

```
def getStartTime( )
```

For recent firmwares, the value is relative to the present time, which means the value is always negative. If the device uses a firmware older than version 13000, value is relative to the start of the time the device was powered on, and is always positive. If you need an absolute UTC timestamp, use `getStartTimeUTC()`.

Returns :

an unsigned number corresponding to the number of seconds between the start of the run and the beginning of this data stream.

datastream→getStartTimeUTC()
datastream→startTimeUTC()
datastream.getStartTimeUTC()

YDataStream

Returns the start time of the data stream, relative to the Jan 1, 1970.

```
def getStartTimeUTC( )
```

If the UTC time was not set in the datalogger at the time of the recording of this data stream, this method returns 0.

Returns :

an unsigned number corresponding to the number of seconds between the Jan 1, 1970 and the beginning of this data stream (i.e. Unix time representation of the absolute time).

3.13. Digital IO function interface

The Yoctopuce application programming interface allows you to switch the state of each bit of the I/O port. You can switch all bits at once, or one by one. The library can also automatically generate short pulses of a determined duration. Electrical behavior of each I/O can be modified (open drain and reverse polarity).

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_digitalio.js'></script>
nodejs var yoctolib = require('yoctolib');
var YDigitalIO = yoctolib.YDigitalIO;
php require_once('yocto_digitalio.php');
cpp #include "yocto_digitalio.h"
m #import "yocto_digitalio.h"
pas uses yocto_digitalio;
vb yocto_digitalio.vb
cs yocto_digitalio.cs
java import com.yoctopuce.YoctoAPI.YDigitalIO;
py from yocto_digitalio import *

```

Global functions

yFindDigitalIO(func)

Retrieves a digital IO port for a given identifier.

yFirstDigitalIO()

Starts the enumeration of digital IO ports currently accessible.

YDigitalIO methods

digitalio->delayedPulse(bitno, ms_delay, ms_duration)

Schedules a pulse on a single bit for a specified duration.

digitalio->describe()

Returns a short text that describes unambiguously the instance of the digital IO port in the form TYPE(NAME)=SERIAL.FUNCTIONID.

digitalio->get_advertisedValue()

Returns the current value of the digital IO port (no more than 6 characters).

digitalio->get_bitDirection(bitno)

Returns the direction of a single bit from the I/O port (0 means the bit is an input, 1 an output).

digitalio->get_bitOpenDrain(bitno)

Returns the type of electrical interface of a single bit from the I/O port.

digitalio->get_bitPolarity(bitno)

Returns the polarity of a single bit from the I/O port (0 means the I/O works in regular mode, 1 means the I/O works in reverse mode).

digitalio->get_bitState(bitno)

Returns the state of a single bit of the I/O port.

digitalio->get_errorMessage()

Returns the error message of the latest error with the digital IO port.

digitalio->get_errorType()

Returns the numerical error code of the latest error with the digital IO port.

digitalio->get_friendlyName()

Returns a global identifier of the digital IO port in the format MODULE_NAME . FUNCTION_NAME.

digitalio→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

digitalio→get_functionId()

Returns the hardware identifier of the digital IO port, without reference to the module.

digitalio→get_hardwareId()

Returns the unique hardware identifier of the digital IO port in the form SERIAL.FUNCTIONID.

digitalio→get_logicalName()

Returns the logical name of the digital IO port.

digitalio→get_module()

Gets the YModule object for the device on which the function is located.

digitalio→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

digitalio→get_outputVoltage()

Returns the voltage source used to drive output bits.

digitalio→get_portDirection()

Returns the IO direction of all bits of the port: 0 makes a bit an input, 1 makes it an output.

digitalio→get_portOpenDrain()

Returns the electrical interface for each bit of the port.

digitalio→get_portPolarity()

Returns the polarity of all the bits of the port.

digitalio→get_portSize()

Returns the number of bits implemented in the I/O port.

digitalio→get_portState()

Returns the digital IO port state: bit 0 represents input 0, and so on.

digitalio→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

digitalio→isOnline()

Checks if the digital IO port is currently reachable, without raising any error.

digitalio→isOnline_async(callback, context)

Checks if the digital IO port is currently reachable, without raising any error (asynchronous version).

digitalio→load(msValidity)

Preloads the digital IO port cache with a specified validity duration.

digitalio→load_async(msValidity, callback, context)

Preloads the digital IO port cache with a specified validity duration (asynchronous version).

digitalio→nextDigitalIO()

Continues the enumeration of digital IO ports started using yFirstDigitalIO().

digitalio→pulse(bitno, ms_duration)

Triggers a pulse on a single bit for a specified duration.

digitalio→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

digitalio→set_bitDirection(bitno, bitdirection)

Changes the direction of a single bit from the I/O port.

digitalio→set_bitOpenDrain(bitno, opendrain)

Changes the electrical interface of a single bit from the I/O port.

digitalio→set_bitPolarity(bitno, bitpolarity)

Changes the polarity of a single bit from the I/O port.

digitalio→set_bitState(bitno, bitstate)

Sets a single bit of the I/O port.

digitalio→set_logicalName(newval)

Changes the logical name of the digital IO port.

digitalio→set_outputVoltage(newval)

Changes the voltage source used to drive output bits.

digitalio→set_portDirection(newval)

Changes the IO direction of all bits of the port: 0 makes a bit an input, 1 makes it an output.

digitalio→set_portOpenDrain(newval)

Changes the electrical interface for each bit of the port.

digitalio→set_portPolarity(newval)

Changes the polarity of all the bits of the port: 0 makes a bit an input, 1 makes it an output.

digitalio→set_portState(newval)

Changes the digital IO port state: bit 0 represents input 0, and so on.

digitalio→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

digitalio→toggle_bitState(bitno)

Reverts a single bit of the I/O port.

digitalio→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YDigitalIO.FindDigitalIO()**yFindDigitalIO()YDigitalIO.FindDigitalIO()****YDigitalIO**

Retrieves a digital IO port for a given identifier.

```
def FindDigitalIO( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the digital IO port is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YDigitalIO.isOnline()` to test if the digital IO port is indeed online at a given time. In case of ambiguity when looking for a digital IO port by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the digital IO port

Returns :

a `YDigitalIO` object allowing you to drive the digital IO port.

YDigitalIO.FirstDigitalIO()

YDigitalIO

yFirstDigitalIO()YDigitalIO.FirstDigitalIO()

Starts the enumeration of digital IO ports currently accessible.

```
def FirstDigitalIO( )
```

Use the method `YDigitalIO.nextDigitalIO()` to iterate on next digital IO ports.

Returns :

a pointer to a `YDigitalIO` object, corresponding to the first digital IO port currently online, or a null pointer if there are none.

digitalio→delayedPulse()digitalio.delayedPulse()******YDigitalIO**

Schedules a pulse on a single bit for a specified duration.

```
def delayedPulse( bitno, ms_delay, ms_duration)
```

The specified bit will be turned to 1, and then back to 0 after the given duration.

Parameters :

bitno the bit number; lowest bit has index 0

ms_delay waiting time before the pulse, in milliseconds

ms_duration desired pulse duration in milliseconds. Be aware that the device time resolution is not guaranteed up to the millisecond.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→describe()digitalio.describe()**YDigitalIO**

Returns a short text that describes unambiguously the instance of the digital IO port in the form
TYPE (NAME)=SERIAL . FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the digital IO port (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

digitalio→get_advertisedValue()
digitalio→advertisedValue()
digitalio.get_advertisedValue()

YDigitalIO

Returns the current value of the digital IO port (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the digital IO port (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

digitalio→get_bitDirection()

YDigitalIO

digitalio→bitDirection()digitalio.get_bitDirection()

Returns the direction of a single bit from the I/O port (0 means the bit is an input, 1 an output).

```
def get_bitDirection( bitno )
```

Parameters :

bitno the bit number; lowest bit has index 0

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→get_bitOpenDrain()**YDigitalIO****digitalio→bitOpenDrain()digitalio.get_bitOpenDrain()**

Returns the type of electrical interface of a single bit from the I/O port.

```
def get_bitOpenDrain( bitno )
```

(0 means the bit is an input, 1 an output).

Parameters :

bitno the bit number; lowest bit has index 0

Returns :

0 means the a bit is a regular input/output, 1 means the bit is an open-drain (open-collector) input/output.

On failure, throws an exception or returns a negative error code.

digitalio→get_bitPolarity()**YDigitalIO****digitalio→bitPolarity()digitalio.get_bitPolarity()**

Returns the polarity of a single bit from the I/O port (0 means the I/O works in regular mode, 1 means the I/O works in reverse mode).

```
def get_bitPolarity( bitno)
```

Parameters :

bitno the bit number; lowest bit has index 0

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→get_bitState()**YDigitalIO****digitalio→bitState()digitalio.get_bitState()**

Returns the state of a single bit of the I/O port.

```
def get_bitState( bitno )
```

Parameters :

bitno the bit number; lowest bit has index 0

Returns :

the bit state (0 or 1)

On failure, throws an exception or returns a negative error code.

digitalio→get_errorMessage()
digitalio→errorMessage()
digitalio.get_errorMessage()

YDigitalIO

Returns the error message of the latest error with the digital IO port.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the digital IO port object

digitalio→get_errorType()**YDigitalIO****digitalio→errorType()digitalio.get_errorType()**

Returns the numerical error code of the latest error with the digital IO port.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the digital IO port object

digitalio→get_friendlyName() **YDigitalIO**
digitalio→friendlyName()digitalio.get_friendlyName()

Returns a global identifier of the digital IO port in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the digital IO port if they are defined, otherwise the serial number of the module and the hardware identifier of the digital IO port (for example: MyCustomName . relay1)

Returns :

a string that uniquely identifies the digital IO port using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

digitalio→get_functionDescriptor()
digitalio→functionDescriptor()
digitalio.get_functionDescriptor()

YDigitalIO

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

digitalio→get_functionId()

YDigitalIO

digitalio→functionId()digitalio.get_functionId()

Returns the hardware identifier of the digital IO port, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the digital IO port (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

digitalio→get_hardwareId()**YDigitalIO****digitalio→hardwareId()digitalio.get_hardwareId()**

Returns the unique hardware identifier of the digital IO port in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the digital IO port (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the digital IO port (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

digitalio→get_logicalName()

YDigitalIO

digitalio→logicalName()digitalio.get_logicalName()

Returns the logical name of the digital IO port.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the digital IO port.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

digitalio→get_module()**YDigitalIO****digitalio→module()digitalio.get_module()**

Gets the YModule object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

digitalio→get_outputVoltage()
digitalio→outputVoltage()
digitalio.get_outputVoltage()

YDigitalIO

Returns the voltage source used to drive output bits.

```
def get_outputVoltage( )
```

Returns :

a value among Y_OUTPUTVOLTAGE_USB_5V, Y_OUTPUTVOLTAGE_USB_3V and Y_OUTPUTVOLTAGE_EXT_V corresponding to the voltage source used to drive output bits

On failure, throws an exception or returns Y_OUTPUTVOLTAGE_INVALID.

digitalio→get_portDirection()**YDigitalIO****digitalio→portDirection()digitalio.get_portDirection()**

Returns the IO direction of all bits of the port: 0 makes a bit an input, 1 makes it an output.

```
def get_portDirection( )
```

Returns :

an integer corresponding to the IO direction of all bits of the port: 0 makes a bit an input, 1 makes it an output

On failure, throws an exception or returns Y_PORTDIRECTION_INVALID.

`digitalio→get_portOpenDrain()`
`digitalio→portOpenDrain()`
`digitalio.get_portOpenDrain()`

YDigitalIO

Returns the electrical interface for each bit of the port.

```
def get_portOpenDrain( )
```

For each bit set to 0 the matching I/O works in the regular, intuitive way, for each bit set to 1, the I/O works in reverse mode.

Returns :

an integer corresponding to the electrical interface for each bit of the port

On failure, throws an exception or returns Y_PORTOPENDRAIN_INVALID.

digitalio→get_portPolarity()**YDigitalIO****digitalio→portPolarity()digitalio.get_portPolarity()**

Returns the polarity of all the bits of the port.

```
def get_portPolarity( )
```

For each bit set to 0, the matching I/O works the regular, intuitive way; for each bit set to 1, the I/O works in reverse mode.

Returns :

an integer corresponding to the polarity of all the bits of the port

On failure, throws an exception or returns Y_PORTPOLARITY_INVALID.

digitalio→get_portSize()

YDigitalIO

digitalio→portSize()digitalio.get_portSize()

Returns the number of bits implemented in the I/O port.

```
def get_portSize( )
```

Returns :

an integer corresponding to the number of bits implemented in the I/O port

On failure, throws an exception or returns Y_PORTSIZE_INVALID.

digitalio→get_portState()**YDigitalIO****digitalio→portState()digitalio.get_portState()**

Returns the digital IO port state: bit 0 represents input 0, and so on.

```
def get_portState( )
```

Returns :

an integer corresponding to the digital IO port state: bit 0 represents input 0, and so on

On failure, throws an exception or returns Y_PORTSTATE_INVALID.

digitalio→get(userData)

YDigitalIO

digitalio→userData()digitalio.get(userData)

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

digitalio→isOnline()digitalio.isOnline()**YDigitalIO**

Checks if the digital IO port is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the digital IO port in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the digital IO port.

Returns :

`true` if the digital IO port can be reached, and `false` otherwise

digitalio→load()|digitalio.load()**YDigitalIO**

Preloads the digital IO port cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→nextDigitalIO() digitalio.nextDigitalIO()**YDigitalIO**

Continues the enumeration of digital IO ports started using `yFirstDigitalIO()`.

```
def nextDigitalIO( )
```

Returns :

a pointer to a `YDigitalIO` object, corresponding to a digital IO port currently online, or a null pointer if there are no more digital IO ports to enumerate.

digitalio→pulse()digitalio.pulse()****

YDigitalIO

Triggers a pulse on a single bit for a specified duration.

```
def pulse( bitno, ms_duration )
```

The specified bit will be turned to 1, and then back to 0 after the given duration.

Parameters :

bitno the bit number; lowest bit has index 0

ms_duration desired pulse duration in milliseconds. Be aware that the device time resolution is not guaranteed up to the millisecond.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→registerValueCallback()
digitalio.registerValueCallback()**YDigitalIO**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

digitalio→set_bitDirection() YDigitalIO
digitalio→setBitDirection()digitalio.set_bitDirection()

Changes the direction of a single bit from the I/O port.

```
def set_bitDirection( bitno, bitdirection)
```

Parameters :

bitno the bit number; lowest bit has index 0

bitdirection direction to set, 0 makes the bit an input, 1 makes it an output. Remember to call the `saveToFlash()` method to make sure the setting is kept after a reboot.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→set_bitOpenDrain()
digitalio→setBitOpenDrain()
digitalio.set_bitOpenDrain()

YDigitalIO

Changes the electrical interface of a single bit from the I/O port.

```
def set_bitOpenDrain( bitno, opendrain)
```

Parameters :

bitno the bit number; lowest bit has index 0

opendrain 0 makes a bit a regular input/output, 1 makes it an open-drain (open-collector) input/output. Remember to call the `saveToFlash()` method to make sure the setting is kept after a reboot.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→set_bitPolarity()**YDigitalIO****digitalio→setBitPolarity()digitalio.set_bitPolarity()**

Changes the polarity of a single bit from the I/O port.

```
def set_bitPolarity( bitno, bitpolarity)
```

Parameters :

bitno the bit number; lowest bit has index 0.

bitpolarity polarity to set, 0 makes the I/O work in regular mode, 1 makes the I/O works in reverse mode.

Remember to call the `saveToFlash()` method to make sure the setting is kept after a reboot.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→set_bitState()**YDigitalIO****digitalio→setBitState()digitalio.set_bitState()**

Sets a single bit of the I/O port.

```
def set_bitState( bitno, bitstate)
```

Parameters :

bitno the bit number; lowest bit has index 0

bitstate the state of the bit (1 or 0)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→set_logicalName()
digitalio→setLogicalName()
digitalio.set_logicalName()

YDigitalIO

Changes the logical name of the digital IO port.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the digital IO port.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

**digitalio→set_outputVoltage()
digitalio→setOutputVoltage()
digitalio.set_outputVoltage()****YDigitalIO**

Changes the voltage source used to drive output bits.

```
def set_outputVoltage( newval)
```

Remember to call the `saveToFlash()` method to make sure the setting is kept after a reboot.

Parameters :

newval a value among `Y_OUTPUTVOLTAGE_USB_5V`, `Y_OUTPUTVOLTAGE_USB_3V` and `Y_OUTPUTVOLTAGE_EXT_V` corresponding to the voltage source used to drive output bits

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

**digitalio→set_portDirection()
digitalio→setPortDirection()
digitalio.set_portDirection()****YDigitalIO**

Changes the IO direction of all bits of the port: 0 makes a bit an input, 1 makes it an output.

```
def set_portDirection( newval)
```

Remember to call the `saveToFlash()` method to make sure the setting is kept after a reboot.

Parameters :

newval an integer corresponding to the IO direction of all bits of the port: 0 makes a bit an input, 1 makes it an output

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→set_portOpenDrain()
digitalio→setPortOpenDrain()
digitalio.set_portOpenDrain()

YDigitalIO

Changes the electrical interface for each bit of the port.

```
def set_portOpenDrain( newval)
```

0 makes a bit a regular input/output, 1 makes it an open-drain (open-collector) input/output. Remember to call the `saveToFlash()` method to make sure the setting is kept after a reboot.

Parameters :

newval an integer corresponding to the electrical interface for each bit of the port

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→set_portPolarity() digitalio→setPortPolarity()digitalio.set_portPolarity()

YDigitalIO

Changes the polarity of all the bits of the port: 0 makes a bit an input, 1 makes it an output.

```
def set_portPolarity( newval)
```

Remember to call the `saveToFlash()` method to make sure the setting will be kept after a reboot.

Parameters :

newval an integer corresponding to the polarity of all the bits of the port: 0 makes a bit an input, 1 makes it an output

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→set_portState()**YDigitalIO****digitalio→setPortState()digitalio.set_portState()**

Changes the digital IO port state: bit 0 represents input 0, and so on.

```
def set_portState( newval)
```

This function has no effect on bits configured as input in portDirection.

Parameters :

newval an integer corresponding to the digital IO port state: bit 0 represents input 0, and so on

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

digitalio→set(userData)

YDigitalIO

digitalio→setUserData()|digitalio.set(userData)

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData):
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

digitalio→toggle_bitState()digitalio.toggle_bitState()**YDigitalIO**

Reverts a single bit of the I/O port.

```
def toggle_bitState( bitno)
```

Parameters :

bitno the bit number; lowest bit has index 0

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

3.14. Display function interface

Yoctopuce display interface has been designed to easily show information and images. The device provides built-in multi-layer rendering. Layers can be drawn offline, individually, and freely moved on the display. It can also replay recorded sequences (animations).

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_display.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YDisplay = yoctolib.YDisplay;
php	require_once('yocto_display.php');
cpp	#include "yocto_display.h"
m	#import "yocto_display.h"
pas	uses yocto_display;
vb	yocto_display.vb
cs	yocto_display.cs
java	import com.yoctopuce.YoctoAPI.YDisplay;
py	from yocto_display import *

Global functions

yFindDisplay(func)

Retrieves a display for a given identifier.

yFirstDisplay()

Starts the enumeration of displays currently accessible.

YDisplay methods

display→copyLayerContent(srcLayerId, dstLayerId)

Copies the whole content of a layer to another layer.

display→describe()

Returns a short text that describes unambiguously the instance of the display in the form TYPE (NAME)=SERIAL.FUNCTIONID.

display→fade(brightness, duration)

Smoothly changes the brightness of the screen to produce a fade-in or fade-out effect.

display→get_advertisedValue()

Returns the current value of the display (no more than 6 characters).

display→get_brightness()

Returns the luminosity of the module informative leds (from 0 to 100).

display→get_displayHeight()

Returns the display height, in pixels.

display→get_displayLayer(layerId)

Returns a YDisplayLayer object that can be used to draw on the specified layer.

display→get_displayType()

Returns the display type: monochrome, gray levels or full color.

display→get_displayWidth()

Returns the display width, in pixels.

display→get_enabled()

Returns true if the screen is powered, false otherwise.

display→get_errorMessage()

Returns the error message of the latest error with the display.

display→get_errorType()

Returns the numerical error code of the latest error with the display.

display→get_friendlyName()

Returns a global identifier of the display in the format MODULE_NAME . FUNCTION_NAME.

display→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

display→get_functionId()

Returns the hardware identifier of the display, without reference to the module.

display→get_hardwareId()

Returns the unique hardware identifier of the display in the form SERIAL . FUNCTIONID.

display→get_layerCount()

Returns the number of available layers to draw on.

display→get_layerHeight()

Returns the height of the layers to draw on, in pixels.

display→get_layerWidth()

Returns the width of the layers to draw on, in pixels.

display→get_logicalName()

Returns the logical name of the display.

display→get_module()

Gets the YModule object for the device on which the function is located.

display→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

display→get_orientation()

Returns the currently selected display orientation.

display→get_startupSeq()

Returns the name of the sequence to play when the displayed is powered on.

display→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

display→isOnline()

Checks if the display is currently reachable, without raising any error.

display→isOnline_async(callback, context)

Checks if the display is currently reachable, without raising any error (asynchronous version).

display→load(msValidity)

Preloads the display cache with a specified validity duration.

display→load_async(msValidity, callback, context)

Preloads the display cache with a specified validity duration (asynchronous version).

display→newSequence()

Starts to record all display commands into a sequence, for later replay.

display→nextDisplay()

Continues the enumeration of displays started using yFirstDisplay().

display→pauseSequence(delay_ms)

Waits for a specified delay (in milliseconds) before playing next commands in current sequence.

display→playSequence(sequenceName)

Replays a display sequence previously recorded using newSequence() and saveSequence().

display→registerValueCallback(callback)

3. Reference

Registers the callback function that is invoked on every change of advertised value.

display→resetAll()

Clears the display screen and resets all display layers to their default state.

display→saveSequence(sequenceName)

Stops recording display commands and saves the sequence into the specified file on the display internal memory.

display→set_brightness(newval)

Changes the brightness of the display.

display→set_enabled(newval)

Changes the power state of the display.

display→set_logicalName(newval)

Changes the logical name of the display.

display→set_orientation(newval)

Changes the display orientation.

display→set_startupSeq(newval)

Changes the name of the sequence to play when the displayed is powered on.

display→set(userData)

Stores a user context provided as argument in the userData attribute of the function.

display→stopSequence()

Stops immediately any ongoing sequence replay.

display→swapLayerContent(layerIdA, layerIdB)

Swaps the whole content of two layers.

display→upload(pathname, content)

Uploads an arbitrary file (for instance a GIF file) to the display, to the specified full path name.

display→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YDisplay.FindDisplay() yFindDisplay()YDisplay.FindDisplay()

YDisplay

Retrieves a display for a given identifier.

```
def FindDisplay( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the display is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YDisplay.isOnline()` to test if the display is indeed online at a given time. In case of ambiguity when looking for a display by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the display

Returns :

a `YDisplay` object allowing you to drive the display.

YDisplay.FirstDisplay()

YDisplay

yFirstDisplay()YDisplay.FirstDisplay()

Starts the enumeration of displays currently accessible.

```
def FirstDisplay( )
```

Use the method `YDisplay.nextDisplay()` to iterate on next displays.

Returns :

a pointer to a `YDisplay` object, corresponding to the first display currently online, or a `null` pointer if there are none.

**display→copyLayerContent()
display.copyLayerContent()****YDisplay**

Copies the whole content of a layer to another layer.

```
def copyLayerContent( srcLayerId, dstLayerId)
```

The color and transparency of all the pixels from the destination layer are set to match the source pixels. This method only affects the displayed content, but does not change any property of the layer object. Note that layer 0 has no transparency support (it is always completely opaque).

Parameters :

srcLayerId the identifier of the source layer (a number in range 0..layerCount-1)

dstLayerId the identifier of the destination layer (a number in range 0..layerCount-1)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→describe()display.describe()**YDisplay**

Returns a short text that describes unambiguously the instance of the display in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the display (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

display→fade()display.fade()**YDisplay**

Smoothly changes the brightness of the screen to produce a fade-in or fade-out effect.

```
def fade( brightness, duration)
```

Parameters :

brightness the new screen brightness

duration duration of the brightness transition, in milliseconds.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→get_advertisedValue()
display→advertisedValue()
display.get_advertisedValue()

YDisplay

Returns the current value of the display (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the display (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

display→get_brightness()**YDisplay****display→brightness()display.get_brightness()**

Returns the luminosity of the module informative leds (from 0 to 100).

```
def get_brightness( )
```

Returns :

an integer corresponding to the luminosity of the module informative leds (from 0 to 100)

On failure, throws an exception or returns Y_BRIGHTNESS_INVALID.

display→get_displayHeight()

YDisplay

display→displayHeight()display.get_displayHeight()

Returns the display height, in pixels.

```
def get_displayHeight( )
```

Returns :

an integer corresponding to the display height, in pixels

On failure, throws an exception or returns Y_DISPLAYHEIGHT_INVALID.

display→get_displayLayer() **YDisplay**
display→displayLayer()display.get_displayLayer()

Returns a YDisplayLayer object that can be used to draw on the specified layer.

```
def get_displayLayer( layerId)
```

The content is displayed only when the layer is active on the screen (and not masked by other overlapping layers).

Parameters :

layerId the identifier of the layer (a number in range 0..layerCount-1)

Returns :

an YDisplayLayer object

On failure, throws an exception or returns null.

display→get_displayType()

YDisplay

display→displayType()display.get_displayType()

Returns the display type: monochrome, gray levels or full color.

```
def get_displayType( )
```

Returns :

a value among Y_DISPLAYTYPE_MONO, Y_DISPLAYTYPE_GRAY and Y_DISPLAYTYPE_RGB corresponding to the display type: monochrome, gray levels or full color

On failure, throws an exception or returns Y_DISPLAYTYPE_INVALID.

display→get_displayWidth()**YDisplay****display→displayWidth()display.get_displayWidth()**

Returns the display width, in pixels.

```
def get_displayWidth( )
```

Returns :

an integer corresponding to the display width, in pixels

On failure, throws an exception or returns Y_DISPLAYWIDTH_INVALID.

display→get_enabled() YDisplay
display→enabled()display.get_enabled()

Returns true if the screen is powered, false otherwise.

```
def get_enabled( )
```

Returns :

either Y_ENABLED_FALSE or Y_ENABLED_TRUE, according to true if the screen is powered, false otherwise

On failure, throws an exception or returns Y_ENABLED_INVALID.

display→get_errorMessage()**YDisplay****display→errorMessage()display.getErrorMessage()**

Returns the error message of the latest error with the display.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the display object

display→get_errorType()

YDisplay

display→errorType()display.get_errorType()

Returns the numerical error code of the latest error with the display.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the display object

display→get_friendlyName()**YDisplay****display→friendlyName()display.get_friendlyName()**

Returns a global identifier of the display in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the display if they are defined, otherwise the serial number of the module and the hardware identifier of the display (for example: MyCustomName . relay1)

Returns :

a string that uniquely identifies the display using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

display→get_functionDescriptor()
display→functionDescriptor()
display.get_functionDescriptor()

YDisplay

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

display→get_functionId()**YDisplay****display→functionId()display.get_functionId()**

Returns the hardware identifier of the display, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the display (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

display→get_hardwareId()

YDisplay

display→hardwareId()display.get_hardwareId()

Returns the unique hardware identifier of the display in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the display (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the display (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

display→get_layerCount()
display→layerCount()display.get_layerCount()

YDisplay

Returns the number of available layers to draw on.

```
def get_layerCount( )
```

Returns :

an integer corresponding to the number of available layers to draw on

On failure, throws an exception or returns Y_LAYERCOUNT_INVALID.

display→get_layerHeight()

YDisplay

display→layerHeight()display.get_layerHeight()

Returns the height of the layers to draw on, in pixels.

```
def get_layerHeight( )
```

Returns :

an integer corresponding to the height of the layers to draw on, in pixels

On failure, throws an exception or returns Y_LAYERHEIGHT_INVALID.

display→get_layerWidth()**YDisplay****display→layerWidth()display.get_layerWidth()**

Returns the width of the layers to draw on, in pixels.

```
def get_layerWidth( )
```

Returns :

an integer corresponding to the width of the layers to draw on, in pixels

On failure, throws an exception or returns Y_LAYERWIDTH_INVALID.

display→get_logicalName() YDisplay
display→logicalName()display.get_logicalName()

Returns the logical name of the display.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the display.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

display→get_module()**YDisplay****display→module()display.get_module()**

Gets the YModule object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

display→get_orientation()

YDisplay

display→orientation()display.get_orientation()

Returns the currently selected display orientation.

```
def get_orientation( )
```

Returns :

a value among Y_ORIENTATION_LEFT, Y_ORIENTATION_UP, Y_ORIENTATION_RIGHT and Y_ORIENTATION_DOWN corresponding to the currently selected display orientation

On failure, throws an exception or returns Y_ORIENTATION_INVALID.

display→get_startupSeq()**YDisplay****display→startupSeq()display.get_startupSeq()**

Returns the name of the sequence to play when the displayed is powered on.

```
def get_startupSeq( )
```

Returns :

a string corresponding to the name of the sequence to play when the displayed is powered on

On failure, throws an exception or returns Y_STARTUPSEQ_INVALID.

display→get(userData)

YDisplay

display→userData()display.get(userData)

Returns the value of the userData attribute, as previously stored using method set(userData).

```
def get(userData) :
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

display→isOnline()display.isOnline()**YDisplay**

Checks if the display is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the display in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the display.

Returns :

`true` if the display can be reached, and `false` otherwise

**display→load()
display.load()****YDisplay**

Preloads the display cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

display→newSequence()display.newSequence()******YDisplay**

Starts to record all display commands into a sequence, for later replay.

```
def newSequence( )
```

The name used to store the sequence is specified when calling `saveSequence()`, once the recording is complete.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→nextDisplay()`display.nextDisplay()`

YDisplay

Continues the enumeration of displays started using `yFirstDisplay()`.

```
def nextDisplay( )
```

Returns :

a pointer to a YDisplay object, corresponding to a display currently online, or a null pointer if there are no more displays to enumerate.

display→pauseSequence()display.pauseSequence()**YDisplay**

Waits for a specified delay (in milliseconds) before playing next commands in current sequence.

```
def pauseSequence( delay_ms)
```

This method can be used while recording a display sequence, to insert a timed wait in the sequence (without any immediate effect). It can also be used dynamically while playing a pre-recorded sequence, to suspend or resume the execution of the sequence. To cancel a delay, call the same method with a zero delay.

Parameters :

delay_ms the duration to wait, in milliseconds

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→playSequence()display.playSequence()******YDisplay**

Replays a display sequence previously recorded using newSequence() and saveSequence().

```
def playSequence( sequenceName)
```

Parameters :

sequenceName the name of the newly created sequence

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→registerValueCallback()
display.registerValueCallback()**YDisplay**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

display→resetAll()display.resetAll()**YDisplay**

Clears the display screen and resets all display layers to their default state.

```
def resetAll( )
```

Using this function in a sequence will kill the sequence play-back. Don't use that function to reset the display at sequence start-up.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

**display→saveSequence()
display.saveSequence()****YDisplay**

Stops recording display commands and saves the sequence into the specified file on the display internal memory.

```
def saveSequence( sequenceName)
```

The sequence can be later replayed using `playSequence()`.

Parameters :

`sequenceName` the name of the newly created sequence

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

**display→set_brightness()
display→setBrightness()display.set_brightness()****YDisplay**

Changes the brightness of the display.

```
def set_brightness( newval)
```

The parameter is a value between 0 and 100. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval an integer corresponding to the brightness of the display

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→set_enabled()
display→setEnabled()display.set_enabled()**YDisplay**

Changes the power state of the display.

```
def set_enabled( newval )
```

Parameters :

newval either Y_ENABLED_FALSE or Y_ENABLED_TRUE, according to the power state of the display

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→set_logicalName() YDisplay
display→setLogicalName()display.set_logicalName()

Changes the logical name of the display.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the display.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

**display→set_orientation()
display→setOrientation()display.set_orientation()****YDisplay**

Changes the display orientation.

```
def set_orientation( newval)
```

Remember to call the saveToFlash() method of the module if the modification must be kept.

Parameters :

newval a value among Y_ORIENTATION_LEFT, Y_ORIENTATION_UP, Y_ORIENTATION_RIGHT and Y_ORIENTATION_DOWN corresponding to the display orientation

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→set_startupSeq() **YDisplay**
display→setStartupSeq()display.set_startupSeq()

Changes the name of the sequence to play when the displayed is powered on.

```
def set_startupSeq( newval)
```

Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the name of the sequence to play when the displayed is powered on

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→set(userData)
display→setUserData()display.set(userData)**YDisplay**

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData) data
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

display→stopSequence()**display.stopSequence()**

YDisplay

Stops immediately any ongoing sequence replay.

```
def stopSequence( )
```

The display is left as is.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

**display→swapLayerContent()
display.swapLayerContent()****YDisplay**

Swaps the whole content of two layers.

```
def swapLayerContent( layerIdA, layerIdB )
```

The color and transparency of all the pixels from the two layers are swapped. This method only affects the displayed content, but does not change any property of the layer objects. In particular, the visibility of each layer stays unchanged. When used between one hidden layer and a visible layer, this method makes it possible to easily implement double-buffering. Note that layer 0 has no transparency support (it is always completely opaque).

Parameters :

layerIdA the first layer (a number in range 0..layerCount-1)

layerIdB the second layer (a number in range 0..layerCount-1)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

display→upload()display.upload()**YDisplay**

Uploads an arbitrary file (for instance a GIF file) to the display, to the specified full path name.

```
def upload( pathname, content)
```

If a file already exists with the same path name, its content is overwritten.

Parameters :

pathname path and name of the new file to create

content binary buffer with the content to set

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

3.15. DisplayLayer object interface

A DisplayLayer is an image layer containing objects to display (bitmaps, text, etc.). The content is displayed only when the layer is active on the screen (and not masked by other overlapping layers).

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_display.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YDisplay = yoctolib.YDisplay;
php	require_once('yocto_display.php');
cpp	#include "yocto_display.h"
m	#import "yocto_display.h"
pas	uses yocto_display;
vb	yocto_display.vb
cs	yocto_display.cs
java	import com.yoctopuce.YoctoAPI.YDisplay;
py	from yocto_display import *

YDisplayLayer methods

displaylayer→clear()

Erases the whole content of the layer (makes it fully transparent).

displaylayer→clearConsole()

Blanks the console area within console margins, and resets the console pointer to the upper left corner of the console.

displaylayer→consoleOut(text)

Outputs a message in the console area, and advances the console pointer accordingly.

displaylayer→drawBar(x1, y1, x2, y2)

Draws a filled rectangular bar at a specified position.

displaylayer→drawBitmap(x, y, w, bitmap, bgcol)

Draws a bitmap at the specified position.

displaylayer→drawCircle(x, y, r)

Draws an empty circle at a specified position.

displaylayer→drawDisc(x, y, r)

Draws a filled disc at a given position.

displaylayer→drawImage(x, y, imagename)

Draws a GIF image at the specified position.

displaylayer→drawPixel(x, y)

Draws a single pixel at the specified position.

displaylayer→drawRect(x1, y1, x2, y2)

Draws an empty rectangle at a specified position.

displaylayer→drawText(x, y, anchor, text)

Draws a text string at the specified position.

displaylayer→get_display()

Gets parent YDisplay.

displaylayer→get_displayHeight()

Returns the display height, in pixels.

displaylayer→get_displayWidth()

Returns the display width, in pixels.

3. Reference

displaylayer→get_layerHeight()

Returns the height of the layers to draw on, in pixels.

displaylayer→get_layerWidth()

Returns the width of the layers to draw on, in pixels.

displaylayer→hide()

Hides the layer.

displaylayer→lineTo(x, y)

Draws a line from current drawing pointer position to the specified position.

displaylayer→moveTo(x, y)

Moves the drawing pointer of this layer to the specified position.

displaylayer→reset()

Reverts the layer to its initial state (fully transparent, default settings).

displaylayer→selectColorPen(color)

Selects the pen color for all subsequent drawing functions, including text drawing.

displaylayer→selectEraser()

Selects an eraser instead of a pen for all subsequent drawing functions, except for bitmap copy functions.

displaylayer→selectFont(fontname)

Selects a font to use for the next text drawing functions, by providing the name of the font file.

displaylayer→selectGrayPen(graylevel)

Selects the pen gray level for all subsequent drawing functions, including text drawing.

displaylayer→setAntialiasingMode(mode)

Enables or disables anti-aliasing for drawing oblique lines and circles.

displaylayer→setConsoleBackground(bgcol)

Sets up the background color used by the clearConsole function and by the console scrolling feature.

displaylayer→setConsoleMargins(x1, y1, x2, y2)

Sets up display margins for the consoleOut function.

displaylayer→setConsoleWordWrap(wordwrap)

Sets up the wrapping behaviour used by the consoleOut function.

displaylayer→setLayerPosition(x, y, scrollTime)

Sets the position of the layer relative to the display upper left corner.

displaylayer→unhide()

Shows the layer.

displaylayer→clear()displaylayer.clear()**YDisplayLayer**

Erases the whole content of the layer (makes it fully transparent).

```
def clear( )
```

This method does not change any other attribute of the layer. To reinitialize the layer attributes to defaults settings, use the method `reset()` instead.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→clearConsole()
displaylayer.clearConsole()

YDisplayLayer

Blanks the console area within console margins, and resets the console pointer to the upper left corner of the console.

```
def clearConsole( )
```

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→consoleOut()displaylayer.consoleOut()**YDisplayLayer**

Outputs a message in the console area, and advances the console pointer accordingly.

```
def consoleOut( text)
```

The console pointer position is automatically moved to the beginning of the next line when a newline character is met, or when the right margin is hit. When the new text to display extends below the lower margin, the console area is automatically scrolled up.

Parameters :

text the message to display

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→drawBar()displaylayer.drawBar()**YDisplayLayer**

Draws a filled rectangular bar at a specified position.

```
def drawBar( x1, y1, x2, y2)
```

Parameters :

- x1** the distance from left of layer to the left border of the rectangle, in pixels
- y1** the distance from top of layer to the top border of the rectangle, in pixels
- x2** the distance from left of layer to the right border of the rectangle, in pixels
- y2** the distance from top of layer to the bottom border of the rectangle, in pixels

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

**displaylayer→drawBitmap()
displaylayer.drawBitmap()****YDisplayLayer**

Draws a bitmap at the specified position.

```
def drawBitmap( x, y, w, bitmap, bgcol)
```

The bitmap is provided as a binary object, where each pixel maps to a bit, from left to right and from top to bottom. The most significant bit of each byte maps to the leftmost pixel, and the least significant bit maps to the rightmost pixel. Bits set to 1 are drawn using the layer selected pen color. Bits set to 0 are drawn using the specified background gray level, unless -1 is specified, in which case they are not drawn at all (as if transparent).

Parameters :

- x** the distance from left of layer to the left of the bitmap, in pixels
- y** the distance from top of layer to the top of the bitmap, in pixels
- w** the width of the bitmap, in pixels
- bitmap** a binary object
- bgcol** the background gray level to use for zero bits (0 = black, 255 = white), or -1 to leave the pixels unchanged

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→drawCircle()displaylayer.drawCircle()**YDisplayLayer**

Draws an empty circle at a specified position.

```
def drawCircle( x, y, r)
```

Parameters :

- x** the distance from left of layer to the center of the circle, in pixels
- y** the distance from top of layer to the center of the circle, in pixels
- r** the radius of the circle, in pixels

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→drawDisc()displaylayer.drawDisc()**YDisplayLayer**

Draws a filled disc at a given position.

```
def drawDisc( x, y, r)
```

Parameters :

x the distance from left of layer to the center of the disc, in pixels

y the distance from top of layer to the center of the disc, in pixels

r the radius of the disc, in pixels

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→drawImage()displaylayer.drawImage()**YDisplayLayer**

Draws a GIF image at the specified position.

```
def drawImage( x, y, imagename)
```

The GIF image must have been previously uploaded to the device built-in memory. If you experience problems using an image file, check the device logs for any error message such as missing image file or bad image file format.

Parameters :

- x** the distance from left of layer to the left of the image, in pixels
- y** the distance from top of layer to the top of the image, in pixels
- imagename** the GIF file name

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

**displaylayer→drawPixel()
displaylayer.drawPixel()****YDisplayLayer**

Draws a single pixel at the specified position.

```
def drawPixel( x, y)
```

Parameters :

x the distance from left of layer, in pixels

y the distance from top of layer, in pixels

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→drawRect()displaylayer.drawRect()**YDisplayLayer**

Draws an empty rectangle at a specified position.

```
def drawRect( x1, y1, x2, y2)
```

Parameters :

- x1** the distance from left of layer to the left border of the rectangle, in pixels
- y1** the distance from top of layer to the top border of the rectangle, in pixels
- x2** the distance from left of layer to the right border of the rectangle, in pixels
- y2** the distance from top of layer to the bottom border of the rectangle, in pixels

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→drawText()displaylayer.drawText()**YDisplayLayer**

Draws a text string at the specified position.

```
def drawText( x, y, anchor, text)
```

The point of the text that is aligned to the specified pixel position is called the anchor point, and can be chosen among several options. Text is rendered from left to right, without implicit wrapping.

Parameters :

x the distance from left of layer to the text anchor point, in pixels
y the distance from top of layer to the text anchor point, in pixels
anchor the text anchor point, chosen among the Y_ALIGN enumeration: Y_ALIGN_TOP_LEFT,
Y_ALIGN_CENTER_LEFT, Y_ALIGN_BASELINE_LEFT, Y_ALIGN_BOTTOM_LEFT,
Y_ALIGN_TOP_CENTER, Y_ALIGN_CENTER, Y_ALIGN_BASELINE_CENTER,
Y_ALIGN_BOTTOM_CENTER, Y_ALIGN_TOP_DECIMAL,
Y_ALIGN_CENTER_DECIMAL, Y_ALIGN_BASELINE_DECIMAL,
Y_ALIGN_BOTTOM_DECIMAL, Y_ALIGN_TOP_RIGHT, Y_ALIGN_CENTER_RIGHT,
Y_ALIGN_BASELINE_RIGHT, Y_ALIGN_BOTTOM_RIGHT.
text the text string to draw

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→get_display()

YDisplayLayer

displaylayer→display()displaylayer.get_display()

Gets parent YDisplay.

```
def get_display( )
```

Returns the parent YDisplay object of the current YDisplayLayer.

Returns :

an YDisplay object

displaylayer→get_displayHeight()
displaylayer→displayHeight()
displaylayer.get_displayHeight()

YDisplayLayer

Returns the display height, in pixels.

```
def get_displayHeight( )
```

Returns :

an integer corresponding to the display height, in pixels On failure, throws an exception or returns Y_DISPLAYHEIGHT_INVALID.

displaylayer→get_displayWidth()
displaylayer→displayWidth()
displaylayer.get_displayWidth()

YDisplayLayer

Returns the display width, in pixels.

```
def get_displayWidth( )
```

Returns :

an integer corresponding to the display width, in pixels On failure, throws an exception or returns Y_DISPLAYWIDTH_INVALID.

displaylayer→get_layerHeight()
displaylayer→layerHeight()
displaylayer.get_layerHeight()

YDisplayLayer

Returns the height of the layers to draw on, in pixels.

```
def get_layerHeight( )
```

Returns :

an integer corresponding to the height of the layers to draw on, in pixels

On failure, throws an exception or returns Y_LAYERHEIGHT_INVALID.

displaylayer→get_layerWidth()
displaylayer→layerWidth()
displaylayer.get_layerWidth()

YDisplayLayer

Returns the width of the layers to draw on, in pixels.

```
def get_layerWidth( )
```

Returns :

an integer corresponding to the width of the layers to draw on, in pixels

On failure, throws an exception or returns Y_LAYERWIDTH_INVALID.

**displaylayer→hide()
displaylayer.hide()****YDisplayLayer**

Hides the layer.

```
def hide( )
```

The state of the layer is preserved but the layer is not displayed on the screen until the next call to `unhide()`. Hiding the layer can positively affect the drawing speed, since it postpones the rendering until all operations are completed (double-buffering).

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→lineTo()displaylayer.lineTo()**YDisplayLayer**

Draws a line from current drawing pointer position to the specified position.

```
def lineTo( x, y)
```

The specified destination pixel is included in the line. The pointer position is then moved to the end point of the line.

Parameters :

- x** the distance from left of layer to the end point of the line, in pixels
- y** the distance from top of layer to the end point of the line, in pixels

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→moveTo()displaylayer.moveTo()**YDisplayLayer**

Moves the drawing pointer of this layer to the specified position.

```
def moveTo( x, y)
```

Parameters :

x the distance from left of layer, in pixels

y the distance from top of layer, in pixels

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

**displaylayer→reset()
displaylayer.reset()****YDisplayLayer**

Reverts the layer to its initial state (fully transparent, default settings).

```
def reset( )
```

Reinitializes the drawing pointer to the upper left position, and selects the most visible pen color. If you only want to erase the layer content, use the method `clear()` instead.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→selectColorPen()
displaylayer.selectColorPen()**YDisplayLayer**

Selects the pen color for all subsequent drawing functions, including text drawing.

```
def selectColorPen( color)
```

The pen color is provided as an RGB value. For grayscale or monochrome displays, the value is automatically converted to the proper range.

Parameters :

color the desired pen color, as a 24-bit RGB value

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

**displaylayer→selectEraser()
displaylayer.selectEraser()****YDisplayLayer**

Selects an eraser instead of a pen for all subsequent drawing functions, except for bitmap copy functions.

```
def selectEraser( )
```

Any point drawn using the eraser becomes transparent (as when the layer is empty), showing the other layers beneath it.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→selectFont()displaylayer.selectFont()**YDisplayLayer**

Selects a font to use for the next text drawing functions, by providing the name of the font file.

```
def selectFont( fontname )
```

You can use a built-in font as well as a font file that you have previously uploaded to the device built-in memory. If you experience problems selecting a font file, check the device logs for any error message such as missing font file or bad font file format.

Parameters :

fontname the font file name

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→selectGrayPen()
displaylayer.selectGrayPen()**YDisplayLayer**

Selects the pen gray level for all subsequent drawing functions, including text drawing.

```
def selectGrayPen( graylevel)
```

The gray level is provided as a number between 0 (black) and 255 (white, or whichever the highest color is). For monochrome displays (without gray levels), any value lower than 128 is rendered as black, and any value equal or above to 128 is non-black.

Parameters :

graylevel the desired gray level, from 0 to 255

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→setAntialiasingMode()
displaylayer.setAntialiasingMode()**YDisplayLayer**

Enables or disables anti-aliasing for drawing oblique lines and circles.

```
def setAntialiasingMode( mode)
```

Anti-aliasing provides a smoother aspect when looked from far enough, but it can add fuzziness when the display is looked from very close. At the end of the day, it is your personal choice. Anti-aliasing is enabled by default on grayscale and color displays, but you can disable it if you prefer. This setting has no effect on monochrome displays.

Parameters :

mode true to enable antialiasing, false to disable it.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→setConsoleBackground()
displaylayer.setConsoleBackground()**YDisplayLayer**

Sets up the background color used by the `clearConsole` function and by the console scrolling feature.

```
def setConsoleBackground( bgcol)
```

Parameters :

bgcol the background gray level to use when scrolling (0 = black, 255 = white), or -1 for transparent

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→setConsoleMargins()
displaylayer.setConsoleMargins()**YDisplayLayer**

Sets up display margins for the `consoleOut` function.

```
def setConsoleMargins( x1, y1, x2, y2)
```

Parameters :

- x1** the distance from left of layer to the left margin, in pixels
- y1** the distance from top of layer to the top margin, in pixels
- x2** the distance from left of layer to the right margin, in pixels
- y2** the distance from top of layer to the bottom margin, in pixels

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→setConsoleWordWrap()
displaylayer.setConsoleWordWrap()**YDisplayLayer**

Sets up the wrapping behaviour used by the `consoleOut` function.

```
def setConsoleWordWrap( wordwrap)
```

Parameters :

wordwrap true to wrap only between words, false to wrap on the last column anyway.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→setLayerPosition()
displaylayer.setLayerPosition()**YDisplayLayer**

Sets the position of the layer relative to the display upper left corner.

```
def setLayerPosition( x, y, scrollTime)
```

When smooth scrolling is used, the display offset of the layer is automatically updated during the next milliseconds to animate the move of the layer.

Parameters :

- x** the distance from left of display to the upper left corner of the layer
- y** the distance from top of display to the upper left corner of the layer
- scrollTime** number of milliseconds to use for smooth scrolling, or 0 if the scrolling should be immediate.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

displaylayer→unhide()**displaylayer.unhide()**

YDisplayLayer

Shows the layer.

```
def unhide( )
```

Shows the layer again after a hide command.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

3.16. External power supply control interface

Yoctopuce application programming interface allows you to control the power source to use for module functions that require high current. The module can also automatically disconnect the external power when a voltage drop is observed on the external power source (external battery running out of power).

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_dualpower.js'></script>
node.js	var yoctolib = require('yoctolib');
php	var YDualPower = yoctolib.YDualPower;
require_once('yocto_dualpower.php');	
cpp	#include "yocto_dualpower.h"
m	#import "yocto_dualpower.h"
pas	uses yocto_dualpower;
vb	yocto_dualpower.vb
cs	yocto_dualpower.cs
java	import com.yoctopuce.YoctoAPI.YDualPower;
py	from yocto_dualpower import *

Global functions

yFindDualPower(func)

Retrieves a dual power control for a given identifier.

yFirstDualPower()

Starts the enumeration of dual power controls currently accessible.

YDualPower methods

dualpower→describe()

Returns a short text that describes unambiguously the instance of the power control in the form TYPE (NAME)=SERIAL.FUNCTIONID.

dualpower→get_advertisedValue()

Returns the current value of the power control (no more than 6 characters).

dualpower→get_errorMessage()

Returns the error message of the latest error with the power control.

dualpower→get_errorType()

Returns the numerical error code of the latest error with the power control.

dualpower→get_extVoltage()

Returns the measured voltage on the external power source, in millivolts.

dualpower→get_friendlyName()

Returns a global identifier of the power control in the format MODULE_NAME . FUNCTION_NAME.

dualpower→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

dualpower→get_functionId()

Returns the hardware identifier of the power control, without reference to the module.

dualpower→get_hardwareId()

Returns the unique hardware identifier of the power control in the form SERIAL.FUNCTIONID.

dualpower→get_logicalName()

Returns the logical name of the power control.

dualpower→get_module()

3. Reference

Gets the YModule object for the device on which the function is located.

dualpower→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

dualpower→get_powerControl()

Returns the selected power source for module functions that require lots of current.

dualpower→get_powerState()

Returns the current power source for module functions that require lots of current.

dualpower→get_userData()

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

dualpower→isOnline()

Checks if the power control is currently reachable, without raising any error.

dualpower→isOnline_async(callback, context)

Checks if the power control is currently reachable, without raising any error (asynchronous version).

dualpower→load(msValidity)

Preloads the power control cache with a specified validity duration.

dualpower→load_async(msValidity, callback, context)

Preloads the power control cache with a specified validity duration (asynchronous version).

dualpower→nextDualPower()

Continues the enumeration of dual power controls started using `yFirstDualPower()`.

dualpower→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

dualpower→set_logicalName(newval)

Changes the logical name of the power control.

dualpower→set_powerControl(newval)

Changes the selected power source for module functions that require lots of current.

dualpower→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

dualpower→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YDualPower.FindDualPower()**yFindDualPower()YDualPower.FindDualPower()****YDualPower**

Retrieves a dual power control for a given identifier.

```
def FindDualPower( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the power control is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YDualPower.isOnline()` to test if the power control is indeed online at a given time. In case of ambiguity when looking for a dual power control by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the power control

Returns :

a `YDualPower` object allowing you to drive the power control.

YDualPower.FirstDualPower()

YDualPower

yFirstDualPower()YDualPower.FirstDualPower()

Starts the enumeration of dual power controls currently accessible.

```
def FirstDualPower( )
```

Use the method `YDualPower.nextDualPower()` to iterate on next dual power controls.

Returns :

a pointer to a `YDualPower` object, corresponding to the first dual power control currently online, or a null pointer if there are none.

dualpower→describe()dualpower.describe()**YDualPower**

Returns a short text that describes unambiguously the instance of the power control in the form TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the power control (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

dualpower→get_advertisedValue()
dualpower→advertisedValue()
dualpower.get_advertisedValue()

YDualPower

Returns the current value of the power control (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the power control (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

dualpower→getErrorMessage()
dualpower→errorMessage()
dualpower.getErrorMessage()

YDualPower

Returns the error message of the latest error with the power control.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the power control object

dualpower→get_errorType()

YDualPower

dualpower→errorType()dualpower.get_errorType()

Returns the numerical error code of the latest error with the power control.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the power control object

dualpower→get_extVoltage()**YDualPower****dualpower→extVoltage()dualpower.get_extVoltage()**

Returns the measured voltage on the external power source, in millivolts.

```
def get_extVoltage( )
```

Returns :

an integer corresponding to the measured voltage on the external power source, in millivolts

On failure, throws an exception or returns Y_EXTVOLTAGE_INVALID.

dualpower→get_friendlyName()
dualpower→friendlyName()
dualpower.get_friendlyName()

YDualPower

Returns a global identifier of the power control in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the power control if they are defined, otherwise the serial number of the module and the hardware identifier of the power control (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the power control using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

dualpower→get_functionDescriptor()
dualpower→functionDescriptor()
dualpower.get_functionDescriptor()

YDualPower

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

dualpower→get_functionId()
dualpower→functionId()dualpower.get_functionId()

YDualPower

Returns the hardware identifier of the power control, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the power control (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

dualpower→get_hardwareId()**dualpower→hardwareId()dualpower.get_hardwareId()****YDualPower**

Returns the unique hardware identifier of the power control in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the power control (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the power control (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

dualpower→get_logicalName()
dualpower→logicalName()
dualpower.get_logicalName()

YDualPower

Returns the logical name of the power control.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the power control.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

dualpower→get_module()**YDualPower****dualpower→module()dualpower.get_module()**

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

dualpower→get_powerControl()
dualpower→powerControl()
dualpower.get_powerControl()

YDualPower

Returns the selected power source for module functions that require lots of current.

```
def get_powerControl( )
```

Returns :

a value among Y_POWERCONTROL_AUTO, Y_POWERCONTROL_FROM_USB, Y_POWERCONTROL_FROM_EXT and Y_POWERCONTROL_OFF corresponding to the selected power source for module functions that require lots of current

On failure, throws an exception or returns Y_POWERCONTROL_INVALID.

dualpower→get_powerState()
dualpower→powerState()
dualpower.get_powerState()

YDualPower

Returns the current power source for module functions that require lots of current.

```
def get_powerState( )
```

Returns :

a value among Y_POWERSTATE_OFF, Y_POWERSTATE_FROM_USB and Y_POWERSTATE_FROM_EXT corresponding to the current power source for module functions that require lots of current

On failure, throws an exception or returns Y_POWERSTATE_INVALID.

dualpower→get(userData)

YDualPower

dualpower→userData()dualpower.get(userData)

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

dualpower→isOnline()**YDualPower**

Checks if the power control is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the power control in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the power control.

Returns :

`true` if the power control can be reached, and `false` otherwise

dualpower→load()dualpower.load()**YDualPower**

Preloads the power control cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

dualpower→nextDualPower()
dualpower.nextDualPower()**YDualPower**

Continues the enumeration of dual power controls started using `yFirstDualPower()`.

```
def nextDualPower( )
```

Returns :

a pointer to a `YDualPower` object, corresponding to a dual power control currently online, or a `null` pointer if there are no more dual power controls to enumerate.

**dualpower→registerValueCallback()
dualpower.registerValueCallback()****YDualPower**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

dualpower→set_logicalName()
dualpower→setLogicalName()
dualpower.set_logicalName()

YDualPower

Changes the logical name of the power control.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the logical name of the power control.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

dualpower→set_powerControl()
dualpower→setPowerControl()
dualpower.set_powerControl()

YDualPower

Changes the selected power source for module functions that require lots of current.

```
def set_powerControl( newval)
```

Parameters :

newval a value among Y_POWERCONTROL_AUTO, Y_POWERCONTROL_FROM_USB, Y_POWERCONTROL_FROM_EXT and Y_POWERCONTROL_OFF corresponding to the selected power source for module functions that require lots of current

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

dualpower→set(userData())**YDualPower****dualpower→setUserData()dualpower.set(userData())**

Stores a user context provided as argument in the userData attribute of the function.

```
def setUserData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.17. Files function interface

The filesystem interface makes it possible to store files on some devices, for instance to design a custom web UI (for networked devices) or to add fonts (on display devices).

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_files.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YFiles = yoctolib.YFiles;
php	require_once('yocto_files.php');
cpp	#include "yocto_files.h"
m	#import "yocto_files.h"
pas	uses yocto_files;
vb	yocto_files.vb
cs	yocto_files.cs
java	import com.yoctopuce.YoctoAPI.YFiles;
py	from yocto_files import *

Global functions

yFindFiles(func)

Retrieves a filesystem for a given identifier.

yFirstFiles()

Starts the enumeration of filesystems currently accessible.

YFiles methods

files→describe()

Returns a short text that describes unambiguously the instance of the filesystem in the form TYPE (NAME)=SERIAL .FUNCTIONID.

files→download(pathname)

Downloads the requested file and returns a binary buffer with its content.

files→download_async(pathname, callback, context)

Downloads the requested file and returns a binary buffer with its content.

files→format_fs()

Reinitialize the filesystem to its clean, unfragmented, empty state.

files→get_advertisedValue()

Returns the current value of the filesystem (no more than 6 characters).

files→get_errorMessage()

Returns the error message of the latest error with the filesystem.

files→get_errorType()

Returns the numerical error code of the latest error with the filesystem.

files→get_filesCount()

Returns the number of files currently loaded in the filesystem.

files→get_freeSpace()

Returns the free space for uploading new files to the filesystem, in bytes.

files→get_friendlyName()

Returns a global identifier of the filesystem in the format MODULE_NAME .FUNCTION_NAME.

files→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

files→get_functionId()

Returns the hardware identifier of the filesystem, without reference to the module.

files→get_hardwareId()

Returns the unique hardware identifier of the filesystem in the form SERIAL.FUNCTIONID.

files→get_list(pattern)

Returns a list of YFileRecord objects that describe files currently loaded in the filesystem.

files→get_logicalName()

Returns the logical name of the filesystem.

files→get_module()

Gets the YModule object for the device on which the function is located.

files→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

files→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

files→isOnline()

Checks if the filesystem is currently reachable, without raising any error.

files→isOnline_async(callback, context)

Checks if the filesystem is currently reachable, without raising any error (asynchronous version).

files→load(msValidity)

Preloads the filesystem cache with a specified validity duration.

files→load_async(msValidity, callback, context)

Preloads the filesystem cache with a specified validity duration (asynchronous version).

files→nextFiles()

Continues the enumeration of filesystems started using yFirstFiles().

files→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

files→remove(pathname)

Deletes a file, given by its full path name, from the filesystem.

files→set_logicalName(newval)

Changes the logical name of the filesystem.

files→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

files→upload(pathname, content)

Uploads a file to the filesystem, to the specified full path name.

files→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YFiles.FindFiles()**YFiles****yFindFiles()YFiles.FindFiles()**

Retrieves a filesystem for a given identifier.

```
def FindFiles( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the filesystem is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YFiles.isOnline()` to test if the filesystem is indeed online at a given time. In case of ambiguity when looking for a filesystem by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the filesystem

Returns :

a `YFiles` object allowing you to drive the filesystem.

YFiles.FirstFiles()**YFiles****yFirstFiles()YFiles.FirstFiles()**

Starts the enumeration of filesystems currently accessible.

```
def FirstFiles( )
```

Use the method `YFiles.nextFiles()` to iterate on next filesystems.

Returns :

a pointer to a `Yfiles` object, corresponding to the first filesystem currently online, or a `null` pointer if there are none.

files→describe(files.describe())**YFiles**

Returns a short text that describes unambiguously the instance of the filesystem in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the filesystem (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

files→download()files.download()**YFiles**

Downloads the requested file and returns a binary buffer with its content.

```
def download( pathname)
```

Parameters :

pathname path and name of the file to download

Returns :

a binary buffer with the file content

On failure, throws an exception or returns an empty content.

files→format_fs()files.format_fs()

YFiles

Reinitialize the filesystem to its clean, unfragmented, empty state.

```
def format_fs( )
```

All files previously uploaded are permanently lost.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

files→get_advertisedValue()**YFiles****files→advertisedValue()files.get_advertisedValue()**

Returns the current value of the filesystem (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the filesystem (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

files→getErrorMessage() YFiles
files→errorMessage()files.getErrorMessage()

Returns the error message of the latest error with the filesystem.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occured while using the filesystem object

files→get_errorType()**YFiles****files→errorType()files.get_errorType()**

Returns the numerical error code of the latest error with the filesystem.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the filesystem object

files→get_filesCount()

YFiles

files→filesCount()files.get_filesCount()

Returns the number of files currently loaded in the filesystem.

```
def get_filesCount( )
```

Returns :

an integer corresponding to the number of files currently loaded in the filesystem

On failure, throws an exception or returns Y_FILESCOUNT_INVALID.

files→get_freeSpace()**YFiles****files→freeSpace()files.get_freeSpace()**

Returns the free space for uploading new files to the filesystem, in bytes.

```
def get_freeSpace( )
```

Returns :

an integer corresponding to the free space for uploading new files to the filesystem, in bytes

On failure, throws an exception or returns Y_FREESPACE_INVALID.

files→get_friendlyName()	YFiles
files→friendlyName()files.get_friendlyName()	

Returns a global identifier of the filesystem in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the filesystem if they are defined, otherwise the serial number of the module and the hardware identifier of the filesystem (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the filesystem using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

`files→get_functionDescriptor()`
`files→functionDescriptor()`
`files.get_functionDescriptor()`

YFiles

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

files→get_functionId()	YFiles
files→functionId()files.get_functionId()	

Returns the hardware identifier of the filesystem, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the filesystem (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

files→get_hwId()**YFiles****files→hardwareId()files.get_hwId()**

Returns the unique hardware identifier of the filesystem in the form SERIAL.FUNCTIONID.

```
def get_hwId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the filesystem (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the filesystem (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

files→get_list()**YFiles****files→list()files.get_list()**

Returns a list of YFileRecord objects that describe files currently loaded in the filesystem.

```
def get_list( pattern)
```

Parameters :

pattern an optional filter pattern, using star and question marks as wildcards. When an empty pattern is provided, all file records are returned.

Returns :

a list of YFileRecord objects, containing the file path and name, byte size and 32-bit CRC of the file content.

On failure, throws an exception or returns an empty list.

`files→get_logicalName()`

YFiles

`files→logicalName()files.get_logicalName()`

Returns the logical name of the filesystem.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the filesystem.

On failure, throws an exception or returns `Y_LOGICALNAME_INVALID`.

files→get_module()	YFiles
files→module()files.get_module()	

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

files→get(userData)**YFiles****files→userData(files.get(userData))**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

files→isOnline()files.isOnline()**YFiles**

Checks if the filesystem is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the filesystem in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the filesystem.

Returns :

`true` if the filesystem can be reached, and `false` otherwise

files→load()files.load()**YFiles**

Preloads the filesystem cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

files→nextFiles()files.nextFiles()

YFiles

Continues the enumeration of filesystems started using `yFirstFiles()`.

```
def nextFiles( )
```

Returns :

a pointer to a YFiles object, corresponding to a filesystem currently online, or a null pointer if there are no more filesystems to enumerate.

**files→registerValueCallback()
files.registerValueCallback()****YFiles**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

files→remove()files.remove()**YFiles**

Deletes a file, given by its full path name, from the filesystem.

```
def remove( pathname)
```

Because of filesystem fragmentation, deleting a file may not always free up the whole space used by the file. However, rewriting a file with the same path name will always reuse any space not freed previously. If you need to ensure that no space is taken by previously deleted files, you can use `format_fs` to fully reinitialize the filesystem.

Parameters :

pathname path and name of the file to remove.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

files→set_logicalName()

YFiles

files→setLogicalName()files.set_logicalName()

Changes the logical name of the filesystem.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the filesystem.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

files→set(userData)

YFiles

files→setUserData(files.set(userData))

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData):
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

files→upload()files.upload()

YFiles

Uploads a file to the filesystem, to the specified full path name.

```
def upload( pathname, content)
```

If a file already exists with the same path name, its content is overwritten.

Parameters :

pathname path and name of the new file to create
content binary buffer with the content to set

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

3.18. GenericSensor function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_geneticsensor.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YGenericSensor = yoctolib.YGenericSensor;
php	require_once('yocto_geneticsensor.php');
cpp	#include "yocto_geneticsensor.h"
m	#import "yocto_geneticsensor.h"
pas	uses yocto_geneticsensor;
vb	yocto_geneticsensor.vb
cs	yocto_geneticsensor.cs
java	import com.yoctopuce.YoctoAPI.YGenericSensor;
py	from yocto_geneticsensor import *

Global functions

yFindGenericSensor(func)

Retrieves a generic sensor for a given identifier.

yFirstGenericSensor()

Starts the enumeration of generic sensors currently accessible.

YGenericSensor methods

geneticsensor→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

geneticsensor→describe()

Returns a short text that describes unambiguously the instance of the generic sensor in the form TYPE (NAME) = SERIAL . FUNCTIONID.

geneticsensor→get_advertisedValue()

Returns the current value of the generic sensor (no more than 6 characters).

geneticsensor→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor.

geneticsensor→get_currentValue()

Returns the current measured value.

geneticsensor→get_errorMessage()

Returns the error message of the latest error with the generic sensor.

geneticsensor→get_errorType()

Returns the numerical error code of the latest error with the generic sensor.

geneticsensor→get_friendlyName()

Returns a global identifier of the generic sensor in the format MODULE_NAME . FUNCTION_NAME.

geneticsensor→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

geneticsensor→get_functionId()

Returns the hardware identifier of the generic sensor, without reference to the module.

geneticsensor→get_hardwareId()

Returns the unique hardware identifier of the generic sensor in the form SERIAL . FUNCTIONID.

genericsensor→get_highestValue()	Returns the maximal value observed for the measure since the device was started.
genericsensor→get_logFrequency()	Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.
genericsensor→get_logicalName()	Returns the logical name of the generic sensor.
genericsensor→get_lowestValue()	Returns the minimal value observed for the measure since the device was started.
genericsensor→get_module()	Gets the YModule object for the device on which the function is located.
genericsensor→get_module_async(callback, context)	Gets the YModule object for the device on which the function is located (asynchronous version).
genericsensor→get_recordedData(startTime, endTime)	Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.
genericsensor→get_reportFrequency()	Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.
genericsensor→get_resolution()	Returns the resolution of the measured values.
genericsensor→get_signalBias()	Returns the electric signal bias for zero shift adjustment.
genericsensor→get_signalRange()	Returns the electric signal range used by the sensor.
genericsensor→get_signalUnit()	Returns the measuring unit of the electrical signal used by the sensor.
genericsensor→get_signalValue()	Returns the measured value of the electrical signal used by the sensor.
genericsensor→get_unit()	Returns the measuring unit for the measure.
genericsensor→get_userData()	Returns the value of the userData attribute, as previously stored using method set(userData).
genericsensor→get_valueRange()	Returns the physical value range measured by the sensor.
genericsensor→isOnline()	Checks if the generic sensor is currently reachable, without raising any error.
genericsensor→isOnline_async(callback, context)	Checks if the generic sensor is currently reachable, without raising any error (asynchronous version).
genericsensor→load(msValidity)	Preloads the generic sensor cache with a specified validity duration.
genericsensor→loadCalibrationPoints(rawValues, refValues)	Retrieves error correction data points previously entered using the method calibrateFromPoints.
genericsensor→load_async(msValidity, callback, context)	Preloads the generic sensor cache with a specified validity duration (asynchronous version).
genericsensor→nextGenericSensor()	Continues the enumeration of generic sensors started using yFirstGenericSensor().

3. Reference

genericsensor→registerTimedReportCallback(callback)

Registers the callback function that is invoked on every periodic timed notification.

genericsensor→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

genericsensor→set_highestValue(newval)

Changes the recorded maximal value observed.

genericsensor→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

genericsensor→set_logicalName(newval)

Changes the logical name of the generic sensor.

genericsensor→set_lowestValue(newval)

Changes the recorded minimal value observed.

genericsensor→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

genericsensor→set_resolution(newval)

Changes the resolution of the measured physical values.

genericsensor→set_signalBias(newval)

Changes the electric signal bias for zero shift adjustment.

genericsensor→set_signalRange(newval)

Changes the electric signal range used by the sensor.

genericsensor→set_unit(newval)

Changes the measuring unit for the measured value.

genericsensor→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

genericsensor→set_valueRange(newval)

Changes the physical value range measured by the sensor.

genericsensor→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

genericsensor→zeroAdjust()

Adjusts the signal bias so that the current signal value is need precisely as zero.

YGenericSensor.FindGenericSensor() yFindGenericSensor() YGenericSensor.FindGenericSensor()

YGenericSensor

Retrieves a generic sensor for a given identifier.

```
def FindGenericSensor( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the generic sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YGenericSensor.isOnline()` to test if the generic sensor is indeed online at a given time. In case of ambiguity when looking for a generic sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the generic sensor

Returns :

a `YGenericSensor` object allowing you to drive the generic sensor.

YGenericSensor.FirstGenericSensor()
yFirstGenericSensor()
YGenericSensor.FirstGenericSensor()

YGenericSensor

Starts the enumeration of generic sensors currently accessible.

```
def FirstGenericSensor( )
```

Use the method `YGenericSensor.nextGenericSensor()` to iterate on next generic sensors.

Returns :

a pointer to a `YGenericSensor` object, corresponding to the first generic sensor currently online, or a null pointer if there are none.

genericsensor→calibrateFromPoints()
genericsensor.calibrateFromPoints()**YGenericSensor**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→describe()genericsensor.describe()**YGenericSensor**

Returns a short text that describes unambiguously the instance of the generic sensor in the form
TYPE (NAME)=SERIAL . FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the generic sensor (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

genericsensor→get_advertisedValue()
genericsensor→advertisedValue()
genericsensor.get_advertisedValue()

YGenericSensor

Returns the current value of the generic sensor (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the generic sensor (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

genericsensor→get_currentRawValue()
genericsensor→currentRawValue()
genericsensor.get_currentRawValue()

YGenericSensor

Returns the uncalibrated, unrounded raw value returned by the sensor.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

genericsensor→get_currentValue()
genericsensor→currentValue()
genericsensor.get_currentValue()

YGenericSensor

Returns the current measured value.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current measured value

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

genericsensor→get_errorMessage()
genericsensor→errorMessage()
genericsensor.get_errorMessage()

YGenericSensor

Returns the error message of the latest error with the generic sensor.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the generic sensor object

genericsensor→get_errorType()
genericsensor→errorType()
genericsensor.get_errorType()

YGenericSensor

Returns the numerical error code of the latest error with the generic sensor.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the generic sensor object

genericsensor→get_friendlyName()
genericsensor→friendlyName()
genericsensor.get_friendlyName()

YGenericSensor

Returns a global identifier of the generic sensor in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the generic sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the generic sensor (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the generic sensor using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

genericsensor→get_functionDescriptor()
genericsensor→functionDescriptor()
genericsensor.get_functionDescriptor()

YGenericSensor

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

`genericsensor→get_functionId()`
`genericsensor→functionId()`
`genericsensor.get_functionId()`

YGenericSensor

Returns the hardware identifier of the generic sensor, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the generic sensor (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

`genericsensor→get_hardwareId()`
`genericsensor→hardwareId()`
`genericsensor.get_hardwareId()`

YGenericSensor

Returns the unique hardware identifier of the generic sensor in the form SERIAL.FUNCTIONID.

`def get_hardwareId()`

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the generic sensor (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the generic sensor (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

genericsensor→get_highestValue()
genericsensor→highestValue()
genericsensor.get_highestValue()

YGenericSensor

Returns the maximal value observed for the measure since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the measure since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

genericsensor→get_logFrequency()
genericsensor→logFrequency()
genericsensor.get_logFrequency()

YGenericSensor

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

genericsensor→get_logicalName()
genericsensor→logicalName()
genericsensor.get_logicalName()

YGenericSensor

Returns the logical name of the generic sensor.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the generic sensor.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

genericsensor→get_lowestValue()
genericsensor→lowestValue()
genericsensor.get_lowestValue()

YGenericSensor

Returns the minimal value observed for the measure since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the measure since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

genericsensor→get_module()
genericsensor→module()
genericsensor.get_module()

YGenericSensor

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

genericsensor→get_recordedData()
genericsensor→recordedData()
genericsensor.get_recordedData()

YGenericSensor

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime)
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

genericsensor→get_reportFrequency()
genericsensor→reportFrequency()
genericsensor.get_reportFrequency()

YGenericSensor

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

genericsensor→get_resolution()
genericsensor→resolution()
genericsensor.get_resolution()

YGenericSensor

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

`genericsensor→get_signalBias()`
`genericsensor→signalBias()`
`genericsensor.get_signalBias()`

YGenericSensor

Returns the electric signal bias for zero shift adjustment.

```
def get_signalBias( )
```

A positive bias means that the signal is over-reporting the measure, while a negative bias means that the signal is underreporting the measure.

Returns :

a floating point number corresponding to the electric signal bias for zero shift adjustment

On failure, throws an exception or returns Y_SIGNALBIAS_INVALID.

genericsensor→get_signalRange()
genericsensor→signalRange()
genericsensor.get_signalRange()

YGenericSensor

Returns the electric signal range used by the sensor.

```
def get_signalRange( )
```

Returns :

a string corresponding to the electric signal range used by the sensor

On failure, throws an exception or returns Y_SIGNALRANGE_INVALID.

genericsensor→get_signalUnit()
genericsensor→signalUnit()
genericsensor.get_signalUnit()

YGenericSensor

Returns the measuring unit of the electrical signal used by the sensor.

```
def get_signalUnit( )
```

Returns :

a string corresponding to the measuring unit of the electrical signal used by the sensor

On failure, throws an exception or returns Y_SIGNALUNIT_INVALID.

genericsensor→get_signalValue()
genericsensor→signalValue()
genericsensor.get_signalValue()

YGenericSensor

Returns the measured value of the electrical signal used by the sensor.

```
def get_signalValue( )
```

Returns :

a floating point number corresponding to the measured value of the electrical signal used by the sensor

On failure, throws an exception or returns Y_SIGNALVALUE_INVALID.

genericsensor→get_unit()

YGenericSensor

genericsensor→unit()genericsensor.get_unit()

Returns the measuring unit for the measure.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the measure

On failure, throws an exception or returns Y_UNIT_INVALID.

genericsensor→get(userData)
genericsensor→userData()
genericsensor.get(userData)

YGenericSensor

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData) :
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

genericsensor→get_valueRange()
genericsensor→valueRange()
genericsensor.get_valueRange()

YGenericSensor

Returns the physical value range measured by the sensor.

```
def get_valueRange( )
```

Returns :

a string corresponding to the physical value range measured by the sensor

On failure, throws an exception or returns Y_VALUERANGE_INVALID.

genericsensor→isOnline()genericsensor.isOnline()**YGenericSensor**

Checks if the generic sensor is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the generic sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the generic sensor.

Returns :

`true` if the generic sensor can be reached, and `false` otherwise

genericsensor→load()genericsensor.load()**YGenericSensor**

Preloads the generic sensor cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

**genericsensor→loadCalibrationPoints()
genericsensor.loadCalibrationPoints()****YGenericSensor**

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→nextGenericSensor()
genericsensor.nextGenericSensor()

YGenericSensor

Continues the enumeration of generic sensors started using `yFirstGenericSensor()`.

```
def nextGenericSensor( )
```

Returns :

a pointer to a `YGenericSensor` object, corresponding to a generic sensor currently online, or a `null` pointer if there are no more generic sensors to enumerate.

genericsensor→registerTimedReportCallback()
genericsensor.registerTimedReportCallback()**YGenericSensor**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

**genericsensor→registerValueCallback()
genericsensor.registerValueCallback()****YGenericSensor**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

genericsensor→set_highestValue()
genericsensor→setHighestValue()
genericsensor.set_highestValue()

YGenericSensor

Changes the recorded maximal value observed.

```
def set_highestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→set_logFrequency()
genericsensor→setLogFrequency()
genericsensor.set_logFrequency()

YGenericSensor

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→set_logicalName()
genericsensor→setLogicalName()
genericsensor.set_logicalName()

YGenericSensor

Changes the logical name of the generic sensor.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the logical name of the generic sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→set_lowestValue()
genericsensor→setLowestValue()
genericsensor.set_lowestValue()

YGenericSensor

Changes the recorded minimal value observed.

```
def set_lowestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→set_reportFrequency()
genericsensor→setReportFrequency()
genericsensor.set_reportFrequency()

YGenericSensor

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval)
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→set_resolution()
genericsensor→setResolution()
genericsensor.set_resolution()

YGenericSensor

Changes the resolution of the measured physical values.

```
def set_resolution( newval )
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→set_signalBias()
genericsensor→setSignalBias()
genericsensor.set_signalBias()

YGenericSensor

Changes the electric signal bias for zero shift adjustment.

```
def set_signalBias( newval )
```

If your electric signal reads positif when it should be zero, setup a positive signalBias of the same value to fix the zero shift.

Parameters :

newval a floating point number corresponding to the electric signal bias for zero shift adjustment

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→set_signalRange()
genericsensor→setSignalRange()
genericsensor.set_signalRange()

YGenericSensor

Changes the electric signal range used by the sensor.

```
def set_signalRange( newval)
```

Parameters :

newval a string corresponding to the electric signal range used by the sensor

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→set_unit()**YGenericSensor****genericsensor→setUnit()genericsensor.set_unit()**

Changes the measuring unit for the measured value.

```
def set_unit( newval)
```

Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the measuring unit for the measured value

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→set(userData)
genericsensor→setUserData()
genericsensor.set(userData)

YGenericSensor

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData) data
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

genericsensor→set_valueRange()
genericsensor→setValueRange()
genericsensor.set_valueRange()

YGenericSensor

Changes the physical value range measured by the sensor.

```
def set_valueRange( newval)
```

As a side effect, the range modification may automatically modify the display resolution.

Parameters :

newval a string corresponding to the physical value range measured by the sensor

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

genericsensor→zeroAdjust()
genericsensor.zeroAdjust()

YGenericSensor

Adjusts the signal bias so that the current signal value is need precisely as zero.

```
def zeroAdjust( )
```

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

3.19. Gyroscope function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_gyro.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YGyro = yoctolib.YGyro;
php	require_once('yocto_gyro.php');
cpp	#include "yocto_gyro.h"
m	#import "yocto_gyro.h"
pas	uses yocto_gyro;
vb	yocto_gyro.vb
cs	yocto_gyro.cs
java	import com.yoctopuce.YoctoAPI.YGyro;
py	from yocto_gyro import *

Global functions

yFindGyro(func)

Retrieves a gyroscope for a given identifier.

yFirstGyro()

Starts the enumeration of gyroscopes currently accessible.

YGyro methods

gyro→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

gyro→describe()

Returns a short text that describes unambiguously the instance of the gyroscope in the form TYPE (NAME)=SERIAL .FUNCTIONID.

gyro→get_advertisedValue()

Returns the current value of the gyroscope (no more than 6 characters).

gyro→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in degrees per second, as a floating point number.

gyro→get_currentValue()

Returns the current value of the angular velocity, in degrees per second, as a floating point number.

gyro→get_errorMessage()

Returns the error message of the latest error with the gyroscope.

gyro→get_errorType()

Returns the numerical error code of the latest error with the gyroscope.

gyro→get_friendlyName()

Returns a global identifier of the gyroscope in the format MODULE_NAME . FUNCTION_NAME.

gyro→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

gyro→get_functionId()

Returns the hardware identifier of the gyroscope, without reference to the module.

gyro→get_hardwareId()

gyro→get_hardwareId()	Returns the unique hardware identifier of the gyroscope in the form SERIAL.FUNCTIONID.
gyro→get_heading()	Returns the estimated heading angle, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.
gyro→get_highestValue()	Returns the maximal value observed for the angular velocity since the device was started.
gyro→get_logFrequency()	Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.
gyro→get_logicalName()	Returns the logical name of the gyroscope.
gyro→get_lowestValue()	Returns the minimal value observed for the angular velocity since the device was started.
gyro→get_module()	Gets the YModule object for the device on which the function is located.
gyro→get_module_async(callback, context)	Gets the YModule object for the device on which the function is located (asynchronous version).
gyro→get_pitch()	Returns the estimated pitch angle, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.
gyro→get_quaternionW()	Returns the w component (real part) of the quaternion describing the device estimated orientation, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.
gyro→get_quaternionX()	Returns the x component of the quaternion describing the device estimated orientation, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.
gyro→get_quaternionY()	Returns the y component of the quaternion describing the device estimated orientation, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.
gyro→get_quaternionZ()	Returns the z component of the quaternion describing the device estimated orientation, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.
gyro→get_recordedData(startTime, endTime)	Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.
gyro→get_reportFrequency()	Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.
gyro→get_resolution()	Returns the resolution of the measured values.
gyro→get_roll()	Returns the estimated roll angle, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.
gyro→get_unit()	Returns the measuring unit for the angular velocity.
gyro→get_userData()	Returns the value of the userData attribute, as previously stored using method set(userData).
gyro→get_xValue()	

Returns the angular velocity around the X axis of the device, as a floating point number.
gyro→get_yValue()
Returns the angular velocity around the Y axis of the device, as a floating point number.
gyro→get_zValue()
Returns the angular velocity around the Z axis of the device, as a floating point number.
gyro→isOnline()
Checks if the gyroscope is currently reachable, without raising any error.
gyro→isOnline_async(callback, context)
Checks if the gyroscope is currently reachable, without raising any error (asynchronous version).
gyro→load(msValidity)
Preloads the gyroscope cache with a specified validity duration.
gyro→loadCalibrationPoints(rawValues, refValues)
Retrieves error correction data points previously entered using the method calibrateFromPoints.
gyro→load_async(msValidity, callback, context)
Preloads the gyroscope cache with a specified validity duration (asynchronous version).
gyro→nextGyro()
Continues the enumeration of gyroscopes started using yFirstGyro().
gyro→registerAnglesCallback(callback)
Registers a callback function that will be invoked each time that the estimated device orientation has changed.
gyro→registerQuaternionCallback(callback)
Registers a callback function that will be invoked each time that the estimated device orientation has changed.
gyro→registerTimedReportCallback(callback)
Registers the callback function that is invoked on every periodic timed notification.
gyro→registerValueCallback(callback)
Registers the callback function that is invoked on every change of advertised value.
gyro→set_highestValue(newval)
Changes the recorded maximal value observed.
gyro→set_logFrequency(newval)
Changes the datalogger recording frequency for this function.
gyro→set_logicalName(newval)
Changes the logical name of the gyroscope.
gyro→set_lowestValue(newval)
Changes the recorded minimal value observed.
gyro→set_reportFrequency(newval)
Changes the timed value notification frequency for this function.
gyro→set_resolution(newval)
Changes the resolution of the measured physical values.
gyro→set_userData(data)
Stores a user context provided as argument in the userData attribute of the function.
gyro→wait_async(callback, context)
Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YGyro.FindGyro() yFindGyro()YGyro.FindGyro()

YGyro

Retrieves a gyroscope for a given identifier.

```
def FindGyro( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the gyroscope is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YGyro.isOnline()` to test if the gyroscope is indeed online at a given time. In case of ambiguity when looking for a gyroscope by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the gyroscope

Returns :

a `YGyro` object allowing you to drive the gyroscope.

YGyro.FirstGyro()**YGyro****yFirstGyro()YGyro.FirstGyro()**

Starts the enumeration of gyroscopes currently accessible.

```
def FirstGyro( )
```

Use the method `YGyro.nextGyro()` to iterate on next gyroscopes.

Returns :

a pointer to a `YGyro` object, corresponding to the first gyro currently online, or a `null` pointer if there are none.

**gyro→calibrateFromPoints()
gyro.calibrateFromPoints()****YGyro**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

gyro→describe()gyro.describe()**YGyro**

Returns a short text that describes unambiguously the instance of the gyroscope in the form TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the gyroscope (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

gyro→get_advertisedValue() **YGyro**
gyro→advertisedValue()gyro.get_advertisedValue()

Returns the current value of the gyroscope (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the gyroscope (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

gyro→get_currentRawValue()**YGyro****gyro→currentRawValue()gyro.get_currentRawValue()**

Returns the uncalibrated, unrounded raw value returned by the sensor, in degrees per second, as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in degrees per second, as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

gyro→get_currentValue() **YGyro**
gyro→currentValue()gyro.get_currentValue()

Returns the current value of the angular velocity, in degrees per second, as a floating point number.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current value of the angular velocity, in degrees per second, as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

gyro→get_errorMessage()**YGyro****gyro→errorMessage()gyro.get_errorMessage()**

Returns the error message of the latest error with the gyroscope.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the gyroscope object

gyro→get_errorType()

YGyro

gyro→errorType()gyro.get_errorType()

Returns the numerical error code of the latest error with the gyroscope.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the gyroscope object

gyro→get_friendlyName()

YGyro

gyro→friendlyName()gyro.get_friendlyName()

Returns a global identifier of the gyroscope in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the gyroscope if they are defined, otherwise the serial number of the module and the hardware identifier of the gyroscope (for example: MyCustomName . relay1)

Returns :

a string that uniquely identifies the gyroscope using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

gyro→get_functionDescriptor()
gyro→functionDescriptor()
gyro.get_functionDescriptor()

YGyro

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

gyro→get_functionId()**YGyro****gyro→functionId()gyro.get_functionId()**

Returns the hardware identifier of the gyroscope, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the gyroscope (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

gyro→get_hardwareId()	YGyro
gyro→hardwareId()gyro.get_hardwareId()	

Returns the unique hardware identifier of the gyroscope in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the gyroscope (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the gyroscope (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

gyro→get_heading()**YGyro****gyro→heading()gyro.get_heading()**

Returns the estimated heading angle, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.

```
def get_heading( )
```

The axis corresponding to the heading can be mapped to any of the device X, Y or Z physical directions using methods of the class `YRefFrame`.

Returns :

a floating-point number corresponding to heading in degrees, between 0 and 360.

gyro→get_highestValue()	YGyro
gyro→highestValue()gyro.get_highestValue()	

Returns the maximal value observed for the angular velocity since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the angular velocity since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

gyro→get_logFrequency()**YGyro****gyro→logFrequency()gyro.get_logFrequency()**

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

gyro→get_logicalName()	YGyro
gyro→logicalName()gyro.get_logicalName()	

Returns the logical name of the gyroscope.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the gyroscope.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

gyro→get_lowestValue()**YGyro****gyro→lowestValue()gyro.get_lowestValue()**

Returns the minimal value observed for the angular velocity since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the angular velocity since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

gyro→get_module()	YGyro
gyro→module()gyro.get_module()	

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

gyro→get_pitch()**YGyro****gyro→pitch()gyro.get_pitch()**

Returns the estimated pitch angle, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.

```
def get_pitch( )
```

The axis corresponding to the pitch angle can be mapped to any of the device X, Y or Z physical directions using methods of the class `YRefFrame`.

Returns :

a floating-point number corresponding to pitch angle in degrees, between -90 and +90.

gyro→get_quaternionW()**YGyro****gyro→quaternionW()gyro.get_quaternionW()**

Returns the w component (real part) of the quaternion describing the device estimated orientation, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.

```
def get_quaternionW( )
```

Returns :

a floating-point number corresponding to the w component of the quaternion.

gyro→get_quaternionX()**YGyro****gyro→quaternionX()gyro.get_quaternionX()**

Returns the x component of the quaternion describing the device estimated orientation, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.

```
def get_quaternionX( )
```

The x component is mostly correlated with rotations on the roll axis.

Returns :

a floating-point number corresponding to the x component of the quaternion.

gyro→get_quaternionY()	YGyro
gyro→quaternionY()gyro.get_quaternionY()	

Returns the *y* component of the quaternion describing the device estimated orientation, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.

```
def get_quaternionY( )
```

The *y* component is mostly correlated with rotations on the pitch axis.

Returns :

a floating-point number corresponding to the *y* component of the quaternion.

gyro→get_quaternionZ()**YGyro****gyro→quaternionZ()gyro.get_quaternionZ()**

Returns the `x` component of the quaternion describing the device estimated orientation, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.

```
def get_quaternionZ( )
```

The `x` component is mostly correlated with changes of heading.

Returns :

a floating-point number corresponding to the `z` component of the quaternion.

gyro→get_recordedData()	YGyro
gyro→recordedData()gyro.get_recordedData()	

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime )
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any meaasure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any meaasure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

gyro→get_reportFrequency()**YGyro****gyro→reportFrequency()gyro.get_reportFrequency()**

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

gyro→get_resolution() YGyro
gyro→resolution()gyro.get_resolution()

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

gyro→get_roll()**YGyro****gyro→roll()gyro.get_roll()**

Returns the estimated roll angle, based on the integration of gyroscopic measures combined with acceleration and magnetic field measurements.

```
def get_roll( )
```

The axis corresponding to the roll angle can be mapped to any of the device X, Y or Z physical directions using methods of the class `YRefFrame`.

Returns :

a floating-point number corresponding to roll angle in degrees, between -180 and +180.

gyro→get_unit()	YGyro
gyro→unit()gyro.get_unit()	

Returns the measuring unit for the angular velocity.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the angular velocity

On failure, throws an exception or returns Y_UNIT_INVALID.

gyro→get(userData)**YGyro****gyro→userData()gyro.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

gyro→get_xValue()

YGyro

gyro→xValue()gyro.get_xValue()

Returns the angular velocity around the X axis of the device, as a floating point number.

```
def get_xValue( )
```

Returns :

a floating point number corresponding to the angular velocity around the X axis of the device, as a floating point number

On failure, throws an exception or returns Y_XVALUE_INVALID.

gyro→get_yValue()**YGyro****gyro→yValue()gyro.get_yValue()**

Returns the angular velocity around the Y axis of the device, as a floating point number.

```
def get_yValue( )
```

Returns :

a floating point number corresponding to the angular velocity around the Y axis of the device, as a floating point number

On failure, throws an exception or returns Y_YVALUE_INVALID.

gyro→get_zValue()

YGyro

gyro→zValue()gyro.get_zValue()

Returns the angular velocity around the Z axis of the device, as a floating point number.

```
def get_zValue( )
```

Returns :

a floating point number corresponding to the angular velocity around the Z axis of the device, as a floating point number

On failure, throws an exception or returns Y_ZVALUE_INVALID.

gyro→isOnline()gyro.isOnline()**YGyro**

Checks if the gyroscope is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the gyroscope in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the gyroscope.

Returns :

`true` if the gyroscope can be reached, and `false` otherwise

gyro→load()gyro.load()**YGyro**

Preloads the gyroscope cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

gyro→loadCalibrationPoints()
gyro.loadCalibrationPoints()**YGyro**

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

gyro→nextGyro()gyro.nextGyro()

YGyro

Continues the enumeration of gyroscopes started using `yFirstGyro()`.

```
def nextGyro( )
```

Returns :

a pointer to a `YGyro` object, corresponding to a gyroscope currently online, or a null pointer if there are no more gyroscopes to enumerate.

**gyro→registerAnglesCallback()
gyro.registerAnglesCallback()****YGyro**

Registers a callback function that will be invoked each time that the estimated device orientation has changed.

```
def registerAnglesCallback( callback)
```

The call frequency is typically around 95Hz during a move. The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to invoke, or a null pointer. The callback function should take four arguments: the YGyro object of the turning device, and the floating point values of the three angles roll, pitch and heading in degrees (as floating-point numbers).

**gyro→registerQuaternionCallback()
gyro.registerQuaternionCallback()****YGyro**

Registers a callback function that will be invoked each time that the estimated device orientation has changed.

```
def registerQuaternionCallback( callback)
```

The call frequency is typically around 95Hz during a move. The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to invoke, or a null pointer. The callback function should take five arguments: the YGyro object of the turning device, and the floating point values of the four components w, x, y and z (as floating-point numbers).

**gyro→registerTimedReportCallback()
gyro.registerTimedReportCallback()****YGyro**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

gyro→registerValueCallback()
gyro.registerValueCallback()**YGyro**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

gyro→set_highestValue()**YGyro****gyro→setHighestValue()gyro.set_highestValue()**

Changes the recorded maximal value observed.

```
def set_highestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

gyro→set_logFrequency()	YGyro
gyro→setLogFrequency()gyro.set_logFrequency()	

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

gyro→set_logicalName()**YGyro****gyro→setLogicalName()gyro.set_logicalName()**

Changes the logical name of the gyroscope.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the gyroscope.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

gyro→set_lowestValue() YGyro
gyro→setLowestValue() gyro.set_lowestValue()

Changes the recorded minimal value observed.

```
def set_lowestValue( newval )
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

gyro→set_reportFrequency()
gyro→setReportFrequency()
gyro.set_reportFrequency()

YGyro

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

gyro→set_resolution()	YGyro
gyro→setResolution()gyro.set_resolution()	

Changes the resolution of the measured physical values.

```
def set_resolution( newval)
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

gyro→set(userData)**YGyro****gyro→setUserData()gyro.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData: Any)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.20. Yocto-hub port interface

YHubPort objects provide control over the power supply for every YoctoHub port and provide information about the device connected to it. The logical name of a YHubPort is always automatically set to the unique serial number of the Yoctopuce device connected to it.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_hubport.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YHubPort = yoctolib.YHubPort;
php	require_once('yocto_hubport.php');
cpp	#include "yocto_hubport.h"
m	#import "yocto_hubport.h"
pas	uses yocto_hubport;
vb	yocto_hubport.vb
cs	yocto_hubport.cs
java	import com.yoctopuce.YoctoAPI.YHubPort;
py	from yocto_hubport import *

Global functions

yFindHubPort(func)

Retrieves a Yocto-hub port for a given identifier.

yFirstHubPort()

Starts the enumeration of Yocto-hub ports currently accessible.

YHubPort methods

hubport→describe()

Returns a short text that describes unambiguously the instance of the Yocto-hub port in the form TYPE (NAME)=SERIAL . FUNCTIONID.

hubport→get_advertisedValue()

Returns the current value of the Yocto-hub port (no more than 6 characters).

hubport→get_baudRate()

Returns the current baud rate used by this Yocto-hub port, in kbps.

hubport→get_enabled()

Returns true if the Yocto-hub port is powered, false otherwise.

hubport→get_errorMessage()

Returns the error message of the latest error with the Yocto-hub port.

hubport→get_errorType()

Returns the numerical error code of the latest error with the Yocto-hub port.

hubport→get_friendlyName()

Returns a global identifier of the Yocto-hub port in the format MODULE_NAME . FUNCTION_NAME.

hubport→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

hubport→get_functionId()

Returns the hardware identifier of the Yocto-hub port, without reference to the module.

hubport→get_hardwareId()

Returns the unique hardware identifier of the Yocto-hub port in the form SERIAL . FUNCTIONID.

hubport→get_logicalName()

Returns the logical name of the Yocto-hub port.

hubport→get_module()	Gets the YModule object for the device on which the function is located.
hubport→get_module_async(callback, context)	Gets the YModule object for the device on which the function is located (asynchronous version).
hubport→get_portState()	Returns the current state of the Yocto-hub port.
hubport→get_userData()	Returns the value of the userData attribute, as previously stored using method set(userData).
hubport→isOnline()	Checks if the Yocto-hub port is currently reachable, without raising any error.
hubport→isOnline_async(callback, context)	Checks if the Yocto-hub port is currently reachable, without raising any error (asynchronous version).
hubport→load(msValidity)	Preloads the Yocto-hub port cache with a specified validity duration.
hubport→load_async(msValidity, callback, context)	Preloads the Yocto-hub port cache with a specified validity duration (asynchronous version).
hubport→nextHubPort()	Continues the enumeration of Yocto-hub ports started using yFirstHubPort().
hubport→registerValueCallback(callback)	Registers the callback function that is invoked on every change of advertised value.
hubport→set_enabled(newval)	Changes the activation of the Yocto-hub port.
hubport→set_logicalName(newval)	Changes the logical name of the Yocto-hub port.
hubport→set_userData(data)	Stores a user context provided as argument in the userData attribute of the function.
hubport→wait_async(callback, context)	Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YHubPort.FindHubPort()**YHubPort****yFindHubPort()YHubPort.FindHubPort()**

Retrieves a Yocto-hub port for a given identifier.

```
def FindHubPort( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the Yocto-hub port is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YHubPort.isOnline()` to test if the Yocto-hub port is indeed online at a given time. In case of ambiguity when looking for a Yocto-hub port by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the Yocto-hub port

Returns :

a `YHubPort` object allowing you to drive the Yocto-hub port.

YHubPort.FirstHubPort()**YHubPort****yFirstHubPort()YHubPort.FirstHubPort()**

Starts the enumeration of Yocto-hub ports currently accessible.

```
def FirstHubPort( )
```

Use the method `YHubPort.nextHubPort()` to iterate on next Yocto-hub ports.

Returns :

a pointer to a `YHubPort` object, corresponding to the first Yocto-hub port currently online, or a `null` pointer if there are none.

hubport→describe()hubport.describe()**YHubPort**

Returns a short text that describes unambiguously the instance of the Yocto-hub port in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the Yocto-hub port (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

hubport→get_advertisedValue()
hubport→advertisedValue()
hubport.get_advertisedValue()

YHubPort

Returns the current value of the Yocto-hub port (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the Yocto-hub port (no more than 6 characters).

On failure, throws an exception or returns `Y_ADVERTISEDVALUE_INVALID`.

hubport→get_baudRate()	YHubPort
hubport→baudRate()hubport.get_baudRate()	

Returns the current baud rate used by this Yocto-hub port, in kbps.

```
def get_baudRate( )
```

The default value is 1000 kbps, but a slower rate may be used if communication problems are encountered.

Returns :

an integer corresponding to the current baud rate used by this Yocto-hub port, in kbps

On failure, throws an exception or returns Y_BAUDRATE_INVALID.

hubport→get_enabled()**YHubPort****hubport→enabled()hubport.get_enabled()**

Returns true if the Yocto-hub port is powered, false otherwise.

```
def get_enabled( )
```

Returns :

either Y_ENABLED_FALSE or Y_ENABLED_TRUE, according to true if the Yocto-hub port is powered, false otherwise

On failure, throws an exception or returns Y_ENABLED_INVALID.

hubport→get_errorMessage()

YHubPort

hubport→errorMessage()hubport.getErrorMessage()

Returns the error message of the latest error with the Yocto-hub port.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the Yocto-hub port object

hubport→get_errorType()**YHubPort****hubport→errorType()hubport.get_errorType()**

Returns the numerical error code of the latest error with the Yocto-hub port.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the Yocto-hub port object

hubport→get_friendlyName()	YHubPort
hubport→friendlyName()hubport.get_friendlyName()	

Returns a global identifier of the Yocto-hub port in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the Yocto-hub port if they are defined, otherwise the serial number of the module and the hardware identifier of the Yocto-hub port (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the Yocto-hub port using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

hubport→get_functionDescriptor()
hubport→functionDescriptor()
hubport.get_functionDescriptor()

YHubPort

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

hubport→get_functionId()

YHubPort

hubport→functionId()hubport.get_functionId()

Returns the hardware identifier of the Yocto-hub port, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the Yocto-hub port (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

hubport→get_hardwareId()**YHubPort****hubport→hardwareId()hubport.get_hardwareId()**

Returns the unique hardware identifier of the Yocto-hub port in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the Yocto-hub port (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the Yocto-hub port (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

hubport→get_logicalName()	YHubPort
hubport→logicalName()hubport.get_logicalName()	

Returns the logical name of the Yocto-hub port.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the Yocto-hub port.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

hubport→get_module()**YHubPort****hubport→module()hubport.get_module()**

Gets the YModule object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

hubport→get_portState() YHubPort
hubport→portState()hubport.get_portState()

Returns the current state of the Yocto-hub port.

```
def get_portState( )
```

Returns :

a value among `Y_PORTSTATE_OFF`, `Y_PORTSTATE_OVRLD`, `Y_PORTSTATE_ON`, `Y_PORTSTATE_RUN` and `Y_PORTSTATE_PROG` corresponding to the current state of the Yocto-hub port

On failure, throws an exception or returns `Y_PORTSTATE_INVALID`.

hubport→get(userData)**YHubPort****hubport→userData()hubport.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

hubport→isOnline()hubport.isOnline()**YHubPort**

Checks if the Yocto-hub port is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the Yocto-hub port in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the Yocto-hub port.

Returns :

true if the Yocto-hub port can be reached, and false otherwise

hubport→load()hubport.load()**YHubPort**

Preloads the Yocto-hub port cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

hubport→nextHubPort()hubport.nextHubPort()

YHubPort

Continues the enumeration of Yocto-hub ports started using `yFirstHubPort()`.

```
def nextHubPort( )
```

Returns :

a pointer to a `YHubPort` object, corresponding to a Yocto-hub port currently online, or a `null` pointer if there are no more Yocto-hub ports to enumerate.

hubport→registerValueCallback()
hubport.registerValueCallback()**YHubPort**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

hubport→set_enabled()	YHubPort
hubport→setEnabled()hubport.set_enabled()	

Changes the activation of the Yocto-hub port.

```
def set_enabled( newval )
```

If the port is enabled, the connected module is powered. Otherwise, port power is shut down.

Parameters :

newval either Y_ENABLED_FALSE or Y_ENABLED_TRUE, according to the activation of the Yocto-hub port

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

hubport→set_logicalName()
hubport→setLogicalName()
hubport.set_logicalName()

YHubPort

Changes the logical name of the Yocto-hub port.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the logical name of the Yocto-hub port.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

hubport→set(userData)

YHubPort

hubport→setUserData()hubport.set(userData)

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.21. Humidity function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_humidity.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YHumidity = yoctolib.YHumidity;
php	require_once('yocto_humidity.php');
cpp	#include "yocto_humidity.h"
m	#import "yocto_humidity.h"
pas	uses yocto_humidity;
vb	yocto_humidity.vb
cs	yocto_humidity.cs
java	import com.yoctopuce.YoctoAPI.YHumidity;
py	from yocto_humidity import *

Global functions

yFindHumidity(func)

Retrieves a humidity sensor for a given identifier.

yFirstHumidity()

Starts the enumeration of humidity sensors currently accessible.

YHumidity methods

humidity→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

humidity→describe()

Returns a short text that describes unambiguously the instance of the humidity sensor in the form TYPE (NAME)=SERIAL . FUNCTIONID.

humidity→get_advertisedValue()

Returns the current value of the humidity sensor (no more than 6 characters).

humidity→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in %RH, as a floating point number.

humidity→get_currentValue()

Returns the current value of the humidity, in %RH, as a floating point number.

humidity→get_errorMessage()

Returns the error message of the latest error with the humidity sensor.

humidity→get_errorType()

Returns the numerical error code of the latest error with the humidity sensor.

humidity→get_friendlyName()

Returns a global identifier of the humidity sensor in the format MODULE_NAME . FUNCTION_NAME.

humidity→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

humidity→get_functionId()

Returns the hardware identifier of the humidity sensor, without reference to the module.

humidity→get_hardwareId()

Returns the unique hardware identifier of the humidity sensor in the form SERIAL . FUNCTIONID.

3. Reference

humidity→get_highestValue()
Returns the maximal value observed for the humidity since the device was started.
humidity→get_logFrequency()
Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.
humidity→get_logicalName()
Returns the logical name of the humidity sensor.
humidity→get_lowestValue()
Returns the minimal value observed for the humidity since the device was started.
humidity→get_module()
Gets the YModule object for the device on which the function is located.
humidity→get_module_async(callback, context)
Gets the YModule object for the device on which the function is located (asynchronous version).
humidity→get_recordedData(startTime, endTime)
Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.
humidity→get_reportFrequency()
Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.
humidity→get_resolution()
Returns the resolution of the measured values.
humidity→get_unit()
Returns the measuring unit for the humidity.
humidity→get(userData)
Returns the value of the userData attribute, as previously stored using method set(userData).
humidity→isOnline()
Checks if the humidity sensor is currently reachable, without raising any error.
humidity→isOnline_async(callback, context)
Checks if the humidity sensor is currently reachable, without raising any error (asynchronous version).
humidity→load(msValidity)
Preloads the humidity sensor cache with a specified validity duration.
humidity→loadCalibrationPoints(rawValues, refValues)
Retrieves error correction data points previously entered using the method calibrateFromPoints.
humidity→load_async(msValidity, callback, context)
Preloads the humidity sensor cache with a specified validity duration (asynchronous version).
humidity→nextHumidity()
Continues the enumeration of humidity sensors started using yFirstHumidity().
humidity→registerTimedReportCallback(callback)
Registers the callback function that is invoked on every periodic timed notification.
humidity→registerValueCallback(callback)
Registers the callback function that is invoked on every change of advertised value.
humidity→set_highestValue(newval)
Changes the recorded maximal value observed.
humidity→set_logFrequency(newval)
Changes the datalogger recording frequency for this function.
humidity→set_logicalName(newval)
Changes the logical name of the humidity sensor.

humidity→set_lowestValue(newval)

Changes the recorded minimal value observed.

humidity→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

humidity→set_resolution(newval)

Changes the resolution of the measured physical values.

humidity→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

humidity→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YHumidity.FindHumidity() yFindHumidity()YHumidity.FindHumidity()

YHumidity

Retrieves a humidity sensor for a given identifier.

```
def FindHumidity( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the humidity sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YHumidity.isOnline()` to test if the humidity sensor is indeed online at a given time. In case of ambiguity when looking for a humidity sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the humidity sensor

Returns :

a `YHumidity` object allowing you to drive the humidity sensor.

YHumidity.FirstHumidity()**YHumidity****yFirstHumidity()YHumidity.FirstHumidity()**

Starts the enumeration of humidity sensors currently accessible.

```
def FirstHumidity( )
```

Use the method `YHumidity.nextHumidity()` to iterate on next humidity sensors.

Returns :

a pointer to a `YHumidity` object, corresponding to the first humidity sensor currently online, or a null pointer if there are none.

humidity→calibrateFromPoints()**YHumidity****humidity.calibrateFromPoints()**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

humidity→describe()humidity.describe()**YHumidity**

Returns a short text that describes unambiguously the instance of the humidity sensor in the form TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the humidity sensor (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

humidity→get_advertisedValue()

YHumidity

humidity→advertisedValue()

humidity.get_advertisedValue()

Returns the current value of the humidity sensor (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the humidity sensor (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

humidity→get_currentRawValue()
humidity→currentRawValue()
humidity.get_currentRawValue()

YHumidity

Returns the uncalibrated, unrounded raw value returned by the sensor, in %RH, as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in %RH, as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

humidity→get_currentValue()

YHumidity

humidity→currentValue()humidity.get_currentValue()

Returns the current value of the humidity, in %RH, as a floating point number.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current value of the humidity, in %RH, as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

humidity→getErrorMessage()
humidity→errorMessage()
humidity.getErrorMessage()**YHumidity**

Returns the error message of the latest error with the humidity sensor.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the humidity sensor object

humidity→get_errorType()

YHumidity

humidity→errorType()humidity.get_errorType()

Returns the numerical error code of the latest error with the humidity sensor.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the humidity sensor object

humidity→get_friendlyName()
humidity→friendlyName()
humidity.get_friendlyName()

YHumidity

Returns a global identifier of the humidity sensor in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the humidity sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the humidity sensor (for example: MyCustomName . relay1)

Returns :

a string that uniquely identifies the humidity sensor using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

humidity→get_functionDescriptor()
humidity→functionDescriptor()
humidity.get_functionDescriptor()**YHumidity**

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

humidity→get_functionId()**YHumidity****humidity→functionId()humidity.get_functionId()**

Returns the hardware identifier of the humidity sensor, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the humidity sensor (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

humidity→get_hwrid() YHumidity
humidity→hwrid()humidity.get_hwrid()

Returns the unique hardware identifier of the humidity sensor in the form SERIAL.FUNCTIONID.

```
def get_hwrid( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the humidity sensor (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the humidity sensor (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

humidity→get_highestValue()
humidity→highestValue()
humidity.get_highestValue()

YHumidity

Returns the maximal value observed for the humidity since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the humidity since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

humidity→get_logFrequency()	YHumidity
humidity→logFrequency()	
humidity.get_logFrequency()	

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

humidity→get_logicalName()**YHumidity****humidity→logicalName()humidity.get_logicalName()**

Returns the logical name of the humidity sensor.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the humidity sensor.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

humidity→get_lowestValue()

YHumidity

humidity→lowestValue()humidity.get_lowestValue()

Returns the minimal value observed for the humidity since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the humidity since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

humidity→get_module()**YHumidity****humidity→module()humidity.get_module()**

Gets the YModule object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

humidity→get_recordedData()
humidity→recordedData()
humidity.get_recordedData()**YHumidity**

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime )
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any meaasure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any meaasure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

humidity→get_reportFrequency()

YHumidity

humidity→reportFrequency()

humidity.get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

humidity→get_resolution()

YHumidity

humidity→resolution()humidity.get_resolution()

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

humidity→get_unit()**YHumidity****humidity→unit()humidity.get_unit()**

Returns the measuring unit for the humidity.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the humidity

On failure, throws an exception or returns Y_UNIT_INVALID.

humidity→get(userData)

YHumidity

humidity→userData()humidity.get(userData)

Returns the value of the userData attribute, as previously stored using method set(userData).

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

humidity→isOnline()humidity.isOnline()**YHumidity**

Checks if the humidity sensor is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the humidity sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the humidity sensor.

Returns :

`true` if the humidity sensor can be reached, and `false` otherwise

humidity→load()humidity.load()******YHumidity**

Preloads the humidity sensor cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

humidity→loadCalibrationPoints()**YHumidity****humidity.loadCalibrationPoints()**

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

humidity→nextHumidity()**humidity.nextHumidity()**

YHumidity

Continues the enumeration of humidity sensors started using `yFirstHumidity()`.

```
def nextHumidity( )
```

Returns :

a pointer to a `YHumidity` object, corresponding to a humidity sensor currently online, or a null pointer if there are no more humidity sensors to enumerate.

humidity→registerTimedReportCallback()
humidity.registerTimedReportCallback()**YHumidity**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

humidity→registerValueCallback()
humidity.registerValueCallback()**YHumidity**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

humidity→set_highestValue()
humidity→setHighestValue()
humidity.set_highestValue()

YHumidity

Changes the recorded maximal value observed.

```
def set_highestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

humidity→set_logFrequency()
humidity→setLogFrequency()
humidity.set_logFrequency()

YHumidity

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

humidity→set_logicalName()
humidity→setLogicalName()
humidity.set_logicalName()

YHumidity

Changes the logical name of the humidity sensor.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the logical name of the humidity sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

humidity→set_lowestValue()
humidity→setLowestValue()
humidity.set_lowestValue()

YHumidity

Changes the recorded minimal value observed.

```
def set_lowestValue( newval )
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

humidity→set_reportFrequency()
humidity→setReportFrequency()
humidity.set_reportFrequency()

YHumidity

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

humidity→set_resolution()**YHumidity****humidity→setResolution()humidity.set_resolution()**

Changes the resolution of the measured physical values.

```
def set_resolution( newval)
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

humidity→set(userData)**YHumidity****humidity→setUserData()humidity.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData) data
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.22. Led function interface

Yoctopuce application programming interface allows you not only to drive the intensity of the led, but also to have it blink at various preset frequencies.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_led.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YLed = yoctolib.YLed;
php	require_once('yocto_led.php');
cpp	#include "yocto_led.h"
m	#import "yocto_led.h"
pas	uses yocto_led;
vb	yocto_led.vb
cs	yocto_led.cs
java	import com.yoctopuce.YoctoAPI.YLed;
py	from yocto_led import *

Global functions

yFindLed(func)

Retrieves a led for a given identifier.

yFirstLed()

Starts the enumeration of leds currently accessible.

YLed methods

led->describe()

Returns a short text that describes unambiguously the instance of the led in the form TYPE(NAME)=SERIAL.FUNCTIONID.

led->get_advertisedValue()

Returns the current value of the led (no more than 6 characters).

led->get_blinking()

Returns the current led signaling mode.

led->get_errorMessage()

Returns the error message of the latest error with the led.

led->get_errorType()

Returns the numerical error code of the latest error with the led.

led->get_friendlyName()

Returns a global identifier of the led in the format MODULE_NAME . FUNCTION_NAME.

led->get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

led->get_functionId()

Returns the hardware identifier of the led, without reference to the module.

led->get_hardwareId()

Returns the unique hardware identifier of the led in the form SERIAL.FUNCTIONID.

led->get_logicalName()

Returns the logical name of the led.

led->get_luminosity()

Returns the current led intensity (in per cent).

led->get_module()

Gets the YModule object for the device on which the function is located.

led->get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

led->get_power()

Returns the current led state.

led->get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

led->isOnline()

Checks if the led is currently reachable, without raising any error.

led->isOnline_async(callback, context)

Checks if the led is currently reachable, without raising any error (asynchronous version).

led->load(msValidity)

Preloads the led cache with a specified validity duration.

led->load_async(msValidity, callback, context)

Preloads the led cache with a specified validity duration (asynchronous version).

led->nextLed()

Continues the enumeration of leds started using yFirstLed().

led->registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

led->set_blinking(newval)

Changes the current led signaling mode.

led->set_logicalName(newval)

Changes the logical name of the led.

led->set_luminosity(newval)

Changes the current led intensity (in per cent).

led->set_power(newval)

Changes the state of the led.

led->set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

led->wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YLed.FindLed() yFindLed()YLed.FindLed()

YLed

Retrieves a led for a given identifier.

```
def FindLed( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the led is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YLed.isOnline()` to test if the led is indeed online at a given time. In case of ambiguity when looking for a led by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the led

Returns :

a `YLED` object allowing you to drive the led.

YLed.FirstLed() yFirstLed()YLed.FirstLed()

YLed

Starts the enumeration of leds currently accessible.

```
def FirstLed( )
```

Use the method `YLed.nextLed()` to iterate on next leds.

Returns :

a pointer to a `YLed` object, corresponding to the first led currently online, or a `null` pointer if there are none.

led→describe()led.describe()

YLed

Returns a short text that describes unambiguously the instance of the led in the form TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the led (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

led→get_advertisedValue()**YLed****led→advertisedValue()led.get_advertisedValue()**

Returns the current value of the led (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the led (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

**led→get_blinking()
led→blinking()led.get_blinking()**

YLed

Returns the current led signaling mode.

```
def get_blinking( )
```

Returns :

a value among Y_BLINKING_STILL, Y_BLINKING_RELAX, Y_BLINKING_AWARE, Y_BLINKING_RUN, Y_BLINKING_CALL and Y_BLINKING_PANIC corresponding to the current led signaling mode

On failure, throws an exception or returns Y_BLINKING_INVALID.

led->getErrorMessage()**YLed****led->errorMessage()led.getErrorMessage()**

Returns the error message of the latest error with the led.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the led object

led->get_errorType()

YLed

led->errorType()led.get_errorType()

Returns the numerical error code of the latest error with the led.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the led object

led→get_friendlyName()**YLed****led→friendlyName()led.get_friendlyName()**

Returns a global identifier of the led in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the led if they are defined, otherwise the serial number of the module and the hardware identifier of the led (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the led using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

led->get_functionDescriptor()
led->functionDescriptor()
led.get_functionDescriptor()

YLed

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

led→get_functionId()**YLed****led→functionId()led.get_functionId()**

Returns the hardware identifier of the led, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the led (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

led→get_hardwareId()
led→hardwareId()led.get_hardwareId()

YLed

Returns the unique hardware identifier of the led in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the led (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the led (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

led→get_logicalName()**YLed****led→logicalName()led.get_logicalName()**

Returns the logical name of the led.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the led.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

led→get_luminosity()

YLed

led→luminosity()led.get_luminosity()

Returns the current led intensity (in per cent).

```
def get_luminosity( )
```

Returns :

an integer corresponding to the current led intensity (in per cent)

On failure, throws an exception or returns Y_LUMINOSITY_INVALID.

led→get_module()**YLed****led→module()led.get_module()**

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

led→get_power()

YLed

led→power()led.get_power()

Returns the current led state.

```
def get_power( )
```

Returns :

either Y_POWER_OFF or Y_POWER_ON, according to the current led state

On failure, throws an exception or returns Y_POWER_INVALID.

led→get(userData)**YLed****led→userData()led.get(userData())**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

led→isOnline()led.isOnline()**YLed**

Checks if the led is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the led in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the led.

Returns :

`true` if the led can be reached, and `false` otherwise

led→load()led.load()**YLed**

Preloads the led cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

led->nextLed()|led.nextLed()

YLed

Continues the enumeration of leds started using `yFirstLed()`.

```
def nextLed( )
```

Returns :

a pointer to a YLed object, corresponding to a led currently online, or a `null` pointer if there are no more leds to enumerate.

led→registerValueCallback()
led.registerValueCallback()**YLed**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

led→set_blinking() YLed
led→setBlinking()led.set_blinking()

Changes the current led signaling mode.

```
def set_blinking( newval )
```

Parameters :

newval a value among Y_BLINKING_STILL, Y_BLINKING_RELAX, Y_BLINKING_AWARE, Y_BLINKING_RUN, Y_BLINKING_CALL and Y_BLINKING_PANIC corresponding to the current led signaling mode

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

led->set_logicalName()**YLed****led->setLogicalName()led.set_logicalName()**

Changes the logical name of the led.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the led.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

led->set_luminosity()

YLed

led->setLuminosity()led.set_luminosity()

Changes the current led intensity (in per cent).

```
def set_luminosity( newval )
```

Parameters :

newval an integer corresponding to the current led intensity (in per cent)

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

led->set_power()**YLed****led->setPower()|led.set_power()**

Changes the state of the led.

```
def set_power( newval )
```

Parameters :

newval either Y_POWER_OFF or Y_POWER_ON, according to the state of the led

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

led→set(userData)
led→setUserData()|led.set(userData)

YLed

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData|setUserData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.23. LightSensor function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_lightsensor.js'></script>
node.js	var yoctolib = require('yoctolib');
	var YLightSensor = yoctolib.YLightSensor;
php	require_once('yocto_lightsensor.php');
cpp	#include "yocto_lightsensor.h"
m	#import "yocto_lightsensor.h"
pas	uses yocto_lightsensor;
vb	yocto_lightsensor.vb
cs	yocto_lightsensor.cs
java	import com.yoctopuce.YoctoAPI.YLightSensor;
py	from yocto_lightsensor import *

Global functions

yFindLightSensor(func)

Retrieves a light sensor for a given identifier.

yFirstLightSensor()

Starts the enumeration of light sensors currently accessible.

YLightSensor methods

lightsensor→calibrate(calibratedVal)

Changes the sensor-specific calibration parameter so that the current value matches a desired target (linear scaling).

lightsensor→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

lightsensor→describe()

Returns a short text that describes unambiguously the instance of the light sensor in the form TYPE (NAME) = SERIAL.FUNCTIONID.

lightsensor→get_advertisedValue()

Returns the current value of the light sensor (no more than 6 characters).

lightsensor→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in lux, as a floating point number.

lightsensor→get_currentValue()

Returns the current value of the ambient light, in lux, as a floating point number.

lightsensor→get_errorMessage()

Returns the error message of the latest error with the light sensor.

lightsensor→get_errorType()

Returns the numerical error code of the latest error with the light sensor.

lightsensor→get_friendlyName()

Returns a global identifier of the light sensor in the format MODULE_NAME . FUNCTION_NAME.

lightsensor→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

lightsensor→get_functionId()

Returns the hardware identifier of the light sensor, without reference to the module.
lightsensor→get_hardwareId()
Returns the unique hardware identifier of the light sensor in the form SERIAL.FUNCTIONID.
lightsensor→get_highestValue()
Returns the maximal value observed for the ambient light since the device was started.
lightsensor→get_logFrequency()
Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.
lightsensor→get_logicalName()
Returns the logical name of the light sensor.
lightsensor→get_lowestValue()
Returns the minimal value observed for the ambient light since the device was started.
lightsensor→get_measureType()
Returns the type of light measure.
lightsensor→get_module()
Gets the YModule object for the device on which the function is located.
lightsensor→get_module_async(callback, context)
Gets the YModule object for the device on which the function is located (asynchronous version).
lightsensor→get_recordedData(startTime, endTime)
Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.
lightsensor→get_reportFrequency()
Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.
lightsensor→get_resolution()
Returns the resolution of the measured values.
lightsensor→get_unit()
Returns the measuring unit for the ambient light.
lightsensor→get(userData)
Returns the value of the userData attribute, as previously stored using method set(userData).
lightsensor→isOnline()
Checks if the light sensor is currently reachable, without raising any error.
lightsensor→isOnline_async(callback, context)
Checks if the light sensor is currently reachable, without raising any error (asynchronous version).
lightsensor→load(msValidity)
Preloads the light sensor cache with a specified validity duration.
lightsensor→loadCalibrationPoints(rawValues, refValues)
Retrieves error correction data points previously entered using the method calibrateFromPoints.
lightsensor→load_async(msValidity, callback, context)
Preloads the light sensor cache with a specified validity duration (asynchronous version).
lightsensor→nextLightSensor()
Continues the enumeration of light sensors started using yFirstLightSensor().
lightsensor→registerTimedReportCallback(callback)
Registers the callback function that is invoked on every periodic timed notification.
lightsensor→registerValueCallback(callback)
Registers the callback function that is invoked on every change of advertised value.
lightsensor→set_highestValue(newval)

Changes the recorded maximal value observed.

lightsensor→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

lightsensor→set_logicalName(newval)

Changes the logical name of the light sensor.

lightsensor→set_lowestValue(newval)

Changes the recorded minimal value observed.

lightsensor→set_measureType(newval)

Modify the light sensor type used in the device.

lightsensor→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

lightsensor→set_resolution(newval)

Changes the resolution of the measured physical values.

lightsensor→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

lightsensor→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YLightSensor.FindLightSensor() yFindLightSensor()YLightSensor.FindLightSensor()

Retrieves a light sensor for a given identifier.

```
def FindLightSensor( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the light sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YLightSensor.isOnline()` to test if the light sensor is indeed online at a given time. In case of ambiguity when looking for a light sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the light sensor

Returns :

a `YLightSensor` object allowing you to drive the light sensor.

YLightSensor.FirstLightSensor()**YLightSensor****yFirstLightSensor()YLightSensor.FirstLightSensor()**

Starts the enumeration of light sensors currently accessible.

```
def FirstLightSensor( )
```

Use the method `YLightSensor.nextLightSensor()` to iterate on next light sensors.

Returns :

a pointer to a `YLightSensor` object, corresponding to the first light sensor currently online, or a null pointer if there are none.

lightsensor→calibrate()lightsensor.calibrate()**YLightSensor**

Changes the sensor-specific calibration parameter so that the current value matches a desired target (linear scaling).

```
def calibrate( calibratedVal)
```

Parameters :

calibratedVal the desired target value.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→calibrateFromPoints()
lightsensor.calibrateFromPoints()**YLightSensor**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→describe()lightsensor.describe()**YLightSensor**

Returns a short text that describes unambiguously the instance of the light sensor in the form
TYPE (NAME)=SERIAL . FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the light sensor (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

lightsensor→get_advertisedValue()
lightsensor→advertisedValue()
lightsensor.get_advertisedValue()

YLightSensor

Returns the current value of the light sensor (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the light sensor (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

lightsensor→get_currentRawValue()
lightsensor→currentRawValue()
lightsensor.get_currentRawValue()

YLightSensor

Returns the uncalibrated, unrounded raw value returned by the sensor, in lux, as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in lux, as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

lightsensor→get_currentValue()
lightsensor→currentValue()
lightsensor.get_currentValue()

YLightSensor

Returns the current value of the ambient light, in lux, as a floating point number.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current value of the ambient light, in lux, as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

lightsensor→get_errorMessage()
lightsensor→errorMessage()
lightsensor.get_errorMessage()

YLightSensor

Returns the error message of the latest error with the light sensor.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the light sensor object

lightsensor→get_errorType()**YLightSensor****lightsensor→errorType()lightsensor.get_errorType()**

Returns the numerical error code of the latest error with the light sensor.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the light sensor object

lightsensor→get_friendlyName()
lightsensor→friendlyName()
lightsensor.get_friendlyName()

YLightSensor

Returns a global identifier of the light sensor in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the light sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the light sensor (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the light sensor using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

lightsensor→get_functionDescriptor()**YLightSensor****lightsensor→functionDescriptor()****lightsensor.get_functionDescriptor()**

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

lightsensor→get_functionId()

YLightSensor

lightsensor→functionId()lightsensor.get_functionId()

Returns the hardware identifier of the light sensor, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the light sensor (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

lightsensor→get_hwId()
lightsensor→hardwareId()
lightsensor.get_hwId()

YLightSensor

Returns the unique hardware identifier of the light sensor in the form SERIAL.FUNCTIONID.

def get_hwId()

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the light sensor (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the light sensor (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

lightsensor→get_highestValue()
lightsensor→highestValue()
lightsensor.get_highestValue()

YLightSensor

Returns the maximal value observed for the ambient light since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the ambient light since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

lightsensor→get_logFrequency()
lightsensor→logFrequency()
lightsensor.get_logFrequency()

YLightSensor

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

lightsensor→get_logicalName()
lightsensor→logicalName()
lightsensor.get_logicalName()

YLightSensor

Returns the logical name of the light sensor.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the light sensor.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

lightsensor→get_lowestValue()
lightsensor→lowestValue()
lightsensor.get_lowestValue()

YLightSensor

Returns the minimal value observed for the ambient light since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the ambient light since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

lightsensor→get_measureType()
lightsensor→measureType()
lightsensor.get_measureType()

YLightSensor

Returns the type of light measure.

```
def get_measureType( )
```

Returns :

a value among Y_MEASURETYPE_HUMAN_EYE, Y_MEASURETYPE_WIDE_SPECTRUM, Y_MEASURETYPE_INFRARED, Y_MEASURETYPE_HIGH_RATE and Y_MEASURETYPE_HIGH_ENERGY corresponding to the type of light measure

On failure, throws an exception or returns Y_MEASURETYPE_INVALID.

lightsensor→get_module()**YLightSensor****lightsensor→module()lightsensor.get_module()**

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

lightsensor→get_recordedData()
lightsensor→recordedData()
lightsensor.get_recordedData()

YLightSensor

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime)
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

lightsensor→get_reportFrequency()**YLightSensor****lightsensor→reportFrequency()****lightsensor.get_reportFrequency()**

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

lightsensor→get_resolution()

YLightSensor

lightsensor→resolution()lightsensor.get_resolution()

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

lightsensor→get_unit()**YLightSensor****lightsensor→unit()lightsensor.get_unit()**

Returns the measuring unit for the ambient light.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the ambient light

On failure, throws an exception or returns Y_UNIT_INVALID.

lightsensor→get(userData)

YLightSensor

lightsensor→userData()lightsensor.get(userData)

Returns the value of the userData attribute, as previously stored using method set(userData).

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

lightsensor→isOnline()lightsensor.isOnline()**YLightSensor**

Checks if the light sensor is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the light sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the light sensor.

Returns :

`true` if the light sensor can be reached, and `false` otherwise

lightsensor→load()lightsensor.load()**YLightSensor**

Preloads the light sensor cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→loadCalibrationPoints()
lightsensor.loadCalibrationPoints()**YLightSensor**

Retrieves error correction data points previously entered using the method `calibrateFromPoints`.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→nextLightSensor()
lightsensor.nextLightSensor()

YLightSensor

Continues the enumeration of light sensors started using `yFirstLightSensor()`.

```
def nextLightSensor( )
```

Returns :

a pointer to a `YLightSensor` object, corresponding to a light sensor currently online, or a `null` pointer if there are no more light sensors to enumerate.

lightsensor→registerTimedReportCallback()
lightsensor.registerTimedReportCallback()**YLightSensor**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

lightsensor→registerValueCallback()
lightsensor.registerValueCallback()**YLightSensor**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

lightsensor→set_highestValue()
lightsensor→setHighestValue()
lightsensor.set_highestValue()

YLightSensor

Changes the recorded maximal value observed.

```
def set_highestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→set_logFrequency()
lightsensor→setLogFrequency()
lightsensor.set_logFrequency()

YLightSensor

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→set_logicalName()
lightsensor→setLogicalName()
lightsensor.set_logicalName()

YLightSensor

Changes the logical name of the light sensor.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the logical name of the light sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→set_lowestValue()
lightsensor→setLowestValue()
lightsensor.set_lowestValue()

YLightSensor

Changes the recorded minimal value observed.

```
def set_lowestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→set_measureType()
lightsensor→setMeasureType()
lightsensor.set_measureType()**YLightSensor**

Modify the light sensor type used in the device.

```
def set_measureType( newval)
```

The measure can either approximate the response of the human eye, focus on a specific light spectrum, depending on the capabilities of the light-sensitive cell. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a value among `Y_MEASURETYPE_HUMAN_EYE`, `Y_MEASURETYPE_WIDE_SPECTRUM`,
`Y_MEASURETYPE_INFRARED`, `Y_MEASURETYPE_HIGH_RATE` and
`Y_MEASURETYPE_HIGH_ENERGY`

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→set_reportFrequency()
lightsensor→setReportFrequency()
lightsensor.set_reportFrequency()

YLightSensor

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→set_resolution()
lightsensor→setResolution()
lightsensor.set_resolution()

YLightSensor

Changes the resolution of the measured physical values.

```
def set_resolution( newval )
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

lightsensor→set(userData)
lightsensor→setUserData()
lightsensor.set(userData)

YLightSensor

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData) data
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.24. Magnetometer function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_magnetometer.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YMagnetometer = yoctolib.YMagnetometer;
php	require_once('yocto_magnetometer.php');
cpp	#include "yocto_magnetometer.h"
m	#import "yocto_magnetometer.h"
pas	uses yocto_magnetometer;
vb	yocto_magnetometer.vb
cs	yocto_magnetometer.cs
java	import com.yoctopuce.YoctoAPI.YMagnetometer;
py	from yocto_magnetometer import *

Global functions

yFindMagnetometer(func)

Retrieves a magnetometer for a given identifier.

yFirstMagnetometer()

Starts the enumeration of magnetometers currently accessible.

YMagnetometer methods

magnetometer→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

magnetometer→describe()

Returns a short text that describes unambiguously the instance of the magnetometer in the form TYPE (NAME) = SERIAL . FUNCTIONID.

magnetometer→get_advertisedValue()

Returns the current value of the magnetometer (no more than 6 characters).

magnetometer→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in mT, as a floating point number.

magnetometer→get_currentValue()

Returns the current value of the magnetic field, in mT, as a floating point number.

magnetometer→get_errorMessage()

Returns the error message of the latest error with the magnetometer.

magnetometer→get_errorType()

Returns the numerical error code of the latest error with the magnetometer.

magnetometer→get_friendlyName()

Returns a global identifier of the magnetometer in the format MODULE_NAME . FUNCTION_NAME.

magnetometer→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

magnetometer→get_functionId()

Returns the hardware identifier of the magnetometer, without reference to the module.

magnetometer→get_hardwareId()

Returns the unique hardware identifier of the magnetometer in the form SERIAL . FUNCTIONID.

magnetometer→get_highestValue()	Returns the maximal value observed for the magnetic field since the device was started.
magnetometer→get_logFrequency()	Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.
magnetometer→get_logicalName()	Returns the logical name of the magnetometer.
magnetometer→get_lowestValue()	Returns the minimal value observed for the magnetic field since the device was started.
magnetometer→get_module()	Gets the YModule object for the device on which the function is located.
magnetometer→get_module_async(callback, context)	Gets the YModule object for the device on which the function is located (asynchronous version).
magnetometer→get_recordedData(startTime, endTime)	Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.
magnetometer→get_reportFrequency()	Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.
magnetometer→get_resolution()	Returns the resolution of the measured values.
magnetometer→get_unit()	Returns the measuring unit for the magnetic field.
magnetometer→get_userData()	Returns the value of the userData attribute, as previously stored using method set(userData).
magnetometer→get_xValue()	Returns the X component of the magnetic field, as a floating point number.
magnetometer→get_yValue()	Returns the Y component of the magnetic field, as a floating point number.
magnetometer→get_zValue()	Returns the Z component of the magnetic field, as a floating point number.
magnetometer→isOnline()	Checks if the magnetometer is currently reachable, without raising any error.
magnetometer→isOnline_async(callback, context)	Checks if the magnetometer is currently reachable, without raising any error (asynchronous version).
magnetometer→load(msValidity)	Preloads the magnetometer cache with a specified validity duration.
magnetometer→loadCalibrationPoints(rawValues, refValues)	Retrieves error correction data points previously entered using the method calibrateFromPoints.
magnetometer→load_async(msValidity, callback, context)	Preloads the magnetometer cache with a specified validity duration (asynchronous version).
magnetometer→nextMagnetometer()	Continues the enumeration of magnetometers started using yFirstMagnetometer().
magnetometer→registerTimedReportCallback(callback)	Registers the callback function that is invoked on every periodic timed notification.
magnetometer→registerValueCallback(callback)	Registers the callback function that is invoked on every change of advertised value.

magnetometer→set_highestValue(newval)

Changes the recorded maximal value observed.

magnetometer→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

magnetometer→set_logicalName(newval)

Changes the logical name of the magnetometer.

magnetometer→set_lowestValue(newval)

Changes the recorded minimal value observed.

magnetometer→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

magnetometer→set_resolution(newval)

Changes the resolution of the measured physical values.

magnetometer→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

magnetometer→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

Y Magnetometer.FindMagnetometer() yFindMagnetometer() Y Magnetometer.FindMagnetometer()

Y Magnetometer

Retrieves a magnetometer for a given identifier.

```
def FindMagnetometer( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the magnetometer is online at the time it is invoked. The returned object is nevertheless valid. Use the method `Y Magnetometer.isOnline()` to test if the magnetometer is indeed online at a given time. In case of ambiguity when looking for a magnetometer by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the magnetometer

Returns :

a `Y Magnetometer` object allowing you to drive the magnetometer.

**Y Magnetometer.FirstMagnetometer()
yFirstMagnetometer()
Y Magnetometer.FirstMagnetometer()****Y Magnetometer**

Starts the enumeration of magnetometers currently accessible.

```
def FirstMagnetometer( )
```

Use the method `Y Magnetometer.nextMagnetometer()` to iterate on next magnetometers.

Returns :

a pointer to a `Y Magnetometer` object, corresponding to the first magnetometer currently online, or a null pointer if there are none.

magnetometer→calibrateFromPoints()
magnetometer.calibrateFromPoints()**YMagnetometer**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

magnetometer→describe()magnetometer.describe()**YMagnetometer**

Returns a short text that describes unambiguously the instance of the magnetometer in the form TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the magnetometer (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

magnetometer→get_advertisedValue()
magnetometer→advertisedValue()
magnetometer.get_advertisedValue()

YMagnetometer

Returns the current value of the magnetometer (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the magnetometer (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

magnetometer→get_currentRawValue()
magnetometer→currentRawValue()
magnetometer.get_currentRawValue()

YMagnetometer

Returns the uncalibrated, unrounded raw value returned by the sensor, in mT, as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in mT, as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

magnetometer→get_currentValue()
magnetometer→currentValue()
magnetometer.get_currentValue()

YMagnetometer

Returns the current value of the magnetic field, in mT, as a floating point number.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current value of the magnetic field, in mT, as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

magnetometer→get_errorMessage()
magnetometer→errorMessage()
magnetometer.get_errorMessage()

YMagnetometer

Returns the error message of the latest error with the magnetometer.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the magnetometer object

magnetometer→get_errorType()
magnetometer→errorType()
magnetometer.get_errorType()

YMagnetometer

Returns the numerical error code of the latest error with the magnetometer.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the magnetometer object

magnetometer→get_friendlyName()
magnetometer→friendlyName()
magnetometer.get_friendlyName()

YMagnetometer

Returns a global identifier of the magnetometer in the format MODULE_NAME . FUNCTION_NAME.

def get_friendlyName()

The returned string uses the logical names of the module and of the magnetometer if they are defined, otherwise the serial number of the module and the hardware identifier of the magnetometer (for example: MyCustomName . relay1)

Returns :

a string that uniquely identifies the magnetometer using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

magnetometer→get_functionDescriptor()
magnetometer→functionDescriptor()
magnetometer.get_functionDescriptor()

YMagnetometer

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

magnetometer→get_functionId()
magnetometer→functionId()
magnetometer.get_functionId()

YMagnetometer

Returns the hardware identifier of the magnetometer, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the magnetometer (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

magnetometer→get_hardwareId()
magnetometer→hardwareId()
magnetometer.get_hardwareId()

YMagnetometer

Returns the unique hardware identifier of the magnetometer in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the magnetometer (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the magnetometer (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

magnetometer→get_highestValue()
magnetometer→highestValue()
magnetometer.get_highestValue()

YMagnetometer

Returns the maximal value observed for the magnetic field since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the magnetic field since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

magnetometer→get_logFrequency()
magnetometer→logFrequency()
magnetometer.get_logFrequency()

YMagnetometer

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

magnetometer→get_logicalName()
magnetometer→logicalName()
magnetometer.get_logicalName()

YMagnetometer

Returns the logical name of the magnetometer.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the magnetometer.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

magnetometer→get_lowestValue()
magnetometer→lowestValue()
magnetometer.get_lowestValue()

YMagnetometer

Returns the minimal value observed for the magnetic field since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the magnetic field since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

magnetometer→get_module()
magnetometer→module()
magnetometer.get_module()

YMagnetometer

Gets the **YModule** object for the device on which the function is located.

def get_module()

If the function cannot be located on any module, the returned instance of **YModule** is not shown as online.

Returns :

an instance of **YModule**

magnetometer→get_recordedData()
magnetometer→recordedData()
magnetometer.get_recordedData()

YMagnetometer

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime )
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

magnetometer→get_reportFrequency()
magnetometer→reportFrequency()
magnetometer.get_reportFrequency()

YMagnetometer

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

magnetometer→get_resolution()
magnetometer→resolution()
magnetometer.get_resolution()

YMagnetometer

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

magnetometer→get_unit()**YMagnetometer****magnetometer→unit()magnetometer.get_unit()**

Returns the measuring unit for the magnetic field.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the magnetic field

On failure, throws an exception or returns Y_UNIT_INVALID.

magnetometer→get(userData)
magnetometer→userData()
magnetometer.get(userData)

YMagnetometer

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

magnetometer→get_xValue()**YMagnetometer****magnetometer→xValue()magnetometer.get_xValue()**

Returns the X component of the magnetic field, as a floating point number.

```
def get_xValue( )
```

Returns :

a floating point number corresponding to the X component of the magnetic field, as a floating point number

On failure, throws an exception or returns Y_XVALUE_INVALID.

magnetometer→get_yValue()

YMagnetometer

magnetometer→yValue()magnetometer.get_yValue()

Returns the Y component of the magnetic field, as a floating point number.

```
def get_yValue( )
```

Returns :

a floating point number corresponding to the Y component of the magnetic field, as a floating point number

On failure, throws an exception or returns Y_YVALUE_INVALID.

magnetometer→get_zValue()**YMagnetometer****magnetometer→zValue()magnetometer.get_zValue()**

Returns the Z component of the magnetic field, as a floating point number.

```
def get_zValue( )
```

Returns :

a floating point number corresponding to the Z component of the magnetic field, as a floating point number

On failure, throws an exception or returns Y_ZVALUE_INVALID.

magnetometer→isOnline()magnetometer.isOnline()**YMagnetometer**

Checks if the magnetometer is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the magnetometer in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the magnetometer.

Returns :

true if the magnetometer can be reached, and false otherwise

magnetometer→load()magnetometer.load()**YMagnetometer**

Preloads the magnetometer cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

magnetometer→loadCalibrationPoints()
magnetometer.loadCalibrationPoints()**YMagnetometer**

Retrieves error correction data points previously entered using the method `calibrateFromPoints`.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

magnetometer→nextMagnetometer()
magnetometer.nextMagnetometer()**Y Magnetometer**

Continues the enumeration of magnetometers started using `yFirstMagnetometer()`.

```
def nextMagnetometer( )
```

Returns :

a pointer to a `Y Magnetometer` object, corresponding to a magnetometer currently online, or a null pointer if there are no more magnetometers to enumerate.

magnetometer→registerTimedReportCallback()
magnetometer.registerTimedReportCallback()**YMagnetometer**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

magnetometer→registerValueCallback()
magnetometer.registerValueCallback()**YMagnetometer**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

magnetometer→set_highestValue()
magnetometer→setHighestValue()
magnetometer.set_highestValue()

YMagnetometer

Changes the recorded maximal value observed.

```
def set_highestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

magnetometer→set_logFrequency()
magnetometer→setLogFrequency()
magnetometer.set_logFrequency()

YMagmeter

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval)
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

magnetometer→set_logicalName()
magnetometer→setLogicalName()
magnetometer.set_logicalName()

YMagnetometer

Changes the logical name of the magnetometer.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the magnetometer.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

magnetometer→set_lowestValue()
magnetometer→setLowestValue()
magnetometer.set_lowestValue()

YMagnetometer

Changes the recorded minimal value observed.

```
def set_lowestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

magnetometer→set_reportFrequency()
magnetometer→setReportFrequency()
magnetometer.set_reportFrequency()**YMagnetometer**

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

magnetometer→set_resolution()
magnetometer→setResolution()
magnetometer.set_resolution()

YMagnetometer

Changes the resolution of the measured physical values.

```
def set_resolution( newval )
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

magnetometer→set(userData)
magnetometer→setUserData()
magnetometer.set(userData)

YMagnetometer

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.25. Measured value

YMeasure objects are used within the API to represent a value measured at a specified time. These objects are used in particular in conjunction with the YDataSet class.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_api.js'></script>
node.js	var yoctolib = require('yoctolib');
	var YAPI = yoctolib.YAPI;
	var YModule = yoctolib.YModule;
php	require_once('yocto_api.php');
cpp	#include "yocto_api.h"
m	#import "yocto_api.h"
pas	uses yocto_api;
vb	yocto_api.vb
cs	yocto_api.cs
java	import com.yoctopuce.YoctoAPI.YModule;
py	from yocto_api import *

YMeasure methods

measure→get_averageValue()

Returns the average value observed during the time interval covered by this measure.

measure→get_endTimeUTC()

Returns the end time of the measure, relative to the Jan 1, 1970 UTC (Unix timestamp).

measure→get_maxValue()

Returns the largest value observed during the time interval covered by this measure.

measure→get_minValue()

Returns the smallest value observed during the time interval covered by this measure.

measure→get_startTimeUTC()

Returns the start time of the measure, relative to the Jan 1, 1970 UTC (Unix timestamp).

measure→get_averageValue()
measure→averageValue()
measure.get_averageValue()

YMeasure

Returns the average value observed during the time interval covered by this measure.

```
def get_averageValue( )
```

Returns :

a floating-point number corresponding to the average value observed.

measure→get_endTimeUTC()**YMeasure****measure→endTimeUTC()measure.get_endTimeUTC()**

Returns the end time of the measure, relative to the Jan 1, 1970 UTC (Unix timestamp).

```
def get_endTimeUTC( )
```

When the recording rate is higher than 1 sample per second, the timestamp may have a fractional part.

Returns :

an floating point number corresponding to the number of seconds between the Jan 1, 1970 UTC and the end of this measure.

measure→get_maxValue()

YMeasure

measure→maxValue()measure.get_maxValue()

Returns the largest value observed during the time interval covered by this measure.

```
def get_maxValue( )
```

Returns :

a floating-point number corresponding to the largest value observed.

measure→get_minValue()**YMeasure****measure→minValue()measure.get_minValue()**

Returns the smallest value observed during the time interval covered by this measure.

```
def get_minValue( )
```

Returns :

a floating-point number corresponding to the smallest value observed.

measure→getStartTimeUTC()
measure→startTimeUTC()
measure.getStartTimeUTC()

YMeasure

Returns the start time of the measure, relative to the Jan 1, 1970 UTC (Unix timestamp).

```
def getStartTimeUTC( )
```

When the recording rate is higher then 1 sample per second, the timestamp may have a fractional part.

Returns :

an floating point number corresponding to the number of seconds between the Jan 1, 1970 UTC and the beginning of this measure.

3.26. Module control interface

This interface is identical for all Yoctopuce USB modules. It can be used to control the module global parameters, and to enumerate the functions provided by each module.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_api.js'></script>
node.js	var yoctolib = require('yoctolib');
	var YAPI = yoctolib.YAPI;
	var YModule = yoctolib.YModule;
php	require_once('yocto_api.php');
cpp	#include "yocto_api.h"
m	#import "yocto_api.h"
pas	uses yocto_api;
vb	yocto_api.vb
cs	yocto_api.cs
java	import com.yoctopuce.YoctoAPI.YModule;
py	from yocto_api import *

Global functions

yFindModule(func)

Allows you to find a module from its serial number or from its logical name.

yFirstModule()

Starts the enumeration of modules currently accessible.

YModule methods

module→checkFirmware(path, onlynew)

Test if the byn file is valid for this module.

module→describe()

Returns a descriptive text that identifies the module.

module→download(pathname)

Downloads the specified built-in file and returns a binary buffer with its content.

module→functionCount()

Returns the number of functions (beside the "module" interface) available on the module.

module→functionId(functionIndex)

Retrieves the hardware identifier of the *n*th function on the module.

module→functionName(functionIndex)

Retrieves the logical name of the *n*th function on the module.

module→functionValue(functionIndex)

Retrieves the advertised value of the *n*th function on the module.

module→get_allSettings()

Returns all the setting of the module.

module→get_beacon()

Returns the state of the localization beacon.

module→get_errorMessage()

Returns the error message of the latest error with this module object.

module→get_errorType()

Returns the numerical error code of the latest error with this module object.

module→get_firmwareRelease()

3. Reference

Returns the version of the firmware embedded in the module.
module→get_hardwareId() Returns the unique hardware identifier of the module.
module→get_icon2d() Returns the icon of the module.
module→get_lastLogs() Returns a string with last logs of the module.
module→get_logicalName() Returns the logical name of the module.
module→get_luminosity() Returns the luminosity of the module informative leds (from 0 to 100).
module→get_persistentSettings() Returns the current state of persistent module settings.
module→get_productId() Returns the USB device identifier of the module.
module→get_productName() Returns the commercial name of the module, as set by the factory.
module→get_productRelease() Returns the hardware release version of the module.
module→get_rebootCountdown() Returns the remaining number of seconds before the module restarts, or zero when no reboot has been scheduled.
module→get_serialNumber() Returns the serial number of the module, as set by the factory.
module→get_upTime() Returns the number of milliseconds spent since the module was powered on.
module→get_usbCurrent() Returns the current consumed by the module on the USB bus, in milli-amps.
module→get(userData) Returns the value of the userData attribute, as previously stored using method <code>set(userData)</code> .
module→get(userVar) Returns the value previously stored in this attribute.
module→isOnline() Checks if the module is currently reachable, without raising any error.
module→isOnline_async(callback, context) Checks if the module is currently reachable, without raising any error.
module→load(msValidity) Preloads the module cache with a specified validity duration.
module→load_async(msValidity, callback, context) Preloads the module cache with a specified validity duration (asynchronous version).
module→nextModule() Continues the module enumeration started using <code>yFirstModule()</code> .
module→reboot(secBeforeReboot) Schedules a simple module reboot after the given number of seconds.
module→registerLogCallback(callback) Registers a device log callback function.

module→revertFromFlash()

Reloads the settings stored in the nonvolatile memory, as when the module is powered on.

module→saveToFlash()

Saves current settings in the nonvolatile memory of the module.

module→set_allSettings(settings)

Restore all the setting of the module.

module→set_beacon(newval)

Turns on or off the module localization beacon.

module→set_logicalName(newval)

Changes the logical name of the module.

module→set_luminosity(newval)

Changes the luminosity of the module informative leds.

module→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

module→set_userVar(newval)

Returns the value previously stored in this attribute.

module→triggerFirmwareUpdate(secBeforeReboot)

Schedules a module reboot into special firmware update mode.

module→updateFirmware(path)

Prepare a firmware upgrade of the module.

module→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

**YModule.FindModule()
yFindModule()YModule.FindModule()****YModule**

Allows you to find a module from its serial number or from its logical name.

```
def FindModule( func)
```

This function does not require that the module is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YModule.isOnline()` to test if the module is indeed online at a given time. In case of ambiguity when looking for a module by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string containing either the serial number or the logical name of the desired module

Returns :

a `YModule` object allowing you to drive the module or get additional information on the module.

YModule.FirstModule()**YModule****yFirstModule()YModule.FirstModule()**

Starts the enumeration of modules currently accessible.

```
def FirstModule( )
```

Use the method `YModule.nextModule()` to iterate on the next modules.

Returns :

a pointer to a `YModule` object, corresponding to the first module currently online, or a `null` pointer if there are none.

module→checkFirmware()module.checkFirmware()**YModule**

Test if the byn file is valid for this module.

```
def checkFirmware( path, onlynew )
```

This method is useful to test if the module need to be updated. It's possible to pass an directory instead of a file. In this case this method return the path of the most recent appropriate byn file. If the parameter onlynew is true the function will discard firmware that are older or equal to the installed firmware.

Parameters :

path the path of a byn file or a directory that contain byn files

onlynew return only files that are strictly newer

Returns :

: the path of the byn file to use or a empty string if no byn files match the requirement

On failure, throws an exception or returns a string that start with "error:".

module→describe()module.describe()**YModule**

Returns a descriptive text that identifies the module.

```
def describe( )
```

The text may include either the logical name or the serial number of the module.

Returns :

a string that describes the module

module→download()module.download()**YModule**

Downloads the specified built-in file and returns a binary buffer with its content.

```
def download( pathname)
```

Parameters :

pathname name of the new file to load

Returns :

a binary buffer with the file content

On failure, throws an exception or returns YAPI_INVALID_STRING.

module→functionCount()module.functionCount()**YModule**

Returns the number of functions (beside the "module" interface) available on the module.

```
def functionCount( )
```

Returns :

the number of functions on the module

On failure, throws an exception or returns a negative error code.

module→functionId()module.functionId()**YModule**

Retrieves the hardware identifier of the *n*th function on the module.

```
def functionId( functionIndex)
```

Parameters :

functionIndex the index of the function for which the information is desired, starting at 0 for the first function.

Returns :

a string corresponding to the unambiguous hardware identifier of the requested module function

On failure, throws an exception or returns an empty string.

module→functionName()module.functionName()**YModule**

Retrieves the logical name of the *n*th function on the module.

```
def functionName( functionIndex)
```

Parameters :

functionIndex the index of the function for which the information is desired, starting at 0 for the first function.

Returns :

a string corresponding to the logical name of the requested module function

On failure, throws an exception or returns an empty string.

module→functionValue()module.functionValue()**YModule**

Retrieves the advertised value of the *n*th function on the module.

```
def functionValue( functionIndex)
```

Parameters :

functionIndex the index of the function for which the information is desired, starting at 0 for the first function.

Returns :

a short string (up to 6 characters) corresponding to the advertised value of the requested module function

On failure, throws an exception or returns an empty string.

module->get_allSettings()	YModule
module->allSettings()module.get_allSettings()	

Returns all the setting of the module.

```
def get_allSettings( )
```

Useful to backup all the logical name and calibrations parameters of a connected module.

Returns :

a binary buffer with all settings.

On failure, throws an exception or returns YAPI_INVALID_STRING.

module→get_beacon()
module→beacon()module.get_beacon()

YModule

Returns the state of the localization beacon.

```
def get_beacon( )
```

Returns :

either Y_BEACON_OFF or Y_BEACON_ON, according to the state of the localization beacon

On failure, throws an exception or returns Y_BEACON_INVALID.

module->getErrorMessage()	YModule
module->errorMessage()module.getErrorMessage()	

Returns the error message of the latest error with this module object.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using this module object

module→get_errorType() **YModule**
module→errorType()module.get_errorType()

Returns the numerical error code of the latest error with this module object.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using this module object

module->get_firmwareRelease()
module->firmwareRelease()
module.get_firmwareRelease()

YModule

Returns the version of the firmware embedded in the module.

```
def get_firmwareRelease( )
```

Returns :

a string corresponding to the version of the firmware embedded in the module

On failure, throws an exception or returns Y_FIRMWARERELEASE_INVALID.

module→get_hwId()
module→hardwareId()module.get_hwId()

YModule

Returns the unique hardware identifier of the module.

```
def get_hwId( )
```

The unique hardware identifier is made of the device serial number followed by string ".module".

Returns :

a string that uniquely identifies the module

module→get_icon2d()**YModule****module→icon2d()module.get_icon2d()**

Returns the icon of the module.

```
def get_icon2d( )
```

The icon is a PNG image and does not exceeds 1536 bytes.

Returns :

a binary buffer with module icon, in png format. On failure, throws an exception or returns YAPI_INVALID_STRING.

module→get_lastLogs()
module→lastLogs()module.get_lastLogs()

YModule

Returns a string with last logs of the module.

```
def get_lastLogs( )
```

This method return only logs that are still in the module.

Returns :

a string with last logs of the module. On failure, throws an exception or returns YAPI_INVALID_STRING.

module->get_logicalName()	YModule
module->logicalName()module.get_logicalName()	

Returns the logical name of the module.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the module

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

module→get_luminosity()

YModule

module→luminosity()module.get_luminosity()

Returns the luminosity of the module informative leds (from 0 to 100).

```
def get_luminosity( )
```

Returns :

an integer corresponding to the luminosity of the module informative leds (from 0 to 100)

On failure, throws an exception or returns Y_LUMINOSITY_INVALID.

module→get_persistentSettings()
module→persistentSettings()
module.get_persistentSettings()

YModule

Returns the current state of persistent module settings.

```
def get_persistentSettings( )
```

Returns :

a value among Y_PERSISTENTSETTINGS_LOADED, Y_PERSISTENTSETTINGS_SAVED and Y_PERSISTENTSETTINGS_MODIFIED corresponding to the current state of persistent module settings

On failure, throws an exception or returns Y_PERSISTENTSETTINGS_INVALID.

module→get_productId() **YModule**
module→productId()module.get_productId()

Returns the USB device identifier of the module.

```
def get_productId( )
```

Returns :

an integer corresponding to the USB device identifier of the module

On failure, throws an exception or returns Y_PRODUCTID_INVALID.

module->get_productName()	YModule
module->productName()module.get_productName()	

Returns the commercial name of the module, as set by the factory.

```
def get_productName( )
```

Returns :

a string corresponding to the commercial name of the module, as set by the factory

On failure, throws an exception or returns Y_PRODUCTNAME_INVALID.

module→get_productRelease()
module→productRelease()
module.get_productRelease()

YModule

Returns the hardware release version of the module.

```
def get_productRelease( )
```

Returns :

an integer corresponding to the hardware release version of the module

On failure, throws an exception or returns Y_PRODUCTRELEASE_INVALID.

module->get_rebootCountdown()
module->rebootCountdown()
module.get_rebootCountdown()

YModule

Returns the remaining number of seconds before the module restarts, or zero when no reboot has been scheduled.

```
def get_rebootCountdown( )
```

Returns :

an integer corresponding to the remaining number of seconds before the module restarts, or zero when no reboot has been scheduled

On failure, throws an exception or returns Y_REBOOTCOUNTDOWN_INVALID.

module→get_serialNumber() **YModule**
module→serialNumber()module.get_serialNumber()

Returns the serial number of the module, as set by the factory.

```
def get_serialNumber( )
```

Returns :

a string corresponding to the serial number of the module, as set by the factory

On failure, throws an exception or returns Y_SERIALNUMBER_INVALID.

module->get_upTime()	YModule
module->upTime()module.get_upTime()	

Returns the number of milliseconds spent since the module was powered on.

```
def get_upTime( )
```

Returns :

an integer corresponding to the number of milliseconds spent since the module was powered on

On failure, throws an exception or returns Y_UPTIME_INVALID.

module→get_usbCurrent() **YModule**
module→usbCurrent()module.get_usbCurrent()

Returns the current consumed by the module on the USB bus, in milli-amps.

```
def get_usbCurrent( )
```

Returns :

an integer corresponding to the current consumed by the module on the USB bus, in milli-amps

On failure, throws an exception or returns Y_USBCURRENT_INVALID.

module→get(userData)**YModule****module→userData()module.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

module→get_userVar()
module→userVar()module.get_userVar()

YModule

Returns the value previously stored in this attribute.

```
def get_userVar( )
```

On startup and after a device reboot, the value is always reset to zero.

Returns :

an integer corresponding to the value previously stored in this attribute

On failure, throws an exception or returns Y_USERVAR_INVALID.

module→isOnline()|module.isOnline()**YModule**

Checks if the module is currently reachable, without raising any error.

```
def isOnline( )
```

If there are valid cached values for the module, that have not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the requested module.

Returns :

`true` if the module can be reached, and `false` otherwise

module→load()module.load()**YModule**

Preloads the module cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all module attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded module parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

module→nextModule()module.nextModule()**YModule**

Continues the module enumeration started using `yFirstModule()`.

```
def nextModule( )
```

Returns :

a pointer to a `YModule` object, corresponding to the next module found, or a `null` pointer if there are no more modules to enumerate.

module→reboot()module.reboot()**YModule**

Schedules a simple module reboot after the given number of seconds.

```
def reboot( secBeforeReboot )
```

Parameters :

secBeforeReboot number of seconds before rebooting

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

**module→registerLogCallback()
module.registerLogCallback()****YModule**

Registers a device log callback function.

```
def registerLogCallback( callback)
```

This callback will be called each time that a module sends a new log message. Mostly useful to debug a Yoctopuce module.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the module object that emitted the log message, and the character string containing the log.

module→revertFromFlash()
module.revertFromFlash()

YModule

Reloads the settings stored in the nonvolatile memory, as when the module is powered on.

```
def revertFromFlash( )
```

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

module→saveToFlash()module.saveToFlash()**YModule**

Saves current settings in the nonvolatile memory of the module.

```
def saveToFlash( )
```

Warning: the number of allowed save operations during a module life is limited (about 100000 cycles).
Do not call this function within a loop.

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

module→set_allSettings() **YModule**
module→setAllSettings()module.set_allSettings()

Restore all the setting of the module.

```
def set_allSettings( settings)
```

Useful to restore all the logical name and calibrations parameters of a module from a backup.

Parameters :

settings a binary buffer with all settings.

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

module->set_beacon()	YModule
module->setBeacon()module.set_beacon()	

Turns on or off the module localization beacon.

```
def set_beacon( newval)
```

Parameters :

newval either Y_BEACON_OFF or Y_BEACON_ON

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

module->set_logicalName()	YModule
module->setLogicalName() module.set_logicalName()	

Changes the logical name of the module.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the module

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

module->set_luminosity()	YModule
module->setLuminosity()	module.set_luminosity()

Changes the luminosity of the module informative leds.

```
def set_luminosity( newval)
```

The parameter is a value between 0 and 100. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval an integer corresponding to the luminosity of the module informative leds

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

module→set(userData) **YModule**
module→setUserData()**module.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

module->set_userVar()	YModule
module->setUserVar()module.set_userVar()	

Returns the value previously stored in this attribute.

```
def set_userVar( newval )
```

On startup and after a device reboot, the value is always reset to zero.

Parameters :

newval an integer

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

module→triggerFirmwareUpdate()
module.triggerFirmwareUpdate()

YModule

Schedules a module reboot into special firmware update mode.

```
def triggerFirmwareUpdate( secBeforeReboot)
```

Parameters :

secBeforeReboot number of seconds before rebooting

Returns :

`YAPI_SUCCESS` when the call succeeds.

On failure, throws an exception or returns a negative error code.

module→updateFirmware()module.updateFirmware()**YModule**

Prepare a firmware upgrade of the module.

```
def updateFirmware( path)
```

This method return a object YFirmwareUpdate which will handle the firmware upgrade process.

Parameters :

path the path of the byn file to use.

Returns :

: A object YFirmwareUpdate.

3.27. Motor function interface

Yoctopuce application programming interface allows you to drive the power sent to the motor to make it turn both ways, but also to drive accelerations and decelerations. The motor will then accelerate automatically: you will not have to monitor it. The API also allows to slow down the motor by shortening its terminals: the motor will then act as an electromagnetic brake.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_motor.js'></script>
nodejs var yoctolib = require('yoctolib');
var YMotor = yoctolib.YMotor;
php require_once('yocto_motor.php');
cpp #include "yocto_motor.h"
m #import "yocto_motor.h"
pas uses yocto_motor;
vb yocto_motor.vb
cs yocto_motor.cs
java import com.yoctopuce.YoctoAPI.YMotor;
py from yocto_motor import *

```

Global functions

yFindMotor(func)

Retrieves a motor for a given identifier.

yFirstMotor()

Starts the enumeration of motors currently accessible.

YMotor methods

motor→brakingForceMove(targetPower, delay)

Changes progressively the braking force applied to the motor for a specific duration.

motor→describe()

Returns a short text that describes unambiguously the instance of the motor in the form TYPE(NAME)=SERIAL.FUNCTIONID.

motor→drivingForceMove(targetPower, delay)

Changes progressively the power sent to the moteur for a specific duration.

motor→get_advertisedValue()

Returns the current value of the motor (no more than 6 characters).

motor→get_brakingForce()

Returns the braking force applied to the motor, as a percentage.

motor→get_cutOffVoltage()

Returns the threshold voltage under which the controller automatically switches to error state and prevents further current draw.

motor→get_drivingForce()

Returns the power sent to the motor, as a percentage between -100% and +100%.

motor→get_errorMessage()

Returns the error message of the latest error with the motor.

motor→get_errorType()

Returns the numerical error code of the latest error with the motor.

motor→get_failSafeTimeout()

Returns the delay in milliseconds allowed for the controller to run autonomously without receiving any instruction from the control process.

<code>motor->get_frequency()</code>	Returns the PWM frequency used to control the motor.
<code>motor->get_friendlyName()</code>	Returns a global identifier of the motor in the format MODULE_NAME . FUNCTION_NAME.
<code>motor->get_functionDescriptor()</code>	Returns a unique identifier of type YFUN_DESCR corresponding to the function.
<code>motor->get_functionId()</code>	Returns the hardware identifier of the motor, without reference to the module.
<code>motor->get_hardwareId()</code>	Returns the unique hardware identifier of the motor in the form SERIAL . FUNCTIONID.
<code>motor->get_logicalName()</code>	Returns the logical name of the motor.
<code>motor->get_module()</code>	Gets the YModule object for the device on which the function is located.
<code>motor->get_module_async(callback, context)</code>	Gets the YModule object for the device on which the function is located (asynchronous version).
<code>motor->get_motorStatus()</code>	Return the controller state.
<code>motor->get_overCurrentLimit()</code>	Returns the current threshold (in mA) above which the controller automatically switches to error state.
<code>motor->get_starterTime()</code>	Returns the duration (in ms) during which the motor is driven at low frequency to help it start up.
<code>motor->get(userData)</code>	Returns the value of the userData attribute, as previously stored using method <code>set(userData)</code> .
<code>motor->isOnline()</code>	Checks if the motor is currently reachable, without raising any error.
<code>motor->isOnline_async(callback, context)</code>	Checks if the motor is currently reachable, without raising any error (asynchronous version).
<code>motor->keepALive()</code>	Rearms the controller failsafe timer.
<code>motor->load(msValidity)</code>	Preloads the motor cache with a specified validity duration.
<code>motor->load_async(msValidity, callback, context)</code>	Preloads the motor cache with a specified validity duration (asynchronous version).
<code>motor->nextMotor()</code>	Continues the enumeration of motors started using <code>yFirstMotor()</code> .
<code>motor->registerValueCallback(callback)</code>	Registers the callback function that is invoked on every change of advertised value.
<code>motor->resetStatus()</code>	Reset the controller state to IDLE.
<code>motor->set_brakingForce(newval)</code>	Changes immediately the braking force applied to the motor (in percents).
<code>motor->set_cutOffVoltage(newval)</code>	Changes the threshold voltage under which the controller automatically switches to error state and prevents further current draw.

3. Reference

[motor→set_drivingForce\(newval\)](#)

Changes immediately the power sent to the motor.

[motor→set_failSafeTimeout\(newval\)](#)

Changes the delay in milliseconds allowed for the controller to run autonomously without receiving any instruction from the control process.

[motor→set_frequency\(newval\)](#)

Changes the PWM frequency used to control the motor.

[motor→set_logicalName\(newval\)](#)

Changes the logical name of the motor.

[motor→set_overCurrentLimit\(newval\)](#)

Changes the current threshold (in mA) above which the controller automatically switches to error state.

[motor→set_starterTime\(newval\)](#)

Changes the duration (in ms) during which the motor is driven at low frequency to help it start up.

[motor→set_userData\(data\)](#)

Stores a user context provided as argument in the userData attribute of the function.

[motor→wait_async\(callback, context\)](#)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YMotor.FindMotor()**YMotor****yFindMotor()YMotor.FindMotor()**

Retrieves a motor for a given identifier.

```
def FindMotor( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the motor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YMotor.isOnline()` to test if the motor is indeed online at a given time. In case of ambiguity when looking for a motor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the motor

Returns :

a `YMotor` object allowing you to drive the motor.

YMotor.FirstMotor()

YMotor

yFirstMotor()YMotor.FirstMotor()

Starts the enumeration of motors currently accessible.

```
def FirstMotor( )
```

Use the method `YMotor.nextMotor()` to iterate on next motors.

Returns :

a pointer to a `YMotor` object, corresponding to the first motor currently online, or a `null` pointer if there are none.

motor→brakingForceMove()
motor.brakingForceMove()**YMotor**

Changes progressively the braking force applied to the motor for a specific duration.

```
def brakingForceMove( targetPower, delay)
```

Parameters :

targetPower desired braking force, in percents

delay duration (in ms) of the transition

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

motor→describe()motor.describe()**YMotor**

Returns a short text that describes unambiguously the instance of the motor in the form TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the motor (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

motor→drivingForceMove()
motor.drivingForceMove()**YMotor**

Changes progressively the power sent to the moteur for a specific duration.

```
def drivingForceMove( targetPower, delay)
```

Parameters :

targetPower desired motor power, in percents (between -100% and +100%)

delay duration (in ms) of the transition

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

motor→get_advertisedValue()
motor→advertisedValue()
motor.get_advertisedValue()

YMotor

Returns the current value of the motor (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the motor (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

motor→get_brakingForce()**YMotor****motor→brakingForce()motor.get_brakingForce()**

Returns the braking force applied to the motor, as a percentage.

```
def get_brakingForce( )
```

The value 0 corresponds to no braking (free wheel).

Returns :

a floating point number corresponding to the braking force applied to the motor, as a percentage

On failure, throws an exception or returns Y_BRAKINGFORCE_INVALID.

motor→get_cutOffVoltage()**YMotor****motor→cutOffVoltage()motor.get_cutOffVoltage()**

Returns the threshold voltage under which the controller automatically switches to error state and prevents further current draw.

```
def get_cutOffVoltage( )
```

This setting prevents damage to a battery that can occur when drawing current from an "empty" battery.

Returns :

a floating point number corresponding to the threshold voltage under which the controller automatically switches to error state and prevents further current draw

On failure, throws an exception or returns Y_CUTOFFVOLTAGE_INVALID.

motor→get_drivingForce()**YMotor****motor→drivingForce()motor.get_drivingForce()**

Returns the power sent to the motor, as a percentage between -100% and +100%.

```
def get_drivingForce( )
```

Returns :

a floating point number corresponding to the power sent to the motor, as a percentage between -100% and +100%

On failure, throws an exception or returns Y_DRIVINGFORCE_INVALID.

motor→getErrorMessage()

YMotor

motor→errorMessage()motor.getErrorMessage()

Returns the error message of the latest error with the motor.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the motor object

motor→get_errorType()**YMotor****motor→errorType()motor.get_errorType()**

Returns the numerical error code of the latest error with the motor.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the motor object

motor→get_failSafeTimeout() YMotor
motor→failSafeTimeout()motor.get_failSafeTimeout()

Returns the delay in milliseconds allowed for the controller to run autonomously without receiving any instruction from the control process.

```
def get_failSafeTimeout( )
```

When this delay has elapsed, the controller automatically stops the motor and switches to FAILSAFE error. Failsafe security is disabled when the value is zero.

Returns :

an integer corresponding to the delay in milliseconds allowed for the controller to run autonomously without receiving any instruction from the control process

On failure, throws an exception or returns Y_FAILSAFETIMEOUT_INVALID.

motor→get_frequency()**YMotor****motor→frequency()motor.get_frequency()**

Returns the PWM frequency used to control the motor.

```
def get_frequency( )
```

Returns :

a floating point number corresponding to the PWM frequency used to control the motor

On failure, throws an exception or returns Y_FREQUENCY_INVALID.

motor→get_friendlyName()	YMotor
motor→friendlyName()motor.get_friendlyName()	

Returns a global identifier of the motor in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the motor if they are defined, otherwise the serial number of the module and the hardware identifier of the motor (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the motor using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

motor→get_functionDescriptor()
motor→functionDescriptor()
motor.get_functionDescriptor()

YMotor

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

motor→get_functionId()

YMotor

motor→functionId()motor.get_functionId()

Returns the hardware identifier of the motor, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the motor (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

motor→get_hardwareId()**YMotor****motor→hardwareId()motor.get_hardwareId()**

Returns the unique hardware identifier of the motor in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the motor (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the motor (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

motor→get_logicalName()

YMotor

motor→logicalName()motor.get_logicalName()

Returns the logical name of the motor.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the motor.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

motor→get_module()**YMotor****motor→module()motor.get_module()**

Gets the YModule object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

motor→get_motorStatus()	YMotor
motor→motorStatus()motor.get_motorStatus()	

Return the controller state.

```
def get_motorStatus( )
```

Possible states are: IDLE when the motor is stopped/in free wheel, ready to start; FORWD when the controller is driving the motor forward; BACKWD when the controller is driving the motor backward; BRAKE when the controller is braking; LOVOLT when the controller has detected a low voltage condition; HICURR when the controller has detected an overcurrent condition; HIHEAT when the controller has detected an overheat condition; FAILSF when the controller switched on the failsafe security.

When an error condition occurred (LOVOLT, HICURR, HIHEAT, FAILSF), the controller status must be explicitly reset using the `resetStatus` function.

Returns :

a value among Y_MOTORSTATUS_IDLE, Y_MOTORSTATUS_BRAKE,
Y_MOTORSTATUS_FORWD, Y_MOTORSTATUS_BACKWD, Y_MOTORSTATUS_LOVOLT,
Y_MOTORSTATUS_HICURR, Y_MOTORSTATUS_HIHEAT and Y_MOTORSTATUS_FAILSF

On failure, throws an exception or returns Y_MOTORSTATUS_INVALID.

motor→get_overCurrentLimit()
motor→overCurrentLimit()
motor.get_overCurrentLimit()

YMotor

Returns the current threshold (in mA) above which the controller automatically switches to error state.

```
def get_overCurrentLimit( )
```

A zero value means that there is no limit.

Returns :

an integer corresponding to the current threshold (in mA) above which the controller automatically switches to error state

On failure, throws an exception or returns Y_OVERCURRENTLIMIT_INVALID.

motor→get_starterTime()

YMotor

motor→starterTime()motor.get_starterTime()

Returns the duration (in ms) during which the motor is driven at low frequency to help it start up.

```
def get_starterTime( )
```

Returns :

an integer corresponding to the duration (in ms) during which the motor is driven at low frequency to help it start up

On failure, throws an exception or returns Y_STARTERTIME_INVALID.

motor→get(userData)**YMotor****motor→userData()motor.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

motor→isOnline()motor.isOnline()**YMotor**

Checks if the motor is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the motor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the motor.

Returns :

true if the motor can be reached, and false otherwise

motor→keepALive()motor.keepALive()**YMotor**

Rearms the controller failsafe timer.

```
def keepALive( )
```

When the motor is running and the failsafe feature is active, this function should be called periodically to prove that the control process is running properly. Otherwise, the motor is automatically stopped after the specified timeout. Calling a motor `set` function implicitly rearms the failsafe timer.

motor→load()motor.load()**YMotor**

Preloads the motor cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

motor→nextMotor()motor.nextMotor()**YMotor**

Continues the enumeration of motors started using `yFirstMotor()`.

```
def nextMotor( )
```

Returns :

a pointer to a `YMotor` object, corresponding to a motor currently online, or a null pointer if there are no more motors to enumerate.

motor→registerValueCallback()
motor.registerValueCallback()**YMotor**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

motor→resetStatus()motor.resetStatus()**YMotor**

Reset the controller state to IDLE.

```
def resetStatus( )
```

This function must be invoked explicitly after any error condition is signaled.

motor→set_brakingForce() YMotor
motor→setBrakingForce()motor.set_brakingForce()

Changes immediately the braking force applied to the motor (in percents).

```
def set_brakingForce( newval)
```

The value 0 corresponds to no braking (free wheel). When the braking force is changed, the driving power is set to zero. The value is a percentage.

Parameters :

newval a floating point number corresponding to immediately the braking force applied to the motor (in percents)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

motor→set_cutOffVoltage()**YMotor****motor→setCutOffVoltage()motor.set_cutOffVoltage()**

Changes the threshold voltage under which the controller automatically switches to error state and prevents further current draw.

```
def set_cutOffVoltage( newval)
```

This setting prevent damage to a battery that can occur when drawing current from an "empty" battery. Note that whatever the cutoff threshold, the controller switches to undervoltage error state if the power supply goes under 3V, even for a very brief time.

Parameters :

newval a floating point number corresponding to the threshold voltage under which the controller automatically switches to error state and prevents further current draw

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

motor→set_drivingForce()	YMotor
motor→setDrivingForce()motor.set_drivingForce()	

Changes immediately the power sent to the motor.

```
def set_drivingForce( newval )
```

The value is a percentage between -100% to 100%. If you want go easy on your mechanics and avoid excessive current consumption, try to avoid brutal power changes. For example, immediate transition from forward full power to reverse full power is a very bad idea. Each time the driving power is modified, the braking power is set to zero.

Parameters :

newval a floating point number corresponding to immediately the power sent to the motor

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

motor→set_failSafeTimeout()
motor→setFailSafeTimeout()
motor.set_failSafeTimeout()

YMotor

Changes the delay in milliseconds allowed for the controller to run autonomously without receiving any instruction from the control process.

```
def set_failSafeTimeout( newval )
```

When this delay has elapsed, the controller automatically stops the motor and switches to FAILSAFE error. Failsafe security is disabled when the value is zero.

Parameters :

newval an integer corresponding to the delay in milliseconds allowed for the controller to run autonomously without receiving any instruction from the control process

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

motor→set_frequency() YMotor
motor→setFrequency()motor.set_frequency()

Changes the PWM frequency used to control the motor.

```
def set_frequency( newval)
```

Low frequency is usually more efficient and may help the motor to start, but an audible noise might be generated. A higher frequency reduces the noise, but more energy is converted into heat.

Parameters :

newval a floating point number corresponding to the PWM frequency used to control the motor

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

motor→set_logicalName()
motor→setLogicalName()motor.set_logicalName()

YMotor

Changes the logical name of the motor.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the motor.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

motor→set_overCurrentLimit()
motor→setOverCurrentLimit()
motor.set_overCurrentLimit()

YMotor

Changes the current threshold (in mA) above which the controller automatically switches to error state.

```
def set_overCurrentLimit( newval)
```

A zero value means that there is no limit. Note that whatever the current limit is, the controller switches to OVERCURRENT status if the current goes above 32A, even for a very brief time.

Parameters :

newval an integer corresponding to the current threshold (in mA) above which the controller automatically switches to error state

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

motor→set_starterTime()**YMotor****motor→setStarterTime()motor.set_starterTime()**

Changes the duration (in ms) during which the motor is driven at low frequency to help it start up.

```
def set_starterTime( newval)
```

Parameters :

newval an integer corresponding to the duration (in ms) during which the motor is driven at low frequency to help it start up

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

motor→set(userData)

YMotor

motor→setUserData()motor.set(userData)

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.28. Network function interface

YNetwork objects provide access to TCP/IP parameters of Yoctopuce modules that include a built-in network interface.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_network.js'></script>
node.js	var yoctolib = require('yoctolib');
	var YNetwork = yoctolib.YNetwork;
php	require_once('yocto_network.php');
cpp	#include "yocto_network.h"
m	#import "yocto_network.h"
pas	uses yocto_network;
vb	yocto_network.vb
cs	yocto_network.cs
java	import com.yoctopuce.YoctoAPI.YNetwork;
py	from yocto_network import *

Global functions

yFindNetwork(func)

Retrieves a network interface for a given identifier.

yFirstNetwork()

Starts the enumeration of network interfaces currently accessible.

YNetwork methods

network→callbackLogin(username, password)

Connects to the notification callback and saves the credentials required to log into it.

network→describe()

Returns a short text that describes unambiguously the instance of the network interface in the form TYPE (NAME) = SERIAL . FUNCTIONID.

network→get_adminPassword()

Returns a hash string if a password has been set for user "admin", or an empty string otherwise.

network→get_advertisedValue()

Returns the current value of the network interface (no more than 6 characters).

network→get_callbackCredentials()

Returns a hashed version of the notification callback credentials if set, or an empty string otherwise.

network→get_callbackEncoding()

Returns the encoding standard to use for representing notification values.

network→get_callbackMaxDelay()

Returns the maximum waiting time between two callback notifications, in seconds.

network→get_callbackMethod()

Returns the HTTP method used to notify callbacks for significant state changes.

network→get_callbackMinDelay()

Returns the minimum waiting time between two callback notifications, in seconds.

network→get_callbackUrl()

Returns the callback URL to notify of significant state changes.

network→get_discoverable()

Returns the activation state of the multicast announce protocols to allow easy discovery of the module in the network neighborhood (uPnP/Bonjour protocol).

3. Reference

network→get_errorMessage()	Returns the error message of the latest error with the network interface.
network→get_errorType()	Returns the numerical error code of the latest error with the network interface.
network→get_friendlyName()	Returns a global identifier of the network interface in the format MODULE_NAME . FUNCTION_NAME.
network→get_functionDescriptor()	Returns a unique identifier of type YFUN_DESCR corresponding to the function.
network→get_functionId()	Returns the hardware identifier of the network interface, without reference to the module.
network→get_hardwareId()	Returns the unique hardware identifier of the network interface in the form SERIAL . FUNCTIONID.
network→get_ipAddress()	Returns the IP address currently in use by the device.
network→get_logicalName()	Returns the logical name of the network interface.
network→get_macAddress()	Returns the MAC address of the network interface.
network→get_module()	Gets the YModule object for the device on which the function is located.
network→get_module_async(callback, context)	Gets the YModule object for the device on which the function is located (asynchronous version).
network→get_poeCurrent()	Returns the current consumed by the module from Power-over-Ethernet (PoE), in milli-amps.
network→get_primaryDNS()	Returns the IP address of the primary name server to be used by the module.
network→get_readiness()	Returns the current established working mode of the network interface.
network→get_router()	Returns the IP address of the router on the device subnet (default gateway).
network→get_secondaryDNS()	Returns the IP address of the secondary name server to be used by the module.
network→get_subnetMask()	Returns the subnet mask currently used by the device.
network→get_userData()	Returns the value of the userData attribute, as previously stored using method set(userData).
network→get_userPassword()	Returns a hash string if a password has been set for "user" user, or an empty string otherwise.
network→get_wwwWatchdogDelay()	Returns the allowed downtime of the WWW link (in seconds) before triggering an automated reboot to try to recover Internet connectivity.
network→isOnline()	Checks if the network interface is currently reachable, without raising any error.
network→isOnline_async(callback, context)	Checks if the network interface is currently reachable, without raising any error (asynchronous version).

network→load(msValidity)

Preloads the network interface cache with a specified validity duration.

network→load_async(msValidity, callback, context)

Preloads the network interface cache with a specified validity duration (asynchronous version).

network→nextNetwork()

Continues the enumeration of network interfaces started using `yFirstNetwork()`.

network→ping(host)

Pings `str_host` to test the network connectivity.

network→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

network→set_adminPassword(newval)

Changes the password for the "admin" user.

network→set_callbackCredentials(newval)

Changes the credentials required to connect to the callback address.

network→set_callbackEncoding(newval)

Changes the encoding standard to use for representing notification values.

network→set_callbackMaxDelay(newval)

Changes the maximum waiting time between two callback notifications, in seconds.

network→set_callbackMethod(newval)

Changes the HTTP method used to notify callbacks for significant state changes.

network→set_callbackMinDelay(newval)

Changes the minimum waiting time between two callback notifications, in seconds.

network→set_callbackUrl(newval)

Changes the callback URL to notify significant state changes.

network→set_discoverable(newval)

Changes the activation state of the multicast announce protocols to allow easy discovery of the module in the network neighborhood (uPnP/Bonjour protocol).

network→set_logicalName(newval)

Changes the logical name of the network interface.

network→set_primaryDNS(newval)

Changes the IP address of the primary name server to be used by the module.

network→set_secondaryDNS(newval)

Changes the IP address of the secondary name server to be used by the module.

network→set_userData(data)

Stores a user context provided as argument in the `userData` attribute of the function.

network→set_userPassword(newval)

Changes the password for the "user" user.

network→set_wwwWatchdogDelay(newval)

Changes the allowed downtime of the WWW link (in seconds) before triggering an automated reboot to try to recover Internet connectivity.

network→useDHCP(fallbackIpAddr, fallbackSubnetMaskLen, fallbackRouter)

Changes the configuration of the network interface to enable the use of an IP address received from a DHCP server.

network→useStaticIP(ipAddress, subnetMaskLen, router)

Changes the configuration of the network interface to use a static IP address.

network→wait_async(callback, context)

3. Reference

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YNetwork.FindNetwork()**YNetwork****yFindNetwork()YNetwork.FindNetwork()**

Retrieves a network interface for a given identifier.

```
def FindNetwork( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the network interface is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YNetwork.isOnline()` to test if the network interface is indeed online at a given time. In case of ambiguity when looking for a network interface by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the network interface

Returns :

a `YNetwork` object allowing you to drive the network interface.

YNetwork.FirstNetwork()

YNetwork

yFirstNetwork()YNetwork.FirstNetwork()

Starts the enumeration of network interfaces currently accessible.

```
def FirstNetwork( )
```

Use the method `YNetwork.nextNetwork()` to iterate on next network interfaces.

Returns :

a pointer to a `YNetwork` object, corresponding to the first network interface currently online, or a null pointer if there are none.

network→callbackLogin()network.callbackLogin()**YNetwork**

Connects to the notification callback and saves the credentials required to log into it.

```
def callbackLogin( username, password)
```

The password is not stored into the module, only a hashed copy of the credentials are saved. Remember to call the saveToFlash() method of the module if the modification must be kept.

Parameters :

username username required to log to the callback
password password required to log to the callback

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→describe()network.describe()**YNetwork**

Returns a short text that describes unambiguously the instance of the network interface in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the network interface (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

network→get_adminPassword()
network→adminPassword()
network.get_adminPassword()

YNetwork

Returns a hash string if a password has been set for user "admin", or an empty string otherwise.

```
def get_adminPassword( )
```

Returns :

a string corresponding to a hash string if a password has been set for user "admin", or an empty string otherwise

On failure, throws an exception or returns Y_ADMINPASSWORD_INVALID.

network→get_advertisedValue()
network→advertisedValue()
network.get_advertisedValue()

YNetwork

Returns the current value of the network interface (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the network interface (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

network→get_callbackCredentials()
network→callbackCredentials()
network.get_callbackCredentials()

YNetwork

Returns a hashed version of the notification callback credentials if set, or an empty string otherwise.

```
def get_callbackCredentials( )
```

Returns :

a string corresponding to a hashed version of the notification callback credentials if set, or an empty string otherwise

On failure, throws an exception or returns Y_CALLBACKCREDENTIALS_INVALID.

network→get_callbackEncoding()
network→callbackEncoding()
network.get_callbackEncoding()

YNetwork

Returns the encoding standard to use for representing notification values.

```
def get_callbackEncoding( )
```

Returns :

a value among Y_CALLBACKENCODING_FORM, Y_CALLBACKENCODING_JSON, Y_CALLBACKENCODING_JSON_ARRAY, Y_CALLBACKENCODING_CSV and Y_CALLBACKENCODING_YOCTO_API corresponding to the encoding standard to use for representing notification values

On failure, throws an exception or returns Y_CALLBACKENCODING_INVALID.

network→get_callbackMaxDelay()
network→callbackMaxDelay()
network.get_callbackMaxDelay()

YNetwork

Returns the maximum waiting time between two callback notifications, in seconds.

```
def get_callbackMaxDelay( )
```

Returns :

an integer corresponding to the maximum waiting time between two callback notifications, in seconds

On failure, throws an exception or returns Y_CALLBACKMAXDELAY_INVALID.

network→get_callbackMethod()
network→callbackMethod()
network.get_callbackMethod()

YNetwork

Returns the HTTP method used to notify callbacks for significant state changes.

```
def get_callbackMethod( )
```

Returns :

a value among Y_CALLBACKMETHOD_POST, Y_CALLBACKMETHOD_GET and Y_CALLBACKMETHOD_PUT corresponding to the HTTP method used to notify callbacks for significant state changes

On failure, throws an exception or returns Y_CALLBACKMETHOD_INVALID.

network→get_callbackMinDelay()
network→callbackMinDelay()
network.get_callbackMinDelay()

YNetwork

Returns the minimum waiting time between two callback notifications, in seconds.

```
def get_callbackMinDelay( )
```

Returns :

an integer corresponding to the minimum waiting time between two callback notifications, in seconds

On failure, throws an exception or returns Y_CALLBACKMINDELAY_INVALID.

network→get_callbackUrl()

YNetwork

network→callbackUrl()network.get_callbackUrl()

Returns the callback URL to notify of significant state changes.

```
def get_callbackUrl( )
```

Returns :

a string corresponding to the callback URL to notify of significant state changes

On failure, throws an exception or returns Y_CALLBACKURL_INVALID.

network→get_discoverable()	YNetwork
network→discoverable()network.get_discoverable()	

Returns the activation state of the multicast announce protocols to allow easy discovery of the module in the network neighborhood (uPnP/Bonjour protocol).

```
def get_discoverable( )
```

Returns :

either Y_DISCOVERABLE_FALSE or Y_DISCOVERABLE_TRUE, according to the activation state of the multicast announce protocols to allow easy discovery of the module in the network neighborhood (uPnP/Bonjour protocol)

On failure, throws an exception or returns Y_DISCOVERABLE_INVALID.

network→get_errorMessage()
network→errorMessage()
network.get_errorMessage()

YNetwork

Returns the error message of the latest error with the network interface.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the network interface object

network→get_errorType()**YNetwork****network→errorType()network.get_errorType()**

Returns the numerical error code of the latest error with the network interface.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the network interface object

network→get_friendlyName()**YNetwork****network→friendlyName()network.get_friendlyName()**

Returns a global identifier of the network interface in the format MODULE_NAME.FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the network interface if they are defined, otherwise the serial number of the module and the hardware identifier of the network interface (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the network interface using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

network→get_functionDescriptor()
network→functionDescriptor()
network.get_functionDescriptor()

YNetwork

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

network→get_functionId()

YNetwork

network→functionId()network.get_functionId()

Returns the hardware identifier of the network interface, without reference to the module.

```
def get_functionId( )
```

For example relay1

Returns :

a string that identifies the network interface (ex: relay1)

On failure, throws an exception or returns Y_FUNCTIONID_INVALID.

network→get_hardwareId()**YNetwork****network→hardwareId()network.get_hardwareId()**

Returns the unique hardware identifier of the network interface in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the network interface (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the network interface (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

network→get_ipAddress()

YNetwork

network→ipAddress()network.get_ipAddress()

Returns the IP address currently in use by the device.

```
def get_ipAddress( )
```

The address may have been configured statically, or provided by a DHCP server.

Returns :

a string corresponding to the IP address currently in use by the device

On failure, throws an exception or returns Y_IPADDRESS_INVALID.

network→get_logicalName()	YNetwork
network→logicalName()network.get_logicalName()	

Returns the logical name of the network interface.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the network interface.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

network→get_macAddress() YNetwork
network→macAddress()network.get_macAddress()

Returns the MAC address of the network interface.

```
def get_macAddress( )
```

The MAC address is also available on a sticker on the module, in both numeric and barcode forms.

Returns :

a string corresponding to the MAC address of the network interface

On failure, throws an exception or returns Y_MACADDRESS_INVALID.

network→get_module()**YNetwork****network→module()network.get_module()**

Gets the YModule object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

network→get_poeCurrent()**YNetwork****network→poeCurrent()network.get_poeCurrent()**

Returns the current consumed by the module from Power-over-Ethernet (PoE), in milli-amps.

```
def get_poeCurrent( )
```

The current consumption is measured after converting PoE source to 5 Volt, and should never exceed 1800 mA.

Returns :

an integer corresponding to the current consumed by the module from Power-over-Ethernet (PoE), in milli-amps

On failure, throws an exception or returns Y_POECURRENT_INVALID.

network→get_primaryDNS()**YNetwork****network→primaryDNS()network.get_primaryDNS()**

Returns the IP address of the primary name server to be used by the module.

```
def get_primaryDNS( )
```

Returns :

a string corresponding to the IP address of the primary name server to be used by the module

On failure, throws an exception or returns Y_PRIMARYDNS_INVALID.

network→get_readiness()**YNetwork****network→readiness()network.get_readiness()**

Returns the current established working mode of the network interface.

```
def get_readiness( )
```

Level zero (DOWN_0) means that no hardware link has been detected. Either there is no signal on the network cable, or the selected wireless access point cannot be detected. Level 1 (LIVE_1) is reached when the network is detected, but is not yet connected. For a wireless network, this shows that the requested SSID is present. Level 2 (LINK_2) is reached when the hardware connection is established. For a wired network connection, level 2 means that the cable is attached at both ends. For a connection to a wireless access point, it shows that the security parameters are properly configured. For an ad-hoc wireless connection, it means that there is at least one other device connected on the ad-hoc network. Level 3 (DHCP_3) is reached when an IP address has been obtained using DHCP. Level 4 (DNS_4) is reached when the DNS server is reachable on the network. Level 5 (WWW_5) is reached when global connectivity is demonstrated by properly loading the current time from an NTP server.

Returns :

a value among Y_READINESS_DOWN, Y_READINESS_EXISTS, Y_READINESS_LINKED, Y_READINESS_LAN_OK and Y_READINESS_WWW_OK corresponding to the current established working mode of the network interface

On failure, throws an exception or returns Y_READINESS_INVALID.

network→get_router()**YNetwork****network→router()network.get_router()**

Returns the IP address of the router on the device subnet (default gateway).

```
def get_router( )
```

Returns :

a string corresponding to the IP address of the router on the device subnet (default gateway)

On failure, throws an exception or returns Y_ROUTER_INVALID.

network→get_secondaryDNS()
network→secondaryDNS()
network.get_secondaryDNS()

YNetwork

Returns the IP address of the secondary name server to be used by the module.

```
def get_secondaryDNS( )
```

Returns :

a string corresponding to the IP address of the secondary name server to be used by the module

On failure, throws an exception or returns Y_SECONDARYDNS_INVALID.

network→get_subnetMask()	YNetwork
network→subnetMask()network.get_subnetMask()	

Returns the subnet mask currently used by the device.

```
def get_subnetMask( )
```

Returns :

a string corresponding to the subnet mask currently used by the device

On failure, throws an exception or returns Y_SUBNETMASK_INVALID.

network→get(userData)

YNetwork

network→userData()network.get(userData())

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

network→get_userPassword()
network→userPassword()
network.get_userPassword()

YNetwork

Returns a hash string if a password has been set for "user" user, or an empty string otherwise.

```
def get_userPassword( )
```

Returns :

a string corresponding to a hash string if a password has been set for "user" user, or an empty string otherwise

On failure, throws an exception or returns Y_USERPASSWORD_INVALID.

network→get_wwwWatchdogDelay()
network→wwwWatchdogDelay()
network.get_wwwWatchdogDelay()

YNetwork

Returns the allowed downtime of the WWW link (in seconds) before triggering an automated reboot to try to recover Internet connectivity.

```
def get_wwwWatchdogDelay( )
```

A zero value disables automated reboot in case of Internet connectivity loss.

Returns :

an integer corresponding to the allowed downtime of the WWW link (in seconds) before triggering an automated reboot to try to recover Internet connectivity

On failure, throws an exception or returns Y_WWWWATCHDOGDELAY_INVALID.

network→isOnline()|network.isOnline()**YNetwork**

Checks if the network interface is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the network interface in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the network interface.

Returns :

`true` if the network interface can be reached, and `false` otherwise

network→load()|network.load()**YNetwork**

Preloads the network interface cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

network→nextNetwork()network.nextNetwork()**YNetwork**

Continues the enumeration of network interfaces started using `yFirstNetwork()`.

```
def nextNetwork( )
```

Returns :

a pointer to a `YNetwork` object, corresponding to a network interface currently online, or a `null` pointer if there are no more network interfaces to enumerate.

network→ping()network.ping()**YNetwork**

Pings str_host to test the network connectivity.

```
def ping( host)
```

Sends four ICMP ECHO_REQUEST requests from the module to the target str_host. This method returns a string with the result of the 4 ICMP ECHO_REQUEST requests.

Parameters :

host the hostname or the IP address of the target

Returns :

a string with the result of the ping.

network→registerValueCallback()
network.registerValueCallback()**YNetwork**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

network→set_adminPassword()
network→setAdminPassword()
network.set_adminPassword()

YNetwork

Changes the password for the "admin" user.

```
def set_adminPassword( newval )
```

This password becomes instantly required to perform any change of the module state. If the specified value is an empty string, a password is not required anymore. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the password for the "admin" user

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_callbackCredentials()
network→setCallbackCredentials()
network.set_callbackCredentials()

YNetwork

Changes the credentials required to connect to the callback address.

```
def set_callbackCredentials( newval)
```

The credentials must be provided as returned by function `get_callbackCredentials`, in the form `username:hash`. The method used to compute the hash varies according to the authentication scheme implemented by the callback. For Basic authentication, the hash is the MD5 of the string `username:password`. For Digest authentication, the hash is the MD5 of the string `username:realm:password`. For a simpler way to configure callback credentials, use function `callbackLogin` instead. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the credentials required to connect to the callback address

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_callbackEncoding()
network→setCallbackEncoding()
network.set_callbackEncoding()

YNetwork

Changes the encoding standard to use for representing notification values.

```
def set_callbackEncoding( newval)
```

Parameters :

newval a value among Y_CALLBACKENCODING_FORM, Y_CALLBACKENCODING_JSON, Y_CALLBACKENCODING_JSON_ARRAY, Y_CALLBACKENCODING_CSV and Y_CALLBACKENCODING_YOCTO_API corresponding to the encoding standard to use for representing notification values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_callbackMaxDelay()
network→setCallbackMaxDelay()
network.set_callbackMaxDelay()

YNetwork

Changes the maximum waiting time between two callback notifications, in seconds.

```
def set_callbackMaxDelay( newval)
```

Parameters :

newval an integer corresponding to the maximum waiting time between two callback notifications, in seconds

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_callbackMethod()
network→setCallbackMethod()
network.set_callbackMethod()

YNetwork

Changes the HTTP method used to notify callbacks for significant state changes.

```
def set_callbackMethod( newval )
```

Parameters :

newval a value among Y_CALLBACKMETHOD_POST, Y_CALLBACKMETHOD_GET and Y_CALLBACKMETHOD_PUT corresponding to the HTTP method used to notify callbacks for significant state changes

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_callbackMinDelay()
network→setCallbackMinDelay()
network.set_callbackMinDelay()

YNetwork

Changes the minimum waiting time between two callback notifications, in seconds.

```
def set_callbackMinDelay( newval)
```

Parameters :

newval an integer corresponding to the minimum waiting time between two callback notifications, in seconds

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_callbackUrl() **YNetwork**
network→setCallbackUrl()network.set_callbackUrl()

Changes the callback URL to notify significant state changes.

```
def set_callbackUrl( newval)
```

Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the callback URL to notify significant state changes

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_discoverable()
network→setDiscoverable()
network.set_discoverable()

YNetwork

Changes the activation state of the multicast announce protocols to allow easy discovery of the module in the network neighborhood (uPnP/Bonjour protocol).

```
def set_discoverable( newval)
```

Parameters :

newval either `Y_DISCOVERABLE_FALSE` or `Y_DISCOVERABLE_TRUE`, according to the activation state of the multicast announce protocols to allow easy discovery of the module in the network neighborhood (uPnP/Bonjour protocol)

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_logicalName()
network→setLogicalName()
network.set_logicalName()

YNetwork

Changes the logical name of the network interface.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the network interface.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_primaryDNS()	YNetwork
network→setPrimaryDNS()network.set_primaryDNS()	

Changes the IP address of the primary name server to be used by the module.

```
def set_primaryDNS( newval)
```

When using DHCP, if a value is specified, it overrides the value received from the DHCP server. Remember to call the `saveToFlash()` method and then to reboot the module to apply this setting.

Parameters :

newval a string corresponding to the IP address of the primary name server to be used by the module

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_secondaryDNS()
network→setSecondaryDNS()
network.set_secondaryDNS()

YNetwork

Changes the IP address of the secondary name server to be used by the module.

```
def set_secondaryDNS( newval )
```

When using DHCP, if a value is specified, it overrides the value received from the DHCP server. Remember to call the `saveToFlash()` method and then to reboot the module to apply this setting.

Parameters :

newval a string corresponding to the IP address of the secondary name server to be used by the module

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set(userData)**YNetwork****network→setUserData()network.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData: Any)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

network→set_userPassword()
network→setUserPassword()
network.set_userPassword()

YNetwork

Changes the password for the "user" user.

```
def set_userPassword( newval )
```

This password becomes instantly required to perform any use of the module. If the specified value is an empty string, a password is not required anymore. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the password for the "user" user

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→set_wwwWatchdogDelay()
network→setWwwWatchdogDelay()
network.set_wwwWatchdogDelay()

YNetwork

Changes the allowed downtime of the WWW link (in seconds) before triggering an automated reboot to try to recover Internet connectivity.

```
def set_wwwWatchdogDelay( newval)
```

A zero value disables automated reboot in case of Internet connectivity loss. The smallest valid non-zero timeout is 90 seconds.

Parameters :

newval an integer corresponding to the allowed downtime of the WWW link (in seconds) before triggering an automated reboot to try to recover Internet connectivity

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

network→useDHCP()network.useDHCP()**YNetwork**

Changes the configuration of the network interface to enable the use of an IP address received from a DHCP server.

```
def useDHCP( fallbackIpAddr, fallbackSubnetMaskLen, fallbackRouter )
```

Until an address is received from a DHCP server, the module uses the IP parameters specified to this function. Remember to call the `saveToFlash()` method and then to reboot the module to apply this setting.

Parameters :

fallbackIpAddr	fallback IP address, to be used when no DHCP reply is received
fallbackSubnetMaskLen	fallback subnet mask length when no DHCP reply is received, as an integer (eg. 24 means 255.255.255.0)
fallbackRouter	fallback router IP address, to be used when no DHCP reply is received

Returns :

`YAPI_SUCCESS` when the call succeeds.

On failure, throws an exception or returns a negative error code.

network→useStaticIP()network.useStaticIP()**YNetwork**

Changes the configuration of the network interface to use a static IP address.

```
def useStaticIP( ipAddress, subnetMaskLen, router)
```

Remember to call the `saveToFlash()` method and then to reboot the module to apply this setting.

Parameters :

ipAddress device IP address

subnetMaskLen subnet mask length, as an integer (eg. 24 means 255.255.255.0)

router router IP address (default gateway)

Returns :

`YAPI_SUCCESS` when the call succeeds.

On failure, throws an exception or returns a negative error code.

3.29. OS control

The OScontrol object allows some control over the operating system running a VirtualHub. OsControl is available on the VirtualHub software only. This feature must be activated at the VirtualHub start up with -o option.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_oscontrol.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YOsControl = yoctolib.YOsControl;
php	require_once('yocto_oscontrol.php');
cpp	#include "yocto_oscontrol.h"
m	#import "yocto_oscontrol.h"
pas	uses yocto_oscontrol;
vb	yocto_oscontrol.vb
cs	yocto_oscontrol.cs
java	import com.yoctopuce.YoctoAPI.YOsControl;
py	from yocto_oscontrol import *

Global functions

yFindOsControl(func)

Retrieves OS control for a given identifier.

yFirstOsControl()

Starts the enumeration of OS control currently accessible.

YOsControl methods

oscontrol→describe()

Returns a short text that describes unambiguously the instance of the OS control in the form TYPE (NAME)=SERIAL . FUNCTIONID.

oscontrol→get_advertisedValue()

Returns the current value of the OS control (no more than 6 characters).

oscontrol→get_errorMessage()

Returns the error message of the latest error with the OS control.

oscontrol→get_errorType()

Returns the numerical error code of the latest error with the OS control.

oscontrol→get_friendlyName()

Returns a global identifier of the OS control in the format MODULE_NAME . FUNCTION_NAME.

oscontrol→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

oscontrol→get_functionId()

Returns the hardware identifier of the OS control, without reference to the module.

oscontrol→get_hardwareId()

Returns the unique hardware identifier of the OS control in the form SERIAL . FUNCTIONID.

oscontrol→get_logicalName()

Returns the logical name of the OS control.

oscontrol→get_module()

Gets the YModule object for the device on which the function is located.

oscontrol→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

oscontrol->get_shutdownCountdown()

Returns the remaining number of seconds before the OS shutdown, or zero when no shutdown has been scheduled.

oscontrol->get(userData)

Returns the value of the userData attribute, as previously stored using method set(userData).

oscontrol->isOnline()

Checks if the OS control is currently reachable, without raising any error.

oscontrol->isOnline_async(callback, context)

Checks if the OS control is currently reachable, without raising any error (asynchronous version).

oscontrol->load(msValidity)

Preloads the OS control cache with a specified validity duration.

oscontrol->load_async(msValidity, callback, context)

Preloads the OS control cache with a specified validity duration (asynchronous version).

oscontrol->nextOsControl()

Continues the enumeration of OS control started using yFirstOsControl().

oscontrol->registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

oscontrol->set_logicalName(newval)

Changes the logical name of the OS control.

oscontrol->set(userData)

Stores a user context provided as argument in the userData attribute of the function.

oscontrol->shutdown(secBeforeShutDown)

Schedules an OS shutdown after a given number of seconds.

oscontrol->wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YOsControl.FindOsControl() yFindOsControl()YOsControl.FindOsControl()

Retrieves OS control for a given identifier.

```
def FindOsControl( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the OS control is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YOsControl.isOnline()` to test if the OS control is indeed online at a given time. In case of ambiguity when looking for OS control by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the OS control

Returns :

a `YOsControl` object allowing you to drive the OS control.

YOsControl.FirstOsControl()**YOsControl****yFirstOsControl()YOsControl.FirstOsControl()**

Starts the enumeration of OS control currently accessible.

```
def FirstOsControl( )
```

Use the method `YOsControl.nextOsControl()` to iterate on next OS control.

Returns :

a pointer to a `YOsControl` object, corresponding to the first OS control currently online, or a null pointer if there are none.

oscontrol→describe()oscontrol.describe()**YOscControl**

Returns a short text that describes unambiguously the instance of the OS control in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the OS control (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

oscontrol→get_advertisedValue()
oscontrol→advertisedValue()
oscontrol.get_advertisedValue()**YOsControl**

Returns the current value of the OS control (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the OS control (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

oscontrol→get_errorMessage()
oscontrol→errorMessage()
oscontrol.get_errorMessage()

YOsControl

Returns the error message of the latest error with the OS control.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the OS control object

oscontrol→get_errorType()**YOscControl****oscontrol→errorType()oscontrol.get_errorType()**

Returns the numerical error code of the latest error with the OS control.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the OS control object

oscontrol→get_friendlyName()
oscontrol→friendlyName()
oscontrol.get_friendlyName()

YOsControl

Returns a global identifier of the OS control in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the OS control if they are defined, otherwise the serial number of the module and the hardware identifier of the OS control (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the OS control using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

oscontrol→get_functionDescriptor()
oscontrol→functionDescriptor()
oscontrol.get_functionDescriptor()**YOsControl**

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

oscontrol→get_functionId()

YOsControl

oscontrol→functionId()oscontrol.get_functionId()

Returns the hardware identifier of the OS control, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the OS control (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

oscontrol→get_hardwareId()	YOsControl
oscontrol→hardwareId()oscontrol.get_hardwareId()	

Returns the unique hardware identifier of the OS control in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the OS control (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the OS control (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

oscontrol→get_logicalName()
oscontrol→logicalName()
oscontrol.get_logicalName()

YOsControl

Returns the logical name of the OS control.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the OS control.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

oscontrol→get_module()**YOsControl****oscontrol→module()oscontrol.get_module()**

Gets the YModule object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

oscontrol→get_shutdownCountdown()
oscontrol→shutdownCountdown()
oscontrol.get_shutdownCountdown()

YOsControl

Returns the remaining number of seconds before the OS shutdown, or zero when no shutdown has been scheduled.

```
def get_shutdownCountdown( )
```

Returns :

an integer corresponding to the remaining number of seconds before the OS shutdown, or zero when no shutdown has been scheduled

On failure, throws an exception or returns Y_SHUTDOWNCOUNTDOWN_INVALID.

oscontrol→get(userData)**YOsControl****oscontrol→userData()oscontrol.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

**oscontrol→isOnline()
oscontrol.isOnline()****YOsControl**

Checks if the OS control is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the OS control in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the OS control.

Returns :

true if the OS control can be reached, and false otherwise

oscontrol→load()oscontrol.load()**YOscControl**

Preloads the OS control cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

**oscontrol→nextOsControl()
oscontrol.nextOsControl()**

YOsControl

Continues the enumeration of OS control started using `yFirstOsControl()`.

```
def nextOsControl( )
```

Returns :

a pointer to a `YOsControl` object, corresponding to OS control currently online, or a `null` pointer if there are no more OS control to enumerate.

oscontrol→registerValueCallback()
oscontrol.registerValueCallback()**YOscControl**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

oscontrol→set_logicalName()
oscontrol→setLogicalName()
oscontrol.set_logicalName()

YOsControl

Changes the logical name of the OS control.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the OS control.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

oscontrol→set(userData)**YOsControl****oscontrol→setUserData()oscontrol.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData):
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

oscontrol→shutdown()oscontrol.shutdown()**YOsControl**

Schedules an OS shutdown after a given number of seconds.

```
def shutdown( secBeforeShutDown)
```

Parameters :

secBeforeShutDown number of seconds before shutdown

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

3.30. Power function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_power.js'></script>
node.js	var yoctolib = require('yoctolib');
	var YPower = yoctolib.YPower;
php	require_once('yocto_power.php');
cpp	#include "yocto_power.h"
m	#import "yocto_power.h"
pas	uses yocto_power;
vb	yocto_power.vb
cs	yocto_power.cs
java	import com.yoctopuce.YoctoAPI.YPower;
py	from yocto_power import *

Global functions

yFindPower(func)

Retrieves a electrical power sensor for a given identifier.

yFirstPower()

Starts the enumeration of electrical power sensors currently accessible.

YPower methods

power→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

power→describe()

Returns a short text that describes unambiguously the instance of the electrical power sensor in the form TYPE (NAME)=SERIAL.FUNCTIONID.

power→get_advertisedValue()

Returns the current value of the electrical power sensor (no more than 6 characters).

power→get_cosPhi()

Returns the power factor (the ratio between the real power consumed, measured in W, and the apparent power provided, measured in VA).

power→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in Watt, as a floating point number.

power→get_currentValue()

Returns the current value of the electrical power, in Watt, as a floating point number.

power→get_errorMessage()

Returns the error message of the latest error with the electrical power sensor.

power→get_errorType()

Returns the numerical error code of the latest error with the electrical power sensor.

power→get_friendlyName()

Returns a global identifier of the electrical power sensor in the format MODULE_NAME.FUNCTION_NAME.

power→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

power→get_functionId()

3. Reference

Returns the hardware identifier of the electrical power sensor, without reference to the module.
power→get_hardwareId()
Returns the unique hardware identifier of the electrical power sensor in the form SERIAL.FUNCTIONID.
power→get_highestValue()
Returns the maximal value observed for the electrical power since the device was started.
power→get_logFrequency()
Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.
power→get_logicalName()
Returns the logical name of the electrical power sensor.
power→get_lowestValue()
Returns the minimal value observed for the electrical power since the device was started.
power→get_meter()
Returns the energy counter, maintained by the wattmeter by integrating the power consumption over time.
power→get_meterTimer()
Returns the elapsed time since last energy counter reset, in seconds.
power→get_module()
Gets the YModule object for the device on which the function is located.
power→get_module_async(callback, context)
Gets the YModule object for the device on which the function is located (asynchronous version).
power→get_recordedData(startTime, endTime)
Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.
power→get_reportFrequency()
Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.
power→get_resolution()
Returns the resolution of the measured values.
power→get_unit()
Returns the measuring unit for the electrical power.
power→get(userData)
Returns the value of the userData attribute, as previously stored using method set(userData).
power→isOnline()
Checks if the electrical power sensor is currently reachable, without raising any error.
power→isOnline_async(callback, context)
Checks if the electrical power sensor is currently reachable, without raising any error (asynchronous version).
power→load(msValidity)
Preloads the electrical power sensor cache with a specified validity duration.
power→loadCalibrationPoints(rawValues, refValues)
Retrieves error correction data points previously entered using the method calibrateFromPoints.
power→load_async(msValidity, callback, context)
Preloads the electrical power sensor cache with a specified validity duration (asynchronous version).
power→nextPower()
Continues the enumeration of electrical power sensors started using yFirstPower().
power→registerTimedReportCallback(callback)
Registers the callback function that is invoked on every periodic timed notification.
power→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

power→reset()

Resets the energy counter.

power→set_highestValue(newval)

Changes the recorded maximal value observed.

power→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

power→set_logicalName(newval)

Changes the logical name of the electrical power sensor.

power→set_lowestValue(newval)

Changes the recorded minimal value observed.

power→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

power→set_resolution(newval)

Changes the resolution of the measured physical values.

power→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

power→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YPower.FindPower() yFindPower()YPower.FindPower()

YPower

Retrieves a electrical power sensor for a given identifier.

```
def FindPower( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the electrical power sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YPower.isOnline()` to test if the electrical power sensor is indeed online at a given time. In case of ambiguity when looking for a electrical power sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the electrical power sensor

Returns :

a `YPower` object allowing you to drive the electrical power sensor.

YPower.FirstPower()**YPower****yFirstPower()YPower.FirstPower()**

Starts the enumeration of electrical power sensors currently accessible.

```
def FirstPower( )
```

Use the method `YPower.nextPower()` to iterate on next electrical power sensors.

Returns :

a pointer to a `YPower` object, corresponding to the first electrical power sensor currently online, or a null pointer if there are none.

**power→calibrateFromPoints()
power.calibrateFromPoints()****YPower**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

power→describe()power.describe()**YPower**

Returns a short text that describes unambiguously the instance of the electrical power sensor in the form TYPE (NAME)=SERIAL . FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

```
a string that describes the electrical power sensor (ex:  
Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)
```

power→get_advertisedValue()
power→advertisedValue()
power.get_advertisedValue()

YPower

Returns the current value of the electrical power sensor (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the electrical power sensor (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

power→get_cosPhi()**YPower****power→cosPhi()power.get_cosPhi()**

Returns the power factor (the ratio between the real power consumed, measured in W, and the apparent power provided, measured in VA).

```
def get_cosPhi( )
```

Returns :

a floating point number corresponding to the power factor (the ratio between the real power consumed, measured in W, and the apparent power provided, measured in VA)

On failure, throws an exception or returns Y_COSPHI_INVALID.

power→get_currentRawValue()
power→currentRawValue()
power.get_currentRawValue()

YPower

Returns the uncalibrated, unrounded raw value returned by the sensor, in Watt, as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in Watt, as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

power→get_currentValue()**YPower****power→currentValue()power.get_currentValue()**

Returns the current value of the electrical power, in Watt, as a floating point number.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current value of the electrical power, in Watt, as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

power→getErrorMessage() YPower
power→errorMessage() power.getErrorMessage()

Returns the error message of the latest error with the electrical power sensor.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the electrical power sensor object

power→get_errorType()**YPower****power→errorType()power.get_errorType()**

Returns the numerical error code of the latest error with the electrical power sensor.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the electrical power sensor object

power→get_friendlyName() YPower
power→friendlyName()power.get_friendlyName()

Returns a global identifier of the electrical power sensor in the format MODULE_NAME.FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the electrical power sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the electrical power sensor (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the electrical power sensor using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

power→get_functionDescriptor()
power→functionDescriptor()
power.get_functionDescriptor()

YPower

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

power→get_functionId()

YPower

power→functionId()power.get_functionId()

Returns the hardware identifier of the electrical power sensor, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the electrical power sensor (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

power→get_hardwareId()**YPower****power→hardwareId()power.get_hardwareId()**

Returns the unique hardware identifier of the electrical power sensor in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the electrical power sensor (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the electrical power sensor (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

power→get_highestValue() YPower
power→highestValue()power.get_highestValue()

Returns the maximal value observed for the electrical power since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the electrical power since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

power→get_logFrequency()**YPower****power→logFrequency()power.get_logFrequency()**

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

power→get_logicalName()

YPower

power→logicalName()power.get_logicalName()

Returns the logical name of the electrical power sensor.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the electrical power sensor.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

power→get_lowestValue()**YPower****power→lowestValue()power.get_lowestValue()**

Returns the minimal value observed for the electrical power since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the electrical power since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

power→get_meter()**YPower****power→meter()power.get_meter()**

Returns the energy counter, maintained by the wattmeter by integrating the power consumption over time.

```
def get_meter( )
```

Note that this counter is reset at each start of the device.

Returns :

a floating point number corresponding to the energy counter, maintained by the wattmeter by integrating the power consumption over time

On failure, throws an exception or returns Y_METER_INVALID.

power→get_meterTimer()**YPower****power→meterTimer()power.get_meterTimer()**

Returns the elapsed time since last energy counter reset, in seconds.

```
def get_meterTimer( )
```

Returns :

an integer corresponding to the elapsed time since last energy counter reset, in seconds

On failure, throws an exception or returns Y_METERTIMER_INVALID.

**power→get_module()
power→module()power.get_module()****YPower**

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

power→get_recordedData()	YPower
power→recordedData()power.get_recordedData()	

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime)
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

power→get_reportFrequency()
power→reportFrequency()
power.get_reportFrequency()

YPower

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

power→get_resolution()**YPower****power→resolution()power.get_resolution()**

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

power→get_unit()
power→unit()power.get_unit()

YPower

Returns the measuring unit for the electrical power.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the electrical power

On failure, throws an exception or returns Y_UNIT_INVALID.

power→get(userData)**YPower****power→userData()power.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

power→isOnline()power.isOnline()**YPower**

Checks if the electrical power sensor is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the electrical power sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the electrical power sensor.

Returns :

true if the electrical power sensor can be reached, and false otherwise

power→load()power.load()**YPower**

Preloads the electrical power sensor cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

power→loadCalibrationPoints()
power.loadCalibrationPoints()**YPower**

Retrieves error correction data points previously entered using the method `calibrateFromPoints`.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

power→nextPower()power.nextPower()**YPower**

Continues the enumeration of electrical power sensors started using `yFirstPower()`.

```
def nextPower( )
```

Returns :

a pointer to a `YPower` object, corresponding to a electrical power sensor currently online, or a null pointer if there are no more electrical power sensors to enumerate.

**power→registerTimedReportCallback()
power.registerTimedReportCallback()****YPower**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

power→registerValueCallback()
power.registerValueCallback()**YPower**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

power→reset() power.reset()

YPower

Resets the energy counter.

```
def reset( )
```

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

power→set_highestValue()**YPower****power→setHighestValue()power.set_highestValue()**

Changes the recorded maximal value observed.

```
def set_highestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

power→set_logFrequency() YPower
power→setLogFrequency()power.set_logFrequency()

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval)
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

power→set_logicalName()**YPower****power→setLogicalName()power.set_logicalName()**

Changes the logical name of the electrical power sensor.

```
def set_logicalName( newval )
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the electrical power sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

power→set_lowestValue()	YPower
power→setLowestValue()power.set_lowestValue()	

Changes the recorded minimal value observed.

```
def set_lowestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

power→set_reportFrequency()
power→setReportFrequency()
power.set_reportFrequency()

YPower

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

power→set_resolution() YPower
power→setResolution()power.set_resolution()

Changes the resolution of the measured physical values.

```
def set_resolution( newval)
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

power→set(userData)**YPower****power→setUserData()power.set(userData())**

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData) {
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.31. Pressure function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_pressure.js'></script>
nodejs var yoctolib = require('yoctolib');
var YPressure = yoctolib.YPressure;
php require_once('yocto_pressure.php');
cpp #include "yocto_pressure.h"
m #import "yocto_pressure.h"
pas uses yocto_pressure;
vb yocto_pressure.vb
cs yocto_pressure.cs
java import com.yoctopuce.YoctoAPI.YPressure;
py from yocto_pressure import *

```

Global functions

yFindPressure(func)

Retrieves a pressure sensor for a given identifier.

yFirstPressure()

Starts the enumeration of pressure sensors currently accessible.

YPressure methods

pressure→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

pressure→describe()

Returns a short text that describes unambiguously the instance of the pressure sensor in the form TYPE (NAME) = SERIAL . FUNCTIONID.

pressure→get_advertisedValue()

Returns the current value of the pressure sensor (no more than 6 characters).

pressure→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in millibar (hPa), as a floating point number.

pressure→get_currentValue()

Returns the current value of the pressure, in millibar (hPa), as a floating point number.

pressure→get_errorMessage()

Returns the error message of the latest error with the pressure sensor.

pressure→get_errorType()

Returns the numerical error code of the latest error with the pressure sensor.

pressure→get_friendlyName()

Returns a global identifier of the pressure sensor in the format MODULE_NAME . FUNCTION_NAME.

pressure→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

pressure→get_functionId()

Returns the hardware identifier of the pressure sensor, without reference to the module.

pressure→get_hardwareId()

Returns the unique hardware identifier of the pressure sensor in the form SERIAL.FUNCTIONID.
pressure→get_highestValue()
Returns the maximal value observed for the pressure since the device was started.
pressure→get_logFrequency()
Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.
pressure→get_logicalName()
Returns the logical name of the pressure sensor.
pressure→get_lowestValue()
Returns the minimal value observed for the pressure since the device was started.
pressure→get_module()
Gets the YModule object for the device on which the function is located.
pressure→get_module_async(callback, context)
Gets the YModule object for the device on which the function is located (asynchronous version).
pressure→get_recordedData(startTime, endTime)
Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.
pressure→get_reportFrequency()
Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.
pressure→get_resolution()
Returns the resolution of the measured values.
pressure→get_unit()
Returns the measuring unit for the pressure.
pressure→get(userData)
Returns the value of the userData attribute, as previously stored using method set(userData).
pressure→isOnline()
Checks if the pressure sensor is currently reachable, without raising any error.
pressure→isOnline_async(callback, context)
Checks if the pressure sensor is currently reachable, without raising any error (asynchronous version).
pressure→load(msValidity)
Preloads the pressure sensor cache with a specified validity duration.
pressure→loadCalibrationPoints(rawValues, refValues)
Retrieves error correction data points previously entered using the method calibrateFromPoints.
pressure→load_async(msValidity, callback, context)
Preloads the pressure sensor cache with a specified validity duration (asynchronous version).
pressure→nextPressure()
Continues the enumeration of pressure sensors started using yFirstPressure().
pressure→registerTimedReportCallback(callback)
Registers the callback function that is invoked on every periodic timed notification.
pressure→registerValueCallback(callback)
Registers the callback function that is invoked on every change of advertised value.
pressure→set_highestValue(newval)
Changes the recorded maximal value observed.
pressure→set_logFrequency(newval)
Changes the datalogger recording frequency for this function.
pressure→set_logicalName(newval)

3. Reference

Changes the logical name of the pressure sensor.

pressure→set_lowestValue(newval)

Changes the recorded minimal value observed.

pressure→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

pressure→set_resolution(newval)

Changes the resolution of the measured physical values.

pressure→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

pressure→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YPressure.FindPressure()**YPressure****yFindPressure()YPressure.FindPressure()**

Retrieves a pressure sensor for a given identifier.

```
def FindPressure( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the pressure sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YPressure.isOnline()` to test if the pressure sensor is indeed online at a given time. In case of ambiguity when looking for a pressure sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the pressure sensor

Returns :

a `YPressure` object allowing you to drive the pressure sensor.

YPressure.FirstPressure()

YPressure

yFirstPressure()YPressure.FirstPressure()

Starts the enumeration of pressure sensors currently accessible.

```
def FirstPressure( )
```

Use the method `YPressure.nextPressure()` to iterate on next pressure sensors.

Returns :

a pointer to a `YPressure` object, corresponding to the first pressure sensor currently online, or a null pointer if there are none.

pressure→calibrateFromPoints()
pressure.calibrateFromPoints()**YPressure**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

pressure→describe()pressure.describe()**YPressure**

Returns a short text that describes unambiguously the instance of the pressure sensor in the form
TYPE (NAME)=SERIAL . FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the pressure sensor (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

pressure→get_advertisedValue()

YPressure

pressure→advertisedValue()

pressure.get_advertisedValue()

Returns the current value of the pressure sensor (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the pressure sensor (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

pressure→get_currentRawValue()	YPressure
pressure→currentRawValue()	
pressure.get_currentRawValue()	

Returns the uncalibrated, unrounded raw value returned by the sensor, in millibar (hPa), as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in millibar (hPa), as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

pressure→get_currentValue()

YPressure

pressure→currentValue()pressure.get_currentValue()

Returns the current value of the pressure, in millibar (hPa), as a floating point number.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current value of the pressure, in millibar (hPa), as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

pressure→get_errorMessage()
pressure→errorMessage()
pressure.get_errorMessage()

YPressure

Returns the error message of the latest error with the pressure sensor.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the pressure sensor object

pressure→get_errorType()

YPressure

pressure→errorType()pressure.get_errorType()

Returns the numerical error code of the latest error with the pressure sensor.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the pressure sensor object

pressure→get_friendlyName()	YPressure
pressure→friendlyName()	
pressure.get_friendlyName()	

Returns a global identifier of the pressure sensor in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the pressure sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the pressure sensor (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the pressure sensor using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

pressure→get_functionDescriptor()
pressure→functionDescriptor()
pressure.get_functionDescriptor()

YPressure

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

pressure→get_functionId() YPressure
pressure→functionId()pressure.get_functionId()

Returns the hardware identifier of the pressure sensor, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the pressure sensor (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

pressure→get_hardwareId()

YPressure

pressure→hardwareId()pressure.get_hardwareId()

Returns the unique hardware identifier of the pressure sensor in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the pressure sensor (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the pressure sensor (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

pressure→get_highestValue()
pressure→highestValue()
pressure.get_highestValue()

YPressure

Returns the maximal value observed for the pressure since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the pressure since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

pressure→get_logFrequency()
pressure→logFrequency()
pressure.get_logFrequency()

YPressure

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

pressure→get_logicalName()

YPressure

pressure→logicalName()pressure.get_logicalName()

Returns the logical name of the pressure sensor.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the pressure sensor.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

pressure→get_lowestValue()

YPressure

pressure→lowestValue()pressure.get_lowestValue()

Returns the minimal value observed for the pressure since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the pressure since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

pressure→get_module()

YPressure

pressure→module()pressure.get_module()

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

pressure→get_recordedData()
pressure→recordedData()
pressure.get_recordedData()

YPressure

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime)
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

pressure→get_reportFrequency()	YPressure
pressure→reportFrequency()	
pressure.get_reportFrequency()	

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

pressure→get_resolution()

YPressure

pressure→resolution()pressure.get_resolution()

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

pressure→get_unit()

YPressure

pressure→unit()pressure.get_unit()

Returns the measuring unit for the pressure.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the pressure

On failure, throws an exception or returns Y_UNIT_INVALID.

pressure→get(userData)**YPressure****pressure→userData()pressure.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

pressure→isOnline()pressure.isOnline()**YPressure**

Checks if the pressure sensor is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the pressure sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the pressure sensor.

Returns :

true if the pressure sensor can be reached, and false otherwise

pressure→load()pressure.load()**YPressure**

Preloads the pressure sensor cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

pressure→loadCalibrationPoints()
pressure.loadCalibrationPoints()**YPressure**

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pressure→nextPressure()pressure.nextPressure()**YPressure**

Continues the enumeration of pressure sensors started using `yFirstPressure()`.

```
def nextPressure( )
```

Returns :

a pointer to a `YPressure` object, corresponding to a pressure sensor currently online, or a null pointer if there are no more pressure sensors to enumerate.

**pressure→registerTimedReportCallback()
pressure.registerTimedReportCallback()****YPressure**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

pressure→registerValueCallback()
pressure.registerValueCallback()**YPressure**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

pressure→set_highestValue()
pressure→setHighestValue()
pressure.set_highestValue()

YPressure

Changes the recorded maximal value observed.

```
def set_highestValue( newval )
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pressure→set_logFrequency()
pressure→setLogFrequency()
pressure.set_logFrequency()

YPressure

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval)
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pressure→set_logicalName()
pressure→setLogicalName()
pressure.set_logicalName()

YPressure

Changes the logical name of the pressure sensor.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the pressure sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

pressure→set_lowestValue()
pressure→setLowestValue()
pressure.set_lowestValue()

YPressure

Changes the recorded minimal value observed.

```
def set_lowestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pressure→set_reportFrequency()	YPressure
pressure→setReportFrequency()	
pressure.set_reportFrequency()	

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pressure→set_resolution()**YPressure****pressure→setResolution()pressure.set_resolution()**

Changes the resolution of the measured physical values.

```
def set_resolution( newval )
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pressure→set(userData)

YPressure

pressure→setUserData()pressure.set(userData)

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.32. PwmInput function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_pwminput.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YPwmInput = yoctolib.YPwmInput;
php	require_once('yocto_pwminput.php');
cpp	#include "yocto_pwminput.h"
m	#import "yocto_pwminput.h"
pas	uses yocto_pwminput;
vb	yocto_pwminput.vb
cs	yocto_pwminput.cs
java	import com.yoctopuce.YoctoAPI.YPwmInput;
py	from yocto_pwminput import *

Global functions

yFindPwmInput(func)

Retrieves a voltage sensor for a given identifier.

yFirstPwmInput()

Starts the enumeration of voltage sensors currently accessible.

YPwmInput methods

pwminput→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

pwminput→describe()

Returns a short text that describes unambiguously the instance of the voltage sensor in the form TYPE (NAME)=SERIAL .FUNCTIONID.

pwminput→get_advertisedValue()

Returns the current value of the voltage sensor (no more than 6 characters).

pwminput→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in Volt, as a floating point number.

pwminput→get_currentValue()

Returns the current value of PwmInput feature as a floating point number.

pwminput→get_dutyCycle()

Returns the PWM duty cycle, in per cents.

pwminput→get_errorMessage()

Returns the error message of the latest error with the voltage sensor.

pwminput→get_errorType()

Returns the numerical error code of the latest error with the voltage sensor.

pwminput→get_frequency()

Returns the PWM frequency in Hz.

pwminput→get_friendlyName()

Returns a global identifier of the voltage sensor in the format MODULE_NAME .FUNCTION_NAME.

pwminput→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

3. Reference

pwminput→get_functionId()

Returns the hardware identifier of the voltage sensor, without reference to the module.

pwminput→get_hardwareId()

Returns the unique hardware identifier of the voltage sensor in the form SERIAL . FUNCTIONID.

pwminput→get_highestValue()

Returns the maximal value observed for the voltage since the device was started.

pwminput→get_logFrequency()

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

pwminput→get_logicalName()

Returns the logical name of the voltage sensor.

pwminput→get_lowestValue()

Returns the minimal value observed for the voltage since the device was started.

pwminput→get_module()

Gets the YModule object for the device on which the function is located.

pwminput→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

pwminput→get_period()

Returns the PWM period in milliseconds.

pwminput→get_pulseCounter()

Returns the pulse counter value.

pwminput→get_pulseDuration()

Returns the PWM pulse length in milliseconds, as a floating point number.

pwminput→get_pulseTimer()

Returns the timer of the pulses counter (ms)

pwminput→get_pwmReportMode()

Returns the parameter (frequency/duty cycle, pulse width, edges count) returned by the get_currentValue function and callbacks.

pwminput→get_recordedData(startTime, endTime)

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

pwminput→get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

pwminput→get_resolution()

Returns the resolution of the measured values.

pwminput→get_unit()

Returns the measuring unit for the values returned by get_currentValue and callbacks.

pwminput→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

pwminput→isOnline()

Checks if the voltage sensor is currently reachable, without raising any error.

pwminput→isOnline_async(callback, context)

Checks if the voltage sensor is currently reachable, without raising any error (asynchronous version).

pwminput→load(msValidity)

Preloads the voltage sensor cache with a specified validity duration.

pwminput→loadCalibrationPoints(rawValues, refValues)

Retrieves error correction data points previously entered using the method `calibrateFromPoints`.

`pwminput->load_async(msValidity, callback, context)`

Preloads the voltage sensor cache with a specified validity duration (asynchronous version).

`pwminput->nextPwmInput()`

Continues the enumeration of voltage sensors started using `yFirstPwmInput()`.

`pwminput->registerTimedReportCallback(callback)`

Registers the callback function that is invoked on every periodic timed notification.

`pwminput->registerValueCallback(callback)`

Registers the callback function that is invoked on every change of advertised value.

`pwminput->resetCounter()`

Returns the pulse counter value as well as his timer

`pwminput->set_highestValue(newval)`

Changes the recorded maximal value observed.

`pwminput->set_logFrequency(newval)`

Changes the datalogger recording frequency for this function.

`pwminput->set_logicalName(newval)`

Changes the logical name of the voltage sensor.

`pwminput->set_lowestValue(newval)`

Changes the recorded minimal value observed.

`pwminput->set_pwmReportMode(newval)`

Modify the parameter type(frequency/duty cycle, pulse width ou edge count) returned by the `get_currentValue` function and callbacks.

`pwminput->set_reportFrequency(newval)`

Changes the timed value notification frequency for this function.

`pwminput->set_resolution(newval)`

Changes the resolution of the measured physical values.

`pwminput->set(userData)`

Stores a user context provided as argument in the `userData` attribute of the function.

`pwminput->wait_async(callback, context)`

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YPwmInput.FindPwmInput() yFindPwmInput()YPwmInput.FindPwmInput()

Retrieves a voltage sensor for a given identifier.

```
def FindPwmInput( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the voltage sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YPwmInput.isOnline()` to test if the voltage sensor is indeed online at a given time. In case of ambiguity when looking for a voltage sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the voltage sensor

Returns :

a `YPwmInput` object allowing you to drive the voltage sensor.

YPwmInput.FirstPwmInput()**yFirstPwmInput()YPwmInput.FirstPwmInput()****YPwmInput**

Starts the enumeration of voltage sensors currently accessible.

```
def FirstPwmInput( )
```

Use the method `YPwmInput.nextPwmInput()` to iterate on next voltage sensors.

Returns :

a pointer to a `YPwmInput` object, corresponding to the first voltage sensor currently online, or a null pointer if there are none.

pwminput→calibrateFromPoints()
pwminput.calibrateFromPoints()**YPwmInput**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwminput→describe()pwminput.describe()**YPwmInput**

Returns a short text that describes unambiguously the instance of the voltage sensor in the form TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the voltage sensor (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

pwminput→get_advertisedValue()
pwminput→advertisedValue()
pwminput.get_advertisedValue()

YPwmInput

Returns the current value of the voltage sensor (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the voltage sensor (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

pwminput→get_currentRawValue()
pwminput→currentRawValue()
pwminput.get_currentRawValue()

YPwmInput

Returns the uncalibrated, unrounded raw value returned by the sensor, in Volt, as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in Volt, as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

pwminput→get_currentValue()
pwminput→currentValue()
pwminput.get_currentValue()

YPwmInput

Returns the current value of PwmInput feature as a floating point number.

```
def get_currentValue( )
```

Depending on the pwmReportMode setting, this can be the frequency, in Hz, the duty cycle in % or the pulse length.

Returns :

a floating point number corresponding to the current value of PwmInput feature as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

pwminput→get_dutyCycle()**YPwmInput****pwminput→dutyCycle()pwminput.get_dutyCycle()**

Returns the PWM duty cycle, in per cents.

```
def get_dutyCycle( )
```

Returns :

a floating point number corresponding to the PWM duty cycle, in per cents

On failure, throws an exception or returns Y_DUTYCYCLE_INVALID.

pwminput→getErrorMessage()
pwminput→errorMessage()
pwminput.getErrorMessage()

YPwmInput

Returns the error message of the latest error with the voltage sensor.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the voltage sensor object

pwminput→get_errorType()

YPwmInput

pwminput→errorType()pwminput.get_errorType()

Returns the numerical error code of the latest error with the voltage sensor.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the voltage sensor object

pwminput→get_frequency()

YPwmInput

pwminput→frequency()pwminput.get_frequency()

Returns the PWM frequency in Hz.

```
def get_frequency( )
```

Returns :

a floating point number corresponding to the PWM frequency in Hz

On failure, throws an exception or returns Y_FREQUENCY_INVALID.

`pwminput→get_friendlyName()`
`pwminput→friendlyName()`
`pwminput.get_friendlyName()`

`YPwmInput`

Returns a global identifier of the voltage sensor in the format MODULE_NAME . FUNCTION_NAME.

`def get_friendlyName()`

The returned string uses the logical names of the module and of the voltage sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the voltage sensor (for example: MyCustomName . relay1)

Returns :

a string that uniquely identifies the voltage sensor using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns `Y_FRIENDLYNAME_INVALID`.

pwminput→get_functionDescriptor()
pwminput→functionDescriptor()
pwminput.get_functionDescriptor()

YPwmInput

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

pwminput→get_functionId()**YPwmInput****pwminput→functionId()pwminput.get_functionId()**

Returns the hardware identifier of the voltage sensor, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the voltage sensor (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

pwminput→get_hardwareId()	YPwmInput
pwminput→hardwareId()pwminput.get_hardwareId()	

Returns the unique hardware identifier of the voltage sensor in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the voltage sensor (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the voltage sensor (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

pwminput→get_highestValue()
pwminput→highestValue()
pwminput.get_highestValue()

YPwmInput

Returns the maximal value observed for the voltage since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the voltage since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

pwminput→get_logFrequency()
pwminput→logFrequency()
pwminput.get_logFrequency()

YPwmInput

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

pwminput→get_logicalName()
pwminput→logicalName()
pwminput.get_logicalName()

YPwmInput

Returns the logical name of the voltage sensor.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the voltage sensor.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

pwminput→get_lowestValue()
pwminput→lowestValue()
pwminput.get_lowestValue()

YPwmInput

Returns the minimal value observed for the voltage since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the voltage since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

pwminput→get_module()**YPwmInput****pwminput→module()pwminput.get_module()**

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

`pwminput→get_period()`

`YPwmInput`

`pwminput→period()pwminput.get_period()`

Returns the PWM period in milliseconds.

```
def get_period( )
```

Returns :

a floating point number corresponding to the PWM period in milliseconds

On failure, throws an exception or returns `Y_PERIOD_INVALID`.

pwminput→get_pulseCounter()
pwminput→pulseCounter()
pwminput.get_pulseCounter()

YPwmInput

Returns the pulse counter value.

```
def get_pulseCounter( )
```

Actually that counter is incremented twice per period. That counter is limited to 1 billions

Returns :

an integer corresponding to the pulse counter value

On failure, throws an exception or returns Y_PULSECOUNTERR_INVALID.

`pwminput→get_pulseDuration()`
`pwminput→pulseDuration()`
`pwminput.get_pulseDuration()`

`YPwmInput`

Returns the PWM pulse length in milliseconds, as a floating point number.

```
def get_pulseDuration( )
```

Returns :

a floating point number corresponding to the PWM pulse length in milliseconds, as a floating point number

On failure, throws an exception or returns `Y_PULSEDURATION_INVALID`.

`pwminput→get_pulseTimer()`

`YPwmInput`

`pwminput→pulseTimer()pwminput.get_pulseTimer()`

Returns the timer of the pulses counter (ms)

```
def get_pulseTimer( )
```

Returns :

an integer corresponding to the timer of the pulses counter (ms)

On failure, throws an exception or returns `Y_PULSE_TIMER_INVALID`.

pwminput→get_pwmReportMode()
pwminput→pwmReportMode()
pwminput.get_pwmReportMode()

YPwmInput

Returns the parameter (frequency/duty cycle, pulse width, edges count) returned by the get_currentValue function and callbacks.

```
def get_pwmReportMode( )
```

Attention

Returns :

a value among Y_PWMREPORTMODE_PWM_DUTYCYCLE, Y_PWMREPORTMODE_PWM_FREQUENCY, Y_PWMREPORTMODE_PWM_PULSEDURATION and Y_PWMREPORTMODE_PWM_EDGECOUNT corresponding to the parameter (frequency/duty cycle, pulse width, edges count) returned by the get_currentValue function and callbacks

On failure, throws an exception or returns Y_PWMREPORTMODE_INVALID.

pwminput→get_recordedData()
pwminput→recordedData()
pwminput.get_recordedData()

YPwmInput

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime)
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

pwminput→get_reportFrequency()
pwminput→reportFrequency()
pwminput.get_reportFrequency()

YPwmInput

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

pwminput→get_resolution()**YPwmInput****pwminput→resolution()pwminput.get_resolution()**

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

pwminput→get_unit()
pwminput→unit()pwminput.get_unit()

YPwmInput

Returns the measuring unit for the values returned by get_currentValue and callbacks.

```
def get_unit( )
```

That unit will change according to the pwmReportMode settings.

Returns :

a string corresponding to the measuring unit for the values returned by get_currentValue and callbacks

On failure, throws an exception or returns Y_UNIT_INVALID.

pwminput→get(userData)**YPwmInput****pwminput→userData()pwminput.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

pwminput→isOnline()pwminput.isOnline()**YPwmInput**

Checks if the voltage sensor is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the voltage sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the voltage sensor.

Returns :

true if the voltage sensor can be reached, and false otherwise

pwminput→load()pwminput.load()**YPwmInput**

Preloads the voltage sensor cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

pwminput→loadCalibrationPoints()
pwminput.loadCalibrationPoints()**YPwmInput**

Retrieves error correction data points previously entered using the method `calibrateFromPoints`.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwminput→nextPwmInput()
pwminput.nextPwmInput()**YPwmInput**

Continues the enumeration of voltage sensors started using `yFirstPwmInput()`.

```
def nextPwmInput( )
```

Returns :

a pointer to a `YPwmInput` object, corresponding to a voltage sensor currently online, or a `null` pointer if there are no more voltage sensors to enumerate.

**pwminput→registerTimedReportCallback()
pwminput.registerTimedReportCallback()****YPwmInput**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

pwminput→registerValueCallback()
pwminput.registerValueCallback()**YPwmInput**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

pwminput→resetCounter()pwminput.resetCounter()**YPwmInput**

Returns the pulse counter value as well as his timer

```
def resetCounter( )
```

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwminput→set_highestValue()
pwminput→setHighestValue()
pwminput.set_highestValue()

YPwmInput

Changes the recorded maximal value observed.

```
def set_highestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

`pwminput→set_logFrequency()`
`pwminput→setLogFrequency()`
`pwminput.set_logFrequency()`

`YPwmInput`

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

`newval` a string corresponding to the datalogger recording frequency for this function

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwminput→set_logicalName()
pwminput→setLogicalName()
pwminput.set_logicalName()

YPwmInput

Changes the logical name of the voltage sensor.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the logical name of the voltage sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwminput→set_lowestValue()
pwminput→setLowestValue()
pwminput.set_lowestValue()

YPwmInput

Changes the recorded minimal value observed.

```
def set_lowestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwminput→set_pwmReportMode()
pwminput→setPwmReportMode()
pwminput.set_pwmReportMode()

YPwmInput

Modify the parameter type(frequency/duty cycle, pulse width ou edge count) returned by the get_currentValue function and callbacks.

```
def set_pwmReportMode( newval )
```

The edge count value will be limited to the 6 lowest digit, for values greater than one million, use get_pulseCounter().

Parameters :

newval a value among Y_PWMREPORTMODE_PWM_DUTYCYCLE,
Y_PWMREPORTMODE_PWM_FREQUENCY,
Y_PWMREPORTMODE_PWM_PULSEDURATION and
Y_PWMREPORTMODE_PWM_EDGECOUNT

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwminput→set_reportFrequency()	YPwmInput
pwminput→setReportFrequency()	
pwminput.set_reportFrequency()	

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwminput→set_resolution()
pwminput→setResolution()
pwminput.set_resolution()

YPwmInput

Changes the resolution of the measured physical values.

```
def set_resolution( newval)
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwminput→set(userData)

YPwmInput

pwminput→setUserData()pwminput.set(userData)

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData):
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.33. Pwm function interface

The Yoctopuce application programming interface allows you to configure, start, and stop the PWM.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_pwmoutput.js'></script>
node.js	var yoctolib = require('yoctolib');
	var YPwmOutput = yoctolib.YPwmOutput;
php	require_once('yocto_pwmoutput.php');
cpp	#include "yocto_pwmoutput.h"
m	#import "yocto_pwmoutput.h"
pas	uses yocto_pwmoutput;
vb	yocto_pwmoutput.vb
cs	yocto_pwmoutput.cs
java	import com.yoctopuce.YoctoAPI.YPwmOutput;
py	from yocto_pwmoutput import *

Global functions

yFindPwmOutput(func)

Retrieves a PWM for a given identifier.

yFirstPwmOutput()

Starts the enumeration of PWMs currently accessible.

YPwmOutput methods

pwmoutput→describe()

Returns a short text that describes unambiguously the instance of the PWM in the form TYPE (NAME)=SERIAL .FUNCTIONID.

pwmoutput→dutyCycleMove(target, ms_duration)

Performs a smooth change of the pulse duration toward a given value.

pwmoutput→get_advertisedValue()

Returns the current value of the PWM (no more than 6 characters).

pwmoutput→get_dutyCycle()

Returns the PWM duty cycle, in per cents.

pwmoutput→get_dutyCycleAtPowerOn()

Returns the PWMs duty cycle at device power on as a floating point number between 0 and 100

pwmoutput→get_enabled()

Returns the state of the PWMs.

pwmoutput→get_enabledAtPowerOn()

Returns the state of the PWM at device power on.

pwmoutput→get_errorMessage()

Returns the error message of the latest error with the PWM.

pwmoutput→get_errorType()

Returns the numerical error code of the latest error with the PWM.

pwmoutput→get_frequency()

Returns the PWM frequency in Hz.

pwmoutput→get_friendlyName()

Returns a global identifier of the PWM in the format MODULE_NAME . FUNCTION_NAME.

pwmoutput→get_functionDescriptor()

3. Reference

Returns a unique identifier of type YFUN_DESCR corresponding to the function.
pwmoutput->get_functionId() Returns the hardware identifier of the PWM, without reference to the module.
pwmoutput->get_hardwareId() Returns the unique hardware identifier of the PWM in the form SERIAL.FUNCTIONID.
pwmoutput->get_logicalName() Returns the logical name of the PWM.
pwmoutput->get_module() Gets the YModule object for the device on which the function is located.
pwmoutput->get_module_async(callback, context) Gets the YModule object for the device on which the function is located (asynchronous version).
pwmoutput->get_period() Returns the PWM period in milliseconds.
pwmoutput->get_pulseDuration() Returns the PWM pulse length in milliseconds, as a floating point number.
pwmoutput->get_userData() Returns the value of the userData attribute, as previously stored using method set(userData).
pwmoutput->isOnline() Checks if the PWM is currently reachable, without raising any error.
pwmoutput->isOnline_async(callback, context) Checks if the PWM is currently reachable, without raising any error (asynchronous version).
pwmoutput->load(msValidity) Preloads the PWM cache with a specified validity duration.
pwmoutput->load_async(msValidity, callback, context) Preloads the PWM cache with a specified validity duration (asynchronous version).
pwmoutput->nextPwmOutput() Continues the enumeration of PWMs started using yFirstPwmOutput().
pwmoutput->pulseDurationMove(ms_target, ms_duration) Performs a smooth transition of the pulse duration toward a given value.
pwmoutput->registerValueCallback(callback) Registers the callback function that is invoked on every change of advertised value.
pwmoutput->set_dutyCycle(newval) Changes the PWM duty cycle, in per cents.
pwmoutput->set_dutyCycleAtPowerOn(newval) Changes the PWM duty cycle at device power on.
pwmoutput->set_enabled(newval) Stops or starts the PWM.
pwmoutput->set_enabledAtPowerOn(newval) Changes the state of the PWM at device power on.
pwmoutput->set_frequency(newval) Changes the PWM frequency.
pwmoutput->set_logicalName(newval) Changes the logical name of the PWM.
pwmoutput->set_period(newval) Changes the PWM period in milliseconds.

pwmoutput→set_pulseDuration(newval)

Changes the PWM pulse length, in milliseconds.

pwmoutput→set(userData)

Stores a user context provided as argument in the userData attribute of the function.

pwmoutput→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YPwmOutput.FindPwmOutput() yFindPwmOutput()YPwmOutput.FindPwmOutput()

Retrieves a PWM for a given identifier.

```
def FindPwmOutput( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the PWM is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YPwmOutput.isOnline()` to test if the PWM is indeed online at a given time. In case of ambiguity when looking for a PWM by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the PWM

Returns :

a `YPwmOutput` object allowing you to drive the PWM.

YPwmOutput.FirstPwmOutput()**YPwmOutput****yFirstPwmOutput()YPwmOutput.FirstPwmOutput()**

Starts the enumeration of PWMs currently accessible.

```
def FirstPwmOutput( )
```

Use the method `YPwmOutput.nextPwmOutput()` to iterate on next PWMs.

Returns :

a pointer to a `YPwmOutput` object, corresponding to the first PWM currently online, or a `null` pointer if there are none.

pwmoutput→describe()pwmoutput.describe()**YPwmOutput**

Returns a short text that describes unambiguously the instance of the PWM in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the PWM (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

pwmoutput→dutyCycleMove()
pwmoutput.dutyCycleMove()**YPwmOutput**

Performs a smooth change of the pulse duration toward a given value.

```
def dutyCycleMove( target, ms_duration)
```

Parameters :

target new duty cycle at the end of the transition (floating-point number, between 0 and 1)

ms_duration total duration of the transition, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmoutput→get_advertisedValue()
pwmoutput→advertisedValue()
pwmoutput.get_advertisedValue()

YPwmOutput

Returns the current value of the PWM (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the PWM (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

`pwmoutput→get_dutyCycle()`

`YPwmOutput`

`pwmoutput→dutyCycle()pwmoutput.get_dutyCycle()`

Returns the PWM duty cycle, in per cents.

```
def get_dutyCycle( )
```

Returns :

a floating point number corresponding to the PWM duty cycle, in per cents

On failure, throws an exception or returns `Y_DUTYCYCLE_INVALID`.

pwmoutput→get_dutyCycleAtPowerOn()
pwmoutput→dutyCycleAtPowerOn()
pwmoutput.get_dutyCycleAtPowerOn()

YPwmOutput

Returns the PWMs duty cycle at device power on as a floating point number between 0 and 100

```
def get_dutyCycleAtPowerOn( )
```

Returns :

a floating point number corresponding to the PWMs duty cycle at device power on as a floating point number between 0 and 100

On failure, throws an exception or returns Y_DUTYCYCLEATPOWERON_INVALID.

pwmoutput→get_enabled()**YPwmOutput****pwmoutput→enabled()pwmoutput.get_enabled()**

Returns the state of the PWMs.

```
def get_enabled( )
```

Returns :

either Y_ENABLED_FALSE or Y_ENABLED_TRUE, according to the state of the PWMs

On failure, throws an exception or returns Y_ENABLED_INVALID.

pwmoutput→get_enabledAtPowerOn()
pwmoutput→enabledAtPowerOn()
pwmoutput.get_enabledAtPowerOn()

YPwmOutput

Returns the state of the PWM at device power on.

```
def get_enabledAtPowerOn( )
```

Returns :

either Y_ENABLEDATPOWERON_FALSE or Y_ENABLEDATPOWERON_TRUE, according to the state of the PWM at device power on

On failure, throws an exception or returns Y_ENABLEDATPOWERON_INVALID.

pwmoutput→get_errorMessage()
pwmoutput→errorMessage()
pwmoutput.get_errorMessage()

YPwmOutput

Returns the error message of the latest error with the PWM.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the PWM object

pwmoutput→get_errorType()
pwmoutput→errorType()pwmoutput.get_errorType()

YPwmOutput

Returns the numerical error code of the latest error with the PWM.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the PWM object

`pwmoutput→get_frequency()`

`YPwmOutput`

`pwmoutput→frequency()pwmoutput.get_frequency()`

Returns the PWM frequency in Hz.

```
def get_frequency( )
```

Returns :

a floating point number corresponding to the PWM frequency in Hz

On failure, throws an exception or returns `Y_FREQUENCY_INVALID`.

pwmoutput→get_friendlyName()
pwmoutput→friendlyName()
pwmoutput.get_friendlyName()

YPwmOutput

Returns a global identifier of the PWM in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the PWM if they are defined, otherwise the serial number of the module and the hardware identifier of the PWM (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the PWM using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

pwmoutput→get_functionDescriptor()
pwmoutput→functionDescriptor()
pwmoutput.get_functionDescriptor()

YPwmOutput

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

def get_functionDescriptor()

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

pwmoutput→get_functionId()

YPwmOutput

pwmoutput→functionId()pwmoutput.get_functionId()

Returns the hardware identifier of the PWM, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the PWM (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

pwmoutput→get_hwId()
pwmoutput→hardwareId()
pwmoutput.get_hwId()

YPwmOutput

Returns the unique hardware identifier of the PWM in the form SERIAL.FUNCTIONID.

def get_hwId()

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the PWM (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the PWM (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

pwmoutput→get_logicalName()
pwmoutput→logicalName()
pwmoutput.get_logicalName()

YPwmOutput

Returns the logical name of the PWM.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the PWM.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

pwmoutput→get_module()**YPwmOutput****pwmoutput→module()pwmoutput.get_module()**

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

pwmoutput→get_period()

YPwmOutput

pwmoutput→period()pwmoutput.get_period()

Returns the PWM period in milliseconds.

```
def get_period( )
```

Returns :

a floating point number corresponding to the PWM period in milliseconds

On failure, throws an exception or returns Y_PERIOD_INVALID.

`pwmoutput->get_pulseDuration()`
`pwmoutput->pulseDuration()`
`pwmoutput.get_pulseDuration()`

`YPwmOutput`

Returns the PWM pulse length in milliseconds, as a floating point number.

```
def get_pulseDuration( )
```

Returns :

a floating point number corresponding to the PWM pulse length in milliseconds, as a floating point number

On failure, throws an exception or returns `Y_PULSEDURATION_INVALID`.

pwmoutput→get(userData)

YPwmOutput

pwmoutput→userData()pwmoutput.get(userData)

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

pwmoutput→isOnline()**YPwmOutput**

Checks if the PWM is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the PWM in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the PWM.

Returns :

`true` if the PWM can be reached, and `false` otherwise

pwmoutput→load()pwmoutput.load()**YPwmOutput**

Preloads the PWM cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmoutput→nextPwmOutput()
pwmoutput.nextPwmOutput()**YPwmOutput**

Continues the enumeration of PWMs started using `yFirstPwmOutput()`.

```
def nextPwmOutput( )
```

Returns :

a pointer to a `YPwmOutput` object, corresponding to a PWM currently online, or a `null` pointer if there are no more PWMs to enumerate.

**pwmoutput→pulseDurationMove()
pwmoutput.pulseDurationMove()****YPwmOutput**

Performs a smooth transition of the pulse duration toward a given value.

```
def pulseDurationMove( ms_target, ms_duration)
```

Any period, frequency, duty cycle or pulse width change will cancel any ongoing transition process.

Parameters :

ms_target new pulse duration at the end of the transition (floating-point number, representing the pulse duration in milliseconds)

ms_duration total duration of the transition, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

**pwmoutput→registerValueCallback()
pwmoutput.registerValueCallback()****YPwmOutput**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

pwmoutput→set_dutyCycle()
pwmoutput→setDutyCycle()
pwmoutput.set_dutyCycle()

YPwmOutput

Changes the PWM duty cycle, in per cents.

```
def set_dutyCycle( newval )
```

Parameters :

newval a floating point number corresponding to the PWM duty cycle, in per cents

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmoutput→set_dutyCycleAtPowerOn()
pwmoutput→setDutyCycleAtPowerOn()
pwmoutput.set_dutyCycleAtPowerOn()

YPwmOutput

Changes the PWM duty cycle at device power on.

```
def set_dutyCycleAtPowerOn( newval)
```

Remember to call the matching module `saveToFlash()` method, otherwise this call will have no effect.

Parameters :

newval a floating point number corresponding to the PWM duty cycle at device power on

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmoutput→set_enabled() YPwmOutput
pwmoutput→setEnabled()pwmoutput.set_enabled()

Stops or starts the PWM.

```
def set_enabled( newval)
```

Parameters :

newval either Y_ENABLED_FALSE or Y_ENABLED_TRUE

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmoutput→set_enabledAtPowerOn()
pwmoutput→setEnabledAtPowerOn()
pwmoutput.set_enabledAtPowerOn()

YPwmOutput

Changes the state of the PWM at device power on.

```
def set_enabledAtPowerOn( newval)
```

Remember to call the matching module `saveToFlash()` method, otherwise this call will have no effect.

Parameters :

newval either `Y_ENABLEDATPOWERON_FALSE` or `Y_ENABLEDATPOWERON_TRUE`, according to the state of the PWM at device power on

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmoutput→set_frequency()
pwmoutput→setFrequency()
pwmoutput.set_frequency()

YPwmOutput

Changes the PWM frequency.

```
def set_frequency( newval )
```

The duty cycle is kept unchanged thanks to an automatic pulse width change.

Parameters :

newval a floating point number corresponding to the PWM frequency

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmoutput→set_logicalName()
pwmoutput→setLogicalName()
pwmoutput.set_logicalName()

YPwmOutput

Changes the logical name of the PWM.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the logical name of the PWM.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmoutput→set_period()**YPwmOutput****pwmoutput→setPeriod()pwmoutput.set_period()**

Changes the PWM period in milliseconds.

```
def set_period( newval)
```

Parameters :

newval a floating point number corresponding to the PWM period in milliseconds

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmoutput→set_pulseDuration()
pwmoutput→setPulseDuration()
pwmoutput.set_pulseDuration()

YPwmOutput

Changes the PWM pulse length, in milliseconds.

```
def set_pulseDuration( newval)
```

A pulse length cannot be longer than period, otherwise it is truncated.

Parameters :

newval a floating point number corresponding to the PWM pulse length, in milliseconds

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmoutput→set(userData)
pwmoutput→setUserData()
pwmoutput.set(userData)

YPwmOutput

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.34. PwmPowerSource function interface

The Yoctopuce application programming interface allows you to configure the voltage source used by all PWM on the same device.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_pwmpowersource.js'></script>
nodejs var yoctolib = require('yoctolib');
var YPwmPowerSource = yoctolib.YPwmPowerSource;
php require_once('yocto_pwmpowersource.php');
cpp #include "yocto_pwmpowersource.h"
m #import "yocto_pwmpowersource.h"
pas uses yocto_pwmpowersource;
vb yocto_pwmpowersource.vb
cs yocto_pwmpowersource.cs
java import com.yoctopuce.YoctoAPI.YPwmPowerSource;
py from yocto_pwmpowersource import *

```

Global functions

yFindPwmPowerSource(func)

Retrieves a voltage source for a given identifier.

yFirstPwmPowerSource()

Starts the enumeration of Voltage sources currently accessible.

YPwmPowerSource methods

pwmpowersource→describe()

Returns a short text that describes unambiguously the instance of the voltage source in the form
TYPE (NAME) = SERIAL . FUNCTIONID.

pwmpowersource→get_advertisedValue()

Returns the current value of the voltage source (no more than 6 characters).

pwmpowersource→get_errorMessage()

Returns the error message of the latest error with the voltage source.

pwmpowersource→get_errorType()

Returns the numerical error code of the latest error with the voltage source.

pwmpowersource→get_friendlyName()

Returns a global identifier of the voltage source in the format MODULE_NAME . FUNCTION_NAME.

pwmpowersource→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

pwmpowersource→get_functionId()

Returns the hardware identifier of the voltage source, without reference to the module.

pwmpowersource→get_hardwareId()

Returns the unique hardware identifier of the voltage source in the form SERIAL . FUNCTIONID.

pwmpowersource→get_logicalName()

Returns the logical name of the voltage source.

pwmpowersource→get_module()

Gets the YModule object for the device on which the function is located.

pwmpowersource→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

3. Reference

pwmpowersource→get_powerMode()

Returns the selected power source for the PWM on the same device

pwmpowersource→get(userData)

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

pwmpowersource→isOnline()

Checks if the voltage source is currently reachable, without raising any error.

pwmpowersource→isOnline_async(callback, context)

Checks if the voltage source is currently reachable, without raising any error (asynchronous version).

pwmpowersource→load(msValidity)

Preloads the voltage source cache with a specified validity duration.

pwmpowersource→load_async(msValidity, callback, context)

Preloads the voltage source cache with a specified validity duration (asynchronous version).

pwmpowersource→nextPwmPowerSource()

Continues the enumeration of Voltage sources started using `yFirstPwmPowerSource()`.

pwmpowersource→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

pwmpowersource→set_logicalName(newval)

Changes the logical name of the voltage source.

pwmpowersource→set_powerMode(newval)

Changes the PWM power source.

pwmpowersource→set(userData)

Stores a user context provided as argument in the userData attribute of the function.

pwmpowersource→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YPwmPowerSource.FindPwmPowerSource() yFindPwmPowerSource() YPwmPowerSource.FindPwmPowerSource()

YPwmPowerSource

Retrieves a voltage source for a given identifier.

```
def FindPwmPowerSource( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the voltage source is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YPwmPowerSource.isOnline()` to test if the voltage source is indeed online at a given time. In case of ambiguity when looking for a voltage source by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the voltage source

Returns :

a `YPwmPowerSource` object allowing you to drive the voltage source.

YPwmPowerSource.FirstPwmPowerSource()
yFirstPwmPowerSource()
YPwmPowerSource.FirstPwmPowerSource()

YPwmPowerSource

Starts the enumeration of Voltage sources currently accessible.

```
def FirstPwmPowerSource( )
```

Use the method `YPwmPowerSource.nextPwmPowerSource()` to iterate on next Voltage sources.

Returns :

a pointer to a `YPwmPowerSource` object, corresponding to the first source currently online, or a null pointer if there are none.

pwmpowersource→describe()
pwmpowersource.describe()**YPwmPowerSource**

Returns a short text that describes unambiguously the instance of the voltage source in the form
TYPE (NAME) =SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the voltage source (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

pwmpowersource→get_advertisedValue()
pwmpowersource→advertisedValue()
pwmpowersource.get_advertisedValue()

YPwmPowerSource

Returns the current value of the voltage source (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the voltage source (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

pwmpowersource→get_errorMessage()
pwmpowersource→errorMessage()
pwmpowersource.get_errorMessage()

YPwmPowerSource

Returns the error message of the latest error with the voltage source.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the voltage source object

pwmpowersource→get_errorType()
pwmpowersource→errorType()
pwmpowersource.get_errorType()

YPwmPowerSource

Returns the numerical error code of the latest error with the voltage source.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the voltage source object

pwmpowersource→get_friendlyName()
pwmpowersource→friendlyName()
pwmpowersource.get_friendlyName()

YPwmPowerSource

Returns a global identifier of the voltage source in the format MODULE_NAME . FUNCTION_NAME.

def get_friendlyName()

The returned string uses the logical names of the module and of the voltage source if they are defined, otherwise the serial number of the module and the hardware identifier of the voltage source (for example: MyCustomName . relay1)

Returns :

a string that uniquely identifies the voltage source using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

pwmpowersource→get_functionDescriptor()
pwmpowersource→functionDescriptor()
pwmpowersource.get_functionDescriptor()

YPwmPowerSource

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

pwmpowersource→get_functionId()
pwmpowersource→functionId()
pwmpowersource.get_functionId()

YPwmPowerSource

Returns the hardware identifier of the voltage source, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the voltage source (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

pwmpowersource→get_hwrid()
pwmpowersource→hardwareId()
pwmpowersource.get_hwrid()

YPwmPowerSource

Returns the unique hardware identifier of the voltage source in the form SERIAL.FUNCTIONID.

```
def get_hwrid( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the voltage source (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the voltage source (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

pwmpowersource→get_logicalName()
pwmpowersource→logicalName()
pwmpowersource.get_logicalName()

YPwmPowerSource

Returns the logical name of the voltage source.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the voltage source.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

pwmpowersource→get_module()
pwmpowersource→module()
pwmpowersource.get_module()

YPwmPowerSource

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

pwmpowersource→get_powerMode()
pwmpowersource→powerMode()
pwmpowersource.get_powerMode()

YPwmPowerSource

Returns the selected power source for the PWM on the same device

```
def get_powerMode( )
```

Returns :

a value among Y_POWERMODE_USB_5V, Y_POWERMODE_USB_3V, Y_POWERMODE_EXT_V and Y_POWERMODE_OPNDRN corresponding to the selected power source for the PWM on the same device

On failure, throws an exception or returns Y_POWERMODE_INVALID.

pwmpowersource→get(userData)
pwmpowersource→userData()
pwmpowersource.get(userData)

YPwmPowerSource

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

pwmpowersource→isOnline()
pwmpowersource.isOnline()**YPwmPowerSource**

Checks if the voltage source is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the voltage source in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the voltage source.

Returns :

`true` if the voltage source can be reached, and `false` otherwise

pwmpowersource→load()pwmpowersource.load()**YPwmPowerSource**

Preloads the voltage source cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmpowersource→nextPwmPowerSource()
pwmpowersource.nextPwmPowerSource()**YPwmPowerSource**

Continues the enumeration of Voltage sources started using `yFirstPwmPowerSource()`.

```
def nextPwmPowerSource( )
```

Returns :

a pointer to a `YPwmPowerSource` object, corresponding to a voltage source currently online, or a `null` pointer if there are no more Voltage sources to enumerate.

pwmpowersource→registerValueCallback()
pwmpowersource.registerValueCallback()**YPwmPowerSource**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

pwmpowersource→set_logicalName()
pwmpowersource→setLogicalName()
pwmpowersource.set_logicalName()

YPwmPowerSource

Changes the logical name of the voltage source.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the voltage source.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmpowersource→set_powerMode()
pwmpowersource→setPowerMode()
pwmpowersource.set_powerMode()

YPwmPowerSource

Changes the PWM power source.

```
def set_powerMode( newval)
```

PWM can use isolated 5V from USB, isolated 3V from USB or voltage from an external power source. The PWM can also work in open drain mode. In that mode, the PWM actively pulls the line down. Warning: this setting is common to all PWM on the same device. If you change that parameter, all PWM located on the same device are affected. If you want the change to be kept after a device reboot, make sure to call the matching module `saveToFlash()`.

Parameters :

newval a value among `Y_POWERMODE_USB_5V`, `Y_POWERMODE_USB_3V`, `Y_POWERMODE_EXT_V` and `Y_POWERMODE_OPNDRN` corresponding to the PWM power source

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

pwmpowersource→set(userData)
pwmpowersource→setUserData()
pwmpowersource.set(userData)

YPwmPowerSource

Stores a user context provided as argument in the userData attribute of the function.

```
def setUserData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.35. Quaternion interface

The Yoctopuce API YQt class provides direct access to the Yocto3D attitude estimation using a quaternion. It is usually not needed to use the YQt class directly, as the YGyro class provides a more convenient higher-level interface.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_gyro.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YGyro = yoctolib.YGyro;
php	require_once('yocto_gyro.php');
cpp	#include "yocto_gyro.h"
m	#import "yocto_gyro.h"
pas	uses yocto_gyro;
vb	yocto_gyro.vb
cs	yocto_gyro.cs
java	import com.yoctopuce.YoctoAPI.YGyro;
py	from yocto_gyro import *

Global functions

yFindQt(func)

Retrieves a quaternion component for a given identifier.

yFirstQt()

Starts the enumeration of quaternion components currently accessible.

YQt methods

qt→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

qt→describe()

Returns a short text that describes unambiguously the instance of the quaternion component in the form TYPE (NAME) = SERIAL . FUNCTIONID.

qt→get_advertisedValue()

Returns the current value of the quaternion component (no more than 6 characters).

qt→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in units, as a floating point number.

qt→get_currentValue()

Returns the current value of the value, in units, as a floating point number.

qt→get_errorMessage()

Returns the error message of the latest error with the quaternion component.

qt→get_errorType()

Returns the numerical error code of the latest error with the quaternion component.

qt→get_friendlyName()

Returns a global identifier of the quaternion component in the format MODULE_NAME . FUNCTION_NAME.

qt→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

qt→get_functionId()

Returns the hardware identifier of the quaternion component, without reference to the module.

qt→get_hardwareId()

Returns the unique hardware identifier of the quaternion component in the form SERIAL.FUNCTIONID.
qt→get_highestValue()
Returns the maximal value observed for the value since the device was started.
qt→get_logFrequency()
Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.
qt→get_logicalName()
Returns the logical name of the quaternion component.
qt→get_lowestValue()
Returns the minimal value observed for the value since the device was started.
qt→get_module()
Gets the YModule object for the device on which the function is located.
qt→get_module_async(callback, context)
Gets the YModule object for the device on which the function is located (asynchronous version).
qt→get_recordedData(startTime, endTime)
Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.
qt→get_reportFrequency()
Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.
qt→get_resolution()
Returns the resolution of the measured values.
qt→get_unit()
Returns the measuring unit for the value.
qt→get_userData()
Returns the value of the userData attribute, as previously stored using method set(userData).
qt→isOnline()
Checks if the quaternion component is currently reachable, without raising any error.
qt→isOnline_async(callback, context)
Checks if the quaternion component is currently reachable, without raising any error (asynchronous version).
qt→load(msValidity)
Preloads the quaternion component cache with a specified validity duration.
qt→loadCalibrationPoints(rawValues, refValues)
Retrieves error correction data points previously entered using the method calibrateFromPoints.
qt→load_async(msValidity, callback, context)
Preloads the quaternion component cache with a specified validity duration (asynchronous version).
qt→nextQt()
Continues the enumeration of quaternion components started using yFirstQt().
qt→registerTimedReportCallback(callback)
Registers the callback function that is invoked on every periodic timed notification.
qt→registerValueCallback(callback)
Registers the callback function that is invoked on every change of advertised value.
qt→set_highestValue(newval)
Changes the recorded maximal value observed.
qt→set_logFrequency(newval)
Changes the datalogger recording frequency for this function.
qt→set_logicalName(newval)

3. Reference

Changes the logical name of the quaternion component.

qt→set_lowestValue(newval)

Changes the recorded minimal value observed.

qt→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

qt→set_resolution(newval)

Changes the resolution of the measured physical values.

qt→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

qt→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YQt.FindQt()**YQt****yFindQt() YQt.FindQt()**

Retrieves a quaternion component for a given identifier.

```
def FindQt( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the quaternion component is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YQt.isOnline()` to test if the quaternion component is indeed online at a given time. In case of ambiguity when looking for a quaternion component by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the quaternion component

Returns :

a `YQt` object allowing you to drive the quaternion component.

YQt.FirstQt() yFirstQt()YQt.FirstQt()

YQt

Starts the enumeration of quaternion components currently accessible.

```
def FirstQt( )
```

Use the method `YQt .nextQt()` to iterate on next quaternion components.

Returns :

a pointer to a `YQt` object, corresponding to the first quaternion component currently online, or a `null` pointer if there are none.

qt→calibrateFromPoints()qt.calibrateFromPoints()**YQt**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

qt→describe()qt.describe()**YQt**

Returns a short text that describes unambiguously the instance of the quaternion component in the form TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

```
a string that describes the quaternion component (ex:  
Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)
```

qt→get_advertisedValue()
qt→advertisedValue()qt.get_advertisedValue()**YQt**

Returns the current value of the quaternion component (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the quaternion component (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

qt→get_currentRawValue()	YQt
qt→currentRawValue()qt.get_currentRawValue()	

Returns the uncalibrated, unrounded raw value returned by the sensor, in units, as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in units, as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

qt→get_currentValue()
qt→currentValue()qt.get_currentValue()**YQt**

Returns the current value of the value, in units, as a floating point number.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current value of the value, in units, as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

**qt→get_errorMessage()
qt→errorMessage()qt.get_errorMessage()****YQt**

Returns the error message of the latest error with the quaternion component.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the quaternion component object

qt→get_errorType()**YQt****qt→errorType()qt.get_errorType()**

Returns the numerical error code of the latest error with the quaternion component.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the quaternion component object

qt→get_friendlyName()
qt→friendlyName()qt.get_friendlyName()**YQt**

Returns a global identifier of the quaternion component in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the quaternion component if they are defined, otherwise the serial number of the module and the hardware identifier of the quaternion component (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the quaternion component using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

qt->get_functionDescriptor()**YQt****qt->functionDescriptor()qt.get_functionDescriptor()**

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

qt→get_functionId()

YQt

qt→functionId()qt.get_functionId()

Returns the hardware identifier of the quaternion component, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the quaternion component (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

qt→get_hardwareId()**YQt****qt→hardwareId()qt.get_hardwareId()**

Returns the unique hardware identifier of the quaternion component in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the quaternion component (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the quaternion component (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

qt→get_highestValue()**YQt****qt→highestValue()qt.get_highestValue()**

Returns the maximal value observed for the value since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the value since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

qt→get_logFrequency()**YQt****qt→logFrequency()qt.get_logFrequency()**

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

qt→get_logicalName()
qt→logicalName()qt.get_logicalName()**YQt**

Returns the logical name of the quaternion component.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the quaternion component.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

qt→get_lowestValue()**YQt****qt→lowestValue()qt.get_lowestValue()**

Returns the minimal value observed for the value since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the value since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

qt→get_module()**YQt****qt→module()qt.get_module()**

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

qt→get_recordedData()**YQt****qt→recordedData()qt.get_recordedData()**

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime)
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

qt→get_reportFrequency() **YQt**
qt→reportFrequency()qt.get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

qt→get_resolution()**YQt****qt→resolution()qt.get_resolution()**

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

qt→get_unit() qt→unit()qt.get_unit()

YQt

Returns the measuring unit for the value.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the value

On failure, throws an exception or returns Y_UNIT_INVALID.

qt→get(userData())
qt→userData()qt.get(userData())**YQt**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData( )
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

qt→isOnline()qt.isOnline()**YQt**

Checks if the quaternion component is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the quaternion component in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the quaternion component.

Returns :

`true` if the quaternion component can be reached, and `false` otherwise

qt→load()qt.load()**YQt**

Preloads the quaternion component cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

qt→loadCalibrationPoints()qt.loadCalibrationPoints()**YQt**

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

qt→nextQt()qt.nextQt()**YQt**

Continues the enumeration of quaternion components started using `yFirstQt()`.

```
def nextQt( )
```

Returns :

a pointer to a `YQt` object, corresponding to a quaternion component currently online, or a `null` pointer if there are no more quaternion components to enumerate.

**qt→registerTimedReportCallback()
qt.registerTimedReportCallback()**

YQt

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

qt→registerValueCallback()
qt.registerValueCallback()

YQt

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

**qt→set_highestValue()
qt→setHighestValue()qt.set_highestValue()****YQt**

Changes the recorded maximal value observed.

```
def set_highestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

qt→set_logFrequency()**YQt****qt→setLogFrequency()qt.set_logFrequency()**

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval)
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

qt→set_logicalName()
qt→setLogicalName()qt.set_logicalName()**YQt**

Changes the logical name of the quaternion component.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the quaternion component.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

qt→set_lowestValue()**YQt****qt→setLowestValue()qt.set_lowestValue()**

Changes the recorded minimal value observed.

```
def set_lowestValue( newval )
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

qt→set_reportFrequency() **YQt**
qt→setReportFrequency()qt.set_reportFrequency()

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval)
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

qt→set_resolution()**YQt****qt→setResolution()qt.set_resolution()**

Changes the resolution of the measured physical values.

```
def set_resolution( newval )
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

qt→set(userData)

YQt

qt→setUserData()qt.set(userData)

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData):
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.36. Real Time Clock function interface

The RealTimeClock function maintains and provides current date and time, even accross power cut lasting several days. It is the base for automated wake-up functions provided by the WakeUpScheduler. The current time may represent a local time as well as an UTC time, but no automatic time change will occur to account for daylight saving time.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_realtimedclock.js'></script>
node.js	var yoctolib = require('yoctolib');
	var YRealTimeClock = yoctolib.YRealTimeClock;
php	require_once('yocto_realtimedclock.php');
cpp	#include "yocto_realtimedclock.h"
m	#import "yocto_realtimedclock.h"
pas	uses yocto_realtimedclock;
vb	yocto_realtimedclock.vb
cs	yocto_realtimedclock.cs
java	import com.yoctopuce.YoctoAPI.YRealTimeClock;
py	from yocto_realtimedclock import *

Global functions

yFindRealTimeClock(func)

Retrieves a clock for a given identifier.

yFirstRealTimeClock()

Starts the enumeration of clocks currently accessible.

YRealTimeClock methods

realtimeclock→describe()

Returns a short text that describes unambiguously the instance of the clock in the form TYPE (NAME)=SERIAL . FUNCTIONID.

realtimeclock→get_advertisedValue()

Returns the current value of the clock (no more than 6 characters).

realtimeclock→get_dateTime()

Returns the current time in the form "YYYY/MM/DD hh:mm:ss"

realtimeclock→get_errorMessage()

Returns the error message of the latest error with the clock.

realtimeclock→get_errorType()

Returns the numerical error code of the latest error with the clock.

realtimeclock→get_friendlyName()

Returns a global identifier of the clock in the format MODULE_NAME . FUNCTION_NAME.

realtimeclock→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

realtimeclock→get_functionId()

Returns the hardware identifier of the clock, without reference to the module.

realtimeclock→get_hardwareId()

Returns the unique hardware identifier of the clock in the form SERIAL . FUNCTIONID.

realtimeclock→get_logicalName()

Returns the logical name of the clock.

realtimeclock→get_module()

3. Reference

Gets the YModule object for the device on which the function is located.

realtimeclock→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

realtimeclock→get_timeSet()

Returns true if the clock has been set, and false otherwise.

realtimeclock→get_unixTime()

Returns the current time in Unix format (number of elapsed seconds since Jan 1st, 1970).

realtimeclock→get_userData()

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

realtimeclock→get_utcOffset()

Returns the number of seconds between current time and UTC time (time zone).

realtimeclock→isOnline()

Checks if the clock is currently reachable, without raising any error.

realtimeclock→isOnline_async(callback, context)

Checks if the clock is currently reachable, without raising any error (asynchronous version).

realtimeclock→load(msValidity)

Preloads the clock cache with a specified validity duration.

realtimeclock→load_async(msValidity, callback, context)

Preloads the clock cache with a specified validity duration (asynchronous version).

realtimeclock→nextRealTimeClock()

Continues the enumeration of clocks started using `yFirstRealTimeClock()`.

realtimeclock→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

realtimeclock→set_logicalName(newval)

Changes the logical name of the clock.

realtimeclock→set_unixTime(newval)

Changes the current time.

realtimeclock→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

realtimeclock→set_utcOffset(newval)

Changes the number of seconds between current time and UTC time (time zone).

realtimeclock→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YRealTimeClock.FindRealTimeClock() yFindRealTimeClock() YRealTimeClock.FindRealTimeClock()

YRealTimeClock

Retrieves a clock for a given identifier.

```
def FindRealTimeClock( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the clock is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YRealTimeClock.isOnline()` to test if the clock is indeed online at a given time. In case of ambiguity when looking for a clock by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the clock

Returns :

a `YRealTimeClock` object allowing you to drive the clock.

YRealTimeClock.FirstRealTimeClock()

YRealTimeClock

yFirstRealTimeClock()

YRealTimeClock.FirstRealTimeClock()

Starts the enumeration of clocks currently accessible.

```
def FirstRealTimeClock()
```

Use the method `YRealTimeClock.nextRealTimeClock()` to iterate on next clocks.

Returns :

a pointer to a `YRealTimeClock` object, corresponding to the first clock currently online, or a null pointer if there are none.

realtimeclock→describe()realtimeclock.describe()**YRealTimeClock**

Returns a short text that describes unambiguously the instance of the clock in the form TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the clock (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

realtimeclock→get_advertisedValue()
realtimeclock→advertisedValue()
realtimeclock.get_advertisedValue()

YRealTimeClock

Returns the current value of the clock (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the clock (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

realtimeclock→get_dateTime()
realtimeclock→dateTime()
realtimeclock.get_dateTime()

YRealTimeClock

Returns the current time in the form "YYYY/MM/DD hh:mm:ss"

```
def get_dateTime( )
```

Returns :

a string corresponding to the current time in the form "YYYY/MM/DD hh:mm:ss"

On failure, throws an exception or returns Y_DATEETIME_INVALID.

realtimeclock→getErrorMessage()
realtimeclock→errorMessage()
realtimeclock.getErrorMessage()

YRealTimeClock

Returns the error message of the latest error with the clock.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the clock object

realtimeclock→get_errorType()
realtimeclock→errorType()
realtimeclock.get_errorType()

YRealTimeClock

Returns the numerical error code of the latest error with the clock.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the clock object

`realtimeclock→get_friendlyName()`
`realtimeclock→friendlyName()`
`realtimeclock.get_friendlyName()`

YRealTimeClock

Returns a global identifier of the clock in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the clock if they are defined, otherwise the serial number of the module and the hardware identifier of the clock (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the clock using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

realtimeclock→get_functionDescriptor()
realtimeclock→functionDescriptor()
realtimeclock.get_functionDescriptor()

YRealTimeClock

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

realtimeclock→get_functionId()
realtimeclock→functionId()
realtimeclock.get_functionId()

YRealTimeClock

Returns the hardware identifier of the clock, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the clock (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

realtimeclock→get_hwId()
realtimeclock→hwId()
realtimeclock.get_hwId()

YRealTimeClock

Returns the unique hardware identifier of the clock in the form SERIAL.FUNCTIONID.

def get_hwId()

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the clock (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the clock (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

realtimeclock→get_logicalName()
realtimeclock→logicalName()
realtimeclock.get_logicalName()

YRealTimeClock

Returns the logical name of the clock.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the clock.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

realtimeclock→get_module()**YRealTimeClock****realtimeclock→module()realtimeclock.get_module()**

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

realtimeclock→get_timeSet()

YRealTimeClock

realtimeclock→timeSet()realtimeclock.get_timeSet()

Returns true if the clock has been set, and false otherwise.

```
def get_timeSet( )
```

Returns :

either Y_TIMESET_FALSE or Y_TIMESET_TRUE, according to true if the clock has been set, and false otherwise

On failure, throws an exception or returns Y_TIMESET_INVALID.

realtimeclock→get_unixTime()
realtimeclock→unixTime()
realtimeclock.get_unixTime()

YRealTimeClock

Returns the current time in Unix format (number of elapsed seconds since Jan 1st, 1970).

```
def get_unixTime( )
```

Returns :

an integer corresponding to the current time in Unix format (number of elapsed seconds since Jan 1st, 1970)

On failure, throws an exception or returns Y_UNIXTIME_INVALID.

realtimeclock→get(userData)
realtimeclock→userData()
realtimeclock.get(userData)

YRealTimeClock

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

realtimeclock→get_utcOffset()
realtimeclock→utcOffset()
realtimeclock.get_utcOffset()

YRealTimeClock

Returns the number of seconds between current time and UTC time (time zone).

```
def get_utcOffset( )
```

Returns :

an integer corresponding to the number of seconds between current time and UTC time (time zone)

On failure, throws an exception or returns Y_UTCOFFSET_INVALID.

realtimeclock→isOnline()realtimeclock.isOnline()**YRealTimeClock**

Checks if the clock is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the clock in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the clock.

Returns :

`true` if the clock can be reached, and `false` otherwise

realtimeclock→load()realtimeclock.load()**YRealTimeClock**

Preloads the clock cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

realtimeclock→nextRealTimeClock()
realtimeclock.nextRealTimeClock()

YRealTimeClock

Continues the enumeration of clocks started using `yFirstRealTimeClock()`.

```
def nextRealTimeClock( )
```

Returns :

a pointer to a `YRealTimeClock` object, corresponding to a clock currently online, or a `null` pointer if there are no more clocks to enumerate.

realtimeclock→registerValueCallback()
realtimeclock.registerValueCallback()**YRealTimeClock**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

`realtimeclock→set_logicalName()`
`realtimeclock→setLogicalName()`
`realtimeclock.set_logicalName()`

YRealTimeClock

Changes the logical name of the clock.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the clock.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

realtimeclock→set_unixTime()
realtimeclock→setUnixTime()
realtimeclock.set_unixTime()

YRealTimeClock

Changes the current time.

```
def set_unixTime( newval)
```

Time is specified in Unix format (number of elapsed seconds since Jan 1st, 1970). If current UTC time is known, utcOffset will be automatically adjusted for the new specified time.

Parameters :

newval an integer corresponding to the current time

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

realtimeclock→set(userData)
realtimeclock→setUserData()
realtimeclock.set(userData)

YRealTimeClock

Stores a user context provided as argument in the userData attribute of the function.

```
def setUserData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

realtimeclock→set_utcOffset()
realtimeclock→setUtcOffset()
realtimeclock.set_utcOffset()

YRealTimeClock

Changes the number of seconds between current time and UTC time (time zone).

```
def set_utcOffset( newval )
```

The timezone is automatically rounded to the nearest multiple of 15 minutes. If current UTC time is known, the current time will automatically be updated according to the selected time zone.

Parameters :

newval an integer corresponding to the number of seconds between current time and UTC time (time zone)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

3.37. Reference frame configuration

This class is used to setup the base orientation of the Yocto-3D, so that the orientation functions, relative to the earth surface plane, use the proper reference frame. The class also implements a tridimensional sensor calibration process, which can compensate for local variations of standard gravity and improve the precision of the tilt sensors.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_refframe.js'></script>
nodejs var yoctolib = require('yoctolib');
var YRefFrame = yoctolib.YRefFrame;
php require_once('yocto_refframe.php');
cpp #include "yocto_refframe.h"
m #import "yocto_refframe.h"
pas uses yocto_refframe;
vb yocto_refframe.vb
cs yocto_refframe.cs
java import com.yoctopuce.YoctoAPI.YRefFrame;
py from yocto_refframe import *

```

Global functions

yFindRefFrame(func)

Retrieves a reference frame for a given identifier.

yFirstRefFrame()

Starts the enumeration of reference frames currently accessible.

YRefFrame methods

refframe→cancel3DCalibration()

Aborts the sensors tridimensional calibration process et restores normal settings.

refframe→describe()

Returns a short text that describes unambiguously the instance of the reference frame in the form TYPE(NAME)=SERIAL.FUNCTIONID.

refframe→get_3DCalibrationHint()

Returns instructions to proceed to the tridimensional calibration initiated with method start3DCalibration.

refframe→get_3DCalibrationLogMsg()

Returns the latest log message from the calibration process.

refframe→get_3DCalibrationProgress()

Returns the global process indicator for the tridimensional calibration initiated with method start3DCalibration.

refframe→get_3DCalibrationStage()

Returns index of the current stage of the calibration initiated with method start3DCalibration.

refframe→get_3DCalibrationStageProgress()

Returns the process indicator for the current stage of the calibration initiated with method start3DCalibration.

refframe→get_advertisedValue()

Returns the current value of the reference frame (no more than 6 characters).

refframe→get_bearing()

Returns the reference bearing used by the compass.

refframe→get_errorMessage()

Returns the error message of the latest error with the reference frame.

refframe→get_errorType()

Returns the numerical error code of the latest error with the reference frame.

refframe→get_friendlyName()

Returns a global identifier of the reference frame in the format MODULE_NAME . FUNCTION_NAME.

refframe→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

refframe→get_functionId()

Returns the hardware identifier of the reference frame, without reference to the module.

refframe→get_hardwareId()

Returns the unique hardware identifier of the reference frame in the form SERIAL . FUNCTIONID.

refframe→get_logicalName()

Returns the logical name of the reference frame.

refframe→get_module()

Gets the YModule object for the device on which the function is located.

refframe→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

refframe→get_mountOrientation()

Returns the installation orientation of the device, as configured in order to define the reference frame for the compass and the pitch/roll tilt sensors.

refframe→get_mountPosition()

Returns the installation position of the device, as configured in order to define the reference frame for the compass and the pitch/roll tilt sensors.

refframe→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

refframe→isOnline()

Checks if the reference frame is currently reachable, without raising any error.

refframe→isOnline_async(callback, context)

Checks if the reference frame is currently reachable, without raising any error (asynchronous version).

refframe→load(msValidity)

Preloads the reference frame cache with a specified validity duration.

refframe→load_async(msValidity, callback, context)

Preloads the reference frame cache with a specified validity duration (asynchronous version).

refframe→more3DCalibration()

Continues the sensors tridimensional calibration process previously initiated using method start3DCalibration.

refframe→nextRefFrame()

Continues the enumeration of reference frames started using yFirstRefFrame().

refframe→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

refframe→save3DCalibration()

Applies the sensors tridimensional calibration parameters that have just been computed.

refframe→set_bearing(newval)

Changes the reference bearing used by the compass.

refframe→set_logicalName(newval)

3. Reference

Changes the logical name of the reference frame.

refframe→set_mountPosition(*position*, *orientation*)

Changes the compass and tilt sensor frame of reference.

refframe→set(userData)

Stores a user context provided as argument in the userData attribute of the function.

refframe→start3DCalibration()

Initiates the sensors tridimensional calibration process.

refframe→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YRefFrame.FindRefFrame()**YRefFrame****yFindRefFrame()YRefFrame.FindRefFrame()**

Retrieves a reference frame for a given identifier.

```
def FindRefFrame( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the reference frame is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YRefFrame.isOnline()` to test if the reference frame is indeed online at a given time. In case of ambiguity when looking for a reference frame by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the reference frame

Returns :

a `YRefFrame` object allowing you to drive the reference frame.

YRefFrame.FirstRefFrame()

YRefFrame

yFirstRefFrame()YRefFrame.FirstRefFrame()

Starts the enumeration of reference frames currently accessible.

```
def FirstRefFrame( )
```

Use the method `YRefFrame.nextRefFrame()` to iterate on next reference frames.

Returns :

a pointer to a `YRefFrame` object, corresponding to the first reference frame currently online, or a null pointer if there are none.

refframe→cancel3DCalibration()
refframe.cancel3DCalibration()**YRefFrame**

Aborts the sensors tridimensional calibration process et restores normal settings.

```
def cancel3DCalibration( )
```

On failure, throws an exception or returns a negative error code.

refframe→describe()refferame.describe()**YRefFrame**

Returns a short text that describes unambiguously the instance of the reference frame in the form
TYPE (NAME)=SERIAL . FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the reference frame (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

refframe→get_3DCalibrationHint()
refframe→3DCalibrationHint()
refframe.get_3DCalibrationHint()

YRefFrame

Returns instructions to proceed to the tridimensional calibration initiated with method start3DCalibration.

```
def get_3DCalibrationHint( )
```

Returns :
a character string.

`refframe→get_3DCalibrationLogMsg()`

YRefFrame

`refframe→3DCalibrationLogMsg()`

`refframe.get_3DCalibrationLogMsg()`

Returns the latest log message from the calibration process.

```
def get_3DCalibrationLogMsg( )
```

When no new message is available, returns an empty string.

Returns :

a character string.

refframe→get_3DCalibrationProgress()
refframe→3DCalibrationProgress()
refframe.get_3DCalibrationProgress()

YRefFrame

Returns the global process indicator for the tridimensional calibration initiated with method start3DCalibration.

```
def get_3DCalibrationProgress( )
```

Returns :

an integer between 0 (not started) and 100 (stage completed).

`refframe→get_3DCalibrationStage()`
`refframe→3DCalibrationStage()`
`refframe.get_3DCalibrationStage()`

YRefFrame

Returns index of the current stage of the calibration initiated with method `start3DCalibration`.

```
def get_3DCalibrationStage( )
```

Returns :

an integer, growing each time a calibration stage is completed.

refframe→get_3DCalibrationStageProgress()
refframe→3DCalibrationStageProgress()
refframe.get_3DCalibrationStageProgress()

YRefFrame

Returns the process indicator for the current stage of the calibration initiated with method start3DCalibration.

```
def get_3DCalibrationStageProgress( )
```

Returns :

an integer between 0 (not started) and 100 (stage completed).

refframe→get_advertisedValue()
refframe→advertisedValue()
refframe.get_advertisedValue()

YRefFrame

Returns the current value of the reference frame (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the reference frame (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

refframe→get_bearing()**YRefFrame****refframe→bearing()refframe.get_bearing()**

Returns the reference bearing used by the compass.

```
def get_bearing( )
```

The relative bearing indicated by the compass is the difference between the measured magnetic heading and the reference bearing indicated here.

Returns :

a floating point number corresponding to the reference bearing used by the compass

On failure, throws an exception or returns Y_BEARING_INVALID.

refframe→getErrorMessage()
refframe→errorMessage()
refframe.getErrorMessage()

YRefFrame

Returns the error message of the latest error with the reference frame.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the reference frame object

refframe→get_errorType()**YRefFrame****refframe→errorType()refframe.get_errorType()**

Returns the numerical error code of the latest error with the reference frame.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the reference frame object

`refframe→get_friendlyName()`

YRefFrame

`refframe→friendlyName()refframe.get_friendlyName()`

Returns a global identifier of the reference frame in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the reference frame if they are defined, otherwise the serial number of the module and the hardware identifier of the reference frame (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the reference frame using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

refframe→get_functionDescriptor()
refframe→functionDescriptor()
refframe.get_functionDescriptor()

YRefFrame

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

def get_functionDescriptor()

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

`refframe→get_functionId()`

YRefFrame

`refframe→functionId()refframe.get_functionId()`

Returns the hardware identifier of the reference frame, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the reference frame (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

refframe→get_hardwareId()**YRefFrame****refframe→hardwareId()refframe.get_hardwareId()**

Returns the unique hardware identifier of the reference frame in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the reference frame (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the reference frame (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

`refframe→get_logicalName()`

YRefFrame

`refframe→logicalName()refframe.get_logicalName()`

Returns the logical name of the reference frame.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the reference frame.

On failure, throws an exception or returns `Y_LOGICALNAME_INVALID`.

refframe→get_module()**YRefFrame****refframe→module()refframe.get_module()**

Gets the YModule object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

refframe→get_mountOrientation()
refframe→mountOrientation()
refframe.get_mountOrientation()

YRefFrame

Returns the installation orientation of the device, as configured in order to define the reference frame for the compass and the pitch/roll tilt sensors.

```
def get_mountOrientation( )
```

Returns :

a value among the enumeration Y_MOUNTORIENTATION (Y_MOUNTORIENTATION_TWELVE, Y_MOUNTORIENTATION_THREE, Y_MOUNTORIENTATION_SIX, Y_MOUNTORIENTATION_NINE) corresponding to the orientation of the "X" arrow on the device, as on a clock dial seen from an observer in the center of the box. On the bottom face, the 12H orientation points to the front, while on the top face, the 12H orientation points to the rear.

On failure, throws an exception or returns a negative error code.

refframe→get_mountPosition()**YRefFrame****refframe→mountPosition()****refframe.get_mountPosition()**

Returns the installation position of the device, as configured in order to define the reference frame for the compass and the pitch/roll tilt sensors.

```
def get_mountPosition( )
```

Returns :

a value among the Y_MOUNTPOSITION enumeration (Y_MOUNTPOSITION_BOTTOM, Y_MOUNTPOSITION_TOP, Y_MOUNTPOSITION_FRONT, Y_MOUNTPOSITION_RIGHT, Y_MOUNTPOSITION_REAR, Y_MOUNTPOSITION_LEFT), corresponding to the installation in a box, on one of the six faces.

On failure, throws an exception or returns a negative error code.

`refframe→get(userData)`

YRefFrame

`refframe→userData(refframe.get(userData))`

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

refframe→isOnline()refframe.isOnline()**YRefFrame**

Checks if the reference frame is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the reference frame in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the reference frame.

Returns :

`true` if the reference frame can be reached, and `false` otherwise

refframe→load()refframe.load()**YRefFrame**

Preloads the reference frame cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

refframe→more3DCalibration()
refframe.more3DCalibration()**YRefFrame**

Continues the sensors tridimensional calibration process previously initiated using method `start3DCalibration`.

```
def more3DCalibration( )
```

This method should be called approximately 5 times per second, while positioning the device according to the instructions provided by method `get_3DCalibrationHint`. Note that the instructions change during the calibration process. On failure, throws an exception or returns a negative error code.

refframe→nextRefFrame()refframe.nextRefFrame()

YRefFrame

Continues the enumeration of reference frames started using `yFirstRefFrame()`.

```
def nextRefFrame( )
```

Returns :

a pointer to a `YRefFrame` object, corresponding to a reference frame currently online, or a null pointer if there are no more reference frames to enumerate.

**refframe→registerValueCallback()
refframe.registerValueCallback()****YRefFrame**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

refframe→save3DCalibration()
refframe.save3DCalibration()

YRefFrame

Applies the sensors tridimensional calibration parameters that have just been computed.

```
def save3DCalibration( )
```

Remember to call the `saveToFlash()` method of the module if the changes must be kept when the device is restarted. On failure, throws an exception or returns a negative error code.

refframe→set_bearing()**YRefFrame****refframe→setBearing()refframe.set_bearing()**

Changes the reference bearing used by the compass.

```
def set_bearing( newval)
```

The relative bearing indicated by the compass is the difference between the measured magnetic heading and the reference bearing indicated here. For instance, if you setup as reference bearing the value of the earth magnetic declination, the compass will provide the orientation relative to the geographic North. Similarly, when the sensor is not mounted along the standard directions because it has an additional yaw angle, you can set this angle in the reference bearing so that the compass provides the expected natural direction. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a floating point number corresponding to the reference bearing used by the compass

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

`refframe→set_logicalName()`
`refframe→setLogicalName()`
`refframe.set_logicalName()`

YRefFrame

Changes the logical name of the reference frame.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the logical name of the reference frame.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

refframe→set_mountPosition()
refframe→setMountPosition()
refframe.set_mountPosition()

YRefFrame

Changes the compass and tilt sensor frame of reference.

```
def set_mountPosition( position, orientation)
```

The magnetic compass and the tilt sensors (pitch and roll) naturally work in the plane parallel to the earth surface. In case the device is not installed upright and horizontally, you must select its reference orientation (parallel to the earth surface) so that the measures are made relative to this position.

Parameters :

position a value among the Y_MOUNTPOSITION enumeration (Y_MOUNTPOSITION_BOTTOM, Y_MOUNTPOSITION_TOP, Y_MOUNTPOSITION_FRONT, Y_MOUNTPOSITION_RIGHT, Y_MOUNTPOSITION_REAR, Y_MOUNTPOSITION_LEFT), corresponding to the installation in a box, on one of the six faces.

orientation a value among the enumeration Y_MOUNTORIENTATION (Y_MOUNTORIENTATION_TWELVE, Y_MOUNTORIENTATION_THREE, Y_MOUNTORIENTATION_SIX, Y_MOUNTORIENTATION_NINE) corresponding to the orientation of the "X" arrow on the device, as on a clock dial seen from an observer in the center of the box. On the bottom face, the 12H orientation points to the front, while on the top face, the 12H orientation points to the rear. Remember to call the saveToFlash() method of the module if the modification must be kept.

`refframe→set(userData)`

YRefFrame

`refframe→setUserData()refframe.set(userData)`

Stores a user context provided as argument in the `userData` attribute of the function.

```
def set(userData)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

`data` any kind of object to be stored

refframe→start3DCalibration()
refframe.start3DCalibration()**YRefFrame**

Initiates the sensors tridimensional calibration process.

```
def start3DCalibration( )
```

This calibration is used at low level for inertial position estimation and to enhance the precision of the tilt sensors. After calling this method, the device should be moved according to the instructions provided by method `get_3DCalibrationHint`, and `more3DCalibration` should be invoked about 5 times per second. The calibration procedure is completed when the method `get_3DCalibrationProgress` returns 100. At this point, the computed calibration parameters can be applied using method `save3DCalibration`. The calibration process can be canceled at any time using method `cancel3DCalibration`. On failure, throws an exception or returns a negative error code.

3.38. Relay function interface

The Yoctopuce application programming interface allows you to switch the relay state. This change is not persistent: the relay will automatically return to its idle position whenever power is lost or if the module is restarted. The library can also generate automatically short pulses of determined duration. On devices with two output for each relay (double throw), the two outputs are named A and B, with output A corresponding to the idle position (at power off) and the output B corresponding to the active state. If you prefer the alternate default state, simply switch your cables on the board.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_relay.js'></script>
node.js	var yoctolib = require('yoctolib');
	var YRelay = yoctolib.YRelay;
php	require_once('yocto_relay.php');
cpp	#include "yocto_relay.h"
m	#import "yocto_relay.h"
pas	uses yocto_relay;
vb	yocto_relay.vb
cs	yocto_relay.cs
java	import com.yoctopuce.YoctoAPI.YRelay;
py	from yocto_relay import *

Global functions

yFindRelay(func)

Retrieves a relay for a given identifier.

yFirstRelay()

Starts the enumeration of relays currently accessible.

YRelay methods

relay->delayedPulse(ms_delay, ms_duration)

Schedules a pulse.

relay->describe()

Returns a short text that describes unambiguously the instance of the relay in the form TYPE (NAME)=SERIAL.FUNCTIONID.

relay->get_advertisedValue()

Returns the current value of the relay (no more than 6 characters).

relay->get_countdown()

Returns the number of milliseconds remaining before a pulse (delayedPulse() call). When there is no scheduled pulse, returns zero.

relay->get_errorMessage()

Returns the error message of the latest error with the relay.

relay->get_errorType()

Returns the numerical error code of the latest error with the relay.

relay->get_friendlyName()

Returns a global identifier of the relay in the format MODULE_NAME . FUNCTION_NAME.

relay->get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

relay->get_functionId()

Returns the hardware identifier of the relay, without reference to the module.

relay->get_hardwareId()

Returns the unique hardware identifier of the relay in the form SERIAL.FUNCTIONID.

relay→get_logicalName()

Returns the logical name of the relay.

relay→get_maxTimeOnStateA()

Retourne the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state A before automatically switching back in to B state.

relay→get_maxTimeOnStateB()

Retourne the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state B before automatically switching back in to A state.

relay→get_module()

Gets the YModule object for the device on which the function is located.

relay→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

relay→get_output()

Returns the output state of the relays, when used as a simple switch (single throw).

relay→get_pulseTimer()

Returns the number of milliseconds remaining before the relays is returned to idle position (state A), during a measured pulse generation.

relay→get_state()

Returns the state of the relays (A for the idle position, B for the active position).

relay→get_stateAtPowerOn()

Returns the state of the relays at device startup (A for the idle position, B for the active position, UNCHANGED for no change).

relay→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

relay→isOnline()

Checks if the relay is currently reachable, without raising any error.

relay→isOnline_async(callback, context)

Checks if the relay is currently reachable, without raising any error (asynchronous version).

relay→load(msValidity)

Preloads the relay cache with a specified validity duration.

relay→load_async(msValidity, callback, context)

Preloads the relay cache with a specified validity duration (asynchronous version).

relay→nextRelay()

Continues the enumeration of relays started using yFirstRelay().

relay→pulse(ms_duration)

Sets the relay to output B (active) for a specified duration, then brings it automatically back to output A (idle state).

relay→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

relay→set_logicalName(newval)

Changes the logical name of the relay.

relay→set_maxTimeOnStateA(newval)

Sets the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state A before automatically switching back in to B state.

relay→set_maxTimeOnStateB(newval)

3. Reference

Sets the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state B before automatically switching back in to A state.

relay→set_output(newval)

Changes the output state of the relays, when used as a simple switch (single throw).

relay→set_state(newval)

Changes the state of the relays (A for the idle position, B for the active position).

relay→set_stateAtPowerOn(newval)

Preset the state of the relays at device startup (A for the idle position, B for the active position, UNCHANGED for no modification).

relay→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

relay→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YRelay.FindRelay()

YRelay

yFindRelay()YRelay.FindRelay()

Retrieves a relay for a given identifier.

```
def FindRelay( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the relay is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YRelay.isOnline()` to test if the relay is indeed online at a given time. In case of ambiguity when looking for a relay by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the relay

Returns :

a `YRelay` object allowing you to drive the relay.

YRelay.FirstRelay()

YRelay

yFirstRelay()YRelay.FirstRelay()

Starts the enumeration of relays currently accessible.

```
def FirstRelay( )
```

Use the method `YRelay.nextRelay()` to iterate on next relays.

Returns :

a pointer to a `YRelay` object, corresponding to the first relay currently online, or a `null` pointer if there are none.

relay→delayedPulse()relay.delayedPulse()**YRelay**

Schedules a pulse.

```
def delayedPulse( ms_delay, ms_duration)
```

Parameters :

ms_delay waiting time before the pulse, in millisecondes

ms_duration pulse duration, in millisecondes

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

relay→describe()relay.describe()**YRelay**

Returns a short text that describes unambiguously the instance of the relay in the form TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the relay (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

relay→get_advertisedValue()**YRelay****relay→advertisedValue()relay.get_advertisedValue()**

Returns the current value of the relay (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the relay (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

relay->get_countdown()
relay->countdown()relay.get_countdown()**YRelay**

Returns the number of milliseconds remaining before a pulse (delayedPulse() call) When there is no scheduled pulse, returns zero.

```
def get_countdown( )
```

Returns :

an integer corresponding to the number of milliseconds remaining before a pulse (delayedPulse() call) When there is no scheduled pulse, returns zero

On failure, throws an exception or returns Y_COUNTDOWN_INVALID.

relay→get_errorMessage()**YRelay****relay→errorMessage()relay.getErrorMessage()**

Returns the error message of the latest error with the relay.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the relay object

relay→get_errorType()

YRelay

relay→errorType()relay.get_errorType()

Returns the numerical error code of the latest error with the relay.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the relay object

relay→get_friendlyName()**YRelay****relay→friendlyName()relay.get_friendlyName()**

Returns a global identifier of the relay in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the relay if they are defined, otherwise the serial number of the module and the hardware identifier of the relay (for example: MyCustomName . relay1)

Returns :

a string that uniquely identifies the relay using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

`relay->get_functionDescriptor()`
`relay->functionDescriptor()`
`relay.get_functionDescriptor()`

YRelay

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

relay→get_functionId()**YRelay****relay→functionId()relay.get_functionId()**

Returns the hardware identifier of the relay, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the relay (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

relay→get_hardwareId()	YRelay
relay→hardwareId()relay.get_hardwareId()	

Returns the unique hardware identifier of the relay in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the relay (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the relay (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

relay→get_logicalName()**YRelay****relay→logicalName()relay.get_logicalName()**

Returns the logical name of the relay.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the relay.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

relay→get_maxTimeOnStateA()
relay→maxTimeOnStateA()
relay.get_maxTimeOnStateA()

YRelay

Retourne the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state A before automatically switching back in to B state.

```
def get_maxTimeOnStateA( )
```

Zero means no maximum time.

Returns :

an integer

On failure, throws an exception or returns Y_MAXTIMEONSTATEA_INVALID.

relay→get_maxTimeOnStateB()
relay→maxTimeOnStateB()
relay.get_maxTimeOnStateB()

YRelay

Retourne the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state B before automatically switching back in to A state.

```
def get_maxTimeOnStateB( )
```

Zero means no maximum time.

Returns :

an integer

On failure, throws an exception or returns Y_MAXTIMEONSTATEB_INVALID.

relay→get_module()**YRelay****relay→module()relay.get_module()**

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

relay→get_output()**YRelay****relay→output()relay.get_output()**

Returns the output state of the relays, when used as a simple switch (single throw).

```
def get_output( )
```

Returns :

either Y_OUTPUT_OFF or Y_OUTPUT_ON, according to the output state of the relays, when used as a simple switch (single throw)

On failure, throws an exception or returns Y_OUTPUT_INVALID.

relay→get_pulseTimer() YRelay
relay→pulseTimer()relay.get_pulseTimer()

Returns the number of milliseconds remaining before the relays is returned to idle position (state A), during a measured pulse generation.

```
def get_pulseTimer( )
```

When there is no ongoing pulse, returns zero.

Returns :

an integer corresponding to the number of milliseconds remaining before the relays is returned to idle position (state A), during a measured pulse generation

On failure, throws an exception or returns Y_PULSE_TIMER_INVALID.

relay→get_state()**YRelay****relay→state()relay.get_state()**

Returns the state of the relays (A for the idle position, B for the active position).

```
def get_state( )
```

Returns :

either Y_STATE_A or Y_STATE_B, according to the state of the relays (A for the idle position, B for the active position)

On failure, throws an exception or returns Y_STATE_INVALID.

relay→get_stateAtPowerOn()	YRelay
relay→stateAtPowerOn()relay.get_stateAtPowerOn()	

Returns the state of the relays at device startup (A for the idle position, B for the active position, UNCHANGED for no change).

```
def get_stateAtPowerOn( )
```

Returns :

a value among Y_STATEATPOWERON_UNCHANGED, Y_STATEATPOWERON_A and Y_STATEATPOWERON_B corresponding to the state of the relays at device startup (A for the idle position, B for the active position, UNCHANGED for no change)

On failure, throws an exception or returns Y_STATEATPOWERON_INVALID.

relay→get(userData)**YRelay****relay→userData()relay.get(userData())**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

relay→isOnline()relay.isOnline()**YRelay**

Checks if the relay is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the relay in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the relay.

Returns :

`true` if the relay can be reached, and `false` otherwise

relay→load()relay.load()**YRelay**

Preloads the relay cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

relay→nextRelay()**relay.nextRelay()**

YRelay

Continues the enumeration of relays started using `yFirstRelay()`.

```
def nextRelay( )
```

Returns :

a pointer to a `YRelay` object, corresponding to a relay currently online, or a `null` pointer if there are no more relays to enumerate.

relay→pulse()relay.pulse()******YRelay**

Sets the relay to output B (active) for a specified duration, then brings it automatically back to output A (idle state).

```
def pulse( ms_duration )
```

Parameters :

ms_duration pulse duration, in millisecondes

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

relay→registerValueCallback()
relay.registerValueCallback()**YRelay**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

relay→set_logicalName()**YRelay****relay→setLogicalName()relay.set_logicalName()**

Changes the logical name of the relay.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the relay.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

`relay->set_maxTimeOnStateA()`
`relay->setMaxTimeOnStateA()`
`relay.set_maxTimeOnStateA()`

YRelay

Sets the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state A before automatically switching back in to B state.

```
def set_maxTimeOnStateA( newval )
```

Use zero for no maximum time.

Parameters :

`newval` an integer

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

relay→set_maxTimeOnStateB()
relay→setMaxTimeOnStateB()
relay.set_maxTimeOnStateB()

YRelay

Sets the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state B before automatically switching back in to A state.

```
def set_maxTimeOnStateB( newval)
```

Use zero for no maximum time.

Parameters :

newval an integer

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

relay→set_output()**YRelay****relay→setOutput()relay.set_output()**

Changes the output state of the relays, when used as a simple switch (single throw).

```
def set_output( newval)
```

Parameters :

newval either Y_OUTPUT_OFF or Y_OUTPUT_ON, according to the output state of the relays, when used as a simple switch (single throw)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

relay->set_state()**YRelay****relay->setState()relay.set_state()**

Changes the state of the relays (A for the idle position, B for the active position).

```
def set_state( newval)
```

Parameters :

newval either Y_STATE_A or Y_STATE_B, according to the state of the relays (A for the idle position, B for the active position)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

`relay→set_stateAtPowerOn()`
`relay→setStateAtPowerOn()`
`relay.set_stateAtPowerOn()`

YRelay

Preset the state of the relays at device startup (A for the idle position, B for the active position, UNCHANGED for no modification).

```
def set_stateAtPowerOn( newval )
```

Remember to call the matching module `saveToFlash()` method, otherwise this call will have no effect.

Parameters :

`newval` a value among `Y_STATEATPOWERON_UNCHANGED`, `Y_STATEATPOWERON_A` and `Y_STATEATPOWERON_B`

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

relay→set(userData)**YRelay****relay→setUserData()relay.set(userData())**

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData: Any)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.39. Sensor function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_api.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YAPI = yoctolib.YAPI;
	var YModule = yoctolib.YModule;
php	require_once('yocto_api.php');
cpp	#include "yocto_api.h"
m	#import "yocto_api.h"
pas	uses yocto_api;
vb	yocto_api.vb
cs	yocto_api.cs
java	import com.yoctopuce.YoctoAPI.YModule;
py	from yocto_api import *

Global functions

yFindSensor(func)

Retrieves a sensor for a given identifier.

yFirstSensor()

Starts the enumeration of sensors currently accessible.

YSensor methods

sensor->calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

sensor->describe()

Returns a short text that describes unambiguously the instance of the sensor in the form TYPE(NAME)=SERIAL.FUNCTIONID.

sensor->get_advertisedValue()

Returns the current value of the sensor (no more than 6 characters).

sensor->get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in the specified unit, as a floating point number.

sensor->get_currentValue()

Returns the current value of the measure, in the specified unit, as a floating point number.

sensor->get_errorMessage()

Returns the error message of the latest error with the sensor.

sensor->get_errorType()

Returns the numerical error code of the latest error with the sensor.

sensor->get_friendlyName()

Returns a global identifier of the sensor in the format MODULE_NAME . FUNCTION_NAME.

sensor->get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

sensor->get_functionId()

Returns the hardware identifier of the sensor, without reference to the module.

sensor->get_hardwareId()

Returns the unique hardware identifier of the sensor in the form SERIAL.FUNCTIONID.

sensor→get_highestValue()

Returns the maximal value observed for the measure since the device was started.

sensor→get_logFrequency()

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

sensor→get_logicalName()

Returns the logical name of the sensor.

sensor→get_lowestValue()

Returns the minimal value observed for the measure since the device was started.

sensor→get_module()

Gets the YModule object for the device on which the function is located.

sensor→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

sensor→get_recordedData(startTime, endTime)

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

sensor→get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

sensor→get_resolution()

Returns the resolution of the measured values.

sensor→get_unit()

Returns the measuring unit for the measure.

sensor→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

sensor→isOnline()

Checks if the sensor is currently reachable, without raising any error.

sensor→isOnline_async(callback, context)

Checks if the sensor is currently reachable, without raising any error (asynchronous version).

sensor→load(msValidity)

Preloads the sensor cache with a specified validity duration.

sensor→loadCalibrationPoints(rawValues, refValues)

Retrieves error correction data points previously entered using the method calibrateFromPoints.

sensor→load_async(msValidity, callback, context)

Preloads the sensor cache with a specified validity duration (asynchronous version).

sensor→nextSensor()

Continues the enumeration of sensors started using yFirstSensor().

sensor→registerTimedReportCallback(callback)

Registers the callback function that is invoked on every periodic timed notification.

sensor→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

sensor→set_highestValue(newval)

Changes the recorded maximal value observed.

sensor→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

sensor→set_logicalName(newval)

3. Reference

Changes the logical name of the sensor.

sensor→set_lowestValue(newval)

Changes the recorded minimal value observed.

sensor→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

sensor→set_resolution(newval)

Changes the resolution of the measured physical values.

sensor→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

sensor→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YSensor.FindSensor()**YSensor****yFindSensor()YSensor.FindSensor()**

Retrieves a sensor for a given identifier.

```
def FindSensor( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YSensor.isOnline()` to test if the sensor is indeed online at a given time. In case of ambiguity when looking for a sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the sensor

Returns :

a `YSensor` object allowing you to drive the sensor.

YSensor.FirstSensor()

YSensor

yFirstSensor()YSensor.FirstSensor()

Starts the enumeration of sensors currently accessible.

```
def FirstSensor( )
```

Use the method YSensor.nextSensor() to iterate on next sensors.

Returns :

a pointer to a YSensor object, corresponding to the first sensor currently online, or a null pointer if there are none.

sensor→calibrateFromPoints()
sensor.calibrateFromPoints()**YSensor**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

sensor→describe()sensor.describe()**YSensor**

Returns a short text that describes unambiguously the instance of the sensor in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the sensor (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

sensor→get_advertisedValue()
sensor→advertisedValue()
sensor.get_advertisedValue()

YSensor

Returns the current value of the sensor (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the sensor (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

sensor→get_currentRawValue()
sensor→currentRawValue()
sensor.get_currentRawValue()

YSensor

Returns the uncalibrated, unrounded raw value returned by the sensor, in the specified unit, as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in the specified unit, as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

sensor→get_currentValue()	YSensor
sensor→currentValue()sensor.get_currentValue()	

Returns the current value of the measure, in the specified unit, as a floating point number.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current value of the measure, in the specified unit, as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

sensor→get_errorMessage() YSensor
sensor→errorMessage()sensor.get_errorMessage()

Returns the error message of the latest error with the sensor.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the sensor object

sensor→get_errorType()**YSensor****sensor→errorType()sensor.get_errorType()**

Returns the numerical error code of the latest error with the sensor.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the sensor object

sensor→get_friendlyName()	YSensor
sensor→friendlyName()sensor.get_friendlyName()	

Returns a global identifier of the sensor in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the sensor (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the sensor using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

sensor→get_functionDescriptor()
sensor→functionDescriptor()
sensor.get_functionDescriptor()

YSensor

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

sensor→get_functionId()

YSensor

sensor→functionId()sensor.get_functionId()

Returns the hardware identifier of the sensor, without reference to the module.

```
def get_functionId( )
```

For example relay1

Returns :

a string that identifies the sensor (ex: relay1)

On failure, throws an exception or returns Y_FUNCTIONID_INVALID.

sensor→getHardwareId()	YSensor
sensor→hardwareId()sensor.getHardwareId()	

Returns the unique hardware identifier of the sensor in the form SERIAL.FUNCTIONID.

```
def getHardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the sensor (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the sensor (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

sensor→get_highestValue()

YSensor

sensor→highestValue()sensor.get_highestValue()

Returns the maximal value observed for the measure since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the measure since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

sensor→get_logFrequency()**YSensor****sensor→logFrequency()sensor.get_logFrequency()**

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

sensor→get_logicalName()

YSensor

sensor→logicalName()sensor.get_logicalName()

Returns the logical name of the sensor.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the sensor.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

sensor→get_lowestValue()**YSensor****sensor→lowestValue()sensor.get_lowestValue()**

Returns the minimal value observed for the measure since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the measure since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

sensor→get_module()**YSensor****sensor→module()sensor.get_module()**

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

sensor→get_recordedData()	YSensor
sensor→recordedData()sensor.get_recordedData()	

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime)
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

sensor→get_reportFrequency()
sensor→reportFrequency()
sensor.get_reportFrequency()

YSensor

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

sensor→get_resolution()**YSensor****sensor→resolution()sensor.get_resolution()**

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

sensor→get_unit()

YSensor

sensor→unit()|sensor.get_unit()

Returns the measuring unit for the measure.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the measure

On failure, throws an exception or returns Y_UNIT_INVALID.

sensor→get(userData)**YSensor****sensor→userData()sensor.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

sensor→isOnline()sensor.isOnline()**YSensor**

Checks if the sensor is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the sensor.

Returns :

true if the sensor can be reached, and false otherwise

sensor→load()|sensor.load()**YSensor**

Preloads the sensor cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

sensor→loadCalibrationPoints()
sensor.loadCalibrationPoints()**YSensor**

Retrieves error correction data points previously entered using the method `calibrateFromPoints`.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

sensor→nextSensor()|sensor.nextSensor()**YSensor**

Continues the enumeration of sensors started using `yFirstSensor()`.

```
def nextSensor( )
```

Returns :

a pointer to a `YSensor` object, corresponding to a sensor currently online, or a null pointer if there are no more sensors to enumerate.

**sensor→registerTimedReportCallback()
sensor.registerTimedReportCallback()****YSensor**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

sensor→registerValueCallback()
sensor.registerValueCallback()**YSensor**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

sensor→set_highestValue()	YSensor
sensor→setHighestValue()sensor.set_highestValue()	

Changes the recorded maximal value observed.

```
def set_highestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

sensor→set_logFrequency()
sensor→setLogFrequency()
sensor.set_logFrequency()

YSensor

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval)
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

sensor->set_logicalName()	YSensor
sensor->setLogicalName() sensor.set_logicalName()	

Changes the logical name of the sensor.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

sensor→set_lowestValue()	YSensor
sensor→setLowestValue()sensor.set_lowestValue()	

Changes the recorded minimal value observed.

```
def set_lowestValue( newval )
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

`sensor->set_reportFrequency()`
`sensor->setReportFrequency()`
`sensor.set_reportFrequency()`

YSensor

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

`newval` a string corresponding to the timed value notification frequency for this function

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

sensor→set_resolution()**YSensor****sensor→setResolution()sensor.set_resolution()**

Changes the resolution of the measured physical values.

```
def set_resolution( newval )
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

sensor→set(userData)

YSensor

sensor→setUserData()|sensor.set(userData)

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.40. SerialPort function interface

The SerialPort function interface allows you to fully drive a Yoctopuce serial port, to send and receive data, and to configure communication parameters (baud rate, bit count, parity, flow control and protocol). Note that Yoctopuce serial ports are not exposed as virtual COM ports. They are meant to be used in the same way as all Yoctopuce devices.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_serialport.js'></script>
node.js	var yoctolib = require('yoctolib');
	var YSerialPort = yoctolib.YSerialPort;
php	require_once('yocto_serialport.php');
cpp	#include "yocto_serialport.h"
m	#import "yocto_serialport.h"
pas	uses yocto_serialport;
vb	yocto_serialport.vb
cs	yocto_serialport.cs
java	import com.yoctopuce.YoctoAPI.YSerialPort;
py	from yocto_serialport import *

Global functions

yFindSerialPort(func)

Retrieves a serial port for a given identifier.

yFirstSerialPort()

Starts the enumeration of serial ports currently accessible.

YSerialPort methods

serialport→describe()

Returns a short text that describes unambiguously the instance of the serial port in the form TYPE (NAME)=SERIAL . FUNCTIONID.

serialport→get_CTS()

Read the level of the CTS line.

serialport→get_advertisedValue()

Returns the current value of the serial port (no more than 6 characters).

serialport→get_errCount()

Returns the total number of communication errors detected since last reset.

serialport→get_errorMessage()

Returns the error message of the latest error with the serial port.

serialport→get_errorType()

Returns the numerical error code of the latest error with the serial port.

serialport→get_friendlyName()

Returns a global identifier of the serial port in the format MODULE_NAME . FUNCTION_NAME.

serialport→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

serialport→get_functionId()

Returns the hardware identifier of the serial port, without reference to the module.

serialport→get_hardwareId()

Returns the unique hardware identifier of the serial port in the form SERIAL . FUNCTIONID.

serialport→get_lastMsg()

3. Reference

Returns the latest message fully received (for Line, Frame and Modbus protocols).
serialport→get_logicalName() Returns the logical name of the serial port.
serialport→get_module() Gets the YModule object for the device on which the function is located.
serialport→get_module_async(callback, context) Gets the YModule object for the device on which the function is located (asynchronous version).
serialport→get_msgCount() Returns the total number of messages received since last reset.
serialport→get_protocol() Returns the type of protocol used over the serial line, as a string.
serialport→get_rxCount() Returns the total number of bytes received since last reset.
serialport→get_serialMode() Returns the serial port communication parameters, as a string such as "9600,8N1".
serialport→get_txCount() Returns the total number of bytes transmitted since last reset.
serialport→get(userData) Returns the value of the userData attribute, as previously stored using method <code>set(userData)</code> .
serialport→isOnline() Checks if the serial port is currently reachable, without raising any error.
serialport→isOnline_async(callback, context) Checks if the serial port is currently reachable, without raising any error (asynchronous version).
serialport→load(msValidity) Preloads the serial port cache with a specified validity duration.
serialport→load_async(msValidity, callback, context) Preloads the serial port cache with a specified validity duration (asynchronous version).
serialport→modbusReadBits(slaveNo, pduAddr, nBits) Reads one or more contiguous internal bits (or coil status) from a MODBUS serial device.
serialport→modbusReadInputBits(slaveNo, pduAddr, nBits) Reads one or more contiguous input bits (or discrete inputs) from a MODBUS serial device.
serialport→modbusReadInputRegisters(slaveNo, pduAddr, nWords) Reads one or more contiguous input registers (read-only registers) from a MODBUS serial device.
serialport→modbusReadRegisters(slaveNo, pduAddr, nWords) Reads one or more contiguous internal registers (holding registers) from a MODBUS serial device.
serialport→modbusWriteAndReadRegisters(slaveNo, pduWriteAddr, values, pduReadAddr, nReadWords) Sets several contiguous internal registers (holding registers) on a MODBUS serial device, then performs a contiguous read of a set of (possibly different) internal registers.
serialport→modbusWriteBit(slaveNo, pduAddr, value) Sets a single internal bit (or coil) on a MODBUS serial device.
serialport→modbusWriteBits(slaveNo, pduAddr, bits) Sets several contiguous internal bits (or coils) on a MODBUS serial device.
serialport→modbusWriteRegister(slaveNo, pduAddr, value) Sets a single internal register (or holding register) on a MODBUS serial device.
serialport→modbusWriteRegisters(slaveNo, pduAddr, values)

Sets several contiguous internal registers (or holding registers) on a MODBUS serial device.
serialport→nextSerialPort()
Continues the enumeration of serial ports started using <code>yFirstSerialPort()</code> .
serialport→queryLine(query, maxWait)
Sends a text line query to the serial port, and reads the reply, if any.
serialport→queryMODBUS(slaveNo, pduBytes)
Sends a message to a specified MODBUS slave connected to the serial port, and reads the reply, if any.
serialport→readHex(nBytes)
Reads data from the receive buffer as a hexadecimal string, starting at current stream position.
serialport→readLine()
Reads a single line (or message) from the receive buffer, starting at current stream position.
serialport→readMessages(pattern, maxWait)
Searches for incoming messages in the serial port receive buffer matching a given pattern, starting at current position.
serialport→readStr(nChars)
Reads data from the receive buffer as a string, starting at current stream position.
serialport→read_seek(rxCountVal)
Changes the current internal stream position to the specified value.
serialport→registerValueCallback(callback)
Registers the callback function that is invoked on every change of advertised value.
serialport→reset()
Clears the serial port buffer and resets counters to zero.
serialport→set_RTS(val)
Manually sets the state of the RTS line.
serialport→set_logicalName(newval)
Changes the logical name of the serial port.
serialport→set_protocol(newval)
Changes the type of protocol used over the serial line.
serialport→set_serialMode(newval)
Changes the serial port communication parameters, with a string such as "9600,8N1".
serialport→set_userData(data)
Stores a user context provided as argument in the userData attribute of the function.
serialport→wait_async(callback, context)
Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.
serialport→writeArray(byteList)
Sends a byte sequence (provided as a list of bytes) to the serial port.
serialport→writeBin(buff)
Sends a binary buffer to the serial port, as is.
serialport→writeHex(hexString)
Sends a byte sequence (provided as a hexadecimal string) to the serial port.
serialport→writeLine(text)
Sends an ASCII string to the serial port, followed by a line break (CR LF).
serialport→writeMODBUS(hexString)
Sends a MODBUS message (provided as a hexadecimal string) to the serial port.
serialport→writeStr(text)

3. Reference

Sends an ASCII string to the serial port, as is.
--

YSerialPort.FindSerialPort()**YSerialPort****yFindSerialPort()YSerialPort.FindSerialPort()**

Retrieves a serial port for a given identifier.

```
def FindSerialPort( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the serial port is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YSerialPort.isOnline()` to test if the serial port is indeed online at a given time. In case of ambiguity when looking for a serial port by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the serial port

Returns :

a `YSerialPort` object allowing you to drive the serial port.

YSerialPort.FirstSerialPort()

YSerialPort

yFirstSerialPort()YSerialPort.FirstSerialPort()

Starts the enumeration of serial ports currently accessible.

```
def FirstSerialPort( )
```

Use the method `YSerialPort.nextSerialPort()` to iterate on next serial ports.

Returns :

a pointer to a `YSerialPort` object, corresponding to the first serial port currently online, or a null pointer if there are none.

serialport→describe()serialport.describe()**YSerialPort**

Returns a short text that describes unambiguously the instance of the serial port in the form TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the serial port (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

serialport→get_CTS()
serialport→CTS()serialport.get_CTS()

YSerialPort

Read the level of the CTS line.

```
def get_CTS( )
```

The CTS line is usually driven by the RTS signal of the connected serial device.

Returns :

1 if the CTS line is high, 0 if the CTS line is low.

On failure, throws an exception or returns a negative error code.

serialport→get_advertisedValue()
serialport→advertisedValue()
serialport.get_advertisedValue()

YSerialPort

Returns the current value of the serial port (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the serial port (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

serialport→get_errCount()

YSerialPort

serialport→errCount()serialport.get_errCount()

Returns the total number of communication errors detected since last reset.

```
def get_errCount( )
```

Returns :

an integer corresponding to the total number of communication errors detected since last reset

On failure, throws an exception or returns Y_ERRCOUNT_INVALID.

serialport→get_errorMessage()
serialport→errorMessage()
serialport.get_errorMessage()

YSerialPort

Returns the error message of the latest error with the serial port.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the serial port object

serialport→get_errorType()

YSerialPort

serialport→errorType()serialport.get_errorType()

Returns the numerical error code of the latest error with the serial port.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the serial port object

`serialport→get_friendlyName()`
`serialport→friendlyName()`
`serialport.get_friendlyName()`

YSerialPort

Returns a global identifier of the serial port in the format MODULE_NAME . FUNCTION_NAME.

`def get_friendlyName()`

The returned string uses the logical names of the module and of the serial port if they are defined, otherwise the serial number of the module and the hardware identifier of the serial port (for example: MyCustomName . relay1)

Returns :

a string that uniquely identifies the serial port using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

`serialport→get_functionDescriptor()`
`serialport→functionDescriptor()`
`serialport.get_functionDescriptor()`

YSerialPort

Returns a unique identifier of type `YFUN_DESCR` corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of `YFunction` reference the same physical function on the same physical device.

Returns :

an identifier of type `YFUN_DESCR`.

If the function has never been contacted, the returned value is `Y_FUNCTIONDESCRIPTOR_INVALID`.

serialport→get_functionId()**YSerialPort****serialport→functionId()serialport.get_functionId()**

Returns the hardware identifier of the serial port, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the serial port (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

serialport→get_hardwareId() **YSerialPort**
serialport→hardwareId()serialport.get_hardwareId()

Returns the unique hardware identifier of the serial port in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the serial port (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the serial port (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

serialport→get_lastMsg()**YSerialPort****serialport→lastMsg()serialport.get_lastMsg()**

Returns the latest message fully received (for Line, Frame and Modbus protocols).

```
def get_lastMsg( )
```

Returns :

a string corresponding to the latest message fully received (for Line, Frame and Modbus protocols)

On failure, throws an exception or returns Y_LASTMSG_INVALID.

serialport→get_logicalName()
serialport→logicalName()
serialport.get_logicalName()

YSerialPort

Returns the logical name of the serial port.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the serial port.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

serialport→get_module()**YSerialPort****serialport→module()serialport.get_module()**

Gets the YModule object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

serialport→get_msgCount()

YSerialPort

serialport→msgCount()serialport.get_msgCount()

Returns the total number of messages received since last reset.

```
def get_msgCount( )
```

Returns :

an integer corresponding to the total number of messages received since last reset

On failure, throws an exception or returns Y_MSGCOUNT_INVALID.

serialport→get_protocol()**YSerialPort****serialport→protocol()serialport.get_protocol()**

Returns the type of protocol used over the serial line, as a string.

```
def get_protocol( )
```

Possible values are "Line" for ASCII messages separated by CR and/or LF, "Frame:[timeout]ms" for binary messages separated by a delay time, "Modbus-ASCII" for MODBUS messages in ASCII mode, "Modbus-RTU" for MODBUS messages in RTU mode, "Char" for a continuous ASCII stream or "Byte" for a continuous binary stream.

Returns :

a string corresponding to the type of protocol used over the serial line, as a string

On failure, throws an exception or returns Y_PROTOCOL_INVALID.

serialport→get_rxCount()

YSerialPort

serialport→rxCount()serialport.get_rxCount()

Returns the total number of bytes received since last reset.

```
def get_rxCount( )
```

Returns :

an integer corresponding to the total number of bytes received since last reset

On failure, throws an exception or returns Y_RXCOUNT_INVALID.

serialport→get_serialMode()**YSerialPort****serialport→serialMode()serialport.get_serialMode()**

Returns the serial port communication parameters, as a string such as "9600,8N1".

```
def get_serialMode( )
```

The string includes the baud rate, the number of data bits, the parity, and the number of stop bits. An optional suffix is included if flow control is active: "CtsRts" for hardware handshake, "XOnXOff" for logical flow control and "Simplex" for acquiring a shared bus using the RTS line (as used by some RS485 adapters for instance).

Returns :

a string corresponding to the serial port communication parameters, as a string such as "9600,8N1"

On failure, throws an exception or returns Y_SERIALMODE_INVALID.

serialport→get_txCount()

YSerialPort

serialport→txCount()serialport.get_txCount()

Returns the total number of bytes transmitted since last reset.

```
def get_txCount( )
```

Returns :

an integer corresponding to the total number of bytes transmitted since last reset

On failure, throws an exception or returns Y_TCOUNT_INVALID.

serialport→get(userData)**YSerialPort****serialport→userData()serialport.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

serialport→isOnline()serialport.isOnline()**YSerialPort**

Checks if the serial port is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the serial port in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the serial port.

Returns :

`true` if the serial port can be reached, and `false` otherwise

serialport→load()serialport.load()**YSerialPort**

Preloads the serial port cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

**serialport→modbusReadBits()
serialport.modbusReadBits()****YSerialPort**

Reads one or more contiguous internal bits (or coil status) from a MODBUS serial device.

```
def modbusReadBits( slaveNo, pduAddr, nBits)
```

This method uses the MODBUS function code 0x01 (Read Coils).

Parameters :

slaveNo the address of the slave MODBUS device to query
pduAddr the relative address of the first bit/coil to read (zero-based)
nBits the number of bits/coils to read

Returns :

a vector of integers, each corresponding to one bit.

On failure, throws an exception or returns an empty array.

**serialport→modbusReadInputBits()
serialport.modbusReadInputBits()****YSerialPort**

Reads one or more contiguous input bits (or discrete inputs) from a MODBUS serial device.

```
def modbusReadInputBits( slaveNo, pduAddr, nBits)
```

This method uses the MODBUS function code 0x02 (Read Discrete Inputs).

Parameters :

slaveNo the address of the slave MODBUS device to query
pduAddr the relative address of the first bit/input to read (zero-based)
nBits the number of bits/inputs to read

Returns :

a vector of integers, each corresponding to one bit.

On failure, throws an exception or returns an empty array.

serialport→modbusReadInputRegisters()
serialport.modbusReadInputRegisters()**YSerialPort**

Reads one or more contiguous input registers (read-only registers) from a MODBUS serial device.

```
def modbusReadInputRegisters( slaveNo, pduAddr, nWords)
```

This method uses the MODBUS function code 0x04 (Read Input Registers).

Parameters :

slaveNo the address of the slave MODBUS device to query

pduAddr the relative address of the first input register to read (zero-based)

nWords the number of input registers to read

Returns :

a vector of integers, each corresponding to one 16-bit input value.

On failure, throws an exception or returns an empty array.

serialport→modbusReadRegisters()
serialport.modbusReadRegisters()**YSerialPort**

Reads one or more contiguous internal registers (holding registers) from a MODBUS serial device.

```
def modbusReadRegisters( slaveNo, pduAddr, nWords)
```

This method uses the MODBUS function code 0x03 (Read Holding Registers).

Parameters :

slaveNo the address of the slave MODBUS device to query

pduAddr the relative address of the first holding register to read (zero-based)

nWords the number of holding registers to read

Returns :

a vector of integers, each corresponding to one 16-bit register value.

On failure, throws an exception or returns an empty array.

**serialport→modbusWriteAndReadRegisters()
serialport.modbusWriteAndReadRegisters()****YSerialPort**

Sets several contiguous internal registers (holding registers) on a MODBUS serial device, then performs a contiguous read of a set of (possibly different) internal registers.

```
def modbusWriteAndReadRegisters( slaveNo, pduWriteAddr, values, pduReadAddr, nReadWords)
```

This method uses the MODBUS function code 0x17 (Read/Write Multiple Registers).

Parameters :

slaveNo the address of the slave MODBUS device to drive
pduWriteAddr the relative address of the first internal register to set (zero-based)
values the vector of 16 bit values to set
pduReadAddr the relative address of the first internal register to read (zero-based)
nReadWords the number of 16 bit values to read

Returns :

a vector of integers, each corresponding to one 16-bit register value read.

On failure, throws an exception or returns an empty array.

**serialport→modbusWriteBit()
serialport.modbusWriteBit()****YSerialPort**

Sets a single internal bit (or coil) on a MODBUS serial device.

```
def modbusWriteBit( slaveNo, pduAddr, value)
```

This method uses the MODBUS function code 0x05 (Write Single Coil).

Parameters :

slaveNo the address of the slave MODBUS device to drive
pduAddr the relative address of the bit/coil to set (zero-based)
value the value to set (0 for OFF state, non-zero for ON state)

Returns :

the number of bits/coils affected on the device (1)

On failure, throws an exception or returns zero.

serialport→modbusWriteBits()
serialport.modbusWriteBits()**YSerialPort**

Sets several contiguous internal bits (or coils) on a MODBUS serial device.

```
def modbusWriteBits( slaveNo, pduAddr, bits)
```

This method uses the MODBUS function code 0x0f (Write Multiple Coils).

Parameters :

slaveNo the address of the slave MODBUS device to drive
pduAddr the relative address of the first bit/coil to set (zero-based)
bits the vector of bits to be set (one integer per bit)

Returns :

the number of bits/coils affected on the device

On failure, throws an exception or returns zero.

**serialport→modbusWriteRegister()
serialport.modbusWriteRegister()****YSerialPort**

Sets a single internal register (or holding register) on a MODBUS serial device.

```
def modbusWriteRegister( slaveNo, pduAddr, value)
```

This method uses the MODBUS function code 0x06 (Write Single Register).

Parameters :

slaveNo the address of the slave MODBUS device to drive

pduAddr the relative address of the register to set (zero-based)

value the 16 bit value to set

Returns :

the number of registers affected on the device (1)

On failure, throws an exception or returns zero.

serialport→modbusWriteRegisters()
serialport.modbusWriteRegisters()**YSerialPort**

Sets several contiguous internal registers (or holding registers) on a MODBUS serial device.

```
def modbusWriteRegisters( slaveNo, pduAddr, values)
```

This method uses the MODBUS function code 0x10 (Write Multiple Registers).

Parameters :

slaveNo the address of the slave MODBUS device to drive

pduAddr the relative address of the first internal register to set (zero-based)

values the vector of 16 bit values to set

Returns :

the number of registers affected on the device

On failure, throws an exception or returns zero.

serialport→nextSerialPort()serialport.nextSerialPort()**YSerialPort**

Continues the enumeration of serial ports started using `yFirstSerialPort()`.

```
def nextSerialPort( )
```

Returns :

a pointer to a `YSerialPort` object, corresponding to a serial port currently online, or a null pointer if there are no more serial ports to enumerate.

serialport→queryLine()|serialport.queryLine()**YSerialPort**

Sends a text line query to the serial port, and reads the reply, if any.

```
def queryLine( query, maxWait)
```

This function can only be used when the serial port is configured for 'Line' protocol.

Parameters :

query the line query to send (without CR/LF)

maxWait the maximum number of milliseconds to wait for a reply.

Returns :

the next text line received after sending the text query, as a string. Additional lines can be obtained by calling readLine or readMessages.

On failure, throws an exception or returns an empty array.

serialport→queryMODBUS()
serialport.queryMODBUS()**YSerialPort**

Sends a message to a specified MODBUS slave connected to the serial port, and reads the reply, if any.

```
def queryMODBUS( slaveNo, pduBytes)
```

The message is the PDU, provided as a vector of bytes.

Parameters :

slaveNo the address of the slave MODBUS device to query

pduBytes the message to send (PDU), as a vector of bytes. The first byte of the PDU is the MODBUS function code.

Returns :

the received reply, as a vector of bytes.

On failure, throws an exception or returns an empty array (or a MODBUS error reply).

serialport→readHex()serialport.readHex()**YSerialPort**

Reads data from the receive buffer as a hexadecimal string, starting at current stream position.

```
def readHex( nBytes )
```

If data at current stream position is not available anymore in the receive buffer, the function performs a short read.

Parameters :

nBytes the maximum number of bytes to read

Returns :

a string with receive buffer contents, encoded in hexadecimal

On failure, throws an exception or returns a negative error code.

serialport→readLine()**serialport.readLine()****YSerialPort**

Reads a single line (or message) from the receive buffer, starting at current stream position.

```
def readLine( )
```

This function can only be used when the serial port is configured for a message protocol, such as 'Line' mode or MODBUS protocols. It does not work in plain stream modes, eg. 'Char' or 'Byte').

If data at current stream position is not available anymore in the receive buffer, the function returns the oldest available line and moves the stream position just after. If no new full line is received, the function returns an empty line.

Returns :

a string with a single line of text

On failure, throws an exception or returns a negative error code.

**serialport→readMessages()
serialport.readMessages()****YSerialPort**

Searches for incoming messages in the serial port receive buffer matching a given pattern, starting at current position.

```
def readMessages( pattern, maxWait)
```

This function can only be used when the serial port is configured for a message protocol, such as 'Line' mode or MODBUS protocols. It does not work in plain stream modes, eg. 'Char' or 'Byte', for which there is no "start" of message.

The search returns all messages matching the expression provided as argument in the buffer. If no matching message is found, the search waits for one up to the specified maximum timeout (in milliseconds).

Parameters :

pattern a limited regular expression describing the expected message format, or an empty string if all messages should be returned (no filtering). When using binary protocols, the format applies to the hexadecimal representation of the message.

maxWait the maximum number of milliseconds to wait for a message if none is found in the receive buffer.

Returns :

an array of strings containing the messages found, if any. Binary messages are converted to hexadecimal representation.

On failure, throws an exception or returns an empty array.

serialport→readStr()serialport.readStr()**YSerialPort**

Reads data from the receive buffer as a string, starting at current stream position.

```
def readStr( nChars )
```

If data at current stream position is not available anymore in the receive buffer, the function performs a short read.

Parameters :

nChars the maximum number of characters to read

Returns :

a string with receive buffer contents

On failure, throws an exception or returns a negative error code.

serialport→read_seek()serialport.read_seek()**YSerialPort**

Changes the current internal stream position to the specified value.

```
def read_seek( rxCountVal)
```

This function does not affect the device, it only changes the value stored in the YSerialPort object for the next read operations.

Parameters :

rxCountVal the absolute position index (value of rxCount) for next read operations.

Returns :

nothing.

**serialport→registerValueCallback()
serialport.registerValueCallback()****YSerialPort**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

serialport→reset()serialport.reset()

YSerialPort

Clears the serial port buffer and resets counters to zero.

```
def reset( )
```

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

serialport→set_RTS()**YSerialPort****serialport→setRTS()serialport.set_RTS()**

Manually sets the state of the RTS line.

```
def set_RTS( val)
```

This function has no effect when hardware handshake is enabled, as the RTS line is driven automatically.

Parameters :

val 1 to turn RTS on, 0 to turn RTS off

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

`serialport→set_logicalName()`
`serialport→setLogicalName()`
`serialport.set_logicalName()`

YSerialPort

Changes the logical name of the serial port.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the serial port.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

serialport→set_protocol()**YSerialPort****serialport→setProtocol()serialport.set_protocol()**

Changes the type of protocol used over the serial line.

```
def set_protocol( newval)
```

Possible values are "Line" for ASCII messages separated by CR and/or LF, "Frame:[timeout]ms" for binary messages separated by a delay time, "Modbus-ASCII" for MODBUS messages in ASCII mode, "Modbus-RTU" for MODBUS messages in RTU mode, "Char" for a continuous ASCII stream or "Byte" for a continuous binary stream.

Parameters :

newval a string corresponding to the type of protocol used over the serial line

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

`serialport→set_serialMode()`
`serialport→setSerialMode()`
`serialport.set_serialMode()`

YSerialPort

Changes the serial port communication parameters, with a string such as "9600,8N1".

```
def set_serialMode( newval)
```

The string includes the baud rate, the number of data bits, the parity, and the number of stop bits. An optional suffix can be added to enable flow control: "CtsRts" for hardware handshake, "XOnXOff" for logical flow control and "Simplex" for acquiring a shared bus using the RTS line (as used by some RS485 adapters for instance).

Parameters :

newval a string corresponding to the serial port communication parameters, with a string such as "9600,8N1"

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

serialport→set(userData)**serialport→setUserData()serialport.set(userData)****YSerialPort**

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

serialport→writeArray()serialport.writeArray()**YSerialPort**

Sends a byte sequence (provided as a list of bytes) to the serial port.

```
def writeArray( byteList)
```

Parameters :

byteList a list of byte codes

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

serialport→writeBin()serialport.writeBin()**YSerialPort**

Sends a binary buffer to the serial port, as is.

```
def writeBin( buff)
```

Parameters :

buff the binary buffer to send

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

serialport→writeHex()serialport.writeHex()**YSerialPort**

Sends a byte sequence (provided as a hexadecimal string) to the serial port.

```
def writeHex( hexString)
```

Parameters :

hexString a string of hexadecimal byte codes

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

serialport→writeLine()serialport.writeLine()**YSerialPort**

Sends an ASCII string to the serial port, followed by a line break (CR LF).

```
def writeLine( text)
```

Parameters :

text the text string to send

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

serialport→writeMODBUS()**YSerialPort**

Sends a MODBUS message (provided as a hexadecimal string) to the serial port.

```
def writeMODBUS( hexString )
```

The message must start with the slave address. The MODBUS CRC/LRC is automatically added by the function. This function does not wait for a reply.

Parameters :

hexString a hexadecimal message string, including device address but no CRC/LRC

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

serialport→writeStr()serialport.writeStr()**YSerialPort**

Sends an ASCII string to the serial port, as is.

```
def writeStr( text)
```

Parameters :

text the text string to send

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

3.41. Servo function interface

Yoctopuce application programming interface allows you not only to move a servo to a given position, but also to specify the time interval in which the move should be performed. This makes it possible to synchronize two servos involved in a same move.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_servo.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YServo = yoctolib.YServo;
php	require_once('yocto_servo.php');
cpp	#include "yocto_servo.h"
m	#import "yocto_servo.h"
pas	uses yocto_servo;
vb	yocto_servo.vb
cs	yocto_servo.cs
java	import com.yoctopuce.YoctoAPI.YServo;
py	from yocto_servo import *

Global functions

yFindServo(func)

Retrieves a servo for a given identifier.

yFirstServo()

Starts the enumeration of servos currently accessible.

YServo methods

servo→describe()

Returns a short text that describes unambiguously the instance of the servo in the form TYPE(NAME)=SERIAL.FUNCTIONID.

servo→get_advertisedValue()

Returns the current value of the servo (no more than 6 characters).

servo→get_enabled()

Returns the state of the servos.

servo→get_enabledAtPowerOn()

Returns the servo signal generator state at power up.

servo→get_errorMessage()

Returns the error message of the latest error with the servo.

servo→get_errorType()

Returns the numerical error code of the latest error with the servo.

servo→get_friendlyName()

Returns a global identifier of the servo in the format MODULE_NAME . FUNCTION_NAME.

servo→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

servo→get_functionId()

Returns the hardware identifier of the servo, without reference to the module.

servo→get_hardwareId()

Returns the unique hardware identifier of the servo in the form SERIAL.FUNCTIONID.

servo→get_logicalName()

Returns the logical name of the servo.

`servo→get_module()`

Gets the YModule object for the device on which the function is located.

`servo→get_module_async(callback, context)`

Gets the YModule object for the device on which the function is located (asynchronous version).

`servo→get_neutral()`

Returns the duration in microseconds of a neutral pulse for the servo.

`servo→get_position()`

Returns the current servo position.

`servo→get_positionAtPowerOn()`

Returns the servo position at device power up.

`servo→get_range()`

Returns the current range of use of the servo.

`servo→get_userData()`

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

`servo→isOnline()`

Checks if the servo is currently reachable, without raising any error.

`servo→isOnline_async(callback, context)`

Checks if the servo is currently reachable, without raising any error (asynchronous version).

`servo→load(msValidity)`

Preloads the servo cache with a specified validity duration.

`servo→load_async(msValidity, callback, context)`

Preloads the servo cache with a specified validity duration (asynchronous version).

`servo→move(target, ms_duration)`

Performs a smooth move at constant speed toward a given position.

`servo→nextServo()`

Continues the enumeration of servos started using `yFirstServo()`.

`servo→registerValueCallback(callback)`

Registers the callback function that is invoked on every change of advertised value.

`servo→set_enabled(newval)`

Stops or starts the servo.

`servo→set_enabledAtPowerOn(newval)`

Configure the servo signal generator state at power up.

`servo→set_logicalName(newval)`

Changes the logical name of the servo.

`servo→set_neutral(newval)`

Changes the duration of the pulse corresponding to the neutral position of the servo.

`servo→set_position(newval)`

Changes immediately the servo driving position.

`servo→set_positionAtPowerOn(newval)`

Configure the servo position at device power up.

`servo→set_range(newval)`

Changes the range of use of the servo, specified in per cents.

`servo→set_userData(data)`

Stores a user context provided as argument in the userData attribute of the function.

`servo→wait_async(callback, context)`

3. Reference

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YServo.FindServo() yFindServo()YServo.FindServo()

YServo

Retrieves a servo for a given identifier.

```
def FindServo( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the servo is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YServo.isOnline()` to test if the servo is indeed online at a given time. In case of ambiguity when looking for a servo by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the servo

Returns :

a `YServo` object allowing you to drive the servo.

YServo.FirstServo()

YServo

yFirstServo()YServo.FirstServo()

Starts the enumeration of servos currently accessible.

```
def FirstServo( )
```

Use the method `YServo.nextServo()` to iterate on next servos.

Returns :

a pointer to a `YServo` object, corresponding to the first servo currently online, or a `null` pointer if there are none.

servo→describe()servo.describe()**YServo**

Returns a short text that describes unambiguously the instance of the servo in the form TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the servo (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

servo→get_advertisedValue()

YServo

servo→advertisedValue()servo.get_advertisedValue()

Returns the current value of the servo (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the servo (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

servo→get_enabled()**YServo****servo→enabled()servo.get_enabled()**

Returns the state of the servos.

```
def get_enabled( )
```

Returns :

either Y_ENABLED_FALSE or Y_ENABLED_TRUE, according to the state of the servos

On failure, throws an exception or returns Y_ENABLED_INVALID.

servo→get_enabledAtPowerOn()
servo→enabledAtPowerOn()
servo.get_enabledAtPowerOn()

YServo

Returns the servo signal generator state at power up.

```
def get_enabledAtPowerOn( )
```

Returns :

either Y_ENABLEDATPOWERON_FALSE or Y_ENABLEDATPOWERON_TRUE, according to the servo signal generator state at power up

On failure, throws an exception or returns Y_ENABLEDATPOWERON_INVALID.

servo→get_errorMessage()
servo→errorMessage()servo.getErrorMessage()**YServo**

Returns the error message of the latest error with the servo.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the servo object

servo→get_errorType()
servo→errorType()servo.get_errorType()

YServo

Returns the numerical error code of the latest error with the servo.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the servo object

servo→get_friendlyName()**YServo****servo→friendlyName()servo.get_friendlyName()**

Returns a global identifier of the servo in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the servo if they are defined, otherwise the serial number of the module and the hardware identifier of the servo (for example: MyCustomName . relay1)

Returns :

a string that uniquely identifies the servo using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

servo→get_functionDescriptor()
servo→functionDescriptor()
servo.get_functionDescriptor()

YServo

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

servo→get_functionId()**YServo****servo→functionId()servo.get_functionId()**

Returns the hardware identifier of the servo, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the servo (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

servo→get_hardwareId()**YServo****servo→hardwareId()servo.get_hardwareId()**

Returns the unique hardware identifier of the servo in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the servo (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the servo (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

servo→get_logicalName()
servo→logicalName()servo.get_logicalName()**YServo**

Returns the logical name of the servo.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the servo.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

servo→get_module()**servo→module()servo.get_module()****YServo**

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

servo→get_neutral()**YServo****servo→neutral()servo.get_neutral()**

Returns the duration in microseconds of a neutral pulse for the servo.

```
def get_neutral( )
```

Returns :

an integer corresponding to the duration in microseconds of a neutral pulse for the servo

On failure, throws an exception or returns Y_NEUTRAL_INVALID.

servo→get_position()
servo→position()servo.get_position()

YServo

Returns the current servo position.

```
def get_position( )
```

Returns :

an integer corresponding to the current servo position

On failure, throws an exception or returns Y_POSITION_INVALID.

servo→get_positionAtPowerOn()
servo→positionAtPowerOn()
servo.get_positionAtPowerOn()

YServo

Returns the servo position at device power up.

```
def get_positionAtPowerOn( )
```

Returns :

an integer corresponding to the servo position at device power up

On failure, throws an exception or returns Y_POSITIONATPOWERON_INVALID.

servo→get_range()

YServo

servo→range()servo.get_range()

Returns the current range of use of the servo.

```
def get_range( )
```

Returns :

an integer corresponding to the current range of use of the servo

On failure, throws an exception or returns Y_RANGE_INVALID.

servo→get(userData)**YServo****servo→userData()servo.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

servo→isOnline()servo.isOnline()**YServo**

Checks if the servo is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the servo in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the servo.

Returns :

`true` if the servo can be reached, and `false` otherwise

servo→load()servo.load()**YServo**

Preloads the servo cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

servo→move()servo.move()**YServo**

Performs a smooth move at constant speed toward a given position.

```
def move( target, ms_duration)
```

Parameters :

target new position at the end of the move

ms_duration total duration of the move, in milliseconds

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

servo→nextServo()servo.nextServo()**YServo**

Continues the enumeration of servos started using `yFirstServo()`.

```
def nextServo( )
```

Returns :

a pointer to a `YServo` object, corresponding to a servo currently online, or a `null` pointer if there are no more servos to enumerate.

servo→registerValueCallback()
servo.registerValueCallback()**YServo**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

servo→set_enabled()	YServo
servo→setEnabled()servo.set_enabled()	

Stops or starts the servo.

```
def set_enabled( newval)
```

Parameters :

newval either Y_ENABLED_FALSE or Y_ENABLED_TRUE

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

servo→set_enabledAtPowerOn()
servo→setEnabledAtPowerOn()
servo.set_enabledAtPowerOn()

YServo

Configure the servo signal generator state at power up.

```
def set_enabledAtPowerOn( newval)
```

Remember to call the matching module saveToFlash() method, otherwise this call will have no effect.

Parameters :

newval either Y_ENABLEDATPOWERON_FALSE or Y_ENABLEDATPOWERON_TRUE

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

servo→set_logicalName()**YServo****servo→setLogicalName()servo.set_logicalName()**

Changes the logical name of the servo.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the servo.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

**servo→set_neutral()
servo→setNeutral()servo.set_neutral()****YServo**

Changes the duration of the pulse corresponding to the neutral position of the servo.

```
def set_neutral( newval )
```

The duration is specified in microseconds, and the standard value is 1500 [us]. This setting makes it possible to shift the range of use of the servo. Be aware that using a range higher than what is supported by the servo is likely to damage the servo.

Parameters :

newval an integer corresponding to the duration of the pulse corresponding to the neutral position of the servo

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

servo→set_position()	YServo
servo→setPosition()servo.set_position()	

Changes immediately the servo driving position.

```
def set_position( newval)
```

Parameters :

newval an integer corresponding to immediately the servo driving position

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

servo→set_positionAtPowerOn()
servo→setPositionAtPowerOn()
servo.set_positionAtPowerOn()

YServo

Configure the servo position at device power up.

```
def set_positionAtPowerOn( newval)
```

Remember to call the matching module saveToFlash() method, otherwise this call will have no effect.

Parameters :

newval an integer

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

servo→set_range()**YServo****servo→setRange()servo.set_range()**

Changes the range of use of the servo, specified in per cents.

```
def set_range( newval)
```

A range of 100% corresponds to a standard control signal, that varies from 1 [ms] to 2 [ms]. When using a servo that supports a double range, from 0.5 [ms] to 2.5 [ms], you can select a range of 200%. Be aware that using a range higher than what is supported by the servo is likely to damage the servo.

Parameters :

newval an integer corresponding to the range of use of the servo, specified in per cents

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

servo→set(userData)

YServo

servo→setUserData()servo.set.userData()

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.42. Temperature function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_temperature.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YTemperature = yoctolib.YTemperature;
php	require_once('yocto_temperature.php');
cpp	#include "yocto_temperature.h"
m	#import "yocto_temperature.h"
pas	uses yocto_temperature;
vb	yocto_temperature.vb
cs	yocto_temperature.cs
java	import com.yoctopuce.YoctoAPI.YTemperature;
py	from yocto_temperature import *

Global functions

yFindTemperature(func)

Retrieves a temperature sensor for a given identifier.

yFirstTemperature()

Starts the enumeration of temperature sensors currently accessible.

YTemperature methods

temperature→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

temperature→describe()

Returns a short text that describes unambiguously the instance of the temperature sensor in the form TYPE (NAME) = SERIAL . FUNCTIONID.

temperature→get_advertisedValue()

Returns the current value of the temperature sensor (no more than 6 characters).

temperature→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in Celsius, as a floating point number.

temperature→get_currentValue()

Returns the current value of the temperature, in Celsius, as a floating point number.

temperature→get_errorMessage()

Returns the error message of the latest error with the temperature sensor.

temperature→get_errorType()

Returns the numerical error code of the latest error with the temperature sensor.

temperature→get_friendlyName()

Returns a global identifier of the temperature sensor in the format MODULE_NAME . FUNCTION_NAME.

temperature→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

temperature→get_functionId()

Returns the hardware identifier of the temperature sensor, without reference to the module.

temperature→get_hardwareId()

Returns the unique hardware identifier of the temperature sensor in the form SERIAL . FUNCTIONID.

temperature→get_highestValue()	Returns the maximal value observed for the temperature since the device was started.
temperature→get_logFrequency()	Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.
temperature→get_logicalName()	Returns the logical name of the temperature sensor.
temperature→get_lowestValue()	Returns the minimal value observed for the temperature since the device was started.
temperature→get_module()	Gets the YModule object for the device on which the function is located.
temperature→get_module_async(callback, context)	Gets the YModule object for the device on which the function is located (asynchronous version).
temperature→get_recordedData(startTime, endTime)	Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.
temperature→get_reportFrequency()	Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.
temperature→get_resolution()	Returns the resolution of the measured values.
temperature→get_sensorType()	Returns the temperature sensor type.
temperature→get_unit()	Returns the measuring unit for the temperature.
temperature→get(userData)	Returns the value of the userData attribute, as previously stored using method set(userData).
temperature→isOnline()	Checks if the temperature sensor is currently reachable, without raising any error.
temperature→isOnline_async(callback, context)	Checks if the temperature sensor is currently reachable, without raising any error (asynchronous version).
temperature→load(msValidity)	Preloads the temperature sensor cache with a specified validity duration.
temperature→loadCalibrationPoints(rawValues, refValues)	Retrieves error correction data points previously entered using the method calibrateFromPoints.
temperature→load_async(msValidity, callback, context)	Preloads the temperature sensor cache with a specified validity duration (asynchronous version).
temperature→nextTemperature()	Continues the enumeration of temperature sensors started using yFirstTemperature().
temperature→registerTimedReportCallback(callback)	Registers the callback function that is invoked on every periodic timed notification.
temperature→registerValueCallback(callback)	Registers the callback function that is invoked on every change of advertised value.
temperature→set_highestValue(newval)	Changes the recorded maximal value observed.
temperature→set_logFrequency(newval)	Changes the datalogger recording frequency for this function.

temperature→set_logicalName(newval)

Changes the logical name of the temperature sensor.

temperature→set_lowestValue(newval)

Changes the recorded minimal value observed.

temperature→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

temperature→set_resolution(newval)

Changes the resolution of the measured physical values.

temperature→set_sensorType(newval)

Modify the temperature sensor type.

temperature→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

temperature→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YTemperature.FindTemperature() yFindTemperature()YTemperature.FindTemperature()

Retrieves a temperature sensor for a given identifier.

```
def FindTemperature( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the temperature sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YTemperature.isOnline()` to test if the temperature sensor is indeed online at a given time. In case of ambiguity when looking for a temperature sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the temperature sensor

Returns :

a `YTemperature` object allowing you to drive the temperature sensor.

YTemperature.FirstTemperature()**YTemperature****yFirstTemperature()YTemperature.FirstTemperature()**

Starts the enumeration of temperature sensors currently accessible.

```
def FirstTemperature( )
```

Use the method `YTemperature.nextTemperature()` to iterate on next temperature sensors.

Returns :

a pointer to a `YTemperature` object, corresponding to the first temperature sensor currently online, or a null pointer if there are none.

temperature→calibrateFromPoints()
temperature.calibrateFromPoints()**YTemperature**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→describe()temperature.describe()**YTemperature**

Returns a short text that describes unambiguously the instance of the temperature sensor in the form TYPE (NAME)=SERIAL . FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

```
a string that describes the temperature sensor (ex:  
Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)
```

temperature→get_advertisedValue()
temperature→advertisedValue()
temperature.get_advertisedValue()

YTemperature

Returns the current value of the temperature sensor (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the temperature sensor (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

temperature→get_currentRawValue()
temperature→currentRawValue()
temperature.get_currentRawValue()

YTemperature

Returns the uncalibrated, unrounded raw value returned by the sensor, in Celsius, as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in Celsius, as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

temperature→get_currentValue()
temperature→currentValue()
temperature.get_currentValue()

YTemperature

Returns the current value of the temperature, in Celsius, as a floating point number.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current value of the temperature, in Celsius, as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

temperature→getErrorMessage()
temperature→errorMessage()
temperature.getErrorMessage()

YTemperature

Returns the error message of the latest error with the temperature sensor.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the temperature sensor object

temperature→get_errorType()
temperature→errorType()
temperature.get_errorType()

YTemperature

Returns the numerical error code of the latest error with the temperature sensor.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the temperature sensor object

temperature→get_friendlyName()
temperature→friendlyName()
temperature.get_friendlyName()

YTemperature

Returns a global identifier of the temperature sensor in the format MODULE_NAME.FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the temperature sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the temperature sensor (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the temperature sensor using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

temperature→get_functionDescriptor()
temperature→functionDescriptor()
temperature.get_functionDescriptor()

YTemperature

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

temperature→get_functionId()	YTemperature
temperature→functionId()	
temperature.get_functionId()	

Returns the hardware identifier of the temperature sensor, without reference to the module.

```
def get_functionId( )
```

For example relay1

Returns :

a string that identifies the temperature sensor (ex: relay1)

On failure, throws an exception or returns Y_FUNCTIONID_INVALID.

temperature→get_hardwareId()
temperature→hardwareId()
temperature.get_hardwareId()

YTemperature

Returns the unique hardware identifier of the temperature sensor in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the temperature sensor (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the temperature sensor (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

temperature→get_highestValue()
temperature→highestValue()
temperature.get_highestValue()

YTemperature

Returns the maximal value observed for the temperature since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the temperature since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

temperature→get_logFrequency()	YTemperature
temperature→logFrequency()	
temperature.get_logFrequency()	

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

temperature→get_logicalName()
temperature→logicalName()
temperature.get_logicalName()

YTemperature

Returns the logical name of the temperature sensor.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the temperature sensor.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

temperature→get_lowestValue()
temperature→lowestValue()
temperature.get_lowestValue()

YTemperature

Returns the minimal value observed for the temperature since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the temperature since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

temperature→get_module()**YTemperature****temperature→module()temperature.get_module()**

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

temperature→get_recordedData()
temperature→recordedData()
temperature.get_recordedData()

YTemperature

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime )
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

temperature→get_reportFrequency()
temperature→reportFrequency()
temperature.get_reportFrequency()

YTemperature

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

temperature→get_resolution()
temperature→resolution()
temperature.get_resolution()

YTemperature

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

temperature→get_sensorType()
temperature→sensorType()
temperature.get_sensorType()

YTemperature

Returns the temperature sensor type.

```
def get_sensorType( )
```

Returns :

a value among Y_SENSORTYPE_DIGITAL, Y_SENSORTYPE_TYPE_K,
Y_SENSORTYPE_TYPE_E, Y_SENSORTYPE_TYPE_J, Y_SENSORTYPE_TYPE_N,
Y_SENSORTYPE_TYPE_R, Y_SENSORTYPE_TYPE_S, Y_SENSORTYPE_TYPE_T,
Y_SENSORTYPE_PT100_4WIRES, Y_SENSORTYPE_PT100_3WIRES and
Y_SENSORTYPE_PT100_2WIRES corresponding to the temperature sensor type

On failure, throws an exception or returns Y_SENSORTYPE_INVALID.

temperature→get_unit()

YTemperature

temperature→unit()temperature.get_unit()

Returns the measuring unit for the temperature.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the temperature

On failure, throws an exception or returns Y_UNIT_INVALID.

temperature→get(userData)**YTemperature****temperature→userData()temperature.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

temperature→isOnline()**YTemperature**

Checks if the temperature sensor is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the temperature sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the temperature sensor.

Returns :

`true` if the temperature sensor can be reached, and `false` otherwise

temperature→load()temperature.load()**YTemperature**

Preloads the temperature sensor cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→loadCalibrationPoints()
temperature.loadCalibrationPoints()**YTemperature**

Retrieves error correction data points previously entered using the method `calibrateFromPoints`.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→nextTemperature()
temperature.nextTemperature()

YTemperature

Continues the enumeration of temperature sensors started using `yFirstTemperature()`.

```
def nextTemperature( )
```

Returns :

a pointer to a `YTemperature` object, corresponding to a temperature sensor currently online, or a `null` pointer if there are no more temperature sensors to enumerate.

**temperature→registerTimedReportCallback()
temperature.registerTimedReportCallback()****YTemperature**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

**temperature→registerValueCallback()
temperature.registerValueCallback()****YTemperature**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

temperature→set_highestValue()
temperature→setHighestValue()
temperature.set_highestValue()

YTemperature

Changes the recorded maximal value observed.

```
def set_highestValue( newval )
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→set_logFrequency()
temperature→setLogFrequency()
temperature.set_logFrequency()

YTemperature

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval)
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→set_logicalName()
temperature→setLogicalName()
temperature.set_logicalName()

YTemperature

Changes the logical name of the temperature sensor.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the temperature sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→set_lowestValue()
temperature→setLowestValue()
temperature.set_lowestValue()

YTemperature

Changes the recorded minimal value observed.

```
def set_lowestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→set_reportFrequency()
temperature→setReportFrequency()
temperature.set_reportFrequency()

YTemperature

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→set_resolution()
temperature→setResolution()
temperature.set_resolution()

YTemperature

Changes the resolution of the measured physical values.

```
def set_resolution( newval )
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→set_sensorType()
temperature→setSensorType()
temperature.set_sensorType()

YTemperature

Modify the temperature sensor type.

```
def set_sensorType( newval )
```

This function is used to define the type of thermocouple (K,E...) used with the device. This will have no effect if module is using a digital sensor. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a value among `Y_SENSORTYPE_DIGITAL`, `Y_SENSORTYPE_TYPE_K`,
`Y_SENSORTYPE_TYPE_E`, `Y_SENSORTYPE_TYPE_J`, `Y_SENSORTYPE_TYPE_N`,
`Y_SENSORTYPE_TYPE_R`, `Y_SENSORTYPE_TYPE_S`, `Y_SENSORTYPE_TYPE_T`,
`Y_SENSORTYPE_PT100_4WIRES`, `Y_SENSORTYPE_PT100_3WIRES` and
`Y_SENSORTYPE_PT100_2WIRES`

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

temperature→set(userData)
temperature→setUserData()
temperature.set(userData)

YTemperature

Stores a user context provided as argument in the userData attribute of the function.

```
def setUserData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.43. Tilt function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_tilt.js'></script>
nodejs var yoctolib = require('yoctolib');
var YTilt = yoctolib.YTilt;
php require_once('yocto_tilt.php');
cpp #include "yocto_tilt.h"
m #import "yocto_tilt.h"
pas uses yocto_tilt;
vb yocto_tilt.vb
cs yocto_tilt.cs
java import com.yoctopuce.YoctoAPI.YTilt;
py from yocto_tilt import *

```

Global functions

yFindTilt(func)

Retrieves a tilt sensor for a given identifier.

yFirstTilt()

Starts the enumeration of tilt sensors currently accessible.

YTilt methods

tilt→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

tilt→describe()

Returns a short text that describes unambiguously the instance of the tilt sensor in the form TYPE (NAME) = SERIAL . FUNCTIONID.

tilt→get_advertisedValue()

Returns the current value of the tilt sensor (no more than 6 characters).

tilt→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in degrees, as a floating point number.

tilt→get_currentValue()

Returns the current value of the inclination, in degrees, as a floating point number.

tilt→get_errorMessage()

Returns the error message of the latest error with the tilt sensor.

tilt→get_errorType()

Returns the numerical error code of the latest error with the tilt sensor.

tilt→get_friendlyName()

Returns a global identifier of the tilt sensor in the format MODULE_NAME . FUNCTION_NAME.

tilt→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

tilt→get_functionId()

Returns the hardware identifier of the tilt sensor, without reference to the module.

tilt→get_hardwareId()

Returns the unique hardware identifier of the tilt sensor in the form SERIAL . FUNCTIONID.

tilt→get_highestValue()	Returns the maximal value observed for the inclination since the device was started.
tilt→get_logFrequency()	Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.
tilt→get_logicalName()	Returns the logical name of the tilt sensor.
tilt→get_lowestValue()	Returns the minimal value observed for the inclination since the device was started.
tilt→get_module()	Gets the YModule object for the device on which the function is located.
tilt→get_module_async(callback, context)	Gets the YModule object for the device on which the function is located (asynchronous version).
tilt→get_recordedData(startTime, endTime)	Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.
tilt→get_reportFrequency()	Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.
tilt→get_resolution()	Returns the resolution of the measured values.
tilt→get_unit()	Returns the measuring unit for the inclination.
tilt→get(userData)	Returns the value of the userData attribute, as previously stored using method set(userData).
tilt→isOnline()	Checks if the tilt sensor is currently reachable, without raising any error.
tilt→isOnline_async(callback, context)	Checks if the tilt sensor is currently reachable, without raising any error (asynchronous version).
tilt→load(msValidity)	Preloads the tilt sensor cache with a specified validity duration.
tilt→loadCalibrationPoints(rawValues, refValues)	Retrieves error correction data points previously entered using the method calibrateFromPoints.
tilt→load_async(msValidity, callback, context)	Preloads the tilt sensor cache with a specified validity duration (asynchronous version).
tilt→nextTilt()	Continues the enumeration of tilt sensors started using yFirstTilt().
tilt→registerTimedReportCallback(callback)	Registers the callback function that is invoked on every periodic timed notification.
tilt→registerValueCallback(callback)	Registers the callback function that is invoked on every change of advertised value.
tilt→set_highestValue(newval)	Changes the recorded maximal value observed.
tilt→set_logFrequency(newval)	Changes the datalogger recording frequency for this function.
tilt→set_logicalName(newval)	Changes the logical name of the tilt sensor.

3. Reference

`tilt→set_lowestValue(newval)`

Changes the recorded minimal value observed.

`tilt→set_reportFrequency(newval)`

Changes the timed value notification frequency for this function.

`tilt→set_resolution(newval)`

Changes the resolution of the measured physical values.

`tilt→set_userData(data)`

Stores a user context provided as argument in the userData attribute of the function.

`tilt→wait_async(callback, context)`

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YTilt.FindTilt()**YTilt****yFindTilt()YTilt.FindTilt()**

Retrieves a tilt sensor for a given identifier.

```
def FindTilt( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the tilt sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YTilt.isOnline()` to test if the tilt sensor is indeed online at a given time. In case of ambiguity when looking for a tilt sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

func a string that uniquely characterizes the tilt sensor

Returns :

a `YTilt` object allowing you to drive the tilt sensor.

YTilt.FirstTilt()

YTilt

yFirstTilt()YTilt.FirstTilt()

Starts the enumeration of tilt sensors currently accessible.

```
def FirstTilt( )
```

Use the method `YTilt.nextTilt()` to iterate on next tilt sensors.

Returns :

a pointer to a `YTilt` object, corresponding to the first tilt sensor currently online, or a `null` pointer if there are none.

tilt→calibrateFromPoints()tilt.calibrateFromPoints()**YTilt**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

tilt→describe()tilt.describe()**YTilt**

Returns a short text that describes unambiguously the instance of the tilt sensor in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the tilt sensor (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

tilt→get_advertisedValue()**YTilt****tilt→advertisedValue()tilt.get_advertisedValue()**

Returns the current value of the tilt sensor (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the tilt sensor (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

tilt→get_currentRawValue() YTilt
tilt→currentRawValue()tilt.get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in degrees, as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in degrees, as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

tilt→get_currentValue()**YTilt****tilt→currentValue()tilt.get_currentValue()**

Returns the current value of the inclination, in degrees, as a floating point number.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current value of the inclination, in degrees, as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

tilt→get_errorMessage() YTilt
tilt→errorMessage()tilt.getErrorMessage()

Returns the error message of the latest error with the tilt sensor.

```
def getErrorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the tilt sensor object

tilt→get_errorType()**YTilt****tilt→errorType()tilt.get_errorType()**

Returns the numerical error code of the latest error with the tilt sensor.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the tilt sensor object

tilt→get_friendlyName()	YTilt
tilt→friendlyName()tilt.get_friendlyName()	

Returns a global identifier of the tilt sensor in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the tilt sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the tilt sensor (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the tilt sensor using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

tilt→get_functionDescriptor()**YTilt****tilt→functionDescriptor()tilt.get_functionDescriptor()**

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

tilt→get_functionId()

YTilt

tilt→functionId()tilt.get_functionId()

Returns the hardware identifier of the tilt sensor, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the tilt sensor (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

tilt→get_hardwareId()**YTilt****tilt→hardwareId()tilt.get_hardwareId()**

Returns the unique hardware identifier of the tilt sensor in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the tilt sensor (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the tilt sensor (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

tilt→get_highestValue()

YTilt

tilt→highestValue()tilt.get_highestValue()

Returns the maximal value observed for the inclination since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the inclination since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

tilt→get_logFrequency()**YTilt****tilt→logFrequency()tilt.get_logFrequency()**

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

tilt→get_logicalName()	YTilt
tilt→logicalName()tilt.get_logicalName()	

Returns the logical name of the tilt sensor.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the tilt sensor.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

tilt→get_lowestValue()**YTilt****tilt→lowestValue()tilt.get_lowestValue()**

Returns the minimal value observed for the inclination since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the inclination since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

tilt→get_module()
tilt→module()tilt.get_module()

YTilt

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

tilt→get_recordedData()

YTilt

tilt→recordedData(tilt.get_recordedData())

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime)
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

tilt→get_reportFrequency()	YTilt
tilt→reportFrequency()tilt.get_reportFrequency()	

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

tilt→get_resolution()

YTilt

tilt→resolution()tilt.get_resolution()

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

tilt→get_unit()
tilt→unit()tilt.get_unit()

YTilt

Returns the measuring unit for the inclination.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the inclination

On failure, throws an exception or returns Y_UNIT_INVALID.

tilt→get(userData)**YTilt****tilt→userData()tilt.get(userData)**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

**tilt→isOnline()
tilt.isOnline()****YTilt**

Checks if the tilt sensor is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the tilt sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the tilt sensor.

Returns :

`true` if the tilt sensor can be reached, and `false` otherwise

tilt→load()tilt.load()**YTilt**

Preloads the tilt sensor cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

tilt→loadCalibrationPoints()
tilt.loadCalibrationPoints()**YTilt**

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

tilt→nextTilt()tilt.nextTilt()**YTilt**

Continues the enumeration of tilt sensors started using `yFirstTilt()`.

```
def nextTilt( )
```

Returns :

a pointer to a `YTilt` object, corresponding to a tilt sensor currently online, or a null pointer if there are no more tilt sensors to enumerate.

**tilt→registerTimedReportCallback()
tilt.registerTimedReportCallback()****YTilt**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

tilt→registerValueCallback()
tilt.registerValueCallback()

YTilt

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

tilt→set_highestValue()	YTilt
tilt→setHighestValue()tilt.set_highestValue()	

Changes the recorded maximal value observed.

```
def set_highestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

tilt→set_logFrequency()

YTilt

tilt→setLogFrequency()tilt.set_logFrequency()

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval)
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

tilt→set_logicalName()	YTilt
tilt→setLogicalName()tilt.set_logicalName()	

Changes the logical name of the tilt sensor.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the tilt sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

tilt→set_lowestValue()

YTilt

tilt→setLowestValue()tilt.set_lowestValue()

Changes the recorded minimal value observed.

```
def set_lowestValue( newval )
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

tilt→set_reportFrequency() YTilt
tilt→setReportFrequency()tilt.set_reportFrequency()

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval)
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

tilt→set_resolution()**YTilt****tilt→setResolution()tilt.set_resolution()**

Changes the resolution of the measured physical values.

```
def set_resolution( newval )
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

tilt→set(userData)

YTilt

tilt→setUserData()tilt.set(userData)

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.44. Voc function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_voc.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YVoc = yoctolib.YVoc;
php	require_once('yocto_voc.php');
cpp	#include "yocto_voc.h"
m	#import "yocto_voc.h"
pas	uses yocto_voc;
vb	yocto_voc.vb
cs	yocto_voc.cs
java	import com.yoctopuce.YoctoAPI.YVoc;
py	from yocto_voc import *

Global functions

yFindVoc(func)

Retrieves a Volatile Organic Compound sensor for a given identifier.

yFirstVoc()

Starts the enumeration of Volatile Organic Compound sensors currently accessible.

YVoc methods

voc→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

voc→describe()

Returns a short text that describes unambiguously the instance of the Volatile Organic Compound sensor in the form TYPE (NAME) = SERIAL.FUNCTIONID.

voc→get_advertisedValue()

Returns the current value of the Volatile Organic Compound sensor (no more than 6 characters).

voc→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in ppm (vol), as a floating point number.

voc→get_currentValue()

Returns the current value of the estimated VOC concentration, in ppm (vol), as a floating point number.

voc→get_errorMessage()

Returns the error message of the latest error with the Volatile Organic Compound sensor.

voc→get_errorType()

Returns the numerical error code of the latest error with the Volatile Organic Compound sensor.

voc→get_friendlyName()

Returns a global identifier of the Volatile Organic Compound sensor in the format MODULE_NAME.FUNCTION_NAME.

voc→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

voc→get_functionId()

Returns the hardware identifier of the Volatile Organic Compound sensor, without reference to the module.

voc→get_hardwareId()

3. Reference

Returns the unique hardware identifier of the Volatile Organic Compound sensor in the form SERIAL.FUNCTIONID.

voc->get_highestValue()

Returns the maximal value observed for the estimated VOC concentration since the device was started.

voc->get_logFrequency()

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

voc->get_logicalName()

Returns the logical name of the Volatile Organic Compound sensor.

voc->get_lowestValue()

Returns the minimal value observed for the estimated VOC concentration since the device was started.

voc->get_module()

Gets the YModule object for the device on which the function is located.

voc->get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

voc->get_recordedData(startTime, endTime)

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

voc->get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

voc->get_resolution()

Returns the resolution of the measured values.

voc->get_unit()

Returns the measuring unit for the estimated VOC concentration.

voc->get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

voc->isOnline()

Checks if the Volatile Organic Compound sensor is currently reachable, without raising any error.

voc->isOnline_async(callback, context)

Checks if the Volatile Organic Compound sensor is currently reachable, without raising any error (asynchronous version).

voc->load(msValidity)

Preloads the Volatile Organic Compound sensor cache with a specified validity duration.

voc->loadCalibrationPoints(rawValues, refValues)

Retrieves error correction data points previously entered using the method calibrateFromPoints.

voc->load_async(msValidity, callback, context)

Preloads the Volatile Organic Compound sensor cache with a specified validity duration (asynchronous version).

voc->nextVoc()

Continues the enumeration of Volatile Organic Compound sensors started using yFirstVoc().

voc->registerTimedReportCallback(callback)

Registers the callback function that is invoked on every periodic timed notification.

voc->registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

voc->set_highestValue(newval)

Changes the recorded maximal value observed.

voc→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

voc→set_logicalName(newval)

Changes the logical name of the Volatile Organic Compound sensor.

voc→set_lowestValue(newval)

Changes the recorded minimal value observed.

voc→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

voc→set_resolution(newval)

Changes the resolution of the measured physical values.

voc→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

voc→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YVoc.FindVoc() yFindVoc()YVoc.FindVoc()

YVoc

Retrieves a Volatile Organic Compound sensor for a given identifier.

```
def FindVoc( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the Volatile Organic Compound sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YVoc.isOnline()` to test if the Volatile Organic Compound sensor is indeed online at a given time. In case of ambiguity when looking for a Volatile Organic Compound sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the Volatile Organic Compound sensor

Returns :

a `YVoc` object allowing you to drive the Volatile Organic Compound sensor.

YVoc.FirstVoc()**YVoc****yFirstVoc()YVoc.FirstVoc()**

Starts the enumeration of Volatile Organic Compound sensors currently accessible.

```
def FirstVoc( )
```

Use the method `YVoc.nextVoc()` to iterate on next Volatile Organic Compound sensors.

Returns :

a pointer to a `YVoc` object, corresponding to the first Volatile Organic Compound sensor currently online, or a null pointer if there are none.

voc→calibrateFromPoints()|voc.calibrateFromPoints()**YVoc**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

voc→describe()voc.describe()**YVoc**

Returns a short text that describes unambiguously the instance of the Volatile Organic Compound sensor in the form TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

```
a string that describes the Volatile Organic Compound sensor (ex:  
Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)
```

voc→get_advertisedValue()

YVoc

voc→advertisedValue()voc.get_advertisedValue()

Returns the current value of the Volatile Organic Compound sensor (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the Volatile Organic Compound sensor (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

voc→get_currentRawValue()**YVoc****voc→currentRawValue()voc.get_currentRawValue()**

Returns the uncalibrated, unrounded raw value returned by the sensor, in ppm (vol), as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in ppm (vol), as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

voc→get_currentValue() YVoc
voc→currentValue()voc.get_currentValue()

Returns the current value of the estimated VOC concentration, in ppm (vol), as a floating point number.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current value of the estimated VOC concentration, in ppm (vol), as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

voc→get_errorMessage()**YVoc****voc→errorMessage()voc.get_errorMessage()**

Returns the error message of the latest error with the Volatile Organic Compound sensor.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the Volatile Organic Compound sensor object

voc→get_errorType()
voc→errorType()voc.get_errorType()

YVoc

Returns the numerical error code of the latest error with the Volatile Organic Compound sensor.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the Volatile Organic Compound sensor object

voc→get_friendlyName()**YVoc****voc→friendlyName()voc.get_friendlyName()**

Returns a global identifier of the Volatile Organic Compound sensor in the format MODULE_NAME.FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the Volatile Organic Compound sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the Volatile Organic Compound sensor (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the Volatile Organic Compound sensor using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

voc->get_functionDescriptor()
voc->functionDescriptor()
voc.get_functionDescriptor()

YVoc

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

voc→get_functionId()**YVoc****voc→functionId()voc.get_functionId()**

Returns the hardware identifier of the Volatile Organic Compound sensor, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the Volatile Organic Compound sensor (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

voc→get_hardwareId()**YVoc****voc→hardwareId()voc.get_hardwareId()**

Returns the unique hardware identifier of the Volatile Organic Compound sensor in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the Volatile Organic Compound sensor (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the Volatile Organic Compound sensor (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

voc→get_highestValue()**YVoc****voc→highestValue()voc.get_highestValue()**

Returns the maximal value observed for the estimated VOC concentration since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the estimated VOC concentration since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

voc→get_logFrequency() YVoc
voc→logFrequency()voc.get_logFrequency()

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

voc→get_logicalName()**YVoc****voc→logicalName()voc.get_logicalName()**

Returns the logical name of the Volatile Organic Compound sensor.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the Volatile Organic Compound sensor.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

**voc→get_lowestValue()
voc→lowestValue()voc.get_lowestValue()****YVoc**

Returns the minimal value observed for the estimated VOC concentration since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the estimated VOC concentration since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

voc→get_module()**YVoc****voc→module()voc.get_module()**

Gets the YModule object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of YModule is not shown as online.

Returns :

an instance of YModule

voc→get_recordedData()	YVoc
voc→recordedData()voc.get_recordedData()	

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime )
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any meaasure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any meaasure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

voc→get_reportFrequency()**YVoc****voc→reportFrequency()voc.get_reportFrequency()**

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

voc→get_resolution()
voc→resolution()voc.get_resolution()

YVoc

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

voc→get_unit()**YVoc****voc→unit()voc.get_unit()**

Returns the measuring unit for the estimated VOC concentration.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the estimated VOC concentration

On failure, throws an exception or returns Y_UNIT_INVALID.

voc→get(userData)

YVoc

voc→userData()voc.get(userData())

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

voc→isOnline()voc.isOnline()**YVoc**

Checks if the Volatile Organic Compound sensor is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the Volatile Organic Compound sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the Volatile Organic Compound sensor.

Returns :

`true` if the Volatile Organic Compound sensor can be reached, and `false` otherwise

voc→load()voc.load()**YVoc**

Preloads the Volatile Organic Compound sensor cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

**voc→loadCalibrationPoints()
voc.loadCalibrationPoints()****YVoc**

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voc→nextVoc()voc.nextVoc()

YVoc

Continues the enumeration of Volatile Organic Compound sensors started using `yFirstVoc()`.

```
def nextVoc( )
```

Returns :

a pointer to a `YVoc` object, corresponding to a Volatile Organic Compound sensor currently online, or a null pointer if there are no more Volatile Organic Compound sensors to enumerate.

voc→registerTimedReportCallback()
voc.registerTimedReportCallback()**YVoc**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

voc→registerValueCallback()
voc.registerValueCallback()**YVoc**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

voc→set_highestValue()**YVoc****voc→setHighestValue()voc.set_highestValue()**

Changes the recorded maximal value observed.

```
def set_highestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voc→set_logFrequency() YVoc
voc→setLogFrequency()voc.set_logFrequency()

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval)
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voc→set_logicalName()**YVoc****voc→setLogicalName()voc.set_logicalName()**

Changes the logical name of the Volatile Organic Compound sensor.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the Volatile Organic Compound sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

voc→set_lowestValue()
voc→setLowestValue()voc.set_lowestValue()**YVoc**

Changes the recorded minimal value observed.

```
def set_lowestValue( newval )
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voc→set_reportFrequency()
voc→setReportFrequency()
voc.set_reportFrequency()

YVoc

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

**voc→set_resolution()
voc→setResolution()voc.set_resolution()****YVoc**

Changes the resolution of the measured physical values.

```
def set_resolution( newval)
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voc→set(userData)**YVoc****voc→setUserData()voc.set(userData)**

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.45. Voltage function interface

The Yoctopuce application programming interface allows you to read an instant measure of the sensor, as well as the minimal and maximal values observed.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_voltage.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YVoltage = yoctolib.YVoltage;
php	require_once('yocto_voltage.php');
cpp	#include "yocto_voltage.h"
m	#import "yocto_voltage.h"
pas	uses yocto_voltage;
vb	yocto_voltage.vb
cs	yocto_voltage.cs
java	import com.yoctopuce.YoctoAPI.YVoltage;
py	from yocto_voltage import *

Global functions

yFindVoltage(func)

Retrieves a voltage sensor for a given identifier.

yFirstVoltage()

Starts the enumeration of voltage sensors currently accessible.

YVoltage methods

voltage→calibrateFromPoints(rawValues, refValues)

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

voltage→describe()

Returns a short text that describes unambiguously the instance of the voltage sensor in the form TYPE (NAME) = SERIAL . FUNCTIONID.

voltage→get_advertisedValue()

Returns the current value of the voltage sensor (no more than 6 characters).

voltage→get_currentRawValue()

Returns the uncalibrated, unrounded raw value returned by the sensor, in Volt, as a floating point number.

voltage→get_currentValue()

Returns the current value of the voltage, in Volt, as a floating point number.

voltage→get_errorMessage()

Returns the error message of the latest error with the voltage sensor.

voltage→get_errorType()

Returns the numerical error code of the latest error with the voltage sensor.

voltage→get_friendlyName()

Returns a global identifier of the voltage sensor in the format MODULE_NAME . FUNCTION_NAME.

voltage→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

voltage→get_functionId()

Returns the hardware identifier of the voltage sensor, without reference to the module.

voltage→get_hardwareId()

Returns the unique hardware identifier of the voltage sensor in the form SERIAL . FUNCTIONID.

voltage→get_highestValue()

Returns the maximal value observed for the voltage since the device was started.

voltage→get_logFrequency()

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

voltage→get_logicalName()

Returns the logical name of the voltage sensor.

voltage→get_lowestValue()

Returns the minimal value observed for the voltage since the device was started.

voltage→get_module()

Gets the YModule object for the device on which the function is located.

voltage→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

voltage→get_recordedData(startTime, endTime)

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

voltage→get_reportFrequency()

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

voltage→get_resolution()

Returns the resolution of the measured values.

voltage→get_unit()

Returns the measuring unit for the voltage.

voltage→get(userData)

Returns the value of the userData attribute, as previously stored using method set(userData).

voltage→isOnline()

Checks if the voltage sensor is currently reachable, without raising any error.

voltage→isOnline_async(callback, context)

Checks if the voltage sensor is currently reachable, without raising any error (asynchronous version).

voltage→load(msValidity)

Preloads the voltage sensor cache with a specified validity duration.

voltage→loadCalibrationPoints(rawValues, refValues)

Retrieves error correction data points previously entered using the method calibrateFromPoints.

voltage→load_async(msValidity, callback, context)

Preloads the voltage sensor cache with a specified validity duration (asynchronous version).

voltage→nextVoltage()

Continues the enumeration of voltage sensors started using yFirstVoltage().

voltage→registerTimedReportCallback(callback)

Registers the callback function that is invoked on every periodic timed notification.

voltage→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

voltage→set_highestValue(newval)

Changes the recorded maximal value observed.

voltage→set_logFrequency(newval)

Changes the datalogger recording frequency for this function.

voltage→set_logicalName(newval)

Changes the logical name of the voltage sensor.

3. Reference

voltage→set_lowestValue(newval)

Changes the recorded minimal value observed.

voltage→set_reportFrequency(newval)

Changes the timed value notification frequency for this function.

voltage→set_resolution(newval)

Changes the resolution of the measured physical values.

voltage→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

voltage→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YVoltage.FindVoltage()**YVoltage****yFindVoltage()YVoltage.FindVoltage()**

Retrieves a voltage sensor for a given identifier.

```
def FindVoltage( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the voltage sensor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YVoltage.isOnline()` to test if the voltage sensor is indeed online at a given time. In case of ambiguity when looking for a voltage sensor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the voltage sensor

Returns :

a `YVoltage` object allowing you to drive the voltage sensor.

YVoltage.FirstVoltage() yFirstVoltage()YVoltage.FirstVoltage()

YVoltage

Starts the enumeration of voltage sensors currently accessible.

```
def FirstVoltage( )
```

Use the method `YVoltage.nextVoltage()` to iterate on next voltage sensors.

Returns :

a pointer to a `YVoltage` object, corresponding to the first voltage sensor currently online, or a null pointer if there are none.

voltage→calibrateFromPoints()
voltage.calibrateFromPoints()**YVoltage**

Configures error correction data points, in particular to compensate for a possible perturbation of the measure caused by an enclosure.

```
def calibrateFromPoints( rawValues, refValues)
```

It is possible to configure up to five correction points. Correction points must be provided in ascending order, and be in the range of the sensor. The device will automatically perform a linear interpolation of the error correction between specified points. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

For more information on advanced capabilities to refine the calibration of sensors, please contact support@yoctopuce.com.

Parameters :

rawValues array of floating point numbers, corresponding to the raw values returned by the sensor for the correction points.

refValues array of floating point numbers, corresponding to the corrected values for the correction points.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

voltage→describe()voltage.describe()**YVoltage**

Returns a short text that describes unambiguously the instance of the voltage sensor in the form
TYPE (NAME)=SERIAL . FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the voltage sensor (ex: Relay(MyCustomName.relay1)=RELAYLO1-123456.relay1)

voltage→get_advertisedValue()
voltage→advertisedValue()
voltage.get_advertisedValue()

YVoltage

Returns the current value of the voltage sensor (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the voltage sensor (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

voltage→get_currentRawValue()
voltage→currentRawValue()
voltage.get_currentRawValue()

YVoltage

Returns the uncalibrated, unrounded raw value returned by the sensor, in Volt, as a floating point number.

```
def get_currentRawValue( )
```

Returns :

a floating point number corresponding to the uncalibrated, unrounded raw value returned by the sensor, in Volt, as a floating point number

On failure, throws an exception or returns Y_CURRENTRAWVALUE_INVALID.

voltage→get_currentValue()**YVoltage****voltage→currentValue()voltage.get_currentValue()**

Returns the current value of the voltage, in Volt, as a floating point number.

```
def get_currentValue( )
```

Returns :

a floating point number corresponding to the current value of the voltage, in Volt, as a floating point number

On failure, throws an exception or returns Y_CURRENTVALUE_INVALID.

voltage→get_errorMessage() **YVoltage**
voltage→errorMessage()voltage.get_errorMessage()

Returns the error message of the latest error with the voltage sensor.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the voltage sensor object

voltage→get_errorType()**YVoltage****voltage→errorType()voltage.get_errorType()**

Returns the numerical error code of the latest error with the voltage sensor.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the voltage sensor object

voltage→get_friendlyName()	YVoltage
voltage→friendlyName()voltage.get_friendlyName()	

Returns a global identifier of the voltage sensor in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the voltage sensor if they are defined, otherwise the serial number of the module and the hardware identifier of the voltage sensor (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the voltage sensor using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

voltage→get_functionDescriptor()
voltage→functionDescriptor()
voltage.get_functionDescriptor()

YVoltage

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

voltage→get_functionId()

YVoltage

voltage→functionId()voltage.get_functionId()

Returns the hardware identifier of the voltage sensor, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the voltage sensor (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

voltage→get_hardwareId()**YVoltage****voltage→hardwareId()voltage.get_hardwareId()**

Returns the unique hardware identifier of the voltage sensor in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the voltage sensor (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the voltage sensor (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

voltage→get_highestValue()

YVoltage

voltage→highestValue()voltage.get_highestValue()

Returns the maximal value observed for the voltage since the device was started.

```
def get_highestValue( )
```

Returns :

a floating point number corresponding to the maximal value observed for the voltage since the device was started

On failure, throws an exception or returns Y_HIGHESTVALUE_INVALID.

voltage→get_logFrequency()**YVoltage****voltage→logFrequency()voltage.get_logFrequency()**

Returns the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory.

```
def get_logFrequency( )
```

Returns :

a string corresponding to the datalogger recording frequency for this function, or "OFF" when measures are not stored in the data logger flash memory

On failure, throws an exception or returns Y_LOGFREQUENCY_INVALID.

voltage→get_logicalName()

YVoltage

voltage→logicalName()voltage.get_logicalName()

Returns the logical name of the voltage sensor.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the voltage sensor.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

voltage→get_lowestValue()**YVoltage****voltage→lowestValue()voltage.get_lowestValue()**

Returns the minimal value observed for the voltage since the device was started.

```
def get_lowestValue( )
```

Returns :

a floating point number corresponding to the minimal value observed for the voltage since the device was started

On failure, throws an exception or returns Y_LOWESTVALUE_INVALID.

voltage→get_module()**YVoltage****voltage→module()voltage.get_module()**

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

voltage→get_recordedData()	YVoltage
voltage→recordedData()voltage.get_recordedData()	

Retrieves a DataSet object holding historical data for this sensor, for a specified time interval.

```
def get_recordedData( startTime, endTime)
```

The measures will be retrieved from the data logger, which must have been turned on at the desired time. See the documentation of the DataSet class for information on how to get an overview of the recorded data, and how to load progressively a large set of measures from the data logger.

This function only works if the device uses a recent firmware, as DataSet objects are not supported by firmwares older than version 13000.

Parameters :

startTime the start of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without initial limit.

endTime the end of the desired measure time interval, as a Unix timestamp, i.e. the number of seconds since January 1, 1970 UTC. The special value 0 can be used to include any measure, without ending limit.

Returns :

an instance of YDataSet, providing access to historical data. Past measures can be loaded progressively using methods from the YDataSet object.

voltage→get_reportFrequency()
voltage→reportFrequency()
voltage.get_reportFrequency()

YVoltage

Returns the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function.

```
def get_reportFrequency( )
```

Returns :

a string corresponding to the timed value notification frequency, or "OFF" if timed value notifications are disabled for this function

On failure, throws an exception or returns Y_REPORTFREQUENCY_INVALID.

voltage→get_resolution()

YVoltage

voltage→resolution()voltage.get_resolution()

Returns the resolution of the measured values.

```
def get_resolution( )
```

The resolution corresponds to the numerical precision of the measures, which is not always the same as the actual precision of the sensor.

Returns :

a floating point number corresponding to the resolution of the measured values

On failure, throws an exception or returns Y_RESOLUTION_INVALID.

voltage→get_unit()

YVoltage

voltage→unit()voltage.get_unit()

Returns the measuring unit for the voltage.

```
def get_unit( )
```

Returns :

a string corresponding to the measuring unit for the voltage

On failure, throws an exception or returns Y_UNIT_INVALID.

voltage→get(userData)**YVoltage****voltage→userData()voltage.get(userData())**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

voltage→isOnline()voltage.isOnline()**YVoltage**

Checks if the voltage sensor is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the voltage sensor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the voltage sensor.

Returns :

true if the voltage sensor can be reached, and false otherwise

voltage→load()voltage.load()**YVoltage**

Preloads the voltage sensor cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

voltage→loadCalibrationPoints()**YVoltage****voltage.loadCalibrationPoints()**

Retrieves error correction data points previously entered using the method calibrateFromPoints.

```
def loadCalibrationPoints( rawValues, refValues)
```

Parameters :

rawValues array of floating point numbers, that will be filled by the function with the raw sensor values for the correction points.

refValues array of floating point numbers, that will be filled by the function with the desired values for the correction points.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voltage→nextVoltage()voltage.nextVoltage()**YVoltage**

Continues the enumeration of voltage sensors started using `yFirstVoltage()`.

```
def nextVoltage( )
```

Returns :

a pointer to a `YVoltage` object, corresponding to a voltage sensor currently online, or a null pointer if there are no more voltage sensors to enumerate.

**voltage→registerTimedReportCallback()
voltage.registerTimedReportCallback()****YVoltage**

Registers the callback function that is invoked on every periodic timed notification.

```
def registerTimedReportCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and an `YMeasure` object describing the new advertised value.

voltage→registerValueCallback()
voltage.registerValueCallback()**YVoltage**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

voltage→set_highestValue()
voltage→setHighestValue()
voltage.set_highestValue()

YVoltage

Changes the recorded maximal value observed.

```
def set_highestValue( newval)
```

Parameters :

newval a floating point number corresponding to the recorded maximal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voltage→set_logFrequency()
voltage→setLogFrequency()
voltage.set_logFrequency()

YVoltage

Changes the datalogger recording frequency for this function.

```
def set_logFrequency( newval)
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable recording for this function, use the value "OFF".

Parameters :

newval a string corresponding to the datalogger recording frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voltage→set_logicalName()	YVoltage
voltage→setLogicalName()voltage.set_logicalName()	

Changes the logical name of the voltage sensor.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the voltage sensor.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

voltage→set_lowestValue()	YVoltage
voltage→setLowestValue()voltage.set_lowestValue()	

Changes the recorded minimal value observed.

```
def set_lowestValue( newval )
```

Parameters :

newval a floating point number corresponding to the recorded minimal value observed

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voltage→set_reportFrequency()
voltage→setReportFrequency()
voltage.set_reportFrequency()

YVoltage

Changes the timed value notification frequency for this function.

```
def set_reportFrequency( newval )
```

The frequency can be specified as samples per second, as sample per minute (for instance "15/m") or in samples per hour (eg. "4/h"). To disable timed value notifications for this function, use the value "OFF".

Parameters :

newval a string corresponding to the timed value notification frequency for this function

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voltage→set_resolution()**YVoltage****voltage→setResolution()voltage.set_resolution()**

Changes the resolution of the measured physical values.

```
def set_resolution( newval )
```

The resolution corresponds to the numerical precision when displaying value. It does not change the precision of the measure itself.

Parameters :

newval a floating point number corresponding to the resolution of the measured physical values

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

voltage→set(userData)

YVoltage

voltage→setUserData()|voltage.set(userData())

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.46. Voltage source function interface

Yoctopuce application programming interface allows you to control the module voltage output. You affect absolute output values or make transitions

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_vsource.js'></script>
php	require_once('yocto_vsource.php');
cpp	#include "yocto_vsource.h"
m	#import "yocto_vsource.h"
pas	uses yocto_vsource;
vb	yocto_vsource.vb
cs	yocto_vsource.cs
java	import com.yoctopuce.YoctoAPI.YVSource;
py	from yocto_vsource import *

Global functions

yFindVSource(func)

Retrieves a voltage source for a given identifier.

yFirstVSource()

Starts the enumeration of voltage sources currently accessible.

YVSource methods

vsource→describe()

Returns a short text that describes the function in the form TYPE (NAME) = SERIAL . FUNCTIONID.

vsource→get_advertisedValue()

Returns the current value of the voltage source (no more than 6 characters).

vsource→get_errorMessage()

Returns the error message of the latest error with this function.

vsource→get_errorType()

Returns the numerical error code of the latest error with this function.

vsource→get_extPowerFailure()

Returns true if external power supply voltage is too low.

vsource→get_failure()

Returns true if the module is in failure mode.

vsource→get_friendlyName()

Returns a global identifier of the function in the format MODULE_NAME . FUNCTION_NAME.

vsource→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

vsource→get_functionId()

Returns the hardware identifier of the function, without reference to the module.

vsource→get_hardwareId()

Returns the unique hardware identifier of the function in the form SERIAL . FUNCTIONID.

vsource→get_logicalName()

Returns the logical name of the voltage source.

vsource→get_module()

Gets the YModule object for the device on which the function is located.

vsource→get_module_async(callback, context)

3. Reference

Gets the YModule object for the device on which the function is located (asynchronous version).

vsouce→get_overCurrent()

Returns true if the appliance connected to the device is too greedy .

vsouce→get_overHeat()

Returns TRUE if the module is overheating.

vsouce→get_overLoad()

Returns true if the device is not able to maintain the requested voltage output .

vsouce→get_regulationFailure()

Returns true if the voltage output is too high regarding the requested voltage .

vsouce→get_unit()

Returns the measuring unit for the voltage.

vsouce→get_userData()

Returns the value of the userData attribute, as previously stored using method set(userData).

vsouce→get_voltage()

Returns the voltage output command (mV)

vsouce→isOnline()

Checks if the function is currently reachable, without raising any error.

vsouce→isOnline_async(callback, context)

Checks if the function is currently reachable, without raising any error (asynchronous version).

vsouce→load(msValidity)

Preloads the function cache with a specified validity duration.

vsouce→load_async(msValidity, callback, context)

Preloads the function cache with a specified validity duration (asynchronous version).

vsouce→nextVSource()

Continues the enumeration of voltage sources started using yFirstVSource().

vsouce→pulse(voltage, ms_duration)

Sets device output to a specific volatage, for a specified duration, then brings it automatically to 0V.

vsouce→registerValueCallback(callback)

Registers the callback function that is invoked on every change of advertised value.

vsouce→set_logicalName(newval)

Changes the logical name of the voltage source.

vsouce→set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

vsouce→set_voltage(newval)

Tunes the device output voltage (milliVolts).

vsouce→voltageMove(target, ms_duration)

Performs a smooth move at constant speed toward a given value.

vsouce→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

yFindVSource() —**YVSource****YVSource.FindVSource()YVSource.FindVSource()**

Retrieves a voltage source for a given identifier.

```
def FindVSource( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the voltage source is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YVSource.isOnline()` to test if the voltage source is indeed online at a given time. In case of ambiguity when looking for a voltage source by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the voltage source

Returns :

a `YVSource` object allowing you to drive the voltage source.

yFirstVSource() —

YVSource

YVSource.FirstVSource()YVSource.FirstVSource()

Starts the enumeration of voltage sources currently accessible.

```
def FirstVSource( )
```

Use the method `YVSource.nextVSource()` to iterate on next voltage sources.

Returns :

a pointer to a `YVSource` object, corresponding to the first voltage source currently online, or a null pointer if there are none.

vsource→get_advertisedValue()
vsource→advertisedValue()
vsource.get_advertisedValue()

YVSource

Returns the current value of the voltage source (no more than 6 characters).

def get_advertisedValue()

vsource→get_advertisedValue()
vsource→advertisedValue()vsource.get_advertisedValue()

Returns the current value of the voltage source (no more than 6 characters).

js	function get_advertisedValue()
php	function get_advertisedValue()
cpp	string get_advertisedValue()
m	-(NSString*) advertisedValue
pas	function get_advertisedValue() : string
vb	function get_advertisedValue() As String
cs	string get_advertisedValue()
java	String get_advertisedValue()
py	def get_advertisedValue()
cmd	YVSource target get_advertisedValue

Returns :

a string corresponding to the current value of the voltage source (no more than 6 characters)

On failure, throws an exception or returns **Y_ADVERTISEDVALUE_INVALID**.

vsouce→get_errorMessage()
vsouce→errorMessage()
vsouce.get_errorMessage()

YVSource

Returns the error message of the latest error with this function.

def get_errorMessage()

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occured while using this function object

vsource→get_errorType()**YVSource****vsource→errorType()vsource.get_errorType()**

Returns the numerical error code of the latest error with this function.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using this function object

vsouce→get_extPowerFailure()
vsouce→extPowerFailure()
vsouce.get_extPowerFailure()

YVSource

Returns true if external power supply voltage is too low.

def get_extPowerFailure()

vsouce→get_extPowerFailure()
vsouce→extPowerFailure()vsouce.get_extPowerFailure()

Returns true if external power supply voltage is too low.

js function get_extPowerFailure()
php function get_extPowerFailure()
cpp Y_EXTPOWERFAILURE_enum get_extPowerFailure()
m -(Y_EXTPOWERFAILURE_enum) extPowerFailure
pas function get_extPowerFailure(): Integer
vb function get_extPowerFailure() As Integer
cs int get_extPowerFailure()
java int get_extPowerFailure()
py def get_extPowerFailure()
cmd YVSource target get_extPowerFailure

Returns :

either Y_EXTPOWERFAILURE_FALSE or Y_EXTPOWERFAILURE_TRUE, according to true if external power supply voltage is too low

On failure, throws an exception or returns Y_EXTPOWERFAILURE_INVALID.

vsource→get_failure()
vsource→failure()vsource.get_failure()

YVSource

Returns true if the module is in failure mode.

```
def get_failure( )
```

vsource→get_failure()
vsource→failure()vsource.get_failure()

Returns true if the module is in failure mode.

```
js function get_failure( )
php function get_failure( )
cpp Y_FAILURE_enum get_failure( )
m -(Y_FAILURE_enum) failure
pas function get_failure( ): Integer
vb function get_failure( ) As Integer
cs int get_failure( )
java int get_failure( )
py def get_failure( )
cmd YVSource target get_failure
```

More information can be obtained by testing get_overheat, get_overcurrent etc... When a error condition is met, the output voltage is set to zero and cannot be changed until the reset() function is called.

Returns :

either Y_FAILURE_FALSE or Y_FAILURE_TRUE, according to true if the module is in failure mode

On failure, throws an exception or returns Y_FAILURE_INVALID.

vsources->get_functionDescriptor()	YVSource
vsources->functionDescriptor()	
vsources.get_vsourcDescriptor()	

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR. If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

vsource→get_logicalName()**YVSource****vsource→logicalName()vsource.get_logicalName()**

Returns the logical name of the voltage source.

```
def get_logicalName( )
```

vsource→get_logicalName()**vsource→logicalName()vsource.get_logicalName()**

Returns the logical name of the voltage source.

```
js function get_logicalName( )
php function get_logicalName( )
cpp string get_logicalName( )
m -(NSString*) logicalName
pas function get_logicalName( ): string
vb function get_logicalName( ) As String
cs string get_logicalName( )
java String get_logicalName( )
py def get_logicalName( )
cmd YVSource target get_logicalName
```

Returns :

a string corresponding to the logical name of the voltage source

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

vsouce→get_module()

YVSource

vsouce→module()vsouce.get_module()

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

vsource→get_overCurrent()**YVSource****vsource→overCurrent()vsource.get_overCurrent()**

Returns true if the appliance connected to the device is too greedy .

```
def get_overCurrent( )
```

vsource→get_overCurrent()**vsource→overCurrent()vsource.get_overCurrent()**

Returns true if the appliance connected to the device is too greedy .

```
js function get_overCurrent( )
php function get_overCurrent( )
cpp Y_OVERCURRENT_enum get_overCurrent( )
m -(Y_OVERCURRENT_enum) overCurrent
pas function get_overCurrent( ): Integer
vb function get_overCurrent( ) As Integer
cs int get_overCurrent( )
java int get_overCurrent( )
py def get_overCurrent( )
cmd YVSource target get_overCurrent
```

Returns :

either Y_OVERCURRENT_FALSE or Y_OVERCURRENT_TRUE, according to true if the appliance connected to the device is too greedy

On failure, throws an exception or returns Y_OVERCURRENT_INVALID.

vsouce→get_overHeat() YVSource
vsouce→overHeat()vsouce.get_overHeat()

Returns TRUE if the module is overheating.

```
def get_overHeat( )
```

vsouce→get_overHeat()
vsouce→overHeat()vsouce.get_overHeat()

Returns TRUE if the module is overheating.

```
js   function get_overHeat( )
php  function get_overHeat( )
cpp  Y_OVERHEAT_enum get_overHeat( )
m    -(Y_OVERHEAT_enum) overHeat
pas   function get_overHeat( ): Integer
vb    function get_overHeat( ) As Integer
cs    int get_overHeat( )
java  int get_overHeat( )
py    def get_overHeat( )
cmd   YVSource target get_overHeat
```

Returns :

either Y_OVERHEAT_FALSE or Y_OVERHEAT_TRUE, according to TRUE if the module is overheating

On failure, throws an exception or returns Y_OVERHEAT_INVALID.

vsource→get_overLoad()**YVSource****vsource→overLoad()vsource.get_overLoad()**

Returns true if the device is not able to maintain the requested voltage output .

```
def get_overLoad( )
```

vsource→get_overLoad()**vsource→overLoad()vsource.get_overLoad()**

Returns true if the device is not able to maintain the requested voltage output .

```
js function get_overLoad( )
php function get_overLoad( )
cpp Y_OVERLOAD_enum get_overLoad( )
m -(Y_OVERLOAD_enum) overLoad
pas function get_overLoad( ): Integer
vb function get_overLoad( ) As Integer
cs int get_overLoad( )
java int get_overLoad( )
py def get_overLoad( )
cmd YVSource target get_overLoad
```

Returns :

either Y_OVERLOAD_FALSE or Y_OVERLOAD_TRUE, according to true if the device is not able to maintain the requested voltage output

On failure, throws an exception or returns Y_OVERLOAD_INVALID.

vsOURCE→get_regulationFailure()	YVSource
vsOURCE→regulationFailure()	
vsOURCE.get_regulationFailure()	

Returns true if the voltage output is too high regarding the requested voltage .

```
def get_regulationFailure( )
```

vsOURCE→get_regulationFailure()
vsOURCE→regulationFailure()vsOURCE.get_regulationFailure()

Returns true if the voltage output is too high regarding the requested voltage .

js	function get_regulationFailure()
php	function get_regulationFailure()
cpp	Y_REGULATIONFAILURE_enum get_regulationFailure()
m	-(Y_REGULATIONFAILURE_enum) regulationFailure
pas	function get_regulationFailure(): Integer
vb	function get_regulationFailure() As Integer
cs	int get_regulationFailure()
java	int get_regulationFailure()
py	def get_regulationFailure()
cmd	YVSource target get_regulationFailure

Returns :

either Y_REGULATIONFAILURE_FALSE or Y_REGULATIONFAILURE_TRUE, according to true if the voltage output is too high regarding the requested voltage

On failure, throws an exception or returns Y_REGULATIONFAILURE_INVALID.

vsource→get_unit()**YVSource****vsource→unit()vsource.get_unit()**

Returns the measuring unit for the voltage.

```
def get_unit( )
```

vsource→get_unit()**vsource→unit()vsource.get_unit()**

Returns the measuring unit for the voltage.

```
js   function get_unit( )
php  function get_unit( )
cpp  string get_unit( )
m    -(NSString*) unit
pas   function get_unit( ): string
vb    function get_unit( ) As String
cs    string get_unit( )
java  String get_unit( )
py    def get_unit( )
cmd   YVSource target get_unit
```

Returns :

a string corresponding to the measuring unit for the voltage

On failure, throws an exception or returns Y_UNIT_INVALID.

vsouce→get(userData)

YVSource

vsouce→userData()vsouce.get(userData)

Returns the value of the userData attribute, as previously stored using method set(userData).

def get(userData)

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

vsource→get_voltage()**YVSource****vsource→voltage()vsource.get_voltage()**

Returns the voltage output command (mV)

```
def get_voltage( )
```

Returns :

an integer corresponding to the voltage output command (mV)

On failure, throws an exception or returns Y_VOLTAGE_INVALID.

vsource→isOnline()vsource.isOnline()**YVSource**

Checks if the function is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the function in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the requested function.

Returns :

`true` if the function can be reached, and `false` otherwise

vsource→load()vsource.load()**YVSource**

Preloads the function cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds. On failure, throws an exception or returns a negative error code.

vsource→nextVSource()vsource.nextVSource()

YVSource

Continues the enumeration of voltage sources started using `yFirstVSource()`.

```
def nextVSource( )
```

Returns :

a pointer to a `YVSource` object, corresponding to a voltage source currently online, or a `null` pointer if there are no more voltage sources to enumerate.

vsource→pulse()**YVSource**

Sets device output to a specific voltage, for a specified duration, then brings it automatically to 0V.

```
def pulse( voltage, ms_duration)
```

vsource→pulse()

Sets device output to a specific voltage, for a specified duration, then brings it automatically to 0V.

js	function pulse(voltage, ms_duration)
php	function pulse(\$voltage, \$ms_duration)
cpp	int pulse(int voltage, int ms_duration)
m	-(int) pulse : (int) voltage : (int) ms_duration
pas	function pulse(voltage: integer, ms_duration: integer): integer
vb	function pulse(ByVal voltage As Integer, ByVal ms_duration As Integer) As Integer
cs	int pulse(int voltage, int ms_duration)
java	int pulse(int voltage, int ms_duration)
py	def pulse(voltage, ms_duration)
cmd	YVSource target pulse voltage ms_duration

Parameters :

voltage pulse voltage, in millivolts

ms_duration pulse duration, in milliseconds

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

**vsouce→registerValueCallback()
vsouce.registerValueCallback()****YVSource**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

vsouce→registerValueCallback()vsouce.registerValueCallback()

Registers the callback function that is invoked on every change of advertised value.

```
js   function registerValueCallback( callback)
php  function registerValueCallback( $callback)
cpp  void registerValueCallback( YDisplayUpdateCallback callback)
pas   procedure registerValueCallback( callback: TGenericUpdateCallback)
vb    procedure registerValueCallback( ByVal callback As GenericUpdateCallback)
cs    void registerValueCallback( UpdateCallback callback)
java  void registerValueCallback( UpdateCallback callback)
py    def registerValueCallback( callback)
m     -(void) registerValueCallback : (YFunctionUpdateCallback) callback
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

vsource→set_logicalName()
vsource→setLogicalName()
vsource.set_logicalName()

YVSource

Changes the logical name of the voltage source.

def **set_logicalName(newval)**

vsource→set_logicalName()
vsource→setLogicalName()vsource.set_logicalName()

Changes the logical name of the voltage source.

js	function set_logicalName(newval)
php	function set_logicalName(\$newval)
cpp	int set_logicalName(const string& newval)
m	-(int) setLogicalName : (NSString*) newval
pas	function set_logicalName(newval: string): integer
vb	function set_logicalName(ByVal newval As String) As Integer
cs	int set_logicalName(string newval)
java	int set_logicalName(String newval)
py	def set_logicalName(newval)
cmd	YVSource target set_logicalName newval

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the voltage source

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

vsource→set(userData)

YVSource

vsource→setUserData()|vsource.set(userData)

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

vsouce→set_voltage()**YVSource****vsouce→setVoltage()vsouce.set_voltage()**

Tunes the device output voltage (milliVolts).

```
def set_voltage( newval)
```

vsouce→set_voltage()**vsouce→setVoltage()vsouce.set_voltage()**

Tunes the device output voltage (milliVolts).

```
[js] function set_voltage( newval)
```

```
[php] function set_voltage( $newval)
```

```
[cpp] int set_voltage( int newval)
```

```
[m] -(int) setVoltage : (int) newval
```

```
[pas] function set_voltage( newval: LongInt): integer
```

```
[vb] function set_voltage( ByVal newval As Integer) As Integer
```

```
[cs] int set_voltage( int newval)
```

```
[java] int set_voltage( int newval)
```

```
[py] def set_voltage( newval)
```

```
[cmd] YVSource target set_voltage newval
```

Parameters :

newval an integer

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

vsOURCE→voltageMove()vsOURCE.voltageMove()**YVSource**

Performs a smooth move at constant speed toward a given value.

```
def voltageMove( target, ms_duration)
```

vsOURCE→voltageMove()vsOURCE.voltageMove()

Performs a smooth move at constant speed toward a given value.

<code>js</code>	<code>function voltageMove(target, ms_duration)</code>
<code>php</code>	<code>function voltageMove(\$target, \$ms_duration)</code>
<code>cpp</code>	<code>int voltageMove(int target, int ms_duration)</code>
<code>m</code>	<code>-(int) voltageMove : (int) target : (int) ms_duration</code>
<code>pas</code>	<code>function voltageMove(target: integer, ms_duration: integer): integer</code>
<code>vb</code>	<code>function voltageMove(ByVal target As Integer,</code> <code> ByVal ms_duration As Integer) As Integer</code>
<code>cs</code>	<code>int voltageMove(int target, int ms_duration)</code>
<code>java</code>	<code>int voltageMove(int target, int ms_duration)</code>
<code>py</code>	<code>def voltageMove(target, ms_duration)</code>
<code>cmd</code>	<code>YVSource target voltageMove target ms_duration</code>

Parameters :

target new output value at end of transition, in milliVolts.

ms_duration transition duration, in milliseconds

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

3.47. WakeUpMonitor function interface

The WakeUpMonitor function handles globally all wake-up sources, as well as automated sleep mode.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_wakeupmonitor.js'></script>
node.js	var yoctolib = require('yoctolib');
	var YWakeUpMonitor = yoctolib.YWakeUpMonitor;
php	require_once('yocto_wakeupmonitor.php');
cpp	#include "yocto_wakeupmonitor.h"
m	#import "yocto_wakeupmonitor.h"
pas	uses yocto_wakeupmonitor;
vb	yocto_wakeupmonitor.vb
cs	yocto_wakeupmonitor.cs
java	import com.yoctopuce.YoctoAPI.YWakeUpMonitor;
py	from yocto_wakeupmonitor import *

Global functions

yFindWakeUpMonitor(func)

Retrieves a monitor for a given identifier.

yFirstWakeUpMonitor()

Starts the enumeration of monitors currently accessible.

YWakeUpMonitor methods

wakeupmonitor→describe()

Returns a short text that describes unambiguously the instance of the monitor in the form
TYPE (NAME)=SERIAL . FUNCTIONID.

wakeupmonitor→get_advertisedValue()

Returns the current value of the monitor (no more than 6 characters).

wakeupmonitor→get_errorMessage()

Returns the error message of the latest error with the monitor.

wakeupmonitor→get_errorType()

Returns the numerical error code of the latest error with the monitor.

wakeupmonitor→get_friendlyName()

Returns a global identifier of the monitor in the format MODULE_NAME . FUNCTION_NAME.

wakeupmonitor→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

wakeupmonitor→get_functionId()

Returns the hardware identifier of the monitor, without reference to the module.

wakeupmonitor→get_hardwareId()

Returns the unique hardware identifier of the monitor in the form SERIAL . FUNCTIONID.

wakeupmonitor→get_logicalName()

Returns the logical name of the monitor.

wakeupmonitor→get_module()

Gets the YModule object for the device on which the function is located.

wakeupmonitor→get_module_async(callback, context)

Gets the YModule object for the device on which the function is located (asynchronous version).

wakeupmonitor→get_nextWakeUp()

Returns the next scheduled wake up date/time (UNIX format)
wakeupmonitor→get_powerDuration()
Returns the maximal wake up time (in seconds) before automatically going to sleep.
wakeupmonitor→get_sleepCountdown()
Returns the delay before the next sleep period.
wakeupmonitor→get(userData)
Returns the value of the userData attribute, as previously stored using method <code>set(userData)</code> .
wakeupmonitor→get_wakeUpReason()
Returns the latest wake up reason.
wakeupmonitor→get_wakeUpState()
Returns the current state of the monitor
wakeupmonitor→isOnline()
Checks if the monitor is currently reachable, without raising any error.
wakeupmonitor→isOnline_async(callback, context)
Checks if the monitor is currently reachable, without raising any error (asynchronous version).
wakeupmonitor→load(msValidity)
Preloads the monitor cache with a specified validity duration.
wakeupmonitor→load_async(msValidity, callback, context)
Preloads the monitor cache with a specified validity duration (asynchronous version).
wakeupmonitor→nextWakeUpMonitor()
Continues the enumeration of monitors started using <code>yFirstWakeUpMonitor()</code> .
wakeupmonitor→registerValueCallback(callback)
Registers the callback function that is invoked on every change of advertised value.
wakeupmonitor→resetSleepCountDown()
Resets the sleep countdown.
wakeupmonitor→set_logicalName(newval)
Changes the logical name of the monitor.
wakeupmonitor→set_nextWakeUp(newval)
Changes the days of the week when a wake up must take place.
wakeupmonitor→set_powerDuration(newval)
Changes the maximal wake up time (seconds) before automatically going to sleep.
wakeupmonitor→set_sleepCountdown(newval)
Changes the delay before the next sleep period.
wakeupmonitor→set(userData)
Stores a user context provided as argument in the userData attribute of the function.
wakeupmonitor→sleep(secBeforeSleep)
Goes to sleep until the next wake up condition is met, the RTC time must have been set before calling this function.
wakeupmonitor→sleepFor(secUntilWakeUp, secBeforeSleep)
Goes to sleep for a specific duration or until the next wake up condition is met, the RTC time must have been set before calling this function.
wakeupmonitor→sleepUntil(wakeUpTime, secBeforeSleep)
Go to sleep until a specific date is reached or until the next wake up condition is met, the RTC time must have been set before calling this function.
wakeupmonitor→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

wakeupmonitor→wakeUp()

Forces a wake up.

YWakeUpMonitor.FindWakeUpMonitor() yFindWakeUpMonitor() YWakeUpMonitor.FindWakeUpMonitor()

YWakeUpMonitor

Retrieves a monitor for a given identifier.

```
def FindWakeUpMonitor( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the monitor is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YWakeUpMonitor.isOnline()` to test if the monitor is indeed online at a given time. In case of ambiguity when looking for a monitor by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the monitor

Returns :

a `YWakeUpMonitor` object allowing you to drive the monitor.

YWakeUpMonitor.FirstWakeUpMonitor()
yFirstWakeUpMonitor()
YWakeUpMonitor.FirstWakeUpMonitor()

YWakeUpMonitor

Starts the enumeration of monitors currently accessible.

```
def FirstWakeUpMonitor( )
```

Use the method `YWakeUpMonitor.nextWakeUpMonitor()` to iterate on next monitors.

Returns :

a pointer to a `YWakeUpMonitor` object, corresponding to the first monitor currently online, or a null pointer if there are none.

wakeupmonitor→describe()
wakeupmonitor.describe()**YWakeUpMonitor**

Returns a short text that describes unambiguously the instance of the monitor in the form
TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the monitor (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

wakeupmonitor→get_advertisedValue()
wakeupmonitor→advertisedValue()
wakeupmonitor.get_advertisedValue()**YWakeUpMonitor**

Returns the current value of the monitor (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the monitor (no more than 6 characters).

On failure, throws an exception or returns `Y_ADVERTISEDVALUE_INVALID`.

wakeupmonitor→get_errorMessage()
wakeupmonitor→errorMessage()
wakeupmonitor.get_errorMessage()

YWakeUpMonitor

Returns the error message of the latest error with the monitor.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the monitor object

wakeupmonitor→get_errorType()**YWakeUpMonitor****wakeupmonitor→errorType()****wakeupmonitor.get_errorType()**

Returns the numerical error code of the latest error with the monitor.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the monitor object

wakeupmonitor→get_friendlyName()
wakeupmonitor→friendlyName()
wakeupmonitor.get_friendlyName()

YWakeUpMonitor

Returns a global identifier of the monitor in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the monitor if they are defined, otherwise the serial number of the module and the hardware identifier of the monitor (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the monitor using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

wakeupmonitor→get_functionDescriptor()
wakeupmonitor→functionDescriptor()
wakeupmonitor.get_functionDescriptor()

YWakeUpMonitor

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

wakeupmonitor→get_functionId()
wakeupmonitor→functionId()
wakeupmonitor.get_functionId()

YWakeUpMonitor

Returns the hardware identifier of the monitor, without reference to the module.

```
def get_functionId( )
```

For example relay1

Returns :

a string that identifies the monitor (ex: relay1)

On failure, throws an exception or returns Y_FUNCTIONID_INVALID.

wakeupmonitor→get_hardwareId()
wakeupmonitor→hardwareId()
wakeupmonitor.get_hardwareId()

YWakeUpMonitor

Returns the unique hardware identifier of the monitor in the form SERIAL.FUNCTIONID.

def get_hardwareId()

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the monitor (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the monitor (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

wakeupmonitor→get_logicalName()
wakeupmonitor→logicalName()
wakeupmonitor.get_logicalName()

YWakeUpMonitor

Returns the logical name of the monitor.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the monitor.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

wakeupmonitor→get_module()
wakeupmonitor→module()
wakeupmonitor.get_module()**YWakeUpMonitor**

Gets the **YModule** object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of **YModule** is not shown as online.

Returns :

an instance of **YModule**

wakeupmonitor→get_nextWakeUp()
wakeupmonitor→nextWakeUp()
wakeupmonitor.get_nextWakeUp()

YWakeUpMonitor

Returns the next scheduled wake up date/time (UNIX format)

```
def get_nextWakeUp( )
```

Returns :

an integer corresponding to the next scheduled wake up date/time (UNIX format)

On failure, throws an exception or returns Y_NEXTWAKEUP_INVALID.

wakeupmonitor→get_powerDuration()

YWakeUpMonitor

wakeupmonitor→powerDuration()

wakeupmonitor.get_powerDuration()

Returns the maximal wake up time (in seconds) before automatically going to sleep.

```
def get_powerDuration( )
```

Returns :

an integer corresponding to the maximal wake up time (in seconds) before automatically going to sleep

On failure, throws an exception or returns Y_POWERDURATION_INVALID.

wakeupmonitor→get_sleepCountdown()
wakeupmonitor→sleepCountdown()
wakeupmonitor.get_sleepCountdown()

YWakeUpMonitor

Returns the delay before the next sleep period.

```
def get_sleepCountdown( )
```

Returns :

an integer corresponding to the delay before the next sleep period

On failure, throws an exception or returns Y_SLEEPCOUNTDOWN_INVALID.

wakeupmonitor→get(userData)
wakeupmonitor→userData()
wakeupmonitor.get(userData)

YWakeUpMonitor

Returns the value of the userData attribute, as previously stored using method setUserData.

```
def get.userData( )
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

wakeupmonitor→get_wakeUpReason()
wakeupmonitor→wakeUpReason()
wakeupmonitor.get_wakeUpReason()

YWakeUpMonitor

Returns the latest wake up reason.

```
def get_wakeUpReason( )
```

Returns :

a value among Y_WAKEUPREASON_USBPOWER, Y_WAKEUPREASON_EXTPOWER,
Y_WAKEUPREASON_ENDOFSLEEP, Y_WAKEUPREASON_EXTSIG1,
Y_WAKEUPREASON_SCHEDULE1 and Y_WAKEUPREASON_SCHEDULE2 corresponding to the
latest wake up reason

On failure, throws an exception or returns Y_WAKEUPREASON_INVALID.

wakeupmonitor→get_wakeUpState()
wakeupmonitor→wakeUpState()
wakeupmonitor.get_wakeUpState()

YWakeUpMonitor

Returns the current state of the monitor

```
def get_wakeUpState( )
```

Returns :

either `Y_WAKEUPSTATE_SLEEPING` or `Y_WAKEUPSTATE_AWAKE`, according to the current state of the monitor

On failure, throws an exception or returns `Y_WAKEUPSTATE_INVALID`.

wakeupmonitor→isOnline()wakeupmonitor.isOnline()

YWakeUpMonitor

Checks if the monitor is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the monitor in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the monitor.

Returns :

true if the monitor can be reached, and false otherwise

wakeupmonitor→load()wakeupmonitor.load()**YWakeUpMonitor**

Preloads the monitor cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupmonitor→nextWakeUpMonitor()
wakeupmonitor.nextWakeUpMonitor()

YWakeUpMonitor

Continues the enumeration of monitors started using `yFirstWakeUpMonitor()`.

```
def nextWakeUpMonitor( )
```

Returns :

a pointer to a `YWakeUpMonitor` object, corresponding to a monitor currently online, or a `null` pointer if there are no more monitors to enumerate.

**wakeupmonitor→registerValueCallback()
wakeupmonitor.registerValueCallback()****YWakeUpMonitor**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

wakeupmonitor→resetSleepCountDown()
wakeupmonitor.resetSleepCountDown()

YWakeUpMonitor

Resets the sleep countdown.

```
def resetSleepCountDown( )
```

Returns :

YAPI_SUCCESS if the call succeeds. On failure, throws an exception or returns a negative error code.

wakeupmonitor→set_logicalName()
wakeupmonitor→setLogicalName()
wakeupmonitor.set_logicalName()

YWakeUpMonitor

Changes the logical name of the monitor.

```
def set_logicalName( newval)
```

You can use yCheckLogicalName() prior to this call to make sure that your parameter is valid. Remember to call the saveToFlash() method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the monitor.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupmonitor→set_nextWakeUp()
wakeupmonitor→setNextWakeUp()
wakeupmonitor.set_nextWakeUp()

YWakeUpMonitor

Changes the days of the week when a wake up must take place.

```
def set_nextWakeUp( newval)
```

Parameters :

newval an integer corresponding to the days of the week when a wake up must take place

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupmonitor→set_powerDuration()
wakeupmonitor→setPowerDuration()
wakeupmonitor.set_powerDuration()

YWakeUpMonitor

Changes the maximal wake up time (seconds) before automatically going to sleep.

```
def set_powerDuration( newval)
```

Parameters :

newval an integer corresponding to the maximal wake up time (seconds) before automatically going to sleep

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupmonitor→set_sleepCountdown()
wakeupmonitor→setSleepCountdown()
wakeupmonitor.set_sleepCountdown()

YWakeUpMonitor

Changes the delay before the next sleep period.

```
def set_sleepCountdown( newval )
```

Parameters :

newval an integer corresponding to the delay before the next sleep period

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupmonitor→**set(userData)**
wakeupmonitor→**setUserData()**
wakeupmonitor.set(userData)

YWakeUpMonitor

Stores a user context provided as argument in the userData attribute of the function.

```
def setUserData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

wakeupmonitor→sleep()wakeupmonitor.sleep()**YWakeUpMonitor**

Goes to sleep until the next wake up condition is met, the RTC time must have been set before calling this function.

```
def sleep( secBeforeSleep)
```

Parameters :

secBeforeSleep number of seconds before going into sleep mode,

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

**wakeupmonitor→sleepFor()
wakeupmonitor.sleepFor()****YWakeUpMonitor**

Goes to sleep for a specific duration or until the next wake up condition is met, the RTC time must have been set before calling this function.

```
def sleepFor( secUntilWakeUp, secBeforeSleep)
```

The count down before sleep can be canceled with resetSleepCountDown.

Parameters :

secUntilWakeUp number of seconds before next wake up

secBeforeSleep number of seconds before going into sleep mode

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupmonitor→sleepUntil()
wakeupmonitor.sleepUntil()**YWakeUpMonitor**

Go to sleep until a specific date is reached or until the next wake up condition is met, the RTC time must have been set before calling this function.

```
def sleepUntil( wakeUpTime, secBeforeSleep)
```

The count down before sleep can be canceled with resetSleepCountDown.

Parameters :

wakeUpTime wake-up datetime (UNIX format)
secBeforeSleep number of seconds before going into sleep mode

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupmonitor→wakeUp()**YWakeUpMonitor**

Forces a wake up.

```
def wakeUp( )
```

3.48. WakeUpSchedule function interface

The WakeUpSchedule function implements a wake up condition. The wake up time is specified as a set of months and/or days and/or hours and/or minutes when the wake up should happen.

In order to use the functions described here, you should include:

```

js <script type='text/javascript' src='yocto_wakeupschedule.js'></script>
nodejs var yoctolib = require('yoctolib');
var YWakeUpSchedule = yoctolib.YWakeUpSchedule;
php require_once('yocto_wakeupschedule.php');
cpp #include "yocto_wakeupschedule.h"
m #import "yocto_wakeupschedule.h"
pas uses yocto_wakeupschedule;
vb yocto_wakeupschedule.vb
cs yocto_wakeupschedule.cs
java import com.yoctopuce.YoctoAPI.YWakeUpSchedule;
py from yocto_wakeupschedule import *

```

Global functions

yFindWakeUpSchedule(func)

Retrieves a wake up schedule for a given identifier.

yFirstWakeUpSchedule()

Starts the enumeration of wake up schedules currently accessible.

YWakeUpSchedule methods

wakeupschedule→describe()

Returns a short text that describes unambiguously the instance of the wake up schedule in the form
TYPE (NAME) = SERIAL . FUNCTIONID.

wakeupschedule→get_advertisedValue()

Returns the current value of the wake up schedule (no more than 6 characters).

wakeupschedule→get_errorMessage()

Returns the error message of the latest error with the wake up schedule.

wakeupschedule→get_errorType()

Returns the numerical error code of the latest error with the wake up schedule.

wakeupschedule→get_friendlyName()

Returns a global identifier of the wake up schedule in the format MODULE_NAME . FUNCTION_NAME.

wakeupschedule→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

wakeupschedule→get_functionId()

Returns the hardware identifier of the wake up schedule, without reference to the module.

wakeupschedule→get_hardwareId()

Returns the unique hardware identifier of the wake up schedule in the form SERIAL . FUNCTIONID.

wakeupschedule→get_hours()

Returns the hours scheduled for wake up.

wakeupschedule→get_logicalName()

Returns the logical name of the wake up schedule.

wakeupschedule→get_minutes()

Returns all the minutes of each hour that are scheduled for wake up.

wakeupschedule→get_minutesA()

Returns the minutes in the 00-29 interval of each hour scheduled for wake up.
wakeupschedule→get_minutesB()
Returns the minutes in the 30-59 interval of each hour scheduled for wake up.
wakeupschedule→get_module()
Gets the YModule object for the device on which the function is located.
wakeupschedule→get_module_async(callback, context)
Gets the YModule object for the device on which the function is located (asynchronous version).
wakeupschedule→get_monthDays()
Returns the days of the month scheduled for wake up.
wakeupschedule→get_months()
Returns the months scheduled for wake up.
wakeupschedule→get_nextOccurrence()
Returns the date/time (seconds) of the next wake up occurrence
wakeupschedule→get_userData()
Returns the value of the userData attribute, as previously stored using method set(userData).
wakeupschedule→get_weekDays()
Returns the days of the week scheduled for wake up.
wakeupschedule→isOnline()
Checks if the wake up schedule is currently reachable, without raising any error.
wakeupschedule→isOnline_async(callback, context)
Checks if the wake up schedule is currently reachable, without raising any error (asynchronous version).
wakeupschedule→load(msValidity)
Preloads the wake up schedule cache with a specified validity duration.
wakeupschedule→load_async(msValidity, callback, context)
Preloads the wake up schedule cache with a specified validity duration (asynchronous version).
wakeupschedule→nextWakeUpSchedule()
Continues the enumeration of wake up schedules started using yFirstWakeUpSchedule().
wakeupschedule→registerValueCallback(callback)
Registers the callback function that is invoked on every change of advertised value.
wakeupschedule→set_hours(newval)
Changes the hours when a wake up must take place.
wakeupschedule→set_logicalName(newval)
Changes the logical name of the wake up schedule.
wakeupschedule→set_minutes(bitmap)
Changes all the minutes where a wake up must take place.
wakeupschedule→set_minutesA(newval)
Changes the minutes in the 00-29 interval when a wake up must take place.
wakeupschedule→set_minutesB(newval)
Changes the minutes in the 30-59 interval when a wake up must take place.
wakeupschedule→set_monthDays(newval)
Changes the days of the month when a wake up must take place.
wakeupschedule→set_months(newval)
Changes the months when a wake up must take place.
wakeupschedule→set_userData(data)
Stores a user context provided as argument in the userData attribute of the function.

3. Reference

wakeupschedule→set_weekDays(newval)

Changes the days of the week when a wake up must take place.

wakeupschedule→wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YWakeUpSchedule.FindWakeUpSchedule() yFindWakeUpSchedule() YWakeUpSchedule.FindWakeUpSchedule()

YWakeUpSchedule

Retrieves a wake up schedule for a given identifier.

```
def FindWakeUpSchedule( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the wake up schedule is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YWakeUpSchedule.isOnline()` to test if the wake up schedule is indeed online at a given time. In case of ambiguity when looking for a wake up schedule by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the wake up schedule

Returns :

a `YWakeUpSchedule` object allowing you to drive the wake up schedule.

YWakeUpSchedule.FirstWakeUpSchedule()

YWakeUpSchedule

yFirstWakeUpSchedule()

YWakeUpSchedule.FirstWakeUpSchedule()

Starts the enumeration of wake up schedules currently accessible.

```
def FirstWakeUpSchedule( )
```

Use the method `YWakeUpSchedule.nextWakeUpSchedule()` to iterate on next wake up schedules.

Returns :

a pointer to a `YWakeUpSchedule` object, corresponding to the first wake up schedule currently online, or a null pointer if there are none.

wakeupschedule→describe()
wakeupschedule.describe()**YWakeUpSchedule**

Returns a short text that describes unambiguously the instance of the wake up schedule in the form
TYPE (NAME) =SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the wake up schedule (ex:
Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

wakeupschedule→get_advertisedValue()

YWakeUpSchedule

wakeupschedule→advertisedValue()

wakeupschedule.get_advertisedValue()

Returns the current value of the wake up schedule (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the wake up schedule (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

wakeupschedule→get_errorMessage()
wakeupschedule→errorMessage()
wakeupschedule.get_errorMessage()

YWakeUpSchedule

Returns the error message of the latest error with the wake up schedule.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the wake up schedule object

wakeupschedule→get_errorType()
wakeupschedule→errorType()
wakeupschedule.get_errorType()

YWakeUpSchedule

Returns the numerical error code of the latest error with the wake up schedule.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the wake up schedule object

wakeupschedule→get_friendlyName()
wakeupschedule→friendlyName()
wakeupschedule.get_friendlyName()

YWakeUpSchedule

Returns a global identifier of the wake up schedule in the format MODULE_NAME.FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the wake up schedule if they are defined, otherwise the serial number of the module and the hardware identifier of the wake up schedule (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the wake up schedule using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

wakeupschedule→get_functionDescriptor()
wakeupschedule→functionDescriptor()
wakeupschedule.get_functionDescriptor()

YWakeUpSchedule

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

wakeupschedule→get_functionId()
wakeupschedule→functionId()
wakeupschedule.get_functionId()

YWakeUpSchedule

Returns the hardware identifier of the wake up schedule, without reference to the module.

```
def get_functionId( )
```

For example relay1

Returns :

a string that identifies the wake up schedule (ex: relay1)

On failure, throws an exception or returns Y_FUNCTIONID_INVALID.

wakeupschedule→get_hardwareId()
wakeupschedule→hardwareId()
wakeupschedule.get_hardwareId()

YWakeUpSchedule

Returns the unique hardware identifier of the wake up schedule in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the wake up schedule (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the wake up schedule (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

wakeupschedule→get_hours()
wakeupschedule→hours()
wakeupschedule.get_hours()

YWakeUpSchedule

Returns the hours scheduled for wake up.

```
def get_hours( )
```

Returns :

an integer corresponding to the hours scheduled for wake up

On failure, throws an exception or returns Y_HOURS_INVALID.

wakeupschedule→get_logicalName()
wakeupschedule→logicalName()
wakeupschedule.get_logicalName()

YWakeUpSchedule

Returns the logical name of the wake up schedule.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the wake up schedule.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

wakeupschedule→get_minutes()
wakeupschedule→minutes()
wakeupschedule.get_minutes()

YWakeUpSchedule

Returns all the minutes of each hour that are scheduled for wake up.

```
def get_minutes( )
```

wakeupschedule→get_minutesA()
wakeupschedule→minutesA()
wakeupschedule.get_minutesA()

YWakeUpSchedule

Returns the minutes in the 00-29 interval of each hour scheduled for wake up.

```
def get_minutesA( )
```

Returns :

an integer corresponding to the minutes in the 00-29 interval of each hour scheduled for wake up

On failure, throws an exception or returns Y_MINUTESA_INVALID.

wakeupschedule→get_minutesB()
wakeupschedule→minutesB()
wakeupschedule.get_minutesB()

YWakeUpSchedule

Returns the minutes in the 30-59 interval of each hour scheduled for wake up.

```
def get_minutesB( )
```

Returns :

an integer corresponding to the minutes in the 30-59 interval of each hour scheduled for wake up

On failure, throws an exception or returns Y_MINUTESB_INVALID.

wakeupschedule→get_module()
wakeupschedule→module()
wakeupschedule.get_module()

YWakeUpSchedule

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as online.

Returns :

an instance of `YModule`

wakeupschedule→get_monthDays()

YWakeUpSchedule

wakeupschedule→monthDays()

wakeupschedule.get_monthDays()

Returns the days of the month scheduled for wake up.

```
def get_monthDays( )
```

Returns :

an integer corresponding to the days of the month scheduled for wake up

On failure, throws an exception or returns Y_MONTHDAYS_INVALID.

wakeupschedule→get_months()

YWakeUpSchedule

wakeupschedule→months()

wakeupschedule.get_months()

Returns the months scheduled for wake up.

```
def get_months( )
```

Returns :

an integer corresponding to the months scheduled for wake up

On failure, throws an exception or returns Y_MONTHS_INVALID.

wakeupschedule→get_nextOccurence()
wakeupschedule→nextOccurence()
wakeupschedule.get_nextOccurence()

YWakeUpSchedule

Returns the date/time (seconds) of the next wake up occurence

```
def get_nextOccurence( )
```

Returns :

an integer corresponding to the date/time (seconds) of the next wake up occurence

On failure, throws an exception or returns Y_NEXTOCCURENCE_INVALID.

wakeupschedule→get(userData)

YWakeUpSchedule

wakeupschedule→userData()

wakeupschedule.get(userData)

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

wakeupschedule→get_weekDays()
wakeupschedule→weekDays()
wakeupschedule.get_weekDays()

YWakeUpSchedule

Returns the days of the week scheduled for wake up.

```
def get_weekDays( )
```

Returns :

an integer corresponding to the days of the week scheduled for wake up

On failure, throws an exception or returns Y_WEEKDAYS_INVALID.

wakeupschedule→isOnline()
wakeupschedule.isOnline()**YWakeUpSchedule**

Checks if the wake up schedule is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the wake up schedule in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the wake up schedule.

Returns :

true if the wake up schedule can be reached, and false otherwise

wakeupschedule→load()wakeupschedule.load()**YWakeUpSchedule**

Preloads the wake up schedule cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupschedule→nextWakeUpSchedule()
wakeupschedule.nextWakeUpSchedule()

YWakeUpSchedule

Continues the enumeration of wake up schedules started using `yFirstWakeUpSchedule()`.

```
def nextWakeUpSchedule( )
```

Returns :

a pointer to a `YWakeUpSchedule` object, corresponding to a wake up schedule currently online, or a null pointer if there are no more wake up schedules to enumerate.

**wakeupschedule→registerValueCallback()
wakeupschedule.registerValueCallback()****YWakeUpSchedule**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

wakeupschedule→set_hours()
wakeupschedule→setHours()
wakeupschedule.set_hours()

YWakeUpSchedule

Changes the hours when a wake up must take place.

```
def set_hours( newval)
```

Parameters :

newval an integer corresponding to the hours when a wake up must take place

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupschedule→set_logicalName()
wakeupschedule→setLogicalName()
wakeupschedule.set_logicalName()

YWakeUpSchedule

Changes the logical name of the wake up schedule.

```
def set_logicalName( newval)
```

You can use yCheckLogicalName() prior to this call to make sure that your parameter is valid. Remember to call the saveToFlash() method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the wake up schedule.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupschedule→set_minutes()
wakeupschedule→setMinutes()
wakeupschedule.set_minutes()

YWakeUpSchedule

Changes all the minutes where a wake up must take place.

```
def set_minutes( bitmap)
```

Parameters :

bitmap Minutes 00-59 of each hour scheduled for wake up.

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupschedule→set_minutesA()
wakeupschedule→setMinutesA()
wakeupschedule.set_minutesA()

YWakeUpSchedule

Changes the minutes in the 00-29 interval when a wake up must take place.

```
def set_minutesA( newval)
```

Parameters :

newval an integer corresponding to the minutes in the 00-29 interval when a wake up must take place

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupschedule→set_minutesB()
wakeupschedule→setMinutesB()
wakeupschedule.set_minutesB()

YWakeUpSchedule

Changes the minutes in the 30-59 interval when a wake up must take place.

```
def set_minutesB( newval)
```

Parameters :

newval an integer corresponding to the minutes in the 30-59 interval when a wake up must take place

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupschedule→set_monthDays()
wakeupschedule→setMonthDays()
wakeupschedule.set_monthDays()

YWakeUpSchedule

Changes the days of the month when a wake up must take place.

```
def set_monthDays( newval)
```

Parameters :

newval an integer corresponding to the days of the month when a wake up must take place

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupschedule→set_months()
wakeupschedule→setMonths()
wakeupschedule.set_months()

YWakeUpSchedule

Changes the months when a wake up must take place.

```
def set_months( newval )
```

Parameters :

newval an integer corresponding to the months when a wake up must take place

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

wakeupschedule→set(userData)
wakeupschedule→setUserData()
wakeupschedule.set(userData)

YWakeUpSchedule

Stores a user context provided as argument in the userData attribute of the function.

```
def setUserData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

wakeupschedule→set_weekDays()
wakeupschedule→setWeekDays()
wakeupschedule.set_weekDays()

YWakeUpSchedule

Changes the days of the week when a wake up must take place.

```
def set_weekDays( newval )
```

Parameters :

newval an integer corresponding to the days of the week when a wake up must take place

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

3.49. Watchdog function interface

The watchdog function works like a relay and can cause a brief power cut to an appliance after a preset delay to force this appliance to reset. The Watchdog must be called from time to time to reset the timer and prevent the appliance reset. The watchdog can be driven directly with *pulse* and *delayedpulse* methods to switch off an appliance for a given duration.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_watchdog.js'></script>
node.js	var yoctolib = require('yoctolib');
	var YWatchdog = yoctolib.YWatchdog;
php	require_once('yocto_watchdog.php');
cpp	#include "yocto_watchdog.h"
m	#import "yocto_watchdog.h"
pas	uses yocto_watchdog;
vb	yocto_watchdog.vb
cs	yocto_watchdog.cs
java	import com.yoctopuce.YoctoAPI.YWatchdog;
py	from yocto_watchdog import *

Global functions

yFindWatchdog(func)

Retrieves a watchdog for a given identifier.

yFirstWatchdog()

Starts the enumeration of watchdog currently accessible.

YWatchdog methods

watchdog->delayedPulse(ms_delay, ms_duration)

Schedules a pulse.

watchdog->describe()

Returns a short text that describes unambiguously the instance of the watchdog in the form
TYPE (NAME) = SERIAL.FUNCTIONID.

watchdog->get_advertisedValue()

Returns the current value of the watchdog (no more than 6 characters).

watchdog->get_autoStart()

Returns the watchdog running state at module power on.

watchdog->get_countdown()

Returns the number of milliseconds remaining before a pulse (delayedPulse() call). When there is no scheduled pulse, returns zero.

watchdog->get_errorMessage()

Returns the error message of the latest error with the watchdog.

watchdog->get_errorType()

Returns the numerical error code of the latest error with the watchdog.

watchdog->get_friendlyName()

Returns a global identifier of the watchdog in the format MODULE_NAME . FUNCTION_NAME.

watchdog->get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

watchdog->get_functionId()

Returns the hardware identifier of the watchdog, without reference to the module.

watchdog→get_hardwareId()	Returns the unique hardware identifier of the watchdog in the form SERIAL . FUNCTIONID.
watchdog→get_logicalName()	Returns the logical name of the watchdog.
watchdog→get_maxTimeOnStateA()	Retourne the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state A before automatically switching back in to B state.
watchdog→get_maxTimeOnStateB()	Retourne the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state B before automatically switching back in to A state.
watchdog→get_module()	Gets the YModule object for the device on which the function is located.
watchdog→get_module_async(callback, context)	Gets the YModule object for the device on which the function is located (asynchronous version).
watchdog→get_output()	Returns the output state of the watchdog, when used as a simple switch (single throw).
watchdog→get_pulseTimer()	Returns the number of milliseconds remaining before the watchdog is returned to idle position (state A), during a measured pulse generation.
watchdog→get_running()	Returns the watchdog running state.
watchdog→get_state()	Returns the state of the watchdog (A for the idle position, B for the active position).
watchdog→get_stateAtPowerOn()	Returns the state of the watchdog at device startup (A for the idle position, B for the active position, UNCHANGED for no change).
watchdog→get_triggerDelay()	Returns the waiting duration before a reset is automatically triggered by the watchdog, in milliseconds.
watchdog→get_triggerDuration()	Returns the duration of resets caused by the watchdog, in milliseconds.
watchdog→get_userData()	Returns the value of the userData attribute, as previously stored using method set(userData).
watchdog→isOnline()	Checks if the watchdog is currently reachable, without raising any error.
watchdog→isOnline_async(callback, context)	Checks if the watchdog is currently reachable, without raising any error (asynchronous version).
watchdog→load(msValidity)	Preloads the watchdog cache with a specified validity duration.
watchdog→load_async(msValidity, callback, context)	Preloads the watchdog cache with a specified validity duration (asynchronous version).
watchdog→nextWatchdog()	Continues the enumeration of watchdog started using yFirstWatchdog().
watchdog→pulse(ms_duration)	Sets the relay to output B (active) for a specified duration, then brings it automatically back to output A (idle state).
watchdog→registerValueCallback(callback)	Registers the callback function that is invoked on every change of advertised value.

watchdog->resetWatchdog()

Resets the watchdog.

watchdog->set_autoStart(newval)

Changes the watchdog running state at module power on.

watchdog->set_logicalName(newval)

Changes the logical name of the watchdog.

watchdog->set_maxTimeOnStateA(newval)

Sets the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state A before automatically switching back in to B state.

watchdog->set_maxTimeOnStateB(newval)

Sets the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state B before automatically switching back in to A state.

watchdog->set_output(newval)

Changes the output state of the watchdog, when used as a simple switch (single throw).

watchdog->set_running(newval)

Changes the running state of the watchdog.

watchdog->set_state(newval)

Changes the state of the watchdog (A for the idle position, B for the active position).

watchdog->set_stateAtPowerOn(newval)

Preset the state of the watchdog at device startup (A for the idle position, B for the active position, UNCHANGED for no modification).

watchdog->set_triggerDelay(newval)

Changes the waiting delay before a reset is triggered by the watchdog, in milliseconds.

watchdog->set_triggerDuration(newval)

Changes the duration of resets caused by the watchdog, in milliseconds.

watchdog->set_userData(data)

Stores a user context provided as argument in the userData attribute of the function.

watchdog->wait_async(callback, context)

Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YWatchdog.FindWatchdog() yFindWatchdog()YWatchdog.FindWatchdog()

Retrieves a watchdog for a given identifier.

```
def FindWatchdog( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the watchdog is online at the time it is invoked. The returned object is nevertheless valid. Use the method `YWatchdog.isOnline()` to test if the watchdog is indeed online at a given time. In case of ambiguity when looking for a watchdog by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the watchdog

Returns :

a `YWatchdog` object allowing you to drive the watchdog.

YWatchdog.FirstWatchdog()**YWatchdog****yFirstWatchdog()YWatchdog.FirstWatchdog()**

Starts the enumeration of watchdog currently accessible.

```
def FirstWatchdog( )
```

Use the method `YWatchdog.nextWatchdog()` to iterate on next watchdog.

Returns :

a pointer to a `YWatchdog` object, corresponding to the first watchdog currently online, or a `null` pointer if there are none.

watchdog→delayedPulse()|watchdog.delayedPulse()**YWatchdog**

Schedules a pulse.

```
def delayedPulse( ms_delay, ms_duration)
```

Parameters :

ms_delay waiting time before the pulse, in millisecondes

ms_duration pulse duration, in millisecondes

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→describe()watchdog.describe()**YWatchdog**

Returns a short text that describes unambiguously the instance of the watchdog in the form TYPE (NAME)=SERIAL.FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME is the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the watchdog (ex: Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

watchdog→get_advertisedValue()
watchdog→advertisedValue()
watchdog.get_advertisedValue()

YWatchdog

Returns the current value of the watchdog (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the watchdog (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

watchdog→get_autoStart()**YWatchdog****watchdog→autoStart()watchdog.get_autoStart()**

Returns the watchdog runing state at module power on.

```
def get_autoStart( )
```

Returns :

either Y_AUTOSTART_OFF or Y_AUTOSTART_ON, according to the watchdog runing state at module power on

On failure, throws an exception or returns Y_AUTOSTART_INVALID.

watchdog→get_countdown()**YWatchdog****watchdog→countdown()watchdog.get_countdown()**

Returns the number of milliseconds remaining before a pulse (delayedPulse() call) When there is no scheduled pulse, returns zero.

```
def get_countdown( )
```

Returns :

an integer corresponding to the number of milliseconds remaining before a pulse (delayedPulse() call) When there is no scheduled pulse, returns zero

On failure, throws an exception or returns Y_COUNTDOWN_INVALID.

watchdog→get_errorMessage()
watchdog→errorMessage()
watchdog.get_errorMessage()**YWatchdog**

Returns the error message of the latest error with the watchdog.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the watchdog object

watchdog→get_errorType()

YWatchdog

watchdog→errorType()watchdog.get_errorType()

Returns the numerical error code of the latest error with the watchdog.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the watchdog object

watchdog→get_friendlyName()
watchdog→friendlyName()
watchdog.get_friendlyName()**YWatchdog**

Returns a global identifier of the watchdog in the format MODULE_NAME . FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the watchdog if they are defined, otherwise the serial number of the module and the hardware identifier of the watchdog (for example: MyCustomName . relay1)

Returns :

a string that uniquely identifies the watchdog using logical names (ex: MyCustomName . relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

watchdog→get_functionDescriptor()
watchdog→functionDescriptor()
watchdog.get_functionDescriptor()

YWatchdog

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

watchdog→get_functionId()**YWatchdog****watchdog→functionId()watchdog.get_functionId()**

Returns the hardware identifier of the watchdog, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the watchdog (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

watchdog→get_hardwareId()

YWatchdog

watchdog→hardwareId()watchdog.get_hardwareId()

Returns the unique hardware identifier of the watchdog in the form SERIAL.FUNCTIONID.

```
def get_hardwareId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the watchdog (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the watchdog (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

**watchdog→get_logicalName()
watchdog→logicalName()
watchdog.get_logicalName()****YWatchdog**

Returns the logical name of the watchdog.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the watchdog.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

watchdog→get_maxTimeOnStateA()
watchdog→maxTimeOnStateA()
watchdog.get_maxTimeOnStateA()

YWatchdog

Retourne the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state A before automatically switching back in to B state.

```
def get_maxTimeOnStateA( )
```

Zero means no maximum time.

Returns :

an integer

On failure, throws an exception or returns Y_MAXTIMEONSTATEA_INVALID.

watchdog→get_maxTimeOnStateB()
watchdog→maxTimeOnStateB()
watchdog.get_maxTimeOnStateB()**YWatchdog**

Retourne the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state B before automatically switching back in to A state.

```
def get_maxTimeOnStateB( )
```

Zero means no maximum time.

Returns :

an integer

On failure, throws an exception or returns Y_MAXTIMEONSTATEB_INVALID.

watchdog→get_module()

YWatchdog

watchdog→module()watchdog.get_module()

Gets the **YModule** object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of **YModule** is not shown as online.

Returns :

an instance of **YModule**

watchdog→get_output()**YWatchdog****watchdog→output()watchdog.get_output()**

Returns the output state of the watchdog, when used as a simple switch (single throw).

```
def get_output( )
```

Returns :

either Y_OUTPUT_OFF or Y_OUTPUT_ON, according to the output state of the watchdog, when used as a simple switch (single throw)

On failure, throws an exception or returns Y_OUTPUT_INVALID.

watchdog→get_pulseTimer() **YWatchdog**
watchdog→pulseTimer()watchdog.get_pulseTimer()

Returns the number of milliseconds remaining before the watchdog is returned to idle position (state A), during a measured pulse generation.

```
def get_pulseTimer( )
```

When there is no ongoing pulse, returns zero.

Returns :

an integer corresponding to the number of milliseconds remaining before the watchdog is returned to idle position (state A), during a measured pulse generation

On failure, throws an exception or returns Y_PULSE_TIMER_INVALID.

watchdog→get_running()**YWatchdog****watchdog→running()watchdog.get_running()**

Returns the watchdog running state.

```
def get_running( )
```

Returns :

either Y_RUNNING_OFF or Y_RUNNING_ON, according to the watchdog running state

On failure, throws an exception or returns Y_RUNNING_INVALID.

watchdog→get_state()

YWatchdog

watchdog→state()watchdog.get_state()

Returns the state of the watchdog (A for the idle position, B for the active position).

```
def get_state( )
```

Returns :

either Y_STATE_A or Y_STATE_B, according to the state of the watchdog (A for the idle position, B for the active position)

On failure, throws an exception or returns Y_STATE_INVALID.

watchdog→get_stateAtPowerOn()
watchdog→stateAtPowerOn()
watchdog.get_stateAtPowerOn()

YWatchdog

Returns the state of the watchdog at device startup (A for the idle position, B for the active position, UNCHANGED for no change).

```
def get_stateAtPowerOn( )
```

Returns :

a value among Y_STATEATPOWERON_UNCHANGED, Y_STATEATPOWERON_A and Y_STATEATPOWERON_B corresponding to the state of the watchdog at device startup (A for the idle position, B for the active position, UNCHANGED for no change)

On failure, throws an exception or returns Y_STATEATPOWERON_INVALID.

watchdog→get_triggerDelay()
watchdog→triggerDelay()
watchdog.get_triggerDelay()

YWatchdog

Returns the waiting duration before a reset is automatically triggered by the watchdog, in milliseconds.

```
def get_triggerDelay( )
```

Returns :

an integer corresponding to the waiting duration before a reset is automatically triggered by the watchdog, in milliseconds

On failure, throws an exception or returns Y_TRIGGERDELAY_INVALID.

watchdog→get_triggerDuration()
watchdog→triggerDuration()
watchdog.get_triggerDuration()**YWatchdog**

Returns the duration of resets caused by the watchdog, in milliseconds.

```
def get_triggerDuration( )
```

Returns :

an integer corresponding to the duration of resets caused by the watchdog, in milliseconds

On failure, throws an exception or returns Y_TRIGGERDURATION_INVALID.

watchdog→get(userData)

YWatchdog

watchdog→userData()watchdog.get(userData)

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

watchdog→isOnline()watchdog.isOnline()**YWatchdog**

Checks if the watchdog is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the watchdog in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the watchdog.

Returns :

`true` if the watchdog can be reached, and `false` otherwise

watchdog→load()|watchdog.load()**YWatchdog**

Preloads the watchdog cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

**watchdog→nextWatchdog()
watchdog.nextWatchdog()****YWatchdog**

Continues the enumeration of watchdog started using `yFirstWatchdog()`.

```
def nextWatchdog( )
```

Returns :

a pointer to a `YWatchdog` object, corresponding to a watchdog currently online, or a `null` pointer if there are no more watchdog to enumerate.

watchdog→pulse()watchdog.pulse()**YWatchdog**

Sets the relay to output B (active) for a specified duration, then brings it automatically back to output A (idle state).

```
def pulse( ms_duration )
```

Parameters :

ms_duration pulse duration, in millisecondes

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→registerValueCallback()
watchdog.registerValueCallback()**YWatchdog**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

watchdog→resetWatchdog()
watchdog.resetWatchdog()

YWatchdog

Resets the watchdog.

```
def resetWatchdog( )
```

When the watchdog is running, this function must be called on a regular basis to prevent the watchdog to trigger

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set_autoStart()**YWatchdog****watchdog→setAutoStart()watchdog.set_autoStart()**

Changes the watchdog runningsttae at module power on.

```
def set_autoStart( newval)
```

Remember to call the saveToFlash() method and then to reboot the module to apply this setting.

Parameters :

newval either Y_AUTOSTART_OFF or Y_AUTOSTART_ON, according to the watchdog runningsttae at module power on

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set_logicalName()
watchdog→setLogicalName()
watchdog.set_logicalName()

YWatchdog

Changes the logical name of the watchdog.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

newval a string corresponding to the logical name of the watchdog.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set_maxTimeOnStateA()
watchdog→setMaxTimeOnStateA()
watchdog.set_maxTimeOnStateA()

YWatchdog

Sets the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state A before automatically switching back in to B state.

```
def set_maxTimeOnStateA( newval)
```

Use zero for no maximum time.

Parameters :

newval an integer

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set_maxTimeOnStateB()
watchdog→setMaxTimeOnStateB()
watchdog.set_maxTimeOnStateB()

YWatchdog

Sets the maximum time (ms) allowed for \$THEFUNCTIONS\$ to stay in state B before automatically switching back in to A state.

```
def set_maxTimeOnStateB( newval )
```

Use zero for no maximum time.

Parameters :

newval an integer

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set_output()**YWatchdog****watchdog→setOutput()watchdog.set_output()**

Changes the output state of the watchdog, when used as a simple switch (single throw).

```
def set_output( newval)
```

Parameters :

newval either Y_OUTPUT_OFF or Y_OUTPUT_ON, according to the output state of the watchdog, when used as a simple switch (single throw)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set_running()

YWatchdog

watchdog→setRunning()watchdog.set_running()

Changes the running state of the watchdog.

```
def set_running( newval)
```

Parameters :

newval either Y_RUNNING_OFF or Y_RUNNING_ON, according to the running state of the watchdog

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set_state()**YWatchdog****watchdog→setState()watchdog.set_state()**

Changes the state of the watchdog (A for the idle position, B for the active position).

```
def set_state( newval)
```

Parameters :

newval either Y_STATE_A or Y_STATE_B, according to the state of the watchdog (A for the idle position, B for the active position)

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set_stateAtPowerOn()
watchdog→setStateAtPowerOn()
watchdog.set_stateAtPowerOn()

YWatchdog

Preset the state of the watchdog at device startup (A for the idle position, B for the active position, UNCHANGED for no modification).

```
def set_stateAtPowerOn( newval )
```

Remember to call the matching module `saveToFlash()` method, otherwise this call will have no effect.

Parameters :

newval a value among `Y_STATEATPOWERON_UNCHANGED`, `Y_STATEATPOWERON_A` and `Y_STATEATPOWERON_B`

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set_triggerDelay()
watchdog→setTriggerDelay()
watchdog.set_triggerDelay()

YWatchdog

Changes the waiting delay before a reset is triggered by the watchdog, in milliseconds.

```
def set_triggerDelay( newval)
```

Parameters :

newval an integer corresponding to the waiting delay before a reset is triggered by the watchdog, in milliseconds

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set_triggerDuration()
watchdog→setTriggerDuration()
watchdog.set_triggerDuration()

YWatchdog

Changes the duration of resets caused by the watchdog, in milliseconds.

```
def set_triggerDuration( newval)
```

Parameters :

newval an integer corresponding to the duration of resets caused by the watchdog, in milliseconds

Returns :

YAPI_SUCCESS if the call succeeds.

On failure, throws an exception or returns a negative error code.

watchdog→set(userData())**YWatchdog****watchdog→setUserData()watchdog.set(userData())**

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData( data)
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

3.50. Wireless function interface

YWireless functions provides control over wireless network parameters and status for devices that are wireless-enabled.

In order to use the functions described here, you should include:

js	<script type='text/javascript' src='yocto_wireless.js'></script>
nodejs	var yoctolib = require('yoctolib');
	var YWireless = yoctolib.YWireless;
php	require_once('yocto_wireless.php');
cpp	#include "yocto_wireless.h"
m	#import "yocto_wireless.h"
pas	uses yocto_wireless;
vb	yocto_wireless.vb
cs	yocto_wireless.cs
java	import com.yoctopuce.YoctoAPI.YWireless;
py	from yocto_wireless import *

Global functions

yFindWireless(func)

Retrieves a wireless lan interface for a given identifier.

yFirstWireless()

Starts the enumeration of wireless lan interfaces currently accessible.

YWireless methods

wireless→adhocNetwork(ssid, securityKey)

Changes the configuration of the wireless lan interface to create an ad-hoc wireless network, without using an access point.

wireless→describe()

Returns a short text that describes unambiguously the instance of the wireless lan interface in the form TYPE (NAME) = SERIAL . FUNCTIONID.

wireless→get_advertisedValue()

Returns the current value of the wireless lan interface (no more than 6 characters).

wireless→get_channel()

Returns the 802.11 channel currently used, or 0 when the selected network has not been found.

wireless→get_detectedWlans()

Returns a list of YWlanRecord objects that describe detected Wireless networks.

wireless→get_errorMessage()

Returns the error message of the latest error with the wireless lan interface.

wireless→get_errorType()

Returns the numerical error code of the latest error with the wireless lan interface.

wireless→get_friendlyName()

Returns a global identifier of the wireless lan interface in the format MODULE_NAME . FUNCTION_NAME.

wireless→get_functionDescriptor()

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

wireless→get_functionId()

Returns the hardware identifier of the wireless lan interface, without reference to the module.

wireless→get_hardwareId()

Returns the unique hardware identifier of the wireless lan interface in the form SERIAL . FUNCTIONID.

wireless→get_linkQuality()	Returns the link quality, expressed in percent.
wireless→get_logicalName()	Returns the logical name of the wireless lan interface.
wireless→get_message()	Returns the latest status message from the wireless interface.
wireless→get_module()	Gets the YModule object for the device on which the function is located.
wireless→get_module_async(callback, context)	Gets the YModule object for the device on which the function is located (asynchronous version).
wireless→get_security()	Returns the security algorithm used by the selected wireless network.
wireless→get_ssid()	Returns the wireless network name (SSID).
wireless→get_userData()	Returns the value of the userData attribute, as previously stored using method set(userData).
wireless→isOnline()	Checks if the wireless lan interface is currently reachable, without raising any error.
wireless→isOnline_async(callback, context)	Checks if the wireless lan interface is currently reachable, without raising any error (asynchronous version).
wireless→joinNetwork(ssid, securityKey)	Changes the configuration of the wireless lan interface to connect to an existing access point (infrastructure mode).
wireless→load(msValidity)	Preloads the wireless lan interface cache with a specified validity duration.
wireless→load_async(msValidity, callback, context)	Preloads the wireless lan interface cache with a specified validity duration (asynchronous version).
wireless→nextWireless()	Continues the enumeration of wireless lan interfaces started using yFirstWireless().
wireless→registerValueCallback(callback)	Registers the callback function that is invoked on every change of advertised value.
wireless→set_logicalName(newval)	Changes the logical name of the wireless lan interface.
wireless→set_userData(data)	Stores a user context provided as argument in the userData attribute of the function.
wireless→softAPNetwork(ssid, securityKey)	Changes the configuration of the wireless lan interface to create a new wireless network by emulating a WiFi access point (Soft AP).
wireless→wait_async(callback, context)	Waits for all pending asynchronous commands on the module to complete, and invoke the user-provided callback function.

YWireless.FindWireless() yFindWireless()YWireless.FindWireless()

YWireless

Retrieves a wireless lan interface for a given identifier.

```
def FindWireless( func)
```

The identifier can be specified using several formats:

- FunctionLogicalName
- ModuleSerialNumber.FunctionIdentifier
- ModuleSerialNumber.FunctionLogicalName
- ModuleLogicalName.FunctionIdentifier
- ModuleLogicalName.FunctionLogicalName

This function does not require that the wireless lan interface is online at the time it is invoked. The returned object is nevertheless valid. Use the method `Ywireless.isOnline()` to test if the wireless lan interface is indeed online at a given time. In case of ambiguity when looking for a wireless lan interface by logical name, no error is notified: the first instance found is returned. The search is performed first by hardware name, then by logical name.

Parameters :

`func` a string that uniquely characterizes the wireless lan interface

Returns :

a `YWireless` object allowing you to drive the wireless lan interface.

YWireless.FirstWireless()**YWireless****yFirstWireless()YWireless.FirstWireless()**

Starts the enumeration of wireless lan interfaces currently accessible.

```
def FirstWireless( )
```

Use the method `YWireless.nextWireless()` to iterate on next wireless lan interfaces.

Returns :

a pointer to a `YWireless` object, corresponding to the first wireless lan interface currently online, or a null pointer if there are none.

wireless→adhocNetwork()wireless.adhocNetwork()**YWireless**

Changes the configuration of the wireless lan interface to create an ad-hoc wireless network, without using an access point.

```
def adhocNetwork( ssid, securityKey)
```

On the YoctoHub-Wireless-g, it is best to use softAPNetworkInstead(), which emulates an access point (Soft AP) which is more efficient and more widely supported than ad-hoc networks.

When a security key is specified for an ad-hoc network, the network is protected by a WEP40 key (5 characters or 10 hexadecimal digits) or WEP128 key (13 characters or 26 hexadecimal digits). It is recommended to use a well-randomized WEP128 key using 26 hexadecimal digits to maximize security. Remember to call the saveToFlash() method and then to reboot the module to apply this setting.

Parameters :

ssid the name of the network to connect to
securityKey the network key, as a character string

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

wireless→describe()wireless.describe()**YWireless**

Returns a short text that describes unambiguously the instance of the wireless lan interface in the form TYPE (NAME)=SERIAL . FUNCTIONID.

```
def describe( )
```

More precisely, TYPE is the type of the function, NAME it the name used for the first access to the function, SERIAL is the serial number of the module if the module is connected or "unresolved", and FUNCTIONID is the hardware identifier of the function if the module is connected. For example, this method returns Relay(MyCustomName.relay1)=RELAYL01-123456.relay1 if the module is already connected or Relay(BadCustomeName.relay1)=unresolved if the module has not yet been connected. This method does not trigger any USB or TCP transaction and can therefore be used in a debugger.

Returns :

a string that describes the wireless lan interface (ex:
Relay(MyCustomName.relay1)=RELAYL01-123456.relay1)

wireless→get_advertisedValue()
wireless→advertisedValue()
wireless.get_advertisedValue()

YWireless

Returns the current value of the wireless lan interface (no more than 6 characters).

```
def get_advertisedValue( )
```

Returns :

a string corresponding to the current value of the wireless lan interface (no more than 6 characters).

On failure, throws an exception or returns Y_ADVERTISEDVALUE_INVALID.

wireless→get_channel()

YWireless

wireless→channel()wireless.get_channel()

Returns the 802.11 channel currently used, or 0 when the selected network has not been found.

```
def get_channel( )
```

Returns :

an integer corresponding to the 802.11 channel currently used, or 0 when the selected network has not been found

On failure, throws an exception or returns Y_CHANNEL_INVALID.

wireless→get_detectedWlans()
wireless→detectedWlans()
wireless.get_detectedWlans()

YWireless

Returns a list of YWlanRecord objects that describe detected Wireless networks.

```
def get_detectedWlans( )
```

This list is not updated when the module is already connected to an acces point (infrastructure mode). To force an update of this list, adhocNetwork() must be called to disconnect the module from the current network. The returned list must be unallocated by the caller.

Returns :

a list of YWlanRecord objects, containing the SSID, channel, link quality and the type of security of the wireless network.

On failure, throws an exception or returns an empty list.

wireless→get_errorMessage()
wireless→errorMessage()
wireless.get_errorMessage()

YWireless

Returns the error message of the latest error with the wireless lan interface.

```
def get_errorMessage( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a string corresponding to the latest error message that occurred while using the wireless lan interface object

wireless→get_errorType()

YWireless

wireless→errorType()wireless.get_errorType()

Returns the numerical error code of the latest error with the wireless lan interface.

```
def get_errorType( )
```

This method is mostly useful when using the Yoctopuce library with exceptions disabled.

Returns :

a number corresponding to the code of the latest error that occurred while using the wireless lan interface object

wireless→get_friendlyName()**YWireless****wireless→friendlyName()wireless.get_friendlyName()**

Returns a global identifier of the wireless lan interface in the format MODULE_NAME.FUNCTION_NAME.

```
def get_friendlyName( )
```

The returned string uses the logical names of the module and of the wireless lan interface if they are defined, otherwise the serial number of the module and the hardware identifier of the wireless lan interface (for example: MyCustomName.relay1)

Returns :

a string that uniquely identifies the wireless lan interface using logical names (ex: MyCustomName.relay1)

On failure, throws an exception or returns Y_FRIENDLYNAME_INVALID.

wireless→get_functionDescriptor()
wireless→functionDescriptor()
wireless.get_functionDescriptor()

YWireless

Returns a unique identifier of type YFUN_DESCR corresponding to the function.

```
def get_functionDescriptor( )
```

This identifier can be used to test if two instances of YFunction reference the same physical function on the same physical device.

Returns :

an identifier of type YFUN_DESCR.

If the function has never been contacted, the returned value is Y_FUNCTIONDESCRIPTOR_INVALID.

wireless→get_functionId()**YWireless****wireless→functionId()wireless.get_functionId()**

Returns the hardware identifier of the wireless lan interface, without reference to the module.

```
def get_functionId( )
```

For example `relay1`

Returns :

a string that identifies the wireless lan interface (ex: `relay1`)

On failure, throws an exception or returns `Y_FUNCTIONID_INVALID`.

wireless→get_hwId()**YWireless****wireless→hardwareId()wireless.get_hwId()**

Returns the unique hardware identifier of the wireless lan interface in the form SERIAL.FUNCTIONID.

```
def get_hwId( )
```

The unique hardware identifier is composed of the device serial number and of the hardware identifier of the wireless lan interface (for example RELAYL01-123456.relay1).

Returns :

a string that uniquely identifies the wireless lan interface (ex: RELAYL01-123456.relay1)

On failure, throws an exception or returns Y_HARDWAREID_INVALID.

wireless→get_linkQuality()

YWireless

wireless→linkQuality()wireless.get_linkQuality()

Returns the link quality, expressed in percent.

```
def get_linkQuality( )
```

Returns :

an integer corresponding to the link quality, expressed in percent

On failure, throws an exception or returns Y_LINKQUALITY_INVALID.

wireless→get_logicalName()

YWireless

wireless→logicalName()wireless.get_logicalName()

Returns the logical name of the wireless lan interface.

```
def get_logicalName( )
```

Returns :

a string corresponding to the logical name of the wireless lan interface.

On failure, throws an exception or returns Y_LOGICALNAME_INVALID.

wireless→get_message()**YWireless****wireless→message()wireless.get_message()**

Returns the latest status message from the wireless interface.

```
def get_message( )
```

Returns :

a string corresponding to the latest status message from the wireless interface

On failure, throws an exception or returns Y_MESSAGE_INVALID.

wireless→get_module()

YWireless

wireless→module()wireless.get_module()

Gets the `YModule` object for the device on which the function is located.

```
def get_module( )
```

If the function cannot be located on any module, the returned instance of `YModule` is not shown as on-line.

Returns :

an instance of `YModule`

wireless→get_security()**YWireless****wireless→security()wireless.get_security()**

Returns the security algorithm used by the selected wireless network.

```
def get_security( )
```

Returns :

a value among Y_SECURITY_UNKNOWN, Y_SECURITY_OPEN, Y_SECURITY_WEP, Y_SECURITY_WPA and Y_SECURITY_WPA2 corresponding to the security algorithm used by the selected wireless network

On failure, throws an exception or returns Y_SECURITY_INVALID.

wireless→get_ssid()

YWireless

wireless→ssid()wireless.get_ssid()

Returns the wireless network name (SSID).

```
def get_ssid( )
```

Returns :

a string corresponding to the wireless network name (SSID)

On failure, throws an exception or returns Y_SSID_INVALID.

wireless→get(userData)**YWireless****wireless→userData()wireless.get(userData())**

Returns the value of the userData attribute, as previously stored using method `set(userData)`.

```
def get(userData):
```

This attribute is never touched directly by the API, and is at disposal of the caller to store a context.

Returns :

the object stored previously by the caller.

wireless→isOnline()wireless.isOnline()**YWireless**

Checks if the wireless lan interface is currently reachable, without raising any error.

```
def isOnline( )
```

If there is a cached value for the wireless lan interface in cache, that has not yet expired, the device is considered reachable. No exception is raised if there is an error while trying to contact the device hosting the wireless lan interface.

Returns :

`true` if the wireless lan interface can be reached, and `false` otherwise

wireless→joinNetwork()wireless.joinNetwork()**YWireless**

Changes the configuration of the wireless lan interface to connect to an existing access point (infrastructure mode).

```
def joinNetwork( ssid, securityKey)
```

Remember to call the `saveToFlash()` method and then to reboot the module to apply this setting.

Parameters :

ssid the name of the network to connect to
securityKey the network key, as a character string

Returns :

`YAPI_SUCCESS` when the call succeeds.

On failure, throws an exception or returns a negative error code.

wireless→load()|wireless.load()**YWireless**

Preloads the wireless lan interface cache with a specified validity duration.

```
def load( msValidity)
```

By default, whenever accessing a device, all function attributes are kept in cache for the standard duration (5 ms). This method can be used to temporarily mark the cache as valid for a longer period, in order to reduce network traffic for instance.

Parameters :

msValidity an integer corresponding to the validity attributed to the loaded function parameters, in milliseconds

Returns :

YAPI_SUCCESS when the call succeeds.

On failure, throws an exception or returns a negative error code.

wireless→nextWireless()wireless.nextWireless()**YWireless**

Continues the enumeration of wireless lan interfaces started using `yFirstWireless()`.

```
def nextWireless( )
```

Returns :

a pointer to a `YWireless` object, corresponding to a wireless lan interface currently online, or a `null` pointer if there are no more wireless lan interfaces to enumerate.

**wireless→registerValueCallback()
wireless.registerValueCallback()****YWireless**

Registers the callback function that is invoked on every change of advertised value.

```
def registerValueCallback( callback)
```

The callback is invoked only during the execution of `ySleep` or `yHandleEvents`. This provides control over the time when the callback is triggered. For good responsiveness, remember to call one of these two functions periodically. To unregister a callback, pass a null pointer as argument.

Parameters :

callback the callback function to call, or a null pointer. The callback function should take two arguments: the function object of which the value has changed, and the character string describing the new advertised value.

wireless→set_logicalName()
wireless→setLogicalName()
wireless.set_logicalName()

YWireless

Changes the logical name of the wireless lan interface.

```
def set_logicalName( newval)
```

You can use `yCheckLogicalName()` prior to this call to make sure that your parameter is valid. Remember to call the `saveToFlash()` method of the module if the modification must be kept.

Parameters :

`newval` a string corresponding to the logical name of the wireless lan interface.

Returns :

`YAPI_SUCCESS` if the call succeeds.

On failure, throws an exception or returns a negative error code.

wireless→set(userData)

YWireless

wireless→setUserData(wireless.set(userData))

Stores a user context provided as argument in the userData attribute of the function.

```
def set(userData):
```

This attribute is never touched by the API, and is at disposal of the caller to store a context.

Parameters :

data any kind of object to be stored

wireless→softAPNetwork()wireless.softAPNetwork()**YWireless**

Changes the configuration of the wireless lan interface to create a new wireless network by emulating a WiFi access point (Soft AP).

def softAPNetwork(ssid, securityKey)

This function can only be used with the YoctoHub-Wireless-g.

When a security key is specified for a SoftAP network, the network is protected by a WEP40 key (5 characters or 10 hexadecimal digits) or WEP128 key (13 characters or 26 hexadecimal digits). It is recommended to use a well-randomized WEP128 key using 26 hexadecimal digits to maximize security. Remember to call the `saveToFlash()` method and then to reboot the module to apply this setting.

Parameters :

ssid the name of the network to connect to
securityKey the network key, as a character string

Returns :

`YAPI_SUCCESS` when the call succeeds.

On failure, throws an exception or returns a negative error code.

Index

A

Accelerometer 32
adhocNetwork, YWireless 1763
Altitude 74
AnButton 116

B

Blueprint 10
brakingForceMove, YMotor 880

C

calibrate, YLightSensor 743
calibrateFromPoints, YAccelerometer 36
calibrateFromPoints, YAltitude 78
calibrateFromPoints, YCarbonDioxide 158
calibrateFromPoints, YCompass 226
calibrateFromPoints, YCurrent 266
calibrateFromPoints, YGenericSensor 552
calibrateFromPoints, YGyro 601
calibrateFromPoints, YHumidity 677
calibrateFromPoints, YLightSensor 744
calibrateFromPoints, YMagnetometer 785
calibrateFromPoints, YPower 1001
calibrateFromPoints, YPressure 1044
calibrateFromPoints, YPwmInput 1083
calibrateFromPoints, YQt 1192
calibrateFromPoints,YSensor 1330
calibrateFromPoints, YTemperature 1461
calibrateFromPoints, YTilt 1502
calibrateFromPoints, YVoc 1541
calibrateFromPoints, YVoltage 1580
callbackLogin, YNetwork 922
cancel3DCalibration, YRefFrame 1258
CarbonDioxide 154
checkFirmware, YModule 833
CheckLogicalName, YAPI 12
clear, YDisplayLayer 464
clearConsole, YDisplayLayer 465
Clock 1227
ColorLed 193
Compass 222
Configuration 1254
consoleOut, YDisplayLayer 466
copyLayerContent, YDisplay 420
Current 262

D

Data 335, 345, 357
DataLogger 301
delayedPulse, YDigitalIO 376
delayedPulse, YRelay 1294
delayedPulse, YWatchdog 1719

describe, YAccelerometer 37
describe, YAltitude 79
describe, YAnButton 120
describe, YCarbonDioxide 159
describe, YColorLed 196
describe, YCompass 227
describe, YCurrent 267
describe, YDataLogger 305
describe, YDigitalIO 377
describe, YDisplay 421
describe, YDualPower 498
describe, YFiles 523
describe, YGenericSensor 553
describe, YGyro 602
describe, YHubPort 651
describe, YHumidity 678
describe, YLed 715
describe, YLightSensor 745
describe, YMagnetometer 786
describe, YModule 834
describe, YMotor 881
describe, YNetwork 923
describe, YOsControl 977
describe, YPower 1002
describe, YPressure 1045
describe, YPwmInput 1084
describe, YPwmOutput 1131
describe, YPwmPowerSource 1168
describe, YQt 1193
describe, YRealTimeClock 1230
describe, YRefFrame 1259
describe, YRelay 1295
describe, YSensor 1331
describe, YSerialPort 1370
describe, YServo 1426
describe, YTemperature 1462
describe, YTilt 1503
describe, YVoc 1542
describe, YVoltage 1581
describe, YWakeUpMonitor 1647
describe, YWakeUpSchedule 1682
describe, YWatchdog 1720
describe, YWireless 1764
Digital 372
DisableExceptions, YAPI 13
Display 416
DisplayLayer 463
download, YFiles 524
download, YModule 835
drawBar, YDisplayLayer 467
drawBitmap, YDisplayLayer 468
drawCircle, YDisplayLayer 469
drawDisc, YDisplayLayer 470
drawImage, YDisplayLayer 471
drawPixel, YDisplayLayer 472

drawRect, YDisplayLayer 473
drawText, YDisplayLayer 474
drivingForceMove, YMotor 882
dutyCycleMove, YPwmOutput 1132
Dynamic 3

E

EnableExceptions, YAPI 14
Error 7
External 495

F

fade, YDisplay 422
Files 3, 520
FindAccelerometer, YAccelerometer 34
FindAltitude, YAltitude 76
FindAnButton, YAnButton 118
FindCarbonDioxide, YCarbonDioxide 156
FindColorLed, YColorLed 194
FindCompass, YCompass 224
FindCurrent, YCurrent 264
FindDataLogger, YDataLogger 303
FindDigitalIO, YDigitalIO 374
FindDisplay, YDisplay 418
FindDualPower, YDualPower 496
FindFiles, YFiles 521
FindGenericSensor, YGenericSensor 550
FindGyro, YGyro 599
FindHubPort, YHubPort 649
FindHumidity, YHumidity 675
FindLed, YLed 713
FindLightSensor, YLightSensor 741
FindMagnetometer, YMagnetometer 783
FindModule, YModule 831
FindMotor, YMotor 878
FindNetwork, YNetwork 920
FindOsControl, YOsControl 975
FindPower, YPower 999
FindPressure, YPressure 1042
FindPwmInput, YPwmInput 1081
FindPwmOutput, YPwmOutput 1129
FindPwmPowerSource, YPwmPowerSource 1166
FindQt, YQt 1190
FindRealTimeClock, YRealTimeClock 1228
FindRefFrame, YRefFrame 1256
FindRelay, YRelay 1292
FindSensor, YSensor 1328
FindSerialPort, YSerialPort 1368
FindServo, YServo 1424
FindTemperature, YTemperature 1459
FindTilt, YTilt 1500
FindVoc, YVoc 1539
FindVoltage, YVoltage 1578
FindVSource, YVSource 1616
FindWakeUpMonitor, YWakeUpMonitor 1645
FindWakeUpSchedule, YWakeUpSchedule 1680
FindWatchdog, YWatchdog 1717

FindWireless, YWireless 1761
FirstAccelerometer, YAccelerometer 35
FirstAltitude, YAltitude 77
FirstAnButton, YAnButton 119
FirstCarbonDioxide, YCarbonDioxide 157
FirstColorLed, YColorLed 195
FirstCompass, YCompass 225
FirstCurrent, YCurrent 265
FirstDataLogger, YDataLogger 304
FirstDigitalIO, YDigitalIO 375
FirstDisplay, YDisplay 419
FirstDualPower, YDualPower 497
FirstFiles, YFiles 522
FirstGenericSensor, YGenericSensor 551
FirstGyro, YGyro 600
FirstHubPort, YHubPort 650
FirstHumidity, YHumidity 676
FirstLed, YLed 714
FirstLightSensor, YLightSensor 742
FirstMagnetometer, YMagnetometer 784
FirstModule, YModule 832
FirstMotor, YMotor 879
FirstNetwork, YNetwork 921
FirstOsControl, YOsControl 976
FirstPower, YPower 1000
FirstPressure, YPressure 1043
FirstPwmInput, YPwmInput 1082
FirstPwmOutput, YPwmOutput 1130
FirstPwmPowerSource, YPwmPowerSource 1167
FirstQt, YQt 1191
FirstRealTimeClock, YRealTimeClock 1229
FirstRefFrame, YRefFrame 1257
FirstRelay, YRelay 1293
FirstSensor, YSensor 1329
FirstSerialPort, YSerialPort 1369
FirstServo, YServo 1425
FirstTemperature, YTemperature 1460
FirstTilt, YTilt 1501
FirstVoc, YVoc 1540
FirstVoltage, YVoltage 1579
FirstVSource, YVSource 1617
FirstWakeUpMonitor, YWakeUpMonitor 1646
FirstWakeUpSchedule, YWakeUpSchedule 1681
FirstWatchdog, YWatchdog 1718
FirstWireless, YWireless 1762
forgetAllDataStreams, YDataLogger 306
format_fs, YFiles 525
Formatted 335
Frame 1254
FreeAPI, YAPI 15
functionCount, YModule 836
functionId, YModule 837
functionName, YModule 838
Functions 11
functionValue, YModule 839

G

General 11
GenericSensor 548
get_3DCalibrationHint, YRefFrame 1260
get_3DCalibrationLogMsg, YRefFrame 1261
get_3DCalibrationProgress, YRefFrame 1262
get_3DCalibrationStage, YRefFrame 1263
get_3DCalibrationStageProgress, YRefFrame 1264
get_adminPassword, YNetwork 924
get_advertisedValue, YAccelerometer 38
get_advertisedValue, YAltitude 80
get_advertisedValue, YAnButton 121
get_advertisedValue, YCarbonDioxide 160
get_advertisedValue, YColorLed 197
get_advertisedValue, YCompass 228
get_advertisedValue, YCurrent 268
get_advertisedValue, YDataLogger 307
get_advertisedValue, YDigitalIO 378
get_advertisedValue, YDisplay 423
get_advertisedValue, YDualPower 499
get_advertisedValue, YFiles 526
get_advertisedValue, YGenericSensor 554
get_advertisedValue, YGyro 603
get_advertisedValue, YHubPort 652
get_advertisedValue, YHumidity 679
get_advertisedValue, YLed 716
get_advertisedValue, YLightSensor 746
get_advertisedValue, YMagnetometer 787
get_advertisedValue, YMotor 883
get_advertisedValue, YNetwork 925
get_advertisedValue, YOsControl 978
get_advertisedValue, YPower 1003
get_advertisedValue, YPressure 1046
get_advertisedValue, YPwmInput 1085
get_advertisedValue, YPwmOutput 1133
get_advertisedValue, YPwmPowerSource 1169
get_advertisedValue, YQt 1194
get_advertisedValue, YRealTimeClock 1231
get_advertisedValue, YRefFrame 1265
get_advertisedValue, YRelay 1296
get_advertisedValue,YSensor 1332
get_advertisedValue, YSerialPort 1372
get_advertisedValue, YServo 1427
get_advertisedValue, YTemperature 1463
get_advertisedValue, YTilt 1504
get_advertisedValue, YVoc 1543
get_advertisedValue, YVoltage 1582
get_advertisedValue, YVSource 1618
get_advertisedValue, YWakeUpMonitor 1648
get_advertisedValue, YWakeUpSchedule 1683
get_advertisedValue, YWatchdog 1721
get_advertisedValue, YWireless 1765
get_allSettings, YModule 840
get_analogCalibration, YAnButton 122
get_autoStart, YDataLogger 308
get_autoStart, YWatchdog 1722
get_averageValue, YDataRun 335
get_averageValue, YDataStream 358
get_averageValue, YMeasure 823
get_baudRate, YHubPort 653
get_beacon, YModule 841
get_beaconDriven, YDataLogger 309
get_bearing, YRefFrame 1266
get_bitDirection, YDigitalIO 379
get_bitOpenDrain, YDigitalIO 380
get_bitPolarity, YDigitalIO 381
get_bitState, YDigitalIO 382
get_blinking, YLed 717
get_brakingForce, YMotor 884
get_brightness, YDisplay 424
get_calibratedValue, YAnButton 123
get_calibrationMax, YAnButton 124
get_calibrationMin, YAnButton 125
get_callbackCredentials, YNetwork 926
get_callbackEncoding, YNetwork 927
get_callbackMaxDelay, YNetwork 928
get_callbackMethod, YNetwork 929
get_callbackMinDelay, YNetwork 930
get_callbackUrl, YNetwork 931
get_channel, YWireless 1766
get_columnCount, YDataStream 359
get_columnNames, YDataStream 360
get_cosPhi, YPower 1004
get_countdown, YRelay 1297
get_countdown, YWatchdog 1723
get_CTS, YSerialPort 1371
get_currentRawValue, YAccelerometer 39
get_currentRawValue, YAltitude 81
get_currentRawValue, YCarbonDioxide 161
get_currentRawValue, YCompass 229
get_currentRawValue, YCurrent 269
get_currentRawValue, YGenericSensor 555
get_currentRawValue, YGyro 604
get_currentRawValue, YHumidity 680
get_currentRawValue, YLightSensor 747
get_currentRawValue, YMagnetometer 788
get_currentRawValue, YPower 1005
get_currentRawValue, YPressure 1047
get_currentRawValue, YPwmInput 1086
get_currentRawValue, YQt 1195
get_currentRawValue, YSensor 1333
get_currentRawValue, YTemperature 1464
get_currentRawValue, YTilt 1505
get_currentRawValue, YVoc 1544
get_currentRawValue, YVoltage 1583
get_currentRunIndex, YDataLogger 310
get_currentValue, YAccelerometer 40
get_currentValue, YAltitude 82
get_currentValue, YCarbonDioxide 162
get_currentValue, YCompass 230
get_currentValue, YCurrent 270
get_currentValue, YGenericSensor 556
get_currentValue, YGyro 605
get_currentValue, YHumidity 681
get_currentValue, YLightSensor 748
get_currentValue, YMagnetometer 789

get_currentValue, YPower 1006
get_currentValue, YPressure 1048
get_currentValue, YPwmInput 1087
get_currentValue, YQt 1196
get_currentValue, YSensor 1334
get_currentValue, YTemperature 1465
get_currentValue, YTilt 1506
get_currentValue, YVoc 1545
get_currentValue, YVoltage 1584
get_cutOffVoltage, YMotor 885
get_data, YDataStream 361
get_dataRows, YDataStream 362
get_dataSamplesIntervalMs, YDataStream 363
get_dataSets, YDataLogger 311
get_dataStreams, YDataLogger 312
get_dateTime, YRealTimeClock 1232
get_detectedWlans, YWireless 1767
get_discoverable, YNetwork 932
get_display, YDisplayLayer 475
get_displayHeight, YDisplay 425
get_displayHeight, YDisplayLayer 476
get_displayLayer, YDisplay 426
get_displayType, YDisplay 427
get_displayWidth, YDisplay 428
get_displayWidth, YDisplayLayer 477
get_drivingForce, YMotor 886
get_duration, YDataRun 336
get_duration, YDataStream 364
get_dutyCycle, YPwmInput 1088
get_dutyCycle, YPwmOutput 1134
get_dutyCycleAtPowerOn, YPwmOutput 1135
get_enabled, YDisplay 429
get_enabled, YHubPort 654
get_enabled, YPwmOutput 1136
get_enabled, YServo 1428
get_enabledAtPowerOn, YPwmOutput 1137
get_enabledAtPowerOn, YServo 1429
get_endTimeUTC, YDataSet 346
get_endTimeUTC, YMeasure 824
get_errCount, YSerialPort 1373
getErrorMessage, YAccelerometer 41
getErrorMessage, YAltitude 83
getErrorMessage, YAnButton 126
getErrorMessage, YCarbonDioxide 163
getErrorMessage, YColorLed 198
getErrorMessage, YCompass 231
getErrorMessage, YCurrent 271
getErrorMessage, YDataLogger 313
getErrorMessage, YDigitalIO 383
getErrorMessage, YDisplay 430
getErrorMessage, YDualPower 500
getErrorMessage, YFiles 527
getErrorMessage, YGenericSensor 557
getErrorMessage, YGyro 606
getErrorMessage, YHubPort 655
getErrorMessage, YHumidity 682
getErrorMessage, YLed 718
getErrorMessage, YLightSensor 749
getErrorMessage, YMagnetometer 790
getErrorMessage, YModule 842
getErrorMessage, YMotor 887
getErrorMessage, YNetwork 933
getErrorMessage, YOsControl 979
getErrorMessage, YPower 1007
getErrorMessage, YPressure 1049
getErrorMessage, YPwmInput 1089
getErrorMessage, YPwmOutput 1138
getErrorMessage, YPwmPowerSource 1170
getErrorMessage, YQt 1197
getErrorMessage, YRealTimeClock 1233
getErrorMessage, YRefFrame 1267
getErrorMessage, YRelay 1298
getErrorMessage, YSensor 1335
getErrorMessage, YSerialPort 1374
getErrorMessage, YServo 1430
getErrorMessage, YTemperature 1466
getErrorMessage, YTilt 1507
getErrorMessage, YVoc 1546
getErrorMessage, YVoltage 1585
getErrorMessage, YVSource 1619
getErrorMessage, YWakeUpMonitor 1649
getErrorMessage, YWakeUpSchedule 1684
getErrorMessage, YWatchdog 1724
getErrorMessage, YWireless 1768
get_errorType, YAccelerometer 42
get_errorType, YAltitude 84
get_errorType, YAnButton 127
get_errorType, YCarbonDioxide 164
get_errorType, YColorLed 199
get_errorType, YCompass 232
get_errorType, YCurrent 272
get_errorType, YDataLogger 314
get_errorType, YDigitalIO 384
get_errorType, YDisplay 431
get_errorType, YDualPower 501
get_errorType, YFiles 528
get_errorType, YGenericSensor 558
get_errorType, YGyro 607
get_errorType, YHubPort 656
get_errorType, YHumidity 683
get_errorType, YLed 719
get_errorType, YLightSensor 750
get_errorType, YMagnetometer 791
get_errorType, YModule 843
get_errorType, YMotor 888
get_errorType, YNetwork 934
get_errorType, YOsControl 980
get_errorType, YPower 1008
get_errorType, YPressure 1050
get_errorType, YPwmInput 1090
get_errorType, YPwmOutput 1139
get_errorType, YPwmPowerSource 1171
get_errorType, YQt 1198
get_errorType, YRealTimeClock 1234
get_errorType, YRefFrame 1268
get_errorType, YRelay 1299
get_errorType, YSensor 1336
get_errorType, YSerialPort 1375

get_errorType, YServo 1431
get_errorType, YTemperature 1467
get_errorType, YTilt 1508
get_errorType, YVoc 1547
get_errorType, YVoltage 1586
get_errorType, YVSource 1620
get_errorType, YWakeUpMonitor 1650
get_errorType, YWakeUpSchedule 1685
get_errorType, YWatchdog 1725
get_errorType, YWireless 1769
get_extPowerFailure, YVSource 1621
get_extVoltage, YDualPower 502
get_failSafeTimeout, YMotor 889
get_failure, YVSource 1622
get_filesCount, YFiles 529
get_firmwareRelease, YModule 844
get_freeSpace, YFiles 530
get_frequency, YMotor 890
get_frequency, YPwmInput 1091
get_frequency, YPwmOutput 1140
get_friendlyName, YAccelerometer 43
get_friendlyName, YAltitude 85
get_friendlyName, YAnButton 128
get_friendlyName, YCarbonDioxide 165
get_friendlyName, YColorLed 200
get_friendlyName, YCompass 233
get_friendlyName, YCurrent 273
get_friendlyName, YDataLogger 315
get_friendlyName, YDigitalIO 385
get_friendlyName, YDisplay 432
get_friendlyName, YDualPower 503
get_friendlyName, YFiles 531
get_friendlyName, YGenericSensor 559
get_friendlyName, YGyro 608
get_friendlyName, YHubPort 657
get_friendlyName, YHumidity 684
get_friendlyName, YLed 720
get_friendlyName, YLightSensor 751
get_friendlyName, YMagnetometer 792
get_friendlyName, YMotor 891
get_friendlyName, YNetwork 935
get_friendlyName, YOsControl 981
get_friendlyName, YPower 1009
get_friendlyName, YPressure 1051
get_friendlyName, YPwmInput 1092
get_friendlyName, YPwmOutput 1141
get_friendlyName, YPwmPowerSource 1172
get_friendlyName, YQt 1199
get_friendlyName, YRealTimeClock 1235
get_friendlyName, YRefFrame 1269
get_friendlyName, YRelay 1300
get_friendlyName, YSensor 1337
get_friendlyName, YSerialPort 1376
get_friendlyName, YServo 1432
get_friendlyName, YTemperature 1468
get_friendlyName, YTilt 1509
get_friendlyName, YVoc 1548
get_friendlyName, YVoltage 1587
get_friendlyName, YWakeUpMonitor 1651
get_friendlyName, YWakeUpSchedule 1686
get_friendlyName, YWatchdog 1726
get_friendlyName, YWireless 1770
get_functionDescriptor, YAccelerometer 44
get_functionDescriptor, YAltitude 86
get_functionDescriptor, YAnButton 129
get_functionDescriptor, YCarbonDioxide 166
get_functionDescriptor, YColorLed 201
get_functionDescriptor, YCompass 234
get_functionDescriptor, YCurrent 274
get_functionDescriptor, YDataLogger 316
get_functionDescriptor, YDigitalIO 386
get_functionDescriptor, YDisplay 433
get_functionDescriptor, YDualPower 504
get_functionDescriptor, YFiles 532
get_functionDescriptor, YGenericSensor 560
get_functionDescriptor, YGyro 609
get_functionDescriptor, YHubPort 658
get_functionDescriptor, YHumidity 685
get_functionDescriptor, YLed 721
get_functionDescriptor, YLightSensor 752
get_functionDescriptor, YMagnetometer 793
get_functionDescriptor, YMotor 892
get_functionDescriptor, YNetwork 936
get_functionDescriptor, YOsControl 982
get_functionDescriptor, YPower 1010
get_functionDescriptor, YPressure 1052
get_functionDescriptor, YPwmInput 1093
get_functionDescriptor, YPwmOutput 1142
get_functionDescriptor, YPwmPowerSource 1173
get_functionDescriptor, YQt 1200
get_functionDescriptor, YRealTimeClock 1236
get_functionDescriptor, YRefFrame 1270
get_functionDescriptor, YRelay 1301
get_functionDescriptor, YSensor 1338
get_functionDescriptor, YSerialPort 1377
get_functionDescriptor, YServo 1433
get_functionDescriptor, YTemperature 1469
get_functionDescriptor, YTilt 1510
get_functionDescriptor, YVoc 1549
get_functionDescriptor, YVoltage 1588
get_functionDescriptor, YVSource 1623
get_functionDescriptor, YWakeUpMonitor 1652
get_functionDescriptor, YWakeUpSchedule 1687
get_functionDescriptor, YWatchdog 1727
get_functionDescriptor, YWireless 1771
get_functionId, YAccelerometer 45
get_functionId, YAltitude 87
get_functionId, YAnButton 130
get_functionId, YCarbonDioxide 167
get_functionId, YColorLed 202
get_functionId, YCompass 235
get_functionId, YCurrent 275
get_functionId, YDataLogger 317
get_functionId, YDataSet 347
get_functionId, YDigitalIO 387
get_functionId, YDisplay 434
get_functionId, YDualPower 505
get_functionId, YFiles 533

get_functionId, YGenericSensor 561
get_functionId, YGyro 610
get_functionId, YHubPort 659
get_functionId, YHumidity 686
get_functionId, YLed 722
get_functionId, YLightSensor 753
get_functionId, YMagnetometer 794
get_functionId, YMotor 893
get_functionId, YNetwork 937
get_functionId, YOsControl 983
get_functionId, YPower 1011
get_functionId, YPressure 1053
get_functionId, YPwmInput 1094
get_functionId, YPwmOutput 1143
get_functionId, YPwmPowerSource 1174
get_functionId, YQt 1201
get_functionId, YRealTimeClock 1237
get_functionId, YRefFrame 1271
get_functionId, YRelay 1302
get_functionId, YSensor 1339
get_functionId, YSerialPort 1378
get_functionId,YServo 1434
get_functionId, YTemperature 1470
get_functionId, YTilt 1511
get_functionId, YVoc 1550
get_functionId, YVoltage 1589
get_functionId, YWakeUpMonitor 1653
get_functionId, YWakeUpSchedule 1688
get_functionId, YWatchdog 1728
get_functionId, YWireless 1772
get_hardwareId, YAccelerometer 46
get_hardwareId, YAltitude 88
get_hardwareId, YAnButton 131
get_hardwareId, YCarbonDioxide 168
get_hardwareId, YColorLed 203
get_hardwareId, YCompass 236
get_hardwareId, YCurrent 276
get_hardwareId, YDataLogger 318
get_hardwareId, YDataSet 348
get_hardwareId, YDigitalIO 388
get_hardwareId, YDisplay 435
get_hardwareId, YDualPower 506
get_hardwareId, YFiles 534
get_hardwareId, YGenericSensor 562
get_hardwareId, YGyro 611
get_hardwareId, YHubPort 660
get_hardwareId, YHumidity 687
get_hardwareId, YLed 723
get_hardwareId, YLightSensor 754
get_hardwareId, YMagnetometer 795
get_hardwareId, YModule 845
get_hardwareId, YMotor 894
get_hardwareId, YNetwork 938
get_hardwareId, YOsControl 984
get_hardwareId, YPower 1012
get_hardwareId, YPressure 1054
get_hardwareId, YPwmInput 1095
get_hardwareId, YPwmOutput 1144
get_hardwareId, YPwmPowerSource 1175
get_hardwareId, YQt 1202
get_hardwareId, YRealTimeClock 1238
get_hardwareId, YRefFrame 1272
get_hardwareId, YRelay 1303
get_hardwareId, YSensor 1340
get_hardwareId, YSerialPort 1379
get_hardwareId, YServo 1435
get_hardwareId, YTemperature 1471
get_hardwareId, YTilt 1512
get_hardwareId, YVoc 1551
get_hardwareId, YVoltage 1590
get_hardwareId, YWakeUpMonitor 1654
get_hardwareId, YWakeUpSchedule 1689
get_hardwareId, YWatchdog 1729
get_hardwareId, YWireless 1773
get_heading, YGyro 612
get_highestValue, YAccelerometer 47
get_highestValue, YAltitude 89
get_highestValue, YCarbonDioxide 169
get_highestValue, YCompass 237
get_highestValue, YCurrent 277
get_highestValue, YGenericSensor 563
get_highestValue, YGyro 613
get_highestValue, YHumidity 688
get_highestValue, YLightSensor 755
get_highestValue, YMagnetometer 796
get_highestValue, YPower 1013
get_highestValue, YPressure 1055
get_highestValue, YPwmInput 1096
get_highestValue, YQt 1203
get_highestValue, YSensor 1341
get_highestValue, YTemperature 1472
get_highestValue, YTilt 1513
get_highestValue, YVoc 1552
get_highestValue, YVoltage 1591
get_hours, YWakeUpSchedule 1690
get_hslColor, YColorLed 204
get_icon2d, YModule 846
get_ipAddress, YNetwork 939
get_isPressed, YAnButton 132
get_lastLogs, YSerialPort 1380
get_lastMsg, YSerialPort 1380
get_lastTimePressed, YAnButton 133
get_lastTimeReleased, YAnButton 134
get_layerCount, YDisplay 436
get_layerHeight, YDisplay 437
get_layerHeight, YDisplayLayer 478
get_layerWidth, YDisplay 438
get_layerWidth, YDisplayLayer 479
get_linkQuality, YWireless 1774
get_list, YFiles 535
get_logFrequency, YAccelerometer 48
get_logFrequency, YAltitude 90
get_logFrequency, YCarbonDioxide 170
get_logFrequency, YCompass 238
get_logFrequency, YCurrent 278
get_logFrequency, YGenericSensor 564
get_logFrequency, YGyro 614
get_logFrequency, YHumidity 689

get_logFrequency, YLightSensor 756
get_logFrequency, YMagnetometer 797
get_logFrequency, YPower 1014
get_logFrequency, YPressure 1056
get_logFrequency, YPwmInput 1097
get_logFrequency, YQt 1204
get_logFrequency, YSensor 1342
get_logFrequency, YTTemperature 1473
get_logFrequency, YTilt 1514
get_logFrequency, YVoc 1553
get_logFrequency, YVoltage 1592
get_logicalName, YAccelerometer 49
get_logicalName, YAltitude 91
get_logicalName, YAnButton 135
get_logicalName, YCarbonDioxide 171
get_logicalName, YColorLed 205
get_logicalName, YCompass 239
get_logicalName, YCurrent 279
get_logicalName, YDataLogger 319
get_logicalName, YDigitalIO 389
get_logicalName, YDisplay 439
get_logicalName, YDualPower 507
get_logicalName, YFiles 536
get_logicalName, YGenericSensor 565
get_logicalName, YGyro 615
get_logicalName, YHubPort 661
get_logicalName, YHumidity 690
get_logicalName, YLed 724
get_logicalName, YLightSensor 757
get_logicalName, YMagnetometer 798
get_logicalName, YModule 848
get_logicalName, YMotor 895
get_logicalName, YNetwork 940
get_logicalName, YOsControl 985
get_logicalName, YPower 1015
get_logicalName, YPressure 1057
get_logicalName, YPwmInput 1098
get_logicalName, YPwmOutput 1145
get_logicalName, YPwmPowerSource 1176
get_logicalName, YQt 1205
get_logicalName, YRealTimeClock 1239
get_logicalName, YRefFrame 1273
get_logicalName, YRelay 1304
get_logicalName, YSensor 1343
get_logicalName, YSerialPort 1381
get_logicalName, YServo 1436
get_logicalName, YTTemperature 1474
get_logicalName, YTilt 1515
get_logicalName, YVoc 1554
get_logicalName, YVoltage 1593
get_logicalName, YVSource 1624
get_logicalName, YWakeUpMonitor 1655
get_logicalName, YWakeUpSchedule 1691
get_logicalName, YWatchdog 1730
get_logicalName, YWireless 1775
get_lowestValue, YAccelerometer 50
get_lowestValue, YAltitude 92
get_lowestValue, YCarbonDioxide 172
get_lowestValue, YCompass 240
get_lowestValue, YCurrent 280
get_lowestValue, YGenericSensor 566
get_lowestValue, YGyro 616
get_lowestValue, YHumidity 691
get_lowestValue, YLightSensor 758
get_lowestValue, YMagnetometer 799
get_lowestValue, YPower 1016
get_lowestValue, YPressure 1058
get_lowestValue, YPwmInput 1099
get_lowestValue, YQt 1206
get_lowestValue, YSensor 1344
get_lowestValue, YTTemperature 1475
get_lowestValue, YTilt 1516
get_lowestValue, YVoc 1555
get_lowestValue, YVoltage 1594
get_luminosity, YLed 725
get_luminosity, YModule 849
get_macAddress, YNetwork 941
get_magneticHeading, YCompass 241
get_maxTimeOnStateA, YRelay 1305
get_maxTimeOnStateA, YWatchdog 1731
get_maxTimeOnStateB, YRelay 1306
get_maxTimeOnStateB, YWatchdog 1732
get_maxValue, YDataRun 337
get_maxValue, YDataStream 365
get_maxValue, YMeasure 825
get_measureNames, YDataRun 338
get_measures, YDataSet 349
get_measureType, YLightSensor 759
get_message, YWireless 1776
get_meter, YPower 1017
get_meterTimer, YPower 1018
get_minutes, YWakeUpSchedule 1692
get_minutesA, YWakeUpSchedule 1693
get_minutesB, YWakeUpSchedule 1694
get_minValue, YDataRun 339
get_minValue, YDataStream 366
get_minValue, YMeasure 826
get_module, YAccelerometer 51
get_module, YAltitude 93
get_module, YAnButton 136
get_module, YCarbonDioxide 173
get_module, YColorLed 206
get_module, YCompass 242
get_module, YCurrent 281
get_module, YDataLogger 320
get_module, YDigitalIO 390
get_module, YDisplay 440
get_module, YDualPower 508
get_module, YFiles 537
get_module, YGenericSensor 567
get_module, YGyro 617
get_module, YHubPort 662
get_module, YHumidity 692
get_module, YLed 726
get_module, YLightSensor 760
get_module, YMagnetometer 800
get_module, YMotor 896
get_module, YNetwork 942

get_module, YOsControl 986
get_module, YPower 1019
get_module, YPressure 1059
get_module, YPwmInput 1100
get_module, YPwmOutput 1146
get_module, YPwmPowerSource 1177
get_module, YQt 1207
get_module, YRealTimeClock 1240
get_module, YRefFrame 1274
get_module, YRelay 1307
get_module, YSensor 1345
get_module, YSerialPort 1382
get_module, YServo 1437
get_module, YTemperature 1476
get_module, YTilt 1517
get_module, YVoc 1556
get_module, YVoltage 1595
get_module, YVSource 1625
get_module, YWakeUpMonitor 1656
get_module, YWakeUpSchedule 1695
get_module, YWatchdog 1733
get_module, YWireless 1777
get_monthDays, YWakeUpSchedule 1696
get_months, YWakeUpSchedule 1697
get_motorStatus, YMotor 897
get_mountOrientation, YRefFrame 1275
get_mountPosition, YRefFrame 1276
get_msgCount, YSerialPort 1383
get_neutral, YServo 1438
get_nextOccurrence, YWakeUpSchedule 1698
get_nextWakeUp, YWakeUpMonitor 1657
get_orientation, YDisplay 441
get_output, YRelay 1308
get_output, YWatchdog 1734
get_outputVoltage, YDigitalIO 391
get_overCurrent, YVSource 1626
get_overCurrentLimit, YMotor 898
get_overHeat, YVSource 1627
get_overLoad, YVSource 1628
get_period, YPwmInput 1101
get_period, YPwmOutput 1147
get_persistentSettings, YModule 850
get_pitch, YGyro 618
get_poeCurrent, YNetwork 943
get_portDirection, YDigitalIO 392
get_portOpenDrain, YDigitalIO 393
get_portPolarity, YDigitalIO 394
get_portSize, YDigitalIO 395
get_portState, YDigitalIO 396
get_portState, YHubPort 663
get_position, YServo 1439
get_positionAtPowerOn, YServo 1440
get_power, YLed 727
get_powerControl, YDualPower 509
get_powerDuration, YWakeUpMonitor 1658
get_powerMode, YPwmPowerSource 1178
get_powerState, YDualPower 510
get_preview, YDataSet 350
get_primaryDNS, YNetwork 944
get_productId, YModule 851
get_productName, YModule 852
get_productRelease, YModule 853
get_progress, YDataSet 351
get_protocol, YSerialPort 1384
get_pulseCounter, YAnButton 137
get_pulseCounter, YPwmInput 1102
get_pulseDuration, YPwmInput 1103
get_pulseDuration, YPwmOutput 1148
get_pulseTimer, YAnButton 138
get_pulseTimer, YPwmInput 1104
get_pulseTimer, YRelay 1309
get_pulseTimer, YWatchdog 1735
get_pwmReportMode, YPwmInput 1105
get_qnh, YAltitude 94
get_quaternionW, YGyro 619
get_quaternionX, YGyro 620
get_quaternionY, YGyro 621
get_quaternionZ, YGyro 622
get_range, YServo 1441
get_rawValue, YAnButton 139
get_readiness, YNetwork 945
get_rebootCountdown, YModule 854
get_recordedData, YAccelerometer 52
get_recordedData, YAltitude 95
get_recordedData, YCarbonDioxide 174
get_recordedData, YCompass 243
get_recordedData, YCurrent 282
get_recordedData, YGenericSensor 568
get_recordedData, YGyro 623
get_recordedData, YHumidity 693
get_recordedData, YLightSensor 761
get_recordedData, YMagnetometer 801
get_recordedData, YPower 1020
get_recordedData, YPressure 1060
get_recordedData, YPwmInput 1106
get_recordedData, YQt 1208
get_recordedData, YSensor 1346
get_recordedData, YTemperature 1477
get_recordedData, YTilt 1518
get_recordedData, YVoc 1557
get_recordedData, YVoltage 1596
get_recording, YDataLogger 321
get_regulationFailure, YVSource 1629
get_reportFrequency, YAccelerometer 53
get_reportFrequency, YAltitude 96
get_reportFrequency, YCarbonDioxide 175
get_reportFrequency, YCompass 244
get_reportFrequency, YCurrent 283
get_reportFrequency, YGenericSensor 569
get_reportFrequency, YGyro 624
get_reportFrequency, YHumidity 694
get_reportFrequency, YLightSensor 762
get_reportFrequency, YMagnetometer 802
get_reportFrequency, YPower 1021
get_reportFrequency, YPressure 1061
get_reportFrequency, YPwmInput 1107
get_reportFrequency, YQt 1209
get_reportFrequency, YSensor 1347

get_reportFrequency, YTemperature 1478
get_reportFrequency, YTilt 1519
get_reportFrequency, YVoc 1558
get_reportFrequency, YVoltage 1597
get_resolution, YAccelerometer 54
get_resolution, YAltitude 97
get_resolution, YCarbonDioxide 176
get_resolution, YCompass 245
get_resolution, YCurrent 284
get_resolution, YGenericSensor 570
get_resolution, YGyro 625
get_resolution, YHumidity 695
get_resolution, YLightSensor 763
get_resolution, YMagnetometer 803
get_resolution, YPower 1022
get_resolution, YPressure 1062
get_resolution, YPwmInput 1108
get_resolution, YQt 1210
get_resolution,YSensor 1348
get_resolution, YTemperature 1479
get_resolution, YTilt 1520
get_resolution, YVoc 1559
get_resolution, YVoltage 1598
get_rgbColor, YColorLed 207
get_rgbColorAtPowerOn, YColorLed 208
get_roll, YGyro 626
get_router, YNetwork 946
getRowCount, YDataStream 367
get_runIndex, YDataStream 368
get_running, YWatchdog 1736
get_rxCount, YSerialPort 1385
get_secondaryDNS, YNetwork 947
get_security, YWireless 1778
get_sensitivity, YAnButton 140
get_sensorType, YTemperature 1480
get_serialMode, YSerialPort 1386
get_serialNumber, YModule 855
get_shutdownCountdown, YOsControl 987
get_signalBias, YGenericSensor 571
get_signalRange, YGenericSensor 572
get_signalUnit, YGenericSensor 573
get_signalValue, YGenericSensor 574
get_sleepCountdown, YWakeUpMonitor 1659
get_ssId, YWireless 1779
get_starterTime, YMotor 899
get_startTime, YDataStream 369
get_startTimeUTC, YDataRun 340
get_startTimeUTC, YDataSet 352
get_startTimeUTC, YDataStream 370
get_startTimeUTC, YMeasure 827
get_startupSeq, YDisplay 442
get_state, YRelay 1310
get_state, YWatchdog 1737
get_stateAtPowerOn, YRelay 1311
get_stateAtPowerOn, YWatchdog 1738
get_subnetMask, YNetwork 948
get_summary, YDataSet 353
get_timeSet, YRealTimeClock 1241
get_timeUTC, YDataLogger 322
get_triggerDelay, YWatchdog 1739
get_triggerDuration, YWatchdog 1740
get_txCount, YSerialPort 1387
get_unit, YAccelerometer 55
get_unit, YAltitude 98
get_unit, YCarbonDioxide 177
get_unit, YCompass 246
get_unit, YCurrent 285
get_unit, YDataSet 354
get_unit, YGenericSensor 575
get_unit, YGyro 627
get_unit, YHumidity 696
get_unit, YLightSensor 764
get_unit, YMagnetometer 804
get_unit, YPower 1023
get_unit, YPressure 1063
get_unit, YPwmInput 1109
get_unit, YQt 1211
get_unit, YSensor 1349
get_unit, YTemperature 1481
get_unit, YTilt 1521
get_unit, YVoc 1560
get_unit, YVoltage 1599
get_unit, YVSource 1630
get_unixTime, YRealTimeClock 1242
get_upTime, YModule 856
get_usbCurrent, YModule 857
get_userData, YAccelerometer 56
get_userData, YAltitude 99
get_userData, YAnButton 141
get_userData, YCarbonDioxide 178
get_userData, YColorLed 209
get_userData, YCompass 247
get_userData, YCurrent 286
get_userData, YDataLogger 323
get_userData, YDigitalIO 397
get_userData, YDisplay 443
get_userData, YDualPower 511
get_userData, YFiles 538
get_userData, YGenericSensor 576
get_userData, YGyro 628
get_userData, YHubPort 664
get_userData, YHumidity 697
get_userData, YLed 728
get_userData, YLightSensor 765
get_userData, YMagnetometer 805
get_userData, YModule 858
get_userData, YMotor 900
get_userData, YNetwork 949
get_userData, YOsControl 988
get_userData, YPower 1024
get_userData, YPressure 1064
get_userData, YPwmInput 1110
get_userData, YPwmOutput 1149
get_userData, YPwmPowerSource 1179
get_userData, YQt 1212
get_userData, YRealTimeClock 1243
get_userData, YRefFrame 1277
get_userData, YRelay 1312

get(userData, YSensor 1350
get(userData, YSerialPort 1388
get(userData, YServo 1442
get(userData, YTTemperature 1482
get(userData, YTilt 1522
get(userData, YVoc 1561
get(userData, YVoltage 1600
get(userData, YVSource 1631
get(userData, YWakeUpMonitor 1660
get(userData, YWakeUpSchedule 1699
get(userData, YWatchdog 1741
get(userData, YWireless 1780
get(userPassword, YNetwork 950
get(userVar, YModule 859
get_utcOffset, YRealTimeClock 1244
get_valueCount, YDataRun 341
get_valueInterval, YDataRun 342
get_valueRange, YGenericSensor 577
get_voltage, YVSource 1632
get_wakeUpReason, YWakeUpMonitor 1661
get_wakeUpState, YWakeUpMonitor 1662
get_weekDays, YWakeUpSchedule 1700
get_wwwWatchdogDelay, YNetwork 951
get_xValue, YAccelerometer 57
get_xValue, YGyro 629
get_xValue, YMagnetometer 806
get_yValue, YAccelerometer 58
get_yValue, YGyro 630
get_yValue, YMagnetometer 807
get_zValue, YAccelerometer 59
get_zValue, YGyro 631
get_zValue, YMagnetometer 808
GetAPIVersion, YAPI 16
GetTickCount, YAPI 17
Gyroscope 597

H

HandleEvents, YAPI 18
hide, YDisplayLayer 480
hslMove, YColorLed 210
Humidity 673

I

InitAPI, YAPI 19
Interface 32, 74, 116, 154, 193, 222, 262, 301, 372, 416, 463, 495, 520, 548, 597, 648, 673, 712, 739, 781, 829, 876, 917, 997, 1040, 1079, 1127, 1165, 1188, 1227, 1290, 1326, 1365, 1422, 1457, 1498, 1537, 1576, 1615, 1643, 1678, 1715, 1760
Introduction 1
isOnline, YAccelerometer 60
isOnline, YAltitude 100
isOnline, YAnButton 142
isOnline, YCarbonDioxide 179
isOnline, YColorLed 211
isOnline, YCompass 248
isOnline, YCurrent 287

isOnline, YDataLogger 324
isOnline, YDigitalIO 398
isOnline, YDisplay 444
isOnline, YDualPower 512
isOnline, YFiles 539
isOnline, YGenericSensor 578
isOnline, YGyro 632
isOnline, YHubPort 665
isOnline, YHumidity 698
isOnline, YLed 729
isOnline, YLightSensor 766
isOnline, YMagnetometer 809
isOnline, YModule 860
isOnline, YMotor 901
isOnline, YNetwork 952
isOnline, YOsControl 989
isOnline, YPower 1025
isOnline, YPressure 1065
isOnline, YPwmInput 1111
isOnline, YPwmOutput 1150
isOnline, YPwmPowerSource 1180
isOnline, YQt 1213
isOnline, YRealTimeClock 1245
isOnline, YRefFrame 1278
isOnline, YRelay 1313
isOnline, YSensor 1351
isOnline, YSerialPort 1389
isOnline, YServo 1443
isOnline, YTTemperature 1483
isOnline, YTilt 1523
isOnline, YVoc 1562
isOnline, YVoltage 1601
isOnline, YVSource 1633
isOnline, YWakeUpMonitor 1663
isOnline, YWakeUpSchedule 1701
isOnline, YWatchdog 1742
isOnline, YWireless 1781

J

joinNetwork, YWireless 1782

K

keepALive, YMotor 902

L

Library 3
LightSensor 739
lineTo, YDisplayLayer 481
load, YAccelerometer 61
load, YAltitude 101
load, YAnButton 143
load, YCarbonDioxide 180
load, YColorLed 212
load, YCompass 249
load, YCurrent 288
load, YDataLogger 325
load, YDigitalIO 399

load, YDisplay 445
load, YDualPower 513
load, YFiles 540
load, YGenericSensor 579
load, YGyro 633
load, YHubPort 666
load, YHumidity 699
load, YLed 730
load, YLightSensor 767
load, YMagnetometer 810
load, YModule 861
load, YMotor 903
load, YNetwork 953
load, YOsControl 990
load, YPower 1026
load, YPressure 1066
load, YPwmInput 1112
load, YPwmOutput 1151
load, YPwmPowerSource 1181
load, YQt 1214
load, YRealTimeClock 1246
load, YRefFrame 1279
load, YRelay 1314
load,YSensor 1352
load, YSerialPort 1390
load, YServo 1444
load, YTemperature 1484
load, YTilt 1524
load, YVoc 1563
load, YVoltage 1602
load, YVSource 1634
load, YWakeUpMonitor 1664
load, YWakeUpSchedule 1702
load, YWatchdog 1743
load, YWireless 1783
loadCalibrationPoints, YAccelerometer 62
loadCalibrationPoints, YAltitude 102
loadCalibrationPoints, YCarbonDioxide 181
loadCalibrationPoints, YCompass 250
loadCalibrationPoints, YCurrent 289
loadCalibrationPoints, YGenericSensor 580
loadCalibrationPoints, YGyro 634
loadCalibrationPoints, YHumidity 700
loadCalibrationPoints, YLightSensor 768
loadCalibrationPoints, YMagnetometer 811
loadCalibrationPoints, YPower 1027
loadCalibrationPoints, YPressure 1067
loadCalibrationPoints, YPwmInput 1113
loadCalibrationPoints, YQt 1215
loadCalibrationPoints, YSensor 1353
loadCalibrationPoints, YTemperature 1485
loadCalibrationPoints, YTilt 1525
loadCalibrationPoints, YVoc 1564
loadCalibrationPoints, YVoltage 1603
loadMore, YDataSet 355

M

Magnetometer 781
Measured 823

modbusReadBits, YSerialPort 1391
modbusReadInputBits, YSerialPort 1392
modbusReadInputRegisters, YSerialPort 1393
modbusReadRegisters, YSerialPort 1394
modbusWriteAndReadRegisters, YSerialPort 1395
modbusWriteBit, YSerialPort 1396
modbusWriteBits, YSerialPort 1397
modbusWriteRegister, YSerialPort 1398
modbusWriteRegisters, YSerialPort 1399
Module 5, 829
more3DCalibration, YRefFrame 1280
Motor 876
move, YServo 1445
moveTo, YDisplayLayer 482

N

Network 917
newSequence, YDisplay 446
nextAccelerometer, YAccelerometer 63
nextAltitude, YAltitude 103
nextAnButton, YAnButton 144
nextCarbonDioxide, YCarbonDioxide 182
nextColorLed, YColorLed 213
nextCompass, YCompass 251
nextCurrent, YCurrent 290
nextDataLogger, YDataLogger 326
nextDigitalIO, YDigitalIO 400
nextDisplay, YDisplay 447
nextDualPower, YDualPower 514
nextFiles, YFiles 541
nextGenericSensor, YGenericSensor 581
nextGyro, YGyro 635
nextHubPort, YHubPort 667
nextHumidity, YHumidity 701
nextLed, YLed 731
nextLightSensor, YLightSensor 769
nextMagnetometer, YMagnetometer 812
nextModule, YModule 862
nextMotor, YMotor 904
nextNetwork, YNetwork 954
nextOsControl, YOsControl 991
nextPower, YPower 1028
nextPressure, YPressure 1068
nextPwmInput, YPwmInput 1114
nextPwmOutput, YPwmOutput 1152
nextPwmPowerSource, YPwmPowerSource 1182
nextQt, YQt 1216
nextRealTimeClock, YRealTimeClock 1247
nextRefFrame, YRefFrame 1281
nextRelay, YRelay 1315
nextSensor, YSensor 1354
nextSerialPort, YSerialPort 1400
nextServo, YServo 1446
nextTemperature, YTemperature 1486
nextTilt, YTilt 1526
nextVoc, YVoc 1565
nextVoltage, YVoltage 1604

nextVSource, YVSource 1635
nextWakeUpMonitor, YWakeUpMonitor 1665
nextWakeUpSchedule, YWakeUpSchedule 1703
nextWatchdog, YWatchdog 1744
nextWireless, YWireless 1784

O

Object 463

P

pauseSequence, YDisplay 448
ping, YNetwork 955
playSequence, YDisplay 449
Port 648
Power 495, 997
PreregisterHub, YAPI 20
Pressure 1040
pulse, YDigitalIO 401
pulse, YRelay 1316
pulse, YVSource 1636
pulse, YWatchdog 1745
pulseDurationMove, YPwmOutput 1153
PwmInput 1079
PwmPowerSource 1165
Python 3

Q

Quaternion 1188
queryLine, YSerialPort 1401
queryMODBUS, YSerialPort 1402

R

read_seek, YSerialPort 1407
readHex, YSerialPort 1403
readLine, YSerialPort 1404
readMessages, YSerialPort 1405
readStr, YSerialPort 1406
Real 1227
reboot, YModule 863
Recorded 345
Reference 10, 1254
registerAnglesCallback, YGyro 636
RegisterDeviceArrivalCallback, YAPI 21
RegisterDeviceRemovalCallback, YAPI 22
RegisterHub, YAPI 23
RegisterHubDiscoveryCallback, YAPI 24
registerLogCallback, YModule 864
RegisterLogFunction, YAPI 25
registerQuaternionCallback, YGyro 637
registerTimedReportCallback, YAccelerometer 64
registerTimedReportCallback, YAltitude 104
registerTimedReportCallback, YCarbonDioxide 183
registerTimedReportCallback, YCompass 252
registerTimedReportCallback, YCurrent 291
registerTimedReportCallback, YGenericSensor

582
registerTimedReportCallback, YGyro 638
registerTimedReportCallback, YHumidity 702
registerTimedReportCallback, YLightSensor 770
registerTimedReportCallback, YMagnetometer 813
registerTimedReportCallback, YPower 1029
registerTimedReportCallback, YPressure 1069
registerTimedReportCallback, YPwmInput 1115
registerTimedReportCallback, YQt 1217
registerTimedReportCallback, YSensor 1355
registerTimedReportCallback, YTemperature 1487
registerTimedReportCallback, YTilt 1527
registerTimedReportCallback, YVoc 1566
registerTimedReportCallback, YVoltage 1605
registerValueCallback, YAccelerometer 65
registerValueCallback, YAltitude 105
registerValueCallback, YAnButton 145
registerValueCallback, YCarbonDioxide 184
registerValueCallback, YColorLed 214
registerValueCallback, YCompass 253
registerValueCallback, YCurrent 292
registerValueCallback, YDataLogger 327
registerValueCallback, YDigitalIO 402
registerValueCallback, YDisplay 450
registerValueCallback, YDualPower 515
registerValueCallback, YFiles 542
registerValueCallback, YGenericSensor 583
registerValueCallback, YGyro 639
registerValueCallback, YHubPort 668
registerValueCallback, YHumidity 703
registerValueCallback, YLed 732
registerValueCallback, YLightSensor 771
registerValueCallback, YMagnetometer 814
registerValueCallback, YMotor 905
registerValueCallback, YNetwork 956
registerValueCallback, YOsControl 992
registerValueCallback, YPower 1030
registerValueCallback, YPressure 1070
registerValueCallback, YPwmInput 1116
registerValueCallback, YPwmOutput 1154
registerValueCallback, YPwmPowerSource 1183
registerValueCallback, YQt 1218
registerValueCallback, YRealTimeClock 1248
registerValueCallback, YRefFrame 1282
registerValueCallback, YRelay 1317
registerValueCallback, YSensor 1356
registerValueCallback, YSerialPort 1408
registerValueCallback, YServo 1447
registerValueCallback, YTemperature 1488
registerValueCallback, YTilt 1528
registerValueCallback, YVoc 1567
registerValueCallback, YVoltage 1606
registerValueCallback, YVSource 1637
registerValueCallback, YWakeUpMonitor 1666
registerValueCallback, YWakeUpSchedule 1704
registerValueCallback, YWatchdog 1746
registerValueCallback, YWireless 1785

Relay 1290
remove, YFiles 543
reset, YDisplayLayer 483
reset, YPower 1031
reset, YSerialPort 1409
resetAll, YDisplay 451
resetCounter, YAnButton 146
resetCounter, YPwmInput 1117
resetSleepCountDown, YWakeUpMonitor 1667
resetStatus, YMotor 906
resetWatchdog, YWatchdog 1747
revertFromFlash, YModule 865
rgbMove, YColorLed 215

S

save3DCalibration, YRefFrame 1283
saveSequence, YDisplay 452
saveToFlash, YModule 866
SelectArchitecture, YAPI 26
selectColorPen, YDisplayLayer 484
selectEraser, YDisplayLayer 485
selectFont, YDisplayLayer 486
selectGrayPen, YDisplayLayer 487
Sensor 1326
Sequence 335, 345, 357
SerialPort 1365
Servo 1422
set_adminPassword, YNetwork 957
set_allSettings, YModule 867
set_analogCalibration, YAnButton 147
set_autoStart, YDataLogger 328
set_autoStart, YWatchdog 1748
set_beacon, YModule 868
set_beaconDriven, YDataLogger 329
set_bearing, YRefFrame 1284
set_bitDirection, YDigitalIO 403
set_bitOpenDrain, YDigitalIO 404
set_bitPolarity, YDigitalIO 405
set_bitState, YDigitalIO 406
set_blinking, YLed 733
set_brakingForce, YMotor 907
set_brightness, YDisplay 453
set_calibrationMax, YAnButton 148
set_calibrationMin, YAnButton 149
set_callbackCredentials, YNetwork 958
set_callbackEncoding, YNetwork 959
set_callbackMaxDelay, YNetwork 960
set_callbackMethod, YNetwork 961
set_callbackMinDelay, YNetwork 962
set_callbackUrl, YNetwork 963
set_currentValue, YAltitude 106
set_cutOffVoltage, YMotor 908
set_discoverable, YNetwork 964
set_drivingForce, YMotor 909
set_dutyCycle, YPwmOutput 1155
set_dutyCycleAtPowerOn, YPwmOutput 1156
set_enabled, YDisplay 454
set_enabled, YHubPort 669
set_enabled, YPwmOutput 1157

set_enabled, YServo 1448
set_enabledAtPowerOn, YPwmOutput 1158
set_enabledAtPowerOn, YServo 1449
set_failSafeTimeout, YMotor 910
set_frequency, YMotor 911
set_frequency, YPwmOutput 1159
set_highestValue, YAccelerometer 66
set_highestValue, YAltitude 107
set_highestValue, YCarbonDioxide 185
set_highestValue, YCompass 254
set_highestValue, YCurrent 293
set_highestValue, YGenericSensor 584
set_highestValue, YGyro 640
set_highestValue, YHumidity 704
set_highestValue, YLightSensor 772
set_highestValue, YMagnetometer 815
set_highestValue, YPower 1032
set_highestValue, YPressure 1071
set_highestValue, YPwmInput 1118
set_highestValue, YQt 1219
set_highestValue, YSensor 1357
set_highestValue, YTemperature 1489
set_highestValue, YTilt 1529
set_highestValue, YVoc 1568
set_highestValue, YVoltage 1607
set_hours, YWakeUpSchedule 1705
set_hslColor, YColorLed 216
set_logFrequency, YAccelerometer 67
set_logFrequency, YAltitude 108
set_logFrequency, YCarbonDioxide 186
set_logFrequency, YCompass 255
set_logFrequency, YCurrent 294
set_logFrequency, YGenericSensor 585
set_logFrequency, YGyro 641
set_logFrequency, YHumidity 705
set_logFrequency, YLightSensor 773
set_logFrequency, YMagnetometer 816
set_logFrequency, YPower 1033
set_logFrequency, YPressure 1072
set_logFrequency, YPwmInput 1119
set_logFrequency, YQt 1220
set_logFrequency, YSensor 1358
set_logFrequency, YTemperature 1490
set_logFrequency, YTilt 1530
set_logFrequency, YVoc 1569
set_logFrequency, YVoltage 1608
set_logicalName, YAccelerometer 68
set_logicalName, YAltitude 109
set_logicalName, YAnButton 150
set_logicalName, YCarbonDioxide 187
set_logicalName, YColorLed 217
set_logicalName, YCompass 256
set_logicalName, YCurrent 295
set_logicalName, YDataLogger 330
set_logicalName, YDigitalIO 407
set_logicalName, YDisplay 455
set_logicalName, YDualPower 516
set_logicalName, YFiles 544
set_logicalName, YGenericSensor 586

set_logicalName, YGyro 642
set_logicalName, YHubPort 670
set_logicalName, YHumidity 706
set_logicalName, YLed 734
set_logicalName, YLightSensor 774
set_logicalName, YMagnetometer 817
set_logicalName, YModule 869
set_logicalName, YMotor 912
set_logicalName, YNetwork 965
set_logicalName, YOsControl 993
set_logicalName, YPower 1034
set_logicalName, YPressure 1073
set_logicalName, YPwmInput 1120
set_logicalName, YPwmOutput 1160
set_logicalName, YPwmPowerSource 1184
set_logicalName, YQt 1221
set_logicalName, YRealTimeClock 1249
set_logicalName, YRefFrame 1285
set_logicalName, YRelay 1318
set_logicalName, YSensor 1359
set_logicalName, YSerialPort 1411
set_logicalName, YServo 1450
set_logicalName, YTemperature 1491
set_logicalName, YTilt 1531
set_logicalName, YVoc 1570
set_logicalName, YVoltage 1609
set_logicalName, YVSource 1638
set_logicalName, YWakeUpMonitor 1668
set_logicalName, YWakeUpSchedule 1706
set_logicalName, YWatchdog 1749
set_logicalName, YWireless 1786
set_lowestValue, YAccelerometer 69
set_lowestValue, YAltitude 110
set_lowestValue, YCarbonDioxide 188
set_lowestValue, YCompass 257
set_lowestValue, YCurrent 296
set_lowestValue, YGenericSensor 587
set_lowestValue, YGyro 643
set_lowestValue, YHumidity 707
set_lowestValue, YLightSensor 775
set_lowestValue, YMagnetometer 818
set_lowestValue, YPower 1035
set_lowestValue, YPressure 1074
set_lowestValue, YPwmInput 1121
set_lowestValue, YQt 1222
set_lowestValue, YSensor 1360
set_lowestValue, YTemperature 1492
set_lowestValue, YTilt 1532
set_lowestValue, YVoc 1571
set_lowestValue, YVoltage 1610
set_luminosity, YLed 735
set_luminosity, YModule 870
set_maxTimeOnStateA, YRelay 1319
set_maxTimeOnStateA, YWatchdog 1750
set_maxTimeOnStateB, YRelay 1320
set_maxTimeOnStateB, YWatchdog 1751
set_measureType, YLightSensor 776
set_minutes, YWakeUpSchedule 1707
set_minutesA, YWakeUpSchedule 1708
set_minutesB, YWakeUpSchedule 1709
set_monthDays, YWakeUpSchedule 1710
set_months, YWakeUpSchedule 1711
set_mountPosition, YRefFrame 1286
set_neutral, YServo 1451
set_nextWakeUp, YWakeUpMonitor 1669
set_orientation, YDisplay 456
set_output, YRelay 1321
set_output, YWatchdog 1752
set_outputVoltage, YDigitalIO 408
set_overCurrentLimit, YMotor 913
set_period, YPwmOutput 1161
set_portDirection, YDigitalIO 409
set_portOpenDrain, YDigitalIO 410
set_portPolarity, YDigitalIO 411
set_portState, YDigitalIO 412
set_position, YServo 1452
set_positionAtPowerOn, YServo 1453
set_power, YLed 736
set_powerControl, YDualPower 517
set_powerDuration, YWakeUpMonitor 1670
set_powerMode, YPwmPowerSource 1185
set_primaryDNS, YNetwork 966
set_protocol, YSerialPort 1412
set_pulseDuration, YPwmOutput 1162
set_pwmReportMode, YPwmInput 1122
set_qnh, YAltitude 111
set_range, YServo 1454
set_recording, YDataLogger 331
set_reportFrequency, YAccelerometer 70
set_reportFrequency, YAltitude 112
set_reportFrequency, YCarbonDioxide 189
set_reportFrequency, YCompass 258
set_reportFrequency, YCurrent 297
set_reportFrequency, YGenericSensor 588
set_reportFrequency, YGyro 644
set_reportFrequency, YHumidity 708
set_reportFrequency, YLightSensor 777
set_reportFrequency, YMagnetometer 819
set_reportFrequency, YPower 1036
set_reportFrequency, YPressure 1075
set_reportFrequency, YPwmInput 1123
set_reportFrequency, YQt 1223
set_reportFrequency, YSensor 1361
set_reportFrequency, YTemperature 1493
set_reportFrequency, YTilt 1533
set_reportFrequency, YVoc 1572
set_reportFrequency, YVoltage 1611
set_resolution, YAccelerometer 71
set_resolution, YAltitude 113
set_resolution, YCarbonDioxide 190
set_resolution, YCompass 259
set_resolution, YCurrent 298
set_resolution, YGenericSensor 589
set_resolution, YGyro 645
set_resolution, YHumidity 709
set_resolution, YLightSensor 778
set_resolution, YMagnetometer 820
set_resolution, YPower 1037

set_resolution, YPressure 1076
set_resolution, YPwmInput 1124
set_resolution, YQt 1224
set_resolution, YSensor 1362
set_resolution, YTemperature 1494
set_resolution, YTilt 1534
set_resolution, YVoc 1573
set_resolution, YVoltage 1612
set_rgbColor, YColorLed 218
set_rgbColorAtPowerOn, YColorLed 219
set_RTS, YSerialPort 1410
set_running, YWatchdog 1753
set_secondaryDNS, YNetwork 967
set_sensitivity, YAnButton 151
set_sensorType, YTemperature 1495
set_serialMode, YSerialPort 1413
set_signalBias, YGenericSensor 590
set_signalRange, YGenericSensor 591
set_sleepCountdown, YWakeUpMonitor 1671
set_starterTime, YMotor 914
set_startupSeq, YDisplay 457
set_state, YRelay 1322
set_state, YWatchdog 1754
set_stateAtPowerOn, YRelay 1323
set_stateAtPowerOn, YWatchdog 1755
set_timeUTC, YDataLogger 332
set_triggerDelay, YWatchdog 1756
set_triggerDuration, YWatchdog 1757
set_unit, YGenericSensor 592
set_unixTime, YRealTimeClock 1250
set(userData, YAccelerometer 72
set(userData, YAltitude 114
set(userData, YAnButton 152
set(userData, YCarbonDioxide 191
set(userData, YColorLed 220
set(userData, YCompass 260
set(userData, YCurrent 299
set(userData, YDataLogger 333
set(userData, YDigitalIO 413
set(userData, YDisplay 458
set(userData, YDualPower 518
set(userData, YFiles 545
set(userData, YGenericSensor 593
set(userData, YGyro 646
set(userData, YHubPort 671
set(userData, YHumidity 710
set(userData, YLed 737
set(userData, YLightSensor 779
set(userData, YMagnetometer 821
set(userData, YModule 871
set(userData, YMotor 915
set(userData, YNetwork 968
set(userData, YOsControl 994
set(userData, YPower 1038
set(userData, YPressure 1077
set(userData, YPwmInput 1125
set(userData, YPwmOutput 1163
set(userData, YPwmPowerSource 1186
set(userData, YQt 1225
set(userData, YRealTimeClock 1251
set(userData, YRefFrame 1287
set(userData, YRelay 1324
set(userData, YSensor 1363
set(userData, YSerialPort 1414
set(userData, YServo 1455
set(userData, YTemperature 1496
set(userData, YTilt 1535
set(userData, YVoc 1574
set(userData, YVoltage 1613
set(userData, YVSource 1639
set(userData, YWakeUpMonitor 1672
set(userData, YWakeUpSchedule 1712
set(userData, YWatchdog 1758
set(userData, YWireless 1787
set(userPassword, YNetwork 969
set(userVar, YModule 872
set_utcOffset, YRealTimeClock 1252
set_valueInterval, YDataRun 343
set_valueRange, YGenericSensor 594
set_voltage, YVSource 1640
set_weekDays, YWakeUpSchedule 1713
set_wwwWatchdogDelay, YNetwork 970
setAntialiasingMode, YDisplayLayer 488
setConsoleBackground, YDisplayLayer 489
setConsoleMargins, YDisplayLayer 490
setConsoleWordWrap, YDisplayLayer 491
setLayerPosition, YDisplayLayer 492
shutdown, YOsControl 995
Sleep, YAPI 27
sleep, YWakeUpMonitor 1673
sleepFor, YWakeUpMonitor 1674
sleepUntil, YWakeUpMonitor 1675
softAPNetwork, YWireless 1788
Source 3, 1615
start3DCalibration, YRefFrame 1288
stopSequence, YDisplay 459
Supply 495
swapLayerContent, YDisplay 460

T

Temperature 1457
Tilt 1498
Time 1227
toggle_bitState, YDigitalIO 414
triggerFirmwareUpdate, YModule 873
TriggerHubDiscovery, YAPI 28

U

Unformatted 357
unhide, YDisplayLayer 493
UnregisterHub, YAPI 29
UpdateDeviceList, YAPI 30
updateFirmware, YModule 874
upload, YDisplay 461
upload, YFiles 546
useDHCP, YNetwork 971
useStaticIP, YNetwork 972

V

Value 823
Voltage 1576, 1615
voltageMove, YVSource 1641

W

wakeUp, YWakeUpMonitor 1676
WakeUpMonitor 1643
WakeUpSchedule 1678
Watchdog 1715
Wireless 1760
writeArray, YSerialPort 1415
writeBin, YSerialPort 1416
writeHex, YSerialPort 1417
writeLine, YSerialPort 1418
writeMODBUS, YSerialPort 1419
writeStr, YSerialPort 1420

Y

YAccelerometer 34-72
YAltitude 76-114
YAnButton 118-152
YAPI 12-30
YCarbonDioxide 156-191
yCheckLogicalName 12
YColorLed 194-220
YCompass 224-260
YCurrent 264-299
YDataLogger 303-333
YDataRun 335-343
YDataSet 346-355
YDataStream 358-370
YDigitalIO 374-414
yDisableExceptions 13
YDisplay 418-461
YDisplayLayer 464-493
YDualPower 496-518
yEnableExceptions 14
YFiles 521-546
yFindAccelerometer 34
yFindAltitude 76
yFindAnButton 118
yFindCarbonDioxide 156
yFindColorLed 194
yFindCompass 224
yFindCurrent 264
yFindDataLogger 303
yFindDigitalIO 374
yFindDisplay 418
yFindDualPower 496
yFindFiles 521
yFindGenericSensor 550
yFindGyro 599
yFindHubPort 649
yFindHumidity 675
yFindLed 713
yFindLightSensor 741

yFindMagnetometer 783
yFindModule 831
yFindMotor 878
yFindNetwork 920
yFindOsControl 975
yFindPower 999
yFindPressure 1042
yFindPwmInput 1081
yFindPwmOutput 1129
yFindPwmPowerSource 1166
yFindQt 1190
yFindRealTimeClock 1228
yFindRefFrame 1256
yFindRelay 1292
yFindSensor 1328
yFindSerialPort 1368
yFindServo 1424
yFindTemperature 1459
yFindTilt 1500
yFindVoc 1539
yFindVoltage 1578
yFindVSource 1616
yFindWakeUpMonitor 1645
yFindWakeUpSchedule 1680
yFindWatchdog 1717
yFindWireless 1761
yFirstAccelerometer 35
yFirstAltitude 77
yFirstAnButton 119
yFirstCarbonDioxide 157
yFirstColorLed 195
yFirstCompass 225
yFirstCurrent 265
yFirstDataLogger 304
yFirstDigitalIO 375
yFirstDisplay 419
yFirstDualPower 497
yFirstFiles 522
yFirstGenericSensor 551
yFirstGyro 600
yFirstHubPort 650
yFirstHumidity 676
yFirstLed 714
yFirstLightSensor 742
yFirstMagnetometer 784
yFirstModule 832
yFirstMotor 879
yFirstNetwork 921
yFirstOsControl 976
yFirstPower 1000
yFirstPressure 1043
yFirstPwmInput 1082
yFirstPwmOutput 1130
yFirstPwmPowerSource 1167
yFirstQt 1191
yFirstRealTimeClock 1229
yFirstRefFrame 1257
yFirstRelay 1293
yFirstSensor 1329

yFirstSerialPort 1369
yFirstServo 1425
yFirstTemperature 1460
yFirstTilt 1501
yFirstVoc 1540
yFirstVoltage 1579
yFirstVSource 1617
yFirstWakeUpMonitor 1646
yFirstWakeUpSchedule 1681
yFirstWatchdog 1718
yFirstWireless 1762
yFreeAPI 15
YGenericSensor 550-595
yGetAPIVersion 16
yGetTickCount 17
YGyro 599-646
yHandleEvents 18
YHubPort 649-671
YHumidity 675-710
yInitAPI 19
YLed 713-737
YLightSensor 741-779
YMagnetometer 783-821
YMeasure 823-827
YModule 831-874
YMotor 878-915
YNetwork 920-972
Yocto-Demo 3
Yocto-hub 648
YOscControl 975-995
YPower 999-1038
yPreregisterHub 20
YPressure 1042-1077
YPwmInput 1081-1125
YPwmOutput 1129-1163
YPwmPowerSource 1166-1186
YQt 1190-1225
YRealTimeClock 1228-1252
YRefFrame 1256-1288
yRegisterDeviceArrivalCallback 21
yRegisterDeviceRemovalCallback 22
yRegisterHub 23
yRegisterHubDiscoveryCallback 24
yRegisterLogFunction 25
YRelay 1292-1324
ySelectArchitecture 26
YSensor 1328-1363
YSerialPort 1368-1420
YServo 1424-1455
ySleep 27
YTemperature 1459-1496
YTilt 1500-1535
yTriggerHubDiscovery 28
yUnregisterHub 29
yUpdateDeviceList 30
YVoc 1539-1574
YVoltage 1578-1613
YVSource 1616-1641
YWakeUpMonitor 1645-1676
YWakeUpSchedule 1680-1713
YWatchdog 1717-1758
YWireless 1761-1788

Z

zeroAdjust, YGenericSensor 595