



The Yocto-PowerRelay-V3 is a USB power relay. It contains a robust USB-driven SPDT relay switch: you can drive by software the relay input to one of the two outputs. To make it easier to test your project, two LEDs show the output currently active.

This device only includes a single relay, but it can drive higher loads than the Yocto-Relay and the Yocto-PowerRelay-V2. The relay and the connector can stand a current of 5A, and when put in an enclosure, the Yocto-PowerRelay-V3 can be used to switch directly appliances connected to the mains, up to 250 V AC r.m.s. in overvoltage category II.

Be aware that although this relay has a better endurance to inductive loads than the Yocto-PowerRelay-V2, using a relay to drive inductive loads (motors, transformers) may lead to accelerated aging of the relay. Please refer to the documentation for hints on reducing this type of problems.

Specifications

Product ID	RELAYHI3
USB connector	micro-B
Width	20 mm
Length	55 mm
Weight	15 g
Relay type	OMRON G6RL-14-ASI
Channels	1
Max switching current	5 A
Max switching power	1250 VA
Operate time	12 ms (max)
Release time	7 ms (max)
Max withstanding voltage	1000 V AC
Max working voltage	250 V AC
IEC protection class	class II
USB insulation, clearance dist.	10 mm
USB insulation, creepage dist.	10 mm
USB insulation, dielectric strength	5 kV
Normal operating temperature	5...40 °C
Extended operating temperature [‡]	-30...85 °C
RoHS	Yes
USB Vendor ID	0x24E0
USB Device ID	0x008A
Suggested enclosure	YoctoBox-Long-Thick-Black
Harmonized tariff code	8542.3190
Made in	Switzerland

[‡] The extended temperature range is defined based on components specifications and has been tested during a limited duration (1h). When using the device in harsh environments for a long period of time, we strongly advise to run extensive tests before going to production.



For more information: www.yoctopuce.com/EN/products/yocto-powerrelay-v3